

Dataset Reference

FortiAnalyzer 6.4.8



FORTINET DOCUMENT LIBRARY

<https://docs.fortinet.com>

FORTINET VIDEO GUIDE

<https://video.fortinet.com>

FORTINET BLOG

<https://blog.fortinet.com>

CUSTOMER SERVICE & SUPPORT

<https://support.fortinet.com>

FORTINET TRAINING & CERTIFICATION PROGRAM

<https://www.fortinet.com/training-certification>

NSE INSTITUTE

<https://training.fortinet.com>

FORTIGUARD CENTER

<https://www.fortiguard.com>

END USER LICENSE AGREEMENT

<https://www.fortinet.com/doc/legal/EULA.pdf>

FEEDBACK

Email: techdoc@fortinet.com



May 3, 2022

FortiAnalyzer 6.4.8 Dataset Reference

05-648-0803421-20220503

TABLE OF CONTENTS

Introduction	4
Understanding datasets and macros	4
Dataset Reference List	5
Macro Reference List	270
Change Log	273

Introduction

This document provides information about the various types of FortiAnalyzer datasets.

Understanding datasets and macros

FortiAnalyzer datasets are collections of log messages from monitored devices.

Charts in FortiAnalyzer are generated based on the datasets. To create a chart, you can use the predefined datasets, or you can create your own custom datasets by querying the log messages in the SQL database on the FortiAnalyzer unit. Both predefined and custom datasets can be cloned, but only custom datasets can be deleted. You can also view the SQL query for a dataset, and test the query against specific devices or log arrays.

You can create custom reports that contain macros that are created based on predefined and custom datasets. Macros are used to dynamically display the device log data as text in a report. They can be embedded within a text field of a paragraph in a report layout in XML format. Macros display a single value, such as a user name, highest session count, or highest bandwidth, and so on.

For more information about how to create datasets, charts, and macros, see the FortiAnalyzer *Administration Guide*.

Dataset Reference List

The following tables list the datasets included with FortiAnalyzer. The tables contain the name, SQL query syntax, and log category for each dataset.

Dataset Name	Description	Log Category
Traffic-Bandwidth-Summary-Day-Of-Month	Traffic bandwidth timeline	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in
from
  ###(select timestamp, sum(bandwidth) as bandwidth, sum(traffic_out) as traffic_out, sum
(timestamp) as timestamp, dvid, srcip, dstip, epid, euid, coalesce(nullifna(`user`), nullifna
(`unauthuser`), ipstr(`srcip`)) as user_src, service, count(*) as sessions, sum(coalesce
(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce
(sentdelta, sentbyte, 0)) as traffic_out, sum(coalesce(rcvddelta, rcvdbyte, 0)) as traffic_
in from $log-traffic where $filter and (logflag&(1|32)>0) group by timestamp, dvid, srcip,
dstip, epid, euid, user_src, service /*SkipSTART*/order by timestamp desc/*SkipEND*/)base###
base_query group by timestamp order by bandwidth desc)### t where $filter-drilldown group by
hodex having sum(traffic_out+traffic_in)>0 order by hodex
```

Dataset Name	Description	Log Category
Session-Summary-Day-Of-Month	Number of session timeline	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  sum(sessions) as sessions
from
  ###(select timestamp, sum(sessions) as sessions from ###base(/*tag:rpt_base_t_bndwidth_
sess*/select $flex_timestamp as timestamp, dvid, srcip, dstip, epid, euid, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, service, count(*) as
sessions, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in from $log-traffic where $filter and (logflag&(1|32)>0) group by
timestamp, dvid, srcip, dstip, epid, euid, user_src, service /*SkipSTART*/order by timestamp
desc/*SkipEND*/)base### base_query group by timestamp order by sessions desc)### t where
$filter-drilldown group by hodex order by hodex
```

Dataset Name	Description	Log Category
Top-Users-By-Bandwidth	Bandwidth application top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
```

```

        ipstr(`srcip`)
    ) as user_src,
    sum(
        coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvddelta, rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentdelta, sentbyte, 0)
    ) as traffic_out,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag &(1 | 32)> 0
    )
group by
    user_src
having
    sum(
        coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
Top-App-By-Bandwidth	Top applications by bandwidth usage	traffic

```

select
    app_group_name(app) as app_group,
    sum(
        coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvddelta, rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentdelta, sentbyte, 0)
    ) as traffic_out,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag &(1 | 32)> 0
    )
    and nullifna(app) is not null
group by
    app_group
having
    sum(

```

```

    coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-User-Source-By-Sessions	Top user source by session count	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  user_src
order by
  sessions desc

```

Dataset Name	Description	Log Category
Top-App-By-Sessions	Top applications by session count	traffic

```

select
  app_group_name(app) as app_group,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app_group
order by
  sessions desc

```

Dataset Name	Description	Log Category
Top-Destination-Addresses-By-Sessions	Top destinations by session count	traffic

```

select
  coalesce(
    nullifna(

```

```

        root_domain(hostname)
    ),
    ipstr(dstip)
) as domain,
count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
group by
    domain
order by
    sessions desc

```

Dataset Name	Description	Log Category
Top-Destination-Addresses-By-Bandwidth	Top destinations by bandwidth usage	traffic

```

select
    coalesce(
        nullifna(
            root_domain(hostname)
        ),
        ipstr(dstip)
    ) as domain,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and coalesce(
        nullifna(
            root_domain(hostname)
        ),
        ipstr(`dstip`)
    ) is not null
group by
    domain
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )

```



```
)> 0
order by
bandwidth desc
```

Dataset Name	Description	Log Category
DHCP-Summary-By-Port	Event top dhcp summary	event

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2;
drop
  table if exists rpt_tmptbl_3; create temporary table rpt_tmptbl_1 as
select
  devintf,
  mac
from
  ###(select concat(interface, '.', devid) as devintf, mac from $log where $last3day_period
$filter and logid_to_int(logid) = 26001 and dhcp_msg = 'Ack' group by devintf, mac)### t
group by devintf, mac; create temporary table rpt_tmptbl_2 as select devintf, mac from ###
(select concat(interface, '.', devid) as devintf, mac from $log where $filter and logid_to_
int(logid) = 26001 and dhcp_msg = 'Ack' group by devintf, mac)### t group by devintf, mac;
create temporary table rpt_tmptbl_3 as select distinct on (1) devintf, cast(used*100.0/total
as decimal(18,2)) as percent_of_allocated_ip from ###(select distinct on (devintf) concat
(interface, '.', devid) as devintf, used, total, itime from $log where $filter and logid_to_
int(logid)=26003 and total>0 /*SkipSTART*/order by devintf, itime desc/*SkipEND*/)### t
order by devintf, itime desc; select t1.devintf as interface, percent_of_allocated_ip, new_
cli_count from rpt_tmptbl_3 t1 inner join (select devintf, count(mac) as new_cli_count from
rpt_tmptbl_2 where not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.mac=rpt_tmptbl_
1.mac) group by devintf) t2 on t1.devintf=t2.devintf order by interface, percent_of_
allocated_ip desc
```

Dataset Name	Description	Log Category
Top-Wifi-Client-By-Bandwidth	Traffic top WiFi client by bandwidth usage	traffic

```
select
  user_src,
  srcssid,
  devtype_new,
  hostname_mac,
  sum(bandwidth) as bandwidth
from
  (
    select
      user_src,
      srcssid,
      get_devtype(srcswversion, osname, devtype) as devtype_new,
      hostname_mac,
      sum(bandwidth) as bandwidth
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna
(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as
osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte,
```

```
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter
and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap,
srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal
desc/*SkipEND*/)### t group by user_src, srcssid, devtype_new, hostname_mac having sum
(bandwidth)>0 union all select user_src, ssid as srcssid, null as devtype_new, stamac as
hostname_mac, sum(bandwidth) as bandwidth from ###(select $flex_timestamp as timestamp,
stamac, stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentdelta, 0))
as sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce
(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr
(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order
by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over (partition by stamac order
by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is
not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req',
'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by
bandwidth desc/*SkipEND*/)### t where user_src is not null group by user_src, ssid, devtype_
new, stamac having sum(bandwidth)>0) t group by user_src, srcssid, devtype_new, hostname_mac
order by bandwidth desc
```

Dataset Name	Description	Log Category
Traffic-History-By-Active-User	Traffic history by active user	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  count(
    distinct(user_src)
  ) as total_user
from
  ###(select timestamp, user_src, sum(sessions) as sessions from ###base(/*tag:rpt_base_t_
bndwidth_sess*/select $flex_timestamp as timestamp, dvid, srcip, dstip, epid, euid, coalesce
(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, service, count(*) as
sessions, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in from $log-traffic where $filter and (logflag&(1|32)>0) group by
timestamp, dvid, srcip, dstip, epid, euid, user_src, service /*SkipSTART*/order by timestamp
desc/*SkipEND*/)base### base_query group by timestamp, user_src order by sessions desc)### t
where $filter-drilldown group by hodex order by hodex
```

Dataset Name	Description	Log Category
Top-Allowed-Websites-By-Requests	UTM top allowed web sites by request	traffic

```
select
  hostname,
  catdesc,
  count(*) as requests
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and utmevent in (
    & #039;webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') and
```

hostname is not null and (utmaction not in ('block', 'blocked') or action!='deny') group by hostname, catdesc order by requests desc

Dataset Name	Description	Log Category
Top-50-Websites-By-Bandwidth	Webfilter top allowed web sites by bandwidth usage	webfilter

```
select
  domain,
  string_agg(
    distinct catdesc,
    & #039;; ' ) as agg_catdesc, sum(bandwidth) as bandwidth, sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out from ###(select coalesce(nullifna(hostname), ipstr(`dstip`))
as domain, catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum
(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log-
traffic where $filter and (logflag&1>0) and utmaction!='blocked' and (countweb>0 or ((logver
is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-
word', 'web-content', 'command-block', 'script-filter')))) group by domain, catdesc having
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 /*SkipSTART*/order by bandwidth
desc/*SkipEND*/)### t group by domain, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Blocked-Websites	UTM top blocked web sites by request	traffic

```
select
  hostname,
  count(*) as requests
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and utmevent in (
    & #039;webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') and
hostname is not null and (utmaction in ('block', 'blocked') or action='deny') group by
hostname order by requests desc
```

Dataset Name	Description	Log Category
Top-Web-Users-By-Request	UTM top web users by request	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  get_devtype(srcswversion, osname, devtype) as devtype_new,
  srcname,
  count(*) as requests
from
  $log
where
```

```

$filter
and (
    logflag&1>0
)
and utmevent in (
    & #039;webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') group
by user_src, devtype_new, srcname order by requests desc

```

Dataset Name	Description	Log Category
Top-Allowed-WebSites-By-Bandwidth	UTM top allowed websites by bandwidth usage	traffic

```

select
    appid,
    hostname,
    catdesc,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and utmevent in (
        & #039;webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') and
hostname is not null group by appid, hostname, catdesc having sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Blocked-Web-Users	UTM top blocked web users	traffic

```

select
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    get_devtype(srcswversion, osname, devtype) as devtype_new,
    srcname,
    count(*) as requests
from
    $log
where
    $filter
    and (
        logflag&1>0
    )

```

```

)
and utmevent in (
    & #039;webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') and
(utmaction in ('block', 'blocked') or action='deny') group by user_src, devtype_new, srcname
order by requests desc

```

Dataset Name	Description	Log Category
Top-20-Web-Users-By-Bandwidth	Webfilter top web users by bandwidth usage	webfilter

```

select
    user_src,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as
traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log-traffic where $filter and
(logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (hostname is not
null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-
filter')))) group by user_src having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0
/*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t group by user_src order by bandwidth
desc

```

Dataset Name	Description	Log Category
Top-Web-Users-By-Bandwidth	UTM top web users by bandwidth usage	traffic

```

select
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    get_devtype(srcswversion, osname, devtype) as devtype_new,
    srcname,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and utmevent in (
        & #039;webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') group

```

```
by user_src, devtype_new, srcname having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0
order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Video-Streaming-Websites-By-Bandwidth	UTM top video streaming websites by bandwidth usage	traffic

```
select
  appid,
  hostname,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and catdesc in (
    & #039;Streaming Media and Download') group by appid, hostname having sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Email-Senders-By-Count	Default top email senders by count	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as requests
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and service in (
    & #039;smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') group by user_
src order by requests desc
```

Dataset Name	Description	Log Category
Top-Email-Receivers-By-Count	Default email top receivers by count	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as requests
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and service in (
    & #039;pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp',
    'pop3s', 'POP3S', '995/tcp') group by user_src order by requests desc

```

Dataset Name	Description	Log Category
Top-Email-Senders-By-Bandwidth	Default email top senders by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and service in (
    & #039;smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') group by user_
src having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Email-Receivers-By-Bandwidth	Default email top receivers by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from

```

```

$log
where
$filter
and (
    logflag&1>0
)
and service in (
    & #039;pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp',
'pop3s', 'POP3S', '995/tcp') group by user_src having sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0))>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Malware-By-Name	UTM top virus	virus

```

select
    virus,
    max(virusid_s) as virusid,
    (
        case when virus like & #039;Riskware%' then 'Spyware' when virus like 'Adware%' then
'Adware' else 'Virus' end) as malware_type, sum(totalnum) as totalnum from ###(select virus,
virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where
$filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not null group
by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by virus,
malware_type order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Virus-By-Name	UTM top virus	virus

```

select
    virus,
    max(virusid_s) as virusid,
    (
        case when virus like & #039;Riskware%' then 'Spyware' when virus like 'Adware%' then
'Adware' else 'Virus' end) as malware_type, sum(totalnum) as totalnum from ###(select virus,
virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where
$filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not null group
by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by virus,
malware_type order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Virus-Victim	UTM top virus user	virus

```

select
    user_src,
    sum(totalnum) as totalnum
from
    ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as totalnum
from $log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is
not null group by user_src /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by
user_src order by totalnum desc

```


Dataset Name	Description	Log Category
Top-Attack-Source	UTM top attack source	attack

```
select
  coalesce(
    nullifna(`user`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as totalnum
from
  $log
where
  $filter
group by
  user_src
order by
  totalnum desc
```

Dataset Name	Description	Log Category
Top-Attack-Victim	UTM top attack dest	attack

```
select
  dstip,
  count(*) as totalnum
from
  $log
where
  $filter
  and dstip is not null
group by
  dstip
order by
  totalnum desc
```

Dataset Name	Description	Log Category
Top-Static-IPSEC-Tunnels-By-Bandwidth	Top static IPsec tunnels by bandwidth usage	event

```
select
  vpn_name,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      tunnelid,
      vpn_name,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_
```

```

in)- min(min_traffic_in) end
    ) as traffic_in,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
    ) as traffic_out,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out)
else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out)
end
    ) as bandwidth
from
    ###(select devid, vd, remip, vpn_trim(vpn_tunnel) as vpn_name, tunnelid, tunnelip, max
(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in,
min(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in,
min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time from $log where $filter
and subtype='vpn' and tunneltype like 'ipsec%' and nullifna(vpn_tunnel) is not null and
action in ('tunnel-stats', 'tunnel-down') and tunnelid is not null group by devid, vd,
remip, vpn_name, tunnelid, tunnelip)### t where (tunnelip is null or tunnelip='0.0.0.0')
group by devid, vd, remip, vpn_name, tunnelid) tt group by vpn_name having sum(traffic_
in+traffic_out)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-SSL-VPN-Tunnel-Users-By-Bandwidth	Top SSL VPN tunnel users by bandwidth usage	event

```

select
    user_src,
    remip as remote_ip,
    from_dtime(
        min(s_time)
    ) as start_time,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
    (
        select
            devid,
            vd,
            remip,
            user_src,
            tunnelid,
            min(s_time) as s_time,
            max(e_time) as e_time,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out)
else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out)
end
            ) as bandwidth,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_
in)- min(min_traffic_in) end
            ) as traffic_in,
            (

```

```

        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
    ) as traffic_out
from
    ###(select devid, vd, remip, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src,
tunnelid, tunneltype, max(coalesce(duration,0)) as max_duration, min(coalesce(duration,0))
as min_duration, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, min
(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvbyte, 0)) as min_traffic_in,
max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvbyte, 0)) as max_traffic_in
from $log where $filter and subtype='vpn' and tunneltype like 'ssl%' and action in ('tunnel-
stats', 'tunnel-down', 'tunnel-up') and coalesce(nullifna(`user`), ipstr(`remip`)) is not
null and tunnelid is not null group by devid, vd, user_src, remip, tunnelid, tunneltype)###
t where tunneltype='ssl-tunnel' group by devid, vd, user_src, remip, tunnelid) tt where
bandwidth>0 group by user_src, remote_ip order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Tunnels-By-Bandwidth	Top dial up IPsec tunnels by bandwidth usage	event

```

select
    vpn_name,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
    (
        select
            devid,
            vd,
            tunnelid,
            remip,
            vpn_name,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_
in)- min(min_traffic_in) end
            ) as traffic_in,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
            ) as traffic_out,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out)
else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out)
end
            ) as bandwidth
        from
            ###(select devid, vd, remip, vpn_trim(vpntunnel) as vpn_name, tunnelid, tunnelip, max
(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvbyte, 0)) as max_traffic_in,
min(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvbyte, 0)) as min_traffic_in,
min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time from $log where $filter
and subtype='vpn' and tunneltype like 'ipsec%' and nullifna(vpntunnel) is not null and
action in ('tunnel-stats', 'tunnel-down') and tunnelid is not null group by devid, vd,
remip, vpn_name, tunnelid, tunnelip)### t where not (tunnelip is null or tunnelip='0.0.0.0')
group by devid, vd, remip, vpn_name, tunnelid) tt group by vpn_name having sum(traffic_
out+traffic_in)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Users-By-Bandwidth	Top dial up IPsec users by bandwidth usage	event

```
select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr('remip`)
  ) as user_src,
  remip,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      string_agg(
        distinct xauthuser_agg,
        & #039; ' ) as xauthuser_agg, string_agg(distinct user_agg, ' ' ) as user_agg, remip,
      tunnelid, min(s_time) as s_time, max(e_time) as e_time, (case when min(s_time)=max(e_time)
      then max(max_traffic_in)+max(max_traffic_out) else max(max_traffic_in)-min(min_traffic_in)+max(max_traffic_out)-min(min_traffic_out) end) as bandwidth, (case when min(s_time)=max(e_time) then max(max_traffic_in) else max(max_traffic_in)-min(min_traffic_in) end) as traffic_in, (case when min(s_time)=max(e_time) then max(max_traffic_out) else max(max_traffic_out)-min(min_traffic_out) end) as traffic_out from ###(select devid, vd, remip, nullifna('xauthuser`) as xauthuser_agg, nullifna('user`) as user_agg, tunnelid, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, max(coalesce(duration,0)) as max_duration, min(coalesce(duration,0)) as min_duration, min(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in from $log where $filter and subtype='vpn' and tunneltype like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0') and action in ('tunnel-stats', 'tunnel-down', 'tunnel-up') and tunnelid is not null and tunnelid!=0 group by devid, vd, remip, xauthuser_agg, user_agg, tunnelid order by tunnelid)### t group by devid, vd, remip, tunnelid) tt where bandwidth>0 group by user_src, remip order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Users-By-Duration	Top dial up IPsec users by duration	event

```
select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr('remip`)
  ) as user_src,
  from_dtime(
    min(s_time)
```

```

    ) as start_time,
    sum(duration) as duration,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
(
    select
        devid,
        vd,
        remip,
        string_agg(
            distinct xauthuser_agg,
            & #039; ' ) as xauthuser_agg, string_agg(distinct user_agg, ' ' ) as user_agg,
        tunnelid, min(s_time) as s_time, max(e_time) as e_time, (case when min(s_time)=max(e_time)
        then max(max_duration) else max(max_duration)-min(min_duration) end) as duration, (case when
        min(s_time)=max(e_time) then max(max_traffic_in)+max(max_traffic_out) else max(max_traffic_
        in)-min(min_traffic_in)+max(max_traffic_out)-min(min_traffic_out) end) as bandwidth, (case
        when min(s_time)=max(e_time) then max(max_traffic_in) else max(max_traffic_in)-min(min_
        traffic_in) end) as traffic_in, (case when min(s_time)=max(e_time) then max(max_traffic_out)
        else max(max_traffic_out)-min(min_traffic_out) end) as traffic_out from ###(select devid,
        vd, remip, nullifna('xauthuser') as xauthuser_agg, nullifna('user') as user_agg, tunnelid,
        min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, max(coalesce
        (duration,0)) as max_duration, min(coalesce(duration,0)) as min_duration, min(coalesce
        (sentbyte, 0)) as min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, max
        (coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in
        from $log where $filter and subtype='vpn' and tunneltype like 'ipsec%' and not (tunnelip is
        null or tunnelip='0.0.0.0') and action in ('tunnel-stats', 'tunnel-down', 'tunnel-up') and
        tunnelid is not null and tunnelid!=0 group by devid, vd, remip, xauthuser_agg, user_agg,
        tunnelid order by tunnelid)### t group by devid, vd, remip, tunnelid) tt where bandwidth>0
        group by user_src order by duration desc

```

Dataset Name	Description	Log Category
Top-SSL-VPN-Web-Mode-Users-By-Bandwidth	Top SSL VPN web mode users by bandwidth usage	event

```

select
    user_src,
    remip as remote_ip,
    from_dtime(
        min(s_time)
    ) as start_time,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
(
    select
        devid,
        vd,
        user_src,
        remip,
        tunnelid,
        min(s_time) as s_time,
        max(e_time) as e_time,

```

```

(
    case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out)
else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out)
end
) as bandwidth,
(
    case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_
in)- min(min_traffic_in) end
) as traffic_in,
(
    case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
) as traffic_out
from
    ###(select devid, vd, remip, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src,
tunnelid, tunneltype, max(coalesce(duration,0)) as max_duration, min(coalesce(duration,0))
as min_duration, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, min
(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvbyte, 0)) as min_traffic_in,
max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvbyte, 0)) as max_traffic_in
from $log where $filter and subtype='vpn' and tunneltype like 'ssl%' and action in ('tunnel-
stats', 'tunnel-down', 'tunnel-up') and coalesce(nullifna(`user`), ipstr(`remip`)) is not
null and tunnelid is not null group by devid, vd, user_src, remip, tunnelid, tunneltype)###
t group by devid, vd, user_src, remip, tunnelid) tt where bandwidth>0 group by user_src,
remote_ip order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-SSL-VPN-Web-Mode-Users-By-Duration	Top SSL VPN web mode users by duration	event

```

select
    user_src,
    remip as remote_ip,
    from_dtime(
        min(s_time)
    ) as start_time,
    (
        max(e_time)- min(s_time)
    ) as duration
from
    (
        select
            devid,
            vd,
            user_src,
            remip,
            tunnelid,
            min(s_time) as s_time,
            max(e_time) as e_time
        from
            ###(select devid, vd, remip, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src,
tunnelid, tunneltype, max(coalesce(duration,0)) as max_duration, min(coalesce(duration,0))
as min_duration, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, min
(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvbyte, 0)) as min_traffic_in,
max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvbyte, 0)) as max_traffic_in
from $log where $filter and subtype='vpn' and tunneltype like 'ssl%' and action in ('tunnel-

```

```
stats', 'tunnel-down', 'tunnel-up') and coalesce(nullifna(`user`), ipstr(`remip`)) is not
null and tunnelid is not null group by devid, vd, user_src, remip, tunnelid, tunneltype)###
t where tunneltype='ssl-web' group by devid, vd, user_src, remip, tunnelid) tt group by
user_src, remote_ip order by duration desc
```

Dataset Name	Description	Log Category
Top-SSL-VPN-Users-By-Duration	Top SSL VPN users by duration	event

```
select
  user_src,
  tunneltype,
  sum(duration) as duration,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      user_src,
      tunneltype,
      tunnelid,
      (
        case when min(s_time)= max(e_time) then max(max_duration) else max(max_duration)-
min(min_duration) end
      ) as duration,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_
in)- min(min_traffic_in) end
      ) as traffic_in,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
      ) as traffic_out,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out)
else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out)
end
      ) as bandwidth
    from
      ###(select devid, vd, remip, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src,
tunnelid, tunneltype, max(coalesce(duration,0)) as max_duration, min(coalesce(duration,0))
as min_duration, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, min
(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in,
max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in
from $log where $filter and subtype='vpn' and tunneltype like 'ssl%' and action in ('tunnel-
stats', 'tunnel-down', 'tunnel-up') and coalesce(nullifna(`user`), ipstr(`remip`)) is not
null and tunnelid is not null group by devid, vd, user_src, remip, tunnelid, tunneltype)###
t group by devid, vd, remip, user_src, tunnelid, tunneltype) tt where bandwidth>0 group by
user_src, tunneltype order by duration desc
```

Dataset Name	Description	Log Category
vpn-Top-Dial-Up-VPN-Users-By-Duration	Top dial up VPN users by duration	event

```

select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr('remip')
  ) as user_src,
  t_type as tunneltype,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(duration) as duration,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      string_agg(
        distinct xauthuser_agg,
        & #039; ' ) as xauthuser_agg, string_agg(distinct user_agg, ' ' ) as user_agg, t_type,
      tunnelid, min(s_time) as s_time, max(e_time) as e_time, (case when min(s_time)=max(e_time)
      then max(max_duration) else max(max_duration)-min(min_duration) end) as duration, (case when
      min(s_time)=max(e_time) then max(max_traffic_in)+max(max_traffic_out) else max(max_traffic_
      in)-min(min_traffic_in)+max(max_traffic_out)-min(min_traffic_out) end) as bandwidth, (case
      when min(s_time)=max(e_time) then max(max_traffic_in) else max(max_traffic_in)-min(min_
      traffic_in) end) as traffic_in, (case when min(s_time)=max(e_time) then max(max_traffic_out)
      else max(max_traffic_out)-min(min_traffic_out) end) as traffic_out from ###(select devid,
      vd, remip, nullifna('xauthuser') as xauthuser_agg, nullifna('user') as user_agg, (case when
      tunneltype like 'ipsec%' then 'ipsec' else tunneltype end) as t_type, tunnelid, tunnelip,
      min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, max(coalesce
      (duration,0)) as max_duration, min(coalesce(duration,0)) as min_duration, min(coalesce
      (sentbyte, 0)) as min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, max
      (coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in,
      sum((case when action='tunnel-up' then 1 else 0 end)) as tunnelup from $log where $filter
      and subtype='vpn' and (tunneltype like 'ipsec%' or tunneltype like 'ssl%') and action in
      ('tunnel-up', 'tunnel-stats', 'tunnel-down') and tunnelid is not null and tunnelid!=0 group
      by xauthuser_agg, user_agg, devid, vd, remip, t_type, tunnelid, tunnelip)### t where (t_type
      like 'ssl%' or (t_type like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0')))
      group by devid, vd, remip, t_type, tunnelid) tt where bandwidth>0 group by user_src,
      tunneltype order by duration desc

```

Dataset Name	Description	Log Category
vpn-User-Login-history	VPN user login history	event

```

select
  $flex_timescale(timestamp) as hodex,
  sum(tunnelup) as total_num

```



```

from
(
  select
    timestamp,
    devid,
    vd,
    remip,
    tunnelid,
    max(tunnelup) as tunnelup,
    max(traffic_in) as traffic_in,
    max(traffic_out) as traffic_out
  from
    ###(select $flex_timestamp as timestamp, devid, vd, remip, tunnelid, max((case when
    action='tunnel-up' then 1 else 0 end)) as tunnelup, max(coalesce(sentbyte, 0)) as traffic_
    out, max(coalesce(rcvdbyte, 0)) as traffic_in from $log where $filter and subtype='vpn' and
    (tunneltype like 'ipsec%' or tunneltype like 'ssl%') and action in ('tunnel-up', 'tunnel-
    stats', 'tunnel-down') and tunnelid is not null group by timestamp, devid, vd, remip,
    tunnelid /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t group by timestamp, devid,
    vd, remip, tunnelid having max(tunnelup) > 0 and max(traffic_in)+max(traffic_out)>0) t group
    by hodex order by total_num desc

```

Dataset Name	Description	Log Category
vpn-Failed-Login-Attempts	VPN failed logins	event

```

select
  f_user,
  tunneltype,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`xauthuser`), `user`) as f_user, tunneltype, count(*) as
  total_num from $log where $filter and subtype='vpn' and (tunneltype='ipsec' or left
  (tunneltype, 3)='ssl') and action in ('ssl-login-fail', 'ipsec-login-fail') and coalesce
  (nullifna(`xauthuser`), nullifna(`user`)) is not null group by f_user, tunneltype)### t
  group by f_user, tunneltype order by total_num desc

```

Dataset Name	Description	Log Category
vpn-Authenticated-Logins	VPN authenticated logins	event

```

select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as f_user,
  t_type as tunneltype,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(total_num) as total_num,
  sum(duration) as duration
from
(
  select
    string_agg(

```

```

distinct xauthuser_agg,
& #039; ') as xauthuser_agg, string_agg(distinct user_agg, ' ') as user_agg, t_type,
devid, vd, remip, tunnelid, min(s_time) as s_time, max(e_time) as e_time, (case when min(s_
time)=max(e_time) then max(max_duration) else max(max_duration)-min(min_duration) end) as
duration, (case when min(s_time)=max(e_time) then max(max_traffic_in)+max(max_traffic_out)
else max(max_traffic_in)-min(min_traffic_in)+max(max_traffic_out)-min(min_traffic_out) end)
as bandwidth, (case when min(s_time)=max(e_time) then max(max_traffic_in) else max(max_
traffic_in)-min(min_traffic_in) end) as traffic_in, (case when min(s_time)=max(e_time) then
max(max_traffic_out) else max(max_traffic_out)-min(min_traffic_out) end) as traffic_out, sum
(tunnelup) as total_num from ###(select devid, vd, remip, nullifna(`xauthuser`) as
xauthuser_agg, nullifna(`user`) as user_agg, (case when tunneltype like 'ipsec%' then
'ipsec' else tunneltype end) as t_type, tunnelid, tunnelip, min(coalesce(dtime, 0)) as s_
time, max(coalesce(dtime, 0)) as e_time, max(coalesce(duration,0)) as max_duration, min
(coalesce(duration,0)) as min_duration, min(coalesce(sentbyte, 0)) as min_traffic_out, min
(coalesce(rcvdbyte, 0)) as min_traffic_in, max(coalesce(sentbyte, 0)) as max_traffic_out,
max(coalesce(rcvdbyte, 0)) as max_traffic_in, sum((case when action='tunnel-up' then 1 else
0 end)) as tunnelup from $log where $filter and subtype='vpn' and (tunneltype like 'ipsec%'
or tunneltype like 'ssl%') and action in ('tunnel-up', 'tunnel-stats', 'tunnel-down') and
tunnelid is not null and tunnelid!=0 group by xauthuser_agg, user_agg, devid, vd, remip, t_
type, tunnelid, tunnelip)### t group by t_type, devid, vd, remip, tunnelid having max
(tunnelup) > 0) tt where bandwidth>0 group by f_user, tunneltype order by total_num desc

```

Dataset Name	Description	Log Category
vpn-Traffic-Usage-Trend-VPN-Summary	VPN traffic usage trend	event

```

select
  hodesk,
  sum(ssl_traffic_bandwidth) as ssl_bandwidth,
  sum(ipsec_traffic_bandwidth) as ipsec_bandwidth
from
(
  select
    $flex_timescale(timestamp) as hodesk,
    devid,
    vd,
    remip,
    tunnelid,
    (
      case when t_type like & #039;ssl%' then (case when min(s_time)=max(e_time) then max
(max_traffic_in)+max(max_traffic_out) else max(max_traffic_in)-min(min_traffic_in)+max(max_
traffic_out)-min(min_traffic_out) end) else 0 end) as ssl_traffic_bandwidth, (case when t_
type like 'ipsec%' then (case when min(s_time)=max(e_time) then max(max_traffic_in)+max(max_
traffic_out) else max(max_traffic_in)-min(min_traffic_in)+max(max_traffic_out)-min(min_
traffic_out) end) else 0 end) as ipsec_traffic_bandwidth, min(s_time) as s_time, max(e_
time) as e_time from ###(select $flex_timestamp as timestamp, devid, vd, remip, tunnelid,
(case when tunneltype like 'ipsec%' then 'ipsec' else tunneltype end) as t_type, (case when
action='tunnel-up' then 1 else 0 end) as tunnelup, max(coalesce(sentbyte, 0)) as max_
traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in, min(coalesce(sentbyte, 0)) as
min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, min(coalesce(dtime, 0)) as s_
time, max(coalesce(dtime, 0)) as e_time from $log where $filter and subtype='vpn' and
(tunneltype like 'ipsec%' or tunneltype like 'ssl%') and action in ('tunnel-up','tunnel-
stats', 'tunnel-down') and tunnelid is not null and tunnelid!=0 group by timestamp, devid,
vd, remip, t_type, tunnelid, action /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t
group by hodesk, devid, t_type, vd, remip, tunnelid) tt group by hodesk order by hodesk

```

Dataset Name	Description	Log Category
Top-S2S-IPSEC-Tunnels-By-Bandwidth-and-Availability	Top S2S IPsec tunnels by bandwidth usage and avail	event

```
select
  vpngroup,
  tunneltype,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in,
  sum(bandwidth) as bandwidth,
  sum(uptime) as uptime
from
(
  select
    vpngroup,
    tunneltype,
    tunnelid,
    devid,
    vd,
    sum(sent_end - sent_beg) as traffic_out,
    sum(rcvd_end - rcvd_beg) as traffic_in,
    sum(
      sent_end - sent_beg + rcvd_end - rcvd_beg
    ) as bandwidth,
    sum(duration_end - duration_beg) as uptime
  from
    ###(select tunnelid, tunneltype, vpngroup, devid, vd, min(coalesce(sentbyte, 0)) as
    sent_beg, max(coalesce(sentbyte, 0)) as sent_end, min(coalesce(rcvdbyte, 0)) as rcvd_beg,
    max(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce(duration, 0)) as duration_beg, max
    (coalesce(duration, 0)) as duration_end from $log where $filter and subtype='vpn' and
    action='tunnel-stats' and tunneltype like 'ipsec%' and (tunnelip is null or
    tunnelip='0.0.0.0') and nullifna(`user`) is null and tunnelid is not null and tunnelid!=0
    group by tunnelid, tunneltype, vpngroup, devid, vd /*SkipSTART*/order by
    tunnelid/*SkipEND*/)### t group by vpngroup, tunneltype, tunnelid, devid, vd order by
    bandwidth desc) t where bandwidth>0 group by vpngroup, tunneltype order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Dialup-IPSEC-By-Bandwidth-and-Availability	Top dialup IPsec users by bandwidth usage and avail	event

```
select
  user_src,
  remip,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in,
  sum(bandwidth) as bandwidth,
  sum(uptime) as uptime
from
(
  select
    user_src,
    remip,
    tunnelid,
    devid,
```

```

        vd,
        sum(sent_end - sent_beg) as traffic_out,
        sum(rcvd_end - rcvd_beg) as traffic_in,
        sum(
            sent_end - sent_beg + rcvd_end - rcvd_beg
        ) as bandwidth,
        sum(duration_end - duration_beg) as uptime
    from
        ###(select tunnelid, coalesce(nullifna(`xauthuser`), nullifna(`user`), ipstr(`remip`))
as user_src, remip, devid, vd, min(coalesce(sentbyte, 0)) as sent_beg, max(coalesce
(sentbyte, 0)) as sent_end, min(coalesce(rcvdbyte, 0)) as rcvd_beg, max(coalesce(rcvdbyte,
0)) as rcvd_end, min(coalesce(duration, 0)) as duration_beg, max(coalesce(duration, 0)) as
duration_end from $log where $filter and subtype='vpn' and action='tunnel-stats' and
tunneltype like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0') and tunnelid is
not null and tunnelid!=0 group by tunnelid, user_src, remip, devid, vd /*SkipSTART*/order by
tunnelid/*SkipEND*/)### t group by user_src, remip, tunnelid, devid, vd order by bandwidth
desc) t where bandwidth>0 group by user_src, remip order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-SSL-Tunnel-Mode-By-Bandwidth-and-Availability	Top SSL tunnel users by bandwidth usage and avail	event

```

select
    user_src,
    remote_ip,
    sum(traffic_out) as traffic_out,
    sum(traffic_in) as traffic_in,
    sum(bandwidth) as bandwidth,
    sum(uptime) as uptime
from
    (
        select
            user_src,
            remip as remote_ip,
            tunnelid,
            devid,
            vd,
            sum(sent_end - sent_beg) as traffic_out,
            sum(rcvd_end - rcvd_beg) as traffic_in,
            sum(
                sent_end - sent_beg + rcvd_end - rcvd_beg
            ) as bandwidth,
            sum(duration_end - duration_beg) as uptime
        from
            ###(select tunnelid, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src, remip,
devid, vd, min(coalesce(sentbyte, 0)) as sent_beg, max(coalesce(sentbyte, 0)) as sent_end,
min(coalesce(rcvdbyte, 0)) as rcvd_beg, max(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce
(duration, 0)) as duration_beg, max(coalesce(duration, 0)) as duration_end from $log where
$filter and subtype='vpn' and action='tunnel-stats' and tunneltype in ('ssl-tunnel', 'ssl')
and coalesce(nullifna(`user`), ipstr(`remip`)) is not null and tunnelid is not null group by
tunnelid, user_src, remip, devid, vd /*SkipSTART*/order by tunnelid/*SkipEND*/)### t group
by user_src, remote_ip, tunnelid, devid, vd order by bandwidth desc) t where bandwidth>0
group by user_src, remote_ip order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-SSL-Web-Mode-By-Bandwidth-and-Availability	Top SSL web users by bandwidth usage and avail	event

```

select
  user_src,
  remote_ip,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in,
  sum(bandwidth) as bandwidth,
  sum(uptime) as uptime
from
(
  select
    user_src,
    remip as remote_ip,
    tunnelid,
    devid,
    vd,
    sum(sent_end - sent_beg) as traffic_out,
    sum(rcvd_end - rcvd_beg) as traffic_in,
    sum(
      sent_end - sent_beg + rcvd_end - rcvd_beg
    ) as bandwidth,
    sum(duration_end - duration_beg) as uptime
  from
    ###(select tunnelid, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src, remip,
    devid, vd, min(coalesce(sentbyte, 0)) as sent_beg, max(coalesce(sentbyte, 0)) as sent_end,
    min(coalesce(rcvdbyte, 0)) as rcvd_beg, max(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce
    (duration, 0)) as duration_beg, max(coalesce(duration, 0)) as duration_end from $log where
    $filter and subtype='vpn' and action='tunnel-stats' and tunneltype='ssl-web' and coalesce
    (nullifna(`user`), ipstr(`remip`)) is not null and tunnelid is not null group by tunnelid,
    user_src, remip, devid, vd /*SkipSTART*/order by tunnelid/*SkipEND*/)### t group by user_
    src, remote_ip, tunnelid, devid, vd having sum(sent_end-sent_beg+rcvd_end-rcvd_beg)>0 order
    by bandwidth desc) t where bandwidth>0 group by user_src, remote_ip order by bandwidth desc

```

Dataset Name	Description	Log Category
Admin-Login-Summary	Event admin login summary	event

```

select
  f_user,
  ui,
  sum(login) as total_num,
  sum(login_duration) as total_duration,
  sum(config_change) as total_change
from
(
  select
    `user` as f_user,
    ui,
    (
      case when logid_to_int(logid)= 32001 then 1 else 0 end
    ) as login,
    (

```

```

        case when logid_to_int(logid)= 32003 then duration else 0 end
    ) as login_duration,
    (
        case when logid_to_int(logid)= 32003
            and state is not null then 1 else 0 end
    ) as config_change
from
    $log
where
    $filter
    and nullifna(`user`) is not null
    and logid_to_int(logid) in (32001, 32003)
) t
group by
    f_user,
    ui
having
    sum(login)+ sum(config_change)> 0
order by
    total_num desc

```

Dataset Name	Description	Log Category
Admin-Login-Summary-By-Date	Event admin login summary by date	event

```

select
    $flex_timescale(timestamp) as dom,
    sum(total_num) as total_num,
    sum(total_change) as total_change
from
    ###(select timestamp, sum(login) as total_num, sum(config_change) as total_change from
    (select $flex_timestamp as timestamp, (case when logid_to_int(logid)=32001 then 1 else 0
    end) as login, (case when logid_to_int(logid)=32003 and state is not null then 1 else 0 end)
    as config_change from $log where $filter and logid_to_int(logid) in (32001, 32003)) t group
    by timestamp having sum(login)+sum(config_change)>0 /*SkipSTART*/order by timestamp
    desc/*SkipEND*/)### t group by dom order by dom

```

Dataset Name	Description	Log Category
Admin-Failed-Login-Summary	Event admin failed login summary	event

```

select
    `user` as f_user,
    ui,
    count(status) as total_failed
from
    $log
where
    $filter
    and nullifna(`user`) is not null
    and logid_to_int(logid) = 32002
group by
    ui,
    f_user
order by
    total_failed desc

```

Dataset Name	Description	Log Category
System-Summary-By-Severity	Event system summary by severity	event

```
select
  severity_tmp as severity,
  sum(count) as total_num
from
  ###(select coalesce(nullifna(logdesc), msg) as msg_desc, (case when level in ('critical',
'alert', 'emergency') then 'Critical' when level='error' then 'High' when level='warning'
then 'Medium' when level='notice' then 'Low' else 'Info' end) as severity_tmp, count(*) as
count from $log where $filter and subtype='system' group by msg_desc, severity_tmp
/*SkipSTART*/order by count desc/*SkipEND*/)### t group by severity order by total_num desc
```

Dataset Name	Description	Log Category
System-Summary-By-Date	Event system summary by date	event

```
select
  $flex_timescale(timestamp) as dom,
  sum(critical) as critical,
  sum(high) as high,
  sum(medium) as medium
from
  ###(select $flex_timestamp as timestamp, sum(case when level in ('critical', 'alert',
'emergency') then 1 else 0 end) as critical, sum(case when level = 'error' then 1 else 0
end) as high, sum(case when level = 'warning' then 1 else 0 end) as medium from $log where
$filter and subtype='system' group by timestamp /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t group by dom order by dom
```

Dataset Name	Description	Log Category
Important-System-Summary-By-Date	Event system summary by date	event

```
select
  $flex_timescale(timestamp) as dom,
  sum(critical) as critical,
  sum(high) as high,
  sum(medium) as medium
from
  ###(select $flex_timestamp as timestamp, sum(case when level in ('critical', 'alert',
'emergency') then 1 else 0 end) as critical, sum(case when level = 'error' then 1 else 0
end) as high, sum(case when level = 'warning' then 1 else 0 end) as medium from $log where
$filter and subtype='system' group by timestamp /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t group by dom order by dom
```

Dataset Name	Description	Log Category
System-Critical-Severity-Events	Event system critical severity events	event

```
select
  msg_desc as msg,
  severity_tmp as severity,
  sum(count) as counts
from
  ###(select coalesce(nullifna(logdesc), msg) as msg_desc, (case when level in ('critical',
```

```
'alert', 'emergency') then 'Critical' when level='error' then 'High' when level='warning'
then 'Medium' when level='notice' then 'Low' else 'Info' end) as severity_tmp, count(*) as
count from $log where $filter and subtype='system' group by msg_desc, severity_tmp
/*SkipSTART*/order by count desc/*SkipEND*/)### t where severity_tmp='Critical' group by
msg, severity_tmp order by counts desc
```

Dataset Name	Description	Log Category
System-High-Severity-Events	Event system high severity events	event

```
select
  msg_desc as msg,
  severity_tmp as severity,
  sum(count) as counts
from
  ###(select coalesce(nullifna(logdesc), msg) as msg_desc, (case when level in ('critical',
'alert', 'emergency') then 'Critical' when level='error' then 'High' when level='warning'
then 'Medium' when level='notice' then 'Low' else 'Info' end) as severity_tmp, count(*) as
count from $log where $filter and subtype='system' group by msg_desc, severity_tmp
/*SkipSTART*/order by count desc/*SkipEND*/)### t where severity_tmp='High' group by msg,
severity_tmp order by counts desc
```

Dataset Name	Description	Log Category
System-Medium-Severity-Events	Event system medium severity events	event

```
select
  msg_desc as msg,
  severity_tmp as severity,
  sum(count) as counts
from
  ###(select coalesce(nullifna(logdesc), msg) as msg_desc, (case when level in ('critical',
'alert', 'emergency') then 'Critical' when level='error' then 'High' when level='warning'
then 'Medium' when level='notice' then 'Low' else 'Info' end) as severity_tmp, count(*) as
count from $log where $filter and subtype='system' group by msg_desc, severity_tmp
/*SkipSTART*/order by count desc/*SkipEND*/)### t where severity_tmp='Medium' group by msg,
severity_tmp order by counts desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Traffic-Summary	UTM drilldown traffic summary	traffic

```
select
  srcip,
  srcname
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
srcip, srcname, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log
where $filter and (logflag&1>0) group by user_src, srcip, srcname order by bandwidth
desc)### t where $filter-drilldown group by srcip, srcname
```

Dataset Name	Description	Log Category
utm-drilldown-Top-User-Destination	UTM drilldown top user destination	traffic


```

select
  appid,
  app,
  dstip,
  sum(sessions) as sessions,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  appid, app, dstip, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as
  bandwidth from $log where $filter and (logflag&1>0) and dstip is not null and nullifna(app)
  is not null group by user_src, appid, app, dstip having sum(coalesce(sentbyte, 0)+coalesce
  (rcvdbyte, 0))>0 order by bandwidth desc)### t where $filter-drilldown group by appid, app,
  dstip order by bandwidth desc

```

Dataset Name	Description	Log Category
utm-drilldown-Email-Senders-Summary	UTM drilldown email senders summary	traffic

```

select
  sum(requests) as requests,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth
  from $log where $filter and (logflag&1>0) and service in ('smtp', 'SMTP', '25/tcp',
  '587/tcp', 'smtps', 'SMTPS', '465/tcp') group by user_src, sender order by requests desc)###
  t where $filter-drilldown

```

Dataset Name	Description	Log Category
utm-drilldown-Email-Recipients-Summary	UTM drilldown email recipients summary	traffic

```

select
  sum(requests) as requests,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as
  bandwidth from $log where $filter and (logflag&1>0) and recipient is not null and service in
  ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s',
  'POP3S', '995/tcp') group by user_src, recipient order by requests desc)### t where $filter-
  drilldown

```

Dataset Name	Description	Log Category
utm-drilldown-Top-Email-Recipients-By-Bandwidth	UTM drilldown top email recipients	traffic

```

select
  recipient,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as

```

bandwidth from \$log where \$filter and (logflag&1>0) and recipient is not null and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') group by user_src, recipient order by requests desc)### t where \$filter-drilldown group by recipient having sum(bandwidth)>0 order by bandwidth desc

Dataset Name	Description	Log Category
utm-drilldown-Top-Email-Senders-By-Bandwidth	UTM drilldown top email senders	traffic

```
select
  sender,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth
  from $log where $filter and (logflag&1>0) and service in ('smtp', 'SMTP', '25/tcp',
  '587/tcp', 'smtps', 'SMTPS', '465/tcp') group by user_src, sender order by requests desc)###
  t where $filter-drilldown and sender is not null group by sender having sum(bandwidth)>0
  order by bandwidth desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Allowed-Websites-By-Bandwidth	UTM drilldown top allowed web sites by bandwidth	traffic

```
select
  appid,
  hostname,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  appid, hostname, (case when utmaction in ('block', 'blocked') then 1 else 0 end) as blocked,
  sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth from $log-traffic where
  $filter and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and
  (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-
  block', 'script-filter')))) and hostname is not null group by user_src, appid, hostname,
  blocked order by bandwidth desc)### t where $filter-drilldown and blocked=0 group by appid,
  hostname order by bandwidth desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Blocked-Websites-By-Request	UTM drilldown top blocked web sites by request	webfilter

```
select
  appid,
  hostname,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, 0 as appid, hostname,
  (case when action='blocked' then 1 else 0 end) as blocked, count(*) as requests from $log
  where $filter and (eventtype is null or logver>=502000000) and hostname is not null group by
  user_src, appid, hostname, blocked order by requests desc)### t where $filter-drilldown and
  blocked=1 group by appid, hostname order by requests desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Virus-By-Name	UTM drilldown top virus	virus

```
select
    virus,
    sum(totalnum) as totalnum
from
    ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, count(*) as
totalnum from $log where $filter and (eventtype is null or logver>=502000000) and nullifna
(virus) is not null group by user_src, virus order by totalnum desc)### t where $filter-
drilldown group by virus order by totalnum desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Attacks	UTM drilldown top attacks by name	attack

```
select
    attack,
    sum(attack_count) as attack_count
from
    ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, attack, count(*) as
attack_count from $log where $filter and nullifna(attack) is not null group by user_src,
attack order by attack_count desc)### t where $filter-drilldown group by attack order by
attack_count desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Vulnerability	UTM drilldown top vulnerability by name	netscan

```
select
    vuln,
    sum(totalnum) as totalnum
from
    ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, vuln, count(*) as
totalnum from $log where $filter and action='vuln-detection' and vuln is not null group by
user_src, vuln order by totalnum desc)### t where $filter-drilldown group by vuln order by
totalnum desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-App-By-Bandwidth	UTM drilldown top applications by bandwidth usage	traffic

```
select
    appid,
    app,
    sum(bandwidth) as bandwidth
from
    ###(select user_src, appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum
(sessions) as sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip,
epid, euid, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
appid, app, appcat, apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta,
rcvdbyte, 0)) as bandwidth, count(*) as sessions from $log-traffic where $filter and
(logflag&(1|32)>0) and nullifna(app) is not null group by dvid, srcip, dstip, epid, euid,
user_src, appid, app, appcat, apprisk order by sessions desc)base### t group by user_src,
appid, app, appcat, apprisk /*SkipSTART*/order by sessions desc, bandwidth
```

```
desc/*SkipEND*/)### t where $filter-drilldown group by appid, app having sum(bandwidth)>0
order by bandwidth desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-App-By-Sessions	UTM drilldown top applications by session count	traffic

```
select
  appid,
  app,
  sum(sessions) as sessions
from
  ###(select user_src, appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum
(sessions) as sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip,
epid, euid, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
appid, app, appcat, apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta,
rcvdbyte, 0)) as bandwidth, count(*) as sessions from $log-traffic where $filter and
(logflag&(1|32)>0) and nullifna(app) is not null group by dvid, srcip, dstip, epid, euid,
user_src, appid, app, appcat, apprisk order by sessions desc)base### t group by user_src,
appid, app, appcat, apprisk /*SkipSTART*/order by sessions desc, bandwidth
desc/*SkipEND*/)### t where $filter-drilldown group by appid, app order by sessions desc
```

Dataset Name	Description	Log Category
Top5-Users-By-Bandwidth	UTM drilldown top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as dldn_user,
  count(*) as session,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  dldn_user
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
```

```
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Top-App-By-Bandwidth-Sessions	Top applications by bandwidth usage	traffic

```
select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvddelta, rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentdelta, sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag &(1 | 32)> 0
  )
  and nullifna(app) is not null
group by
  app_group
having
  sum(
    coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Category-By-Bandwidth	Application risk application usage by category	traffic

```
select
  appcat,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as
sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app,
appcat, apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app,
appcat, apprisk order by sessions desc)base### t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null group by appcat order by bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Top-Users-By-Bandwidth-Sessions	Bandwidth application top users by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvddelta, rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentdelta, sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag &(1 | 32)> 0
  )
group by
  user_src
having
  sum(
    coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
bandwidth-app-Traffic-By-Active-User-Number	Bandwidth application traffic by active user number	traffic

```

select
  $flex_timescale(timestamp) as hindex,
  count(
    distinct(user_src)
  ) as total_user
from
  ###(select $flex_timestamp as timestamp, coalesce(nullifna(`user`), nullifna
(`unauthuser`), ipstr(`srcip`)) as user_src from $log where $filter and (logflag&(1|32)>0)
group by timestamp, user_src order by timestamp desc)### t group by hindex order by hindex

```

Dataset Name	Description	Log Category
bandwidth-app-Top-Dest-By-Bandwidth-Sessions	Bandwidth application top dest by bandwidth usage sessions	traffic

```

select
  coalesce(
    nullifna(
      root_domain(hostname)
    ),
    ipstr(`dstip`)
  ) as domain,
  sum(
    coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvddelta, rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentdelta, sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag & (1 | 32) > 0
  )
group by
  domain
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
bandwidth-app-Top-Policies-By-Bandwidth-Sessions	Top policies by bandwidth and sessions	traffic

```

select
  coalesce(
    pol.name,
    cast(policyid as text)
  ) as polid,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions
from
  ###(select policyid, poluuid, sum(coalesce(rcvdbyte, 0) + coalesce(sentbyte, 0)) as
bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as traffic_
out, count(*) as sessions from $log where $filter and (logflag&1>0) group by policyid,
poluuid order by bandwidth desc)### t1 left join $ADOMTBL_PLHD_POLINFO pol on
t1.poluuid=pol.uuid group by polid order by bandwidth desc

```

Dataset Name	Description	Log Category
bandwidth-app-Traffic-Statistics	Bandwidth application traffic statistics	traffic

```

drop
  table if exists rpt_tmptbl_1; create temporary table rpt_tmptbl_1(

```

```

        total_sessions varchar(255),
        total_bandwidth varchar(255),
        ave_session varchar(255),
        ave_bandwidth varchar(255),
        active_date varchar(255),
        total_users varchar(255),
        total_app varchar(255),
        total_dest varchar(255)
    ); insert into rpt_tmptbl_1 (
        total_sessions, total_bandwidth,
        ave_session, ave_bandwidth
    )
select
    format_numeric_no_decimal(
        sum(sessions)
    ) as total_sessions,
    bandwidth_unit(
        sum(bandwidth)
    ) as total_bandwidth,
    format_numeric_no_decimal(
        cast(
            sum(sessions)/ $days_num as decimal(18, 0)
        )
    ) as ave_session,
    bandwidth_unit(
        cast(
            sum(bandwidth)/ $days_num as decimal(18, 0)
        )
    ) as ave_bandwidth
from
    ###(select count(*) as sessions, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta,
rcvdbyte, 0)) as bandwidth from $log where $filter and (logflag&(1|32)>0))### t; update rpt_
tmptbl_1 set active_date=t1.dom from (select dom, sum(sessions) as sessions from ###(select
$DAY_OF_MONTH as dom, count(*) as sessions from $log where $filter and (logflag&(1|32)>0)
group by dom order by sessions desc)### t group by dom order by sessions desc limit 1) as
t1; update rpt_tmptbl_1 set total_users=t2.totalnum from (select format_numeric_no_decimal
(count(distinct(user_src))) as totalnum from ###(select coalesce(nullifna(`user`), nullifna
(`unauthuser`), ipstr(`srcip`)) as user_src, count(*) as count from $log where $filter and
(logflag&(1|32)>0) group by user_src order by count desc)### t) as t2; update rpt_tmptbl_1
set total_app=t3.totalnum from (select format_numeric_no_decimal(count(distinct(app_grp)))
as totalnum from ###(select app_group_name(app) as app_grp, count(*) as count from $log
where $filter and (logflag&(1|32)>0) and nullifna(app) is not null group by app_grp order by
count desc)### t) as t3; update rpt_tmptbl_1 set total_dest=t4.totalnum from (select format_
numeric_no_decimal(count(distinct(dstip))) as totalnum from ###(select dstip, count(*) as
count from $log where $filter and (logflag&(1|32)>0) and dstip is not null group by dstip
order by count desc)### t ) as t4; select 'Total Sessions' as summary, total_sessions as
stats from rpt_tmptbl_1 union all select 'Total Bytes Transferred' as summary, total_
bandwidth as stats from rpt_tmptbl_1 union all select 'Most Active Date By Sessions' as
summary, active_date as stats from rpt_tmptbl_1 union all select 'Total Users' as summary,
total_users as stats from rpt_tmptbl_1 union all select 'Total Applications' as summary,
total_app as stats from rpt_tmptbl_1 union all select 'Total Destinations' as summary,
total_dest as stats from rpt_tmptbl_1 union all select 'Average Sessions Per Day' as
summary, ave_session as stats from rpt_tmptbl_1 union all select 'Average Bytes Per Day' as
summary, ave_bandwidth as stats from rpt_tmptbl_1

```


Dataset Name	Description	Log Category
Score-Summary-For-All-Users-Devices	Reputation score summary for all users devices	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  sum(scores) as scores
from
  ###(select $flex_timestamp as timestamp, sum(crsscore%65536) as scores, count(*) as
totalnum from $log where $filter and (logflag&1>0) and crsscore is not null group by
timestamp having sum(crsscore%65536)>0 order by timestamp desc)### t group by hodex order by
hodex
```

Dataset Name	Description	Log Category
Number-Of-Incidents-For-All-Users-Devices	Reputation number of incidents for all users devices	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  sum(scores) as scores,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, sum(crsscore%65536) as scores, count(*) as
totalnum from $log where $filter and (logflag&1>0) and crsscore is not null group by
timestamp having sum(crsscore%65536)>0 order by timestamp desc)### t group by hodex order by
hodex
```

Dataset Name	Description	Log Category
Top-Users-By-Reputation-Scores	Reputation top users by scores	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(crsscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crsscore is not null
group by
  user_src
having
  sum(crsscore % 65536)> 0
order by
  scores desc
```

Dataset Name	Description	Log Category
Top-Devices-By-Reputation-Scores	Reputation top devices by scores	traffic

```

select
  max(
    get_devtype(srcswversion, osname, devtype)
  ) as devtype_new,
  coalesce(
    nullifna(`srcname`),
    nullifna(`srcmac`),
    ipstr(`srcip`)
  ) as dev_src,
  sum(crscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crscore is not null
group by
  dev_src
having
  sum(crscore % 65536)> 0
order by
  scores desc

```

Dataset Name	Description	Log Category
Top-Users-With-Increased-Scores	Reputation top users with increased scores	traffic

```

drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  f_user,
  sum(sum_rp_score) as sum_rp_score
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as f_user,
  sum(crscore%65536) as sum_rp_score from $log where $pre_period $filter and (logflag&1>0) and
  crscore is not null group by f_user having sum(crscore%65536)>0 order by sum_rp_score
  desc)### t group by f_user; create temporary table rpt_tmptbl_2 as select f_user, sum(sum_
  rp_score) as sum_rp_score from ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`),
  ipstr(`srcip`)) as f_user, sum(crscore%65536) as sum_rp_score from $log where $filter and
  (logflag&1>0) and crscore is not null group by f_user having sum(crscore%65536)>0 order by
  sum_rp_score desc)### t group by f_user; select t1.f_user, sum(t1.sum_rp_score) as t1_sum_
  score, sum(t2.sum_rp_score) as t2_sum_score, (sum(t2.sum_rp_score)-sum(t1.sum_rp_score)) as
  delta from rpt_tmptbl_1 as t1 inner join rpt_tmptbl_2 as t2 on t1.f_user=t2.f_user where
  t2.sum_rp_score > t1.sum_rp_score group by t1.f_user order by delta desc

```

Dataset Name	Description	Log Category
Top-Devices-With-Increased-Scores	Reputation top devices with increased scores	traffic

```

drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  f_device,
  devtype_new,
  sum(sum_rp_score) as sum_rp_score
from
  ###(select coalesce(nullifna(`srcname`),nullifna(`srcmac`), ipstr(`srcip`)) as f_device,
  get_devtype(srswversion, osname, devtype) as devtype_new, sum(crswscore%65536) as sum_rp_
  score from $log where $pre_period $filter and (logflag&1>0) and crswscore is not null group by
  f_device, devtype_new having sum(crswscore%65536)>0 order by sum_rp_score desc)### t group by
  f_device, devtype_new; create temporary table rpt_tmptbl_2 as select f_device, devtype_new,
  sum(sum_rp_score) as sum_rp_score from ###(select coalesce(nullifna(`srcname`),nullifna
  (`srcmac`), ipstr(`srcip`)) as f_device, get_devtype(srswversion, osname, devtype) as
  devtype_new, sum(crswscore%65536) as sum_rp_score from $log where $filter and (logflag&1>0)
  and crswscore is not null group by f_device, devtype_new having sum(crswscore%65536)>0 order by
  sum_rp_score desc)### t group by f_device, devtype_new; select t1.f_device, t1.devtype_new ,
  sum(t1.sum_rp_score) as t1_sum_score, sum(t2.sum_rp_score) as t2_sum_score, (sum(t2.sum_rp_
  score)-sum(t1.sum_rp_score)) as delta from rpt_tmptbl_1 as t1 inner join rpt_tmptbl_2 as t2
  on t1.f_device=t2.f_device and t1.devtype_new=t2.devtype_new where t2.sum_rp_score > t1.sum_
  rp_score group by t1.f_device, t1.devtype_new order by delta desc

```

Dataset Name	Description	Log Category
Attacks-By-Severity	Threat attacks by severity	attack

```

select
  (
    case when severity =& #039;critical' then 'Critical' when severity='high' then 'High'
    when severity='medium' then 'Medium' when severity='low' then 'Low' when severity='info'
    then 'Info' end) as severity, count(*) as totalnum from $log where $filter group by severity
    order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Attacks-Detected	Threat top attacks detected	attack

```

select
  attack,
  attackid,
  cve,
  severity,
  sum(attack_count) as attack_count
from
  ###(select attack, attackid, t1.severity, cve, (case when t1.severity = 'critical' then 1
  when t1.severity = 'high' then 2 when t1.severity = 'medium' then 3 when t1.severity =
  'low' then 4 else 5 end) as severity_level, count(*) as attack_count from $log t1 left join
  (select name, cve, vuln_type from ips_mdata) t2 on t1.attack=t2.name where $filter and
  nullifna(attack) is not null group by attack, attackid, t1.severity, severity_level, cve
  /*SkipSTART*/order by severity_level, attack_count desc/*SkipEND*/)### t group by attack,
  attackid, severity, severity_level, cve order by severity_level, attack_count desc

```

Dataset Name	Description	Log Category
Top-Attacks-Blocked	Threat top attacks blocked	attack

```
select
  attack,
  count(*) as attack_count
from
  $log
where
  $filter
  and nullifna(attack) is not null
  and action not in (
    & #039;detected', 'pass_session') group by attack order by attack_count desc
```

Dataset Name	Description	Log Category
Top-Virus-Source	Threat top virus source	virus

```
select
  srcip,
  hostname,
  sum(totalnum) as totalnum
from
  ###(select srcip , ipstr(`dstip`) as hostname, count(*) as totalnum from $log where
  $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not null group
  by srcip, hostname /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by srcip,
  hostname order by totalnum desc
```

Dataset Name	Description	Log Category
Intrusion-in-Last-7-Days	Threat intrusion timeline	attack

```
select
  $flex_timescale(timestamp) as hindex,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter
  group by timestamp /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t group by hindex
  order by hindex
```

Dataset Name	Description	Log Category
Virus-Time-Line	Threat virus timeline	virus

```
select
  $flex_datetime(timestamp) as hindex,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter and
  (eventtype is null or logver>=502000000) and nullifna(virus) is not null group by timestamp
  /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t group by hindex order by hindex
```

Dataset Name	Description	Log Category
Top-Spyware-Victims	Threat top spyware victims	virus

```
select
  user_src,
  sum(totalnum) as totalnum
```

```
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, count(*) as
totalnum from $log where $filter group by user_src, virus /*SkipSTART*/order by totalnum
desc/*SkipEND*/)### t where virus like 'Riskware%' group by user_src order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Spyware-by-Name	Threat top spyware by name	virus

```
select
  virus,
  max(virusid_s) as virusid,
  sum(totalnum) as totalnum
from
  ###(select filename, analyticscksum, service, fsaverdict, dtype, coalesce(nullifna
(`user`), ipstr(`srcip`)) as user_src, virus, virusid_to_str(virusid, eventtype) as virusid_
s, count(*) as totalnum from $log where $filter group by filename, analyticscksum, service,
fsaverdict, dtype, user_src, virus, virusid_s /*SkipSTART*/order by totalnum
desc/*SkipEND*/)### t where virus like 'Riskware%' group by virus order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Spyware-Source	Threat top spyware source	traffic

```
select
  srcip,
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and virus like & #039;Riskware%' group by srcip, hostname order by totalnum desc
```

Dataset Name	Description	Log Category
Spyware-Time-Line	Threat spyware timeline	virus

```
select
  $flex_timescale(timestamp) as hindex,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter and
virus like 'Riskware%' group by timestamp /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t group by hindex order by hindex
```

Dataset Name	Description	Log Category
Top-Adware-Victims	Threat top adware victims	virus

```
select
  user_src,
  sum(totalnum) as totalnum
```

```
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, count(*) as
totalnum from $log where $filter group by user_src, virus /*SkipSTART*/order by totalnum
desc/*SkipEND*/)### t where virus like 'Adware%' group by user_src order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Adware-by-Name	Threat top adware by name	virus

```
select
  virus,
  max(virusid_s) as virusid,
  sum(totalnum) as totalnum
from
  ###(select filename, analyticscksum, service, fsaverdict, dtype, coalesce(nullifna
(`user`), ipstr(`srcip`)) as user_src, virus, virusid_to_str(virusid, eventtype) as virusid_
s, count(*) as totalnum from $log where $filter group by filename, analyticscksum, service,
fsaverdict, dtype, user_src, virus, virusid_s /*SkipSTART*/order by totalnum
desc/*SkipEND*/)### t where virus like 'Adware%' group by virus order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Adware-Source	Threat top adware source	traffic

```
select
  srcip,
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and virus like & #039;Adware%' group by srcip, hostname order by totalnum desc
```

Dataset Name	Description	Log Category
Adware-Time-Line	Threat adware timeline	virus

```
select
  $flex_timescale(timestamp) as hodex,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter and
virus like 'Adware%' group by timestamp /*SkipSTART*/order by timestamp desc/*SkipEND*/)###
t group by hodex order by hodex
```

Dataset Name	Description	Log Category
Intrusions-Timeline-By-Severity	Threat intrusions timeline by severity	attack

```
select
  $flex_timescale(timestamp) as timescale,
  sum(critical) as critical,
```

```

sum(high) as high,
sum(medium) as medium,
sum(low) as low,
sum(info) as info
from
###(select $flex_timestamp as timestamp, sum(case when severity = 'critical' then 1 else 0
end) as critical, sum(case when severity = 'high' then 1 else 0 end) as high, sum(case when
severity = 'medium' then 1 else 0 end) as medium, sum(case when severity in ('notice',
'low') then 1 else 0 end) as low, sum(case when severity = 'info' or severity = 'debug' then
1 else 0 end) as info from $log where $filter group by timestamp /*SkipSTART*/order by
timestamp desc/*SkipEND*/)### t group by timescale order by timescale

```

Dataset Name	Description	Log Category
Important-Intrusions-Timeline-By-Severity	Threat intrusions timeline by severity	attack

```

select
$flex_timescale(timestamp) as timescale,
sum(critical) as critical,
sum(high) as high,
sum(medium) as medium,
sum(low) as low,
sum(info) as info
from
###(select $flex_timestamp as timestamp, sum(case when severity = 'critical' then 1 else 0
end) as critical, sum(case when severity = 'high' then 1 else 0 end) as high, sum(case when
severity = 'medium' then 1 else 0 end) as medium, sum(case when severity in ('notice',
'low') then 1 else 0 end) as low, sum(case when severity = 'info' or severity = 'debug' then
1 else 0 end) as info from $log where $filter group by timestamp /*SkipSTART*/order by
timestamp desc/*SkipEND*/)### t group by timescale order by timescale

```

Dataset Name	Description	Log Category
Top-Intrusions-By-Types	Threat top intrusions by types	attack

```

select
vuln_type,
count(*) as totalnum
from
$log t1
left join (
select
name,
cve,
vuln_type
from
ips_mdata
) t2 on t1.attack = t2.name
where
$filter
and vuln_type is not null
group by
vuln_type
order by
totalnum desc

```

Dataset Name	Description	Log Category
Critical-Severity-Intrusions	Threat critical severity intrusions	attack

```

select
  attack,
  attackid,
  cve,
  vuln_type,
  count(*) as totalnum
from
  $log t1
  left join (
    select
      name,
      cve,
      vuln_type
    from
      ips_mdata
  ) t2 on t1.attack = t2.name
where
  $filter
  and t1.severity = '& #039;critical' and nullifna(attack) is not null group by attack,
  attackid, cve, vuln_type order by totalnum desc

```

Dataset Name	Description	Log Category
High-Severity-Intrusions	Threat high severity intrusions	attack

```

select
  attack,
  attackid,
  vuln_type,
  cve,
  count(*) as totalnum
from
  $log t1
  left join (
    select
      name,
      cve,
      vuln_type
    from
      ips_mdata
  ) t2 on t1.attack = t2.name
where
  $filter
  and t1.severity = '& #039;high' and nullifna(attack) is not null group by attack, attackid,
  vuln_type, cve order by totalnum desc

```

Dataset Name	Description	Log Category
Medium-Severity-Intrusions	Threat medium severity intrusions	attack

```

select
  attack,

```



```

    vuln_type,
    cve,
    count(*) as totalnum
from
    $log t1
    left join (
        select
            name,
            cve,
            vuln_type
        from
            ips_mdata
    ) t2 on t1.attack = t2.name
where
    $filter
    and t1.severity = & #039;medium' and nullifna(attack) is not null group by attack, vuln_
type, cve order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Intrusion-Victims	Threat top intrusion victims	attack

```

select
    victim,
    sum(cri_num) as critical,
    sum(high_num) as high,
    sum(med_num) as medium,
    sum(cri_num + high_num + med_num) as totalnum
from
    ###(select dstip as victim, sum((case when severity='critical' then 1 else 0 end)) as cri_
num, sum(case when severity='high' then 1 else 0 end) as high_num, sum(case when
severity='medium' then 1 else 0 end) as med_num from $log where $filter and severity in
('critical', 'high', 'medium') group by victim)### t group by victim order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Intrusion-Sources	Threat top intrusion sources	attack

```

select
    source,
    sum(cri_num) as critical,
    sum(high_num) as high,
    sum(med_num) as medium,
    sum(cri_num + high_num + med_num) as totalnum
from
    ###(select srcip as source, sum(case when severity='critical' then 1 else 0 end) as cri_
num, sum(case when severity='high' then 1 else 0 end) as high_num, sum(case when
severity='medium' then 1 else 0 end) as med_num from $log where $filter and severity in
('critical', 'high', 'medium') group by source)### t group by source order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Blocked-Intrusions	Threat top blocked intrusions	attack

```

select
    attack,

```

```

    attackid,
    (
        case when t1.severity =& #039;critical' then 'Critical' when t1.severity='high' then
'High' when t1.severity='medium' then 'Medium' when t1.severity='low' then 'Low' when
t1.severity='info' then 'Info' end) as severity_name, count(*) as totalnum, vuln_type, (case
when t1.severity='critical' then 0 when t1.severity='high' then 1 when t1.severity='medium'
then 2 when t1.severity='low' then 3 when t1.severity='info' then 4 else 5 end) as severity_
number from $log t1 left join (select name, cve, vuln_type from ips_mdata) t2 on
t1.attack=t2.name where $filter and nullifna(attack) is not null and action not in
('detected', 'pass_session') group by attack, attackid, t1.severity, vuln_type order by
severity_number, totalnum desc

```

Dataset Name	Description	Log Category
Top-Monitored-Intrusions	Threat top monitored intrusions	attack

```

select
    attack,
    attackid,
    (
        case when t1.severity =& #039;critical' then 'Critical' when t1.severity='high' then
'High' when t1.severity='medium' then 'Medium' when t1.severity='low' then 'Low' when
t1.severity='info' then 'Info' end) as severity_name, count(*) as totalnum, vuln_type, (case
when t1.severity='critical' then 0 when t1.severity='high' then 1 when t1.severity='medium'
then 2 when t1.severity='low' then 3 when t1.severity='info' then 4 else 5 end) as severity_
number from $log t1 left join (select name, cve, vuln_type from ips_mdata) t2 on
t1.attack=t2.name where $filter and nullifna(attack) is not null and action in ('detected',
'pass_session') group by attack, attackid, t1.severity, vuln_type order by severity_number,
totalnum desc

```

Dataset Name	Description	Log Category
Attacks-Over-HTTP-HTTPSs	Threat attacks over HTTP HTTPSs	attack

```

select
    attack,
    attackid,
    (
        case when severity =& #039;critical' then 'Critical' when severity='high' then 'High'
when severity='medium' then 'Medium' when severity='low' then 'Low' when severity='info'
then 'Info' end) as severity, count(*) as totalnum, (case when severity='critical' then 0
when severity='high' then 1 when severity='medium' then 2 when severity='low' then 3 when
severity='info' then 4 else 5 end) as severity_number from $log where $filter and severity
in ('critical', 'high', 'medium') and upper(service) in ('HTTP', 'HTTPS') group by attack,
attackid, severity, severity_number order by severity_number, totalnum desc

```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OffWire	Default access point detection summary by status off-wire	event

```

select
    (
        case apstatus when 1 then & #039;rogue' when 2 then 'accepted' when 3 then 'suppressed'
else 'others' end) as ap_full_status, count(*) as totalnum from (select apstatus, bssid,
ssid from ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter and

```

```
apstatus is not null and apstatus!=0 and bssid is not null and onwire='no' and logid_to_int
(logid) in (43527, 43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582,
43583, 43584, 43585) group by apstatus, bssid, ssid order by subtotal desc)### t group by
apstatus, bssid, ssid) t group by ap_full_status order by totalnum desc
```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OffWire_table	Default access point detection summary by status off-wire	event

```
select
(
case apstatus when 1 then & #039;rogue' when 2 then 'accepted' when 3 then 'suppressed'
else 'others' end) as ap_full_status, count(*) as totalnum from (select apstatus, bssid,
ssid from ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter and
apstatus is not null and apstatus!=0 and bssid is not null and onwire='no' and logid_to_int
(logid) in (43527, 43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582,
43583, 43584, 43585) group by apstatus, bssid, ssid order by subtotal desc)### t group by
apstatus, bssid, ssid) t group by ap_full_status order by totalnum desc
```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OnWire	Default access point detection summary by status on-wire	event

```
select
(
case apstatus when 1 then & #039;rogue' when 2 then 'accepted' when 3 then 'suppressed'
else 'others' end) as ap_full_status, count(*) as totalnum from (select apstatus, bssid,
ssid from ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter and
apstatus is not null and apstatus!=0 and bssid is not null and onwire='yes' and logid_to_int
(logid) in (43527, 43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582,
43583, 43584, 43585) group by apstatus, bssid, ssid order by subtotal desc)### t group by
apstatus, bssid, ssid) t group by ap_full_status order by totalnum desc
```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OnWire_table	Default access point detection summary by status on-wire	event

```
select
(
case apstatus when 1 then & #039;rogue' when 2 then 'accepted' when 3 then 'suppressed'
else 'others' end) as ap_full_status, count(*) as totalnum from (select apstatus, bssid,
ssid from ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter and
apstatus is not null and apstatus!=0 and bssid is not null and onwire='yes' and logid_to_int
(logid) in (43527, 43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582,
43583, 43584, 43585) group by apstatus, bssid, ssid order by subtotal desc)### t group by
apstatus, bssid, ssid) t group by ap_full_status order by totalnum desc
```

Dataset Name	Description	Log Category
default-Managed-AP-Summary	Default managed access point summary	event

```
select
(
```

```

case when (
    action like & #039;%join%' and logid_to_int(logid) in (43522, 43551)) then
'Authorized' else 'Unauthorized' end) as ap_status, count(*) as totalnum from $log where
$filter and logid_to_int(logid) in (43522, 43551) group by ap_status order by totalnum desc

```

Dataset Name	Description	Log Category
default-Managed-AP-Summary_table	Default managed access point summary	event

```

select
(
    case when (
        action like & #039;%join%' and logid_to_int(logid) in (43522, 43551)) then
'Authorized' else 'Unauthorized' end) as ap_status, count(*) as totalnum from $log where
$filter and logid_to_int(logid) in (43522, 43551) group by ap_status order by totalnum desc

```

Dataset Name	Description	Log Category
default-Unclassified-AP-Summary	Default unclassified access point summary	event

```

select
(
    case onwire when & #039;no' then 'off-wire' when 'yes' then 'on-wire' else 'others' end)
as ap_status, count(*) as totalnum from ###(select onwire, ssid, bssid, count(*) as subtotal
from $log where $filter and apstatus=0 and bssid is not null and logid_to_int(logid) in
(43521, 43525, 43527, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582, 43583, 43584,
43585) group by onwire, ssid, bssid order by subtotal desc)### t group by ap_status order by
totalnum desc

```

Dataset Name	Description	Log Category
default-Unclassified-AP-Summary_table	Default unclassified access point summary	event

```

select
(
    case onwire when & #039;no' then 'off-wire' when 'yes' then 'on-wire' else 'others' end)
as ap_status, count(*) as totalnum from ###(select onwire, ssid, bssid, count(*) as subtotal
from $log where $filter and apstatus=0 and bssid is not null and logid_to_int(logid) in
(43521, 43525, 43527, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582, 43583, 43584,
43585) group by onwire, ssid, bssid order by subtotal desc)### t group by ap_status order by
totalnum desc

```

Dataset Name	Description	Log Category
default-selected-AP-Details-OffWire	Default selected access point details off-wire	event

```

select
(
    case apstatus when 0 then & #039;unclassified' when 1 then 'rogue' when 2 then
'accepted' when 3 then 'suppressed' else 'others' end) as ap_full_status, devid, vd, ssid,
bssid, manuf, rssi, channel, radioband, from_dtime(min(dtime)) as first_seen, from_dtime(max
(dtime)) as last_seen, detectionmethod, itime, onwire as on_wire from $log where $filter and
apstatus is not null and bssid is not null and onwire='no' and logid_to_int(logid) in
(43521, 43563, 43564, 43565, 43566, 43569, 43570, 43571) group by ap_full_status, devid, vd,
ssid, bssid, manuf, rssi, channel, radioband, detectionmethod, itime, onwire,apstatus

```

Dataset Name	Description	Log Category
default-selected-AP-Details-OnWire	Default selected access point details on-wire	event

```
select
(
case apstatus when 0 then & #039;unclassified' when 1 then 'rogue' when 2 then
'accepted' when 3 then 'suppressed' else 'others' end) as ap_full_status, devid, vd, ssid,
bssid, manuf, rssi, channel, radioband, from_dtime(min(dtime)) as first_seen, from_dtime(max
(dtime)) as last_seen, detectionmethod, itime, onwire as on_wire from $log where $filter and
apstatus is not null and bssid is not null and onwire='yes' and logid_to_int(logid) in
(43521, 43563, 43564, 43565, 43566, 43569, 43570, 43571) group by ap_full_status, devid, vd,
ssid, bssid, manuf, rssi, channel, radioband, detectionmethod, itime, onwire, apstatus
```

Dataset Name	Description	Log Category
event-Wireless-Client-Details	Event wireless client details	event

```
drop
table if exists rpt_tmptbl_1; create temporary table rpt_tmptbl_1 as
select
ip,
lmac,
sn,
ssid,
channel,
radioband,
min(first) as first,
max(last) as last
from
###(select ip, lower(mac) as lmac, sn, ssid, channel, radioband, min(dtime) as first, max
(dtime) as last from $log-event where $filter and ip is not null and mac is not null and sn
is not null and ssid is not null group by ip, lmac, sn, ssid, channel, radioband order by
ip)### t group by ip, lmac, sn, ssid, channel, radioband; select user_src, ip, lmac, sn,
ssid, channel, radioband, from_dtime(first) as first_seen, from_dtime(last) as last_seen,
cast(volume as decimal(18,2)) as bandwidth from (select * from rpt_tmptbl_1 inner join
(select user_src, srcip, sum(volume) as volume from ###(select coalesce(nullifna('user'),
nullifna('unauthuser'), ipstr('srcip')) as user_src, srcip, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as volume from $log-traffic where $filter-time and (logflag&1>0)
and srcip is not null group by user_src, srcip having sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0))>0 order by volume desc)### t group by user_src, srcip order by user_src,
srcip) t on rpt_tmptbl_1.ip = t.srcip) t order by volume desc
```

Dataset Name	Description	Log Category
event-Wireless-Accepted-Offwire	Event wireless accepted off-wire	event

```
select
& #039;accepted' as ap_full_status, devid, vd, ssid, bssid, manuf, channel, radioband,
from_dtime(max(last_seen)) as last_seen, detectionmethod, snclosest, 'no' as on_wire from
###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest,
onwire, logid, apstatus, max(dtime) as last_seen from $log where $filter and bssid is not
null and logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570,
43571) group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
snclosest, onwire, logid, apstatus order by last_seen desc)### t where apstatus=2 and
```

```
onwire='no' group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
snclosest order by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Accepted-Onwire	Event wireless accepted on-wire	event

```
select
  & #039;accepted' as ap_full_status, devid, vd, ssid, bssid, manuf, channel, radioband,
from_dtime(max(last_seen)) as last_seen, detectionmethod, snclosest, 'yes' as on_wire from
###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest,
onwire, apstatus, max(dtime) as last_seen from $log where $filter and bssid is not null and
logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571) group
by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest, onwire,
apstatus order by last_seen desc)### t where apstatus=2 and onwire='yes' group by devid, vd,
ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Rogue-Offwire	Event wireless rogue off-wire	event

```
select
  & #039;rogue' as ap_full_status, devid, vd, ssid, bssid, manuf, channel, radioband, from_
dtime(max(last_seen)) as last_seen, detectionmethod, snclosest, 'no' as on_wire from ###
(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest,
onwire, logid, apstatus, max(dtime) as last_seen from $log where $filter and bssid is not
null and logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570,
43571) group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
snclosest, onwire, logid, apstatus order by last_seen desc)### t where apstatus=1 and
onwire='no' group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
snclosest order by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Rogue-Onwire	Event wireless rogue on-wire	event

```
select
  & #039;rogue' as ap_full_status, devid, vd, ssid, bssid, manuf, channel, radioband, from_
dtime(max(last_seen)) as last_seen, detectionmethod, snclosest, 'yes' as on_wire from ###
(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest,
onwire, apstatus, max(dtime) as last_seen from $log where $filter and bssid is not null and
logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571) group
by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest, onwire,
apstatus order by last_seen desc)### t where apstatus=1 and onwire='yes' group by devid, vd,
ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Suppressed-Offwire	Event wireless suppressed off-wire	event

```
select
  & #039;suppressed' as ap_full_status, devid, vd, ssid, bssid, manuf, channel, radioband,
from_dtime(max(last_seen)) as last_seen, detectionmethod, snclosest, 'no' as on_wire from
###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest,
onwire, logid, apstatus, max(dtime) as last_seen from $log where $filter and bssid is not
null and logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570,
```

```
43571) group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
snclosest, onwire, logid, apstatus order by last_seen desc)### t where apstatus=3 and
onwire='no' group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
snclosest order by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Suppressed-Onwire	Event wireless suppressed on-wire	event

```
select
  & #039;suppressed' as ap_full_status, devid, vd, ssid, bssid, manuf, channel, radioband,
from_dtime(max(last_seen)) as last_seen, detectionmethod, snclosest, 'yes' as on_wire from
###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest,
onwire, apstatus, max(dtime) as last_seen from $log where $filter and bssid is not null and
logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571) group
by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest, onwire,
apstatus order by last_seen desc)### t where apstatus=3 and onwire='yes' group by devid, vd,
ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Unclassified-Offwire	Event wireless unclassified off-wire	event

```
select
  & #039;unclassified' as ap_full_status, devid, vd, ssid, bssid, manuf, channel, radioband,
from_dtime(max(last_seen)) as last_seen, detectionmethod, snclosest, 'no' as on_wire from
###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest,
onwire, logid, apstatus, max(dtime) as last_seen from $log where $filter and bssid is not
null and logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570,
43571) group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
snclosest, onwire, logid, apstatus order by last_seen desc)### t where apstatus=0 and
onwire='no' group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
snclosest order by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Unclassified-Onwire	Event wireless unclassified on-wire	event

```
select
  & #039;unclassified' as ap_full_status, devid, vd, ssid, bssid, manuf, channel, radioband,
from_dtime(max(last_seen)) as last_seen, detectionmethod, snclosest, 'yes' as on_wire from
###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest,
onwire, apstatus, max(dtime) as last_seen from $log where $filter and bssid is not null and
logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571) group
by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest, onwire,
apstatus order by last_seen desc)### t where apstatus=0 and onwire='yes' group by devid, vd,
ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order by last_seen desc
```

Dataset Name	Description	Log Category
default-Top-IPSEC-Vpn-Dial-Up-User-By-Bandwidth	Default top IPsec VPN dial up user by bandwidth usage	event

```
select
  coalesce(
    xauthuser_agg,
```

```

        user_agg,
        ipstr('remip`)
    ) as user_src,
from_dtime(
    min(s_time)
) as start_time,
sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in,
sum(traffic_out) as traffic_out
from
(
    select
        devid,
        vd,
        string_agg(
            distinct xauthuser_agg,
            & #039; ' ) as xauthuser_agg, string_agg(distinct user_agg, ' ' ) as user_agg, remip,
tunnelid, min(s_time) as s_time, max(e_time) as e_time, (case when min(s_time)=max(e_time)
then max(max_traffic_in)+max(max_traffic_out) else max(max_traffic_in)-min(min_traffic_
in)+max(max_traffic_out)-min(min_traffic_out) end) as bandwidth, (case when min(s_time)=max
(e_time) then max(max_traffic_in) else max(max_traffic_in)-min(min_traffic_in) end) as
traffic_in, (case when min(s_time)=max(e_time) then max(max_traffic_out) else max(max_
traffic_out)-min(min_traffic_out) end) as traffic_out from ###(select devid, vd, remip,
nullifna('xauthuser`) as xauthuser_agg, nullifna('user`) as user_agg, tunnelid, min(coalesce
(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, max(coalesce(duration,0)) as max_
duration, min(coalesce(duration,0)) as min_duration, min(coalesce(sentbyte, 0)) as min_
traffic_out, min(coalesce(rcvbyte, 0)) as min_traffic_in, max(coalesce(sentbyte, 0)) as
max_traffic_out, max(coalesce(rcvbyte, 0)) as max_traffic_in from $log where $filter and
subtype='vpn' and tunneltype like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0')
and action in ('tunnel-stats', 'tunnel-down', 'tunnel-up') and tunnelid is not null and
tunnelid!=0 group by devid, vd, remip, xauthuser_agg, user_agg, tunnelid order by
tunnelid)### t group by devid, vd, remip, tunnelid) tt group by user_src having sum
(bandwidth)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
default-Top-Sources-Of-SSL-VPN-Tunnels-By-Bandwidth	Default top sources of SSL VPN tunnels by bandwidth usage	event

```

select
    remip as remote_ip,
    sum(bandwidth) as bandwidth
from
(
    select
        devid,
        vd,
        remip,
        tunnelid,
        (
            case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_
in)- min(min_traffic_in) end
        ) as traffic_in,
        (
            case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end

```



```

    ) as traffic_out,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out)
else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out)
end
    ) as bandwidth
from
    ###(select $flex_timestamp as timestamp, devid, vd, remip, tunnelid, (case when
tunneltype like 'ipsec%' then 'ipsec' else tunneltype end) as t_type, (case when
action='tunnel-up' then 1 else 0 end) as tunnelup, max(coalesce(sentbyte, 0)) as max_
traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in, min(coalesce(sentbyte, 0)) as
min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, min(coalesce(dtime, 0)) as s_
time, max(coalesce(dtime, 0)) as e_time from $log where $filter and subtype='vpn' and
(tunneltype like 'ipsec%' or tunneltype like 'ssl%') and action in ('tunnel-up','tunnel-
stats', 'tunnel-down') and tunnelid is not null and tunnelid!=0 group by timestamp, devid,
vd, remip, t_type, tunnelid, action /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t
where t_type like 'ssl%' group by devid, vd, remip, tunnelid) tt group by remote_ip having
sum(traffic_in+traffic_out)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
webfilter-Web-Activity-Summary-By-Requests	Webfilter web activity summary by requests	webfilter

```

select
    $flex_timescale(timestamp) as hodex,
    sum(allowed_request) as allowed_request,
    sum(blocked_request) as blocked_request
from
    ###(select $flex_timestamp as timestamp, sum(case when action!='blocked' then 1 else 0
end) as allowed_request, sum(case when action='blocked' then 1 else 0 end) as blocked_
request from $log where $filter and (eventtype is null or logver>=502000000) group by
timestamp /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t group by hodex order by
hodex

```

Dataset Name	Description	Log Category
traffic-Browsing-Time-Summary	Traffic browsing time summary	traffic

```

select
    $flex_timescale(timestamp) as hodex,
    cast(
        ebtr_value(
            ebtr_agg_flat(browsetime),
            null,
            $timespan
        )/ 60.0 as decimal(18, 2)
    ) as browsetime
from
    ###(select $flex_timestamp as timestamp, ebtr_agg_flat($browse_time) as browsetime from
$log where $filter and (logflag&1>0) and $browse_time is not null group by timestamp
/*SkipSTART*/order by timestamp desc/*SkipEND*/)### t group by hodex order by hodex

```

Dataset Name	Description	Log Category
webfilter-Top-Web-Users-By-Blocked-Requests	Webfilter top web users by blocked requests	webfilter

```
select
  user_src,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as requests
from $log where $filter and (eventtype is null or logver>=502000000) and coalesce(nullifna
(`user`), ipstr(`srcip`)) is not null and action='blocked' group by user_src
/*SkipSTART*/order by requests desc/*SkipEND*/)### t group by user_src order by requests
desc
```

Dataset Name	Description	Log Category
webfilter-Top-Web-Users-By-Allowed-Requests	Webfilter top web users by allowed requests	webfilter

```
select
  user_src,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as requests
from $log where $filter and (eventtype is null or logver>=502000000) and coalesce(nullifna
(`user`), ipstr(`srcip`)) is not null and action!='blocked' group by user_src
/*SkipSTART*/order by requests desc/*SkipEND*/)### t group by user_src order by requests
desc
```

Dataset Name	Description	Log Category
traffic-Top-Web-Users-By-Browsing-Time	Traffic top web users by browsing time	traffic

```
select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select user_src, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from (select coalesce
(nullifna(`user`), ipstr(`srcip`)) as user_src, ebtr_agg_flat($browse_time) as browsetime,
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as
traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and $browse_
time is not null group by user_src) t group by user_src /*SkipSTART*/order by ebtr_value
(ebtr_agg_flat(browsetime), null, null) desc/*SkipEND*/)### t group by user_src order by
browsetime desc
```

Dataset Name	Description	Log Category
webfilter-Top-Blocked-Web-Sites-By-Requests	Webfilter top blocked web sites by requests	webfilter

```
select
    domain,
    catdesc,
    sum(requests) as requests
from
    ###(select hostname as domain, catdesc, count(*) as requests from $log where $filter and
    (eventtype is null or logver>=502000000) and hostname is not null and catdesc is not null
    and action='blocked' group by domain, catdesc /*SkipSTART*/order by requests
    desc/*SkipEND*/)### t group by domain, catdesc order by requests desc
```

Dataset Name	Description	Log Category
webfilter-Top-Allowed-Web-Sites-By-Requests	Webfilter top allowed web sites by requests	webfilter

```
select
    domain,
    string_agg(
        distinct catdesc,
        & #039;;, ' ) as agg_catdesc, sum(requests) as requests from ###(select hostname as
    domain, catdesc, count(*) as requests from $log where $filter and (eventtype is null or
    logver>=502000000) and hostname is not null and catdesc is not null and action!='blocked'
    group by domain, catdesc /*SkipSTART*/order by requests desc/*SkipEND*/)### t group by
    domain order by requests desc
```

Dataset Name	Description	Log Category
webfilter-Top-Video-Streaming-Websites-By-Bandwidth	Webfilter top video streaming websites by bandwidth usage	webfilter

```
select
    domain,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
    ###(select coalesce(nullifna(root_domain(hostname)), 'other') as domain, sum(coalesce
    (sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in,
    sum(coalesce(sentbyte, 0)) as traffic_out from $log-traffic where $filter and (logflag&l>0)
    and (countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or
    utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter'))))
    and catdesc in ('Streaming Media and Download') group by domain having sum(coalesce
    (sentbyte, 0)+coalesce(rcvdbyte, 0))>0 /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t
    group by domain order by bandwidth desc
```

Dataset Name	Description	Log Category
webfilter-Top-Blocked-Web-Categories	Webfilter top blocked web categories	webfilter

```
select
  catdesc,
  sum(requests) as requests
from
  ###(select catdesc, count(*) as requests from $log-webfilter where $filter and (eventtype
  is null or logver>=502000000) and catdesc is not null and action='blocked' group by catdesc
/*SkipSTART*/order by requests desc/*SkipEND*/)### t group by catdesc order by requests desc
```

Dataset Name	Description	Log Category
webfilter-Top-Allowed-Web-Categories	Webfilter top allowed web categories	webfilter

```
select
  catdesc,
  sum(requests) as requests
from
  ###(select catdesc, count(*) as requests from $log-webfilter where $filter and (eventtype
  is null or logver>=502000000) and catdesc is not null and action!='blocked' group by catdesc
/*SkipSTART*/order by requests desc/*SkipEND*/)### t group by catdesc order by requests desc
```

Dataset Name	Description	Log Category
traffic-Top-50-Sites-By-Browsing-Time	Traffic top sites by browsing time	traffic

```
select
  hostname,
  string_agg(
    distinct catdesc,
    & #039;; ' ) as agg_catdesc, ebtr_value(ebtr_agg_flat(browsetime), null, $timespan) as
  browsetime, sum(bandwidth) as bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as
  traffic_out from ###(select hostname, catdesc, ebtr_agg_flat(browsetime) as browsetime, sum
  (bandwidth) as bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out
  from (select hostname, catdesc, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
  (sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in,
  sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and (logflag&l>0) and
  hostname is not null and $browse_time is not null group by hostname, catdesc) t group by
  hostname, catdesc /*SkipSTART*/order by ebtr_value(ebtr_agg_flat(browsetime), null, null)
  desc/*SkipEND*/)### t group by hostname order by browsetime desc
```

Dataset Name	Description	Log Category
traffic-Top-10-Categories-By-Browsing-Time	Traffic top category by browsing time	traffic

```
select
  catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as bandwidth
  from (select catdesc, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce(sentbyte,
  0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and (logflag&l>0) and catdesc
```

```
is not null and $browse_time is not null group by catdesc) t group by catdesc
/*SkipSTART*/order by ebtr_value(ebtr_agg_flat(browsetime), null, null) desc/*SkipEND*/)###
t group by catdesc order by browsetime desc
```

Dataset Name	Description	Log Category
traffic-Top-Destination-Countries-By-Browsing-Time	Traffic top destination countries by browsing time	traffic

```
select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select dstcountry, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from (select
dstcountry, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce(sentbyte, 0))+coalesce
(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce
(sentbyte, 0)) as traffic_out from $log where $filter and (logflag&1>0) and $browse_time is
not null group by dstcountry) t group by dstcountry /*SkipSTART*/order by ebtr_value(ebtr_
agg_flat(browsetime), null, null) desc/*SkipEND*/)### t group by dstcountry order by
browsetime desc
```

Dataset Name	Description	Log Category
webfilter-Top-Search-Phrases	Webfilter top search phrases	webfilter

```
select
  keyword,
  count(*) as requests
from
  $log
where
  $filter
  and keyword is not null
group by
  keyword
order by
  requests desc
```

Dataset Name	Description	Log Category
Top-10-Users-Browsing-Time	Estimated browsing time	traffic

```
select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
```

```

    ) as browsetime
from
    ###(select user_src, ebtr_agg_flat(browsetime) as browsetime from (select coalesce
    (nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ebtr_agg_flat
    ($browse_time) as browsetime from $log where $filter and (logflag&1>0) and $browse_time is
    not null group by user_src) t group by user_src order by ebtr_value(ebtr_agg_flat
    (browsetime), null, null) desc)### t group by user_src order by browsetime desc

```

Dataset Name	Description	Log Category
Estimated-Browsing-Time	Estimated browsing time	traffic

```

select
    user_src,
    ebtr_value(
        ebtr_agg_flat(browsetime),
        null,
        $timespan
    ) as browsetime
from
    ###(select user_src, ebtr_agg_flat(browsetime) as browsetime from (select coalesce
    (nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ebtr_agg_flat
    ($browse_time) as browsetime from $log where $filter and (logflag&1>0) and $browse_time is
    not null group by user_src) t group by user_src order by ebtr_value(ebtr_agg_flat
    (browsetime), null, null) desc)### t group by user_src order by browsetime desc

```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Bandwidth	Top access point by bandwidth usage	traffic

```

select
    ap_srcintf,
    sum(bandwidth) as bandwidth
from
    (
        select
            coalesce(ap, srcintf) as ap_srcintf,
            sum(bandwidth) as bandwidth
        from
            ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
            src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna
            (`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as
            osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte,
            0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter
            and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap,
            srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal
            desc/*SkipEND*/)### t group by ap_srcintf having sum(bandwidth)>0 union all select ap as ap_
            srcintf, sum(bandwidth) as bandwidth from ###(select $flex_timestamp as timestamp, stamac,
            stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentdelta, 0)) as
            sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce
            (rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr
            (`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order
            by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over (partition by stamac order
            by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is
            not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req',
            'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by

```

```
bandwidth desc/*SkipEND*/)### t group by ap having sum(bandwidth)>0) t group by ap_srcintf
order by bandwidth desc
```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Client	Top access point by client	traffic

```
select
  ap_srcintf as srcintf,
  count(distinct srcmac) as totalnum
from
  (
    select
      coalesce(ap, srcintf) as ap_srcintf,
      srcmac
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna
(`srcname`), `srcmac`) as hostname_mac, max(srswversion) as srswversion, max(osname) as
osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter
and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap,
srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal
desc/*SkipEND*/)### t where srcmac is not null group by ap_srcintf, srcmac union all (select
ap as ap_srcintf, stamac as srcmac from ###(select $flex_timestamp as timestamp, stamac,
stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentdelta, 0)) as
sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce
(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr
(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order
by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over (partition by stamac order
by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is
not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req',
'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by
bandwidth desc/*SkipEND*/)### t where stamac is not null group by ap, stamac)) t group by
srcintf order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Top-SSID-By-Bandwidth	Top SSIDs by bandwidth usage	traffic

```
select
  srcssid,
  sum(bandwidth) as bandwidth
from
  (
    select
      srcssid,
      sum(bandwidth) as bandwidth
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna
(`srcname`), `srcmac`) as hostname_mac, max(srswversion) as srswversion, max(osname) as
osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter
and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap,
srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal
```

```
desc/*SkipEND*/)### t where srcssid is not null group by srcssid having sum(bandwidth)>0
union all select ssid as srcssid, sum(bandwidth) as bandwidth from ###(select $flex_
timestamp as timestamp, stamac, stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum
(coalesce(sentdelta, 0)) as sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum
(coalesce(sentdelta, 0)+coalesce(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap,
ssid, coalesce(`user`, ipstr(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over
(partition by stamac order by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over
(partition by stamac order by itime) as rcvddelta from $log-event where $filter and
subtype='wireless' and stamac is not null and ssid is not null and action in ('sta-wl-
bridge-traffic-stats', 'reassoc-req', 'assoc-req')) as t group by timestamp, stamac, ap,
ssid, user_src /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t group by ssid having
sum(bandwidth)>0) t group by srcssid order by bandwidth desc
```

Dataset Name	Description	Log Category
wifi-Top-SSID-By-Client	Top SSIDs by client	traffic

```
select
  srcssid,
  count(distinct srcmac) as totalnum
from
  (
    select
      srcssid,
      srcmac
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna
(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as
osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter
and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap,
srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal
desc/*SkipEND*/)### t where srcmac is not null group by srcssid, srcmac union all select
ssid as srcssid, stamac as srcmac from ###(select $flex_timestamp as timestamp, stamac,
stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentdelta, 0)) as
sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce
(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr
(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order
by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over (partition by stamac order
by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is
not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req',
'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by
bandwidth desc/*SkipEND*/)### t where stamac is not null group by ssid, stamac) t where
srcssid is not null group by srcssid order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Top-App-By-Bandwidth	Top WiFi applications by bandwidth usage	traffic

```
select
  appid,
  app,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
```



```

from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and (
        srcssid is not null
        or dstssid is not null
    )
    and nullifna(app) is not null
group by
    appid,
    app
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-Client-By-Bandwidth	Top WiFi client by bandwidth usage	traffic

```

select
    client,
    sum(bandwidth) as bandwidth
from
    (
        select
            (
                coalesce(
                    hostname_mac,
                    & #039;unknown') || ' (' || get_devtype(srcswversion, osname, devtype) || ', ' ||
coalesce(osname, '') || (case when srcswversion is null then '' else ' ' || srcswversion
end) || ')') as client, sum(bandwidth) as bandwidth from ###(select coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ap, srcintf, srcssid, srcssid
as ssid, srcmac, srcmac as stamac, coalesce(nullifna(`srcname`), `srcmac`) as hostname_mac,
max(srcswversion) as srcswversion, max(osname) as osname, max(osversion) as osversion, max
(devtype) as devtype, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, count
(*) as subtotal from $log-traffic where $filter and (logflag&1>0) and (srcssid is not null
or dstssid is not null) group by user_src, ap, srcintf, srcssid, srcmac, hostname_mac
/*SkipSTART*/order by bandwidth desc, subtotal desc/*SkipEND*/)### t group by client having
sum(bandwidth)>0 union all select (coalesce(stamac, 'unknown')) as client, sum(bandwidth) as
bandwidth from ###(select $flex_timestamp as timestamp, stamac, stamac as srcmac, ap, ssid,
ssid as srcssid, user_src, sum(coalesce(sentdelta, 0)) as sentdelta, sum(coalesce(rcvddelta,
0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce(rcvddelta, 0)) as bandwidth from
(select itime, stamac, ap, ssid, coalesce(`user`, ipstr(`srcip`)) as user_src, sentbyte-lag
(coalesce(sentbyte, 0)) over (partition by stamac order by itime) as sentdelta, rcvbyte-lag
(coalesce(rcvbyte, 0)) over (partition by stamac order by itime) as rcvddelta from $log-
event where $filter and subtype='wireless' and stamac is not null and ssid is not null and
action in ('sta-wl-bridge-traffic-stats', 'reassoc-req', 'assoc-req')) as t group by
timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t

```

group by client having sum(bandwidth) > 0) t where client is not null group by client order by bandwidth desc

Dataset Name	Description	Log Category
wifi-Top-OS-By-Bandwidth	Top WiFi os by bandwidth usage	traffic

```
select
(
  coalesce(
    osname,
    & #039;unknown') || ' ' || coalesce(srcswversion, '')) as os, sum(bandwidth) as
bandwidth from ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce
(nullifna(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max
(osname) as osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic
where $filter and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by
user_src, ap, srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc,
subtotal desc/*SkipEND*/)### t group by os having sum(bandwidth)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
wifi-Top-OS-By-WiFi-Client	Top WiFi os by WiFi client	traffic

```
select
(
  coalesce(
    osname,
    & #039;unknown') || ' ' || coalesce(osversion, '')) as os, count(distinct srcmac) as
totalnum from ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce
(nullifna(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max
(osname) as osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic
where $filter and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by
user_src, ap, srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc,
subtotal desc/*SkipEND*/)### t where srcmac is not null group by os order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Top-Device-By-Bandwidth	Top WiFi device by bandwidth usage	traffic

```
select
  get_devtype(srcswversion, osname, devtype) as devtype_new,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna
(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as
osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter
and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap,
srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal
desc/*SkipEND*/)### t where devtype is not null group by devtype_new having sum(bandwidth)>0
order by bandwidth desc
```

Dataset Name	Description	Log Category
wifi-Top-Device-By-Client	Top WiFi device by client	traffic

```
select
  devtype_new,
  count(distinct srcmac) as totalnum
from
  (
    select
      get_devtype(srcswversion, osname, devtype) as devtype_new,
      srcmac
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap, srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal desc/*SkipEND*/)### t where srcmac is not null) t where devtype_new is not null group by devtype_new order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Overall-Traffic	WiFi overall traffic	traffic

```
select
  sum(bandwidth) as bandwidth
from
  (
    select
      sum(bandwidth) as bandwidth
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap, srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal desc/*SkipEND*/)### t group by srcssid union all select sum(bandwidth) as bandwidth from ### (select $flex_timestamp as timestamp, stamac, stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentedelta, 0)) as sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentedelta, 0)+coalesce(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over (partition by stamac order by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req', 'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t) t
```

Dataset Name	Description	Log Category
wifi-Num-Distinct-Client	WiFi num distinct client	traffic

```

select
  count(distinct srcmac) as totalnum
from
  (
    select
      srcmac
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap, srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal desc/*SkipEND*/)### t where srcmac is not null group by srcmac union all select stamac as srcmac from ###(select $flex_timestamp as timestamp, stamac, stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentdelta, 0)) as sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over (partition by stamac order by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req', 'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t where stamac is not null group by stamac) t

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Bandwidth-and-Sessions	Top subnets by application bandwidth	traffic

```

select
  ip_subnet(`srcip`) as subnet,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  subnet
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0

```

```
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
Top30-Subnets-by-Application-Bandwidth	Top applications by bandwidth	traffic

```
select
  ip_subnet(`srcip`) as subnet,
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  subnet,
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
Top30-Subnets-by-Application-Sessions	Top applications by sessions	traffic

```
select
  ip_subnet(`srcip`) as subnet,
  app_group_name(app) as app_group,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  subnet,
  app_group
order by
  sessions desc
```

Dataset Name	Description	Log Category
Top30-Subnets-by-Website-Bandwidth	Top websites and web category by bandwidth	traffic

```
select
  subnet,
  website,
  sum(bandwidth) as bandwidth
from
  ###(select ip_subnet(`srcip`) as subnet, hostname as website, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and hostname is not
null and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and
(hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-
block', 'script-filter')))) group by subnet, website order by bandwidth desc)### t group by
subnet, website order by bandwidth desc
```

Dataset Name	Description	Log Category
Top30-Subnets-by-Website-Hits	Top websites and web category by sessions	webfilter

```
select
  subnet,
  website,
  sum(hits) as hits
from
  ###(select ip_subnet(`srcip`) as subnet, hostname as website, count(*) as hits from $log
where $filter and hostname is not null and (eventtype is null or logver>=502000000) group by
subnet, website order by hits desc)### t group by subnet, website order by hits desc
```

Dataset Name	Description	Log Category
Top30-Subnets-with-Top10-User-by-Bandwidth	Top users by bandwidth	traffic

```
select
  ip_subnet(`srcip`) as subnet,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and srcip is not null
group by
  subnet,
  user_src
having
```

```

sum(
  coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
)> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top30-Subnets-with-Top10-User-by-Sessions	Top users by sessions	traffic

```

select
  ip_subnet(`srcip`) as subnet,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  subnet,
  user_src
order by
  sessions desc

```

Dataset Name	Description	Log Category
app-Top-20-Category-and-Applications-by-Bandwidth	Top category and applications by bandwidth usage	traffic

```

select
  appcat,
  app,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  appcat,
  app
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )

```

```

    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
app-Top-20-Category-and-Applications-by-Session	Top category and applications by session	traffic

```

select
    appcat,
    app,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
group by
    appcat,
    app
order by
    sessions desc

```

Dataset Name	Description	Log Category
app-Top-500-Allowed-Applications-by-Bandwidth	Top allowed applications by bandwidth usage	traffic

```

select
    from_itime(itime) as timestamp,
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    appcat,
    app,
    coalesce(
        root_domain(hostname),
        ipstr(dstip)
    ) as destination,
    sum(
        coalesce(`sentbyte`, 0)+ coalesce(`rcvdbyte`, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and action in (

```



```
& #039;accept', 'close', 'timeout') group by timestamp, user_src, appcat, app,
destination order by bandwidth desc
```

Dataset Name	Description	Log Category
app-Top-500-Blocked-Applications-by-Session	Top blocked applications by session	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  appcat,
  app,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and action in (
    & #039;deny', 'blocked', 'reset', 'dropped') group by user_src, appcat, app order by
sessions desc
```

Dataset Name	Description	Log Category
web-Detailed-Website-Browsing-Log	Web detailed website browsing log	traffic

```
select
  from_dtime(dtime) as timestamp,
  catdesc,
  hostname as website,
  status,
  sum(bandwidth) as bandwidth
from
  ###(select dtime, catdesc, hostname, cast(utmaction as text) as status, sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and
hostname is not null and (logflag&1>0) and (countweb>0 or ((logver is null or
logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-word',
'web-content', 'command-block', 'script-filter')))) group by dtime, catdesc, hostname,
utmaction order by dtime desc)### t group by dtime, catdesc, website, status order by dtime
desc
```

Dataset Name	Description	Log Category
web-Hourly-Category-and-Website-Hits-Action	Web hourly category and website hits action	webfilter

```
select
  hod,
  website,
  sum(hits) as hits
```

```

from
  ###(select $hour_of_day as hod, (hostname || ' (' || coalesce(`catdesc`, 'Unknown') ||
  ')') as website , count(*) as hits from $log where $filter and hostname is not null and
  (eventtype is null or logver>=502000000) group by hod, website order by hod, hits desc)### t
group by hod, website order by hod, hits desc

```

Dataset Name	Description	Log Category
web-Top-20-Category-and-Websites-by-Bandwidth	Web top category and websites by bandwidth usage	traffic

```

select
  website,
  catdesc,
  sum(bandwidth) as bandwidth
from
  ###(select hostname as website, catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))
  as bandwidth from $log-traffic where $filter and hostname is not null and (logflag&1>0) and
  (countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent
  in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by
  website, catdesc order by bandwidth desc)### t group by website, catdesc order by bandwidth
  desc

```

Dataset Name	Description	Log Category
web-Top-20-Category-and-Websites-by-Session	Web top category and websites by session	webfilter

```

select
  website,
  catdesc,
  sum(sessions) as hits
from
  ###(select hostname as website, catdesc, count(*) as sessions from $log where $filter and
  hostname is not null and (eventtype is null or logver>=502000000) group by hostname, catdesc
  order by sessions desc)### t group by website, catdesc order by hits desc

```

Dataset Name	Description	Log Category
web-Top-500-Website-Sessions-by-Bandwidth	Web top website sessions by bandwidth usage	traffic

```

select
  from_dtime(dtime) as timestamp,
  user_src,
  website,
  catdesc,
  cast(
    sum(dura)/ 60 as decimal(18, 2)
  ) as dura,
  sum(bandwidth) as bandwidth
from
  ###(select dtime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, hostname as website, catdesc, sum(coalesce(duration, 0)) as dura, sum(coalesce
  (sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and hostname is
  not null and (logflag&1>0) and action in ('accept','close','timeout') group by dtime, user_

```

```
src, website, catdesc having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by
bandwidth desc)### t group by dtime, user_src, website, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
web-Top-500-User-Visted-Websites-by-Bandwidth	Web top user visted websites by bandwidth usage	traffic

```
select
  website,
  catdesc,
  sum(bandwidth) as bandwidth
from
  ###(select hostname as website, catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))
as bandwidth from $log-traffic where $filter and hostname is not null and (logflag&1>0) and
(countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent
in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by
hostname, catdesc having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by
bandwidth desc)### t group by website, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
web-Top-500-User-Visted-Websites-by-Session	Web top user visted websites by session	webfilter

```
select
  website,
  catdesc,
  sum(sessions) as sessions
from
  ###(select hostname as website, catdesc, count(*) as sessions from $log where $filter and
hostname is not null and (eventtype is null or logver>=502000000) group by hostname, catdesc
order by sessions desc)### t group by website, catdesc order by sessions desc
```

Dataset Name	Description	Log Category
fct-Installed-Feature-Summary	Installed Feature Summary	fct-event

```
select
  subtype,
  count(distinct fctuid) as totalnum
from
  ###(select uid as fctuid, regexp_replace(os, '\\(build.*', '') as os_short, fctver,
subtype, fgtserial, max(case when msg like 'Compliance rules%applied' then 1 else 0 end) as
compliance_flag from $log where $filter and subtype != 'admin' group by uid, os_short,
fctver, subtype, fgtserial)### t where subtype is not null group by subtype order by
totalnum desc
```

Dataset Name	Description	Log Category
fct-Device-by-Operating-System	Device by OS	fct-event

```
select
  os_short as os,
  count(distinct fctuid) as totalnum
from
```

```
###(select uid as fctuid, regexp_replace(os, '\\(build.*', '') as os_short, fctver,
subtype, fgtserial, max(case when msg like 'Compliance rules%applied' then 1 else 0 end) as
compliance_flag from $log where $filter and subtype != 'admin' group by uid, os_short,
fctver, subtype, fgtserial)### t where os_short is not null group by os order by totalnum
desc
```

Dataset Name	Description	Log Category
fct-Installed-FortiClient-Version	FortiClient Version	fct-event

```
select
  fctver as fctver_short,
  count(distinct fctuid) as totalnum
from
  ###(select uid as fctuid, regexp_replace(os, '\\(build.*', '') as os_short, fctver,
subtype, fgtserial, max(case when msg like 'Compliance rules%applied' then 1 else 0 end) as
compliance_flag from $log where $filter and subtype != 'admin' group by uid, os_short,
fctver, subtype, fgtserial)### t where fctver is not null group by fctver order by totalnum
desc
```

Dataset Name	Description	Log Category
fct-Endpoint-Profile-Deployment	Endpoint Profile Deployment	fct-event

```
select
  profile,
  count(distinct fctuid) as totalnum
from
  ###(select uid as fctuid, coalesce(nullifna(usingpolicy), 'No Profile') as profile from
$log where $filter group by uid, profile)### t group by profile order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Client-Summary	Client Summary	fct-event

```
select
  hostname,
  deviceip,
  os_short as os,
  profile,
  fctver,
  from_itime(
    max(itime)
  ) as last_seen
from
  ###(select hostname, deviceip, regexp_replace(os, '\\(build.*', '') as os_short, nullifna
(usingpolicy) as profile, fctver, max(itime) as itime from $log where $filter and os is not
null group by hostname, deviceip, os_short, profile, fctver order by itime desc)### t group
by hostname, deviceip, os, profile, fctver order by last_seen desc
```

Dataset Name	Description	Log Category
fct-Total-Threats-Found	Total Threats Found	fct-traffic

```
select
  utmevent_s as utmevent,
```

```

count(distinct threat) as totalnum
from
    ###(select coalesce(nullifna(lower(utmevent)), 'unknown') as utmevent_s, threat from $log
where $filter and threat is not null and utmaction='blocked' group by utmevent_s, threat)###
t group by utmevent order by totalnum desc

```

Dataset Name	Description	Log Category
fct-Top10-AV-Threats-Detected	Top AV Threats Detected	fct-traffic

```

select
    threat,
    sum(totalnum) as totalnum
from
    (
        (
            select
                threat,
                sum(totalnum) as totalnum
            from
                ###(select threat, count(*) as totalnum from $log-fct-traffic where $filter and
threat is not null and lower(utmevent)='antivirus' group by threat order by totalnum
desc)### t group by threat) union all (select threat, sum(totalnum) as totalnum from ###
(select virus as threat, count(*) as totalnum from $log-fct-event where $filter and virus is
not null group by threat order by totalnum desc)### t group by threat)) t group by threat
order by totalnum desc

```

Dataset Name	Description	Log Category
fct-Top10-Infected-Devices-with-Botnet	Top Infected Devices with Botnet	fct-traffic

```

select
    hostname,
    count(*) as totalnum
from
    $log
where
    $filter
    and hostname is not null
    and lower(utmevent) in (
        & #039;webfilter', 'appfirewall') and lower(threat) like '%botnet%' group by hostname
order by totalnum desc

```

Dataset Name	Description	Log Category
fct-Top10-Infected-Devices-with-Virus-Malware	Top Infected Devices with Virus Malware	fct-traffic

```

select
    hostname,
    sum(totalnum) as totalnum
from
    (
        (
            select

```

```

        hostname,
        sum(totalnum) as totalnum
    from
        ###(select hostname, count(*) as totalnum from $log-fct-traffic where $filter and
hostname is not null and lower(utmevent) in ('antivirus', 'antimalware') group by hostname
order by totalnum desc)### t group by hostname) union all (select hostname, sum(totalnum) as
totalnum from ###(select hostname, count(*) as totalnum from $log-fct-event where $filter
and hostname is not null and virus is not null group by hostname order by totalnum desc)###
t group by hostname)) t group by hostname order by totalnum desc

```

Dataset Name	Description	Log Category
fct-All-Antivirus-Antimalware-Detections	All Antivirus and Antimalware Detections	fct-traffic

```

select
    threat,
    hostname,
    hostuser,
    utmaction,
    from_dtime(
        max(dtime)
    ) as last_seen
from
    (
        (
            select
                threat,
                hostname,
                hostuser,
                utmaction,
                max(dtime) as dtime
            from
                ###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser,
utmaction, max(dtime) as dtime from $log-fct-traffic where $filter and lower(utmevent) in
('antivirus', 'antimalware') group by threat, hostname, hostuser, utmaction order by
threat)### t group by threat, hostname, hostuser, utmaction) union all (select threat,
hostname, hostuser, utmaction, max(dtime) as dtime from ###(select virus as threat,
hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, action as utmaction, max(dtime)
as dtime from $log-fct-event where $filter and (logflag is null or logflag&8=0) and virus is
not null group by threat, hostname, hostuser, utmaction order by threat)### t group by
threat, hostname, hostuser, utmaction)) t group by threat, hostname, hostuser, utmaction
order by threat

```

Dataset Name	Description	Log Category
fct-Web-Filter-Violations	Web Filter Violations	fct-traffic

```

select
    hostuser,
    hostname,
    string_agg(
        distinct remotename,
        & #039;;') as remotename, utmaction, sum(total) as totalnum, from_dtime(max(dtime)) as
last_seen from ###(select remotename, hostname, coalesce(nullifna(`user`), 'Unknown') as
hostuser, utmaction, count(*) as total, max(dtime) as dtime from $log where $filter and

```

```
lower(utmevent)='webfilter' and utmaction='blocked' group by remotename, hostname, hostuser,
utmaction order by total desc)### t group by hostuser, hostname, utmaction order by totalnum
desc
```

Dataset Name	Description	Log Category
fct-Application-Firewall	Application Firewall	fct-traffic

```
select
  threat,
  hostname,
  hostuser,
  utmaction,
  from_dtime(
    max(dtime)
  ) as last_seen
from
  ###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, utmaction,
max(dtime) as dtime from $log where $filter and lower(utmevent)='appfirewall' and
utmaction='blocked' group by threat, hostname, hostuser, utmaction order by dtime desc)###
t1 left join app_mdata t2 on t1.threat=t2.name group by threat, risk, hostname, hostuser,
utmaction order by risk desc
```

Dataset Name	Description	Log Category
fct-Errors-and-Alerts	Errors and Alerts	fct-event

```
select
  msg,
  hostname,
  hostuser,
  from_dtime(
    max(dtime)
  ) as last_seen
from
  ###(select msg, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, max(dtime) as
dtime from $log where $filter and level in ('error', 'alert') group by msg, hostname,
hostuser order by dtime desc)### t group by msg, hostname, hostuser order by last_seen desc
```

Dataset Name	Description	Log Category
fct-Threats-by-Top-Devices	Threats by Top Devices	fct-traffic

```
select
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and hostname is not null
  and utmevent is not null
  and utmaction =& #039;blocked' group by hostname order by totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Device-Vulnerabilities	Vulnerabilities Detected by User/Device	fct-netscan

```
select
  vulnseverity,
  (
    CASE vulnseverity WHEN & #039;Critical' THEN 5 WHEN 'High' THEN 4 WHEN 'Medium' THEN 3
    WHEN 'Info' THEN 2 WHEN 'Low' THEN 1 ELSE 0 END) as severity_number, count(distinct
    vulnname) as vuln_num from ###(select vulnseverity, devid, vulnname from $log where $filter
    and nullifna(vulnseverity) is not null and nullifna(vulnname) is not null group by
    vulnseverity, vulnname, devid)### t group by vulnseverity order by severity_number desc
```

Dataset Name	Description	Log Category
fct-vuln-Category-Type-Vulnerabilities	Vulnerabilities Detected by Category Type	fct-netscan

```
select
  vulncat,
  count(distinct vulnname) as totalnum
from
  ###(select vulncat, vulnname from $log where $filter and nullifna(vulncat) is not null and
  nullifna(vulnname) is not null group by vulncat, vulnname)### t group by vulncat order by
  totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerabilities-by-OS	Forticlient Vulnerabilities by OS	fct-netscan

```
select
  os,
  count(distinct vulnname) as totalnum
from
  ###(select os, vulnname from $log where $filter and nullifna(os) is not null and nullifna
  (vulnname) is not null group by os, vulnname)### t group by os order by totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerabilities-by-Risk-Level	Number Vulnerability by Device and Risk Level	fct-netscan

```
select
  vulnseverity,
  (
    case when vulnseverity =& #039;Critical' then 5 when vulnseverity='High' then 4 when
    vulnseverity='Medium' then 3 when vulnseverity='Low' then 2 when vulnseverity='Info' then 1
    else 0 end) as severity_number, count(distinct vulnname) as vuln_num, count(distinct devid)
    as dev_num from ###(select vulnseverity, devid, vulnname from $log where $filter and
    nullifna(vulnseverity) is not null and nullifna(vulnname) is not null and nullifna(devid) is
    not null group by vulnseverity, vulnname, devid)### t group by vulnseverity order by dev_num
    desc, severity_number desc
```

Dataset Name	Description	Log Category
fct-vuln-Device-by-Risk-Level	Number Vulnerability by Device and Risk Level	fct-netscan


```
select
  vulnseverity,
  (
    case when vulnseverity = & #039;Critical' then 5 when vulnseverity='High' then 4 when
vulnseverity='Medium' then 3 when vulnseverity='Low' then 2 when vulnseverity='Info' then 1
else 0 end) as severity_number, count(distinct vulnname) as vuln_num, count(distinct devid)
as dev_num from ###(select vulnseverity, devid, vulnname from $log where $filter and
nullifna(vulnseverity) is not null and nullifna(vulnname) is not null and nullifna(devid) is
not null group by vulnseverity, vulnname, devid)### t group by vulnseverity order by dev_num
desc, severity_number desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerability-Trend	Vulnerability Trend	fct-netscan

```
select
  $flex_timescale(timestamp) as hindex,
  count(distinct vulnname) as total_num
from
  ###(select $flex_timestamp as timestamp, vulnname from $log where $filter and nullifna
(vulnname) is not null group by timestamp, vulnname order by timestamp desc)### t group by
hindex order by hindex
```

Dataset Name	Description	Log Category
fct-vuln-Details-by-Risk-Level-Device	Vulnerability Details for Each Risk Level by Device	fct-netscan

```
select
  hostname,
  os,
  vulnseverity,
  count(distinct vulnname) as vuln_num,
  count(distinct products) as products,
  count(distinct cve_id) as cve_count
from
  ###(select hostname, os, vulnname, vulnseverity, vulnid from $log where $filter and
vulnname is not null and vulnseverity is not null and hostname is not null group by
hostname, os, vulnname, vulnseverity, vulnid)### t1 left join fct_mdata t2 on
t1.vulnid=t2.vid::int group by hostname, os, vulnseverity order by vuln_num desc, hostname
```

Dataset Name	Description	Log Category
fct-vuln-Details-by-Device-User	Vulnerability Details by Device User	fct-netscan

```
select
  hostname,
  (
    & #039;<div>' || vulnname || '</div>') as vulnname, vulnseverity, vulncat, string_agg
(distinct products, ',') as products, string_agg(distinct cve_id, ',') as cve_list, ('<a
href=' || String_agg(DISTINCT vendor_link, ',') || '>Remediation Info</a>') as vendor_link
from ###(select hostname, vulnname, vulnseverity, vulncat, vulnid from $log where $filter
and vulnname is not null and hostname is not null group by hostname, vulnname, vulnseverity,
vulncat, vulnid)### t1 inner join fct_mdata t2 on t1.vulnid=t2.vid::int group by hostname,
vulnname, vulnseverity, vulncat order by hostname
```

Dataset Name	Description	Log Category
fct-vuln-Remediation-by-Device	Remediate The Vulnerability Found on Device	fct-netscan

```
select
  hostname,
  (
    & #039;<div>' || vulnname || '</div>') as vulnname, vulnseverity, string_agg(distinct
  vendor_link, ',') as vendor_link from ###(select hostname, vulnname, vulnseverity, vulnid
  from $log where $filter and vulnname is not null and hostname is not null group by hostname,
  vulnname, vulnseverity, vulnid)### t1 inner join fct_mdata t2 on t1.vulnid=t2.vid::int group
  by hostname, vulnname, vulnseverity order by vulnseverity, hostname
```

Dataset Name	Description	Log Category
fct-vuln-Remediation-by-Vulnerability	Remediation by Vulnerability	fct-netscan

```
select
  (
    & #039;<b>' || vulnname || '</b><br><br>' || 'Description<br><div style=word-
  break:normal>' || description || '</div><br><br>' || 'Affected Products<br>' || products
  || '<br><br>' || 'Impact<br>' || impact || '<br><br>' || 'Recommended Actions<br>' ||
  vendor_link || '<br><br><br>') as remediation from ###(select devid, vulnname,
  vulnseverity, (case vulnseverity when 'low' then 1 when 'info' then 2 when 'medium' then 3
  when 'high' then 4 when 'critical' then 5 else 0 end) as severity_level, vulnid from $log
  where $filter and vulnname is not null group by devid, vulnname, vulnseverity, severity_
  level, vulnid order by severity_level)### t1 inner join fct_mdata t2 on
  t1.vulnid=t2.vid::int group by remediation order by remediation
```

Dataset Name	Description	Log Category
fct-vuln-Top-30-Targeted-High-Risk-Vulnerabilities	Top 30 Targeted High Risk Vulnerabilities	fct-netscan

```
select
  t3.cve_id,
  score,
  string_agg(
    distinct products,
    & #039;;,') as products, ('<a href=' || String_agg(vendor_link, ',') || '>Mitigation
  Infomation</a>') as vendor_link from ###(select vulnid from $log where $filter group by
  vulnid)### t1 inner join fct_mdata t2 on t2.vid=t1.vulnid::text inner join fct_cve_score t3
  on strpos(t2.cve_id, t3.cve_id) > 0 group by t3.cve_id, score order by score desc, t3.cve_id
```

Dataset Name	Description	Log Category
fct-Endpoints-by-FortiGate	Endpoints by FortiGate	fct-event

```
select
  fgtserial,
  count(distinct fctuid) as totalnum
from
  ###(select uid as fctuid, regexp_replace(os, '\\(build.*', '') as os_short, fctver,
  subtype, fgtserial, max(case when msg like 'Compliance rules%applied' then 1 else 0 end) as
  compliance_flag from $log where $filter and subtype != 'admin' group by uid, os_short,
```

```
fctver, subtype, fgtserial)### t where fgtserial is not null group by fgtserial order by
totalnum desc
```

Dataset Name	Description	Log Category
fct-Top-Malware-Detections	Top Infected Devices with Malware	fct-traffic

```
select
  hostname,
  fctuid,
  sum(totalnum) as totalnum
from
  (
    (
      select
        hostname,
        fctuid,
        sum(totalnum) as totalnum
      from
        ###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser,
        utmaction, max(dtime) as dtime, uid as fctuid, count(*) as totalnum from $log-fct-traffic
        where $filter and lower(utmevent) in ('antivirus', 'antimalware') group by threat, hostname,
        hostuser, utmaction, uid order by threat)### t group by hostname, fctuid) union all (select
        hostname, fctuid, sum(totalnum) as totalnum from ###(select virus as threat, hostname,
        coalesce(nullifna(`user`), 'Unknown') as hostuser, action as utmaction, max(dtime) as dtime,
        uid as fctuid, count(*) as totalnum from $log-fct-event where $filter and (logflag is null
        or logflag&8=0) and virus is not null group by threat, hostname, hostuser, utmaction, uid
        order by threat)### t group by hostname, fctuid)) t group by hostname, fctuid order by
        totalnum desc
```

Dataset Name	Description	Log Category
fct-Top10-Malware-Detections	Top 10 Infected Devices with Malware	fct-traffic

```
select
  threat,
  hostname,
  hostuser,
  utmaction,
  fctuid,
  sum(totalnum) as totalnum
from
  (
    (
      select
        threat,
        hostname,
        hostuser,
        utmaction,
        fctuid,
        sum(totalnum) as totalnum
      from
        ###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser,
        utmaction, max(dtime) as dtime, uid as fctuid, count(*) as totalnum from $log-fct-traffic
        where $filter and lower(utmevent) in ('antivirus', 'antimalware') group by threat, hostname,
        hostuser, utmaction, uid order by threat)### t group by threat, hostname, hostuser,
```

```
utmaction, fctuid) union all (select threat, hostname, hostuser, utmaction, fctuid, sum
(totalnum) as totalnum from ###(select virus as threat, hostname, coalesce(nullifna(`user`),
'Unknown') as hostuser, action as utmaction, max(dtime) as dtime, uid as fctuid, count(*) as
totalnum from $log-fct-event where $filter and (logflag is null or logflag&8=0) and virus is
not null group by threat, hostname, hostuser, utmaction, uid order by threat)### t group by
threat, hostname, hostuser, utmaction, fctuid)) t where utmaction != 'pass' group by threat,
hostname, hostuser, utmaction, fctuid order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Devices-with-Botnet	Infected Devices with Botnet	fct-traffic

```
select
  threat,
  hostname,
  coalesce(
    nullifna(`user`),
    & #039;Unknown') as hostuser, utmaction, uid as fctuid, count(*) as totalnum from $log
where $filter and hostname is not null and lower(utmevent) in ('webfilter', 'appfirewall')
and lower(threat) like '%botnet%' group by threat, hostname, hostuser, utmaction, fctuid
order by totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerability-by-Hostname	Vulnerability Details for Each Risk Level by Device	fct-netscan

```
select
  hostname,
  os,
  vulnseverity,
  count(distinct vulnname) as vuln_num,
  count(distinct products) as products,
  count(distinct cve_id) as cve_count
from
  ###(select hostname, os, vulnname, vulnseverity, vulnid from $log where $filter and
vulnname is not null and vulnseverity is not null and hostname is not null group by
hostname, os, vulnname, vulnseverity, vulnid)### t1 left join fct_mdata t2 on
t1.vulnid=t2.vid::int group by hostname, os, vulnseverity order by vuln_num desc, hostname
```

Dataset Name	Description	Log Category
fct-Users-With-Web-Violations	Web Filter Violations	fct-traffic

```
select
  hostuser,
  hostname,
  string_agg(
    distinct remotename,
    & #039;;') as remotename, utmaction, sum(total) as totalnum, from_dtime(max(dtime)) as
last_seen from ###(select remotename, hostname, coalesce(nullifna(`user`), 'Unknown') as
hostuser, utmaction, count(*) as total, max(dtime) as dtime from $log where $filter and
lower(utmevent)='webfilter' and utmaction='blocked' group by remotename, hostname, hostuser,
utmaction order by total desc)### t group by hostuser, hostname, utmaction order by totalnum
desc
```

Dataset Name	Description	Log Category
fct-Compliance-by-FortiGate	FortiClinet Compliance by FortiGate Enforcing	fct-event

```
select
  fgtserial,
  count(distinct fctuid) as totalnum
from
  (
    select
      fgtserial,
      fctuid,
      max(compliance_flag) as compliance_flag
    from
      ###(select uid as fctuid, regexp_replace(os, '\\(build.*', '') as os_short, fctver,
      subtype, fgtserial, max(case when msg like 'Compliance rules%applied' then 1 else 0 end) as
      compliance_flag from $log where $filter and subtype != 'admin' group by uid, os_short,
      fctver, subtype, fgtserial)### tt group by fgtserial, fctuid) t where compliance_flag = 1
    group by fgtserial order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Compliance-Status	Number of FortiClinets by Compliance Status	fct-event

```
select
  (
    case compliance_flag when 1 then & #039;Compliant' else 'Non-Compliant' end) as
    compliance, count(distinct fctuid) as totalnum from (select fctuid, max(compliance_flag) as
    compliance_flag from ###(select uid as fctuid, regexp_replace(os, '\\(build.*', '') as os_
    short, fctver, subtype, fgtserial, max(case when msg like 'Compliance rules%applied' then 1
    else 0 end) as compliance_flag from $log where $filter and subtype != 'admin' group by uid,
    os_short, fctver, subtype, fgtserial)### tt group by fctuid) t group by compliance order by
    totalnum desc
```

Dataset Name	Description	Log Category
fct-Non-Compliant-Endpoints	Non-compliant Endpoints	fct-event

```
select
  t1.fgtserial,
  t3.srcintf,
  t2.epname as hostname,
  t2.mac,
  & #039;Non-Compliant' as status from (select fgtserial, fctuid, max(compliance_flag) as
  compliance_flag from ###(select uid as fctuid, regexp_replace(os, '\\(build.*', '') as os_
  short, fctver, subtype, fgtserial, max(case when msg like 'Compliance rules%applied' then 1
  else 0 end) as compliance_flag from $log where $filter and subtype != 'admin' group by uid,
  os_short, fctver, subtype, fgtserial)### tt group by fgtserial, fctuid) t1 left join $ADOM_
  ENDPOINT t2 on t1.fctuid = t2.fctuid left join $ADOM_EPEU_DEVMAP t3 on t2.epid = t3.epid
  where compliance_flag = 0 group by t1.fctuid, t1.fgtserial, t3.srcintf, t2.epname, t2.mac
```

Dataset Name	Description	Log Category
fct-Traffic-Web-Hits	Web Traffic Trend	fct-traffic

```
select
  $flex_timescale(timestamp) as hindex,
  sum(requests) as requests
from
  ###(select $flex_timestamp as timestamp, count(*) as requests from $log where $filter and
  lower(utmevent)='webfilter' group by timestamp order by timestamp desc)### t group by hindex
order by hindex
```

Dataset Name	Description	Log Category
fct-Traffic-Top-Allowed-Web-Cat	Top Visited Web Categories	fct-traffic

```
select
  category,
  sum(requests) as requests
from
  ###(select fct_webcat(threat) as category, remotename as website, count(*) as requests
  from $log where $filter and direction='outbound' and threat is not null and
  utmaction='passthrough' and lower(utmevent)='webfilter' group by category, website order by
  requests desc)### t group by category order by requests desc
```

Dataset Name	Description	Log Category
fct-Traffic-Top-Allowed-Website	Top Visited Websites	fct-traffic

```
select
  website,
  string_agg(
    distinct category,
    & #039;;, ' ') as agg_category, sum(requests) as requests from ###(select fct_webcat
  (threat) as category, remotename as website, count(*) as requests from $log where $filter
  and direction='outbound' and threat is not null and utmaction='passthrough' and lower
  (utmevent)='webfilter' group by category, website order by requests desc)### t where website
  is not null group by website order by requests desc
```

Dataset Name	Description	Log Category
fct-Traffic-Top-Category-By-Website-Session	Top Web Categories by Website Session	fct-traffic

```
select
  fct_webcat(threat) as category,
  remotename as website,
  count(*) as requests
from
  $log
where
  $filter
  and nullifna(threat) is not null
  and lower(utmevent)='webfilter' group by category, website order by requests desc
```

Dataset Name	Description	Log Category
fct-Traffic-Top-Web-Users-By-Website	Top Web Users by Website	fct-traffic

```

select
  coalesce(
    nullifna(`user`),
    ipstr(`srcip`)
  ) as user_src,
  remotename as website,
  count(*) as requests
from
  $log
where
  $filter
  and direction =& #039;outbound' and remotename is not null and utmaction='passthrough' and
  lower(utmevent)='webfilter' group by user_src, website order by requests desc

```

Dataset Name	Description	Log Category
os-Detect-OS-Count	Detected operation system count	traffic

```

select
  (
    coalesce(
      osname,
      & #039;Unknown')) as os, count(*) as totalnum from $log where $filter and
  (logflag&l>0) group by os order by totalnum desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Sessions-Table	Drilldown top applications by session count	traffic

```

select
  appid,
  app,
  sum(sessions) as sessions
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and nullifna(app) is not null group by appid, app order by
sessions desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Sessions-Bar	Drilldown top applications by session count	traffic

```

select
  appid,
  app,
  sum(sessions) as sessions
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and nullifna(app) is not null group by appid, app order by
sessions desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Bandwidth-Table	Drilldown top applications by bandwidth usage	traffic

```
select
  appid,
  app,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and nullifna(app) is not null group by appid, app having sum
(bandwidth)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Bandwidth-Bar	Drilldown top applications by bandwidth usage	traffic

```
select
  appid,
  app,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and nullifna(app) is not null group by appid, app having sum
(bandwidth)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-Destination-By-Sessions-Table	Drilldown top destination by session count	traffic

```
select
  dstip,
  sum(sessions) as sessions
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and dstip is not null group by dstip order by sessions desc
```

Dataset Name	Description	Log Category
drilldown-Top-Destination-By-Bandwidth-Table	Drilldown top destination by bandwidth usage	traffic

```
select
  dstip,
```



```

sum(bandwidth) as bandwidth
from
###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and dstip is not null group by dstip having sum(bandwidth)>0 order
by bandwidth desc

```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Sessions-Table	Drilldown top user by session count	traffic

```

select
  user_src,
  sum(sessions) as sessions
from
###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and user_src is not null group by user_src order by sessions desc

```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Sessions-Bar	Drilldown top user by session count	traffic

```

select
  user_src,
  sum(sessions) as sessions
from
###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and user_src is not null group by user_src order by sessions desc

```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Bandwidth-Table	Drilldown top user by bandwidth usage	traffic

```

select
  user_src,
  sum(bandwidth) as bandwidth
from
###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and user_src is not null group by user_src having sum(bandwidth)>0
order by bandwidth desc

```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Bandwidth-Bar	Drilldown top user by bandwidth usage	traffic

```

select
  user_src,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&l>0)
group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)###
t where $filter-drilldown and user_src is not null group by user_src having sum(bandwidth)>0
order by bandwidth desc

```

Dataset Name	Description	Log Category
drilldown-Top-Web-User-By-Visit-Table	Drilldown top web user by visit	traffic

```

select
  user_src,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests from $log-traffic where $filter-exclude-var and
(logflag&l>0) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') and hostname is not null group by user_src, hostname order by requests
desc)### union all ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests from $log-webfilter where $filter-exclude-var and (eventtype
is null or logver>=502000000) and hostname is not null group by user_src, hostname order by requests desc)###) t where $filter-drilldown and user_src is not null group by user_src
order by visits desc

```

Dataset Name	Description	Log Category
drilldown-Top-Web-User-By-Visit-Bar	Drilldown top web user by visit	traffic

```

select
  user_src,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests from $log-traffic where $filter-exclude-var and
(logflag&l>0) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') and hostname is not null group by user_src, hostname order by requests
desc)### union all ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests from $log-webfilter where $filter-exclude-var and (eventtype
is null or logver>=502000000) and hostname is not null group by user_src, hostname order by requests desc)###) t where $filter-drilldown and user_src is not null group by user_src
order by visits desc

```

Dataset Name	Description	Log Category
drilldown-Top-Website-By-Request-Table	Drilldown top website by request	traffic

```
select
  hostname,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests from $log-traffic where $filter-exclude-var and (logflag&l>0) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') and hostname is not null group by user_src, hostname order by requests desc)### union all ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests from $log-webfilter where $filter-exclude-var and (eventtype is null or logver>=502000000) and hostname is not null group by user_src, hostname order by requests desc)###) t where $filter-drilldown and hostname is not null group by hostname order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Website-By-Request-Bar	Drilldown top website by request	traffic

```
select
  hostname,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests from $log-traffic where $filter-exclude-var and (logflag&l>0) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') and hostname is not null group by user_src, hostname order by requests desc)### union all ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests from $log-webfilter where $filter-exclude-var and (eventtype is null or logver>=502000000) and hostname is not null group by user_src, hostname order by requests desc)###) t where $filter-drilldown and hostname is not null group by hostname order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Sender-By-Volume	Drilldown top email sender by volume	traffic

```
select
  sender,
  sum(bandwidth) as volume
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and (logflag&l>0) and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in ('general-email-log', 'spamfilter') group by sender, recipient order by requests desc)### union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and eventtype is null group by `from`, `to` order by requests desc)###) t where $filter-drilldown and sender is not null group by sender having sum(bandwidth)>0 order by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Send-Recipient-By-Volume	Drilldown top email send recipient by volume	traffic

```
select
  recipient,
  sum(bandwidth) as volume
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
    (rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and (logflag&1>0)
    and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and
    utmevent in ('general-email-log', 'spamfilter') group by sender, recipient order by requests
    desc)### union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum
    (coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where
    $filter-exclude-var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS',
    '465/tcp') and eventtype is null group by `from`, `to` order by requests desc)###) t where
    $filter-drilldown and recipient is not null group by recipient having sum(bandwidth)>0 order
    by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Sender-By-Count	Drilldown top email sender by count	traffic

```
select
  sender,
  sum(requests) as requests
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
    (rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and (logflag&1>0)
    and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and
    utmevent in ('general-email-log', 'spamfilter') group by sender, recipient order by requests
    desc)### union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum
    (coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where
    $filter-exclude-var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS',
    '465/tcp') and eventtype is null group by `from`, `to` order by requests desc)###) t where
    $filter-drilldown and sender is not null group by sender order by requests desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Send-Recipient-By-Count	Drilldown top email send recipient by count	traffic

```
select
  recipient,
  sum(requests) as requests
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
    (rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and (logflag&1>0)
    and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and
    utmevent in ('general-email-log', 'spamfilter') group by sender, recipient order by requests
    desc)### union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum
    (coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where
```

\$filter-exclude-var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and eventtype is null group by `from`, `to` order by requests desc)###) t where \$filter-drilldown and recipient is not null group by recipient order by requests desc

Dataset Name	Description	Log Category
drilldown-Top-Email-Recipient-By-Volume	Drilldown top email receiver by volume	traffic

```
select
  recipient,
  sum(bandwidth) as volume
from
  (
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0) and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by recipient, sender order by requests desc)### union all ###(select `to` as recipient, `from` as sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-var and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and eventtype is null group by `to`, `from` order by requests desc)###) t where $filter-drilldown and recipient is not null group by recipient having sum(bandwidth)>0 order by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Receive-Sender-By-Volume	Drilldown top email receive sender by volume	traffic

```
select
  sender,
  sum(bandwidth) as volume
from
  (
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0) and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by recipient, sender order by requests desc)### union all ###(select `to` as recipient, `from` as sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-var and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and eventtype is null group by `to`, `from` order by requests desc)###) t where $filter-drilldown and sender is not null group by sender having sum(bandwidth)>0 order by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Recipient-By-Count	Drilldown top email receiver by count	traffic

```
select
  recipient,
  sum(requests) as requests
```

```

from
(
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0) and
service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS',
'993/tcp', 'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter')
group by recipient, sender order by requests desc)### union all ###(select `to` as
recipient, `from` as sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-var and service in
('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s',
'POP3S', '995/tcp') and eventtype is null group by `to`, `from` order by requests desc)###)
t where $filter-drilldown and recipient is not null group by recipient order by requests
desc

```

Dataset Name	Description	Log Category
drilldown-Top-Email-Receive-Sender-By-Count	Drilldown top email receive sender by count	traffic

```

select
    sender,
    sum(requests) as requests
from
(
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0) and
service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS',
'993/tcp', 'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter')
group by recipient, sender order by requests desc)### union all ###(select `to` as
recipient, `from` as sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-var and service in
('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s',
'POP3S', '995/tcp') and eventtype is null group by `to`, `from` order by requests desc)###)
t where $filter-drilldown and sender is not null group by sender order by requests desc

```

Dataset Name	Description	Log Category
drilldown-Top-Attack-Destination	Drilldown top attack dest	attack

```

select
    dstip,
    sum(totalnum) as totalnum
from
    ###(select srcip, dstip, count(*) as totalnum from $log where $filter-exclude-var group by
srcip, dstip order by totalnum desc)### t where $filter-drilldown and dstip is not null
group by dstip order by totalnum desc

```

Dataset Name	Description	Log Category
drilldown-Top-Attack-Source	Drilldown top attack source	attack

```

select
    srcip,
    sum(totalnum) as totalnum
from
    ###(select srcip, dstip, count(*) as totalnum from $log where $filter-exclude-var group by

```

```
srcip, dstip order by totalnum desc)### t where $filter-drilldown and srcip is not null
group by srcip order by totalnum desc
```

Dataset Name	Description	Log Category
drilldown-Top-Attack-List	Drilldown top attack list	attack

```
select
  from_itime(itime) as timestamp,
  attack,
  srcip,
  dstip
from
  ###(select itime, attack, srcip, dstip from $log where $filter-exclude-var order by itime
desc)### t where $filter-drilldown order by timestamp desc
```

Dataset Name	Description	Log Category
drilldown-Top-Virus	UTM top virus	virus

```
select
  virus,
  max(virusid_s) as virusid,
  (
    case when virus like & #039;Riskware%' then 'Spyware' when virus like 'Adware%' then
'Adware' else 'Virus' end) as malware_type, sum(totalnum) as totalnum from ###(select virus,
virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where
$filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not null group
by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by virus,
malware_type order by totalnum desc
```

Dataset Name	Description	Log Category
drilldown-Virus-Detail	Drilldown virus detail	virus

```
select
  from_itime(itime) as timestamp,
  virus,
  user_src,
  dstip,
  hostname,
  recipient
from
  ###(select itime, virus, coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, dstip,
cast(' ' as char) as hostname, cast(' ' as char) as recipient from $log where $filter and
(eventtype is null or logver>=502000000) and nullifna(virus) is not null order by itime
desc)### t where $filter-drilldown order by timestamp desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Blocked-Web-Sites-By-Requests	User drilldown top blocked web sites by requests	webfilter

```
select
  hostname,
  sum(requests) as requests
```

```

from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, action, count
  (*) as requests from $log where $filter and hostname is not null group by user_src,
  hostname, action order by requests desc)### t where $filter-drilldown and action='blocked'
group by hostname order by requests desc

```

Dataset Name	Description	Log Category
user-drilldown-Top-Allowed-Web-Sites-By-Requests	User drilldown top allowed web sites by requests	webfilter

```

select
  hostname,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, action, count
  (*) as requests from $log where $filter and hostname is not null group by user_src,
  hostname, action order by requests desc)### t where $filter-drilldown and action!='blocked'
group by hostname order by requests desc

```

Dataset Name	Description	Log Category
user-drilldown-Top-Blocked-Web-Categories	User drilldown top blocked web categories	webfilter

```

select
  catdesc,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, catdesc, action, count
  (*) as requests from $log where $filter and catdesc is not null group by user_src, catdesc,
  action order by requests desc)### t where $filter-drilldown and action='blocked' group by
  catdesc order by requests desc

```

Dataset Name	Description	Log Category
user-drilldown-Top-Allowed-Web-Categories	User drilldown top allowed web categories	webfilter

```

select
  catdesc,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, catdesc, action, count
  (*) as requests from $log where $filter and catdesc is not null group by user_src, catdesc,
  action order by requests desc)### t where $filter-drilldown and action!='blocked' group by
  catdesc order by requests desc

```

Dataset Name	Description	Log Category
user-drilldown-Top-Attacks	User drilldown top attacks by name	attack

```

select
  attack,
  sum(attack_count) as attack_count
from

```



```
###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, attack, (case when
severity in ('critical', 'high') then 1 else 0 end) as high_severity, count(*) as attack_
count from $log where $filter and nullifna(attack) is not null group by user_src, attack,
high_severity order by attack_count desc)### t where $filter-drilldown group by attack order
by attack_count desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Attacks-High-Severity	User drilldown top attacks high severity	attack

```
select
  attack,
  sum(attack_count) as attack_count
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, attack, (case when
severity in ('critical', 'high') then 1 else 0 end) as high_severity, count(*) as attack_
count from $log where $filter and nullifna(attack) is not null group by user_src, attack,
high_severity order by attack_count desc)### t where $filter-drilldown and high_severity=1
group by attack order by attack_count desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Virus-By-Name	User drilldown top virus	virus

```
select
  virus,
  max(virusid_s) as virusid,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, virusid_to_str
(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where $filter and nullifna
(virus) is not null group by user_src, virus, virusid_s order by totalnum desc)### t where
$filter-drilldown group by virus order by totalnum desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Virus-Receivers-Over-Email	User drilldown top virus receivers over email	virus

```
select
  receiver,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, `to` as receiver, count
(*) as totalnum from $log where $filter and subtype='infected' and (service in ('smtp',
'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') or service in ('pop3', 'POP3',
'110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S',
'995/tcp')) and nullifna(virus) is not null group by user_src, receiver order by totalnum
desc)### t where $filter-drilldown group by receiver order by totalnum desc
```

Dataset Name	Description	Log Category
user-drilldown-Count-Spam-Activity-by-Hour-of-Day	User drilldown count spam activity by hour of day	emailfilter

```
select
  $hour_of_day(timestamp) as hourstamp,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, coalesce(nullifna(`user`), ipstr(`srcip`)) as
  user_src, `from` as mf_sender, `to` as mf_receiver, action, eventtype, count(*) as totalnum
  from $log where $filter group by timestamp, user_src, mf_sender, mf_receiver, action,
  eventtype /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown and
  mf_receiver is not null and action in ('detected', 'blocked') group by hourstamp order by
  hourstamp
```

Dataset Name	Description	Log Category
user-drilldown-Top-Spam-Sources	User drilldown top spam sources	emailfilter

```
select
  mf_sender,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, coalesce(nullifna(`user`), ipstr(`srcip`)) as
  user_src, `from` as mf_sender, `to` as mf_receiver, action, eventtype, count(*) as totalnum
  from $log where $filter group by timestamp, user_src, mf_sender, mf_receiver, action,
  eventtype /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown and
  mf_sender is not null and action in ('detected', 'blocked') group by mf_sender order by
  totalnum desc
```

Dataset Name	Description	Log Category
event-Usage-CPU	Event usage CPU	event

```
select
  $hour_of_day(timestamp) as hourstamp,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 2)
  ) as cpu_avg_usage
from
  ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
  trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
  (itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
  (coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
  as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
  (coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
  (totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
  (coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
  part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
  '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
  transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
  count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
  by timestamp, devid, slot)### t group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
event-Usage-Memory	Event usage memory	event

```
select
  $hour_of_day(timestamp) as hourstamp,
```

```

    cast(
        sum(total_mem)/ sum(count) as decimal(6, 2)
    ) as mem_avg_usage
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by hourstamp order by hourstamp

```

Dataset Name	Description	Log Category
event-Usage-Sessions	Event usage sessions	event

```

select
    $hour_of_day(timestamp) as hourstamp,
    cast(
        sum(totalsession)/ sum(count) as decimal(10, 2)
    ) as sess_avg_usage
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by hourstamp order by hourstamp

```

Dataset Name	Description	Log Category
event-Usage-CPU-Sessions	Event usage CPU sessions	event

```

select
    $hour_of_day(timestamp) as hourstamp,
    cast(
        sum(totalsession)/ sum(count) as decimal(10, 2)
    ) as sess_avg_usage,
    cast(
        sum(total_cpu)/ sum(count) as decimal(6, 2)
    ) as cpu_avg_usage
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_

```

```
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
App-Risk-Top-Users-By-Bandwidth	Top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  srcip,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and srcip is not null
group by
  user_src,
  srcip
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
App-Risk-Top-User-Source-By-Sessions	Application risk top user source by session count	traffic

```

select
  srcip,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and srcip is not null
group by
  srcip,
  user_src
order by
  sessions desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Users-By-Reputation-Scores-Bar	Application risk reputation top users by scores	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(crsscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crsscore is not null
group by
  user_src
having
  sum(crsscore % 65536)> 0
order by
  scores desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Devices-By-Reputation-Scores	Application risk reputation top devices by scores	traffic

```

select
  max(

```

```

        get_devtype(srcswversion, osname, devtype)
    ) as devtype_new,
    coalesce(
        nullifna(`srcname`),
        nullifna(`srcmac`),
        ipstr(`srcip`)
    ) as dev_src,
    sum(crscore % 65536) as scores
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and crscore is not null
group by
    dev_src
having
    sum(crscore % 65536)> 0
order by
    scores desc

```

Dataset Name	Description	Log Category
App-Risk-Application-Usage-By-Category-With-Pie	Application risk application usage by category	traffic

```

select
    appcat,
    sum(bandwidth) as bandwidth
from
    ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as
sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app,
appcat, apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app,
appcat, apprisk order by sessions desc)base### t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null group by appcat order by bandwidth desc

```

Dataset Name	Description	Log Category
App-Risk-App-Usage-by-Category	Application risk application usage by category	traffic

```

select
    appcat,
    sum(bandwidth) as bandwidth
from
    ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as
sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app,
appcat, apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app,

```

```

appcat, apprisk order by sessions desc)base### t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null group by appcat order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-20-Categories-By-Bandwidth	Webfilter categories by bandwidth usage	webfilter

```

select
  catdesc,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from
$log-traffic where $filter and (logflag&1>0) and (countweb>0 or ((logver is null or
logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-word',
'web-content', 'command-block', 'script-filter')))) and catdesc is not null group by catdesc
/*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t group by catdesc order by bandwidth
desc

```

Dataset Name	Description	Log Category
App-Risk-Key-Applications-Crossing-The-Network	Application risk application activity	traffic

```

select
  app_group_name(app) as app_group,
  appcat,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  count(*) as num_session
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app_group,
  appcat
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
App-Risk-Applications-Running-Over-HTTP	Application risk applications running over HTTP	traffic

```

select
  app_group_name(app) as app_group,
  service,
  count(*) as sessions,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )

```

```

    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(app) is not null
    and service in (
        & #039;80/tcp', '443/tcp', 'HTTP', 'HTTPS', 'http', 'https') group by app_group, service
having sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0))>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Web-Sites-Visited-By-Network-Users-Pie-Cha	Application risk web browsing summary category	traffic

```

select
    catdesc,
    sum(num_sess) as num_sess,
    sum(bandwidth) as bandwidth
from
    ###(select catdesc, count(*) as num_sess, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0))
as bandwidth from $log-traffic where $filter and (logflag&1>0) and (countweb>0 or ((logver
is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-
word', 'web-content', 'command-block', 'script-filter')))) and catdesc is not null group by
catdesc order by num_sess desc)### t group by catdesc order by num_sess desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Web-Sites-Visited-By-Network-Users	Application risk web browsing summary category	traffic

```

select
    catdesc,
    sum(num_sess) as num_sess,
    sum(bandwidth) as bandwidth
from
    ###(select catdesc, count(*) as num_sess, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0))
as bandwidth from $log-traffic where $filter and (logflag&1>0) and (countweb>0 or ((logver
is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-
word', 'web-content', 'command-block', 'script-filter')))) and catdesc is not null group by
catdesc order by num_sess desc)### t group by catdesc order by num_sess desc

```

Dataset Name	Description	Log Category
App-Risk-Web-Browsing-Hostname-Category	Application risk web browsing activity hostname category	webfilter

```

select
    domain,
    catdesc,
    sum(visits) as visits
from
    ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, catdesc, count(*) as

```


visits from \$log where \$filter and (eventtype is null or logver>=502000000) and catdesc is not null group by domain, catdesc order by visits desc)### t group by domain, catdesc order by visits desc

Dataset Name	Description	Log Category
Top-Destination-Countries-By-Browsing-Time	Traffic top destination countries by browsing time	traffic

```
select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select dstcountry, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from (select
dstcountry, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce(sentbyte, 0))+coalesce
(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce
(sentbyte, 0)) as traffic_out from $log where $filter and (logflag&l>0) and $browse_time is
not null group by dstcountry) t group by dstcountry /*SkipSTART*/order by ebtr_value(ebtr_
agg_flat(browsetime), null, null) desc/*SkipEND*/)### t group by dstcountry order by
browsetime desc
```

Dataset Name	Description	Log Category
App-Risk-Traffic-Top-Hostnames-By-Browsing-Time	Traffic top domains by browsing time	traffic

```
select
  hostname,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select hostname, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from (select hostname, ebtr_
agg_flat($browse_time) as browsetime, sum(coalesce(sentbyte, 0))+coalesce(rcvdbyte, 0)) as
bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as traffic_
out from $log where $filter and (logflag&l>0) and hostname is not null and $browse_time is
not null group by hostname) t group by hostname /*SkipSTART*/order by ebtr_value(ebtr_agg_
flat(browsetime), null, null) desc/*SkipEND*/)### t group by hostname order by browsetime
desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Threat-Vectors-Crossing-The-Network	Application risk top threat vectors	attack

```
select
  severity,
  count(*) as totalnum
from
  $log
where
  $filter
group by
  severity
order by
  totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Critical-Threat-Vectors-Crossing-The-Network	Application risk top critical threat vectors	attack

```
select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity =& #039;critical' and nullifna(attack) is not null group by  attack,
severity, ref order by totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-High-Threat-Vectors-Crossing-The-Network	Application risk top high threat vectors	attack

```
select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity =& #039;high' and nullifna(attack) is not null group by  attack, severity,
ref order by totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Medium-Threat-Vectors-Crossing-The-Network	Application risk top medium threat vectors	attack

```

select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity =& #039;medium' and nullifna(attack) is not null group by attack, severity,
ref order by totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Low-Threat-Vectors-Crossing-The-Network	Application risk top low threat vectors	attack

```

select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity =& #039;low' and nullifna(attack) is not null group by attack, severity, ref
order by totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Info-Threat-Vectors-Crossing-The-Network	Application risk top info threat vectors	attack

```

select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity =& #039;info' and nullifna(attack) is not null group by attack, severity,
ref order by totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Virus-By-Name	UTM top virus	virus

```

select
  virus,
  max(virusid_s) as virusid,
  (
    case when virus like & #039;Riskware%' then 'Spyware' when virus like 'Adware%' then
'Adware' else 'Virus' end) as malware_type, sum(totalnum) as totalnum from ###(select virus,

```

```
virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where
$filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not null group
by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by virus,
malware_type order by totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Virus-Victim	UTM top virus user	virus

```
select
  user_src,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as totalnum
from $log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is
not null group by user_src /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by
user_src order by totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Data-Loss-Prevention-Type-Events	Application risk DLP UTM event	dlp

```
select
  subtype : :text as utmsubtype,
  count(*) as number
from
  ###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
subtype, srcip, dstip, severity, filename, direction, filesize, (case when
severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
(`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
$filter-drilldown and subtype is not null group by subtype order by number desc
```

Dataset Name	Description	Log Category
App-Risk-Vulnerability-Discovered	Application risk vulnerability discovered	netscan

```
select
  vuln,
  vulnref as ref,
  vulncat,
  severity,
  count(*) as totalnum
from
  $log
where
  $filter
  and vuln is not null
group by
  vuln,
  vulnref,
  vulncat,
  severity
order by
  totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Malware-Discovered	Application risk virus discovered	virus

```
select
  dom,
  sum(totalnum) as totalnum
from
  ###(select $DAY_OF_MONTH as dom, count(*) as totalnum from $log where $filter and nullifna
(virus) is not null and (eventtype is null or logver>=502000000) group by dom order by
totalnum desc)### t group by dom order by totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Breakdown-Of-Risk-Applications	Application risk breakdown of risk applications	traffic

```
select
  unnest(
    string_to_array(
      behavior,
      & #039;;,') as d_behavior, count(*) as number from $log t1 inner join app_mdata t2 on
t1.appid=t2.id where $filter and (logflag&1>0) group by d_behavior order by number desc
```

Dataset Name	Description	Log Category
App-Risk-Number-Of-Applications-By-Risk-Behavior	Application risk number of applications by risk behavior	traffic

```
select
  risk as d_risk,
  unnest(
    string_to_array(
      behavior,
      & #039;;,') as f_behavior, count(*) as number from $log t1 inner join app_mdata t2 on
t1.appid=t2.id where $filter and (logflag&1>0) group by risk, f_behavior order by risk desc,
number desc
```

Dataset Name	Description	Log Category
App-Risk-High-Risk-Application	Application risk high risk application	traffic

```
select
  risk as d_risk,
  behavior as d_behavior,
  t2.id,
  t2.name,
  t2.app_cat,
  t2.technology,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  count(*) as sessions
from
  $log t1
```

```

inner join app_mdata t2 on t1.appid = t2.id
where
  $filter
  and (
    logflag&1>0
  )
  and behavior is not null
group by
  t2.id
order by
  risk desc,
  sessions desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Severe-High-Risk-Application	Severe and high risk applications	traffic

```

select
  appcat,
  count(distinct app) as total_num
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as
sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app,
appcat, apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app,
appcat, apprisk order by sessions desc)base### t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null and apprisk in ('critical', 'high') group by appcat order
by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Threats-Prevention	Threat Prevention	app-ctrl

```

select
  threat_name,
  count(distinct threats) as total_num
from
  (
    ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name, app as threats from
$log-app-ctrl where $filter and lower(appcat)='botnet' group by app)### union all ###(select
cast('Malware & Botnet C&C' as char(32)) as threat_name, virus as threats from $log-virus
where $filter and nullifna(virus) is not null group by virus)### union all ###(select cast
('Malicious & Phishing Sites' as char(32)) as threat_name, hostname as threats from $log-
webfilter where $filter and cat in (26, 61) group by hostname)### union all ###(select cast
('Critical & High Intrusion Attacks' as char(32)) as threat_name, attack as threats from
$log-attack where $filter and severity in ('critical', 'high') group by attack)###) t group
by threat_name order by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Application-Vulnerability	Application vulnerabilities discovered	attack

```

select
  attack,
  attackid,
  vuln_type,
  cve,
  severity_number,
  count(distinct dstip) as victims,
  count(distinct srcip) as sources,
  sum(totalnum) as totalnum
from
  ###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then 5
when t1.severity='high' then 4 when t1.severity='medium' then 3 when t1.severity='low' then
2 when t1.severity='info' then 1 else 0 end) as severity_number, dstip, srcip, count(*) as
totalnum from $log t1 left join (select name, cve, vuln_type from ips_mdata) t2 on
t1.attack=t2.name where $filter and nullifna(attack) is not null and t1.severity is not null
group by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip)### t group by
attack, attackid, vuln_type, severity_number, cve order by severity_number desc, totalnum
desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Breakdown-Of-High-Risk-Application	Severe and high risk applications	traffic

```

select
  appcat,
  count(distinct app) as total_num
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as
sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, eid,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app,
appcat, apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
nullifna(app) is not null group by dvid, srcip, dstip, epid, eid, user_src, appid, app,
appcat, apprisk order by sessions desc)base### t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null and apprisk in ('critical', 'high') group by appcat order
by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-20-High-Risk-Application	Application risk high risk application	traffic

```

select
  risk as d_risk,
  count(distinct user_src) as users,
  id,
  name,
  app_cat,
  technology,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###(select lower(app) as lowapp, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count

```

```
(*) as sessions from $log where $filter and (logflag&1>0) group by lowapp, user_src order by
bandwidth desc)### t1 inner join app_mdata t2 on t1.lowapp=lower(t2.name) where risk>='4'
group by id, name, app_cat, technology, risk order by d_risk desc, sessions desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-High-Risk-Application-Behavioral	Application Behavioral Characteristics	traffic

```
select
  behavior,
  round(
    sum(total_num)* 100 / sum(
      sum(total_num)
    ) over (),
    2
  ) as percentage
from
  (
    ###(select (case when lower(appcat)='botnet' then 'malicious' when lower
(appcat)='remote.access' then 'tunneling' when lower(appcat) in ('storage.backup',
'video/audio') then 'bandwidth-consuming' when lower(appcat)='p2p' then 'peer-to-peer' when
lower(appcat)='proxy' then 'proxy' end) as behavior, sum(sessions) as total_num from ###base
(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid, coalesce(nullifna(`user`),
nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app, appcat, apprisk, sum
(coalesce(sentsdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, count(*)
as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and nullifna(app) is not
null group by dvid, srcip, dstip, epid, euid, user_src, appid, app, appcat, apprisk order by
sessions desc)base### t where lower(appcat) in ('botnet', 'remote.access', 'storage.backup',
'video/audio', 'p2p', 'proxy') and apprisk in ('critical', 'high') group by appcat order by
total_num desc)### union all ###(select 'malicious' as behavior, count(*) as total_num from
$log-attack where $filter and (logflag&16>0) and severity in ('critical', 'high') group by
behavior)###) t where $filter-drilldown group by behavior order by percentage desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Key-Application-Crossing-The-Network	Key Application Crossing The Network	traffic

```
select
  risk as d_risk,
  count(distinct user_src) as users,
  id,
  name,
  app_cat,
  technology,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###(select app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
user_src, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as
sessions from $log where $filter and (logflag&1>0) group by app, user_src order by bandwidth
desc)### t1 inner join app_mdata t2 on t1.app=t2.name group by id, app, app_cat, technology,
risk order by bandwidth desc
```


Dataset Name	Description	Log Category
Apprisk-Ctrl-Risk-Application-Usage-By-Category-With-Pie	Application risk application usage by category	traffic

```
select
  appcat,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as
sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app,
appcat, apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app,
appcat, apprisk order by sessions desc)base### t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null group by appcat order by bandwidth desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Category-Breakdown-By-Bandwidth	Category breakdown of all applications, sorted by bandwidth	traffic

```
select
  appcat,
  count(distinct app) as app_num,
  count(distinct user_src) as user_num,
  sum(bandwidth) as bandwidth,
  sum(sessions) as num_session
from
  ###(select app, appcat, user_src, sum(bandwidth) as bandwidth, sum(sessions) as sessions
from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid, coalesce
(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app, appcat,
apprisk, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app,
appcat, apprisk order by sessions desc)base### t where nullifna(appcat) is not null group by
app, appcat, user_src order by bandwidth desc)### t where $filter-drilldown group by appcat
order by bandwidth desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-Web-Applications-by-Bandwidth	Top 25 Web Categories by Bandwidth	traffic

```
select
  d_risk,
  id,
  name,
  technology,
  count(distinct f_user) as user_num,
  sum(bandwidth) as bandwidth,
  sum(num_session) as num_session
from
```

```
###(select risk as d_risk, t2.id, t2.name, t2.technology, coalesce(nullifna(t1.`user`),
nullifna(t1.`unauthuser`), ipstr(t1.`srcip`)) as f_user, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth, count(*) as num_session from $log t1 inner join app_mdata t2 on
t1.appid=t2.id where $filter and (logflag&1>0) and nullifna(app) is not null and service in
('80/tcp', '443/tcp', 'HTTP', 'HTTPS', 'http', 'https') group by risk, t2.id, t2.name,
t2.technology, f_user)### t group by d_risk, id, name, technology order by bandwidth desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```
select
  catdesc,
  count(distinct f_user) as user_num,
  sum(sessions) as sessions,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
f_user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth
from $log-traffic where $filter and catdesc is not null and (logflag&1>0) and (countweb>0 or
((logver is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter',
'banned-word', 'web-content', 'command-block', 'script-filter')))) group by f_user, catdesc
order by sessions desc)### t group by catdesc order by sessions desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Common-Virus-Botnet-Spyware	Common virus disvocered, the botnet communications and the spyware/adware	traffic

```
select
  virus_s as virus,
  (
    case when lower(appcat)=& #039;botnet' then 'Botnet C&C' else (case when virus_s like
'Riskware%' then 'Spyware' when virus_s like 'Adware%' then 'Adware' else 'Virus' end) end)
as malware_type, appid, app, count(distinct dstip) as victims, count(distinct srcip) as
source, sum(total_num) as total_num from (###(select app as virus_s, appcat, appid, app,
dstip, srcip, count(*) as total_num from $log-traffic where $filter and (logflag&1>0) and
lower(appcat)='botnet' group by virus_s, appcat, appid, dstip, srcip, app order by total_num
desc)### union all ###(select unnest(string_to_array(virus, ',')) as virus_s, appcat, appid,
app, dstip, srcip, count(*) as total_num from $log-traffic where $filter and (logflag&1>0)
and virus is not null group by virus_s, appcat, appid, dstip, srcip, app order by total_num
desc)### union all ###(select attack as virus_s, 'botnet' as appcat, 0 as appid, attack as
app, dstip, srcip, count(*) as total_num from $log-attack where $filter and (logflag&16>0)
group by virus_s, appcat, appid, dstip, srcip, app order by total_num desc)###) t group by
virus, appid, app, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Zero-Day-Detected-On-Network	Zero-day malware detected on the network	traffic

```
select
  virus_s,
  appid,
  app,
```

```

count(distinct dstip) as victims,
count(distinct srcip) as source,
sum(total_num) as total_num
from
###(select unnest(string_to_array(virus, ',')) as virus_s, appid, app, dstip, srcip, count
(*) as total_num from $log where $filter and (logflag&1>0) and virus like
'%PossibleThreat.SB%' group by virus_s, dstip, srcip, appid, app )### t where virus_s like
'%PossibleThreat.SB%' group by virus_s, appid, app order by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Files-Analyzed-By-FortiCloud-Sandbox	Files analyzed by FortiCloud Sandbox	virus

```

select
$DAY_OF_MONTH as dom,
count(*) as total_num
from
$log
where
$filter
and nullifna(filename) is not null
and logid_to_int(logid)= 9233
group by
dom
order by
dom

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Malicious-Files-Detected-By-FortiCloud-Sandbox	Files detected by FortiCloud Sandbox	virus

```

select
filename,
analyticscksum,
count(distinct dstip) as victims,
count(distinct srcip) as source
from
###(select filename, analyticscksum, dstip, srcip from $log where $filter and filename is
not null and logid_to_int(logid)=9233 and analyticscksum is not null group by filename,
analyticscksum, srcip, dstip)### t group by filename, analyticscksum order by victims desc,
source desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-File-Transferred-By-Application	File transferred by applications on the network	app-ctrl

```

select
appid,
app,
filename,
cloudaction,
max(filesize) as filesize
from

```

```

$log
where
$filter
and filesize is not null
and clouduser is not null
and filename is not null
group by
cloudaction,
appid,
app,
filename
order by
filesize desc

```

Dataset Name	Description	Log Category
appctrl-Top-Blocked-SCCP-Callers	Appctrl top blocked SCCP callers	app-ctrl

```

select
srcname as caller,
count(*) as totalnum
from
$log
where
$filter
and lower(appcat)='& #039;voip' and app='sccp' and action='block' and srcname is not null
group by caller order by totalnum desc

```

Dataset Name	Description	Log Category
appctrl-Top-Blocked-SIP-Callers	Appctrl top blocked SIP callers	app-ctrl

```

select
srcname as caller,
count(*) as totalnum
from
$log
where
$filter
and srcname is not null
and lower(appcat)='& #039;voip' and app='sip' and action='block' group by caller order by
totalnum desc

```

Dataset Name	Description	Log Category
security-Top20-High-Risk-Application-In-Use	High risk application in use	traffic

```

select
d_risk,
count(distinct f_user) as users,
name,
app_cat,
technology,
sum(bandwidth) as bandwidth,
sum(sessions) as sessions

```

```

from
    ###(select risk as d_risk, coalesce(nullifna(t1.`user`), nullifna(t1.`unauthuser`), ipstr
    (t1.`srcip`)) as f_user, t2.name, t2.app_cat, t2.technology, sum(coalesce(sentbyte,
    0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as sessions from $log t1 inner join app_
    mdata t2 on t1.appid=t2.id where $filter and risk>='4' and (logflag&1>0) group by f_user,
    t2.name, t2.app_cat, t2.technology, risk)### t group by d_risk, name, app_cat, technology
    order by d_risk desc, sessions desc

```

Dataset Name	Description	Log Category
security-High-Risk-Application-By-Category	High risk application by category	traffic

```

select
    app_cat,
    count(distinct app) as total_num
from
    ###(select app_cat, app from $log t1 inner join app_mdata t2 on t1.appid=t2.id where
    $filter and risk>='4' and (logflag&1>0) group by app_cat, app)### t group by app_cat order
    by total_num desc

```

Dataset Name	Description	Log Category
security-Top10-Application-Categories-By-Bandwidth	Application risk application usage by category	traffic

```

select
    appcat,
    sum(bandwidth) as bandwidth
from
    ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as
    sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid,
    coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app,
    appcat, apprisk, sum(coalesce(sentsdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
    bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
    nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app,
    appcat, apprisk order by sessions desc)base### t group by appid, app, appcat, apprisk
    /*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
    and nullifna(appcat) is not null group by appcat order by bandwidth desc

```

Dataset Name	Description	Log Category
Security-Category-Breakdown-By-Bandwidth	Category breakdown of all applications, sorted by bandwidth	traffic

```

select
    appcat,
    count(distinct app) as app_num,
    count(distinct user_src) as user_num,
    sum(bandwidth) as bandwidth,
    sum(sessions) as num_session
from
    ###(select app, appcat, user_src, sum(bandwidth) as bandwidth, sum(sessions) as sessions
    from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid, coalesce
    (nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app, appcat,
    apprisk, sum(coalesce(sentsdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as

```

bandwidth, count(*) as sessions from \$log-traffic where \$filter and (logflag&(1|32)>0) and nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app, appcat, apprisk order by sessions desc)### t where nullifna(appcat) is not null group by app, appcat, user_src order by bandwidth desc)### t where \$filter-drilldown group by appcat order by bandwidth desc

Dataset Name	Description	Log Category
security-Top25-Web-Applications-By-Bandwidth	Top Web Applications by Bandwidth	traffic

```
select
  d_risk,
  name,
  app_cat,
  technology,
  count(distinct f_user) as users,
  sum(bandwidth) as bandwidth,
  sum(num_session) as sessions
from
  ###(select risk as d_risk, t2.app_cat, t2.name, t2.technology, coalesce(nullifna
(tl.`user`), nullifna(tl.`unauthuser`), ipstr(tl.`srcip`)) as f_user, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as num_session from $log t1 inner join app_
mdata t2 on t1.appid=t2.id where $filter and (logflag&1>0) and nullifna(app) is not null and
service in ('80/tcp', '443/tcp', 'HTTP', 'HTTPS', 'http', 'https') group by risk, t2.app_
cat, t2.name, t2.technology, f_user)### t group by d_risk, name, app_cat, technology order
by bandwidth desc
```

Dataset Name	Description	Log Category
Security-Top25-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```
select
  catdesc,
  count(distinct f_user) as user_num,
  sum(sessions) as sessions,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
f_user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth
from $log-traffic where $filter and catdesc is not null and (logflag&1>0) and (countweb>0 or
((logver is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter',
'banned-word', 'web-content', 'command-block', 'script-filter')))) group by f_user, catdesc
order by sessions desc)### t group by catdesc order by sessions desc
```

Dataset Name	Description	Log Category
security-Top25-Malware-Virus-Botnet-Spyware	Malware: viruses, Bots, Spyware/Adware	traffic

```
select
  virus_s as virus,
  (
    case when lower(appcat)=% #039;botnet' then 'Botnet C&C' else (case when virus_s like
'Riskware%' then 'Spyware' when virus_s like 'Adware%' then 'Adware' else 'Virus' end) end)
```

```
as malware_type, count(distinct dstip) as victims, count(distinct srcip) as source, sum
(total_num) as total_num from (###(select app as virus_s, appcat, dstip, srcip, count(*) as
total_num from $log-traffic where $filter and (logflag&l>0) and lower(appcat)='botnet' group
by virus_s, appcat, dstip, srcip order by total_num desc)### union all ###(select unnest
(string_to_array(virus, ',')) as virus_s, appcat, dstip, srcip, count(*) as total_num from
$log-traffic where $filter and (logflag&l>0) and virus is not null group by virus_s, appcat,
dstip, srcip order by total_num desc)### union all ###(select attack as virus_s, 'null' as
appcat, dstip, srcip, count(*) as total_num from $log-attack where $filter and
(logflag&l6>0) group by virus_s, appcat, dstip, srcip order by total_num desc)###) t group
by virus, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Malware-Virus-Spyware	Malware: viruses, Spyware/Adware	virus

```
select
  virus,
  max(virusid_s) as virusid,
  malware_type,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  ###(select virus, virusid_to_str(virusid, eventtype) as virusid_s, srcip, dstip, (case
when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then 'Adware' else
'Virus' end) as malware_type, count(*) as total_num from $log where $filter and nullifna
(virus) is not null group by virus, virusid_s, srcip, dstip order by total_num desc)### t
group by virus, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Malware-Botnet	Malware: Botnet	appctrl

```
select
  app,
  appid,
  malware_type,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  (
    ###(select app, appid, cast('Botnet C&C' as char(32)) as malware_type, srcip, dstip,
count(*) as total_num from $log-app-ctrl where $filter and lower(appcat)='botnet' and
nullifna(app) is not null group by app, appid, malware_type, srcip, dstip order by total_num
desc)### union all ###(select attack, 0 as appid, cast('Botnet C&C' as char(32)) as malware_
type, srcip, dstip, count(*) as total_num from $log-attack where $filter and (logflag&l6>0)
group by attack, appid, malware_type, srcip, dstip order by total_num desc)###) t group by
app, appid, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Victims-of-Malware	Victims of Malware	virus

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  virus as malware,
  count(*) as total_num
from
  $log
where
  $filter
  and virus is not null
group by
  user_src,
  malware
order by
  total_num desc

```

Dataset Name	Description	Log Category
security-Top10-Victims-of-Phishing-Site	Victims of Phishing Site	webfilter

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  (
    lower(service) || & #039;://' || hostname || url) as phishing_site, count(*) as total_
num from $log where $filter and lower(service) in ('http', 'https') and hostname is not null
and cat in (26, 61) group by user_src, phishing_site order by total_num desc

```

Dataset Name	Description	Log Category
security-Top25-Malicious-Phishing-Sites	Malicious Phishing Site	webfilter

```

select
  phishing_site,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total) as total_num
from
  ###(select (lower(service) || '://' || hostname || url) as phishing_site, dstip, srcip,
count(*) as total from $log where $filter and lower(service) in ('http', 'https') and
hostname is not null and cat in (26, 61) group by phishing_site, dstip, srcip order by total
desc)### t group by phishing_site order by total_num desc

```

Dataset Name	Description	Log Category
security-Application-Vulnerability	Application vulnerabilities discovered	attack


```

select
  attack,
  attackid,
  vuln_type,
  cve,
  severity_number,
  count(distinct dstip) as victims,
  count(distinct srcip) as sources,
  sum(totalnum) as totalnum
from
  ###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then 5
when t1.severity='high' then 4 when t1.severity='medium' then 3 when t1.severity='low' then
2 when t1.severity='info' then 1 else 0 end) as severity_number, dstip, srcip, count(*) as
totalnum from $log t1 left join (select name, cve, vuln_type from ips_mdata) t2 on
t1.attack=t2.name where $filter and nullifna(attack) is not null and t1.severity is not null
group by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip )### t group by
attack, attackid, vuln_type, severity_number, cve order by severity_number desc, totalnum
desc

```

Dataset Name	Description	Log Category
security-Files-Analyzed-By-FortiCloud-Sandbox	Files analyzed by FortiCloud Sandbox	virus

```

select
  $day_of_week as dow,
  count(*) as total_num
from
  $log
where
  $filter
  and nullifna(filename) is not null
  and logid_to_int(logid)= 9233
group by
  dow
order by
  dow

```

Dataset Name	Description	Log Category
Security-Zero-Day-Detected-On-Network	Zero-day malware detected on the network	traffic

```

select
  virus_s,
  app,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  ###(select unnest(string_to_array(virus, ',')) as virus_s, app, dstip, srcip, count(*) as
total_num from $log where $filter and (logflag&1>0) and virus like '%PossibleThreat.SB%'
group by virus_s, dstip, srcip, app)### t group by virus_s, app order by total_num desc

```

Dataset Name	Description	Log Category
security-Data-Loss-Incidents-By-Severity	Data loss incidents summary by severity	dlp

```
select
  initcap(severity : :text) as s_severity,
  count(*) as total_num
from
  ###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
  subtype, srcip, dstip, severity, filename, direction, filesize, (case when
  severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
  (`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
  as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
  $filter-drilldown and severity is not null group by s_severity order by total_num desc
```

Dataset Name	Description	Log Category
security-Data-Loss-Files-By-Service	Data Loss Files By Service	dlp

```
select
  filename,
  (
    case direction when & #039;incoming' then 'Download' when 'outgoing' then 'Upload' end)
  as action, max(filesize) as filesize, service from ###(select itime, hostname, `from` as
  sender, `to` as receiver, profile, action, service, subtype, srcip, dstip, severity,
  filename, direction, filesize, (case when severity='critical' then 'Critical Data
  Exfiltration' else (case when coalesce(nullifna(`user`), ipstr(`srcip`)) is not null then
  'User Associated Data Loss' else NULL end) end) as data_loss from $log where $filter
  /*SkipSTART*/order by itime desc/*SkipEND*/)### t where $filter-drilldown and filesize is
  not null group by filename, direction, service order by filesize desc
```

Dataset Name	Description	Log Category
security-Endpoint-Security-Events-Summary	Endpoint Security Events summary	fct-traffic

```
select
  (
    case utmevent when & #039;antivirus' then 'Malware incidents' when 'webfilter' then
    'Malicious/phishing websites' when 'appfirewall' then 'Risk applications' when 'dlp' then
    'Data loss incidents' when 'netscan' then 'Vulnerability detected' else 'Others' end) as
  events, count(*) as total_num from $log where $filter and utmevent is not null group by
  events order by total_num desc
```

Dataset Name	Description	Log Category
security-Top-Endpoing-Running-High-Risk-Application	Endpoints Running High Risk Application	fct-traffic

```
select
  coalesce(
    nullifna(`user`),
    ipstr(`srcip`),
    & #039;Unknown') as f_user, coalesce(nullifna(hostname), 'Unknown') as host_name, threat
```

```
as app, t2.app_cat as appcat, risk as d_risk from $log t1 inner join app_mdata t2 on
t1.threat=t2.name where $filter and utmevent='appfirewall' and risk>='4' group by f_user,
host_name, t1.threat, t2.app_cat, t2.risk order by risk desc
```

Dataset Name	Description	Log Category
security-Top-Endpoints-Infected-With-Malware	Endpoints Infected With Malware	fct-event

```
select
  coalesce(
    nullifna(`user`),
    ipstr(`deviceip`),
    & #039;Unknown') as f_user, coalesce(nullifna(hostname), 'Unknown') as host_name, virus,
file from $log where $filter and subtype='av' and virus is not null group by f_user, host_
name, virus, file
```

Dataset Name	Description	Log Category
security-Top-Endpoints-With-Web-Violateions	Endpoints With Web Violations	fct-traffic

```
select
  f_user,
  host_name,
  remotename,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as f_user, coalesce(nullifna
(hostname), 'Unknown') as host_name, remotename, count(*) as total_num from $log where
$filter and utmevent='webfilter' and remotename is not null and utmaction='blocked' group by
f_user, host_name, remotename order by total_num desc)### t group by f_user, host_name,
remotename order by total_num desc
```

Dataset Name	Description	Log Category
security-Top-Endpoints-With-Data-Loss-Incidents	Endpoints With Data Loss Incidents	fct-event

```
select
  f_user,
  host_name,
  msg,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`user`), ipstr(`deviceip`), 'Unknown') as f_user, coalesce
(nullifna(hostname), 'Unknown') as host_name, msg, count(*) as total_num from $log where
$filter and subtype='dlp' group by f_user, host_name, msg order by total_num desc)### t
group by f_user, host_name, msg order by total_num desc
```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Call-Registrations-by-Hour-of-Day	Content count total SCCP call registrations by hour of day	content

```

select
    $hour_of_day as hourstamp,
    count(*) as totalnum
from
    $log
where
    $filter
    and proto =& #039;sccp' and kind='register' group by hourstamp order by hourstamp

```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Calls-Duration-by-Hour-of-Day	Content count total SCCP calls duration by hour of day	content

```

select
    $hour_of_day as hourstamp,
    sum(duration) as sccp_usage
from
    $log
where
    $filter
    and proto =& #039;sccp' and kind='call-info' and status='end' group by hourstamp order by hourstamp

```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Calls-per-Status	Content count total SCCP calls per status	content

```

select
    status,
    count(*) as totalnum
from
    $log
where
    $filter
    and proto =& #039;sccp' and kind='call-info' group by status order by totalnum desc

```

Dataset Name	Description	Log Category
content-Count-Total-SIP-Call-Registrations-by-Hour-of-Day	Content count total SIP call registrations by hour of day	content

```

select
    $hour_of_day as hourstamp,
    count(*) as totalnum
from
    $log
where
    $filter
    and proto =& #039;sip' and kind='register' group by hourstamp order by hourstamp

```

Dataset Name	Description	Log Category
content-Count-Total-SIP-Calls-per-Status	Content count total SIP calls per status	content

```
select
  status,
  count(*) as totalnum
from
  $log
where
  $filter
  and proto = & #039;sip' and kind='call' group by status order by totalnum desc
```

Dataset Name	Description	Log Category
content-Dist-Total-SIP-Calls-by-Duration	Content dist total SIP calls by duration	content

```
select
  (
    case when duration<60 then & #039;LESS_ONE_MIN' when duration < 600 then 'LESS_TEN_MIN'
    when duration < 3600 then 'LESS_ONE_HOUR' when duration >= 3600 then 'MORE_ONE_HOUR' else
    'unknown' end) as f_duration, count(*) as totalnum from $log where $filter and proto='sip'
    and kind='call' and status='end' group by f_duration order by totalnum desc
```

Dataset Name	Description	Log Category
Botnet-Activity-By-Sources	Botnet activity by sources	traffic

```
select
  app,
  user_src,
  sum(events) as events
from
  (
    (
      select
        app,
        user_src,
        sum(totalnum) as events
      from
        ###(select app, appcat, apprisk, srcip, dstip, coalesce(nullifna(`user`), nullifna(
        `unauthuser`), ipstr(`srcip`)) as user_src, count(*) as totalnum from $log-traffic where
        $filter and (logflag&1>0) and appcat='Botnet' and nullifna(app) is not null group by app,
        appcat, apprisk, srcip, dstip, user_src order by totalnum desc)### t group by app, user_src
        order by events desc) union all (select attack, user_src, sum(totalnum) as events from ###
        (select attack, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
        src, $flex_timestamp as timestamp, hostname, severity, crlevel, eventtype, service, dstip,
        srcip, count(*) as totalnum from $log-attack where $filter and (logflag&16>0) group by
        attack, user_src, timestamp, hostname, severity, crlevel, eventtype, service, dstip, srcip
        order by timestamp desc)### t group by attack, user_src order by events desc)) t group by
        app, user_src order by events desc
```

Dataset Name	Description	Log Category
Botnet-Infected-Hosts	Botnet infected hosts	traffic

```
select
  user_src,
  devtype_new,
```

```

    host_mac,
    sum(events) as events
from
(
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, get_devtype(srcswversion, osname, devtype) as devtype_new, coalesce(srcname, srcmac) as host_mac, count(*) as events from $log-traffic where $filter and (logflag&1>0) and appcat='Botnet' group by user_src, devtype_new, host_mac order by events desc)### union all
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, 'Unknown' as devtype_new, hostname as host_mac, count(*) as events from $log-attack where $filter and (logflag&16>0) group by user_src, devtype_new, host_mac order by events desc)###) t group by user_src, devtype_new, host_mac order by events desc

```

Dataset Name	Description	Log Category
Detected-Botnet	Detected botnet	traffic

```

select
    app,
    sum(events) as events
from
(
    (
        select
            app,
            sum(totalnum) as events
        from
            ###(select app, appcat, apprisk, srcip, dstip, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, count(*) as totalnum from $log-traffic where $filter and (logflag&1>0) and appcat='Botnet' and nullifna(app) is not null group by app, appcat, apprisk, srcip, dstip, user_src order by totalnum desc)### t group by app order by events desc) union all
            (select attack, sum(totalnum) as events from ###(select attack, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, $flex_timestamp as timestamp, hostname, severity, crlevel, eventtype, service, dstip, srcip, count(*) as totalnum from $log-attack where $filter and (logflag&16>0) group by attack, user_src, timestamp, hostname, severity, crlevel, eventtype, service, dstip, srcip order by timestamp desc)### t group by attack order by events desc)) t group by app order by events desc

```

Dataset Name	Description	Log Category
Botnet-Sources	Botnet sources	traffic

```

select
    dstip,
    domain,
    sum(events) as events
from
(
    (
        select
            dstip,
            domain,
            sum(events) as events
        from
            ###(select dstip, root_domain(hostname) as domain, count(*) as events from $log-traffic where $filter and (logflag&1>0) and appcat='Botnet' and dstip is not null group by

```

```
dstip, domain order by events desc)### t group by dstip, domain) union all (select dstip,
root_domain(hostname) as domain, sum(totalnum) as events from ###(select attack, coalesce
(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, $flex_timestamp as
timestamp, hostname, severity, crlevel, eventtype, service, dstip, srcip, count(*) as
totalnum from $log-attack where $filter and (logflag&16>0) group by attack, user_src,
timestamp, hostname, severity, crlevel, eventtype, service, dstip, srcip order by timestamp
desc)### t group by dstip, domain)) t group by dstip, domain order by events desc
```

Dataset Name	Description	Log Category
Botnet-Victims	Botnet victims	traffic

```
select
  user_src,
  sum(events) as events
from
  (
    (
      select
        user_src,
        sum(totalnum) as events
      from
        ###(select app, appcat, apprisk, srcip, dstip, coalesce(nullifna(`user`), nullifna
(`unauthuser`), ipstr(`srcip`)) as user_src, count(*) as totalnum from $log-traffic where
$filter and (logflag&1>0) and appcat='Botnet' and nullifna(app) is not null group by app,
appcat, apprisk, srcip, dstip, user_src order by totalnum desc)### t group by user_src)
union all (select user_src, sum(totalnum) as events from ###(select attack, coalesce
(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, $flex_timestamp as
timestamp, hostname, severity, crlevel, eventtype, service, dstip, srcip, count(*) as
totalnum from $log-attack where $filter and (logflag&16>0) group by attack, user_src,
timestamp, hostname, severity, crlevel, eventtype, service, dstip, srcip order by timestamp
desc)### t group by user_src)) t group by user_src order by events desc
```

Dataset Name	Description	Log Category
Botnet-Timeline	Botnet timeline	traffic

```
select
  $flex_datetime(timestamp) as hodex,
  sum(events) as events
from
  (
    ###(select $flex_timestamp as timestamp, count(*) as events from $log-traffic where
$filter and (logflag&1>0) and appcat='Botnet' group by timestamp order by timestamp desc)###
union all ###(select $flex_timestamp as timestamp, count(*) as events from $log-dns where
$filter and (botnetdomain is not null or botnetip is not null) group by timestamp order by
timestamp)### union all ###(select $flex_timestamp as timestamp, count(*) as events from
$log-attack where $filter and (logflag&16>0) group by timestamp order by timestamp)###) t
group by hodex order by hodex
```

Dataset Name	Description	Log Category
Application-Session-History	Application session history	traffic

```
select
  $flex_timescale(timestamp) as hodex,
```

```

sum(counter) as counter
from
###(select $flex_timestamp as timestamp, count(*) as counter from $log where $filter and
(logflag&1>0) group by timestamp order by timestamp desc)### t group by hodex order by hodex

```

Dataset Name	Description	Log Category
Application-Usage-List	Detailed application usage	traffic

```

select
  appid,
  app,
  appcat,
  (
    case when (
      utmaction in (
        & #039;block', 'blocked') or action='deny') then 'Blocked' else 'Allowed' end) as
    custaction, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as num_
    session from $log where $filter and (logflag&1>0) and nullifna(app) is not null and policyid
    != 0 group by appid, app, appcat, custaction order by bandwidth desc

```

Dataset Name	Description	Log Category
PCI-DSS-Compliance-Summary	PCI DSS Compliance Summary	event

```

select
  status,
  num_reason as requirements,
  cast(
    num_reason * 100.0 /(
      sum(num_reason) over()
    ) as decimal(18, 2)
  ) as percent
from
  (
    select
      (
        case when fail_count>0 then & #039;Non-Compliant' else 'Compliant' end) as status,
        count(distinct reason) as num_reason from (select ftnt_pci_id, (sum(fail_count) over
        (partition by ftnt_pci_id)) as fail_count, reason from ###(select ftnt_pci_id, (case when
        result='fail' then 1 else 0 end) as fail_count, reason from $log t1 inner join pci_dss_mdata
        t2 on t1.reason=t2.ftnt_id where $filter and subtype='compliance-check' group by ftnt_pci_
        id, result, reason)### t) t group by status) t order by status

```

Dataset Name	Description	Log Category
PCI-DSS-Non-Compliant-Requirements-By-Severity	PCI DSS Non-Compliant Requirements by Severity	event

```

with query as (
  select
    *
  from
    (
      select
        ftnt_pci_id,

```



```

        severity,
        (
            sum(fail_count) over (partition by ftnt_pci_id)
        ) as fail_count,
        reason
    from
        ###(select ftnt_pci_id, t2.severity, (case when result='fail' then 1 else 0 end) as
fail_count, reason from $log t1 inner join pci_dss_mdata t2 on t1.reason=t2.ftnt_id where
$filter and subtype='compliance-check' group by ftnt_pci_id, t2.severity, result, reason)###
t) t where fail_count>0) select t.severity, count(distinct t.reason) as requirements from
(select distinct on (1) reason, severity from query order by reason, (case lower(severity)
when 'high' then 4 when 'critical' then 3 when 'medium' then 2 when 'low' then 1 else 0 end)
desc) t group by t.severity order by requirements desc

```

Dataset Name	Description	Log Category
PCI-DSS-Compliant-Requirements-By-Severity	PCI DSS Compliant Requirements by Severity	event

```

with query as (
    select
        *
    from
        (
            select
                ftnt_pci_id,
                severity,
                (
                    sum(fail_count) over (partition by ftnt_pci_id)
                ) as fail_count,
                reason
            from
                ###(select ftnt_pci_id, t2.severity, (case when result='fail' then 1 else 0 end) as
fail_count, reason from $log t1 inner join pci_dss_mdata t2 on t1.reason=t2.ftnt_id where
$filter and subtype='compliance-check' group by ftnt_pci_id, t2.severity, result, reason)###
t) t where fail_count=0) select t.severity, count(distinct t.reason) as requirements from
(select distinct on (1) reason, severity from query order by reason, (case lower(severity)
when 'high' then 4 when 'critical' then 3 when 'medium' then 2 when 'low' then 1 else 0 end)
desc) t group by t.severity order by requirements desc

```

Dataset Name	Description	Log Category
PCI-DSS-Fortinet-Security-Best-Practice-Summary	PCI DSS Fortinet Security Best Practice Summary	event

```

select
    status,
    num_reason as practices,
    cast(
        num_reason * 100.0 / (
            sum(num_reason) over()
        ) as decimal(18, 2)
    ) as percent
from
    (
        select

```

```
(
    case when result =& #039;fail' then 'Failed' else 'Passed' end) as status, count
(distinct reason) as num_reason from ###(select result, reason from $log where $filter and
subtype='compliance-check' and result in ('fail','pass') group by result, reason)### t group
by status) t order by status desc
```

Dataset Name	Description	Log Category
PCI-DSS-Failed-Fortinet-Security-Best-Practices-By-Severity	PCI DSS Failed Fortinet Security Best Practices by Severity	event

```
select
    status,
    num_reason as practices,
    cast(
        num_reason * 100.0 /(
            sum(num_reason) over()
        ) as decimal(18, 2)
    ) as percent
from
    (
        select
            initcap(status) as status,
            count(distinct reason) as num_reason
        from
            ###(select status, reason from $log where $filter and subtype='compliance-check' and
result='fail' group by status, reason)### t group by status) t order by status
```

Dataset Name	Description	Log Category
PCI-DSS-Passed-Fortinet-Security-Best-Practices-By-Severity	PCI DSS Passed Fortinet Security Best Practices by Severity	event

```
select
    status,
    num_reason as practices,
    cast(
        num_reason * 100.0 /(
            sum(num_reason) over()
        ) as decimal(18, 2)
    ) as percent
from
    (
        select
            initcap(status) as status,
            count(distinct reason) as num_reason
        from
            ###(select status, reason from $log where $filter and subtype='compliance-check' and
result='pass' group by status, reason)### t group by status) t order by status
```

Dataset Name	Description	Log Category
PCI-DSS-Requirements-Compliance-Details	PCI DSS Requirements Compliance Details	event

```
select
  ftnt_pci_id,
  left(
    string_agg(
      distinct ftnt_id,
      & #039;;', 120) as practice, (case when sum(fail_count)>0 then 'Non-Compliant' else
'Compliant' end) as compliance, pci_requirement from ###(select ftnt_pci_id, ftnt_id, (case
when result='fail' then 1 else 0 end) as fail_count, pci_requirement from $log t1 inner join
pci_dss_mdata t2 on t1.reason=t2.ftnt_id where $filter and subtype='compliance-check' group
by ftnt_pci_id, ftnt_id, result, pci_requirement)### t group by ftnt_pci_id, pci_requirement
order by ftnt_pci_id
```

Dataset Name	Description	Log Category
PCI-DSS-Fortinet-Security-Best-Practice-Details	PCI DSS Fortinet Security Best Practice Details	event

```
select
  reason as ftnt_id,
  msg,
  initcap(status) as status,
  module
from
  $log
where
  $filter
  and subtype =& #039;compliance-check' group by reason, status, module, msg order by ftnt_
id
```

Dataset Name	Description	Log Category
DLP-Email-Activity-Details	Email DLP Violations Summary	dlp

```
select
  from_itime(itime) as timestamp,
  sender,
  receiver,
  regexp_replace(
    filename,
    & #039;.*/', '') as filename, filesize, profile, action, direction from ###(select
itime, hostname, `from` as sender, `to` as receiver, profile, action, service, subtype,
srcip, dstip, severity, filename, direction, filesize, (case when severity='critical' then
'Critical Data Exfiltration' else (case when coalesce(nullifna(`user`), ipstr(`srcip`)) is
not null then 'User Associated Data Loss' else NULL end) end) as data_loss from $log where
$filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where $filter-drilldown and
(service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') or service in
('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s',
'POP3S', '995/tcp')) order by timestamp desc
```

Dataset Name	Description	Log Category
Email-DLP-Chart	Email DLP Activity Summary	dlp

```
select
  profile,
  count(*) as total_num
```

```

from
  ###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
  subtype, srcip, dstip, severity, filename, direction, filesize, (case when
  severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
  (`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
  as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
  $filter-drilldown and (service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS',
  '465/tcp') or service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps',
  'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp')) group by profile order by total_num desc

```

Dataset Name	Description	Log Category
DLP-Web-Activity-Details	Web DLP Violations Summary	dlp

```

select
  from_time(itime) as timestamp,
  srcip,
  dstip,
  hostname,
  profile,
  filename,
  filesize,
  action,
  direction
from
  ###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
  subtype, srcip, dstip, severity, filename, direction, filesize, (case when
  severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
  (`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
  as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
  $filter-drilldown and lower(service) in ('http', 'https') order by timestamp desc

```

Dataset Name	Description	Log Category
Web-DLP-Chart	Web DLP Activity Summary	dlp

```

select
  profile,
  count(*) as total_num
from
  ###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
  subtype, srcip, dstip, severity, filename, direction, filesize, (case when
  severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
  (`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
  as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
  $filter-drilldown and lower(service) in ('http', 'https') group by profile order by total_
  num desc

```

Dataset Name	Description	Log Category
DLP-FTP-Activity-Details	Web DLP Violations Summary	dlp

```

select
  from_time(itime) as timestamp,
  srcip,
  dstip,

```

```

filename,
profile,
filesize,
action,
direction
from
###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
subtype, srcip, dstip, severity, filename, direction, filesize, (case when
severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
(`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
$filter-drilldown and lower(service) in ('ftp', 'ftps') order by timestamp desc

```

Dataset Name	Description	Log Category
FTP-DLP-Chart	FTP DLP Activity Summary	dlp

```

select
  profile,
  count(*) as total_num
from
  ###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
subtype, srcip, dstip, severity, filename, direction, filesize, (case when
severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
(`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
$filter-drilldown and lower(service) in ('ftp', 'ftps') group by profile order by total_num
desc

```

Dataset Name	Description	Log Category
top-users-by-browsetime	Top Users by website browsetime	traffic

```

select
  user_src,
  domain,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###(select user_src, domain, ebtr_agg_flat(browsetime) as browsetime from (select coalesce
(nullifna(`user`), ipstr(`srcip`)) as user_src, coalesce(nullifna(hostname), ipstr(`dstip`))
as domain, ebtr_agg_flat($browse_time) as browsetime from $log where $filter and $browse_
time is not null group by user_src, domain) t group by user_src, domain order by ebtr_value
(ebtr_agg_flat(browsetime), null, null) desc)### t group by user_src, domain order by
browsetime desc

```

Dataset Name	Description	Log Category
wifi-usage-by-hour-authenticated	Wifi Usage by Hour - Authenticated	event

```

select
  hod,
  count(distinct stamac) as totalnum

```

```
from
  ###(select $HOUR_OF_DAY as hod, stamac from $log where $filter and subtype='wireless' and
  action='client-authentication' group by hod, stamac)### t group by hod order by hod
```

Dataset Name	Description	Log Category
wifi-usage-authenticated-timeline	Wifi Usage Timeline - Authenticated	event

```
select
  $flex_timescale(timestamp) as hodex,
  count(distinct stamac) as totalnum
from
  ###(select $flex_timestamp as timestamp, stamac from $log where $filter and
  subtype='wireless' and action='client-authentication' group by timestamp, stamac order by
  timestamp desc)### t group by hodex order by hodex
```

Dataset Name	Description	Log Category
app-top-user-by-bandwidth	Top 10 Applications Bandwidth by User Drilldown	traffic

```
select
  app,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(`sentbyte`, 0)+ coalesce(`rcvdbyte`, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app,
  user_src
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
app-top-user-by-session	Top 10 Application Sessions by User Drilldown	traffic

```
select
  app,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
```

```

from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(app) is not null
group by
    app,
    user_src
order by
    sessions desc

```

Dataset Name	Description	Log Category
traffic-Interface-Bandwidth-Usage	Interface Bandwidth Usage	traffic

```

with qry as (
    select
        dom as dom_s,
        devid as devid_s,
        vd as vd_s,
        srcintf,
        dstintf,
        total_sent,
        total_rcvd
    from
        ###(select $DAY_OF_MONTH as dom, devid, vd, srcintf, dstintf, sum(coalesce(sentbyte, 0))
as total_sent, sum(coalesce(rcvdbyte, 0)) as total_rcvd, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as total from $log where $filter and (logflag&1>0) and nullifna(srcintf) is
not null and nullifna(dstintf) is not null group by dom, devid, vd, srcintf, dstintf having
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by total desc)### t) select dom,
unnest(array['download', 'upload']) as type, unnest(array[sum(download), sum(upload)]) as
bandwidth from (select coalesce(t1.dom_s, t2.dom_s) as dom, coalesce(t1.devid_s, t2.devid_s)
as devid, coalesce(t1.vd_s, t2.vd_s) as vd, coalesce(t1.srcintf, t2.dstintf) as intf, sum
(coalesce(t1.total_sent, 0)+coalesce(t2.total_rcvd, 0)) as download, sum(coalesce(t2.total_
sent, 0)+coalesce(t1.total_rcvd, 0)) as upload from qry t1 full join qry t2 on t1.dom_
s=t2.dom_s and t1.srcintf=t2.dstintf group by dom, devid, vd, intf) t where $filter-
drilldown group by dom order by dom

```

Dataset Name	Description	Log Category
ctap-SB-Files-Needing-Inspection-vs- Others	Files Needing Inspection vs Others	virus

```

select
    (
        case when suffix in (
            &
            #039;bat','cmd','exe','jar','msi','vbs','7z','zip','gzip','lzw','tar','rar','cab','doc','doc
x','xls','xlsx','ppt','pptx','pdf','swf','lnk','js') then 'Higher Risk File Types' else
'Excluded Files' end) as files, sum(total_num) as total_num from ###(select file_name_ext
(filename) as suffix, count(*) as total_num from $log where $filter and dtype='fortisandbox'
and nullifna(filename) is not null group by suffix order by total_num desc)### t group by
files order by total_num desc

```

Dataset Name	Description	Log Category
ctap-SB-Breakdown-of-File-Types	Breakdown of File Types	virus

```
select
(
case when suffix in (
& #039;exe','msi','upx','vbs','bat','cmd','dll','ps1','jar') then 'Executable Files'
when suffix in ('pdf') then 'Adobe PDF' when suffix in ('swf') then 'Adobe Flash' when
suffix in ('doc','docx','rtf','dotx','docm','dotm','dot') then 'Microsoft Word' when suffix
in ('xls','xlsx','xltx','xlsm','xlsb','xlam','xlt') then 'Microsoft Excel' when suffix in
('ppsx','ppt','pptx','potx','sldx','pptm','ppsm','potm','ppam','sldm','pps','pot') then
'Microsoft PowerPoint' when suffix in ('msg') then 'Microsoft Outlook' when suffix in
('htm','js','url','lnk') then 'Web Files' when suffix in
('cab','tgz','z','7z','tar','lzh','kgb','rar','zip','gz','xz','bz2') then 'Archive Files'
when suffix in ('apk') then 'Android Files' else 'Others' end) as filetype, sum(total_num)
as total_num from ###(select file_name_ext(filename) as suffix, count(*) as total_num from
$log where $filter and dtype='fortisandbox' and nullifna(filename) is not null group by
suffix order by total_num desc)### t group by filetype order by total_num desc
```

Dataset Name	Description	Log Category
ctap-SB-Top-Sandbox-Malicious-Exes		virus

```
select
(
case fsaverdict when & #039;malicious' then 5 when 'high risk' then 4 when 'medium risk'
then 3 when 'low risk' then 2 else 1 end) as risk, filename, service, count(*) as total_num
from $log where $filter and dtype='fortisandbox' and file_name_ext(filename)='exe' and
fsaverdict not in ('clean','submission failed') group by filename, risk, service order by
risk desc, total_num desc, filename
```

Dataset Name	Description	Log Category
ctap-SB-Sources-of-Sandbox-Discovered-Malware	Sources of Sandbox Discovered Malware	virus

```
select
srcip,
count(*) as total_num
from
$log
where
$filter
and dtype =& #039;fortisandbox' and nullifna(filename) is not null and fsaverdict not in
('clean','submission failed') group by srcip order by total_num desc
```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-High-Risk-Application	Application risk high risk application	traffic

```
select
risk as d_risk,
count(distinct user_src) as users,
id,
name,
```



```

app_cat,
technology,
sum(bandwidth) as bandwidth,
sum(sessions) as sessions
from
###(select lower(app) as lowapp, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, count
(*) as sessions from $log where $filter and (logflag&1>0) group by lowapp, user_src order by
bandwidth desc)### t1 inner join app_mdata t2 on t1.lowapp=lower(t2.name) where risk>='4'
group by id, name, app_cat, technology, risk order by d_risk desc, sessions desc

```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Application-Vulnerability	Application vulnerabilities discovered	attack

```

select
attack,
attackid,
vuln_type,
cve,
severity_number,
count(distinct dstip) as victims,
count(distinct srcip) as sources,
sum(totalnum) as totalnum
from
###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then 5
when t1.severity='high' then 4 when t1.severity='medium' then 3 when t1.severity='low' then 2
when t1.severity='info' then 1 else 0 end) as severity_number, dstip, srcip, count(*) as
totalnum from $log t1 left join (select name, cve, vuln_type from ips_mdata) t2 on
t1.attack=t2.name where $filter and nullifna(attack) is not null and t1.severity is not null
group by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip)### t group by
attack, attackid, vuln_type, severity_number, cve order by severity_number desc, totalnum
desc

```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Common-Virus-Botnet-Spyware	Common Virus Botnet Spyware	app-ctrl

```

select
malware as virus,
(
case when lower(appcat)=& #039;botnet' then 'Botnet C&C' else (case when malware like
'Riskware%' then 'Spyware' when malware like 'Adware%' then 'Adware' else 'Virus' end) end)
as malware_type, appid, app, count(distinct dstip) as victims, count(distinct srcip) as
source, sum(total_num) as total_num from (###(select app as malware, appcat, appid, app,
dstip, srcip, count(*) as total_num from $log-app-ctrl where $filter and lower
(appcat)='botnet' group by malware, appcat, appid, app, dstip, srcip, app order by total_num
desc)### union all ###(select virus as malware, 'null' as appcat, 0 as appid, service as
app, dstip, srcip, count(*) as total_num from $log-virus where $filter and virus is not null
group by malware, appcat, app, appid, dstip, srcip order by total_num desc)### union all ###
(select attack as malware, 'null' as appcat, 0 as appid, service as app, dstip, srcip, count
(*) as total_num from $log-attack where $filter and (logflag&16>0) group by malware, appcat,
app, appid, dstip, srcip order by total_num desc)###) t group by malware, malware_type, app,
appid order by total_num desc

```

Dataset Name	Description	Log Category
ctap-App-Risk-Reputation-Top-Devices-By-Scores	Reputation Top Devices By-Scores	traffic

```
select
  coalesce(
    nullifna(`srcname`),
    ipstr(`srcip`),
    nullifna(`srcmac`)
  ) as dev_src,
  sum(crscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crscore is not null
group by
  dev_src
having
  sum(crscore % 65536)> 0
order by
  scores desc
```

Dataset Name	Description	Log Category
ctap-HTTP-SSL-Traffic-Ratio	HTTP SSL Traffic Ratio	traffic

```
select
  (
    case when service in (
      & #039;80/tcp', 'HTTP', 'http') then 'HTTP' else 'HTTPS' end) as service, sum
    (coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and
    (logflag&1>0) and nullifna(app) is not null and service in ('80/tcp', '443/tcp', 'HTTP',
    'HTTPS', 'http', 'https') group by service having sum(coalesce(sentbyte, 0)+coalesce
    (rcvdbyte, 0))>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
ctap-Top-Source-Countries	Top Source Countries	traffic

```
select
  srccountry,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
```

```

and nullifna(srccountry) is not null
and srccountry <> & #039;Reserved' group by srccountry having sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc, srccountry

```

Dataset Name	Description	Log Category
ctap-SaaS-Apps	CTAP SaaS Apps	traffic

```

select
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select app_group_name(app) as app_group, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as
traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) and nullifna
(app) is not null group by app_group having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0))>0 order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app_group)=lower
(t2.name) where behavior like '%Cloud%' group by app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-IaaS-Apps	CTAP IaaS Apps	traffic

```

select
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select app_group_name(app) as app_group, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as
traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) and nullifna
(app) is not null group by app_group having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0))>0 order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app_group)=lower
(t2.name) where app_cat='Cloud.IT' group by app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-RAS-Apps	CTAP RAS Apps	traffic

```

select
  name as app_group,
  sum(bandwidth) as bandwidth
from
  ###(select app_group_name(app) as app_group, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as
traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) and nullifna
(app) is not null group by app_group having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0))>0 order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app_group)=lower
(t2.name) where app_cat='Remote.Access' group by name order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Proxy-Apps	CTAP Proxy Apps	traffic

```

select
  name as app_group,
  sum(bandwidth) as bandwidth

```

```

from
  ###(select app_group_name(app) as app_group, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as
traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) and nullifna
(app) is not null group by app_group having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0))>0 order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app_group)=lower
(t2.name) where app_cat='Proxy' group by name order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-SocialMedia-App-By-Bandwidth	Top SocialMedia Applications by Bandwidth Usage	traffic

```

select
  app_group,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions
from
  ###(select app_group_name(app) as app_group, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as
traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) and nullifna
(app) is not null group by app_group having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0))>0 order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app_group)=lower
(t2.name) where app_cat='Social.Media' group by app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-Streaming-App-By-Bandwidth	Top Streaming applications by bandwidth usage	traffic

```

select
  app_group,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions
from
  ###(select app_group_name(app) as app_group, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as
traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) and nullifna
(app) is not null group by app_group having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
0))>0 order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app_group)=lower
(t2.name) where app_cat='Video/Audio' group by app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-Game-App-By-Bandwidth	Top Game applications by bandwidth usage	traffic

```

select
  app_group,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions

```

```

from
    ###(select app_group_name(app) as app_group, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) and nullifna (app) is not null group by app_group having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app_group)=lower (t2.name) where app_cat='Game' group by app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-P2P-App-By-Bandwidth	Top P2P applications by bandwidth usage	traffic

```

select
    app_group,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out,
    sum(sessions) as sessions
from
    ###(select app_group_name(app) as app_group, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) and nullifna (app) is not null group by app_group having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app_group)=lower (t2.name) where app_cat='P2P' group by app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Top-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```

select
    catdesc,
    count(distinct f_user) as user_num,
    sum(sessions) as sessions,
    sum(bandwidth) as bandwidth
from
    ###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as f_user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and catdesc is not null and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by f_user, catdesc order by sessions desc)### t group by catdesc order by sessions desc

```

Dataset Name	Description	Log Category
ctap-App-Risk-Applications-Running-Over-HTTP	Application risk applications running over HTTP	traffic

```

select
    app_group_name(app) as app_group,
    service,
    count(*) as sessions,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth

```

```

from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
  and service in (
    & #039;80/tcp', '443/tcp', 'HTTP', 'HTTPS', 'http', 'https') group by app_group, service
having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-App-Risk-Web-Browsing-Activity-Hostname-Category	Application risk web browsing activity hostname category	webfilter

```

select
  domain,
  catdesc,
  sum(visits) as visits
from
  ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, catdesc, count(*) as
visits from $log where $filter and (eventtype is null or logver>=502000000) and catdesc is
not null group by domain, catdesc order by visits desc)### t group by domain, catdesc order
by visits desc

```

Dataset Name	Description	Log Category
ctap-Top-Sites-By-Browsing-Time	Traffic top sites by browsing time	traffic

```

select
  hostname,
  string_agg(
    distinct catdesc,
    & #039;; ' ) as agg_catdesc, ebtr_value(ebtr_agg_flat(browsetime), null, $timespan) as
browsetime, sum(bandwidth) as bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as
traffic_out from ###(select hostname, catdesc, ebtr_agg_flat(browsetime) as browsetime, sum
(bandwidth) as bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out
from (select hostname, catdesc, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in,
sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and (logflag&1>0) and
hostname is not null and $browse_time is not null group by hostname, catdesc) t group by
hostname, catdesc /*SkipSTART*/order by ebtr_value(ebtr_agg_flat(browsetime), null, null)
desc/*SkipEND*/)### t group by hostname order by browsetime desc

```

Dataset Name	Description	Log Category
ctap-Average-Bandwidth-Hour	Average Bandwidth Hour	traffic

```

select
  hourstamp,
  sum(bandwidth)/ count(distinct daystamp) as bandwidth
from
  ###(select to_char(from_dtime(dtime), 'HH24:00') as hourstamp, to_char(from_dtime(dtime),
'DD Mon') as daystamp, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from

```

```
$log where $filter and (logflag&1>0) group by hourstamp, daystamp having sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by hourstamp)### t group by hourstamp order by
hourstamp
```

Dataset Name	Description	Log Category
ctap-Top-Bandwidth-Hosts	Top Bandwidth Hosts	traffic

```
select
  hostname,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log - traffic
where
  $filter
  and hostname is not null
  and (
    logflag&1>0
  )
group by
  hostname
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )>0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
saas-Application-Discovered	All Applications Discovered on the Network	traffic

```
select
  (
    case is_saas when 1 then & #039;SaaS Apps' else 'Other Apps' end) as app_type, count
(distinct app_s) as total_num from ###(select app_s, (case when saas_s>=10 then 1 else 0
end) as is_saas from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s from $log
where $filter and apps is not null) t group by app_s, is_saas)### t group by is_saas order
by is_saas
```

Dataset Name	Description	Log Category
saas-SaaS-Application-by-Category	Number of SaaS Applications by Category	traffic

```
select
  (
    case saas_cat when 0 then & #039;Sanctioned' else 'Unsanctioned' end) as saas_cat_str,
count(distinct app_s) as num_saas_app from ###(select app_s, saas_s%10 as saas_cat, sum
(sentbyte+rcvdbyte) as bandwidth, count(*) as total_app from (select unnest(apps) as app_s,
unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as
rcvdbyte from $log where $filter and apps is not null) t where saas_s>=10 group by app_s,
saas_cat order by bandwidth desc)### t where saas_cat in (0, 1) group by saas_cat order by
saas_cat
```

Dataset Name	Description	Log Category
saas-SaaS-Application-by-Bandwidth	Number of SaaS Applications by Bandwidth	traffic

```
select
(
case saas_cat when 0 then & #039;Sanctioned' else 'Tolerated' end) as saas_cat_str, sum
(bandwidth) as bandwidth from ###(select app_s, saas_s%10 as saas_cat, sum
(sentbyte+rcvdbyte) as bandwidth, count(*) as total_app from (select unnest(apps) as app_s,
unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as
rcvdbyte from $log where $filter and apps is not null) t where saas_s>=10 group by app_s,
saas_cat order by bandwidth desc)### t where saas_cat in (0, 2) group by saas_cat order by
saas_cat
```

Dataset Name	Description	Log Category
saas-SaaS-Application-by-Session	Number of SaaS Applications by Session	traffic

```
select
(
case saas_cat when 0 then & #039;Sanctioned' else 'Tolerated' end) as saas_cat_str, sum
(total_app) as total_app from ###(select app_s, saas_s%10 as saas_cat, sum
(sentbyte+rcvdbyte) as bandwidth, count(*) as total_app from (select unnest(apps) as app_s,
unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as
rcvdbyte from $log where $filter and apps is not null) t where saas_s>=10 group by app_s,
saas_cat order by bandwidth desc)### t where saas_cat in (0, 2) group by saas_cat order by
saas_cat
```

Dataset Name	Description	Log Category
saas-SaaS-App-Users-vs-Others	Number of Users of SaaS Apps vs Others	traffic

```
select
(
case is_saas when 0 then & #039;Other Apps' else 'SaaS Apps' end) as app_type, count
(distinct saasuser) as total_user from ###(select saasuser, saas_s/10 as is_saas from
(select coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`), srcname,
ipstr(`srcip`)) as saasuser, unnest(saasinfo) as saas_s from $log where $filter and apps is
not null) t group by saasuser, is_saas)### t group by app_type
```

Dataset Name	Description	Log Category
saas-SaaS-App-Users	Number of Users of SaaS Apps	traffic

```
select
(
case saas_cat when 0 then & #039;Sanctioned' when 1 then 'Unsanctioned' else 'Others'
end) as app_type, count(distinct saasuser) as total_user from ###(select saasuser, saas_s%10
as saas_cat from (select coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna
(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser, unnest(saasinfo) as saas_s from $log
where $filter and apps is not null) t where saas_s>=10 group by saasuser, saas_cat)### t
group by saas_cat order by saas_cat
```


Dataset Name	Description	Log Category
saas-Top-SaaS-User-by-Bandwidth-Session	Top SaaS Users by Bandwidth and Session	traffic

```
select
  saasuser,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
    sum(sessions)- sum(session_block)
  ) as session_pass,
  count(distinct app_s) as total_app
from
  ###(select saasuser, app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as traffic_in, sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_block
from (select coalesce(nullifna('user'), nullifna('clouduser'), nullifna('unauthuser'),
srcname, ipstr('srcip')) as saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_s,
coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN
(logflag&2>0) THEN 1 ELSE 0 END) as is_blocked from $log where $filter and apps is not null)
t where saas_s>=10 group by saasuser, app_s order by bandwidth desc)### t group by saasuser
order by bandwidth desc
```

Dataset Name	Description	Log Category
saas-Top-Category-by-SaaS-Application-Usage	Top Categories by SaaS Application Usage	traffic

```
select
  app_cat,
  (
    case saas_cat when 0 then & #039;Sanctioned' else 'Unsactioned' end) as saas_cat_str,
  count(distinct app_s) as total_app from ###(select app_s, saas_s%10 as saas_cat from (select
unnest(apps) as app_s, unnest(saasinfo) as saas_s from $log where $filter and apps is not
null) t where saas_s>=10 group by app_s, saas_cat)### t1 inner join app_mdata t2 on t1.app_
s=t2.name where saas_cat in (0, 1) group by app_cat, saas_cat order by total_app desc
```

Dataset Name	Description	Log Category
saas-Top-SaaS-Category-by-Number-of-User	Top SaaS Categories by Number of Users	traffic

```
select
  app_cat,
  (
    case saas_cat when 0 then & #039;Sanctioned' else 'Unsactioned' end) as saas_cat_str,
  count(distinct saasuser) as total_user from ###(select app_s, saas_s%10 as saas_cat,
saasuser from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s, coalesce(nullifna
('user'), nullifna('clouduser'), nullifna('unauthuser'), srcname, ipstr('srcip')) as
saasuser from $log where $filter and apps is not null) t where saas_s>=10 group by app_s,
saas_cat, saasuser)### t1 inner join app_mdata t2 on t1.app_s=t2.name where saas_cat in (0,
1) group by app_cat, saas_cat order by total_user desc
```

Dataset Name	Description	Log Category
saas-Top-User-by-Number-of-SaaS-Application	Top Users by Number of SaaS Applications	traffic

```
select
  saasuser,
  (
    case saas_cat when 0 then & #039;Sanctioned' else 'Unsactioned' end) as saas_cat_str,
  count(distinct app_s) as total_app from ###(select app_s, saas_s%10 as saas_cat, saasuser
from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s, coalesce(nullifna(`user`),
nullifna(`clouduser`), nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser from
$log where $filter and apps is not null) t where saas_s>=10 group by app_s, saas_cat,
saasuser)### t where saas_cat in (0, 1) group by saasuser, saas_cat order by total_app desc
```

Dataset Name	Description	Log Category
saas-Top-SaaS-Application-by-Bandwidth-Session	Top SaaS Applications by Sessions and Bandwidth	traffic

```
select
  t2.id as app_id,
  app_s,
  app_cat,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
    sum(sessions)- sum(session_block)
  ) as session_pass
from
  ###(select app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as traffic_in, sum
(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_block from
(select unnest(apps) as app_s, unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as
sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN (logflag&2>0) THEN 1 ELSE 0 END) as
is_blocked from $log where $filter and apps is not null) t where saas_s>=10 group by app_
s)### t1 inner join app_mdata t2 on t1.app_s=t2.name group by app_id, app_s, app_cat order
by bandwidth desc
```

Dataset Name	Description	Log Category
saas-Top-Tolerated-SaaS-Application-by-Bandwidth	Top Tolerated SaaS Applications by Bandwidth	traffic

```
select
  app_s,
  sum(sentbyte + rcvdbyte) as bandwidth
from
  (
    select
      unnest(apps) as app_s,
      unnest(saasinfo) as saas_s,
      coalesce(sentbyte, 0) as sentbyte,
```

```

        coalesce(rcvdbyte, 0) as rcvdbyte
    from
        $log
    where
        $filter
        and apps is not null
    ) t
where
    saas_s = 12
group by
    app_s
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
saas-drilldown-Top-Tolerated-SaaS-Application	Top Tolerated SaaS Applications	traffic

```

select
    app_s,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out,
    sum(sessions) as sessions,
    sum(session_block) as session_block,
    (
        sum(sessions) - sum(session_block)
    ) as session_pass
from
    ###(select saasuser, app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as traffic_in,
    sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_block
    from (select coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`),
    srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_s,
    coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN
    (logflag&2>0) THEN 1 ELSE 0 END) as is_blocked from $log where $filter and apps is not null)
    t where saas_s=12 group by saasuser, app_s order by bandwidth desc)### t where $filter-
    drilldown group by app_s order by bandwidth desc

```

Dataset Name	Description	Log Category
saas-Top-User-by-Tolerated-SaaS-Application-Drilldown	Top Users by Tolerated SaaS Applications	traffic

```

select
    saasuser,
    count(distinct app_s) as total_app
from
    ###(select saasuser, app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as traffic_in,
    sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_block
    from (select coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`),
    srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_s,
    coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN
    (logflag&2>0) THEN 1 ELSE 0 END) as is_blocked from $log where $filter and apps is not null)
    t where saas_s=12 group by saasuser, app_s order by bandwidth desc)### t group by saasuser
    order by total_app desc

```

Dataset Name	Description	Log Category
saas-drilldown-Top-File-Sharing-SaaS-Application-Detail	Top File Sharing SaaS Applications Detail	traffic

```
select
  saasuser,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
    sum(sessions)- sum(session_block)
  ) as session_pass
from
  ###(select app_group_name(app_s) as app_group, saasuser, sum(sentbyte+rcvdbyte) as
bandwidth, sum(rcvdbyte) as traffic_in, sum(sentbyte) as traffic_out, count(*) as sessions,
sum(is_blocked) as session_block from (select coalesce(nullifna(`user`), nullifna
(`clouduser`), nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as
app_s, unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0)
as rcvdbyte, (CASE WHEN (logflag&2>0) THEN 1 ELSE 0 END) as is_blocked from $log where
$filter and apps is not null) t where saas_s>=10 group by app_group, saasuser order by
bandwidth desc)### t where $filter-drilldown group by saasuser order by sessions desc
```

Dataset Name	Description	Log Category
saas-Top-File-Sharing-SaaS-Application	Top File Sharing Applications	traffic

```
select
  t2.id as appid,
  (
    case t2.risk when & #039;5' then 'Critical' when '4' then 'High' when '3' then 'Medium'
when '2' then 'Info' else 'Low' end) as risk, app_group, bandwidth, traffic_in, traffic_out,
sessions, session_block, session_pass, total_user from (select app_group, count(distinct
saasuser) as total_user, sum(bandwidth) as bandwidth, sum(traffic_in) as traffic_in, sum
(traffic_out) as traffic_out, sum(sessions) as sessions, sum(session_block) as session_
block, (sum(sessions)-sum(session_block)) as session_pass from ###(select app_group_name
(app_s) as app_group, saasuser, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as
traffic_in, sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_
block from (select coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`),
srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_s,
coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN
(logflag&2>0) THEN 1 ELSE 0 END) as is_blocked from $log where $filter and apps is not null)
t where saas_s>=10 group by app_group, saasuser order by bandwidth desc)### t group by app_
group) t1 inner join app_mdata t2 on lower(t1.app_group)=lower(t2.name) where t2.app_
cat='Storage.Backup' order by total_user desc, bandwidth desc
```

Dataset Name	Description	Log Category
saas-Top-File-Sharing-SaaS-Application-Drilldown	Top File Sharing Applications	traffic

```
select
  t2.id as appid,
  (
    case t2.risk when & #039;5' then 'Critical' when '4' then 'High' when '3' then 'Medium'
when '2' then 'Info' else 'Low' end) as risk, app_group, bandwidth, traffic_in, traffic_out,
sessions, session_block, session_pass, total_user from (select app_group, count(distinct
saasuser) as total_user, sum(bandwidth) as bandwidth, sum(traffic_in) as traffic_in, sum
(traffic_out) as traffic_out, sum(sessions) as sessions, sum(session_block) as session_
block, (sum(sessions)-sum(session_block)) as session_pass from ###(select app_group_name
(app_s) as app_group, saasuser, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as
traffic_in, sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_
block from (select coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`),
srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_s,
coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN
(logflag&2>0) THEN 1 ELSE 0 END) as is_blocked from $log where $filter and apps is not null)
t where saas_s>=10 group by app_group, saasuser order by bandwidth desc)### t group by app_
group) t1 inner join app_mdata t2 on lower(t1.app_group)=lower(t2.name) where t2.app_
cat='Storage.Backup' order by total_user desc, bandwidth desc
```

Dataset Name	Description	Log Category
aware-Device-By-Location	Device by Location	traffic

```
select
  & #039;All'::text as country, count(distinct devid) as device_count from ###(select devid
from $log where $filter group by devid)### t
```

Dataset Name	Description	Log Category
aware-Network-Endpoint-Devices	Endpoint Devices on Network	

```
select
  category,
  total_num
from
  (
    select
      & #039;Seen Devices' as category, 1 as idx, count(distinct epname) as total_num from
(select epname, map_dev.devid, map_dev.vd, max(lastseen) as itime from $ADOM_ENDPOINT t
inner join $ADOM_EPEU_DEVMAP map_dev on t.epid=map_dev.epid where epname is not null group
by epname, map_dev.devid, map_dev.vd) t where $filter and $filter-drilldown union all select
'New Devices' as category, 2 as idx, count(distinct epname) as total_num from (select
epname, map_dev.devid, map_dev.vd, min(firstseen) as itime from $ADOM_ENDPOINT t inner join
$ADOM_EPEU_DEVMAP map_dev on t.epid=map_dev.epid where epname is not null group by epname,
map_dev.devid, map_dev.vd) t where $filter and $filter-drilldown union all select 'Unseen
Devices' as category, 3 as idx, count(distinct t1.epname) as total_num from $ADOM_ENDPOINT
t1 where not exists (select 1 from (select epname, map_dev.devid, map_dev.vd, max(lastseen)
as itime from $ADOM_ENDPOINT t inner join $ADOM_EPEU_DEVMAP map_dev on t.epid=map_dev.epid
where epname is not null group by epname, map_dev.devid, map_dev.vd) t2 where $filter and
$filter-drilldown and t1.epname=t2.epname)) t order by idx
```

Dataset Name	Description	Log Category
aware-New-Endpoint-Devices	New Endpoint Devices	

```

drop
  table if exists devmap_tmp; create temporary table devmap_tmp as (
    select
      epid,
      max(euid) as max_euid
    from
      $ADOM_EPEU_DEVMAP
    where
      euid >= 1024
    group by
      epid
  );
select
  timestamp,
  epname as hostname,
  max(osname) as osname,
  max(devtype) as devtype,
  max(srcip) as srcip,
  string_agg(
    distinct epname,
    & #039;;,'') as user_agg from (select from_itime(itime) as timestamp, osname, epname,
  epdevtype as devtype, epip as srcip, epid from (select max(osname) as osname, max(epname) as
  epname, max(epdevtype) as epdevtype, max(epip) as epip, t.epid, map_dev.devid, map_dev.vd,
  min(firstseen) as itime from $ADOM_ENDPOINT t inner join $ADOM_EPEU_DEVMAP map_dev on
  t.epid=map_dev.epid where epname is not null group by epname, t.epid, map_dev.devid, map_
  dev.vd) t where $filter and $filter-drilldown) t1 inner join devmap_tmp on devmap_
  tmp.epid=t1.epid inner join $ADOM_ENDUSER as teu on devmap_tmp.max_euid=teu.euid group by
  timestamp, hostname order by timestamp desc

```

Dataset Name	Description	Log Category
aware-New-Endpoint-Devices-Trend	New Endpoint Devices Trend	

```

select
  $flex_timescale(itime) as hodex,
  count(distinct epname) as total_num
from
  (
    select
      epname,
      map_dev.devid,
      map_dev.vd,
      min(firstseen) as itime
    from
      $ADOM_ENDPOINT t
      inner join $ADOM_EPEU_DEVMAP map_dev on t.epid = map_dev.epid
    where
      epname is not null
    group by
      epname,
      map_dev.devid,
      map_dev.vd
  ) t
where
  $filter
  and $filter - drilldown

```

```
group by
  horex
order by
  horex
```

Dataset Name	Description	Log Category
aware-Top-Endpoint-Operating-Systems	Top Endpoint Operating Systems	fct-traffic

```
select
  os1 as os,
  count(distinct hostname) as total_num
from
  ###(select split_part(os, ',', 1) as os1, hostname from $log where $filter and nullifna
  (os) is not null group by os1, hostname)### t group by os order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Endpoint-Applications-Windows	Top Endpoint Applications Windows	fct-traffic

```
select
  srcname1 as srcname,
  count(distinct hostname) as total_num
from
  ###(select split_part(srcname, '.', 1) as srcname1, hostname from $log where $filter and
  nullifna(srcname) is not null and lower(os) like '%windows%' group by srcname, hostname)### t
  group by srcname order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Endpoint-Applications-Mac	Top Endpoint Applications Mac	fct-traffic

```
select
  srcname1 as srcname,
  count(distinct hostname) as total_num
from
  ###(select split_part(srcname, '.', 1) as srcname1, hostname from $log where $filter and
  nullifna(srcname) is not null and lower(os) like '%mac os%' group by srcname, hostname)### t
  group by srcname order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-SaaS-Application-by-Number-of-Users	Top SaaS Applications by Number of Users	traffic

```
select
  app_group,
  count(distinct saasuser) as total_user
from
  ###(select app_group_name(app_s) as app_group, saasuser from (select unnest(apps) as app_
  s, unnest(saasinfo) as saas_s, coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna
  (`unauthuser`), srcname, ipstr(`srcip`)) as saasuser from $log where $filter and
  (logflag&1>0) and apps is not null) t where saas_s>=10 group by app_group, saasuser)### t
  group by app_group order by total_user desc
```

Dataset Name	Description	Log Category
aware-Summary-Of-Changes	Summary of Changes	event

```
select
  regexp_replace(
    msg,
    & #039;[^ ]*$','') as msg_trim, count(*) as total_num from $log where $filter and logid_
to_int(logid)=44547 group by msg_trim order by total_num desc
```

Dataset Name	Description	Log Category
aware-Change-Details	Change Details	event

```
select
  $calendar_time as timestamp,
  `user`,
  ui,
  msg
from
  $log
where
  $filter
  and logid_to_int(logid)= 44547
order by
  timestamp desc
```

Dataset Name	Description	Log Category
aware-Vulnerabilities-By-Severity	Vulnerabilities by Security	fct-netscan

```
select
  vulnseverity,
  count(distinct vulnname) as vuln_num
from
  ###(select vulnseverity, vulnname from $log where $filter and nullifna(vulnname) is not
null and nullifna(vulnseverity) is not null group by vulnseverity, vulnname)### t group by
vulnseverity order by vuln_num desc
```

Dataset Name	Description	Log Category
aware-Vulnerabilities-Trend	Vulnerabilities Trend	fct-netscan

```
select
  $flex_timescale(timestamp) as timescale,
  sum(critical) as critical,
  sum(high) as high,
  sum(medium) as medium,
  sum(low) as low
from
  ###(select $flex_timestamp as timestamp, sum(case when lower(vulnseverity) = 'critical'
then 1 else 0 end) as critical, sum(case when lower(vulnseverity) = 'high' then 1 else 0
end) as high, sum(case when lower(vulnseverity) = 'medium' then 1 else 0 end) as medium, sum
(case when lower(vulnseverity) = 'notice' then 1 else 0 end) as Low from $log where $filter
group by timestamp order by timestamp desc)### t group by timescale order by timescale
```


Dataset Name	Description	Log Category
aware-Top-Critical-Vulnerabilities	Top Critical Vulnerabilities	fct-netscan

```
select
  vulnname,
  vulnseverity,
  vulncat,
  count(distinct hostname) as total_num
from
  ###(select hostname, vulnname, vulnseverity, vulncat, count(*) as total_num from $log
where $filter and nullifna(vulnname) is not null and vulnseverity='Critical' group by
hostname, vulnname, vulnseverity, vulncat order by total_num desc)### t group by vulnname,
vulnseverity, vulncat order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Vulnerabilities-Last-Period	Top Vulnerabilities Last Period	fct-netscan

```
select
  vulnname,
  vulnseverity,
  sev_num,
  vulncat,
  count(distinct hostname) as total_num
from
  ###(select hostname, vulnname, vulnseverity, (CASE vulnseverity WHEN 'Critical' THEN 5
WHEN 'High' THEN 4 WHEN 'Medium' THEN 3 WHEN 'Info' THEN 2 WHEN 'Low' THEN 1 ELSE 0 END) as
sev_num, vulncat, count(*) as total_num from $log where $pre_period $filter and nullifna
(vulnname) is not null group by hostname, vulnname, vulnseverity, vulncat order by sev_num
desc, total_num desc)### t group by vulnname, vulnseverity, sev_num, vulncat order by sev_
num desc, total_num desc
```

Dataset Name	Description	Log Category
aware-Top-New-Vulnerabilities	Top New Vulnerabilities	fct-netscan

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  vulnid,
  vulnname,
  vulnseverity,
  vulncat,
  hostname
from
  ###(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $pre_period
$filter and nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; create temporary
table rpt_tmptbl_2 as select vulnid, vulnname, vulnseverity, vulncat, hostname from ###
(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $filter and
nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; select vulnname,
(case when vulnseverity='Critical' then 5 when vulnseverity='High' then 4 when
```

```
vulnseverity='Medium' then 3 when vulnseverity='Low' then 2 when vulnseverity='Info' then 1
else 0 end) as sev, vulnseverity, vulncat, count(distinct hostname) as host_num, cve_id from
rpt_tmptbl_2 t1 left join fct_mdata t2 on t1.vulnid=t2.vid::int where not exists (select 1
from rpt_tmptbl_1 where t1.vulnid=rpt_tmptbl_1.vulnid) group by vulnname, sev, vulnseverity,
vulncat, cve_id order by sev desc, host_num desc
```

Dataset Name	Description	Log Category
aware-Top-User-With-Critical-Vulnerabilities	Top Users with Critical Vulnerabilities	fct-netscan

```
select
  hostname,
  `user` as user_src,
  vulnname,
  vulncat,
  count(*) as total_num
from
  $log
where
  $filter
  and nullifna(`user`) is not null
  and vulnseverity =& #039;Critical' group by hostname, user_src, vulnname, vulncat order by
total_num desc
```

Dataset Name	Description	Log Category
aware-Ingress-Data-Flow-By-Zone	Ingress Data Flow By Zone	traffic

```
select
  app,
  tag,
  sum(rcvdbyte) as rcvdbyte
from
  ###(select dvid, app, dstintf, sum(coalesce(rcvdbyte, 0)) as rcvdbyte from $log where
$filter group by dvid, app, dstintf having sum(coalesce(rcvdbyte, 0)) > 0 order by rcvdbyte
desc)### tt1 inner join (select dvid, intfname, unnest(tags) as tag from intfinfo) tt2 on
tt1.dvid=tt2.dvid and tt1.dstintf=tt2.intfname group by app, tag order by rcvdbyte desc
```

Dataset Name	Description	Log Category
aware-Egress-Data-Flow-By-Zone	Egress Data Flow By Zone	traffic

```
select
  app,
  tag,
  sum(sentbyte) as sentbyte
from
  ###(select dvid, app, srcintf, sum(coalesce(sentbyte, 0)) as sentbyte from $log where
$filter group by dvid, app, srcintf having sum(coalesce(sentbyte, 0)) > 0 order by sentbyte
desc)### tt1 inner join (select dvid, intfname, unnest(tags) as tag from intfinfo) tt2 on
tt1.dvid=tt2.dvid and tt1.srcintf=tt2.intfname group by app, tag order by sentbyte desc
```

Dataset Name	Description	Log Category
aware-Top-Device-Attack-Targets	Top Device Attack Targets	fct-netscan

```

select
  hostname,
  count(*) as total_num
from
  $log
where
  $filter
  and nullifna(hostname) is not null
  and nullifna(vulnname) is not null
group by
  hostname
order by
  total_num desc

```

Dataset Name	Description	Log Category
aware-Top-Attack-Targets	Top Attack Targets	fct-netscan

```

select
  hostname,
  srcip,
  os,
  vuln_num,
  (
    CASE sevid WHEN 5 THEN & #039;Critical' WHEN 4 THEN 'High' WHEN 3 THEN 'Medium' WHEN '2'
    THEN 'Info' ELSE 'Low' END) as vulnseverity, sevid as severity_num, left(cve_agg, 512) as
    cve_agg from (select hostname, max(srcip) as srcip, string_agg(distinct os1, '/') as os,
    count(distinct vulnname) as vuln_num, max((CASE vulnseverity WHEN 'Critical' THEN 5 WHEN
    'High' THEN 4 WHEN 'Medium' THEN 3 WHEN 'Info' THEN 2 WHEN 'Low' THEN 1 ELSE 0 END)) as
    sevid, string_agg(distinct cve_id, ',') as cve_agg from ###(select hostname, max(deviceip)
    as srcip, split_part(os, ',', 1) as os1, vulnname, vulnseverity, vulnid from $log where
    $filter and nullifna(vulnname) is not null and nullifna(vulnseverity) is not null group by
    hostname, os1, vulnname, vulnseverity, vulnid)### t1 left join fct_mdata t2 on
    t1.vulnid=t2.vid::int group by hostname) t order by severity_num desc, vuln_num desc

```

Dataset Name	Description	Log Category
aware-Threats-By-Severity	Threats by Severity	attack

```

select
  initcap(sev) as severity,
  sum(total_num) as total_num
from
  (
    ###(select crlevel::text as sev, count(*) as total_num from $log-virus where $filter and
    nullifna(virus) is not null and crlevel is not null group by sev order by total_num
    desc)### union all ###(select severity::text as sev, count(*) as total_num from $log-attack
    where $filter and nullifna(attack) is not null and severity is not null group by sev order
    by total_num desc)### union all ###(select apprisk::text as sev, count(*) as total_num from
    $log-app-ctrl where $filter and lower(appcat)='botnet' and apprisk is not null group by sev
    order by total_num desc)###) t group by severity order by total_num desc

```

Dataset Name	Description	Log Category
aware-Threats-Type-By-Severity	Threats Type by Severity	virus

```

select
    threat_type,
    sum(critical) as critical,
    sum(high) as high,
    sum(medium) as medium,
    sum(low) as low
from
    (
        ###(select (case when eventtype='botnet' then 'Botnets' else 'Malware' end) as threat_
type, sum(case when crlevel = 'critical' then 1 else 0 end) as critical, sum(case when
crlevel = 'high' then 1 else 0 end) as high, sum(case when crlevel = 'medium' then 1 else 0
end) as medium, sum(case when crlevel = 'low' then 1 else 0 end) as low from $log-virus
where $filter and nullifna(virus) is not null group by threat_type)### union all ###(select
'Intrusions' as threat_type, sum(case when severity = 'critical' then 1 else 0 end) as
critical, sum(case when severity = 'high' then 1 else 0 end) as high, sum(case when severity
= 'medium' then 1 else 0 end) as medium, sum(case when severity = 'low' then 1 else 0 end)
as low from $log-attack where $filter and nullifna(attack) is not null group by threat_
type)### union all ###(select 'Botnets' as threat_type, sum(case when apprisk = 'critical'
then 1 else 0 end) as critical, sum(case when apprisk = 'high' then 1 else 0 end) as high,
sum(case when apprisk = 'medium' then 1 else 0 end) as medium, sum(case when apprisk = 'low'
then 1 else 0 end) as low from $log-app-ctrl where $filter and lower(appcat)='botnet' group
by threat_type)###) t group by threat_type

```

Dataset Name	Description	Log Category
aware-Threats-By-Day	Threats by Day	virus

```

select
    daystamp,
    sum(total_num) as total_num
from
    (
        ###(select $day_of_week as daystamp, count(*) as total_num from $log-virus where $filter
and nullifna(virus) is not null group by daystamp)### union all ###(select $day_of_week as
daystamp, count(*) as total_num from $log-attack where $filter and nullifna(attack) is not
null group by daystamp)### union all ###(select $day_of_week as daystamp, count(*) as total_
num from $log-app-ctrl where $filter and lower(appcat)='botnet' group by daystamp)###) t
group by daystamp order by daystamp

```

Dataset Name	Description	Log Category
aware-Threats-By-Day-Radar	Threats by Day	virus

```

select
    daystamp,
    sum(total_num) as total_num
from
    (
        ###(select $day_of_week as daystamp, count(*) as total_num from $log-virus where $filter
and nullifna(virus) is not null group by daystamp)### union all ###(select $day_of_week as
daystamp, count(*) as total_num from $log-attack where $filter and nullifna(attack) is not
null group by daystamp)### union all ###(select $day_of_week as daystamp, count(*) as total_
num from $log-app-ctrl where $filter and lower(appcat)='botnet' group by daystamp)###) t
group by daystamp order by daystamp

```

Dataset Name	Description	Log Category
aware-Count-Of-Malware-Events	Count of Malware Events	virus

```
select
    virus,
    count(*) as total_num
from
    $log
where
    $filter
    and nullifna(virus) is not null
group by
    virus
order by
    total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Malware-By-Count	Top Malware by Count	app-ctrl

```
select
    virus,
    malware_type,
    risk_level,
    count(distinct dstip) as victim,
    count(distinct srcip) as source,
    sum(total_num) as total_num
from
    (
        ###(select app as virus, 'Botnet C&C' as malware_type, apprisk::text as risk_level,
        dstip, srcip, count(*) as total_num from $log-app-ctrl where $filter and lower
        (appcat)='botnet' and apprisk is not null group by app, malware_type, apprisk, dstip, srcip
        order by total_num desc)### union all ###(select virus, (case when eventtype='botnet' then
        'Botnet C&C' else 'Virus' end) as malware_type, crlevel::text as risk_level, dstip, srcip,
        count(*) as total_num from $log-virus where $filter and nullifna(virus) is not null and
        crlevel is not null group by virus, malware_type, crlevel, dstip, srcip order by total_num
        desc)### union all ###(select attack as virus, (case when eventtype='botnet' then 'Botnet
        C&C' else 'Virus' end) as malware_type, crlevel::text as risk_level, dstip, srcip, count(*)
        as total_num from $log-attack where $filter and (logflag&16>0) and crlevel is not null group
        by virus, malware_type, crlevel, dstip, srcip order by total_num desc)###) t group by virus,
        malware_type, risk_level order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Failed-Login-Attempts	Top Failed Login Attempts	event

```
select
    `user` as f_user,
    ui,
    dstip,
    count(status) as total_failed
from
    $log
where
    $filter
```

```

    and nullifna(`user`) is not null
    and logid_to_int(logid) = 32002
group by
    ui,
    f_user,
    dstip
order by
    total_failed desc

```

Dataset Name	Description	Log Category
aware-Top-Failed-Authentication-Attempts	VPN failed logins	event

```

select
    f_user,
    tunneltype,
    sum(total_num) as total_num
from
    ###(select coalesce(nullifna(`xauthuser`), `user`) as f_user, tunneltype, count(*) as
total_num from $log where $filter and subtype='vpn' and (tunneltype='ipsec' or left
(tunneltype, 3)='ssl') and action in ('ssl-login-fail', 'ipsec-login-fail') and coalesce
(nullifna(`xauthuser`), nullifna(`user`)) is not null group by f_user, tunneltype)### t
group by f_user, tunneltype order by total_num desc

```

Dataset Name	Description	Log Category
aware-Top-Denied-Connections	Top Denied Connections	traffic

```

select
    coalesce(
        nullifna(`user`),
        ipstr(`srcip`)
    ) as user_src,
    service || & #039;(' || ipstr(srcip) || '))' as interface, dstip, count(*) as total_num
from $log where $filter and (logflag&l>0) and action = 'deny' group by user_src, interface,
dstip order by total_num desc

```

Dataset Name	Description	Log Category
aware-Failed-Compliance-Checked-By-Device	Failed Compliance Checked by Device	event

```

select
    devid,
    & #039;Failed' as results, count(distinct reason) as total_num from ###(select devid,
reason from $log where $filter and subtype='compliance-check' and result='fail' group by
devid, reason)### t group by devid, results order by total_num desc

```

Dataset Name	Description	Log Category
aware-loc-Blacklist-Summary	IOC Blacklist Summary	app-ctrl

```

drop
    table if exists tmp_ep_eu_map; create temporary table tmp_ep_eu_map as (
        select

```

```

        epid,
        euid
    from
        $ADOM_EPEU_DEVMAP
    where
        euid >= 1024
);
select
    coalesce(
        nullifna(epname),
        nullifna(
            ipstr(`srcip`)
        ),
        & #039;Unknown') as epname, user_agg, sevid, (CASE sevid WHEN 5 THEN 'Critical' WHEN 4
    THEN 'High' WHEN 3 THEN 'Medium' WHEN '2' THEN 'Info' ELSE 'Low' END) as severity, threats,
    bl_count as total_bl from (select th1.epid, srcip, sevid, bl_count, threats from (select
    epid, srcip, max(verdict)+1 as sevid, sum(bl_count) as bl_count from ((select epid, srcip,
    day_st as itime, bl_count, verdict, unnest(dvid) as dvid_s from $ADOMTBL_PLHD_IOC_VERDICT
    where bl_count>0) union all (select epid, srcip, day_st as itime, bl_count, verdict, unnest
    (dvid) as dvid_s from $ADOMTBL_PLHD_INTERIM_IOC_VERDICT where bl_count>0)) tvdt inner join
    devtable td on td.dvid = tvdt.dvid_s where $filter and $filter-drilldown and $dev_filter
    group by epid, srcip) th1 inner join (select epid, string_agg(name, ',') as threats from
    ((select epid, thid from ((select epid, thid, itime, unnest(dvid) as dvid_s from (select
    epid, unnest(threatid) as thid, day_st as itime, dvid from $ADOMTBL_PLHD_IOC_VERDICT where
    bl_count>0) ta1) union all (select epid, thid, itime, unnest(dvid) as dvid_s from (select
    epid, unnest(threatid) as thid, day_st as itime, dvid from $ADOMTBL_PLHD_INTERIM_IOC_VERDICT
    where bl_count>0) ta2)) t inner join devtable td on td.dvid = t.dvid_s where $filter and
    $filter-drilldown and $dev_filter group by epid, thid) thr inner join td_threat_name_mdata
    tm on tm.id=thr.thid) t group by epid) th2 on th1.epid=th2.epid) t1 left join (select epid,
    string_agg(distinct euname, ',') as user_agg from tmp_ep_eu_map tpu inner join $ADOM_ENDUSER
    as teu on tpu.euid=teu.euid group by epid) t2 on t2.epid=t1.epid inner join $ADOM_ENDPOINT
    as tep on tep.epid=t1.epid order by total_bl desc, sevid desc

```

Dataset Name	Description	Log Category
aware-loc-Potential-Breach-By-Day	IOC Potential Breach by Day	app-ctrl

```

select
    number,
    day_st as itime
from
    (
        select
            count(epid) as number,
            to_char(
                from_itime(itime),
                & #039;Day') as day_st from (select epid, day_st as itime, unnest(dvid) as dvid_s
    from $ADOMTBL_PLHD_INTERIM_IOC_VERDICT where cs_count>0 union all (select epid, day_st as
    itime, unnest(dvid) as dvid_s from $ADOMTBL_PLHD_IOC_VERDICT where cs_count>0)) t inner join
    devtable td on td.dvid = t.dvid_s where $filter and $filter-drilldown group by day_st) tt
    order by itime

```

Dataset Name	Description	Log Category
aware-loc-Potential-Breach-By-Day- Bar	IOC Potential Breach by Day	app-ctrl

```

select
  number,
  day_st as itime
from
  (
    select
      count(epid) as number,
      to_char(
        from_otime(itime),
        & #039;Day') as day_st from (select epid, day_st as itime, unnest(dvid) as dvid_s
from $ADOMTBL_PLHD_INTERIM_IOC_VERDICT where cs_count>0 union all (select epid, day_st as
itime, unnest(dvid) as dvid_s from $ADOMTBL_PLHD_IOC_VERDICT where cs_count>0)) t inner join
devtable td on td.dvid = t.dvid_s where $filter and $filter-drilldown group by day_st) tt
order by itime

```

Dataset Name	Description	Log Category
aware-loc-Suspicion-Summary	IOC Suspicion Summary	app-ctrl

```

select
  coalesce(
    nullifna(epname),
    nullifna(
      ipstr(`srcip`)
    ),
    & #039;Unknown') as epname, cs_count as total_cs, cs_score as max_cs, verdict as max_
verdict, threats from (select th1.epid, srcip, itime, cs_count, verdict, cs_score, threats
from (select epid, srcip, min(itime) as itime, sum(cs_count) as cs_count, max(verdict) as
verdict, max(cs_score) as cs_score from ((select epid, srcip, day_st as itime, cs_count,
verdict, cs_score, unnest(dvid) as dvid_s from $ADOMTBL_PLHD_IOC_VERDICT where bl_count=0
and cs_count>0) union all (select epid, srcip, day_st as itime, cs_count, verdict, cs_score,
unnest(dvid) as dvid_s from $ADOMTBL_PLHD_INTERIM_IOC_VERDICT where bl_count=0 and cs_
count>0)) tvdt inner join devtable td on td.dvid = tvdt.dvid_s where $filter and $filter-
drilldown group by epid, srcip) th1 inner join (select epid, string_agg(name, ',') as
threats from ((select epid, thid from ((select epid, thid, itime, unnest(dvid) as dvid_s
from (select epid, unnest(threatid) as thid, day_st as itime, dvid from $ADOMTBL_PLHD_IOC_
VERDICT where bl_count=0 and cs_count>0) ta1) union all (select epid, thid, itime, unnest
(dvid) as dvid_s from (select epid, unnest(threatid) as thid, day_st as itime, dvid from
$ADOMTBL_PLHD_INTERIM_IOC_VERDICT where bl_count=0 and cs_count>0) ta2)) tt1 inner join
devtable td on td.dvid = tt1.dvid_s where $filter and $filter-drilldown group by epid, thid)
thr inner join td_threat_name_mdata tm on tm.id=thr.thid) tt2 group by epid) th2 on
th1.epid=th2.epid) t inner join $ADOM_ENDPOINT as tep on tep.epid=t.epid order by max_
verdict desc, max_cs desc, total_cs desc

```

Dataset Name	Description	Log Category
aware-Botnet-IP	Top Source IP Affected by Botnet	virus

```

select
  f_user,
  srcip,
  string_agg(
    distinct `virus`,
    & #039;;') as virus_agg, count(distinct ipstr(`dstip`)) as dstip_cnt, max(action) as
action, sum(total_num) as total_num, min(from_otime(first_seen)) as first_seen, max(from_
itime(last_seen)) as last_seen from ###(select coalesce(nullifna(`user`), nullifna

```



```
(`unauthuser`)) as f_user, srcip, virus, dstip, max(action) as action, count(*) as total_num, min(itime) as first_seen, max(itime) as last_seen from $log where $filter and logid in ('0202009248', '0202009249') and virus is not null group by srcip, f_user, virus, dstip order by total_num desc)### t group by srcip, f_user order by total_num desc
```

Dataset Name	Description	Log Category
aware-Botnet-Domain	New Botnet Domains	dns

```
select
  botnet,
  count(distinct `qname`) as qname_cnt,
  count(
    distinct ipstr(`dstip`)
  ) as dnssvr_cnt,
  sum(total_num) as total_num,
  min(
    from_etime(first_seen)
  ) as first_seen,
  max(
    from_etime(last_seen)
  ) as last_seen
from
  ###(select coalesce(`botnetdomain`, ipstr(`botnetip`)) as botnet, qname, dstip, count(*)
  as total_num, min(nanosec_to_sec(eventtime)) as first_seen, max(nanosec_to_sec(eventtime))
  as last_seen from $log where $filter and logid in ('1501054601', '1501054600') group by
  botnet, qname, dstip order by total_num desc)### t group by botnet order by first_seen desc
```

Dataset Name	Description	Log Category
aware-High-Risk-URL-Category	Category of High Risk URLs	webfilter

```
select
  catdesc,
  string_agg(
    distinct hostname,
    & #039;;') as hostname_agg, max(action) as action, sum(total_num) as total_num, min
  (from_etime(first_seen)) as first_seen, max(from_etime(last_seen)) as last_seen from ###
  (select catdesc, hostname, max(action) as action, count(*) as total_num, min(itime) as
  first_seen, max(itime) as last_seen from $log where $filter and cat in (26, 61, 86, 88, 90,
  91, 93) group by catdesc, hostname order by total_num desc)### t group by catdesc order by
  total_num desc
```

Dataset Name	Description	Log Category
aware-Malicious-Files	Type of Malicious Files from AV and Sandbox	virus

```
select
  virus,
  left(url_agg, 1000) as url_agg,
  left(filename_agg, 1000) as filename_agg,
  quarskip,
  action,
  from_sandbox,
  total_num,
  first_seen,
```

```

last_seen
from
(
select
virus,
string_agg(
distinct url,
& #039;<br/>' ) as url_agg, string_agg(distinct filename, '<br/>') as filename_agg,
max(quarskip) as quarskip, max(action) as action, max(from_sandbox) as from_sandbox, sum
(total_num) as total_num, min(from_itime(first_seen)) as first_seen, max(from_itime(last_
seen)) as last_seen from ###(select virus, url, filename, max(quarskip) as quarskip, max
(action) as action, (case when logid in ('0211009234', '0211009235') then 1 else 0 end) as
from_sandbox, count(*) as total_num, min(itime) as first_seen, max(itime) as last_seen from
$log where $filter and virus is not null and logid in ('0211009234', '0201009235',
'0211008192', '0211008193', '0211008194', '0211008195') group by virus, url, filename, from_
sandbox order by total_num desc)### t group by virus) t order by total_num desc

```

Dataset Name	Description	Log Category
newthing-New-Users	New users	fct-traffic

```

drop
table if exists rpt_tmptbl_1;
drop
table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
f_user,
min(start_time) as start_time
from
###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as f_user, min(dtime) as start_time
from $log where $pre_period $filter group by f_user order by start_time desc)### t group by
f_user; create temporary table rpt_tmptbl_2 as select f_user, min(start_time) as start_time
from ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as f_user, min(dtime) as start_
time from $log where $filter group by f_user order by start_time desc)### t group by f_user;
select f_user, from_dtime(min(start_time)) as start_time from rpt_tmptbl_2 where f_user is
not null and not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.f_user=rpt_tmptbl_
1.f_user) group by f_user order by start_time desc

```

Dataset Name	Description	Log Category
newthing-New-Devices	New devices	fct-traffic

```

drop
table if exists rpt_tmptbl_1;
drop
table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
hostname,
os,
srcip,
fctver
from
###(select hostname, os, srcip, fctver from $log where $pre_period $filter and hostname is
not null group by hostname, os, srcip, fctver order by hostname)### t group by hostname, os,
srcip, fctver; create temporary table rpt_tmptbl_2 as select hostname, os, srcip, fctver
from ###(select hostname, os, srcip, fctver from $log where $filter and hostname is not null

```

```
group by hostname, os, srcip, fctver order by hostname)### t group by hostname, os, srcip,
fctver; select hostname, max(fctos_to_devtype(os)) as devtype, string_agg(distinct os, '/')
as os_agg, string_agg(distinct ipstr(srcip), '/') as srcip_agg, string_agg(distinct fctver,
'/') as fctver_agg from rpt_tmptbl_2 where not exists (select 1 from rpt_tmptbl_1 where rpt_
tmptbl_2.hostname=rpt_tmptbl_1.hostname) group by hostname order by hostname
```

Dataset Name	Description	Log Category
newthing-New-Software-Installed	New software installed	fct-traffic

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  srcproduct,
  hostname
from
  ###(select srcproduct, hostname from $log where $pre_period $filter and nullifna
(srcproduct) is not null group by srcproduct, hostname order by srcproduct)### t group by
srcproduct, hostname; create temporary table rpt_tmptbl_2 as select srcproduct, hostname
from ###(select srcproduct, hostname from $log where $filter and nullifna(srcproduct) is not
null group by srcproduct, hostname order by srcproduct)### t group by srcproduct, hostname;
select srcproduct, string_agg(distinct hostname, ',') as host_agg from rpt_tmptbl_2 where
not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.srcproduct=rpt_tmptbl_
1.srcproduct) group by srcproduct order by srcproduct
```

Dataset Name	Description	Log Category
newthing-New-Security-Threats	New security threats	virus

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  threat_name,
  cat_id,
  srcip
from
  (
    ###(select app as threat_name, 1 as cat_id, srcip from $log-app-ctrl where $pre_period
$filter and nullifna(app) is not null and lower(appcat)='botnet' group by threat_name, cat_
id, srcip)### union all ###(select virus as threat_name, 2 as cat_id, srcip from $log-virus
where $pre_period $filter and nullifna(virus) is not null group by threat_name, cat_id,
srcip)### union all ###(select attack as threat_name, 3 as cat_id, srcip from $log-attack
where $pre_period $filter and nullifna(attack) is not null group by threat_name, cat_id,
srcip)###) t; create temporary table rpt_tmptbl_2 as select daystamp, threat_name, cat_id,
srcip from (###(select $DAY_OF_MONTH as daystamp, app as threat_name, 1 as cat_id, srcip
from $log-app-ctrl where $filter and nullifna(app) is not null and lower(appcat)='botnet'
group by daystamp, threat_name, cat_id, srcip order by daystamp)### union all ###(select
$DAY_OF_MONTH as daystamp, virus as threat_name, 2 as cat_id, srcip from $log-virus where
$filter and nullifna(virus) is not null group by daystamp, threat_name, cat_id, srcip order
by daystamp)### union all ###(select $DAY_OF_MONTH as daystamp, attack as threat_name, 3
as cat_id, srcip from $log-attack where $filter and nullifna(attack) is not null group by
daystamp, threat_name, cat_id, srcip order by daystamp)###) t; select threat_name, (case
```

```
cat_id when 1 then 'Botnet' when 2 then 'Malware' when 3 then 'Attack' end) as threat_cat,
count(distinct srcip) as host_num, string_agg(distinct cve, ',') as cve_agg from rpt_tmptbl_
2 left join ips_mdata t2 on rpt_tmptbl_2.threat_name=t2.name where not exists (select 1 from
rpt_tmptbl_1 where rpt_tmptbl_2.threat_name=rpt_tmptbl_1.threat_name) group by threat_name,
threat_cat order by host_num desc
```

Dataset Name	Description	Log Category
newthing-dns-Botnet-Domain-IP	New Queried Botnet C&C Domains and IPs	dns

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  domain,
  malware_type,
  action_s as action,
  srcip,
  sevid
from
  ###(select coalesce(botnetdomain, ipstr(botnetip)) as domain, cast('Botnet C&C' as char
(32)) as malware_type, (case when action='block' then 'Blocked' when action='redirect' then
'Redirected' else 'Passed' end) as action_s, srcip, (CASE WHEN level IN ('critical',
'alert', 'emergency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN
level='notice' THEN 2 ELSE 1 END) as sevid, coalesce(botnetdomain, ipstr(botnetip)) as
sources_s, count(*) as total_num from $log where $pre_period $filter and (botnetdomain is
not null or botnetip is not null) group by domain, action_s, srcip, sevid order by sevid
desc)### t group by domain, malware_type, action, srcip, sevid; create temporary table rpt_
tmptbl_2 as select domain, malware_type, action_s as action, srcip, sevid from ###(select
coalesce(botnetdomain, ipstr(botnetip)) as domain, cast('Botnet C&C' as char(32)) as
malware_type, (case when action='block' then 'Blocked' when action='redirect' then
'Redirected' else 'Passed' end) as action_s, srcip, (CASE WHEN level IN ('critical',
'alert', 'emergency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN
level='notice' THEN 2 ELSE 1 END) as sevid, coalesce(botnetdomain, ipstr(botnetip)) as
sources_s, count(*) as total_num from $log where $filter and (botnetdomain is not null or
botnetip is not null) group by domain, action_s, srcip, sevid order by sevid desc)### t
group by domain, malware_type, action, srcip, sevid; select domain, srcip, sevid, (CASE
sevid WHEN 5 THEN 'Critical' WHEN 4 THEN 'High' WHEN 3 THEN 'Medium' WHEN '2' THEN 'Info'
ELSE 'Low' END) as severity from rpt_tmptbl_2 where (domain is not null and not exists
(select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.domain=rpt_tmptbl_1.domain)) or (srcip is not
null and not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.srcip=rpt_tmptbl_
1.srcip)) group by domain, srcip, sevid order by sevid desc, domain
```

Dataset Name	Description	Log Category
newthing-New-Security-Threats-Timeline	New security threats timeline	virus

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  threat_name,
  cat_id,
```

```

srcip
from
(
    ###(select app as threat_name, 1 as cat_id, srcip from $log-app-ctrl where $pre_period
$filter and nullifna(app) is not null and lower(appcat)='botnet' group by threat_name, cat_
id, srcip)### union all ###(select virus as threat_name, 2 as cat_id, srcip from $log-virus
where $pre_period $filter and nullifna(virus) is not null group by threat_name, cat_id,
srcip)### union all ###(select attack as threat_name, 3 as cat_id, srcip from $log-attack
where $pre_period $filter and nullifna(attack) is not null group by threat_name, cat_id,
srcip)###) t; create temporary table rpt_tmptbl_2 as select timestamp, threat_name, cat_id,
srcip from (###(select $flex_timestamp as timestamp, app as threat_name, 1 as cat_id, srcip
from $log-app-ctrl where $filter and nullifna(app) is not null and lower(appcat)='botnet'
group by timestamp, threat_name, cat_id, srcip order by timestamp)### union all ###(select
$flex_timestamp as timestamp, virus as threat_name, 2 as cat_id, srcip from $log-virus where
$filter and nullifna(virus) is not null group by timestamp, threat_name, cat_id, srcip order
by timestamp)### union all ###(select $flex_timestamp as timestamp, attack as threat_name, 3
as cat_id, srcip from $log-attack where $filter and nullifna(attack) is not null group by
timestamp, threat_name, cat_id, srcip order by timestamp)###) t; select $flex_datetime
(timestamp) as timescale, count(distinct srcip) as host_num, (case cat_id when 1 then
'Botnet' when 2 then 'Malware' when 3 then 'Attack' end) as threat_cat from rpt_tmptbl_2
where not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.threat_name=rpt_tmptbl_
1.threat_name) group by timescale, cat_id order by timescale, cat_id

```

Dataset Name	Description	Log Category
newthing-New-Vulnerability	New vulnerabilities	fct-netscan

```

drop
    table if exists rpt_tmptbl_1;
drop
    table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
    vulnid,
    vulnname,
    vulnseverity,
    vulncat,
    hostname
from
    ###(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $pre_period
$filter and nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; create temporary
table rpt_tmptbl_2 as select vulnid, vulnname, vulnseverity, vulncat, hostname from ###
(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $filter and
nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; select vulnname,
(case when vulnseverity='Critical' then 5 when vulnseverity='High' then 4 when
vulnseverity='Medium' then 3 when vulnseverity='Low' then 2 when vulnseverity='Info' then 1
else 0 end) as sev, vulnseverity, vulncat, count(distinct hostname) as host_num, cve_id from
rpt_tmptbl_2 t1 left join fct_mdata t2 on t1.vulnid=t2.vid::int where not exists (select 1
from rpt_tmptbl_1 where t1.vulnid=rpt_tmptbl_1.vulnid) group by vulnname, sev, vulnseverity,
vulncat, cve_id order by sev desc, host_num desc

```

Dataset Name	Description	Log Category
newthing-New-Vulnerability-Graph	New vulnerabilities (Graph)	fct-netscan

```

drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  vulnid,
  vulnname,
  vulnseverity,
  vulncat,
  hostname
from
  ###(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $pre_period
$filter and nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; create temporary
table rpt_tmptbl_2 as select vulnid, vulnname, vulnseverity, vulncat, hostname from ###
(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $filter and
nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; select
vulnseverity, count (distinct vulnid) as vuln_num from rpt_tmptbl_2 where not exists (select
1 from rpt_tmptbl_1 where rpt_tmptbl_2.vulnid=rpt_tmptbl_1.vulnid) group by vulnseverity
order by (case when vulnseverity='Critical' then 5 when vulnseverity='High' then 4 when
vulnseverity='Medium' then 3 when vulnseverity='Low' then 2 when vulnseverity='Info' then 1
else 0 end) desc

```

Dataset Name	Description	Log Category
newthing-System-Alerts	System Alerts	local-event

```

select
  from_itime(itime) as timestamp,
  msg
from
  $log
where
  $filter
  and msg is not null
  and level =& #039;critical' order by timestamp desc

```

Dataset Name	Description	Log Category
newthing-Configuration-Changes	Configuration Changes	event

```

select
  `user` as f_user,
  devid,
  from_dtime(dtime) as time_s,
  ui,
  msg
from
  $log
where
  $filter
  and cfgtid>0
order by
  time_s desc

```

Dataset Name	Description	Log Category
newthing-FortiGate-Upgrades	FortiGate Upgrades	event

```
select
  devid,
  from_dtime(dtime) as time_s,
  info[1] as intf,
  info[2] as prev_ver,
  info[3] as new_ver
from
  (
    select
      devid,
      dtime,
      regexp_matches(
        msg,
        & #039;from ([^ ]+) \\(((^[^ ]+) -> ([^ ]+)\\))' as info from $log where $filter and
action='restore-image') t order by time_s desc
```

Dataset Name	Description	Log Category
newthing-User-Upgrades	User Upgrades	fct-event

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  fgtserial,
  hostname,
  deviceip,
  os,
  dtime
from
  ###(select distinct on (fgtserial, hostname) fgtserial, hostname, deviceip, os, dtime from
$log where $pre_period $filter and hostname is not null order by fgtserial, hostname, dtime
desc)### t; create temporary table rpt_tmptbl_2 as select fgtserial, hostname, deviceip, os,
dtime from ###(select distinct on (fgtserial, hostname) fgtserial, hostname, deviceip, os,
dtime from $log where $filter and hostname is not null order by fgtserial, hostname, dtime
desc)### t; select distinct on (1, 2) t2.fgtserial as devid, t2.hostname, t2.deviceip, t1.os
as prev_os, t2.os as cur_os, from_dtime(t1.dtime) as time_s from rpt_tmptbl_2 t2 inner join
rpt_tmptbl_1 t1 on t2.fgtserial=t1.fgtserial and t2.hostname=t1.hostname and t2.os!=t1.os
order by devid, t2.hostname, t1.dtime desc
```

Dataset Name	Description	Log Category
GTP-List-of-APN-Used	List of APNs Used	gtp

```
select
  apn,
  from_dtime(
    min(first_seen)
  ) as first_seen,
  from_dtime(
    max(last_seen)
```

```

    ) as last_seen
from
    ###(select apn, min(dtime) as first_seen, max(dtime) as last_seen from $log where $filter
and nullifna(apn) is not null group by apn order by last_seen desc)### t group by apn order
by last_seen desc, first_seen

```

Dataset Name	Description	Log Category
GTP-Top-APN-by-Bytes	Top APNs by Bytes	gtp

```

select
    apn,
    sum(
        coalesce(`u-bytes`, 0)
    ) as total_bytes
from
    $log
where
    $filter
    and nullifna(apn) is not null
    and status =& #039;traffic-count' group by apn having sum(coalesce(`u-bytes`, 0))>0 order
by total_bytes desc

```

Dataset Name	Description	Log Category
GTP-Top-APN-by-Duration	Top APNs by Duration	gtp

```

select
    apn,
    sum(
        coalesce(duration, 0)
    ) as total_dura
from
    $log
where
    $filter
    and nullifna(apn) is not null
    and status =& #039;traffic-count' group by apn having sum(coalesce(duration, 0)) >0 order
by total_dura desc

```

Dataset Name	Description	Log Category
GTP-Top-APN-by-Packets	Top APNs by Number of Packets	gtp

```

select
    apn,
    sum(
        coalesce(`u-pkts`, 0)
    ) as total_num
from
    $log
where
    $filter
    and nullifna(apn) is not null
    and status =& #039;traffic-count' group by apn having sum(coalesce(`u-pkts`, 0))>0 order
by total_num desc

```


Dataset Name	Description	Log Category
Top10-dns-Botnet-Domain-IP	Top Queried Botnet C&C Domains and IPs	dns

```
select
  domain,
  malware_type,
  action,
  count(distinct srcip) as victims,
  count(distinct sources_s) as sources,
  sum(total_num) as total_num
from
  ###(select coalesce(botnetdomain, ipstr(botnetip)) as domain, cast('Botnet C&C' as char
(32)) as malware_type, (case when action='block' then 'Blocked' when action='redirect' then
'Redirected' else 'Passed' end) as action, srcip, (CASE WHEN level IN ('critical', 'alert',
'emergency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN
level='notice' THEN 2 ELSE 1 END) as sevid, coalesce(botnetdomain, ipstr(botnetip)) as
sources_s, count(*) as total_num from $log where $filter and (botnetdomain is not null or
botnetip is not null) group by domain, action, srcip, sevid order by sevid desc)### t group
by domain, malware_type, action order by total_num desc
```

Dataset Name	Description	Log Category
dns-Botnet-Usage	Top Queried Botnet C&C Domains and IPs	dns

```
select
  domain,
  malware_type,
  action,
  count(distinct srcip) as victims,
  count(distinct sources_s) as sources,
  sum(total_num) as total_num
from
  ###(select coalesce(botnetdomain, ipstr(botnetip)) as domain, cast('Botnet C&C' as char
(32)) as malware_type, (case when action='block' then 'Blocked' when action='redirect' then
'Redirected' else 'Passed' end) as action, srcip, (CASE WHEN level IN ('critical', 'alert',
'emergency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN
level='notice' THEN 2 ELSE 1 END) as sevid, coalesce(botnetdomain, ipstr(botnetip)) as
sources_s, count(*) as total_num from $log where $filter and (botnetdomain is not null or
botnetip is not null) group by domain, action, srcip, sevid order by sevid desc)### t group
by domain, malware_type, action order by total_num desc
```

Dataset Name	Description	Log Category
Dns-Detected-Botnet	Top Queried Botnet C&C Domains and IPs	dns

```
select
  domain,
  malware_type,
  action,
  count(distinct srcip) as victims,
  count(distinct sources_s) as sources,
  sum(total_num) as total_num
from
  ###(select coalesce(botnetdomain, ipstr(botnetip)) as domain, cast('Botnet C&C' as char
(32)) as malware_type, (case when action='block' then 'Blocked' when action='redirect' then
```

```
'Redirected' else 'Passed' end) as action, srcip, (CASE WHEN level IN ('critical', 'alert', 'emergency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN level='notice' THEN 2 ELSE 1 END) as sevid, coalesce(botnetdomain, ipstr(botnetip)) as sources_s, count(*) as total_num from $log where $filter and (botnetdomain is not null or botnetip is not null) group by domain, action, srcip, sevid order by sevid desc)### t group by domain, malware_type, action order by total_num desc
```

Dataset Name	Description	Log Category
dns-Botnet-Domain-IP	Queried Botnet C&C Domains and IPs	dns

```
select
  domain,
  srcip,
  sevid,
  (
    CASE sevid WHEN 5 THEN & #039;Critical' WHEN 4 THEN 'High' WHEN 3 THEN 'Medium' WHEN '2' THEN 'Info' ELSE 'Low' END) as severity from ###(select coalesce(botnetdomain, ipstr(botnetip)) as domain, cast('Botnet C&C' as char(32)) as malware_type, (case when action='block' then 'Blocked' when action='redirect' then 'Redirected' else 'Passed' end) as action, srcip, (CASE WHEN level IN ('critical', 'alert', 'emergency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN level='notice' THEN 2 ELSE 1 END) as sevid, coalesce(botnetdomain, ipstr(botnetip)) as sources_s, count(*) as total_num from $log where $filter and (botnetdomain is not null or botnetip is not null) group by domain, action, srcip, sevid order by sevid desc)### t group by domain, srcip, sevid order by sevid desc, domain
```

Dataset Name	Description	Log Category
dns-High-Risk-Source	High Risk Sources	dns

```
select
  srcip,
  sum(total_num) as total_num,
  sum(
    case when sevid = 5 then total_num else 0 end
  ) as num_cri,
  sum(
    case when sevid = 4 then total_num else 0 end
  ) as num_hig,
  sum(
    case when sevid = 3 then total_num else 0 end
  ) as num_med
from
  ###(select srcip, (CASE WHEN level IN ('critical', 'alert', 'emergency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN level='notice' THEN 2 ELSE 1 END) as sevid, count(*) as total_num from $log where $filter and srcip is not null group by srcip, sevid order by total_num desc)### t where sevid>=3 group by srcip having sum(total_num)>0 order by total_num desc
```

Dataset Name	Description	Log Category
dns-DNS-Request-Over-Time	DNS Request Over Time	dns

```
select
  $flex_timescale(timestamp) as timescale,
```

```

sum(
    case when sevid = 5 then total_num else 0 end
) as num_cri,
sum(
    case when sevid = 4 then total_num else 0 end
) as num_hig,
sum(
    case when sevid = 3 then total_num else 0 end
) as num_med,
sum(
    case when sevid = 2 then total_num else 0 end
) as num_inf,
sum(
    case when sevid = 1 then total_num else 0 end
) as num_low
from
    ###(select $flex_timestamp as timestamp, (CASE WHEN level IN ('critical', 'alert',
'emergency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN
level='notice' THEN 2 ELSE 1 END) as sevid, count(*) as total_num from $log where $filter
group by timestamp, sevid order by total_num desc)### t group by timescale order by
timescale

```

Dataset Name	Description	Log Category
dns-Top-Queried-Domain	Top Queried Domain	dns

```

select
    qname,
    count(*) as total_num
from
    $log
where
    $filter
    and qname is not null
group by
    qname
order by
    total_num desc

```

Dataset Name	Description	Log Category
dns-Top-Domain-Lookup-Failure-Bar	Top Domain Lookup Failures	dns

```

select
    qname,
    srcip,
    count(*) as total_num
from
    $log
where
    $filter
    and qname is not null
    and (
        action =& #039;block' or logid_to_int(logid)=54200) group by qname, srcip order by
total_num desc

```

Dataset Name	Description	Log Category
dns-Top-Domain-Lookup-Failure-Table	Top Domain Lookup Failures	dns

```
select
  qname,
  srcip,
  count(*) as total_num
from
  $log
where
  $filter
  and qname is not null
  and (
    action =& #039;block' or logid_to_int(logid)=54200) group by qname, srcip order by
total_num desc
```

Dataset Name	Description	Log Category
dns-Query-Timeout	Query Timeout	dns

```
select
  srcip,
  qname,
  count(*) as total_num
from
  $log
where
  $filter
  and srcip is not null
  and logid_to_int(logid)= 54200
group by
  qname,
  srcip
order by
  total_num desc
```

Dataset Name	Description	Log Category
dns-Blocked-Query	Blocked Queries	dns

```
select
  srcip,
  msg,
  count(*) as total_num
from
  $log
where
  $filter
  and srcip is not null
  and action =& #039;block' group by srcip, msg order by total_num desc
```

Dataset Name	Description	Log Category
perf-stat-cpu-usage-drilldown	Fortigate resource detail timeline	event

```
select
  horex,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps)/ count(*) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps)/ count(*) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  max(lograte_peak) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak,
  cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
  ) as cps_ave,
  max(cps_peak) as cps_peak
from
  (
    select
      horex,
      devid,
      get_fgt_role(devid, slot) as role,
      cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
      ) as cpu_ave,
      cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
      ) as mem_ave,
      cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
      ) as disk_ave,
      cast(
        sum(log_rate) as decimal(10, 2)
      ) as log_rate,
      cast(
        sum(sessions) as decimal(10, 0)
```

```

    ) as sessions,
    cast(
        sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
        max(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
    max(session_peak) as session_peak,
    max(transmit_kbps_peak) as transmit_kbps_peak,
    cast(
        sum(cps_ave) as decimal(10, 0)
    ) as cps_ave,
    sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hodex,
        devid,
        slot,
        sum(total_cpu) / sum(count) as cpu_ave,
        sum(total_mem) / sum(count) as mem_ave,
        sum(total_disk) / sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        ) / 100.00 / sum(count) as log_rate,
        sum(totalsession) / sum(count) as sessions,
        sum(sent) / sum(count) as sent_kbps,
        sum(recv) / sum(count) as recv_kbps,
        sum(sent + recv) / sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak) / 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps) / sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,

```

```
'/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodex, devid, slot) t group
by hodex, devid, role) t group by hodex order by hodex
```

Dataset Name	Description	Log Category
perf-stat-mem-usage-drilldown	Fortigate resource detail timeline	event

```
select
  hodex,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps)/ count(*) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps)/ count(*) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  max(lograte_peak) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak,
  cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
  ) as cps_ave,
  max(cps_peak) as cps_peak
from
  (
    select
      hodex,
      devid,
      get_fgt_role(devid, slot) as role,
      cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
      ) as cpu_ave,
      cast(
```

```

        sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
        max(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
    max(session_peak) as session_peak,
    max(transmit_kbps_peak) as transmit_kbps_peak,
    cast(
        sum(cps_ave) as decimal(10, 0)
    ) as cps_ave,
    sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hindex,
        devid,
        slot,
        sum(total_cpu)/ sum(count) cpu_ave,
        sum(total_mem)/ sum(count) as mem_ave,
        sum(total_disk)/ sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        )/ 100.00 / sum(count) as log_rate,
        sum(totalsession)/ sum(count) as sessions,
        sum(sent)/ sum(count) as sent_kbps,
        sum(recv)/ sum(count) as recv_kbps,
        sum(sent + recv)/ sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak)/ 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps)/ sum(count) as cps_ave,
        max(cps_peak) as cps_peak

```



```

from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodex, devid, slot) t group
by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-disk-usage-drilldown	Fortigate resource detail timeline	event

```

select
    hodex,
    cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate)/ count(*) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions)/ count(*) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps)/ count(*) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps)/ count(*) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps)/ count(*) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    max(lograte_peak) as lograte_peak,
    max(session_peak) as session_peak,
    max(transmit_kbps_peak) as transmit_kbps_peak,
    cast(
        sum(cps_ave)/ count(*) as decimal(10, 0)
    ) as cps_ave,
    max(cps_peak) as cps_peak

```

```
from
(
select
    hindex,
    devid,
    get_fgt_role(devid, slot) as role,
    cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
        max(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
    max(session_peak) as session_peak,
    max(transmit_kbps_peak) as transmit_kbps_peak,
    cast(
        sum(cps_ave) as decimal(10, 0)
    ) as cps_ave,
    sum(cps_peak) as cps_peak
from
(
select
    $flex_timescale(timestamp) as hindex,
    devid,
    slot,
    sum(total_cpu)/ sum(count) cpu_ave,
    sum(total_mem)/ sum(count) as mem_ave,
    sum(total_disk)/ sum(count) as disk_ave,
    sum(
        total_trate + total_erate + total_orate
    )/ 100.00 / sum(count) as log_rate,
    sum(totalsession)/ sum(count) as sessions,
    sum(sent)/ sum(count) as sent_kbps,
```

```

sum(recv)/ sum(count) as recv_kbps,
sum(sent + recv)/ sum(count) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
max(lograte_peak)/ 100.00 as lograte_peak,
max(session_peak) as session_peak,
max(transmit_peak) as transmit_kbps_peak,
sum(cps)/ sum(count) as cps_ave,
max(cps_peak) as cps_peak
from
###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hindex, devid, slot) t group
by hindex, devid, role) t group by hindex order by hindex

```

Dataset Name	Description	Log Category
perf-stat-sessions-drilldown	Fortigate resource detail timeline	event

```

select
  hindex,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps)/ count(*) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps)/ count(*) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
  ) as transmit_kbps,

```

```
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
max(lograte_peak) as lograte_peak,
max(session_peak) as session_peak,
max(transmit_kbps_peak) as transmit_kbps_peak,
cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
) as cps_ave,
max(cps_peak) as cps_peak
from
(
    select
        hodex,
        devid,
        get_fgt_role(devid, slot) as role,
        cast(
            sum(cpu_ave)/ count(*) as decimal(6, 0)
        ) as cpu_ave,
        cast(
            sum(mem_ave)/ count(*) as decimal(6, 0)
        ) as mem_ave,
        cast(
            sum(disk_ave)/ count(*) as decimal(6, 0)
        ) as disk_ave,
        cast(
            sum(log_rate) as decimal(10, 2)
        ) as log_rate,
        cast(
            sum(sessions) as decimal(10, 0)
        ) as sessions,
        cast(
            sum(sent_kbps) as decimal(10, 0)
        ) as sent_kbps,
        cast(
            sum(recv_kbps) as decimal(10, 0)
        ) as recv_kbps,
        cast(
            sum(transmit_kbps) as decimal(10, 0)
        ) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        cast(
            max(lograte_peak) as decimal(10, 2)
        ) as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_kbps_peak) as transmit_kbps_peak,
        cast(
            sum(cps_ave) as decimal(10, 0)
        ) as cps_ave,
        sum(cps_peak) as cps_peak
    from
        (
            select
                $flex_timescale(timestamp) as hodex,
```

```

    devid,
    slot,
    sum(total_cpu)/ sum(count) cpu_ave,
    sum(total_mem)/ sum(count) as mem_ave,
    sum(total_disk)/ sum(count) as disk_ave,
    sum(
        total_trate + total_erate + total_orate
    )/ 100.00 / sum(count) as log_rate,
    sum(totalsession)/ sum(count) as sessions,
    sum(sent)/ sum(count) as sent_kbps,
    sum(recv)/ sum(count) as recv_kbps,
    sum(sent + recv)/ sum(count) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    max(lograte_peak)/ 100.00 as lograte_peak,
    max(session_peak) as session_peak,
    max(transmit_peak) as transmit_kbps_peak,
    sum(cps)/ sum(count) as cps_ave,
    max(cps_peak) as cps_peak
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodex, devid, slot) t group
by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-lograte-drilldown	Fortigate resource detail timeline	event

```

select
    hodex,
    cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate)/ count(*) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions)/ count(*) as decimal(10, 0)
    ) as sessions

```

```
) as sessions,
cast(
  sum(sent_kbps)/ count(*) as decimal(10, 0)
) as sent_kbps,
cast(
  sum(recv_kbps)/ count(*) as decimal(10, 0)
) as recv_kbps,
cast(
  sum(transmit_kbps)/ count(*) as decimal(10, 0)
) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
max(lograte_peak) as lograte_peak,
max(session_peak) as session_peak,
max(transmit_kbps_peak) as transmit_kbps_peak,
cast(
  sum(cps_ave)/ count(*) as decimal(10, 0)
) as cps_ave,
max(cps_peak) as cps_peak
from
(
  select
    hindex,
    devid,
    get_fgt_role(devid, slot) as role,
    cast(
      sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
      sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
      sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
      sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
      sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
      sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
      sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
      sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
      max(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
```

```

max(session_peak) as session_peak,
max(transmit_kbps_peak) as transmit_kbps_peak,
cast(
    sum(cps_ave) as decimal(10, 0)
) as cps_ave,
sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hodex,
        devid,
        slot,
        sum(total_cpu)/ sum(count) cpu_ave,
        sum(total_mem)/ sum(count) as mem_ave,
        sum(total_disk)/ sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        ) / 100.00 / sum(count) as log_rate,
        sum(totalsession)/ sum(count) as sessions,
        sum(sent)/ sum(count) as sent_kbps,
        sum(recv)/ sum(count) as recv_kbps,
        sum(sent + recv)/ sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak)/ 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps)/ sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodex, devid, slot) t group
by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-connections-drilldown	Fortigate resource detail timeline	event

```

select
    hodex,
    cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(

```

```
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps)/ count(*) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps)/ count(*) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  max(lograte_peak) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak,
  cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
  ) as cps_ave,
  max(cps_peak) as cps_peak
from
  (
    select
      hodex,
      devid,
      get_fgt_role(devid, slot) as role,
      cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
      ) as cpu_ave,
      cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
      ) as mem_ave,
      cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
      ) as disk_ave,
      cast(
        sum(log_rate) as decimal(10, 2)
      ) as log_rate,
      cast(
        sum(sessions) as decimal(10, 0)
      ) as sessions,
      cast(
        sum(sent_kbps) as decimal(10, 0)
      ) as sent_kbps,
      cast(
        sum(recv_kbps) as decimal(10, 0)
```



```

    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
        max(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
    max(session_peak) as session_peak,
    max(transmit_kbps_peak) as transmit_kbps_peak,
    cast(
        sum(cps_ave) as decimal(10, 0)
    ) as cps_ave,
    sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hodex,
        devid,
        slot,
        sum(total_cpu)/ sum(count) cpu_ave,
        sum(total_mem)/ sum(count) as mem_ave,
        sum(total_disk)/ sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        )/ 100.00 / sum(count) as log_rate,
        sum(totalsession)/ sum(count) as sessions,
        sum(sent)/ sum(count) as sent_kbps,
        sum(recv)/ sum(count) as recv_kbps,
        sum(sent + recv)/ sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak)/ 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps)/ sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodex, devid, slot) t group
by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-bandwidth-drilldown	Fortigate resource detail timeline	event

```

select
  horex,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps)/ count(*) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(rcv_kbps)/ count(*) as decimal(10, 0)
  ) as rcv_kbps,
  cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  max(lograte_peak) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak,
  cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
  ) as cps_ave,
  max(cps_peak) as cps_peak
from
  (
    select
      horex,
      devid,
      get_fgt_role(devid, slot) as role,
      cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
      ) as cpu_ave,
      cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
      ) as mem_ave,
      cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
      ) as disk_ave,
      cast(

```

```

        sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
        max(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
    max(session_peak) as session_peak,
    max(transmit_kbps_peak) as transmit_kbps_peak,
    cast(
        sum(cps_ave) as decimal(10, 0)
    ) as cps_ave,
    sum(cps_peak) as cps_peak
from
    (
        select
            $flex_timescale(timestamp) as hindex,
            devid,
            slot,
            sum(total_cpu) / sum(count) as cpu_ave,
            sum(total_mem) / sum(count) as mem_ave,
            sum(total_disk) / sum(count) as disk_ave,
            sum(
                total_trate + total_erate + total_orate
            ) / 100.00 / sum(count) as log_rate,
            sum(totalsession) / sum(count) as sessions,
            sum(sent) / sum(count) as sent_kbps,
            sum(recv) / sum(count) as recv_kbps,
            sum(sent + recv) / sum(count) as transmit_kbps,
            max(mem_peak) as mem_peak,
            max(disk_peak) as disk_peak,
            max(cpu_peak) as cpu_peak,
            max(lograte_peak) / 100.00 as lograte_peak,
            max(session_peak) as session_peak,
            max(transmit_peak) as transmit_kbps_peak,
            sum(cps) / sum(count) as cps_ave,
            max(cps_peak) as cps_peak
        from
            ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
            total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
            min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
            (coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
            as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max

```

```
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hindex, devid, slot) t group
by hindex, devid, role) t group by hindex order by hindex
```

Dataset Name	Description	Log Category
perf-stat-usage-summary-average	Fortigate resource summary view	event

```
select
  devid,
  get_fgt_role(devid, slot) as role,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  cast(
    max(lograte_peak) as decimal(10, 2)
  ) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak
from
  (
    select
      devid,
      slot,
      sum(total_cpu)/ sum(count) as cpu_ave,
      sum(total_mem)/ sum(count) as mem_ave,
```

```

sum(total_disk)/ sum(count) as disk_ave,
sum(
    total_trate + total_erate + total_orate
)/ 100.00 / sum(count) as log_rate,
sum(totalsession)/ sum(count) as sessions,
sum(sent)/ sum(count) as sent_kbps,
sum(recv)/ sum(count) as recv_kbps,
sum(sent + recv)/ sum(count) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
max(lograte_peak)/ 100.00 as lograte_peak,
max(session_peak) as session_peak,
max(transmit_peak) as transmit_kbps_peak
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid, slot) t group by devid, role order by devid,
role

```

Dataset Name	Description	Log Category
perf-stat-usage-summary-peak	Fortigate resource summary view	event

```

select
    devid,
    get_fgt_role(devid, slot) as role,
    cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(

```

```

        sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
        max(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
    max(session_peak) as session_peak,
    max(transmit_kbps_peak) as transmit_kbps_peak
from
(
    select
        devid,
        slot,
        sum(total_cpu) / sum(count) as cpu_ave,
        sum(total_mem) / sum(count) as mem_ave,
        sum(total_disk) / sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        ) / 100.00 / sum(count) as log_rate,
        sum(totalsession) / sum(count) as sessions,
        sum(sent) / sum(count) as sent_kbps,
        sum(recv) / sum(count) as recv_kbps,
        sum(sent + recv) / sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak) / 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
        total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
        min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
        (coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
        as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
        (coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
        (totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
        (coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
        part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
        '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
        transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
        count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
        by timestamp, devid, slot)### t group by devid, slot) t group by devid, role order by devid,
        role

```

Dataset Name	Description	Log Category
perf-stat-usage-details-drilldown-master	Fortigate resource summary view	event

```
select
  devid,
  get_fgt_role(devid, slot) as role,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  cast(
    max(lograte_peak) as decimal(10, 2)
  ) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak
from
  (
    select
      devid,
      slot,
      sum(total_cpu)/ sum(count) as cpu_ave,
      sum(total_mem)/ sum(count) as mem_ave,
      sum(total_disk)/ sum(count) as disk_ave,
      sum(
        total_trate + total_erate + total_orate
      )/ 100.00 / sum(count) as log_rate,
      sum(totalsession)/ sum(count) as sessions,
      sum(sent)/ sum(count) as sent_kbps,
      sum(recv)/ sum(count) as recv_kbps,
      sum(sent + recv)/ sum(count) as transmit_kbps,
      max(mem_peak) as mem_peak,
      max(disk_peak) as disk_peak,
      max(cpu_peak) as cpu_peak,
      max(lograte_peak)/ 100.00 as lograte_peak,
      max(session_peak) as session_peak,
      max(transmit_peak) as transmit_kbps_peak
```

```

from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as
total_trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate,
min(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid, slot) t group by devid, role order by devid,
role

```

Dataset Name	Description	Log Category
incident-Incident-Count-by-Status	Incident status distribution	

```

select
    status,
    count(*) as cnt
from
    $incident
group by
    status
order by
    status

```

Dataset Name	Description	Log Category
incident-Incident-Count-by-Status-Donut	Incident status distribution	

```

select
    status,
    count(*) as cnt
from
    $incident
group by
    status
order by
    status

```

Dataset Name	Description	Log Category
incident-Open-Incident-Count-Timeline	Incident count by status over time	

```

select
    $flex_timescale(agg_time) as hodex,
    max(num_sta_draft) as num_sta_draft,
    max(num_sta_analysis) as num_sta_analysis,
    max(num_sta_response) as num_sta_response,
    max(num_sta_closed) as num_sta_closed,
    max(num_sta_cancelled) as num_sta_cancelled

```



```

from
    $incident_history
where
    $cust_time_filter(agg_time)
group by
    hodex
order by
    hodex

```

Dataset Name	Description	Log Category
incident-Closed-Incident-Count-Timeline	Incident count by status over time	

```

select
    $flex_timescale(agg_time) as hodex,
    max(num_sta_draft) as num_sta_draft,
    max(num_sta_analysis) as num_sta_analysis,
    max(num_sta_response) as num_sta_response,
    max(num_sta_closed) as num_sta_closed,
    max(num_sta_cancelled) as num_sta_cancelled
from
    $incident_history
where
    $cust_time_filter(agg_time)
group by
    hodex
order by
    hodex

```

Dataset Name	Description	Log Category
Top-10-Apps-by-Bandwidth	Top applications by bandwidth usage	traffic

```

select
    app_group_name(app) as app_group,
    sum(
        coalesce(sentbyte, 0) + coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(app) is not null
group by
    app_group

```

```

having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-10-User-by-Bandwidth	Top users by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  srcip,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and srcip is not null
group by
  user_src,
  srcip
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-10-Applications-by-Number-of-Users	Top Applications by number of users	traffic

```

select
  app_group_name(app) as app_group,
  count(distinct user_src) as number
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,

```

```
app, appcat from $log where $filter and (logflag&1>0) and nullifna(app) is not null group by
user_src, app, appcat)### t group by app_group order by number desc
```

Dataset Name	Description	Log Category
Top-10-User-by-Session	Top user by session count	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  user_src
order by
  sessions desc
```

Dataset Name	Description	Log Category
Top-10-Apps-by-Session	Top applications by bandwidth usage	traffic

```
select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
```

```
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
Applications-by-Risk-Level	Applications by Risk Level	traffic

```
select
  app_group_name(app) as app_group,
  min(id) as id,
  appcat,
  max(risk) as d_risk,
  (
    case when max(risk)=& #039;5' then 'Critical' when max(risk)='4' then 'High' when max
(risk)='3' then 'Medium' when max(risk)='2' then 'Low' else 'Info' end) as risk_level, sum
(sessions) as sessions, sum(sent) as sent, sum(received) as received, sum(bandwidth) as
bandwidth from ###(select appid, app, appcat, sum(coalesce(sentbyte, 0)) as sent, sum
(coalesce(rcvdbyte, 0)) as received, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log where $filter and (logflag&l>0) group by appid,
app, appcat order by bandwidth desc)### t1 inner join app_mdata t2 on lower(t1.app)=lower
(t2.name) group by app_group, appcat order by d_risk desc, bandwidth desc
```

Dataset Name	Description	Log Category
soc-Event-vs-Incident-Today-Trend	Events vs Incidents Today Trend	

```
select
  item,
  num_cur,
  num_pre,
  num_diff
from
  (
    select
      & #039;Events' as item, num_cur, num_pre, (num_cur-num_pre) as num_diff from (select
(select count(*) from $event where $cust_time_filter(alerttime,TODAY)) as num_cur, (select
count(*) from $event where $cust_time_filter(alerttime,YESTERDAY)) as num_pre) t union all
select 'Incidents' as item, num_cur, num_pre, (num_cur-num_pre) as num_diff from (select
(select count(*) from $incident where $cust_time_filter(createtime,TODAY)) as num_cur,
(select count(*) from $incident where $cust_time_filter(createtime,YESTERDAY)) as num_pre)
t) t order by item
```

Dataset Name	Description	Log Category
soc-Event-vs-Incident-History-Trend	Events vs Incidents History Trend	

```
select
  item,
  num_cur,
  num_pre,
  num_diff
from
  (
    select
      & #039;Events' as item, num_cur, num_pre, (num_cur-num_pre) as num_diff from (select
(select count(*) from $event where $cust_time_filter(alerttime)) as num_cur, (select count
```

```
(*) from $event where $cust_time_filter(alerttime, LAST_N_PERIOD, 1)) as num_pre) t union all
select 'Incidents' as item, num_cur, num_pre, (num_cur-num_pre) as num_diff from (select
(select count(*) from $incident where $cust_time_filter(createtime)) as num_cur, (select
count(*) from $incident where $cust_time_filter(createtime, LAST_N_PERIOD, 1)) as num_pre) t)
t order by item
```

Dataset Name	Description	Log Category
soc-Event-vs-Incident-Trend	Events vs Incidents Trend	

```
select
  t1.item,
  t1.num_cur as num_today,
  t1.num_pre as num_yesterday,
  t1.num_diff as num_diff1,
  t2.num_cur as num_this_period,
  t2.num_pre as num_last_period,
  t2.num_diff as num_diff2
from
  (
    select
      & #039;Events' as item, num_cur, num_pre, (num_cur-num_pre) as num_diff from (select
(select count(*) from $event where $cust_time_filter(alerttime, TODAY)) as num_cur, (select
count(*) from $event where $cust_time_filter(alerttime, YESTERDAY)) as num_pre) t union all
select 'Incidents' as item, num_cur, num_pre, (num_cur-num_pre) as num_diff from (select
(select count(*) from $incident where $cust_time_filter(createtime, TODAY)) as num_cur,
(select count(*) from $incident where $cust_time_filter(createtime, YESTERDAY)) as num_pre)
t) t1 full join (select 'Events' as item, num_cur, num_pre, (num_cur-num_pre) as num_diff
from (select (select count(*) from $event where $cust_time_filter(alerttime)) as num_cur,
(select count(*) from $event where $cust_time_filter(alerttime, LAST_N_PERIOD, 1)) as num_pre)
t union all select 'Incidents' as item, num_cur, num_pre, (num_cur-num_pre) as num_diff from
(select (select count(*) from $incident where $cust_time_filter(createtime)) as num_cur,
(select count(*) from $incident where $cust_time_filter(createtime, LAST_N_PERIOD, 1)) as num_
pre) t) t2 on t1.item=t2.item order by t1.item
```

Dataset Name	Description	Log Category
soc-Total-Event-by-Severity	Total Events by Severity	

```
select
  (
    CASE severity WHEN 0 THEN & #039;Critical' WHEN 1 THEN 'High' WHEN 2 THEN 'Medium' WHEN
3 THEN 'Low' ELSE NULL END) as sev, count(*) as num_events from $event group by severity
order by severity
```

Dataset Name	Description	Log Category
soc-Total-Event-by-Severity-History	Total Events by Severity History	

```
select
  dom,
  (
    CASE severity WHEN 0 THEN & #039;Critical' WHEN 1 THEN 'High' WHEN 2 THEN 'Medium' WHEN
3 THEN 'Low' ELSE NULL END) as sev, sum(num_events) as num_events from (select dom, unnest
(agg_sev) as severity, unnest(agg_num) as num_events from (select $DAY_OF_MONTH(agg_time) as
dom, array[0, 1, 2, 3] as agg_sev, array[max(num_sev_critical), max(num_sev_high), max(num_
```

```
sev_medium), max(num_sev_low)] as agg_num from $event_history where $cust_time_filter(agg_time) group by dom order by dom) t) t group by dom, severity order by dom, severity
```

Dataset Name	Description	Log Category
soc-Total-Event-by-Severity-Category	Total Events Count by Severity and Category	

```
select
(
CASE severity WHEN 0 THEN & #039;Critical' WHEN 1 THEN 'High' WHEN 2 THEN 'Medium' WHEN
3 THEN 'Low' ELSE NULL END) as sev, triggername, count(*) as num_events from $event group by
severity, triggername order by severity, triggername
```

Dataset Name	Description	Log Category
soc-Total-Incident-by-Severity	Total Incidents by Severity	

```
select
severity,
count(*) as num_inc
from
$incident
group by
severity
order by
severity
```

Dataset Name	Description	Log Category
soc-Total-Event-vs-Incident-History	Total Events vs Incidents History	

```
select
coalesce(t1.hodex, t2.hodex) as hodex,
coalesce(num_event_total, 0) as num_event_total,
coalesce(num_inc_total, 0) as num_inc_total,
coalesce(num_event_high, 0) as num_event_high
from
(
select
$flex_timescale(agg_time) as hodex,
max(num_total) as num_event_total,
max(num_sev_critical + num_sev_high) as num_event_high
from
$event_history
where
$cust_time_filter(agg_time)
group by
hodex
order by
hodex
) t1 full
join (
select
$flex_timescale(agg_time) as hodex,
max(
num_sev_high + num_sev_medium + num_sev_low
```

```

        ) as num_inc_total
    from
        $incident_history
    where
        $cust_time_filter(agg_time)
    group by
        hodex
    order by
        hodex
) t2 on t1.hodex = t2.hodex
order by
    hodex

```

Dataset Name	Description	Log Category
soc-Incident-List	List of Incidents	

```

select
    incid_to_str(incid) as incnum,
    from_itime(createtime) as timestamp,
    inc_cat_encode(category) as category,
    severity,
    status,
    endpoint
from
    $incident
where
    $cust_time_filter(createtime)
order by
    createtime desc

```

Dataset Name	Description	Log Category
soc-Incident-by-Severity	Incidents by Severity	

```

select
    severity,
    count(*) as incnum
from
    $incident
where
    $cust_time_filter(createtime)
group by
    severity
order by
    incnum desc

```

Dataset Name	Description	Log Category
soc-Incident-by-Status	Incidents by Status	

```

select
    status,
    count(*) as incnum
from
    $incident

```

```

where
    $cust_time_filter(createtime)
group by
    status
order by
    incnum desc

```

Dataset Name	Description	Log Category
soc-Incident-by-Category-Unresolved	Unresolved Incidents by Category	

```

select
    inc_cat_encode(category) as category,
    count(*) as incnum
from
    $incident
where
    $cust_time_filter(createtime)
    and status not in (
        & #039;closed', 'cancelled') group by category order by incnum desc

```

Dataset Name	Description	Log Category
soc-Incident-by-Severity-Unresolved	Unresolved Incidents by Severity	

```

select
    severity,
    count(*) as incnum
from
    $incident
where
    $cust_time_filter(createtime)
    and status not in (
        & #039;closed', 'cancelled') group by severity order by incnum desc

```

Dataset Name	Description	Log Category
soc-Incident-Timeline-by-Category	Incidents Timeline by Category	

```

select
    $flex_timescale(agg_time) as hodex,
    max(num_cat_cat1) as num_cat1,
    max(num_cat_cat2) as num_cat2,
    max(num_cat_cat3) as num_cat3,
    max(num_cat_cat4) as num_cat4,
    max(num_cat_cat5) as num_cat5,
    max(num_cat_cat6) as num_cat6
from
    $incident_history
where
    $cust_time_filter(agg_time)
group by
    hodex
order by
    hodex

```


Dataset Name	Description	Log Category
soc-Incident-List-Unresolved	List of Unresolved Incidents	

```
select
  incid_to_str(incid) as incnum,
  from_itime(createtime) as timestamp,
  severity,
  status,
  endpoint,
  description
from
  $incident
where
  $cust_time_filter(createtime)
  and status not in (
    & #039;closed', 'cancelled') order by severity desc
```

Dataset Name	Description	Log Category
fex-RSRQ-timeline	FortiExtender RSRQ timeline	event

```
select
  $flex_timescale(timestamp) as hindex,
  cast(
    sum(rsrq_sum) / sum(count) as decimal(18, 2)
  ) || & #039;dB' as rsrq from ###(select $flex_timestamp(dtime) as timestamp, sum(to_number
(rsrq, '999999.99')) as rsrq_sum, sum(to_number(sinr, '999999.99')) as sinr_sum, count(*) as
count from $log where $filter and logid='0111046409' group by timestamp order by timestamp
desc)### t group by hindex order by hindex desc
```

Dataset Name	Description	Log Category
fex-SINR-timeline	FortiExtender SINR timeline	event

```
select
  $flex_timescale(timestamp) as hindex,
  cast(
    sum(sinr_sum) / sum(count) as decimal(18, 0)
  ) || & #039;dB' as sinr from ###(select $flex_timestamp(dtime) as timestamp, sum(to_number
(rsrq, '999999.99')) as rsrq_sum, sum(to_number(sinr, '999999.99')) as sinr_sum, count(*) as
count from $log where $filter and logid='0111046409' group by timestamp order by timestamp
desc)### t group by hindex order by hindex desc
```

Dataset Name	Description	Log Category
fgt-device-monitoring-inventory	FortiGate Device Monitoring Inventory	event

```
select
  devname,
  (
    & #039; ' || devid) as id_devid, ip, platform, os, '1' as total_num from $func-fgt-
inventory as t1 where exists (select 1 from devtable t2 where $dev_filter and
t2.devid=t1.devid) order by devname
```

Dataset Name	Description	Log Category
fgt-inventory-hardware	FortiGate Monitoring Inventory Hardware	event

```
select
  platform,
  count(*) as total_num
from
  $func - fgt - inventory as t1
where
  exists (
    select
      1
    from
      devtable t2
    where
      $dev_filter
      and t2.devid = t1.devid
  )
group by
  platform
order by
  total_num desc
```

Dataset Name	Description	Log Category
fgt-inventory-software	FortiGate Monitoring Inventory Software	event

```
select
  & #039;FortiOS' as sf_name, (platform || ' ' || os) as firmware, count(*) as total_num
from $func-fgt-inventory as t1 where exists (select 1 from devtable t2 where $dev_filter and
t2.devid=t1.devid) group by platform, os order by total_num desc
```

Dataset Name	Description	Log Category
cup-utilization-timeline-for-each-device	FortiGate cpu utilization timeline	event

```
select
  $flex_timescale(timestamp) as hodesk,
  devid,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(total_mem)/ sum(count) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps
from
```

```

###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodex, devid order by hodex

```

Dataset Name	Description	Log Category
status-timeline-by-device-cpu-utilization	FortiGate cpu summary view	event

```

select
  devid,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 0)
  ) as cpu_ave,
  max(cpu_peak) as cpu_peak
from
  ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by cpu_peak desc

```

Dataset Name	Description	Log Category
event-cpu-utilization-dev	FortiGate cpu summary view	event

```

select
  devid,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 0)
  ) as cpu_ave,
  max(cpu_peak) as cpu_peak
from
  ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max

```

```
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(
totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast(
coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by cpu_peak desc
```

Dataset Name	Description	Log Category
memory-utilization-timeline-for-each-device	FortiGate cpu utilization timeline	event

```
select
  $flex_timescale(timestamp) as hindex,
  devid,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(total_mem)/ sum(count) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps
from
  ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min(
itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max(
coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max(
coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(
totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast(
coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hindex, devid order by hindex
```

Dataset Name	Description	Log Category
status-timeline-by-device-mem-utilization	FortiGate memory summary view	event

```
select
  devid,
  cast(
    sum(total_mem)/ sum(count) as decimal(6, 0)
```

```

    ) as mem_ave,
    max(mem_peak) as mem_peak
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by mem_peak desc

```

Dataset Name	Description	Log Category
event-mem-utilization-dev	FortiGate memory summary view	event

```

select
    devid,
    cast(
        sum(total_mem)/ sum(count) as decimal(6, 0)
    ) as mem_ave,
    max(mem_peak) as mem_peak
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by mem_peak desc

```

Dataset Name	Description	Log Category
disk-utilization-timeline-for-each-device	FortiGate cpu utilization timeline	event

```

select
    $flex_timescale(timestamp) as hodex,
    devid,
    cast(
        sum(total_cpu)/ sum(count) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(total_mem)/ sum(count) as decimal(6, 0)
    ) as mem_ave,

```

```

cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
) as disk_ave,
cast(
    sum(sent)/ sum(count) as decimal(10, 0)
) as sent_kbps,
cast(
    sum(recv)/ sum(count) as decimal(10, 0)
) as recv_kbps
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodecx, devid order by hodecx

```

Dataset Name	Description	Log Category
status-timeline-by-device-disk-utilization	FortiGate disk summary view	event

```

select
    devid,
    cast(
        sum(total_disk)/ sum(count) as decimal(6, 0)
    ) as disk_ave,
    max(disk_peak) as disk_peak
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by disk_peak desc

```

Dataset Name	Description	Log Category
event-disk-utilization-dev	FortiGate disk summary view	event

```

select
    devid,

```

```

cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
) as disk_ave,
max(disk_peak) as disk_peak
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by disk_peak desc

```

Dataset Name	Description	Log Category
event-total-session-summary	FortiGate Total Sessions	event

```

select
    devid,
    max(session_peak) as max_session,
    cast(
        sum(totalsession)/ sum(count) as decimal(10, 0)
    ) as sessions,
    max(cps_peak) as cps_peak,
    cast(
        sum(cps)/ sum(count) as decimal(10, 0)
    ) as cps_ave
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by max_session desc

```

Dataset Name	Description	Log Category
event-session-rate-summary	FortiGate Session Rate	event

```

select
    devid,
    max(cps_peak) as max_rate
from

```

```

###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by max_rate desc

```

Dataset Name	Description	Log Category
event-session-summary-dev	FortiGate Total Sessions	event

```

select
  devid,
  max(session_peak) as max_session,
  cast(
    sum(totalsession)/ sum(count) as decimal(10, 0)
  ) as sessions,
  max(cps_peak) as cps_peak,
  cast(
    sum(cps)/ sum(count) as decimal(10, 0)
  ) as cps_ave
from
  ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by max_session desc

```

Dataset Name	Description	Log Category
fgt-intf-down-timeline-for-each-device	FortiGate Interface Down Timeline	event

```

select
  $flex_timescale(timestamp) as hodex,
  devid,
  sum(total_num) as total_num
from
  ###(select $flex_timestamp as timestamp, devid, status, count(*) as total_num from $log
where $filter and logid_to_int(logid)=20099 and status='DOWN' group by timestamp, devid,
status)### t where $filter-drilldown group by hodex, devid order by hodex

```


Dataset Name	Description	Log Category
fgt-intf-down-timeline-by-device	FortiGate Interface Down by Device	event

```
select
  devid,
  status,
  sum(total_num) as total_num
from
  ###(select $flex_timestamp as timestamp, devid, status, count(*) as total_num from $log
where $filter and logid_to_int(logid)=20099 and status='DOWN' group by timestamp, devid,
status)### t group by devid, status order by total_num desc
```

Dataset Name	Description	Log Category
fgt-intf-down-dev-donut	FortiGate Interface Down by Device	event

```
select
  devid,
  status,
  sum(total_num) as total_num
from
  ###(select $flex_timestamp as timestamp, devid, status, count(*) as total_num from $log
where $filter and logid_to_int(logid)=20099 and status='DOWN' group by timestamp, devid,
status)### t group by devid, status order by total_num desc
```

Dataset Name	Description	Log Category
fgt-intf-down-dev-tbl	FortiGate Interface Down by Device	event

```
select
  devid,
  status,
  sum(total_num) as total_num
from
  ###(select $flex_timestamp as timestamp, devid, status, count(*) as total_num from $log
where $filter and logid_to_int(logid)=20099 and status='DOWN' group by timestamp, devid,
status)### t group by devid, status order by total_num desc
```

Dataset Name	Description	Log Category
intf-sent-timeline-for-each-device	FortiGate cpu utilization timeline	event

```
select
  $flex_timescale(timestamp) as hindex,
  devid,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(total_mem)/ sum(count) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
  ) as disk_ave,
  cast(
```

```

        sum(sent)/ sum(count) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv)/ sum(count) as decimal(10, 0)
    ) as recv_kbps
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodex, devid order by hodex

```

Dataset Name	Description	Log Category
status-timeline-by-device-intf-sent	FortiGate interface summary view	event

```

select
    devid,
    cast(
        sum(sent)/ sum(count) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv)/ sum(count) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(sent + recv)/ sum(count) as decimal(10, 0)
    ) as transmit_kbps,
    max(transmit_peak) as transmit_kbps_peak
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by transmit_kbps_peak desc

```

Dataset Name	Description	Log Category
intf-recv-timeline-for-each-device	FortiGate cpu utilization timeline	event

```

select
  $flex_timescale(timestamp) as hodex,
  devid,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(total_mem)/ sum(count) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps
from
  ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t where $filter-drilldown group by hodex, devid order by hodex

```

Dataset Name	Description	Log Category
status-timeline-by-device-intf-recv	FortiGate interface summary view	event

```

select
  devid,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(sent + recv)/ sum(count) as decimal(10, 0)
  ) as transmit_kbps,
  max(transmit_peak) as transmit_kbps_peak
from
  ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce

```

```
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by transmit_kbps_peak desc
```

Dataset Name	Description	Log Category
event-intf-summary-dev	FortiGate interface summary view	event

```
select
  devid,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(sent + recv)/ sum(count) as decimal(10, 0)
  ) as transmit_kbps,
  max(transmit_peak) as transmit_kbps_peak
from
  ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by devid order by transmit_kbps_peak desc
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-util-in-each	FortiGate Interface Statistics Timeline	event

```
select
  $flex_timescale(tmstamp) as horex,
  (
    devname || & #039;:' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from intfstats where $cust_time_filter
(timestamp) group by tmstamp, dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
where $filter-drilldown group by horex, dev_intf order by horex
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-util-in	FortiGate Interface Received Utilization	event

```
select
(
    devname || & #039;:' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, tbl_intf.dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from (select distinct dvid from ###(select dvid
from $log-event where $filter and action='perf-stats' group by dvid)### t) tbl_log inner
join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_time_filter(timestamp)
group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
group by dev_intf order by util_in_avg desc, kbps_in_avg desc, kbps_out_avg desc
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-util-out-each	FortiGate Interface Statistics Timeline	event

```
select
    $flex_timescale(tmstamp) as hindex,
(
    devname || & #039;:' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from intfstats where $cust_time_filter
(timestamp) group by tmstamp, dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
where $filter-drilldown group by hindex, dev_intf order by hindex
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-util-out	FortiGate Interface Sent Utilization	event

```
select
(
    devname || & #039;:' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, tbl_intf.dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from (select distinct dvid from ###(select dvid
from $log-event where $filter and action='perf-stats' group by dvid)### t) tbl_log inner
join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_time_filter(timestamp)
group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
group by dev_intf order by util_out_avg desc, kbps_out_avg desc, kbps_in_avg desc
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-bit-rate-in-each	FortiGate Interface Statistics Timeline	event

```
select
  $flex_timescale(tmstamp) as hodex,
  (
    devname || & #039;::' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from intfstats where $cust_time_filter
(timestamp) group by tmstamp, dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
where $filter-drilldown group by hodex, dev_intf order by hodex
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-bit-rate-in	FortiGate Interface Received Bit Rate	event

```
select
  (
    devname || & #039;::' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, tbl_intf.dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from (select distinct dvid from ###(select dvid
from $log-event where $filter and action='perf-stats' group by dvid)### t) tbl_log inner
join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_time_filter(timestamp)
group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
group by dev_intf order by kbps_in_avg desc
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-bit-rate-out-each	FortiGate Interface Statistics Timeline	event

```
select
  $flex_timescale(tmstamp) as hodex,
  (
    devname || & #039;::' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from intfstats where $cust_time_filter
(timestamp) group by tmstamp, dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
where $filter-drilldown group by hodex, dev_intf order by hodex
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-bit-rate-out	FortiGate Interface Sent Bit Rate	event

```
select
  (
    devname || & #039;::' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
```

```

kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, tbl_intf.dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from (select distinct dvid from ###(select dvid
from $log-event where $filter and action='perf-stats' group by dvid)### t) tbl_log inner
join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_time_filter(timestamp)
group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
group by dev_intf order by kbps_out_avg desc

```

Dataset Name	Description	Log Category
fgt-intf-stats-summary-view	FortiGate Interface Received Utilization	event

```

select
(
devname || & #039;:' || intfname) as dev_intf, cast(sum(bps_out)/sum(interval)/1000 as
decimal(10, 0)) as kbps_out_avg, cast(sum(bps_in)/sum(interval)/1000 as decimal(10, 0)) as
kbps_in_avg, cast(sum(util_out)/sum(interval)/100 as decimal(10, 2)) as util_out_avg, cast
(sum(util_in)/sum(interval)/100 as decimal(10, 2)) as util_in_avg from (select $flex_
timestamp(timestamp) as tmstamp, tbl_intf.dvid, intfname, sum(interval) as interval, sum
(sentbps*interval) as bps_out, sum(rcvdbps*interval) as bps_in, sum(sentutil*interval) as
util_out, sum(rcvdutil*interval) as util_in from (select distinct dvid from ###(select dvid
from $log-event where $filter and action='perf-stats' group by dvid)### t) tbl_log inner
join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_time_filter(timestamp)
group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on t1.dvid = t2.dvid
group by dev_intf order by util_in_avg desc, kbps_in_avg desc, kbps_out_avg desc

```

Dataset Name	Description	Log Category
fgt-ha-failure-timeline	FortiGate HA Failure Timeline	event

```

select
$flex_timescale(timestamp) as hodex,
count(*) as total_num
from
###(select $flex_timestamp as timestamp, dtype, devid, coalesce(nullifna(logdesc), msg) as
msg_desc from $log where $filter and subtype='ha' and logid_to_int(logid) in (35011, 35012,
35013, 37892, 37893, 37897, 37898, 37901, 37902, 37907, 37908) order by dtype desc)### t
group by hodex order by hodex

```

Dataset Name	Description	Log Category
fgt-ha-failure-summary	FortiGate HA Failure Summary	event

```

select
from_dtype(dtype) as time_s,
devid,
msg_desc
from
###(select $flex_timestamp as timestamp, dtype, devid, coalesce(nullifna(logdesc), msg) as
msg_desc from $log where $filter and subtype='ha' and logid_to_int(logid) in (35011, 35012,
35013, 37892, 37893, 37897, 37898, 37901, 37902, 37907, 37908) order by dtype desc)### t
order by time_s desc

```

Dataset Name	Description	Log Category
fgt-env-faults-power	FortiGate Power Supply Faults	event

```
select
  from_dtime(dtime) as time_s,
  devid,
  coalesce(
    nullifna(logdesc),
    msg
  ) as msg_desc
from
  $log
where
  $filter
  and logid_to_int(logid) in (22105, 22107)
order by
  time_s desc
```

Dataset Name	Description	Log Category
fgt-env-faults-fan	FortiGate Fan Faults	event

```
select
  from_dtime(dtime) as time_s,
  devid,
  coalesce(
    nullifna(logdesc),
    msg
  ) as msg_desc
from
  $log
where
  $filter
  and logid_to_int(logid)= 22108
order by
  time_s desc
```

Dataset Name	Description	Log Category
fgt-env-faults-temperature	FortiGate Temperatre Too High	event

```
select
  from_dtime(dtime) as time_s,
  devid,
  coalesce(
    nullifna(logdesc),
    msg
  ) as msg_desc
from
  $log
where
  $filter
  and logid_to_int(logid)= 22109
order by
  time_s desc
```


Dataset Name	Description	Log Category
Behaviour-Banned-Application	Bullying Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($bully_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
Behaviour-Banned-User	Bullying Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($bully_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
Behaviour-Banned-User-Drilldown	Bullying Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($bully_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
behaviour-banned	Bullying Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($bully_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
Self-Harm-Behaviour-Banned-User-Pie	Self-Harm Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
Self-Harm-Behaviour-Banned-Application-Pie	Self-Harm Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
Self-Harm-Behaviour-Banned-User-Bar	Self-Harm Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
Self-Harm-Behaviour-Banned-User-Drilldown	Self-Harm Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
Self-Harm-behaviour-banned	Self-Harm Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(
    distinct app,
    & #039; ' ) as app_agg, string_agg(distinct from_itime(itime)::text, ' ' ) as itime_agg,
  string_agg(distinct user_src, ' ' ) as user_agg, string_agg(distinct `group`, ' ' ) as group_
agg, string_agg(distinct ipstr(`srcip`), ' ' ) as srcip_agg, count(*) as requests from ###
(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in
('facebook_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat',
'gmail_send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by
filename order by requests desc
```

Dataset Name	Description	Log Category
Browsing-Time-per-Social-Media	Browsing Time vs. Domain	traffic

```
select
  domain,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###(select domain, f_user, srcip, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth)
as bandwidth from (select app_group_name(app) as app_group, coalesce(nullifna(`user`),
nullifna(`unauthuser`), ipstr(`srcip`)) as f_user, srcip, coalesce(nullifna(root_domain
(hostname)), ipstr(dstip), NULL) as domain, ebtr_agg_flat($browse_time) as browsetime, sum
(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and
(logflag&l>0) group by app_group, f_user, hostname, domain, srcip, dstip) t1 inner join app_
mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Social.Media' group by domain,
f_user, srcip order by browsetime, bandwidth desc)### t where browsetime is not null group
by domain order by browsetime desc
```

Dataset Name	Description	Log Category
Social-Networking-Bar-Graph	Social Networking Browsing Time	traffic

```
select
  f_user,
  sum(bandwidth) as bandwidth
from
  ###(select domain, f_user, srcip, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth)
as bandwidth from (select app_group_name(app) as app_group, coalesce(nullifna(`user`),
nullifna(`unauthuser`), ipstr(`srcip`)) as f_user, srcip, coalesce(nullifna(root_domain
(hostname)), ipstr(dstip), NULL) as domain, ebtr_agg_flat($browse_time) as browsetime, sum
(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and
(logflag&l>0) group by app_group, f_user, hostname, domain, srcip, dstip) t1 inner join app_
mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Social.Media' group by domain,
f_user, srcip order by browsetime, bandwidth desc)### t where bandwidth>0 group by f_user
order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Social-Networking-Durations-Sources-Drilldown	Top Social Networking Durations from Sources Drilldown	traffic

```
select
  f_user,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###(select domain, f_user, srcip, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth)
as bandwidth from (select app_group_name(app) as app_group, coalesce(nullifna(`user`),
nullifna(`unauthuser`), ipstr(`srcip`)) as f_user, srcip, coalesce(nullifna(root_domain
```

```
(hostname)), ipstr(dstip), NULL) as domain, ebtr_agg_flat($browse_time) as browsetime, sum
(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and
(logflag&l>0) group by app_group, f_user, hostname, domain, srcip, dstip) t1 inner join app_
mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Social.Media' group by domain,
f_user, srcip order by browsetime, bandwidth desc)### t where $filter-drilldown and
browsetime is not null group by f_user order by browsetime desc
```

Dataset Name	Description	Log Category
Top-Social-Networking-Durations-Domains-Drilldown	Browsing Time vs. Domain	traffic

```
select
  domain,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###(select domain, f_user, srcip, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth)
as bandwidth from (select app_group_name(app) as app_group, coalesce(nullifna(`user`),
nullifna(`unauthuser`), ipstr(`srcip`)) as f_user, srcip, coalesce(nullifna(root_domain
(hostname)), ipstr(dstip), NULL) as domain, ebtr_agg_flat($browse_time) as browsetime, sum
(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and
(logflag&l>0) group by app_group, f_user, hostname, domain, srcip, dstip) t1 inner join app_
mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Social.Media' group by domain,
f_user, srcip order by browsetime, bandwidth desc)### t where browsetime is not null group
by domain order by browsetime desc
```

Dataset Name	Description	Log Category
Facebook-Posts	Facebook Posts	app-ctrl

```
select
  from_itime(itime) as i_time,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as f_user,
  srcip,
  filename
from
  $log
where
  $filter
  and lower(app)= lower(
    & #039;Facebook_Post') and filename is not null order by i_time desc
```

Dataset Name	Description	Log Category
Facebook-Chats	Facebook Chats	app-ctrl

```
select
  filename,
```

```
string_agg(
  distinct from_itime(itime): :text,
  & #039; ' ) as itime_agg, string_agg(distinct user_src, ' ' ) as user_agg, string_agg
(distinct `group`, ' ' ) as group_agg, string_agg(distinct ipstr(srcip), ' ' ) as srcip_agg,
count(*) as requests from ###(select filename, itime, coalesce(nullifna(`user`), nullifna
(`unauthuser`), ipstr(`srcip`)) as user_src, `group`, srcip from $log where $filter and
lower(app)=lower('Facebook_Chat') and filename is not null)### t group by filename order by
requests desc
```

Dataset Name	Description	Log Category
Twitter-Posts	Twitter Posts	app-ctrl

```
select
  from_itime(itime) as i_time,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as f_user,
  srcip,
  filename
from
  $log
where
  $filter
  and lower(app)= lower(
    & #039;Twitter_Post') and filename is not null order by i_time desc
```

Dataset Name	Description	Log Category
LinkedIn-Posts-and-Comments	LinkedIn Posts and Comments	app-ctrl

```
select
  filename,
  string_agg(
    distinct from_itime(itime): :text,
    & #039; ' ) as itime_agg, string_agg(distinct user_src, ' ' ) as user_agg, string_agg
(distinct `group`, ' ' ) as group_agg, string_agg(distinct ipstr(srcip), ' ' ) as srcip_agg,
count(*) as requests from ###(select filename, itime, coalesce(nullifna(`user`), nullifna
(`unauthuser`), ipstr(`srcip`)) as user_src, `group`, srcip from $log where $filter and
lower(app)=lower('LinkedIn_Post') and filename is not null)### t group by filename order by
requests desc
```

Dataset Name	Description	Log Category
sdwan-fw-Device-Interface-Quality_ Bibandwidth-drilldown	SD-WAN Device-Interface Statistic	event

```
select
  devid,
  sum(bibandwidth)/ sum(count) as bibandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
```

```

latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and bibandwidth is not null group by devid
having sum(count)>0 order by bibandwidth desc

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Latency-Line	SD-WAN Device-Interface Latency Timeline	event

```

select
  $flex_timescale(timestamp) as hodesk,
  t1.interface,
  min(latency) as latency
from
  (
    select
      timestamp,
      devid,
      interface,
      sum(latency) / sum(count) as latency
    from
      ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as
sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE

```

```

WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t group by timestamp, devid, interface having sum(count)>0) t1 inner
join (select interface, count(*) as num_intf from ###(select $flex_timestamp as timestamp,
csf, devid, vd, interface, healthcheck as sla_rule, sum(link_status) as link_status, sum
(failed_latency) as failed_latency, sum(failed_jitter) as failed_jitter, sum(failed_
packetloss) as failed_packetloss, sum(latency) as latency, max(latency) as latency_max, min
(latency) as latency_min, sum(jitter) as jitter, max(jitter) as jitter_max, min(jitter) as
jitter_min, sum(packetloss) as packetloss, max(packetloss) as packetloss_max, min
(packetloss) as packetloss_min, sum(inbandwidth) as inbandwidth, sum(outbandwidth) as
outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as count, min(sdwan_status) as
sdwan_status from (select itime, csf, devid, vd, interface, healthcheck, link_status, (CASE
WHEN link_status=1 THEN latency ELSE 0 END) AS latency, (CASE WHEN link_status=1 THEN jitter
ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN packetloss ELSE 100 END) AS packetloss,
(CASE WHEN sla_failed=1 AND metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss,
(CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN
sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_
failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN
inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0
END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth
from (select itime, csf, devid, vd, interface, coalesce(healthcheck, name) as healthcheck,
(CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_status, latency::float as latency,
jitter::float as jitter, trim(trailing '%' from packetloss)::float as packetloss, (CASE WHEN
msg LIKE '%SLA failed%' THEN 1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric,
(CASE WHEN msg LIKE '%SLA status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num
(inbandwidth) as inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_
unit_to_num(bibandwidth) as bibandwidth from $log where $filter and logid_to_int
(logid)=22925 AND status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL
OR name IS NOT NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck
/*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown and interface
is not null group by interface order by num_intf desc limit 10)t2 on
t1.interface=t2.interface group by hodex, t1.interface order by hodex

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Jitter-Line	SD-WAN Device-Interface Jitter Timeline	event

```

select
  $flex_timescale(timestamp) as hodex,
  t1.interface,
  min(jitter) as jitter
from
  (
    select
      timestamp,
      devid,

```



```

        interface,
        sum(jitter)/ sum(count) as jitter
    from
        ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as
        sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
        (failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
        as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
        max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
        (packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
        inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
        count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
        healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
        (CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
        packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
        1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
        0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
        failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
        WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
        THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
        ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
        (healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
        status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
        packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
        status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
        THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
        convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
        bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
        interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
        timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
        desc/*SkipEND*/)#### t group by timestamp, devid, interface having sum(count)>0) t1 inner
        join (select interface, count(*) as num_intf from ###(select $flex_timestamp as timestamp,
        csf, devid, vd, interface, healthcheck as sla_rule, sum(link_status) as link_status, sum
        (failed_latency) as failed_latency, sum(failed_jitter) as failed_jitter, sum(failed_
        packetloss) as failed_packetloss, sum(latency) as latency, max(latency) as latency_max, min
        (latency) as latency_min, sum(jitter) as jitter, max(jitter) as jitter_max, min(jitter) as
        jitter_min, sum(packetloss) as packetloss, max(packetloss) as packetloss_max, min
        (packetloss) as packetloss_min, sum(inbandwidth) as inbandwidth, sum(outbandwidth) as
        outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as count, min(sdwan_status) as
        sdwan_status from (select itime, csf, devid, vd, interface, healthcheck, link_status, (CASE
        WHEN link_status=1 THEN latency ELSE 0 END) AS latency, (CASE WHEN link_status=1 THEN jitter
        ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN packetloss ELSE 100 END) AS packetloss,
        (CASE WHEN sla_failed=1 AND metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss,
        (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN
        sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_
        failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN
        inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0
        END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth
        from (select itime, csf, devid, vd, interface, coalesce(healthcheck, name) as healthcheck,
        (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_status, latency::float as latency,
        jitter::float as jitter, trim(trailing '%' from packetloss)::float as packetloss, (CASE WHEN
        msg LIKE '%SLA failed%' THEN 1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric,
        (CASE WHEN msg LIKE '%SLA status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num
        (inbandwidth) as inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_
        unit_to_num(bibandwidth) as bibandwidth from $log where $filter and logid_to_int
        (logid)=22925 AND status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL
        OR name IS NOT NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck

```

```
/*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown and interface
is not null group by interface order by num_intf desc limit 10)t2 on
t1.interface=t2.interface group by hodex, t1.interface order by hodex
```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Packetloss-Line	SD-WAN Device-Interface Packetloss Timeline	event

```
select
  $flex_timescale(timestamp) as hodex,
  t1.interface,
  min(packetloss) as packetloss
from
  (
    select
      timestamp,
      devid,
      interface,
      sum(packetloss)/ sum(count) as packetloss
    from
      ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as
sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t group by timestamp, devid, interface having sum(count)>0) t1 inner
join (select interface, count(*) as num_intf from ###(select $flex_timestamp as timestamp,
csf, devid, vd, interface, healthcheck as sla_rule, sum(link_status) as link_status, sum
(failed_latency) as failed_latency, sum(failed_jitter) as failed_jitter, sum(failed_
packetloss) as failed_packetloss, sum(latency) as latency, max(latency) as latency_max, min
(latency) as latency_min, sum(jitter) as jitter, max(jitter) as jitter_max, min(jitter) as
jitter_min, sum(packetloss) as packetloss, max(packetloss) as packetloss_max, min
(packetloss) as packetloss_min, sum(inbandwidth) as inbandwidth, sum(outbandwidth) as
outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as count, min(sdwan_status) as
```

```

sdwan_status from (select itime, csf, devid, vd, interface, healthcheck, link_status, (CASE
WHEN link_status=1 THEN latency ELSE 0 END) AS latency, (CASE WHEN link_status=1 THEN jitter
ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN packetloss ELSE 100 END) AS packetloss,
(CASE WHEN sla_failed=1 AND metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss,
(CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN
sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_
failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN
inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0
END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth
from (select itime, csf, devid, vd, interface, coalesce(healthcheck, name) as healthcheck,
(CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_status, latency::float as latency,
jitter::float as jitter, trim(trailing '%' from packetloss)::float as packetloss, (CASE WHEN
msg LIKE '%SLA failed%' THEN 1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric,
(CASE WHEN msg LIKE '%SLA status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num
(inbandwidth) as inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_
unit_to_num(bibandwidth) as bibandwidth from $log where $filter and logid_to_int
(logid)=22925 AND status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL
OR name IS NOT NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck
/*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown and interface
is not null group by interface order by num_intf desc limit 10)t2 on
t1.interface=t2.interface group by hodex, t1.interface order by hodex

```

Dataset Name	Description	Log Category
sdwan-Device-Latency-Line	SD-WAN Device Latency Timeline	event

```

select
  $flex_timescale(timestamp) as hodex,
  devid,
  min(latency) as latency
from
  (
    select
      timestamp,
      devid,
      interface,
      sum(latency)/ sum(count) as latency
    from
      ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as
sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_

```

```
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and latency is not null group by timestamp,
devid, interface having sum(count)>0) t1 group by hodex, devid order by hodex
```

Dataset Name	Description	Log Category
sdwan-Device-Jitter-Line	SD-WAN Device Jitter Timeline	event

```
select
  $flex_timescale(timestamp) as hodex,
  devid,
  min(jitter) as jitter
from
  (
    select
      timestamp,
      devid,
      interface,
      sum(jitter)/ sum(count) as jitter
    from
      ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as
sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and jitter is not null group by timestamp,
devid, interface having sum(count)>0) t1 group by hodex, devid order by hodex
```

Dataset Name	Description	Log Category
sdwan-Device-Packetloss-Line	SD-WAN Device Packet Loss Timeline	event

```

select
  $flex_timescale(timestamp) as hodex,
  devid,
  min(packetloss) as packetloss
from
  (
    select
      timestamp,
      devid,
      interface,
      sum(packetloss)/ sum(count) as packetloss
    from
      ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as
      sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
      (failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
      as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
      max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
      (packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
      inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
      count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
      healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
      (CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
      packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
      1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
      0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
      failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
      WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
      THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
      ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
      (healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
      status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
      packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
      status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
      THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
      convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
      bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
      interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
      timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
      desc/*SkipEND*/)### t where $filter-drilldown and packetloss is not null group by timestamp,
      devid, interface having sum(count)>0) t1 group by hodex, devid order by hodex

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Summary-by-Bibandwidth	SD-WAN Device Interface Summary by Bibandwidth	event

```

select
  devid,
  interface,
  sum(bibandwidth)/ sum(count) as bibandwidth,
  cast(
    min(latency_min) as decimal(18, 2)

```

```

) as latency_min,
cast(
    sum(latency)/ sum(count) as decimal(18, 2)
) as latency_avg,
cast(
    max(latency_max) as decimal(18, 2)
) as latency_max,
cast(
    min(jitter_min) as decimal(18, 2)
) as jitter_min,
cast(
    sum(jitter)/ sum(count) as decimal(18, 2)
) as jitter_avg,
cast(
    max(jitter_max) as decimal(18, 2)
) as jitter_max,
cast(
    min(packetloss_min) as decimal(18, 2)
) as packetloss_min,
cast(
    sum(packetloss)/ sum(count) as decimal(18, 2)
) as packetloss_avg,
cast(
    max(packetloss_max) as decimal(18, 2)
) as packetloss_max
from
    ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and interface is not null group by devid,
interface having sum(count)>0 order by devid, interface

```

Dataset Name	Description	Log Category
sdwan-Top-App-By-Bandwidth	Top SD-WAN application by bandwidth	traffic

```
select
  appid,
  app_group,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
  srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
  (vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
  (`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
  (`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
  sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
  rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
  as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
  group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
  appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
  group by appid, app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Top-App-By-Bandwidth-Sankey	Top SD-WAN application by bandwidth usage	traffic

```
select
  & #039;SD-WAN Utilization' as summary, app_group, devid, dstintf as interface, sum
  (bandwidth) as bandwidth from ###(select $flex_timestamp as timestamp, csf, devid, vd,
  srccountry, dstintf, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_name(app)
  as app_group, coalesce(vwlname,vwlservice) as rulename, service, coalesce(nullifna
  (`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore,
  coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce
  (sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce
  (rcvddelta, rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_
  out, count(*) as sessions from $log-traffic where $filter and vwlid IS NOT NULL and
  (logflag&(1|32)>0) group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf,
  srcintfrole, dstintfrole, appid, appcat, app_group, rulename, service, user_src, dev_src)###
  t where $filter-drilldown group by app_group, devid, interface order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-Interface-bandwidth-Drilldown	SD-WAN Device Statistic by Bibandwidth	event

```
select
  devid,
  sum(bibandwidth) / sum(count) as bibandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
  rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
  jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
  latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
  max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
  (packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
  inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
```

```
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and bibandwidth is not null group by devid
having sum(count)>0 order by bibandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-Rules-Donut-Bandwidth	Top SD-WAN Links bandwidth	traffic

```
select
  coalesce(
    rulename,
    & #039;Unknown') as rulename, sum(bandwidth) as bandwidth from ###(select $flex_
timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf, srcintfrole,
dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce(vwlname,vwlservice)
as rulename, service, coalesce(nullifna(`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as
dev_src, sum(crscore%65536) as crscore, coalesce(nullifna(`user`), nullifna(`unauthuser`),
ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta,
rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta, rcvdbyte, 0)) as traffic_in, sum
(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*) as sessions from $log-traffic
where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0) group by timestamp, srccountry,
dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group,
rulename, service, user_src, dev_src)### t where $filter-drilldown group by rulename order
by bandwidth desc limit 10
```

Dataset Name	Description	Log Category
sdwan-device-interface-bandwidth	Top SD-WAN Links bandwidth	traffic

```
select
  interface,
  sum(bandwidth) as bandwidth
from
  (
    (
      select
        srcintf as interface,
        sum(bandwidth) as bandwidth
      from
```



```

    ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf,
srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where srcintfrole='wan'
and $filter-drilldown group by interface) union all (select dstintf as interface, sum
(bandwidth) as bandwidth from ###(select $flex_timestamp as timestamp, csf, devid, vd,
srccountry, dstintf, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_name(app)
as app_group, coalesce(vwlname,vwlservice) as rulename, service, coalesce(nullifna
(`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce
(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce
(rcvddelta, rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_
out, count(*) as sessions from $log-traffic where $filter and vwlid IS NOT NULL and
(logflag&(1|32)>0) group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group, rulename, service, user_src, dev_src)###
t where $filter-drilldown group by interface)) t group by interface order by bandwidth desc
limit 10

```

Dataset Name	Description	Log Category
sdwan-Top-Application-Session-Bandwidth	Top SD-WAN application by bandwidth	traffic

```

select
  appid,
  app_group,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
group by appid, app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
sdwan-Top-Users-By-Bandwidth-Bar	SD-WAN Top users by bandwidth usage	traffic

```

select
  user_src,
  sum(bandwidth) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,

```

```
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
group by user_src order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-top-user-app-Drilldown	SD-WAN Top users and Application by bandwidth	traffic

```
select
  user_src,
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
group by user_src, app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-Intfe-traffic-out-bandwidth-Line	SD-WAN Device-Interface traffic sent bandwidth Timeline	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  t1.dstintf as interface,
  sum(traffic_out) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t1 inner join (select
dstintf, count(*) as num_intf from ###(select $flex_timestamp as timestamp, csf, devid, vd,
srccountry, dstintf, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_name(app)
as app_group, coalesce(vwlname,vwlservice) as rulename, service, coalesce(nullifna
(`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore,
```

```
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(
sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(
rcvddelta, rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_
out, count(*) as sessions from $log-traffic where $filter and vwld IS NOT NULL and
(logflag&(1|32)>0) group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group, rulename, service, user_src, dev_src)###
t where $filter-drilldown group by dstintf order by num_intf desc limit 10)t2 on
t1.dstintf=t2.dstintf group by hindex, t1.dstintf order by hindex
```

Dataset Name	Description	Log Category
sdwan-Device-Intfe-traffic-in-bandwidth-Line	SD-WAN Device-Interface traffic received bandwidth Timeline	traffic

```
select
  $flex_timescale(timestamp) as hindex,
  t1.srcintf as interface,
  sum(traffic_in) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce(
vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr(
`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna(
`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwld IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t1 inner join (select
srcintf, count(*) as num_intf from ###(select $flex_timestamp as timestamp, csf, devid, vd,
srccountry, dstintf, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_name(app)
as app_group, coalesce(vwlname,vwlservice) as rulename, service, coalesce(nullifna(
`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(
sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(
rcvddelta, rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_
out, count(*) as sessions from $log-traffic where $filter and vwld IS NOT NULL and
(logflag&(1|32)>0) group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group, rulename, service, user_src, dev_src)###
t where $filter-drilldown and srcintf is not null and srcintfrole ='wan' group by srcintf
order by num_intf desc limit 10)t2 on t1.srcintf=t2.srcintf group by hindex, t1.srcintf order
by hindex
```

Dataset Name	Description	Log Category
sdwan-Device-Intfe-traffic-bandwidth-Line	SD-WAN Device-Interface traffic sent bandwidth Timeline	traffic

```
select
  $flex_timescale(timestamp) as hindex,
  t1.dstintf as interface,
  sum(traffic_out) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce(
vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
```

```
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta, rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*) as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0) group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group, rulename, service, user_src, dev_src)### t1 inner join (select dstintf, count(*) as num_intf from ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta, rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*) as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0) group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown group by dstintf order by num_intf desc limit 10)t2 on t1.dstintf=t2.dstintf group by hindex, t1.dstintf order by hindex
```

Dataset Name	Description	Log Category
sdwan-Device-SLA-Interface-bandwidth-Drilldown	SD-WAN Device Statistic by Bibandwidth	event

```
select
  devid,
  sum(bibandwidth)/ sum(count) as bibandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter, max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface, healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency, (CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
```

```
desc/*SkipEND*/)### t where $filter-drilldown and bibandwidth is not null group by devid
having sum(count)>0 order by bibandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-SLA-Rule-Latency-Line	SD-WAN Device-SLA-Rule Latency Line	event

```
select
  $flex_timescale(timestamp) as hodesk,
  t1.intf_sla,
  sum(latency)/ sum(count) as latency
from
  (
    select
      timestamp,
      interface || & #039;;' || sla_rule as intf_sla, sum(latency) as latency, sum(count) as
count from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck
as sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where latency is not null group by timestamp, intf_sla having sum
(count)>0) t1 inner join (select interface || ':' || sla_rule as intf_sla, count(*) as num_
intf from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as
sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
```

```

0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and sla_rule is not null group by intf_sla
order by num_intf desc limit 10)t2 on t1.intf_sla=t2.intf_sla group by hindex, t1.intf_sla
order by hindex

```

Dataset Name	Description	Log Category
sdwan-Device-SLA-Rule-Jitter-Line	SD-WAN Device-SLA-Rule Jitter Line	event

```

select
  $flex_timescale(timestamp) as hindex,
  t1.intf_sla,
  sum(jitter)/ sum(count) as jitter
from
  (
    select
      timestamp,
      interface || & #039;;' || sla_rule as intf_sla, sum(jitter) as jitter, sum(count) as
count from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck
as sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by

```

```
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)#### t where jitter is not null group by timestamp, intf_sla having sum
(count)>0) t1 inner join (select interface || ':' || sla_rule as intf_sla, count(*) as num_
intf from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as
sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum
(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency)
as latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)#### t where $filter-drilldown and sla_rule is not null group by intf_sla
order by num_intf desc limit 10)t2 on t1.intf_sla=t2.intf_sla group by hodex, t1.intf_sla
order by hodex
```

Dataset Name	Description	Log Category
sdwan-Device-SLA-Rule-Packetloss-Line	SD-WAN Device-SLA-Rule Packetloss Line	event

```
select
  $flex_timescale(timestamp) as hodex,
  t1.intf_sla,
  sum(packetloss)/ sum(count) as packetloss
from
  (
    select
      timestamp,
      interface || & #039;:' || sla_rule as intf_sla, sum(packetloss) as packetloss, sum
(count) as count from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface,
healthcheck as sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_
latency, sum(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss,
sum(latency) as latency, max(latency) as latency_max, min(latency) as latency_min, sum
(jitter) as jitter, max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as
packetloss, max(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum
(inbandwidth) as inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as
bibandwidth, count(*) as count, min(sdwan_status) as sdwan_status from (select itime, csf,
devid, vd, interface, healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0
```



```

END) AS latency, (CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN
link_status=1 THEN packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND
metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND
metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND
metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE
sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS
inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE
WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth from (select itime, csf,
devid, vd, interface, coalesce(healthcheck, name) as healthcheck, (CASE WHEN status='down'
THEN 0 ELSE 1 END) AS link_status, latency::float as latency, jitter::float as jitter, trim
(trailing '%' from packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN
1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA
status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as
inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num
(bibandwidth) as bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND
status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT
NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by
timestamp desc/*SkipEND*/)### t where packetloss is not null group by timestamp, intf_sla
having sum(count)>0) t1 inner join (select interface || ':' || sla_rule as intf_sla, count
(*) as num_intf from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface,
healthcheck as sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_
latency, sum(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss,
sum(latency) as latency, max(latency) as latency_max, min(latency) as latency_min, sum
(jitter) as jitter, max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as
packetloss, max(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum
(inbandwidth) as inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as
bibandwidth, count(*) as count, min(sdwan_status) as sdwan_status from (select itime, csf,
devid, vd, interface, healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0
END) AS latency, (CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN
link_status=1 THEN packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND
metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND
metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND
metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE
sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS
inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE
WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth from (select itime, csf,
devid, vd, interface, coalesce(healthcheck, name) as healthcheck, (CASE WHEN status='down'
THEN 0 ELSE 1 END) AS link_status, latency::float as latency, jitter::float as jitter, trim
(trailing '%' from packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN
1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA
status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as
inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num
(bibandwidth) as bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND
status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT
NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by
timestamp desc/*SkipEND*/)### t where $filter-drilldown and sla_rule is not null group by
intf_sla order by num_intf desc limit 10)t2 on t1.intf_sla=t2.intf_sla group by hindex,
t1.intf_sla order by hindex

```

Dataset Name	Description	Log Category
sdwan-device-sla-intf-latency-pass-percent	SD-WAN Device Latency Pass Percentage by SLA rules and Interface	event

```

select
    sla_rule,

```



```

interface,
cast(
  100 *(
    1 - sum(failed_latency) / sum(count)
  ) as decimal(18, 2)
) as latency
from
###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown group by sla_rule, interface having sum
(count)>0 order by latency desc

```

Dataset Name	Description	Log Category
sdwan-device-sla-intf-jitter-pass-percent	SD-WAN Device Jitter Pass Percentage by SLA rules and Interface	event

```

select
  sla_rule,
  interface,
cast(
  100 *(
    1 - sum(failed_jitter) / sum(count)
  ) as decimal(18, 2)
) as jitter
from
###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as

```

```

inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown group by sla_rule, interface having sum
(count)>0 order by jitter desc

```

Dataset Name	Description	Log Category
sdwan-device-sla-intf-packetloss-pass-percent	SD-WAN Device Packet Loss Pass Percentage by SLA rules and Interface	event

```

select
  sla_rule,
  interface,
  cast(
    100 *(
      1 - sum(failed_packetloss)/ sum(count)
    ) as decimal(18, 2)
  ) as packetloss
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from

```

```
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown group by sla_rule, interface having sum
(count)>0 order by packetloss desc
```

Dataset Name	Description	Log Category
sdwan-Device-Availability-status	SD-WAN Device Statistic by Bibandwidth	event

```
select
  devid,
  sum(bibandwidth)/ sum(count) as bibandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and bibandwidth is not null group by devid
having sum(count)>0 order by bibandwidth desc
```

Dataset Name	Description	Log Category
sdwan-device-intf-availability- percentage-bar	SD-WAN Device Interface Availability Percentage	event

```
(
  select
    & #039;SD-WAN' as interface, cast(sum(availcnt)*100.0/sum(count) as decimal(18,2)) as
available from (select timestamp, devid, first_value(count) OVER (PARTITION BY timestamp,
```

```

devid ORDER BY link_status/count desc, count desc) as count, first_value(link_status) OVER
(PARTITION BY timestamp, devid ORDER BY link_status/count desc, count desc) as availcnt from
(select timestamp, devid, interface, sum(link_status) as link_status, sum(count) as count
from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and count>0 group by timestamp, devid,
interface)t) t group by interface) union all (select interface, cast(sum(link_
status)*100.0/sum(count) as decimal(18,2)) as available from ###(select $flex_timestamp as
timestamp, csf, devid, vd, interface, healthcheck as sla_rule, sum(link_status) as link_
status, sum(failed_latency) as failed_latency, sum(failed_jitter) as failed_jitter, sum
(failed_packetloss) as failed_packetloss, sum(latency) as latency, max(latency) as latency_
max, min(latency) as latency_min, sum(jitter) as jitter, max(jitter) as jitter_max, min
(jitter) as jitter_min, sum(packetloss) as packetloss, max(packetloss) as packetloss_max,
min(packetloss) as packetloss_min, sum(inbandwidth) as inbandwidth, sum(outbandwidth) as
outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as count, min(sdwan_status) as
sdwan_status from (select itime, csf, devid, vd, interface, healthcheck, link_status, (CASE
WHEN link_status=1 THEN latency ELSE 0 END) AS latency, (CASE WHEN link_status=1 THEN jitter
ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN packetloss ELSE 100 END) AS packetloss,
(CASE WHEN sla_failed=1 AND metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss,
(CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN
sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_
failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN
inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0
END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth
from (select itime, csf, devid, vd, interface, coalesce(healthcheck, name) as healthcheck,
(CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_status, latency::float as latency,
jitter::float as jitter, trim(trailing '%' from packetloss)::float as packetloss, (CASE WHEN
msg LIKE '%SLA failed%' THEN 1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric,
(CASE WHEN msg LIKE '%SLA status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num
(inbandwidth) as inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_
unit_to_num(bibandwidth) as bibandwidth from $log where $filter and logid_to_int
(logid)=22925 AND status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL

```

```
OR name IS NOT NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck
/*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown group by
interface order by interface)
```

Dataset Name	Description	Log Category
sdwan-device-intf-availability-percentage-donut	SD-WAN Device Interface Availability Percentage Donut	event

```
select
  interface,
  unnest(avail) as avail,
  unnest(val) as val
from
  (
    select
      interface,
      array[ & #039;Available', 'Unavailable'] as avail, array[available, 100-available] as
val from ((select 'SD-WAN' as interface, cast(sum(availcnt)*100.0/sum(count) as decimal
(18,2)) as available from (select timestamp, devid, first_value(count) OVER (PARTITION BY
timestamp, devid ORDER BY link_status/count desc, count desc) as count, first_value(link_
status) OVER (PARTITION BY timestamp, devid ORDER BY link_status/count desc, count desc) as
availcnt from (select timestamp, devid, interface, sum(link_status) as link_status, sum
(count) as count from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface,
healthcheck as sla_rule, sum(link_status) as link_status, sum(failed_latency) as failed_
latency, sum(failed_jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss,
sum(latency) as latency, max(latency) as latency_max, min(latency) as latency_min, sum
(jitter) as jitter, max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as
packetloss, max(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum
(inbandwidth) as inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as
bibandwidth, count(*) as count, min(sdwan_status) as sdwan_status from (select itime, csf,
devid, vd, interface, healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0
END) AS latency, (CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN
link_status=1 THEN packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND
metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND
metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND
metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE
sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS
inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE
WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth from (select itime, csf,
devid, vd, interface, coalesce(healthcheck, name) as healthcheck, (CASE WHEN status='down'
THEN 0 ELSE 1 END) AS link_status, latency::float as latency, jitter::float as jitter, trim
(trailing '%' from packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN
1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA
status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as
inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num
(bibandwidth) as bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND
status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT
NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by
timestamp desc/*SkipEND*/)### t where $filter-drilldown and count>0 group by timestamp,
devid, interface)t) t group by interface) union all (select interface, cast(sum(link_
status)*100.0/sum(count) as decimal(18,2)) as available from ###(select $flex_timestamp as
timestamp, csf, devid, vd, interface, healthcheck as sla_rule, sum(link_status) as link_
status, sum(failed_latency) as failed_latency, sum(failed_jitter) as failed_jitter, sum
(failed_packetloss) as failed_packetloss, sum(latency) as latency, max(latency) as latency_
max, min(latency) as latency_min, sum(jitter) as jitter, max(jitter) as jitter_max, min
```

```
(jitter) as jitter_min, sum(packetloss) as packetloss, max(packetloss) as packetloss_max,
min(packetloss) as packetloss_min, sum(inbandwidth) as inbandwidth, sum(outbandwidth) as
outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as count, min(sdwan_status) as
sdwan_status from (select itime, csf, devid, vd, interface, healthcheck, link_status, (CASE
WHEN link_status=1 THEN latency ELSE 0 END) AS latency, (CASE WHEN link_status=1 THEN jitter
ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN packetloss ELSE 100 END) AS packetloss,
(CASE WHEN sla_failed=1 AND metric='packetloss' THEN 1 ELSE 0 END) AS failed_packetloss,
(CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE 0 END) AS failed_jitter, (CASE WHEN
sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS failed_latency, (CASE WHEN sla_
failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE WHEN link_status=1 THEN
inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1 THEN outbandwidth ELSE 0
END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth ELSE 0 END) AS bibandwidth
from (select itime, csf, devid, vd, interface, coalesce(healthcheck, name) as healthcheck,
(CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_status, latency::float as latency,
jitter::float as jitter, trim(trailing '%' from packetloss)::float as packetloss, (CASE WHEN
msg LIKE '%SLA failed%' THEN 1 WHEN status='down' THEN 1 ELSE 0 END) AS sla_failed, metric,
(CASE WHEN msg LIKE '%SLA status%' THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num
(inbandwidth) as inbandwidth, convert_unit_to_num(outbandwidth) as outbandwidth, convert_
unit_to_num(bibandwidth) as bibandwidth from $log where $filter and logid_to_int
(logid)=22925 AND status IS NOT NULL AND interface IS NOT NULL AND (healthcheck IS NOT NULL
OR name IS NOT NULL)) t) t group by timestamp, csf, devid, vd, interface, healthcheck
/*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown group by
interface order by interface)) t) t
```

Dataset Name	Description	Log Category
sdwan-Device-Application-sdwan-Rules-and-Ports-drilldown	SD-WAN Device Statistic by Bibandwidth	event

```
select
  devid,
  sum(bibandwidth)/ sum(count) as bibandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
```

```
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and bibandwidth is not null group by devid
having sum(count)>0 order by bibandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Application-Traffic-Sankey	Top SD-WAN application by bandwidth sankey	traffic

```
select
  & #039;SD-WAN Rules' as summary, 'Rule:' || coalesce(rulename, 'Unknown') as rule_name,
  app_group, devid, dstintf as interface, sum(bandwidth) as bandwidth from ###(select $flex_
  timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf, srcintfrole,
  dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce(vwlname,vwlservice)
  as rulename, service, coalesce(nullifna(`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as
  dev_src, sum(crscore%65536) as crscore, coalesce(nullifna(`user`), nullifna(`unauthuser`),
  ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta,
  rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta, rcvdbyte, 0)) as traffic_in, sum
  (coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*) as sessions from $log-traffic
  where $filter and vwolid IS NOT NULL and (logflag&(1|32)>0) group by timestamp, srccountry,
  dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group,
  rulename, service, user_src, dev_src)### t where $filter-drilldown group by rule_name, app_
  group, devid, interface order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-fw-Device-Interface-test2	SD-WAN Device-Interface Statistic	event

```
select
  devid,
  sum(bibandwidth)/ sum(count) as bibandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
  rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
  jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
  latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
  max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
  (packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
  inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
  count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
  healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
  (CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
  packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
  1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
  0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
  failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
  WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
  THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
  ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
  (healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
  status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
  packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
  status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
  THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
```



```
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and bibandwidth is not null group by devid
having sum(count)>0 order by bibandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-Intf-Avail-Percentage-Timeline	SD-WAN Device Interface Availability Percentage Timeline	event

```
select
  horex,
  interface,
  available
from
  (
    (
      select
        $flex_datetime(timestamp) as horex,
        & #039;SD-WAN' as interface, cast(sum(availcnt)*100.0/sum(count) as decimal(18,2))
as available from (select timestamp, devid, first_value(count) OVER (PARTITION BY timestamp,
devid ORDER BY link_status/count desc, count desc) as count, first_value(link_status) OVER
(PARTITION BY timestamp, devid ORDER BY link_status/count desc, count desc) as availcnt from
(select timestamp, devid, interface, sum(link_status) as link_status, sum(count) as count
from ###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_
rule, sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_
jitter) as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as
latency, max(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter,
max(jitter) as jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max
(packetloss) as packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as
inbandwidth, sum(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as
count, min(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface,
healthcheck, link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency,
(CASE WHEN link_status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN
packetloss ELSE 100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN
1 ELSE 0 END) AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE
0 END) AS failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS
failed_latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE
WHEN link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1
THEN outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth
ELSE 0 END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce
(healthcheck, name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_
status, latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown and count>0 group by timestamp, devid,
interface)t) t group by horex order by horex) union all (select $flex_datetime(timestamp) as
horex, interface, cast(sum(link_status)*100.0/sum(count) as decimal(18,2)) as available from
###(select $flex_timestamp as timestamp, csf, devid, vd, interface, healthcheck as sla_rule,
```



```
sum(link_status) as link_status, sum(failed_latency) as failed_latency, sum(failed_jitter)
as failed_jitter, sum(failed_packetloss) as failed_packetloss, sum(latency) as latency, max
(latency) as latency_max, min(latency) as latency_min, sum(jitter) as jitter, max(jitter) as
jitter_max, min(jitter) as jitter_min, sum(packetloss) as packetloss, max(packetloss) as
packetloss_max, min(packetloss) as packetloss_min, sum(inbandwidth) as inbandwidth, sum
(outbandwidth) as outbandwidth, sum(bibandwidth) as bibandwidth, count(*) as count, min
(sdwan_status) as sdwan_status from (select itime, csf, devid, vd, interface, healthcheck,
link_status, (CASE WHEN link_status=1 THEN latency ELSE 0 END) AS latency, (CASE WHEN link_
status=1 THEN jitter ELSE 0 END) AS jitter, (CASE WHEN link_status=1 THEN packetloss ELSE
100 END) AS packetloss, (CASE WHEN sla_failed=1 AND metric='packetloss' THEN 1 ELSE 0 END)
AS failed_packetloss, (CASE WHEN sla_failed=1 AND metric='jitter' THEN 1 ELSE 0 END) AS
failed_jitter, (CASE WHEN sla_failed=1 AND metric='latency' THEN 1 ELSE 0 END) AS failed_
latency, (CASE WHEN sla_failed=1 THEN 3 ELSE sdwan_status END) AS sdwan_status, (CASE WHEN
link_status=1 THEN inbandwidth ELSE 0 END) AS inbandwidth, (CASE WHEN link_status=1 THEN
outbandwidth ELSE 0 END) AS outbandwidth, (CASE WHEN link_status=1 THEN bibandwidth ELSE 0
END) AS bibandwidth from (select itime, csf, devid, vd, interface, coalesce(healthcheck,
name) as healthcheck, (CASE WHEN status='down' THEN 0 ELSE 1 END) AS link_status,
latency::float as latency, jitter::float as jitter, trim(trailing '%' from
packetloss)::float as packetloss, (CASE WHEN msg LIKE '%SLA failed%' THEN 1 WHEN
status='down' THEN 1 ELSE 0 END) AS sla_failed, metric, (CASE WHEN msg LIKE '%SLA status%'
THEN 1 ELSE 0 END) AS sdwan_status, convert_unit_to_num(inbandwidth) as inbandwidth,
convert_unit_to_num(outbandwidth) as outbandwidth, convert_unit_to_num(bibandwidth) as
bibandwidth from $log where $filter and logid_to_int(logid)=22925 AND status IS NOT NULL AND
interface IS NOT NULL AND (healthcheck IS NOT NULL OR name IS NOT NULL)) t) t group by
timestamp, csf, devid, vd, interface, healthcheck /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t where $filter-drilldown group by hodex, interface order by hodex)) t
order by hodex
```

Dataset Name	Description	Log Category
Top-Web-Sites-by-Bandwidth	Top web sites by bandwidth usage	webfilter

```
select
  domain,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and (logflag&1>0) and
(countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent
in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by
domain having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc)###
t group by domain order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-App-Category-by-Session	Application risk application usage by category	traffic

```
select
  appcat,
  sum(sessions) as total_num
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as
sessions from ###base(/*tag:rpt_base_t_top_app*/select dvid, srcip, dstip, epid, euid,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, appid, app,
appcat, apprisk, sum(coalesce(sentsdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, count(*) as sessions from $log-traffic where $filter and (logflag&(1|32)>0) and
```

```

nullifna(app) is not null group by dvid, srcip, dstip, epid, euid, user_src, appid, app,
appcat, apprisk order by sessions desc)base### t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
group by appcat order by total_num desc

```

Dataset Name	Description	Log Category
Top-Region-Name-by-Traffic	Traffic top destination countries by browsing time	traffic

```

select
    dstcountry,
    sum(bandwidth) as bandwidth
from
    ###(select dstcountry, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from (select
dstcountry, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce
(sentbyte, 0)) as traffic_out from $log where $filter and (logflag&1>0) and $browse_time is
not null group by dstcountry) t group by dstcountry /*SkipSTART*/order by ebtr_value(ebtr_
agg_flat(browsetime), null, null) desc/*SkipEND*/)### t where $filter-drilldown group by
dstcountry order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-App-By-Bandwidth-Chart	Top applications by bandwidth usage	traffic

```

select
    app_group_name(app) as app_group,
    sum(
        coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvddelta, rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentdelta, sentbyte, 0)
    ) as traffic_out,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag &(1 | 32)> 0
    )
    and nullifna(app) is not null
group by
    app_group
having
    sum(
        coalesce(sentdelta, sentbyte, 0)+ coalesce(rcvddelta, rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
Top-Protocols-By-Traffic	Top applications by bandwidth usage	traffic

```
select
  service,
  sum(bandwidth) as bandwidth
from
  ###(select service, sum(bandwidth) as bandwidth from ###base(/*tag:rpt_base_t_bndwidth_
sess*/select $flex_timestamp as timestamp, dvid, srcip, dstip, epid, euid, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, service, count(*) as
sessions, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as
bandwidth, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in from $log-traffic where $filter and (logflag&(1|32)>0) group by
timestamp, dvid, srcip, dstip, epid, euid, user_src, service /*SkipSTART*/order by timestamp
desc/*SkipEND*/)base### base_query group by service order by bandwidth desc)### t where
$filter-drilldown group by service order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Web-Sites-by-Sessions	Top web sites by session count	webfilter

```
select
  domain,
  sum(sessions) as sessions
from
  ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, count(*) as sessions
from $log where $filter and (eventtype is null or logver>=502000000) group by domain order
by sessions desc)### t group by domain order by sessions desc
```

Dataset Name	Description	Log Category
Top-Attacks-by-Count	Threat attacks by severity	attack

```
select
  attack,
  sum(attack_count) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, attack, (case when
severity in ('critical', 'high') then 1 else 0 end) as high_severity, count(*) as attack_
count from $log where $filter and nullifna(attack) is not null group by user_src, attack,
high_severity order by attack_count desc)### t where $filter-drilldown and attack is not
null group by attack order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Spams-by-Count	User drilldown top spam sources	emailfilter

```
select
  user_src,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, coalesce(nullifna(`user`), ipstr(`srcip`)) as
user_src, `from` as mf_sender, `to` as mf_receiver, action, eventtype, count(*) as totalnum
from $log where $filter group by timestamp, user_src, mf_sender, mf_receiver, action,
```

```
eventtype /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown and
mf_sender is not null group by user_src order by totalnum desc
```

Dataset Name	Description	Log Category
utm-Top-Virus-Count	UTM top virus	virus

```
select
  virus,
  max(virusid_s) as virusid,
  (
    case when virus like & #039;Riskware%' then 'Spyware' when virus like 'Adware%' then
'Adware' else 'Virus' end) as malware_type, sum(totalnum) as totalnum from ###(select virus,
virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where
$filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not null group
by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by virus,
malware_type order by totalnum desc
```

Dataset Name	Description	Log Category
security-Antivirus-Inspections	Antivirus Inspections	virus

```
select
  action,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, coalesce(nullifna(`user`), ipstr(`srcip`)) as
user_src, `from` as mf_sender, `to` as mf_receiver, action, eventtype, count(*) as totalnum
from $log where $filter group by timestamp, user_src, mf_sender, mf_receiver, action,
eventtype /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t where $filter-drilldown and
action is not null group by action order by totalnum desc
```

Dataset Name	Description	Log Category
Top-DLP-by-Count	Email DLP Activity Summary	dlp

```
select
  profile,
  count(*) as total_num
from
  ###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
subtype, srcip, dstip, severity, filename, direction, filesize, (case when
severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
(`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
$filter-drilldown and profile is not null group by profile order by total_num desc
```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Client	Top access point by client	traffic

```
select
  ap_srcintf as srcintf,
  count(distinct srcmac) as totalnum
from
  (
```

```

select
  coalesce(ap, srcintf) as ap_srcintf,
  srcmac
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna
(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as
osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter
and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap,
srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal
desc/*SkipEND*/)### t where srcmac is not null group by ap_srcintf, srcmac union all (select
ap as ap_srcintf, stamac as srcmac from ###(select $flex_timestamp as timestamp, stamac,
stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentdelta, 0)) as
sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce
(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr
(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order
by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over (partition by stamac order
by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is
not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req',
'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by
bandwidth desc/*SkipEND*/)### t where stamac is not null group by ap, stamac)) t group by
srcintf order by totalnum desc

```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Bandwidth	Top access point by bandwidth usage	traffic

```

select
  ap_srcintf,
  sum(bandwidth) as bandwidth
from
  (
    select
      coalesce(ap, srcintf) as ap_srcintf,
      sum(bandwidth) as bandwidth
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna
(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as
osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter
and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap,
srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal
desc/*SkipEND*/)### t group by ap_srcintf having sum(bandwidth)>0 union all select ap as ap_
srcintf, sum(bandwidth) as bandwidth from ###(select $flex_timestamp as timestamp, stamac,
stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentdelta, 0)) as
sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce
(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr
(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order
by itime) as sentdelta, rcvdbyte-lag(coalesce(rcvdbyte, 0)) over (partition by stamac order
by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is
not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req',
'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by
bandwidth desc/*SkipEND*/)### t group by ap having sum(bandwidth)>0) t group by ap_srcintf
order by bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-SSID-By-Bandwidth	Top SSIDs by bandwidth usage	traffic

```
select
  srcssid,
  sum(bandwidth) as bandwidth
from
  (
    select
      srcssid,
      sum(bandwidth) as bandwidth
    from
      ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ap, srcintf, srcssid, srcssid as ssid, srcmac, srcmac as stamac, coalesce(nullifna(`srcname`), `srcmac`) as hostname_mac, max(srcswversion) as srcswversion, max(osname) as osname, max(osversion) as osversion, max(devtype) as devtype, sum(coalesce(sentbyte, 0)+coalesce(rcvddelta, 0)) as bandwidth, count(*) as subtotal from $log-traffic where $filter and (logflag&1>0) and (srcssid is not null or dstssid is not null) group by user_src, ap, srcintf, srcssid, srcmac, hostname_mac /*SkipSTART*/order by bandwidth desc, subtotal desc/*SkipEND*/)### t where srcssid is not null group by srcssid having sum(bandwidth)>0
    union all select ssid as srcssid, sum(bandwidth) as bandwidth from ###(select $flex_timestamp as timestamp, stamac, stamac as srcmac, ap, ssid, ssid as srcssid, user_src, sum(coalesce(sentdelta, 0)) as sentdelta, sum(coalesce(rcvddelta, 0)) as rcvddelta, sum(coalesce(sentdelta, 0)+coalesce(rcvddelta, 0)) as bandwidth from (select itime, stamac, ap, ssid, coalesce(`user`, ipstr(`srcip`)) as user_src, sentbyte-lag(coalesce(sentbyte, 0)) over (partition by stamac order by itime) as sentdelta, rcvddelta-lag(coalesce(rcvddelta, 0)) over (partition by stamac order by itime) as rcvddelta from $log-event where $filter and subtype='wireless' and stamac is not null and ssid is not null and action in ('sta-wl-bridge-traffic-stats', 'reassoc-req', 'assoc-req')) as t group by timestamp, stamac, ap, ssid, user_src /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t group by ssid having sum(bandwidth)>0) t group by srcssid order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-Total-Bandwidth-Internal-And-External	CTAP SD-WAN Internal and External Bandwidth	traffic

```
select
  interface,
  bandwidth
from
  (
    (
      select
        & #039;Internal' as interface, coalesce(sum(bandwidth), 0) as bandwidth from ###
      (select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvddelta, 0)) as bandwidth, sum(coalesce(rcvddelta, rcvddelta, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*) as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0) group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-
```

```
drilldown) union all (select 'External' as interface, coalesce(sum(bandwidth), 0) as
bandwidth from ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf,
srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-
drilldown)) t where bandwidth>0
```

Dataset Name	Description	Log Category
sdwan-CTAP-Total-Bandwidth-External-Business-nonBusiness-Network	CTAP SD-WAN Bandwidth of External Business and nonBusiness	traffic

```
select
(
case when appcat not in (
& #039;Network.Service',
'Mobile','Social.Media','Proxy','Video\Audio','Game','P2P','unknown') then 'Business' when
appcat in ('Mobile','Social.Media','Proxy','Video\Audio','Game','P2P','unknown') then
'nonBusiness'when appcat in ('Network.Service') then 'Network Service' end) as app_cat,
coalesce(sum(bandwidth), 0) as bandwidth from ###(select $flex_timestamp as timestamp, csf,
devid, vd, srccountry, dstintf, srcintf, srcintfrole, dstintfrole, appid, appcat, app_group_
name(app) as app_group, coalesce(vwlname,vwlservice) as rulename, service, coalesce(nullifna
(`srcname`),ipstr(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore,
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce
(sentdelta, sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce
(rcvddelta, rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_
out, count(*) as sessions from $log-traffic where $filter and vwlid IS NOT NULL and
(logflag&(1|32)>0) group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group, rulename, service, user_src, dev_src)###
t where $filter-drilldown group by app_cat order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-Top-Appcat-Appgroup-By-Bandwidth-Sankey	CTAP SD-WAN Top SD-WAN application by bandwidth usage	traffic

```
select
& #039;External' as summary, appcat, app_group, sum(bandwidth) as bandwidth from ###
(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
and bandwidth>0 group by appcat, app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-Business-Apps-Bandwidth	CTAP SD-WAN Business Application with Bandwidth	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t1 inner join app_mdata
t2 on lower(t1.app_group)=lower(t2.name) where $filter-drilldown and appcat not in
('Network.Service', 'Mobile','Social.Media','Proxy','Video\Audio','Game','P2P','unknown')
group by app_group order by bandwidth desc, app_group
```

Dataset Name	Description	Log Category
sdwan-CTAP-Cloud-IT-Apps-Bandwidth	CTAP SD-WAN Cloud IT Application Bandwidth	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
and appcat='Cloud.IT' and bandwidth>0 group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-Storage-Backup-Apps-Bandwidth	CTAP SD-WAN Storage Backup Application Bandwidth	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
```



```
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
and appcat='Storage.Backup' and bandwidth>0 group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-Collaboration-Apps-Bandwidth	CTAP SD-WAN Collaboration Application Bandwidth	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
and appcat='Collaboration' and bandwidth>0 group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-Top-Streaming-App-By-Bandwidth	CTAP SD-WAN Top Streaming Application by Bandwidth	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
and appcat='Video\Audio' and bandwidth>0 group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-Top-SocialMedia-App-By-Bandwidth	CTAP SD-WAN Top SocialMedia Application by Bandwidth	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth
from
  ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0))+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
and appcat='Social.Media' and bandwidth>0 group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-App-Risk-Reputation-Top-Devices-By-Scores	Reputation Top Devices By-Scores	traffic

```
select
  coalesce(
    nullifna(`srcname`),
    ipstr(`srcip`),
    nullifna(`srcmac`)
  ) as dev_src,
  sum(crscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crscore is not null
group by
  dev_src
having
  sum(crscore % 65536)> 0
order by
  scores desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-SB-Top-Sandbox-Files	CTAP SD-WAN Sandbox Top Sandbox Files	virus

```
select
  filename,
  analyticscksum,
  service,
  sum(totalnum) as total_num,
  (
    case fsaverdict when & #039;malicious' then 'Malicious' when 'high risk' then 'High'
when 'medium risk' then 'Medium' when 'low risk' then 'Low' else 'Other' end) as risk,
(case fsaverdict when 'malicious' then 5 when 'high risk' then 4 when 'medium risk' then 3
```

```
when 'low risk' then 2 else 1 end) as risk_level from ###(select filename, analyticscksum,
service, fsaverdict, dtype, coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus,
virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where
$filter group by filename, analyticscksum, service, fsaverdict, dtype, user_src, virus,
virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t where $filter-drilldown and
filename is not null and dtype='fortisandbox' and fsaverdict not in ('clean', 'submission
failed') group by filename, analyticscksum, risk_level, risk, service order by risk_level
desc, total_num desc, service, filename
```

Dataset Name	Description	Log Category
sdwan-CTAP-SB-Total-Number-of-Malicious-Suspicious-Files	CTAP SD-WAN Sandbox Malicious Suspicious Files Number	virus

```
select
(
case fsaverdict when & #039;malicious' then 'Malicious' when 'high risk' then 'High'
when 'medium risk' then 'Medium' when 'low risk' then 'Low' else 'Other' end) as risk, sum
(totalnum) as total_num from ###(select filename, analyticscksum, service, fsaverdict,
dtype, coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, virusid_to_str
(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where $filter group by
filename, analyticscksum, service, fsaverdict, dtype, user_src, virus, virusid_s
/*SkipSTART*/order by totalnum desc/*SkipEND*/)### t where $filter-drilldown and
dtype='fortisandbox' and fsaverdict not in ('clean','submission failed') group by risk order
by total_num desc
```

Dataset Name	Description	Log Category
sdwan-CTAP-Top-Source-Countries	CTAP SD-WAN Top Source Countries	traffic

```
select
srccountry,
sum(bandwidth) as bandwidth
from
###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
(vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
(`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
as sessions from $log-traffic where $filter and vwlid IS NOT NULL and (logflag&(1|32)>0)
group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
and nullifna(srccountry) is not null and srccountry <> 'Reserved' and bandwidth>0 group by
srccountry order by bandwidth desc, srccountry
```

Dataset Name	Description	Log Category
sdwan-CTAP-Average-Bandwidth-Day-Hour	CTAP SD-WAN Average Bandwidth by Day of Week and Hour	traffic

```
select
hourstamp,
daystamp,
round(
```

```

        sum(bandwidth) / count(*)
    ) as bandwidth
from
    (
        select
            $hour_of_day(timestamp) as hourstamp,
            $HOUR_OF_DAY(timestamp) as hour_stamp,
            $day_of_week(timestamp) as daystamp,
            sum(bandwidth) as bandwidth
        from
            ###(select $flex_timestamp as timestamp, csf, devid, vd, srccountry, dstintf, srcintf,
            srcintfrole, dstintfrole, appid, appcat, app_group_name(app) as app_group, coalesce
            (vwlname,vwlservice) as rulename, service, coalesce(nullifna(`srcname`),ipstr
            (`srcip`),nullifna(`srcmac`)) as dev_src, sum(crscore%65536) as crscore, coalesce(nullifna
            (`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentdelta,
            sentbyte, 0)+coalesce(rcvddelta, rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvddelta,
            rcvdbyte, 0)) as traffic_in, sum(coalesce(sentdelta, sentbyte, 0)) as traffic_out, count(*)
            as sessions from $log-traffic where $filter and vwldid IS NOT NULL and (logflag&(1|32)>0)
            group by timestamp, srccountry, dstintf, csf, devid, vd, srcintf, srcintfrole, dstintfrole,
            appid, appcat, app_group, rulename, service, user_src, dev_src)### t where $filter-drilldown
            group by hourstamp, hour_stamp, daystamp) t group by hourstamp, daystamp order by hourstamp

```

Dataset Name	Description	Log Category
sdwan-CTAP-Average-Log-Rate-By-Hour	CTAP SD-WAN Average Log Rate by Hour	event

```

select
    $hour_of_day(timestamp) as hourstamp,
    cast(
        (
            sum(
                total_trate + total_erate + total_orate
            )
        ) / sum(count) / 100.0 as decimal(10, 2)
    ) as log_rate
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
    trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
    (itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
    (coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
    as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
    (coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
    (totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
    (coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
    part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
    '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
    transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
    count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
    by timestamp, devid, slot)### t where $filter-drilldown group by hourstamp order by
    hourstamp

```

Dataset Name	Description	Log Category
sdwan-CTAP-CPU-Usage-Per-Hour	Event usage CPU	event

```

select
    $hour_of_day(timestamp) as hourstamp,
    cast(
        sum(total_cpu) / sum(count) as decimal(6, 2)
    ) as cpu_avg_usage
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by hourstamp order by hourstamp

```

Dataset Name	Description	Log Category
sdwan-CTAP-Memory-Usage-Per-Hour	Event usage memory	event

```

select
    $hour_of_day(timestamp) as hourstamp,
    cast(
        sum(total_mem) / sum(count) as decimal(6, 2)
    ) as mem_avg_usage
from
    ###(select $flex_timestamp as timestamp, devid, slot, sum(coalesce(trate, 0)) as total_
trate, sum(coalesce(erate, 0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, min
(itime) as first_seen, max(itime) as last_seen, sum(coalesce(mem, 0)) as total_mem, max
(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce(disk, 0))
as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_peak, max
(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce
(totalsession, 0)) as totalsession, max(coalesce(totalsession, 0)) as session_peak, sum(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_
part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as
transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak,
count(*) as count from $log where $filter and subtype='system' and action='perf-stats' group
by timestamp, devid, slot)### t group by hourstamp order by hourstamp

```

Dataset Name	Description	Log Category
Top-Destination-Addresses-By-Bandwidth-Bar	Top destinations by bandwidth usage	traffic

```

select
    coalesce(
        nullifna(
            root_domain(hostname)
        ),
        ipstr(dstip)
    )

```

```

    ) as domain,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and coalesce(
        nullifna(
            root_domain(hostname)
        ),
        ipstr(`dstip`)
    ) is not null
group by
    domain
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
intf-Timeline-Sampling	Interface Utilization Timeline by Data Sampling	event

```

with base_gry as (
    select
        tm,
        rcvdbps,
        ntile(100) over (
            order by
                rcvdbps
        ) as percentile
    from
        (
            select
                (timestamp / 300 * 300) as tm,
                sum(rcvdbps) as rcvdbps,
                300 as interval
            from
                intfstats_billing tbl
            join (
                select
                    ti.dvid,
                    intfname

```

```

        from
            intfinfo ti
        left join devtable td on ti.dvid = td.dvid
    where
        $dev_filter
    ) tb2 on tb1.dvid = tb2.dvid
    and tb1.intfname = tb2.intfname
where
    $cust_time_filter(timestamp)
group by
    tm
) tmp
),
ref_gry as (
    select
        cast(
            max(rcvdbps)/ 1000000 as decimal(18, 2)
        ) as ref_val
    from
        base_gry
    where
        percentile = 95
)
select
    from_otime(timestamp) as tmstamp,
    cast(
        rcvdbps / 1000000 as decimal(18, 2)
    ) as rcvdbps,
    ref_val
from
    ref_gry,
    (
        select
            tm as timestamp,
            rcvdbps,
            rank() over(
                partition by (tm / 3600)
                order by
                    tm
            ) as r
        from
            base_gry
    ) t
where
    r = 1
order by
    tmstamp

```

Dataset Name	Description	Log Category
intf-Util-Histogram	Interface Utilization Value Distribution	event

```

select
    cast(
        (
            (

```

```
        max(max_value) over ()
    ) * seq / 100
    ) as decimal(16, 0)
    ) as value,
    cnt
from
(
    select
        generate_series(0, 100, 2) as seq
    ) t1
left join (
    select
        perc,
        max_value,
        count(*) as cnt
    from
        (
            select
                WIDTH_BUCKET(
                    rcvdbps,
                    0,
                    (
                        max(rcvdbps) over ()
                    ) + 1,
                    50
                ) * 2 as perc,
                max(rcvdbps) over () as max_value
            from
                (
                    select
                        (timestamp / 300 * 300) as tm,
                        sum(rcvdbps) as rcvdbps,
                        300 as interval
                    from
                        intfstats_billing tb1
                    join (
                        select
                            ti.dvid,
                            intfname
                        from
                            intfinfo ti
                        left join devtable td on ti.dvid = td.dvid
                        where
                            $dev_filter
                    ) tb2 on tb1.dvid = tb2.dvid
                        and tb1.intfname = tb2.intfname
                    where
                        $cust_time_filter(timestamp)
                    group by
                        tm
                ) tmp
            ) t_bucket
        group by
            perc,
            max_value
    ) t2 on t1.seq = t2.perc
```



```
order by
  seq
```

Dataset Name	Description	Log Category
intf-Sorted-Line	Interface Utilization Line Sorted by bps	event

```
with base_gry as (
  select
    rcvdbps,
    ntile(100) over (
      order by
        rcvdbps
    ) as percentile
  from
    (
      select
        (timestamp / 300 * 300) as tm,
        sum(rcvdbps) as rcvdbps,
        300 as interval
      from
        intfstats_billing tbl
      join (
        select
          ti.dvid,
          intfname
        from
          intfinfo ti
        left join devtable td on ti.dvid = td.dvid
        where
          $dev_filter
      ) tb2 on tbl.dvid = tb2.dvid
      and tbl.intfname = tb2.intfname
      where
        $cust_time_filter(timestamp)
      group by
        tm
    ) tmp
),
ref_gry as (
  select
    cast(
      max(rcvdbps) / 1000000 as decimal(18, 2)
    ) as ref_val
  from
    base_gry
  where
    percentile = 95
)
select
  n_perc,
  cast(
    rcvdbps / 1000000 as decimal(18, 2)
  ) as rcvdbps,
  ref_val
from
```

```

(
  select
    seq as n_perc,
    rcvdbps
  from
    (
      select
        generate_series(0, 100, 1) as seq
      ) t1
  left join (
    select
      max(rcvdbps) as rcvdbps,
      percentile
    from
      base_gry
    group by
      percentile
  ) t2 on t1.seq = t2.percentile
) t,
ref_gry
order by
  n_perc

```

Dataset Name	Description	Log Category
intf-Data-Analysis-Table	Interface Utilization Data Analysis	event

```

with base_gry as (
  select
    rcvdbps,
    interval,
    ntile(100) over (
      order by
        rcvdbps
    ) as percentile
  from
    (
      select
        (timestamp / 300 * 300) as tm,
        sum(rcvdbps) as rcvdbps,
        300 as interval
      from
        intfstats_billing tb1
      join (
        select
          ti.dvid,
          intfname
        from
          intfinfo ti
          left join devtable td on ti.dvid = td.dvid
        where
          $dev_filter
      ) tb2 on tb1.dvid = tb2.dvid
      and tb1.intfname = tb2.intfname
    ) where
      $cust_time_filter(timestamp)

```

```

        group by
            tm
    ) tmp
)
select
    min_mbps,
    low_ref_mbps,
    mean_mbps,
    ref_mbps,
    peak_mbps,
    actual_gb,
    total
from
    (
        select
            cast(
                min(rcvdbps)/ 1000000 as decimal(18, 2)
            ) as min_mbps,
            cast(
                avg(rcvdbps)/ 1000000 as decimal(18, 2)
            ) as mean_mbps,
            cast(
                max(rcvdbps)/ 1000000 as decimal(18, 2)
            ) as peak_mbps,
            cast(
                (
                    select
                        max(rcvdbps)
                    from
                        base_qry
                    where
                        percentile = 5
                )/ 1000000 as decimal(18, 2)
            ) as low_ref_mbps,
            cast(
                (
                    select
                        max(rcvdbps)
                    from
                        base_qry
                    where
                        percentile = 95
                )/ 1000000 as decimal(18, 2)
            ) as ref_mbps,
            cast(
                sum(interval * rcvdbps)/ 8 /(1024 * 1024 * 1024) as decimal(18, 2)
            ) as actual_gb,
            count(*) as total
        from
            base_qry
    ) t

```

Dataset Name	Description	Log Category
360-degree-security-Application-Visibility-and-Control-Summary	Application Visibolity and Control Summary	app-ctrl

```
select
  appcat,
  count(distinct app) as total_num
from
  ###(select appcat, app from $log where $filter and app is not null and appcat is not null
group by appcat, app)### t group by appcat order by total_num desc
```

Dataset Name	Description	Log Category
360-degree-security-Threats-Detection-and-Prevention-Summary	Threat Prevention	app-ctrl

```
select
  threat_name,
  count(distinct threats) as total_num
from
  (
    ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name, app as threats from
$log-app-ctrl where $filter and lower(appcat)='botnet' group by app)### union all ###(select
cast('Malware & Botnet C&C' as char(32)) as threat_name, virus as threats from $log-virus
where $filter and nullifna(virus) is not null group by virus)### union all ###(select cast
('Malicious & Phishing Sites' as char(32)) as threat_name, hostname as threats from $log-
webfilter where $filter and cat in (26, 61) group by hostname)### union all ###(select cast
('Critical & High Intrusion Attacks' as char(32)) as threat_name, attack as threats from
$log-attack where $filter and severity in ('critical', 'high') group by attack)###) t group
by threat_name order by total_num desc
```

Dataset Name	Description	Log Category
360-degree-security-Data-Exfiltration-Detection-and-Prevention-Summary	Data Exfiltration Summary	dlp

```
select
  data_loss,
  count(*) as total_num
from
  ###(select itime, hostname, `from` as sender, `to` as receiver, profile, action, service,
subtype, srcip, dstip, severity, filename, direction, filesize, (case when
severity='critical' then 'Critical Data Exfiltration' else (case when coalesce(nullifna
(`user`), ipstr(`srcip`)) is not null then 'User Associated Data Loss' else NULL end) end)
as data_loss from $log where $filter /*SkipSTART*/order by itime desc/*SkipEND*/)### t where
$filter-drilldown and data_loss is not null group by data_loss order by total_num desc
```

Dataset Name	Description	Log Category
360-degree-security-Endpoint-Protection-Summary	Endpoint Protection	fct-traffic

```
select
  blocked_event,
  count(*) as total_num
from
  (
    select
      (
        case utmevent when & #039;antivirus' then 'Malware Deteced and Blocked' when
```

```
'appfirewall' then 'Risk Application Blocked' when 'webfilter' then (case when coalesce  
(nullifna(`user`), ipstr(`srcip`)) is not null then 'Web Sites Violation Blocked' else 'Non  
User Initiated Web Visits' end) else NULL end) as blocked_event from $log where $filter and  
utmaction in ('blocked', 'quarantined')) t where blocked_event is not null group by blocked_  
event order by total_num desc
```

Macro Reference List

The following table lists the available predefined macros that can be used in a report layout to display the log data as text (XML format) dynamically.

Macro Name	Description	Dataset Used	Log Category
Application Category with Highest Session Count	Application category with the highest session count	App-Sessions-By-Category	Traffic
Application with Highest Bandwidth	Application with the highest bandwidth usage	Top-App-By-Bandwidth	Traffic
Application with Highest Session Count	Applications with the highest session count	Top-App-By-Sessions	Traffic
Attack with Highest Session Count	Attack with highest session count	Utm-Top-Attack-Source	Attack
Botnet with Highest Session Count	Botnet with the highest session count	Detected-Botnet	Traffic
Destination with Highest Bandwidth	Destination with the highest bandwidth usage	Top-Destinations-By-Bandwidth	Traffic
Destination with Highest Session Count	Destination with the highest session count	Top-Destinations-By-Sessions	Traffic
Highest Bandwidth Consumed (Application) Category	Highest bandwidth consumed by application category	App-Risk-App-Usage-By-Category	Traffic
Highest Bandwidth Consumed (Application)	Highest bandwidth consumed by application	Top-App-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Destination)	Highest bandwidth consumed by destination	Top-Destinations-By-Bandwidth	Traffic
Highest Bandwidth Consumed (P2P Application)	Highest bandwidth consumed by P2P application	Top-P2P-App-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Source)	Highest bandwidth consumed by source	Top-Users-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Web Category)	Highest bandwidth consumed by website category	Top-Web-Category-by-Bandwidth	Web Filter
Highest Bandwidth Consumed (Website)	Highest bandwidth consumed by website	Top-Web-Sites-by-Bandwidth	Web Filter
Highest Risk Application with Highest Bandwidth	Highest risk application with the highest bandwidth usage	High-Risk-Application-By-Bandwidth	Traffic
Highest Risk Application with Highest Session Count	Highest risk application with the highest session count	High-Risk-Application-By-Sessions	Traffic

Macro Name	Description	Dataset Used	Log Category
Highest Session Count by Application Category	Highest session count by application category	App-Sessions-By-Category	Traffic
Highest Session Count by Application	Highest session count by application	Top-App-By-Sessions	Traffic
Highest Session Count by Attack	Highest session count by attack	Utm-Top-Attack-Source	Attack
Highest Session Count by Botnet	Highest session count by botnet	Detected-Botnet	Traffic
Highest Session Count by Destination	Highest session count by destination	Top-Destinations-By-Sessions	Traffic
Highest Session Count by Highest Severity Attack	Highest session count by highest severity attack	Threat-Attacks-By-Severity	Attack
Highest Session Count by P2P Application	Highest session count by P2P application	Top-P2P-App-By-Sessions	Traffic
Highest Session Count by Source	Highest session count by source	Top-User-Source-By-Sessions	Traffic
Highest Session Count by Virus	Highest session count by virus	Utm-Top-Virus	Traffic
Highest Session Count by Web Category	Highest session count by website category	Top-Web-Category-by-Sessions	Web Filter
Highest Session Count by Website	Highest session count by website	Top-Web-Sites-by-Sessions	Web Filter
Highest Severity Attack with Highest Session Count	Highest severity attack with the highest session count	Threat-Attacks-By-Severity	Attack
P2P Application with Highest Bandwidth	P2P applications with the highest bandwidth usage	Top-P2P-App-By-Bandwidth	Traffic
P2P Application with Highest Session Count	P2P applications with the highest session count	Top-P2P-App-By-Sessions	Traffic
Source with Highest Bandwidth	Source with the highest bandwidth usage	Top-Users-By-Bandwidth	Traffic
Source with Highest Session Count	Source with the highest session count	Top-User-Source-By-Sessions	Traffic
Total Number of Attacks	Total number of attacks detected	Total-Attack-Source	Attack
Total Number of Botnet Events	Total number of botnet events	Total-Number-of-Botnet-Events	Traffic
Total Number of Viruses	Total number of viruses detected	Total-Number-of-Viruses	Traffic
User Details	User details of traffic	Traffic-User-Detail	Traffic
Virus with Highest Session Count	Virus with the highest session count	Utm-Top-Virus	Traffic

Macro Name	Description	Dataset Used	Log Category
Web Category with Highest Bandwidth	Web filtering category with the highest bandwidth usage	Top-Web-Category-by-Bandwidth	Web Filter
Web Category with Highest Session Count	Web filtering category with the highest session count	Top-Web-Category-by-Sessions	Web Filter
Website with Highest Bandwidth	Website with the highest bandwidth usage	Top-Web-Sites-by-Bandwidth	Web Filter
Website with Highest Session Count	Website with the highest session count	Top-Web-Sites-by-Sessions	Web Filter

Change Log

Date	Change Description
2022-05-03	Initial release.



www.fortinet.com

Copyright© 2022 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.