




FortiAnalyzer - Dataset Reference

VERSION 5.4.4



FORTINET DOCUMENT LIBRARY

<http://docs.fortinet.com>

FORTINET VIDEO GUIDE

<http://video.fortinet.com>

FORTINET BLOG

<https://blog.fortinet.com>

CUSTOMER SERVICE & SUPPORT

<https://support.fortinet.com>

FORTIGATE COOKBOOK

<http://cookbook.fortinet.com>

FORTINET TRAINING SERVICES

<http://www.fortinet.com/training>

FORTIGUARD CENTER

<http://www.fortiguard.com>

END USER LICENSE AGREEMENT

<http://www.fortinet.com/doc/legal/EULA.pdf>

FEEDBACK

Email: techdocs@fortinet.com



October 5, 2017

FortiAnalyzer 5.4.4 Dataset Reference

05-544-310522-20171005

TABLE OF CONTENTS

Change Log	4
Introduction	5
Understanding datasets and macros	5
Dataset Reference List	6
Macro Reference List	174

Change Log

Date	Change Description
2017-10-05	Initial release

Introduction

This document provides information about the various types of FortiAnalyzer datasets.

Understanding datasets and macros

FortiAnalyzer datasets are collections of log messages from monitored devices.

Charts in FortiAnalyzer are generated based on the datasets. To create a chart, you can use the predefined datasets, or you can create your own custom datasets by querying the log messages in the SQL database on the FortiAnalyzer unit. Both predefined and custom datasets can be cloned, but only custom datasets can be deleted. You can also view the SQL query for a dataset, and test the query against specific devices or log arrays.

You can create custom reports that contain macros that are created based on predefined and custom datasets. Macros are used to dynamically display the device log data as text in a report. They can be embedded within a text field of a paragraph in a report layout in XML format. Macros display a single value, such as a user name, highest session count, or highest bandwidth, and so on.

For more information about how to create datasets, charts, and macros, see the FortiAnalyzer *Administration Guide*.

Dataset Reference List

The following tables list the available predefined data sets reported by FortiAnalyzer. For documentation and technical support reference purposes, these tables contain the dataset names, SQL query syntax for each dataset, and the log category of the dataset.

Dataset Name	Description	Log Category
Traffic-Bandwidth-Summary-Day-Of-Month	Traffic bandwidth timeline	traffic

```
select
  $flex_timescale(timestamp) as hosex,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in
from
  ###(select $flex_timestamp as timestamp, sum(coalesce(sentbyte, 0)) as traffic_out, sum
    (coalesce(rcvbyte, 0)) as traffic_in from $log where $filter and logid_to_int
    (logid) not in (4, 7, 14) group by timestamp having sum(coalesce(sentbyte,
    0)+coalesce(rcvbyte, 0))>0 order by timestamp desc)### t group by hosex order by
    hosex
```

Dataset Name	Description	Log Category
Session-Summary-Day-Of-Month	Number of session timeline	traffic

```
select
  $flex_timescale(timestamp) as hosex,
  sum(sessions) as sessions
from
  ###(select $flex_timestamp as timestamp, count(*) as sessions from $log where $filter
    and logid_to_int(logid) not in (4, 7, 14) group by timestamp order by timestamp
    desc)### t group by hosex order by hosex
```

Dataset Name	Description	Log Category
Top-Users-By-Bandwidth	Bandwidth application top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvbyte, 0)
```

```

    ) as traffic_in,
    sum(
      coalesce(sentbyte, 0)
    ) as traffic_out,
    count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  user_src
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-App-By-Bandwidth	Top applications by bandwidth usage	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-User-Source-By-Sessions	Top user source by session count	traffic

```

select

```

```

    coalesce(
      nullifna(`user`),
      nullifna(`unauthuser`),
      ipstr(`srcip`)
    ) as user_src,
    count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  user_src
order by
  sessions desc

```

Dataset Name	Description	Log Category
Top-App-By-Sessions	Top applications by session count	traffic

```

select
  app_group_name(app) as app_group,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
group by
  app_group
order by
  sessions desc

```

Dataset Name	Description	Log Category
Top-Destination-Addresses-By-Sessions	Top destinations by session count	traffic

```

select
  coalesce(
    nullifna(
      root_domain(hostname)
    ),
    ipstr(dstip)
  ) as domain,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  domain
order by

```

sessions desc

Dataset Name	Description	Log Category
Top-Destination-Addresses-By-Bandwidth	Top destinations by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(
      root_domain(hostname)
    ),
    ipstr(dstip)
  ) as domain,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and coalesce(
    nullifna(
      root_domain(hostname)
    ),
    ipstr(`dstip`)
  ) is not null
group by
  domain
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
DHCP-Summary-By-Port	Event top dhcp summary	event

```

drop
  table if exists pre_clt_list;
drop
  table if exists cur_clt_list;
drop
  table if exists allocated_ip; create temporary table pre_clt_list as ###(select concat
    (interface, '.', devid) as intf, mac from $log where $last3day_period $filter and
    logid_to_int(logid) = 26001 and dhcp_msg = 'Ack' group by interface, devid,

```

```

mac)###; create temporary table cur_clt_list as ###(select concat(interface, '.',
devid) as intf, mac from $log where $filter and logid_to_int(logid) = 26001 and
dhcp_msg = 'Ack' group by interface, devid, mac)###; create temporary table
allocated_ip as select distinct on (1) intf, cast(used*100.0/total as decimal
(18,2)) as percent_of_allocated_ip from ###(select distinct on (1) concat
(interface, '.', devid) as intf, used, total, itime from $log where $filter and
logid_to_int(logid)=26003 and total>0 order by intf, itime desc)### t order by
intf, itime desc; select t1.intf as interface, percent_of_allocated_ip, new_cli_
count from allocated_ip t1 inner join (select intf, count(mac) as new_cli_count
from cur_clt_list where not exists (select 1 from pre_clt_list where cur_clt_
list.mac=pre_clt_list.mac) group by intf) t2 on t1.intf=t2.intf order by interface,
percent_of_allocated_ip desc

```

Dataset Name	Description	Log Category
Top-Wifi-Client-By-Bandwidth	Traffic top WiFi client by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  srcssid,
  devtype,
  coalesce(
    nullifna(`srcname`),
    `srcmac`
  ) as hostname_mac,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and (
    srcssid is not null
    or dstssid is not null
  )
group by
  user_src,
  srcssid,
  devtype,
  hostname_mac
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Traffic-History-By-Active-User	Traffic history by active user	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  count(
    distinct(user_src)
  ) as total_user
from
  ###(select $flex_timestamp as timestamp, coalesce(nullifna(`user`), nullifna
    (`unauthuser`), ipstr(`srcip`)) as user_src from $log where $filter and logid_to_
    int(logid) not in (4, 7, 14) group by timestamp, user_src order by timestamp
    desc)### t group by hodex order by hodex
```

Dataset Name	Description	Log Category
Top-Allowed-Websites-By-Requests	UTM top allowed web sites by request	traffic

```
select
  hostname,
  catdesc,
  count(*) as requests
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and utmevent in (
    'webfilter', 'banned-word', 'web-content',
    'command-block', 'script-filter'
  )
  and hostname is not null
  and (
    utmaction not in ('block', 'blocked')
    or action != 'deny'
  )
group by
  hostname,
  catdesc
order by
  requests desc
```

Dataset Name	Description	Log Category
Top-50-Websites-By-Bandwidth	Webfilter top allowed web sites by bandwidth usage	webfilter

```
select
  domain,
  string_agg(distinct catdesc, ', ') as agg_catdesc,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
```

```

from
  ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, catdesc, sum
    (coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte,
    0)) as traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log-traffic
    where $filter and logid_to_int(logid) not in (4, 7, 14) and utmaction!='blocked'
    and (countweb>0 or ((logver is null or logver<52) and (hostname is not null or
    utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-
    filter')))) group by domain, catdesc having sum(coalesce(sentbyte, 0)+coalesce
    (rcvbyte, 0))>0 order by bandwidth desc)### t group by domain, catdesc order by
    bandwidth desc
  
```

Dataset Name	Description	Log Category
Top-Blocked-Websites	UTM top blocked web sites by request	traffic

```

select
  hostname,
  count(*) as requests
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and utmevent in (
    'webfilter', 'banned-word', 'web-content',
    'command-block', 'script-filter'
  )
  and hostname is not null
  and (
    utmaction in ('block', 'blocked')
    or action = 'deny'
  )
group by
  hostname
order by
  requests desc
  
```

Dataset Name	Description	Log Category
Top-Web-Users-By-Request	UTM top web users by request	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  devtype,
  srcname,
  count(*) as requests
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  
```

```

    and utmevent in (
      'webfilter', 'banned-word', 'web-content',
      'command-block', 'script-filter'
    )
  group by
    user_src,
    devtype,
    srcname
  order by
    requests desc

```

Dataset Name	Description	Log Category
Top-Allowed-WebSites-By-Bandwidth	UTM top allowed websites by bandwidth usage	traffic

```

select
  appid,
  hostname,
  catdesc,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and utmevent in (
    'webfilter', 'banned-word', 'web-content',
    'command-block', 'script-filter'
  )
  and hostname is not null
group by
  appid,
  hostname,
  catdesc
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-Blocked-Web-Users	UTM top blocked web users	traffic

```

select

```

```

coalesce(
  nullifna(`user`),
  nullifna(`unauthuser`),
  ipstr(`srcip`)
) as user_src,
devtype,
srcname,
count(*) as requests
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and utmevent in (
  'webfilter', 'banned-word', 'web-content',
  'command-block', 'script-filter'
)
and (
  utmaction in ('block', 'blocked')
  or action = 'deny'
)
group by
  user_src,
  devtype,
  srcname
order by
  requests desc
    
```

Dataset Name	Description	Log Category
Top-20-Web-Users-By-Bandwidth	Webfilter top web users by bandwidth usage	webfilter

```

select
  user_src,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log-traffic where $filter and logid_to_int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is null or logver<52) and (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by user_src having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc)### t group by user_src order by bandwidth desc
    
```

Dataset Name	Description	Log Category
Top-Web-Users-By-Bandwidth	UTM top web users by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    
```

```

        ipstr(`srcip`)
    ) as user_src,
    devtype,
    srcname,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out
from
    $log
where
    $filter
    and logid_to_int(logid) not in (4, 7, 14)
    and utmevent in (
        'webfilter', 'banned-word', 'web-content',
        'command-block', 'script-filter'
    )
group by
    user_src,
    devtype,
    srcname
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
Top-Video-Streaming-Websites-By-Bandwidth	UTM top video streaming websites by bandwidth usage	traffic

```

select
    appid,
    hostname,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out
from
    $log
where
    $filter
    and logid_to_int(logid) not in (4, 7, 14)
    and catdesc in ('Streaming Media and Download')

```

```

group by
  appid,
  hostname
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-Email-Senders-By-Count	Default top email senders by count	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as requests
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and service in (
    'smtp', 'SMTP', '25/tcp', '587/tcp',
    'smtps', 'SMTPS', '465/tcp'
  )
group by
  user_src
order by
  requests desc

```

Dataset Name	Description	Log Category
Top-Email-Receivers-By-Count	Default email top receivers by count	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as requests
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and service in (
    'pop3', 'POP3', '110/tcp', 'imap',
    'IMAP', '143/tcp', 'imaps', 'IMAPS',
    '993/tcp', 'pop3s', 'POP3S', '995/tcp'
  )

```

```

)
group by
  user_src
order by
  requests desc

```

Dataset Name	Description	Log Category
Top-Email-Senders-By-Bandwidth	Default email top senders by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and service in (
    'smtp', 'SMTP', '25/tcp', '587/tcp',
    'smtps', 'SMTPS', '465/tcp'
  )
group by
  user_src
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-Email-Receivers-By-Bandwidth	Default email top receivers by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)

```

```

and service in (
  'pop3', 'POP3', '110/tcp', 'imap',
  'IMAP', '143/tcp', 'imaps', 'IMAPS',
  '993/tcp', 'pop3s', 'POP3S', '995/tcp'
)
group by
  user_src
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
    
```

Dataset Name	Description	Log Category
Top-Malware-By-Name	UTM top virus	virus

```

select
  virus,
  max(virusid) as virusid,
  (
    case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then
      'Adware' else 'Virus' end
  ) as malware_type,
  sum(totalnum) as totalnum
from
  (
    ###(select virus, 0 as virusid, count(*) as totalnum from $log-traffic where $filter
      and logid_to_int(logid) not in (4, 7, 14) and utmevent is not null and virus is
      not null group by virus, virusid order by totalnum desc)### union all ###(select
      virus, virusid, count(*) as totalnum from $log-virus where $filter and
      (eventtype is null or logver>=52) and nullifna(virus) is not null group by
      virus, virusid order by totalnum desc)###) t group by virus, malware_type order
      by totalnum desc
    
```

Dataset Name	Description	Log Category
Top-Virus-By-Name	UTM top virus	virus

```

select
  virus,
  max(virusid) as virusid,
  (
    case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then
      'Adware' else 'Virus' end
  ) as malware_type,
  sum(totalnum) as totalnum
from
  (
    ###(select virus, 0 as virusid, count(*) as totalnum from $log-traffic where $filter
      and logid_to_int(logid) not in (4, 7, 14) and utmevent is not null and virus is
      not null group by virus, virusid order by totalnum desc)### union all ###(select
      virus, virusid, count(*) as totalnum from $log-virus where $filter and
      (eventtype is null or logver>=52) and nullifna(virus) is not null group by
    
```

```
virus, virusid order by totalnum desc)###) t group by virus, malware_type order
by totalnum desc
```

Dataset Name	Description	Log Category
Top-Virus-Victim	UTM top virus user	traffic

```
select
  user_src,
  sum(totalnum) as totalnum
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
      user_src, count(*) as totalnum from $log-traffic where $filter and logid_to_int
      (logid) not in (4, 7, 14) and utmevent is not null and virus is not null group
      by user_src order by totalnum desc)### union all ###(select coalesce(nullifna
      (`user`), ipstr(`srcip`)) as user_src, count(*) as totalnum from $log-virus
      where $filter and (eventtype is null or logver>=52) and nullifna(virus) is not
      null group by user_src order by totalnum desc)###) t group by user_src order by
      totalnum desc
```

Dataset Name	Description	Log Category
Top-Attack-Source	UTM top attack source	attack

```
select
  coalesce(
    nullifna(`user`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as totalnum
from
  $log
where
  $filter
group by
  user_src
order by
  totalnum desc
```

Dataset Name	Description	Log Category
Top-Attack-Victim	UTM top attack dest	attack

```
select
  dstip,
  count(*) as totalnum
from
  $log
where
  $filter
  and dstip is not null
group by
  dstip
```

```
order by
totalnum desc
```

Dataset Name	Description	Log Category
Top-Static-IPSEC-Tunnels-By-Bandwidth	Top static IPsec tunnels by bandwidth usage	event

```
select
  vpn_name,
  sum(traffic_in + traffic_out) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      tunnelid,
      vpn_name,
      max(traffic_in) as traffic_in,
      max(traffic_out) as traffic_out
    from
      ###(select devid, vd, remip, vpn_trim(vpntunnel) as vpn_name, tunnelid, max
        (coalesce(sentbyte, 0)) as traffic_out, max(coalesce(rcvdbyte, 0)) as
        traffic_in from $log where $filter and subtype='vpn' and tunneltype like
        'ipsec%' and (tunnelip is null or tunnelip='0.0.0.0') and action in ('tunnel-
        stats', 'tunnel-down') and tunnelid is not null group by devid, vd, remip,
        vpn_name, tunnelid)### t group by devid, vd, remip, vpn_name, tunnelid) tt
        group by vpn_name having sum(traffic_in+traffic_out)>0 order by bandwidth
        desc
```

Dataset Name	Description	Log Category
Top-SSL-VPN-Tunnel-Users-By-Bandwidth	Top SSL VPN tunnel users by bandwidth usage	event

```
select
  user_src,
  remip as remote_ip,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      user_src,
      tunnelid,
```

```

min(s_time) as s_time,
max(e_time) as e_time,
(
  case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
) as bandwidth,
(
  case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)- min(min_traffic_in) end
) as traffic_in,
(
  case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_out)- min(min_traffic_out) end
) as traffic_out
from
###(select devid, vd, remip, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src, tunnelid, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, min(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvbyte, 0)) as min_traffic_in, max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvbyte, 0)) as max_traffic_in from $log where $filter and subtype='vpn' and tunneltype='ssl-tunnel' and action in ('tunnel-stats', 'tunnel-down', 'tunnel-up') and coalesce(nullifna(`user`), ipstr(`remip`)) is not null and tunnelid is not null group by devid, vd, user_src, remip, tunnelid)### t group by devid, vd, user_src, remip, tunnelid) tt group by user_src, remote_ip having sum(bandwidth)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Tunnels-By-Bandwidth	Top dial up IPsec tunnels by bandwidth usage	event

```

select
  vpn_name,
  sum(traffic_out + traffic_in) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
(
  select
    devid,
    vd,
    tunnelid,
    remip,
    vpn_name,
    max(traffic_in) as traffic_in,
    max(traffic_out) as traffic_out
  from
    ###(select devid, vd, remip, vpn_trim(vpntunnel) as vpn_name, tunnelid, max(coalesce(sentbyte, 0)) as traffic_out, max(coalesce(rcvbyte, 0)) as traffic_in from $log where $filter and nullifna(vpntunnel) is not null and subtype='vpn' and tunneltype like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0') and action in ('tunnel-stats', 'tunnel-down') and tunnelid is not null group by devid, vd, remip, vpn_name, tunnelid)### t group by devid, vd, remip, vpn_name, tunnelid) tt group by vpn_name having sum(traffic_out+traffic_in)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Users-By-Band-width	Top dial up IPsec users by bandwidth usage	event

```

select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as user_src,
  remip,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
      string_agg(distinct user_agg, ' ') as user_agg,
      remip,
      tunnelid,
      min(s_time) as s_time,
      max(e_time) as e_time,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
      ) as bandwidth,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)- min(min_traffic_in) end
      ) as traffic_in,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_out)- min(min_traffic_out) end
      ) as traffic_out
    from
      ###(select devid, vd, nullifna(`xauthuser`) as xauthuser_agg, nullifna(`user`) as user_agg, remip, tunnelid, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, min(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in from $log where $filter and subtype='vpn' and tunneltype like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0') and action in ('tunnel-stats', 'tunnel-down', 'tunnel-up') and tunnelid is not null group by devid, vd, xauthuser_agg, user_agg, remip, tunnelid)### t group by devid, vd, remip, tunnelid) tt group by user_src, remip having sum(bandwidth)>0 order by bandwidth desc
  )

```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Users-By-Duration	Top dial up IPsec users by duration	event

```

select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as user_src,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(duration) as duration,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
      string_agg(distinct user_agg, ' ') as user_agg,
      tunnelid,
      min(s_time) as s_time,
      max(e_time) as e_time,
      (
        case when min(s_time)= max(e_time) then max(max_duration) else max(max_
          duration)- min(min_duration) end
      ) as duration,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_
          out) else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)-
          min(min_traffic_out) end
      ) as bandwidth,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_
          traffic_in)- min(min_traffic_in) end
      ) as traffic_in,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_
          traffic_out)- min(min_traffic_out) end
      ) as traffic_out
    from
      ###(select devid, vd, remip, nullifna(`xauthuser`) as xauthuser_agg, nullifna
        (`user`) as user_agg, tunnelid, min(coalesce(dtime, 0)) as s_time, max
        (coalesce(dtime, 0)) as e_time, max(coalesce(duration,0)) as max_duration,
        min(coalesce(duration,0)) as min_duration, min(coalesce(sentbyte, 0)) as min_
        traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, max(coalesce
        (sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_
        in from $log where $filter and subtype='vpn' and tunneltype like 'ipsec%' and
        not (tunnelip is null or tunnelip='0.0.0.0') and action in ('tunnel-stats',
        'tunnel-down', 'tunnel-up') and tunnelid is not null group by devid, vd,

```

```
remip, xauthuser_agg, user_agg, tunnelid order by tunnelid)### t group by
devid, vd, remip, tunnelid) tt group by user_src having sum(bandwidth)>0
order by duration desc
```

Dataset Name	Description	Log Category
Top-SSL-VPN-Web-Mode-Users-By-Bandwidth	Top SSL VPN web mode users by bandwidth usage	event

```
select
  user_src,
  remip as remote_ip,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      user_src,
      remip,
      tunnelid,
      min(s_time) as s_time,
      max(e_time) as e_time,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
      ) as bandwidth,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)- min(min_traffic_in) end
      ) as traffic_in,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_out)- min(min_traffic_out) end
      ) as traffic_out
    from
      ###(select devid, vd, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src,
      remip, tunnelid, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0))
      as e_time, min(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in from $log where $filter and
      subtype='vpn' and tunneltype='ssl-web' and action in ('tunnel-stats', 'tunnel-down', 'tunnel-up') and coalesce(nullifna(`user`), ipstr(`remip`)) is
      not null and tunnelid is not null group by devid, vd, user_src, remip, tunnelid)### t group by devid, vd, user_src, remip, tunnelid) tt group by
      user_src, remote_ip having sum(bandwidth)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-SSL-VPN-Users-By-Duration	Top SSL VPN users by duration	event

```

select
  user_src,
  tunneltype,
  sum(duration) as duration,
  sum(traffic_out + traffic_in) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      user_src,
      tunneltype,
      tunnelid,
      max(duration) as duration,
      max(traffic_in) as traffic_in,
      max(traffic_out) as traffic_out
    from
      ###(select devid, vd, remip, coalesce(nullifna(`user`), ipstr(`remip`)) as user_
      src, tunnelid, tunneltype, max(coalesce(duration, 0)) as duration, max
      (coalesce(sentbyte, 0)) as traffic_out, max(coalesce(rcvbyte, 0)) as
      traffic_in from $log where $filter and subtype='vpn' and tunneltype like
      'ssl%' and action in ('tunnel-stats', 'tunnel-down') and coalesce(nullifna
      (`user`), ipstr(`remip`)) is not null and tunnelid is not null and
      tunnelid!=0 group by devid, vd, remip, user_src, tunnelid, tunneltype)### t
      group by devid, vd, remip, user_src, tunnelid, tunneltype) tt group by user_
      src, tunneltype having sum(traffic_out+traffic_in)>0 order by duration desc
  )

```

Dataset Name	Description	Log Category
vpn-Top-Dial-Up-VPN-Users-By-Duration	Top dial up VPN users by duration	event

```

select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as user_src,
  t_type as tunneltype,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(duration) as duration,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,

```

```

string_agg(distinct user_agg, ' ') as user_agg,
t_type,
tunnelid,
min(s_time) as s_time,
max(e_time) as e_time,
(
  case when min(s_time)= max(e_time) then max(max_duration) else max(max_
    duration)- min(min_duration) end
) as duration,
(
  case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_
    out) else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)-
    min(min_traffic_out) end
) as bandwidth,
(
  case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_
    traffic_in)- min(min_traffic_in) end
) as traffic_in,
(
  case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_
    traffic_out)- min(min_traffic_out) end
) as traffic_out
from
###(select devid, vd, remip, nullifna(`xauthuser`) as xauthuser_agg, nullifna
  (`user`) as user_agg, (case when tunneltype like 'ipsec%' then 'ipsec' else
    tunneltype end) as t_type, tunnelid, min(coalesce(dtime, 0)) as s_time, max
    (coalesce(dtime, 0)) as e_time, max(coalesce(duration,0)) as max_duration,
    min(coalesce(duration,0)) as min_duration, min(coalesce(sentbyte, 0)) as min_
    traffic_out, min(coalesce(rcvbyte, 0)) as min_traffic_in, max(coalesce
    (sentbyte, 0)) as max_traffic_out, max(coalesce(rcvbyte, 0)) as max_traffic_
    in from $log where $filter and subtype='vpn' and (tunneltype like 'ssl%' or
    (tunneltype like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0')))
    and action in ('tunnel-stats', 'tunnel-down', 'tunnel-up') and tunnelid is
    not null and tunnelid!=0 group by devid, vd, remip, xauthuser_agg, user_agg,
    t_type, tunnelid)### t group by devid, vd, remip, t_type, tunnelid) tt group
    by user_src, tunneltype having sum(bandwidth)>0 order by duration desc

```

Dataset Name	Description	Log Category
vpn-User-Login-history	VPN user login history	event

```

select
  $flex_timescale(timestamp) as hodex,
  sum(total_num) as total_num
from
  (
    select
      timestamp,
      devid,
      vd,
      remip,
      tunnelid,
      sum(tunnelup) as total_num,
      max(traffic_in) as traffic_in,
      max(traffic_out) as traffic_out
    from

```

```

###(select $flex_timestamp as timestamp, devid, vd, remip, tunnelid, (case when
  action='tunnel-up' then 1 else 0 end) as tunnelup, max(coalesce(sentbyte, 0))
  as traffic_out, max(coalesce(rcvbyte, 0)) as traffic_in from $log where
  $filter and subtype='vpn' and (tunneltype like 'ipsec%' or tunneltype like
  'ssl%') and action in ('tunnel-up', 'tunnel-stats', 'tunnel-down') and
  tunnelid is not null group by timestamp, action, devid, vd, remip, tunnelid
  order by timestamp desc)### t group by timestamp, devid, vd, remip, tunnelid
  having max(tunnelup) > 0 and max(traffic_in)+max(traffic_out)>0) t group by
  hodex order by total_num desc

```

Dataset Name	Description	Log Category
vpn-Failed-Login-Attempts	VPN failed logins	event

```

select
  f_user,
  tunneltype,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`xauthuser`), `user`) as f_user, tunneltype, count(*) as
  total_num from $log where $filter and subtype='vpn' and (tunneltype='ipsec' or left
  (tunneltype, 3)='ssl') and action in ('ssl-login-fail', 'ipsec-login-fail') and
  coalesce(nullifna(`xauthuser`), nullifna(`user`)) is not null group by f_user,
  tunneltype)### t group by f_user, tunneltype order by total_num desc

```

Dataset Name	Description	Log Category
vpn-Authenticated-Logins	VPN authenticated logins	event

```

select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as f_user,
  t_type as tunneltype,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(total_num) as total_num,
  sum(duration) as duration
from
  (
    select
      string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
      string_agg(distinct user_agg, ' ') as user_agg,
      t_type,
      devid,
      vd,
      remip,
      tunnelid,
      min(s_time) as s_time,
      max(e_time) as e_time,
      (

```

```

        case when min(s_time)= max(e_time) then max(max_duration) else max(max_
            duration)- min(min_duration) end
    ) as duration,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_
            out) else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)-
            min(min_traffic_out) end
    ) as bandwidth,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_
            traffic_in)- min(min_traffic_in) end
    ) as traffic_in,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_
            traffic_out)- min(min_traffic_out) end
    ) as traffic_out,
    sum(tunnelup) as total_num
from
###(select nullifna(`xauthuser`) as xauthuser_agg, nullifna(`user`) as user_agg,
    devid, vd, remip, (case when tunneltype like 'ipsec%' then 'ipsec' else
        tunneltype end) as t_type, tunnelid, sum((case when action='tunnel-up' then 1
            else 0 end)) as tunnelup, min(coalesce(dtime, 0)) as s_time, max(coalesce
            (dtime, 0)) as e_time, max(coalesce(duration,0)) as max_duration, min
            (coalesce(duration,0)) as min_duration, min(coalesce(sentbyte, 0)) as min_
            traffic_out, min(coalesce(rcvbyte, 0)) as min_traffic_in, max(coalesce
            (sentbyte, 0)) as max_traffic_out, max(coalesce(rcvbyte, 0)) as max_traffic_
            in from $log where $filter and subtype='vpn' and (tunneltype like 'ipsec%' or
            tunneltype like 'ssl%') and action in ('tunnel-up', 'tunnel-stats', 'tunnel-
            down') and tunnelid is not null group by xauthuser_agg, user_agg, devid, vd,
            remip, t_type, tunnelid)### t group by t_type, devid, vd, remip, tunnelid
            having max(tunnelup) > 0) tt group by f_user, tunneltype having sum
            (bandwidth) > 0 order by total_num desc

```

Dataset Name	Description	Log Category
vpn-Traffic-Usage-Trend-VPN-Summary	VPN traffic usage trend	event

```

select
    hodex,
    sum(ssl_traffic_out + ssl_traffic_in) as ssl_bandwidth,
    sum(
        ipsec_traffic_out + ipsec_traffic_in
    ) as ipsec_bandwidth
from
    (
        select
            $flex_timescale(timestamp) as hodex,
            devid,
            vd,
            remip,
            tunnelid,
            (
                case when t_type like 'ssl%' then max(traffic_in) else 0 end
            ) as ssl_traffic_in,
            (
                case when t_type like 'ssl%' then max(traffic_out) else 0 end
            ) as ipsec_traffic_out
        from
            tunnelstats
        where
            tunneltype in ('ipsec', 'ssl')
    )

```

```

) as ssl_traffic_out,
(
  case when t_type like 'ipsec%' then max(traffic_in) else 0 end
) as ipsec_traffic_in,
(
  case when t_type like 'ipsec%' then max(traffic_out) else 0 end
) as ipsec_traffic_out
from
###(select $flex_timestamp as timestamp, devid, vd, remip, tunnelid, (case when
  tunneltype like 'ipsec%' then 'ipsec' else tunneltype end) as t_type, max
  (coalesce(sentbyte, 0)) as traffic_out, max(coalesce(rcvbyte, 0)) as
  traffic_in from $log where $filter and subtype='vpn' and (tunneltype like
  'ipsec%' or tunneltype like 'ssl%') and action in ('tunnel-stats', 'tunnel-
  down') and tunnelid is not null group by timestamp, devid, vd, remip, t_type,
  tunnelid order by timestamp desc)### t group by hodex, devid, t_type, vd,
  remip, tunnelid) tt group by hodex order by hodex

```

Dataset Name	Description	Log Category
Top-S2S-IPSEC-Tunnels-By-Bandwidth-and-Availability	Top S2S IPsec tunnels by bandwidth usage and avail	event

```

select
  vpntunnel,
  tunneltype,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in,
  sum(bandwidth) as bandwidth,
  sum(uptime) as uptime
from
(
  select
    vpntunnel,
    tunneltype,
    tunnelid,
    devid,
    vd,
    sum(sent_end - sent_beg) as traffic_out,
    sum(rcvd_end - rcvd_beg) as traffic_in,
    sum(
      sent_end - sent_beg + rcvd_end - rcvd_beg
    ) as bandwidth,
    sum(duration_end - duration_beg) as uptime
  from
    ###(select tunnelid, tunneltype, vpntunnel, devid, vd, min(coalesce(sentbyte, 0))
    as sent_beg, max(coalesce(sentbyte, 0)) as sent_end, min(coalesce(rcvbyte,
    0)) as rcvd_beg, max(coalesce(rcvbyte, 0)) as rcvd_end, min(coalesce
    (duration, 0)) as duration_beg, max(coalesce(duration, 0)) as duration_end
    from $log where $filter and subtype='vpn' and action='tunnel-stats' and
    tunneltype like 'ipsec%' and (tunnelip is null or tunnelip='0.0.0.0') and
    nullifna(`user`) is null and tunnelid is not null group by tunnelid,
    tunneltype, vpntunnel, devid, vd order by tunnelid)### t group by vpntunnel,
    tunneltype, tunnelid, devid, vd order by bandwidth desc) t group by
    vpntunnel, tunneltype order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Dialup-IPSEC-By-Bandwidth-and-Availability	Top dialup IPsec users by bandwidth usage and avail	event

```

select
  user_src,
  remip,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in,
  sum(bandwidth) as bandwidth,
  sum(uptime) as uptime
from
  (
    select
      user_src,
      remip,
      tunnelid,
      devid,
      vd,
      sum(sent_end - sent_beg) as traffic_out,
      sum(rcvd_end - rcvd_beg) as traffic_in,
      sum(
        sent_end - sent_beg + rcvd_end - rcvd_beg
      ) as bandwidth,
      sum(duration_end - duration_beg) as uptime
    from
      ###(select tunnelid, coalesce(nullifna(`xauthuser`), nullifna(`user`), ipstr
        (`remip`)) as user_src, remip, devid, vd, min(coalesce(sentbyte, 0)) as sent_
        beg, max(coalesce(sentbyte, 0)) as sent_end, min(coalesce(rcvdbyte, 0)) as
        rcvd_beg, max(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce(duration, 0))
        as duration_beg, max(coalesce(duration, 0)) as duration_end from $log where
        $filter and subtype='vpn' and action='tunnel-stats' and tunneltype like
        'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0') and tunnelid is not
        null group by tunnelid, user_src, remip, devid, vd order by tunnelid)### t
        group by user_src, remip, tunnelid, devid, vd order by bandwidth desc) t
        group by user_src, remip order by bandwidth desc
  )

```

Dataset Name	Description	Log Category
Top-SSL-Tunnel-Mode-By-Bandwidth-and-Availability	Top SSL tunnel users by bandwidth usage and avail	event

```

select
  user_src,
  remote_ip,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in,
  sum(bandwidth) as bandwidth,
  sum(uptime) as uptime
from
  (
    select
      user_src,

```

```

remip as remote_ip,
tunnelid,
devid,
vd,
sum(sent_end - sent_beg) as traffic_out,
sum(rcvd_end - rcvd_beg) as traffic_in,
sum(
    sent_end - sent_beg + rcvd_end - rcvd_beg
) as bandwidth,
sum(duration_end - duration_beg) as uptime
from
###(select tunnelid, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src,
remip, devid, vd, min(coalesce(sentbyte, 0)) as sent_beg, max(coalesce
(sentbyte, 0)) as sent_end, min(coalesce(rcvdbyte, 0)) as rcvd_beg, max
(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce(duration, 0)) as duration_
beg, max(coalesce(duration, 0)) as duration_end from $log where $filter and
subtype='vpn' and action='tunnel-stats' and tunneltype in ('ssl-tunnel',
'ssl') and coalesce(nullifna(`user`), ipstr(`remip`)) is not null and
tunnelid is not null group by tunnelid, user_src, remip, devid, vd order by
tunnelid)### t group by user_src, remote_ip, tunnelid, devid, vd order by
bandwidth desc) t group by user_src, remote_ip order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-SSL-Web-Mode-By-Bandwidth-and-Availability	Top SSL web users by bandwidth usage and avail	event

```

select
    user_src,
    remote_ip,
    sum(traffic_out) as traffic_out,
    sum(traffic_in) as traffic_in,
    sum(bandwidth) as bandwidth,
    sum(uptime) as uptime
from
(
    select
        user_src,
        remip as remote_ip,
        tunnelid,
        devid,
        vd,
        sum(sent_end - sent_beg) as traffic_out,
        sum(rcvd_end - rcvd_beg) as traffic_in,
        sum(
            sent_end - sent_beg + rcvd_end - rcvd_beg
        ) as bandwidth,
        sum(duration_end - duration_beg) as uptime
    from
        ###(select tunnelid, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src,
remip, devid, vd, min(coalesce(sentbyte, 0)) as sent_beg, max(coalesce
(sentbyte, 0)) as sent_end, min(coalesce(rcvdbyte, 0)) as rcvd_beg, max
(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce(duration, 0)) as duration_
beg, max(coalesce(duration, 0)) as duration_end from $log where $filter and
subtype='vpn' and action='tunnel-stats' and tunneltype='ssl-web' and coalesce
(nullifna(`user`), ipstr(`remip`)) is not null and tunnelid is not null group
by tunnelid, user_src, remip, devid, vd order by tunnelid)### t group by

```

```
user_src, remote_ip, tunnelid, devid, vd having sum(sent_end-sent_beg+rcvd_end-rcvd_beg)>0 order by bandwidth desc) t group by user_src, remote_ip order by bandwidth desc
```

Dataset Name	Description	Log Category
Admin-Login-Summary	Event admin login summary	event

```
select
  f_user,
  ui,
  sum(login) as total_num,
  sum(login_duration) as total_duration,
  sum(config_change) as total_change
from
  (
    select
      `user` as f_user,
      ui,
      (
        case when logid_to_int(logid)= 32001 then 1 else 0 end
      ) as login,
      (
        case when logid_to_int(logid)= 32003 then duration else 0 end
      ) as login_duration,
      (
        case when logid_to_int(logid)= 32003
          and state is not null then 1 else 0 end
      ) as config_change
    from
      $log
    where
      $filter
      and nullifna(`user`) is not null
      and logid_to_int(logid) in (32001, 32003)
  ) t
group by
  f_user,
  ui
having
  sum(login)+ sum(config_change)> 0
order by
  total_num desc
```

Dataset Name	Description	Log Category
Admin-Login-Summary-By-Date	Event admin login summary by date	event

```
select
  $flex_timescale(timestamp) as dom,
  sum(total_num) as total_num,
  sum(total_change) as total_change
from
  ###(select timestamp, sum(login) as total_num, sum(config_change) as total_change from
  (select $flex_timestamp as timestamp, (case when logid_to_int(logid)=32001 then 1
```

```

else 0 end) as login, (case when logid_to_int(logid)=32003 and state is not null
then 1 else 0 end) as config_change from $log where $filter and logid_to_int(logid)
in (32001, 32003)) t group by timestamp having sum(login)+sum(config_change)>0
order by timestamp desc)### t group by dom order by dom

```

Dataset Name	Description	Log Category
Admin-Failed-Login-Summary	Event admin failed login summary	event

```

select
  `user` as f_user,
  ui,
  count(status) as total_failed
from
  $log
where
  $filter
  and nullifna(`user`) is not null
  and logid_to_int(logid) = 32002
group by
  ui,
  f_user
order by
  total_failed desc

```

Dataset Name	Description	Log Category
System-Summary-By-Severity	Event system summary by severity	event

```

select
  (
    case when level in ('critical', 'alert', 'emergency') then 'Critical' when level =
      'error' then 'High' when level = 'warning' then 'Medium' when level = 'notice'
      then 'Low' else 'Info' end
  ) as severity,
  count(*) as total_num
from
  $log
where
  $filter
  and subtype = 'system'
group by
  severity
order by
  total_num desc

```

Dataset Name	Description	Log Category
System-Summary-By-Date	Event system summary by date	event

```

select
  $flex_timescale(timestamp) as dom,
  sum(critical) as critical,
  sum(high) as high,

```

```

sum(medium) as medium
from
###(select $flex_timestamp as timestamp, sum(case when level in ('critical', 'alert',
'emergency') then 1 else 0 end) as critical, sum(case when level = 'error' then 1
else 0 end) as high, sum(case when level = 'warning' then 1 else 0 end) as medium
from $log where $filter and subtype='system' group by timestamp order by timestamp
desc)### t group by dom order by dom
    
```

Dataset Name	Description	Log Category
Important-System-Summary-By-Date	Event system summary by date	event

```

select
$flex_timescale(timestamp) as dom,
sum(critical) as critical,
sum(high) as high,
sum(medium) as medium
from
###(select $flex_timestamp as timestamp, sum(case when level in ('critical', 'alert',
'emergency') then 1 else 0 end) as critical, sum(case when level = 'error' then 1
else 0 end) as high, sum(case when level = 'warning' then 1 else 0 end) as medium
from $log where $filter and subtype='system' group by timestamp order by timestamp
desc)### t group by dom order by dom
    
```

Dataset Name	Description	Log Category
System-Critical-Severity-Events	Event system critical severity events	event

```

select
msg_desc as msg,
severity,
sum(count) as counts
from
###(select coalesce(nullifna(logdesc), msg) as msg_desc, (case when level in
('critical', 'alert', 'emergency') then 'Critical' when level='error' then 'High'
when level='warning' then 'Medium' when level='notice' then 'Low' else 'Info' end)
as severity, count(*) as count from $log where $filter and subtype='system' group
by msg_desc, severity order by count desc)### t where severity='Critical' group by
msg, severity order by counts desc
    
```

Dataset Name	Description	Log Category
System-High-Severity-Events	Event system high severity events	event

```

select
msg_desc as msg,
severity,
sum(count) as counts
from
###(select coalesce(nullifna(logdesc), msg) as msg_desc, (case when level in
('critical', 'alert', 'emergency') then 'Critical' when level='error' then 'High'
when level='warning' then 'Medium' when level='notice' then 'Low' else 'Info' end)
as severity, count(*) as count from $log where $filter and subtype='system' group
    
```

```
by msg_desc, severity order by count desc)### t where severity='High' group by msg,
severity order by counts desc
```

Dataset Name	Description	Log Category
System-Medium-Severity-Events	Event system medium severity events	event

```
select
  msg_desc as msg,
  severity,
  sum(count) as counts
from
  ###(select coalesce(nullifna(logdesc), msg) as msg_desc, (case when level in
    ('critical', 'alert', 'emergency') then 'Critical' when level='error' then 'High'
    when level='warning' then 'Medium' when level='notice' then 'Low' else 'Info' end)
  as severity, count(*) as count from $log where $filter and subtype='system' group
  by msg_desc, severity order by count desc)### t where severity='Medium' group by
  msg, severity order by counts desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Traffic-Summary	UTM drilldown traffic summary	traffic

```
select
  srcip,
  srcname
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
  src, srcip, srcname from $log where $filter and logid_to_int(logid) not in (4, 7,
  14) group by user_src, srcip, srcname)### t where $filter-drilldown group by srcip,
  srcname
```

Dataset Name	Description	Log Category
utm-drilldown-Top-User-Destination	UTM drilldown top user destination	traffic

```
select
  appid,
  app,
  dstip,
  sum(sessions) as sessions,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
  src, appid, app, dstip, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce
  (rcvbyte, 0)) as bandwidth from $log where $filter and logid_to_int(logid) not in
  (4, 7, 14) and dstip is not null and nullifna(app) is not null group by user_src,
  appid, app, dstip having sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0))>0 order
  by bandwidth desc)### t where $filter-drilldown group by appid, app, dstip order by
  bandwidth desc
```

Dataset Name	Description	Log Category
utm-drilldown-Email-Senders-Summary	UTM drilldown email senders summary	traffic

```
select
  sum(requests) as requests,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') group by user_src, sender order by requests desc)### t where $filter-drilldown
```

Dataset Name	Description	Log Category
utm-drilldown-Email-Receivers-Summary	UTM drilldown email receivers summary	traffic

```
select
  sum(requests) as requests,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and recipient is not null and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') group by user_src, recipient order by requests desc)### t where $filter-drilldown
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Email-Recipients-By-Bandwidth	UTM drilldown top email recipients	traffic

```
select
  recipient,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') group by user_src, recipient order by requests desc)### t where $filter-drilldown and recipient is not null group by recipient having sum(bandwidth)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Email-Senders-By-Bandwidth	UTM drilldown top email senders	traffic

```

select
  sender,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
  src, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))
  as bandwidth from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and
  service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') group
  by user_src, sender order by requests desc)### t where $filter-drilldown and sender
  is not null group by sender having sum(bandwidth)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
utm-drilldown-Top-Allowed-Web-sites-By-Bandwidth	UTM drilldown top allowed web sites by bandwidth	traffic

```

select
  appid,
  hostname,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
  src, appid, hostname, (case when utmaction='blocked' then 1 else 0 end) as blocked,
  sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic
  where $filter and logid_to_int(logid) not in (4, 7, 14) and (countweb>0 or ((logver
  is null or logver<52) and (hostname is not null or utmevent in ('webfilter',
  'banned-word', 'web-content', 'command-block', 'script-filter')))) and hostname is
  not null group by user_src, appid, hostname, blocked order by bandwidth desc)### t
  where $filter-drilldown and blocked=0 group by appid, hostname order by bandwidth
  desc

```

Dataset Name	Description	Log Category
utm-drilldown-Top-Blocked-Web-sites-By-Request	UTM drilldown top blocked web sites by request	traffic

```

select
  appid,
  hostname,
  sum(requests) as requests
from
  (
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, appid, hostname, (case when utmaction='blocked' then 1 else 0 end) as
  blocked, count(*) as requests from $log-traffic where $filter and logid_to_int
  (logid) not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word', 'web-
  content', 'command-block', 'script-filter') and hostname is not null group by
  user_src, appid, hostname, blocked order by requests desc)### union all ###
  (select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, 0 as appid,
  hostname, (case when action='blocked' then 1 else 0 end) as blocked, count(*) as
  requests from $log-webfilter where $filter and (eventtype is null or logver>=52)
  and hostname is not null group by user_src, appid, hostname, blocked order by
  requests desc)###) t where $filter-drilldown and blocked=1 group by appid,
  hostname order by requests desc

```

Dataset Name	Description	Log Category
utm-drilldown-Top-Virus-By-Name	UTM drilldown top virus	traffic

```
select
  virus,
  sum(totalnum) as totalnum
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
    user_src, virus, count(*) as totalnum from $log-traffic where $filter and logid_
    to_int(logid) not in (4, 7, 14) and utmevent is not null and virus is not null
    group by user_src, virus order by totalnum desc)### union all ###(select
    coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, count(*) as
    totalnum from $log-virus where $filter and (eventtype is null or logver>=52) and
    nullifna(virus) is not null group by user_src, virus order by totalnum desc)###
    t where $filter-drilldown group by virus order by totalnum desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Attacks	UTM drilldown top attacks by name	attack

```
select
  attack,
  sum(attack_count) as attack_count
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, attack, count(*) as
  attack_count from $log where $filter and nullifna(attack) is not null group by
  user_src, attack order by attack_count desc)### t where $filter-drilldown group by
  attack order by attack_count desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Vulnerability	UTM drilldown top vulnerability by name	netscan

```
select
  vuln,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, vuln, count(*) as
  totalnum from $log where $filter and action='vuln-detection' and vuln is not null
  group by user_src, vuln order by totalnum desc)### t where $filter-drilldown group
  by vuln order by totalnum desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-App-By-Bandwidth	UTM drilldown top applications by bandwidth usage	traffic

```
select
  appid,
  app,
```

```

sum(bandwidth) as bandwidth
from
###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
src, appid, app, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth,
count(*) as sessions from $log where $filter and logid_to_int(logid) not in (4, 7,
14) and nullifna(app) is not null group by user_src, appid, app order by sessions
desc)### t where $filter-drilldown group by appid, app having sum(bandwidth)>0
order by bandwidth desc

```

Dataset Name	Description	Log Category
utm-drilldown-Top-App-By-Sessions	UTM drilldown top applications by session count	traffic

```

select
  appid,
  app,
  sum(sessions) as sessions
from
###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
src, appid, app, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth,
count(*) as sessions from $log where $filter and logid_to_int(logid) not in (4, 7,
14) and nullifna(app) is not null group by user_src, appid, app order by sessions
desc)### t where $filter-drilldown group by appid, app order by sessions desc

```

Dataset Name	Description	Log Category
Top5-Users-By-Bandwidth	UTM drilldown top users by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as dldn_user,
  count(*) as session,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
group by
dldn_user
having
sum(
  coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
)> 0

```

```
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Top-App-By-Bandwidth-Sessions	Top applications by bandwidth usage	traffic

```
select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Category-By-Bandwidth	Application risk application usage by category	traffic

```
select
  appcat,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(appcat) is not null
group by
  appcat
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Top-Users-By-Bandwidth-Sessions	Bandwidth application top users by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  user_src
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
bandwidth-app-Traffic-By-Active-User-Number	Bandwidth application traffic by active user number	traffic

```

select
  $flex_timescale(timestamp) as hodex,
  count(
    distinct(user_src)
  ) as total_user
from
  ###(select $flex_timestamp as timestamp, coalesce(nullifna(`user`), nullifna(
    `unauthuser`), ipstr(`srcip`)) as user_src from $log where $filter and logid_to_
    int(logid) not in (4, 7, 14) group by timestamp, user_src order by timestamp
    desc)### t group by hodex order by hodex

```

Dataset Name	Description	Log Category
bandwidth-app-Top-Dest-By-Bandwidth-Sessions	Bandwidth application top dest by bandwidth usage sessions	traffic

```

select
  coalesce(
    nullifna(
      root_domain(hostname)
    ),
    ipstr(`dstip`)
  ) as domain,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  domain
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
bandwidth-app-Top-Policies-By-Bandwidth-Sessions	Top policies by bandwidth and sessions	traffic

```

select
  coalesce(
    cast(poluid as text),
    cast(policyid as text)
  ) as polid,
  sum(
    coalesce(rcvbyte, 0) + coalesce(sentbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log

```

```

where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  polid
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
bandwidth-app-Traffic-Statistics	Bandwidth application traffic statistics	traffic

```

drop
  table if exists stats_temp; create temporary table stats_temp(
    total_sessions varchar(255),
    total_bandwidth varchar(255),
    ave_session varchar(255),
    ave_bandwidth varchar(255),
    active_date varchar(255),
    total_users varchar(255),
    total_app varchar(255),
    total_dest varchar(255)
  ); insert into stats_temp (
    total_sessions, total_bandwidth,
    ave_session, ave_bandwidth
  )
select
  format_numeric_no_decimal(
    sum(sessions)
  ) as total_sessions,
  bandwidth_unit(
    sum(bandwidth)
  ) as total_bandwidth,
  format_numeric_no_decimal(
    cast(
      sum(sessions)/ $days_num as decimal(18, 0)
    )
  ) as ave_session,
  bandwidth_unit(
    cast(
      sum(bandwidth)/ $days_num as decimal(18, 0)
    )
  ) as ave_bandwidth
from
  ###(select count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as
  bandwidth from $log where $filter and logid_to_int(logid) not in (4, 7, 14))### t;
  update stats_temp set active_date=t1.dom from (select dom, sum(sessions) as
  sessions from ###(select $DAY_OF_MONTH as dom, count(*) as sessions from $log where
  $filter and logid_to_int(logid) not in (4, 7, 14) group by dom order by sessions
  desc)### t group by dom order by sessions desc limit 1) as t1; update stats_temp
  set total_users=t2.totalnum from (select format_numeric_no_decimal(count(distinct
  (user_src))) as totalnum from ###(select coalesce(nullifna(`user`), nullifna
  (`unauthuser`), ipstr(`srcip`)) as user_src, count(*) as count from $log where
  $filter and logid_to_int(logid) not in (4, 7, 14) group by user_src order by count
  desc)### t) as t2; update stats_temp set total_app=t3.totalnum from (select format_
  numeric_no_decimal(count(distinct(app_grp))) as totalnum from ###(select app_group_
  name(app) as app_grp, count(*) as count from $log where $filter and logid_to_int

```

```
(logid) not in (4, 7, 14) and nullifna(app) is not null group by app_grp order by
count desc)### t) as t3; update stats_temp set total_dest=t4.totalnum from (select
format_numeric_no_decimal(count(distinct(dstip))) as totalnum from ###(select
dstip, count(*) as count from $log where $filter and logid_to_int(logid) not in (4,
7, 14) and dstip is not null group by dstip order by count desc)### t ) as t4;
select 'Total Sessions' as summary, total_sessions as stats from stats_temp union
all select 'Total Bytes Transferred' as summary, total_bandwidth as stats from
stats_temp union all select 'Most Active Date By Sessions' as summary, active_date
as stats from stats_temp union all select 'Total Users' as summary, total_users as
stats from stats_temp union all select 'Total Applications' as summary, total_app
as stats from stats_temp union all select 'Total Destinations' as summary, total_
dest as stats from stats_temp union all select 'Average Sessions Per Day' as
summary, ave_session as stats from stats_temp union all select 'Average Bytes Per
Day' as summary, ave_bandwidth as stats from stats_temp
```

Dataset Name	Description	Log Category
Score-Summary-For-All-Users-Devices	Reputation score summary for all users devices	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  sum(scores) as scores
from
  ###(select $flex_timestamp as timestamp, sum(crscore%65536) as scores from $log where
  $filter and logid_to_int(logid) not in (4, 7, 14) and crscore is not null group by
  timestamp having sum(crscore%65536)>0 order by timestamp desc)### t group by hodex
order by hodex
```

Dataset Name	Description	Log Category
Number-Of-Incidents-For-All-Users-Devices	Reputation number of incidents for all users devices	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  sum(scores) as scores,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, sum(crscore%65536) as scores, count(*) as
  totalnum from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and
  crscore is not null group by timestamp having sum(crscore%65536)>0 order by
  timestamp desc)### t group by hodex order by hodex
```

Dataset Name	Description	Log Category
Top-Users-By-Reputation-Scores	Reputation top users by scores	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(crscore % 65536) as scores
```

```

from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and crscore is not null
group by
  user_src
having
  sum(crscore % 65536) > 0
order by
  scores desc

```

Dataset Name	Description	Log Category
Top-Devices-By-Reputation-Scores	Reputation top devices by scores	traffic

```

select
  devtype,
  coalesce(
    nullifna(`srcname`),
    nullifna(`srcmac`),
    ipstr(`srcip`)
  ) as dev_src,
  sum(crscore % 65536) as scores
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and crscore is not null
group by
  devtype,
  dev_src
having
  sum(crscore % 65536) > 0
order by
  scores desc

```

Dataset Name	Description	Log Category
Top-Users-With-Increased-Scores	Reputation top users with increased scores	traffic

```

drop
  table if exists prd1_usr_tbl;
drop
  table if exists prd2_usr_tbl; create temporary table prd1_usr_tbl as ###(select
  coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as f_user, sum
  (crscore%65536) as sum_rp_score from $log where $pre_period $filter and logid_to_
  int(logid) not in (4, 7, 14) and crscore is not null group by f_user having sum
  (crscore%65536)>0 order by sum_rp_score desc)###; create temporary table prd2_usr_
  tbl as ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
  (`srcip`)) as f_user, sum(crscore%65536) as sum_rp_score from $log where $filter
  and logid_to_int(logid) not in (4, 7, 14) and crscore is not null group by f_user
  having sum(crscore%65536)>0 order by sum_rp_score desc)###; select t1.f_user, sum

```

```
(t1.sum_rp_score) as t1_sum_score, sum(t2.sum_rp_score) as t2_sum_score, (sum
(t2.sum_rp_score)-sum(t1.sum_rp_score)) as delta from prd1_usr_tbl as t1 inner join
prd2_usr_tbl as t2 on t1.f_user=t2.f_user where t2.sum_rp_score > t1.sum_rp_score
group by t1.f_user order by delta desc
```

Dataset Name	Description	Log Category
Top-Devices-With-Increased-Scores	Reputation top devices with increased scores	traffic

```
drop
  table if exists prd1_dev_tbl;
drop
  table if exists prd2_dev_tbl; create temporary table prd1_dev_tbl as ###(select
  coalesce(nullifna(`srcname`),nullifna(`srcmac`), ipstr(`srcip`)) as f_device,
  devtype, sum(crscore%65536) as sum_rp_score from $log where $pre_period $filter and
  logid_to_int(logid) not in (4, 7, 14) and crscore is not null group by f_device,
  devtype having sum(crscore%65536)>0 order by sum_rp_score desc)###; create
  temporary table prd2_dev_tbl as ###(select coalesce(nullifna(`srcname`),nullifna
  (`srcmac`), ipstr(`srcip`)) as f_device, devtype, sum(crscore%65536) as sum_rp_
  score from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and crscore
  is not null group by f_device, devtype having sum(crscore%65536)>0 order by sum_rp_
  score desc)###; select t1.f_device, t1.devtype , sum(t1.sum_rp_score) as t1_sum_
  score, sum(t2.sum_rp_score) as t2_sum_score, (sum(t2.sum_rp_score)-sum(t1.sum_rp_
  score)) as delta from prd1_dev_tbl as t1 inner join prd2_dev_tbl as t2 on t1.f_
  device=t2.f_device and t1.devtype=t2.devtype where t2.sum_rp_score > t1.sum_rp_
  score group by t1.f_device, t1.devtype order by delta desc
```

Dataset Name	Description	Log Category
Attacks-By-Severity	Threat attacks by severity	attack

```
select
  (
    case when severity = 'critical' then 'Critical' when severity = 'high' then 'High'
      when severity = 'medium' then 'Medium' when severity = 'low' then 'Low' when
        severity = 'info' then 'Info' end
  ) as severity,
  count(*) as totalnum
from
  $log
where
  $filter
group by
  severity
order by
  totalnum desc
```

Dataset Name	Description	Log Category
Top-Attacks-Detected	Threat top attacks detected	attack

```
select
  attack,
  attackid,
  cve,
```

```

severity,
sum(attack_count) as attack_count
from
###(select attack, attackid, t1.severity, cve, (case when t1.severity = 'critical' then
1 when t1.severity = 'high' then 2 when t1.severity = 'medium' then 3 when
t1.severity = 'low' then 4 else 5 end) as severity_level, count(*) as attack_count
from $log t1 left join ips_mdata t2 on t1.attack=t2.name where $filter and nullifna
(attack) is not null group by attack, attackid, t1.severity, severity_level, cve
order by severity_level, attack_count desc)### t group by attack, attackid,
severity, severity_level, cve order by severity_level, attack_count desc

```

Dataset Name	Description	Log Category
Top-Attacks-Blocked	Threat top attacks blocked	attack

```

select
attack,
count(*) as attack_count
from
$log
where
$filter
and nullifna(attack) is not null
and action not in ('detected', 'pass_session')
group by
attack
order by
attack_count desc

```

Dataset Name	Description	Log Category
Top-Virus-Source	Threat top virus source	traffic

```

select
srcip,
hostname,
sum(totalnum) as totalnum
from
(
###(select srcip, hostname, count(*) as totalnum from $log-traffic where $filter and
logid_to_int(logid) not in (4, 7, 14) and utmevent is not null and virus is not
null group by srcip, hostname order by totalnum desc)### union all ###(select
srcip , ipstr(`dstip`) as hostname, count(*) as totalnum from $log-virus where
$filter and (eventtype is null or logver>=52) and nullifna(virus) is not null
group by srcip, hostname order by totalnum desc)###) t group by srcip, hostname
order by totalnum desc

```

Dataset Name	Description	Log Category
Intrusion-in-Last-7-Days	Threat intrusion timeline	attack

```

select
$flex_timescale(timestamp) as hodesk,
sum(totalnum) as totalnum

```

```

from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter
  group by timestamp order by timestamp desc)### t group by hodex order by hodex
    
```

Dataset Name	Description	Log Category
Virus-Time-Line	Threat virus timeline	virus

```

select
  $flex_timescale(timestamp) as hodex,
  sum(totalnum) as totalnum
from
  (
    ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log-traffic
    where $filter and logid_to_int(logid) not in (4, 7, 14) and utmevent is not null
    and virus is not null group by timestamp order by timestamp desc)### union all
    ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log-virus
    where $filter and (eventtype is null or logver>=52) and nullifna(virus) is not
    null group by timestamp order by timestamp desc)###) t group by hodex order by
  hodex
    
```

Dataset Name	Description	Log Category
Top-Spyware-Victims	Threat top spyware victims	virus

```

select
  user_src,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, count(*) as
  totalnum from $log where $filter group by user_src, virus order by totalnum
  desc)### t where virus like 'Riskware%' group by user_src order by totalnum desc
    
```

Dataset Name	Description	Log Category
Top-Spyware-by-Name	Threat top spyware by name	virus

```

select
  virus,
  max(virusid) as virusid,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, virusid,
  count(*) as totalnum from $log where $filter group by user_src, virus, virusid
  order by totalnum desc)### t where virus like 'Riskware%' group by virus order by
  totalnum desc
    
```

Dataset Name	Description	Log Category
Top-Spyware-Source	Threat top spyware source	traffic

```

select
  srcip,
    
```

```

hostname,
count(*) as totalnum
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and virus like 'Riskware%'
group by
srcip,
hostname
order by
totalnum desc

```

Dataset Name	Description	Log Category
Spyware-Time-Line	Threat spyware timeline	virus

```

select
$flex_timescale(timestamp) as hodesk,
sum(totalnum) as totalnum
from
###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter
and virus like 'Riskware%' group by timestamp order by timestamp desc)### t group
by hodesk order by hodesk

```

Dataset Name	Description	Log Category
Top-Adware-Victims	Threat top adware victims	virus

```

select
user_src,
sum(totalnum) as totalnum
from
###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, count(*) as
totalnum from $log where $filter group by user_src, virus order by totalnum
desc)### t where virus like 'Adware%' group by user_src order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Adware-by-Name	Threat top adware by name	virus

```

select
virus,
max(virusid) as virusid,
sum(totalnum) as totalnum
from
###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, virusid,
count(*) as totalnum from $log where $filter group by user_src, virus, virusid
order by totalnum desc)### t where virus like 'Adware%' group by virus order by
totalnum desc

```

Dataset Name	Description	Log Category
Top-Adware-Source	Threat top adware source	traffic

```

select
  srcip,
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and virus like 'Adware%'
group by
  srcip,
  hostname
order by
  totalnum desc

```

Dataset Name	Description	Log Category
Adware-Time-Line	Threat adware timeline	virus

```

select
  $flex_timescale(timestamp) as hodex,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter
  and virus like 'Adware%' group by timestamp order by timestamp desc)### t group by
  hodex order by hodex

```

Dataset Name	Description	Log Category
Intrusions-Timeline-By-Severity	Threat intrusions timeline by severity	attack

```

select
  $flex_timescale(timestamp) as timescale,
  sum(critical) as critical,
  sum(high) as high,
  sum(medium) as medium,
  sum(low) as low,
  sum(info) as info
from
  ###(select $flex_timestamp as timestamp, sum(case when severity = 'critical' then 1
  else 0 end) as critical, sum(case when severity = 'high' then 1 else 0 end) as
  high, sum(case when severity = 'medium' then 1 else 0 end) as medium, sum(case when
  severity = 'notice' then 1 else 0 end) as low, sum(case when severity = 'info' or
  severity = 'debug' then 1 else 0 end) as info from $log where $filter group by
  timestamp order by timestamp desc)### t group by timescale order by timescale

```

Dataset Name	Description	Log Category
Important-Intrusions-Timeline-By-Severity	Threat intrusions timeline by severity	attack

```

select
  $flex_timescale(timestamp) as timescale,
  sum(critical) as critical,
  sum(high) as high,
  sum(medium) as medium,
  sum(low) as low,
  sum(info) as info
from
  ###(select $flex_timestamp as timestamp, sum(case when severity = 'critical' then 1
  else 0 end) as critical, sum(case when severity = 'high' then 1 else 0 end) as
  high, sum(case when severity = 'medium' then 1 else 0 end) as medium, sum(case when
  severity = 'notice' then 1 else 0 end) as low, sum(case when severity = 'info' or
  severity = 'debug' then 1 else 0 end) as info from $log where $filter group by
  timestamp order by timestamp desc)### t group by timescale order by timescale

```

Dataset Name	Description	Log Category
Top-Intrusions-By-Types	Threat top intrusions by types	attack

```

select
  vuln_type,
  count(*) as totalnum
from
  $log t1
  left join ips_mdata t2 on t1.attack = t2.name
where
  $filter
  and vuln_type is not null
group by
  vuln_type
order by
  totalnum desc

```

Dataset Name	Description	Log Category
Critical-Severity-Intrusions	Threat critical severity intrusions	attack

```

select
  attack,
  attackid,
  cve,
  vuln_type,
  count(*) as totalnum
from
  $log t1
  left join ips_mdata t2 on t1.attack = t2.name
where
  $filter

```

```

    and t1.severity = 'critical'
group by
    attack,
    attackid,
    cve,
    vuln_type
order by
    totalnum desc

```

Dataset Name	Description	Log Category
High-Severity-Intrusions	Threat high severity intrusions	attack

```

select
    attack,
    attackid,
    vuln_type,
    cve,
    count(*) as totalnum
from
    $log t1
    left join ips_mdata t2 on t1.attack = t2.name
where
    $filter
    and t1.severity = 'high'
group by
    attack,
    attackid,
    vuln_type,
    cve
order by
    totalnum desc

```

Dataset Name	Description	Log Category
Medium-Severity-Intrusions	Threat medium severity intrusions	attack

```

select
    attack,
    vuln_type,
    cve,
    count(*) as totalnum
from
    $log t1
    left join ips_mdata t2 on t1.attack = t2.name
where
    $filter
    and t1.severity = 'medium'
group by
    attack,
    vuln_type,
    cve
order by
    totalnum desc

```

Dataset Name	Description	Log Category
Top-Intrusion-Victims	Threat top intrusion victims	attack

```
select
  victim,
  sum(cri_num) as critical,
  sum(high_num) as high,
  sum(med_num) as medium,
  sum(cri_num + high_num + med_num) as totalnum
from
  ###(select dstip as victim, sum((case when severity='critical' then 1 else 0 end)) as
  cri_num, sum(case when severity='high' then 1 else 0 end) as high_num, sum(case
  when severity='medium' then 1 else 0 end) as med_num from $log where $filter and
  severity in ('critical', 'high', 'medium') group by victim)### t group by victim
order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Intrusion-Sources	Threat top intrusion sources	attack

```
select
  source,
  sum(cri_num) as critical,
  sum(high_num) as high,
  sum(med_num) as medium,
  sum(cri_num + high_num + med_num) as totalnum
from
  ###(select srcip as source, sum(case when severity='critical' then 1 else 0 end) as
  cri_num, sum(case when severity='high' then 1 else 0 end) as high_num, sum(case
  when severity='medium' then 1 else 0 end) as med_num from $log where $filter and
  severity in ('critical', 'high', 'medium') group by source)### t group by source
order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Blocked-Intrusions	Threat top blocked intrusions	attack

```
select
  attack,
  attackid,
  (
    case when t1.severity = 'critical' then 'Critical' when t1.severity = 'high' then
    'High' when t1.severity = 'medium' then 'Medium' when t1.severity = 'low' then
    'Low' when t1.severity = 'info' then 'Info' end
  ) as severity_name,
  count(*) as totalnum,
  vuln_type,
  (
    case when t1.severity = 'critical' then 0 when t1.severity = 'high' then 1 when
    t1.severity = 'medium' then 2 when t1.severity = 'low' then 3 when t1.severity =
    'info' then 4 else 5 end
  ) as severity_number
```

```

from
  $log t1
  left join ips_mdata t2 on t1.attack = t2.name
where
  $filter
  and nullifna(attack) is not null
  and action not in ('detected', 'pass_session')
group by
  attack,
  attackid,
  t1.severity,
  vuln_type
order by
  severity_number,
  totalnum desc

```

Dataset Name	Description	Log Category
Top-Monitored-Intrusions	Threat top monitored intrusions	attack

```

select
  attack,
  attackid,
  (
    case when t1.severity = 'critical' then 'Critical' when t1.severity = 'high' then
      'High' when t1.severity = 'medium' then 'Medium' when t1.severity = 'low' then
      'Low' when t1.severity = 'info' then 'Info' end
  ) as severity_name,
  count(*) as totalnum,
  vuln_type,
  (
    case when t1.severity = 'critical' then 0 when t1.severity = 'high' then 1 when
      t1.severity = 'medium' then 2 when t1.severity = 'low' then 3 when t1.severity =
      'info' then 4 else 5 end
  ) as severity_number
from
  $log t1
  left join ips_mdata t2 on t1.attack = t2.name
where
  $filter
  and nullifna(attack) is not null
  and action in ('detected', 'pass_session')
group by
  attack,
  attackid,
  t1.severity,
  vuln_type
order by
  severity_number,
  totalnum desc

```

Dataset Name	Description	Log Category
Attacks-Over-HTTP-HTTPS	Threat attacks over HTTP HTTPS	attack

```

select
  attack,
  attackid,
  (
    case when severity = 'critical' then 'Critical' when severity = 'high' then 'High'
         when severity = 'medium' then 'Medium' when severity = 'low' then 'Low' when
         severity = 'info' then 'Info' end
  ) as severity,
  count(*) as totalnum,
  (
    case when severity = 'critical' then 0 when severity = 'high' then 1 when severity =
         'medium' then 2 when severity = 'low' then 3 when severity = 'info' then 4 else
         5 end
  ) as severity_number
from
  $log
where
  $filter
  and severity in ('critical', 'high', 'medium')
  and upper(service) in ('HTTP', 'HTTPS')
group by
  attack,
  attackid,
  severity,
  severity_number
order by
  severity_number,
  totalnum desc

```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OffWire	Default access point detection summary by status off-wire	event

```

select
  (
    case apstatus when 1 then 'rogue' when 2 then 'accepted' when 3 then 'suppressed'
         else 'others' end
  ) as ap_full_status,
  count(*) as totalnum
from
  (
    select
      apstatus,
      bssid,
      ssid
    from
      ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter
         and apstatus is not null and apstatus!=0 and bssid is not null and
         onwire='no' and logid_to_int(logid) in (43527, 43521, 43525, 43563, 43564,
         43565, 43566, 43569, 43570, 43571, 43582, 43583, 43584, 43585) group by
         apstatus, bssid, ssid order by subtotal desc)### t group by apstatus, bssid,
         ssid) t group by ap_full_status order by totalnum desc
  )

```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OffWire_table	Default access point detection summary by status off-wire	event

```

select
  (
    case apstatus when 1 then 'rogue' when 2 then 'accepted' when 3 then 'suppressed'
    else 'others' end
  ) as ap_full_status,
  count(*) as totalnum
from
  (
    select
      apstatus,
      bssid,
      ssid
    from
      ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter
      and apstatus is not null and apstatus!=0 and bssid is not null and
      onwire='no' and logid_to_int(logid) in (43527, 43521, 43525, 43563, 43564,
      43565, 43566, 43569, 43570, 43571, 43582, 43583, 43584, 43585) group by
      apstatus, bssid, ssid order by subtotal desc)### t group by apstatus, bssid,
      ssid) t group by ap_full_status order by totalnum desc

```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OnWire	Default access point detection summary by status on-wire	event

```

select
  (
    case apstatus when 1 then 'rogue' when 2 then 'accepted' when 3 then 'suppressed'
    else 'others' end
  ) as ap_full_status,
  count(*) as totalnum
from
  (
    select
      apstatus,
      bssid,
      ssid
    from
      ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter
      and apstatus is not null and apstatus!=0 and bssid is not null and
      onwire='yes' and logid_to_int(logid) in (43527, 43521, 43525, 43563, 43564,
      43565, 43566, 43569, 43570, 43571, 43582, 43583, 43584, 43585) group by
      apstatus, bssid, ssid order by subtotal desc)### t group by apstatus, bssid,
      ssid) t group by ap_full_status order by totalnum desc

```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OnWire_table	Default access point detection summary by status on-wire	event

```

select
  (
    case apstatus when 1 then 'rogue' when 2 then 'accepted' when 3 then 'suppressed'
    else 'others' end
  ) as ap_full_status,
  count(*) as totalnum
from
  (
    select
      apstatus,
      bssid,
      ssid
    from
      ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter
      and apstatus is not null and apstatus!=0 and bssid is not null and
      onwire='yes' and logid_to_int(logid) in (43527, 43521, 43525, 43563, 43564,
      43565, 43566, 43569, 43570, 43571, 43582, 43583, 43584, 43585) group by
      apstatus, bssid, ssid order by subtotal desc)### t group by apstatus, bssid,
      ssid) t group by ap_full_status order by totalnum desc

```

Dataset Name	Description	Log Category
default-Managed-AP-Summary	Default managed access point summary	event

```

select
  (
    case when (
      action like '%join%'
      and logid_to_int(logid) in (43522, 43551)
    ) then 'Authorized' else 'Unauthorized' end
  ) as ap_status,
  count(*) as totalnum
from
  $log
where
  $filter
  and logid_to_int(logid) in (43522, 43551)
group by
  ap_status
order by
  totalnum desc

```

Dataset Name	Description	Log Category
default-Managed-AP-Summary_table	Default managed access point summary	event

```

select

```

```
(
  case when (
    action like '%join%'
    and logid_to_int(logid) in (43522, 43551)
  ) then 'Authorized' else 'Unauthorized' end
) as ap_status,
count(*) as totalnum
from
$log
where
$filter
and logid_to_int(logid) in (43522, 43551)
group by
ap_status
order by
totalnum desc
```

Dataset Name	Description	Log Category
default-Unclassified-AP-Summary	Default unclassified access point summary	event

```
select
(
  case onwire when 'no' then 'off-wire' when 'yes' then 'on-wire' else 'others' end
) as ap_status,
count(*) as totalnum
from
###(select onwire, ssid, bssid, count(*) as subtotal from $log where $filter and
apstatus=0 and bssid is not null and logid_to_int(logid) in (43521, 43525, 43527,
43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582, 43583, 43584, 43585) group
by onwire, ssid, bssid order by subtotal desc)### t group by ap_status order by
totalnum desc
```

Dataset Name	Description	Log Category
default-Unclassified-AP-Summary_ table	Default unclassified access point summary	event

```
select
(
  case onwire when 'no' then 'off-wire' when 'yes' then 'on-wire' else 'others' end
) as ap_status,
count(*) as totalnum
from
###(select onwire, ssid, bssid, count(*) as subtotal from $log where $filter and
apstatus=0 and bssid is not null and logid_to_int(logid) in (43521, 43525, 43527,
43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582, 43583, 43584, 43585) group
by onwire, ssid, bssid order by subtotal desc)### t group by ap_status order by
totalnum desc
```

Dataset Name	Description	Log Category
default-selected-AP-Details-OffWire	Default selected access point details off-wire	event

```

select
  (
    case apstatus when 0 then 'unclassified' when 1 then 'rogue' when 2 then 'accepted'
      when 3 then 'suppressed' else 'others' end
  ) as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  rssi,
  channel,
  radioband,
  from_dtime(
    min(dtime)
  ) as first_seen,
  from_dtime(
    max(dtime)
  ) as last_seen,
  detectionmethod,
  itime,
  onwire as on_wire
from
  $log
where
  $filter
  and apstatus is not null
  and bssid is not null
  and onwire = 'no'
  and logid_to_int(logid) in (
    43521, 43563, 43564, 43565, 43566, 43569,
    43570, 43571
  )
group by
  ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  rssi,
  channel,
  radioband,
  detectionmethod,
  itime,
  onwire,
  apstatus

```

Dataset Name	Description	Log Category
default-selected-AP-Details-OnWire	Default selected access point details on-wire	event

```

select
  (
    case apstatus when 0 then 'unclassified' when 1 then 'rogue' when 2 then 'accepted'
      when 3 then 'suppressed' else 'others' end
  )

```

```

    ) as ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    rssi,
    channel,
    radioband,
    from_dtime(
        min(dtime)
    ) as first_seen,
    from_dtime(
        max(dtime)
    ) as last_seen,
    detectionmethod,
    itime,
    onwire as on_wire
from
    $log
where
    $filter
    and apstatus is not null
    and bssid is not null
    and onwire = 'yes'
    and logid_to_int(logid) in (
        43521, 43563, 43564, 43565, 43566, 43569,
        43570, 43571
    )
group by
    ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    rssi,
    channel,
    radioband,
    detectionmethod,
    itime,
    onwire,
    apstatus

```

Dataset Name	Description	Log Category
event-Wireless-Client-Details	Event wireless client details	event

```

drop
    table if exists ip_list; create temporary table ip_list as
select
    ip,
    lower(mac) as lmac,
    sn,
    ssid,
    channel,

```

```

    radioband,
    min(dtime) as first,
    max(dtime) as last
from
    $log - event
where
    $filter
    and ip is not null
    and mac is not null
    and sn is not null
    and ssid is not null
group by
    ip,
    lmac,
    sn,
    ssid,
    channel,
    radioband
order by
    ip;
select
    user_src,
    ip,
    lmac,
    sn,
    ssid,
    channel,
    radioband,
    from_dtime(first) as first_seen,
    from_dtime(last) as last_seen,
    cast(
        volume as decimal(18, 2)
    ) as bandwidth
from
    (
        select
            *
        from
            ip_list
        inner join (
            select
                user_src,
                srcip,
                sum(volume) as volume
            from
                ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
                    (`srcip`)) as user_src, srcip, sum(coalesce(sentbyte, 0)+coalesce
                    (rcvdbyte, 0)) as volume from $log-traffic where $filter-time and logid_
                    to_int(logid) not in (4, 7, 14) and srcip is not null group by user_src,
                    srcip having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by
                    volume desc)### t group by user_src, srcip order by user_src, srcip) t
            on ip_list.ip = t.srcip) t order by volume desc

```

Dataset Name	Description	Log Category
event-Wireless-Accepted-Offwire	Event wireless accepted off-wire	event

```

select
  'accepted' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'no' as on_wire
from
  ###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
    snclosest, onwire, logid, apstatus, max(dtime) as last_seen from $log where $filter
    and bssid is not null and logid_to_int(logid) in (43521, 43525, 43563, 43564,
    43565, 43566, 43569, 43570, 43571) group by devid, vd, ssid, bssid, manuf, channel,
    radioband, detectionmethod, snclosest, onwire, logid, apstatus order by last_seen
    desc)### t where apstatus=2 and onwire='no' group by devid, vd, ssid, bssid, manuf,
    channel, radioband, detectionmethod, snclosest order by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Accepted-Onwire	Event wireless accepted on-wire	event

```

select
  'accepted' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'yes' as on_wire
from
  ###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
    snclosest, onwire, apstatus, max(dtime) as last_seen from $log where $filter and
    bssid is not null and logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565,
    43566, 43569, 43570, 43571) group by devid, vd, ssid, bssid, manuf, channel,
    radioband, detectionmethod, snclosest, onwire, apstatus order by last_seen desc)###
    t where apstatus=2 and onwire='yes' group by devid, vd, ssid, bssid, manuf,
    channel, radioband, detectionmethod, snclosest order by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Rogue-Offwire	Event wireless rogue off-wire	event

```

select
  'rogue' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'no' as on_wire
from
  ###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
    snclosest, onwire, logid, apstatus, max(dtime) as last_seen from $log where $filter
    and bssid is not null and logid_to_int(logid) in (43521, 43525, 43563, 43564,
    43565, 43566, 43569, 43570, 43571) group by devid, vd, ssid, bssid, manuf, channel,
    radioband, detectionmethod, snclosest, onwire, logid, apstatus order by last_seen
    desc)### t where apstatus=1 and onwire='no' group by devid, vd, ssid, bssid, manuf,
    channel, radioband, detectionmethod, snclosest order by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Rogue-Onwire	Event wireless rogue on-wire	event

```

select
  'rogue' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'yes' as on_wire
from
  ###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
    snclosest, onwire, apstatus, max(dtime) as last_seen from $log where $filter and
    bssid is not null and logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565,
    43566, 43569, 43570, 43571) group by devid, vd, ssid, bssid, manuf, channel,
    radioband, detectionmethod, snclosest, onwire, apstatus order by last_seen desc)###
    t where apstatus=1 and onwire='yes' group by devid, vd, ssid, bssid, manuf,
    channel, radioband, detectionmethod, snclosest order by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Suppressed-Offwire	Event wireless suppressed off-wire	event

```

select
  'suppressed' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'no' as on_wire
from
  ###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
    snclosest, onwire, logid, apstatus, max(dtime) as last_seen from $log where $filter
    and bssid is not null and logid_to_int(logid) in (43521, 43525, 43563, 43564,
    43565, 43566, 43569, 43570, 43571) group by devid, vd, ssid, bssid, manuf, channel,
    radioband, detectionmethod, snclosest, onwire, logid, apstatus order by last_seen
    desc)### t where apstatus=3 and onwire='no' group by devid, vd, ssid, bssid, manuf,
    channel, radioband, detectionmethod, snclosest order by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Suppressed-Onwire	Event wireless suppressed on-wire	event

```

select
  'suppressed' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'yes' as on_wire
from
  ###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
    snclosest, onwire, apstatus, max(dtime) as last_seen from $log where $filter and
    bssid is not null and logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565,
    43566, 43569, 43570, 43571) group by devid, vd, ssid, bssid, manuf, channel,
    radioband, detectionmethod, snclosest, onwire, apstatus order by last_seen desc)###
    t where apstatus=3 and onwire='yes' group by devid, vd, ssid, bssid, manuf,
    channel, radioband, detectionmethod, snclosest order by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Unclassified-Offwire	Event wireless unclassified off-wire	event

```

select
  'unclassified' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'no' as on_wire
from
  ###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
    snclosest, onwire, logid, apstatus, max(dtime) as last_seen from $log where $filter
    and bssid is not null and logid_to_int(logid) in (43521, 43525, 43563, 43564,
    43565, 43566, 43569, 43570, 43571) group by devid, vd, ssid, bssid, manuf, channel,
    radioband, detectionmethod, snclosest, onwire, logid, apstatus order by last_seen
    desc)### t where apstatus=0 and onwire='no' group by devid, vd, ssid, bssid, manuf,
    channel, radioband, detectionmethod, snclosest order by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Unclassified-Onwire	Event wireless unclassified on-wire	event

```

select
  'unclassified' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'yes' as on_wire
from
  ###(select devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod,
    snclosest, onwire, apstatus, max(dtime) as last_seen from $log where $filter and
    bssid is not null and logid_to_int(logid) in (43521, 43525, 43563, 43564, 43565,
    43566, 43569, 43570, 43571) group by devid, vd, ssid, bssid, manuf, channel,
    radioband, detectionmethod, snclosest, onwire, apstatus order by last_seen desc)###
    t where apstatus=0 and onwire='yes' group by devid, vd, ssid, bssid, manuf,
    channel, radioband, detectionmethod, snclosest order by last_seen desc

```

Dataset Name	Description	Log Category
default-Top-IPSEC-Vpn-Dial-Up-User-By-Bandwidth	Default top IPsec VPN dial up user by bandwidth usage	event

```

select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as user_src,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
      string_agg(distinct user_agg, ' ') as user_agg,
      remip,
      tunnelid,
      min(s_time) as s_time,
      max(e_time) as e_time,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
      ) as bandwidth,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)- min(min_traffic_in) end
      ) as traffic_in,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_out)- min(min_traffic_out) end
      ) as traffic_out
    from
      ###(select devid, vd, nullifna(`xauthuser`) as xauthuser_agg, nullifna(`user`) as user_agg, remip, tunnelid, min(coalesce(dtime, 0)) as s_time, max(coalesce(dtime, 0)) as e_time, min(coalesce(sentbyte, 0)) as min_traffic_out, min(coalesce(rcvdbyte, 0)) as min_traffic_in, max(coalesce(sentbyte, 0)) as max_traffic_out, max(coalesce(rcvdbyte, 0)) as max_traffic_in from $log where $filter and subtype='vpn' and tunneltype like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0') and action in ('tunnel-stats', 'tunnel-down', 'tunnel-up') and tunnelid is not null group by devid, vd, xauthuser_agg, user_agg, remip, tunnelid order by tunnelid)### t group by devid, vd, remip, tunnelid) tt group by user_src having sum(bandwidth)>0 order by bandwidth desc
  )

```

Dataset Name	Description	Log Category
default-Top-Sources-Of-SSL-VPN-Tunnels-By-Bandwidth	Default top sources of SSL VPN tunnels by bandwidth usage	event

```

select
  remip as remote_ip,
  sum(traffic_in + traffic_out) as bandwidth
from
  (
    select
      devid,
      vd,
      remip,
      tunnelid,
      max(traffic_in) as traffic_in,
      max(traffic_out) as traffic_out
    from
      ###(select devid, vd, remip, tunnelid, max(coalesce(sentbyte, 0)) as traffic_out,
      max(coalesce(rcvbyte, 0)) as traffic_in from $log where $filter and
      subtype='vpn' and tunneltype like 'ssl%' and action in ('tunnel-stats',
      'tunnel-down') and remip is not null and tunnelid is not null group by devid,
      vd, remip, tunnelid order by tunnelid)### t group by devid, vd, remip,
      tunnelid) tt group by remote_ip having sum(traffic_in+traffic_out)>0 order by
      bandwidth desc
  )

```

Dataset Name	Description	Log Category
webfilter-Web-Activity-Summary-By-Requests	Webfilter web activity summary by requests	webfilter

```

select
  $flex_timescale(timestamp) as hodex,
  sum(allowed_request) as allowed_request,
  sum(blocked_request) as blocked_request
from
  (
    ###(select $flex_timestamp as timestamp, sum(case when utmaction!='blocked' then 1
    else 0 end) as allowed_request, sum(case when utmaction='blocked' then 1 else 0
    end) as blocked_request from $log-traffic where $filter and logid_to_int(logid)
    not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word', 'web-content',
    'command-block', 'script-filter') group by timestamp order by timestamp desc)###
    union all ###(select $flex_timestamp as timestamp, sum(case when
    action!='blocked' then 1 else 0 end) as allowed_request, sum(case when
    action='blocked' then 1 else 0 end) as blocked_request from $log-webfilter where
    $filter and (eventtype is null or logver>=52) group by timestamp order by
    timestamp desc)###) t group by hodex order by hodex
  )

```

Dataset Name	Description	Log Category
traffic-Browsing-Time-Summary	Traffic browsing time summary	traffic

```

select

```

```

$flex_timescale(timestamp) as hodex,
cast(
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  )/ 60.0 as decimal(18, 2)
) as browsetime
from
###(select $flex_timestamp as timestamp, ebtr_agg_flat($browse_time) as browsetime from
$log where $filter and logid_to_int(logid) not in (4, 7, 14) and $browse_time is
not null group by timestamp order by timestamp desc)### t group by hodex order by
hodex

```

Dataset Name	Description	Log Category
traffic-Browsing-Time-Summary-Enhanced	Traffic browsing time summary enhanced	traffic

```

select
$flex_timescale(timestamp) as hodex,
cast(
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  )/ 60.0 as decimal(18, 2)
) as browsetime
from
###(select $flex_timestamp as timestamp, ebtr_agg_flat($browse_time) as browsetime from
$log where $filter and logid_to_int(logid) not in (4, 7, 14) and $browse_time is
not null group by timestamp order by timestamp desc)### t group by hodex order by
hodex

```

Dataset Name	Description	Log Category
webfilter-Top-Web-Users-By-Blocked-Requests	Webfilter top web users by blocked requests	webfilter

```

select
  user_src,
  sum(requests) as requests
from
(
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, count(*) as requests from $log-traffic where $filter and logid_to_int
  (logid) not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word', 'web-
  content', 'command-block', 'script-filter') and coalesce(nullifna(`user`),
  nullifna(`unauthuser`), ipstr(`srcip`)) is not null and utmaction='blocked'
  group by user_src order by requests desc)### union all ###(select coalesce
  (nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as requests from $log-
  webfilter where $filter and (eventtype is null or logver>=52) and coalesce
  (nullifna(`user`), ipstr(`srcip`)) is not null and action='blocked' group by
  user_src order by requests desc)###) t group by user_src order by requests desc

```

Dataset Name	Description	Log Category
webfilter-Top-Web-Users-By-Allowed-Requests	Webfilter top web users by allowed requests	webfilter

```
select
  user_src,
  sum(requests) as requests
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
    user_src, count(*) as requests from $log-traffic where $filter and logid_to_int
    (logid) not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word', 'web-
    content', 'command-block', 'script-filter') and coalesce(nullifna(`user`),
    nullifna(`unauthuser`), ipstr(`srcip`)) is not null and utmaction!='blocked'
    group by user_src order by requests desc)### union all ###(select coalesce
    (nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as requests from $log-
    webfilter where $filter and (eventtype is null or logver>=52) and coalesce
    (nullifna(`user`), ipstr(`srcip`)) is not null and action!='blocked' group by
    user_src order by requests desc)###) t group by user_src order by requests desc
```

Dataset Name	Description	Log Category
traffic-Top-Web-Users-By-Browsing-Time	Traffic top web users by browsing time	traffic

```
select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select user_src, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
  bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
  (select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, ebtr_agg_flat
  ($browse_time) as browsetime, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as
  bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as
  traffic_out from $log where $filter and $browse_time is not null group by user_src)
  t group by user_src order by ebtr_value(ebtr_agg_flat(browsetime), null, null)
  desc)### t group by user_src order by browsetime desc
```

Dataset Name	Description	Log Category
webfilter-Top-Blocked-Web-Sites-By-Requests	Webfilter top blocked web sites by requests	webfilter

```
select
  domain,
```

```

catdesc,
sum(requests) as requests
from
(
  ###(select hostname as domain, catdesc, count(*) as requests from $log-traffic where
  $filter and logid_to_int(logid) not in (4, 7, 14) and utmevent in ('webfilter',
  'banned-word', 'web-content', 'command-block', 'script-filter') and hostname is
  not null and utmaction='blocked' group by domain, catdesc order by requests
  desc)### union all ###(select hostname as domain, catdesc, count(*) as requests
  from $log-webfilter where $filter and (eventtype is null or logver>=52) and
  hostname is not null and catdesc is not null and action='blocked' group by
  domain, catdesc order by requests desc)###) t group by domain, catdesc order by
  requests desc

```

Dataset Name	Description	Log Category
webfilter-Top-Allowed-Web-Sites-By-Requests	Webfilter top allowed web sites by requests	webfilter

```

select
  domain,
  string_agg(distinct catdesc, ', ') as agg_catdesc,
  sum(requests) as requests
from
(
  ###(select hostname as domain, catdesc, count(*) as requests from $log-traffic where
  $filter and logid_to_int(logid) not in (4, 7, 14) and utmevent in ('webfilter',
  'banned-word', 'web-content', 'command-block', 'script-filter') and hostname is
  not null and utmaction!='blocked' group by domain, catdesc order by requests
  desc)### union all ###(select hostname as domain, catdesc, count(*) as requests
  from $log-webfilter where $filter and (eventtype is null or logver>=52) and
  hostname is not null and catdesc is not null and action!='blocked' group by
  domain, catdesc order by requests desc)###) t group by domain order by requests
  desc

```

Dataset Name	Description	Log Category
webfilter-Top-Video-Streaming-Websites-By-Bandwidth	Webfilter top video streaming websites by bandwidth usage	webfilter

```

select
  domain,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select coalesce(nullifna(root_domain(hostname)), 'other') as domain, sum(coalesce
  (sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte, 0)) as
  traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log-traffic where
  $filter and logid_to_int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is
  null or logver<52) and (hostname is not null or utmevent in ('webfilter', 'banned-
  word', 'web-content', 'command-block', 'script-filter')))) and catdesc in
  ('Streaming Media and Download') group by domain having sum(coalesce(sentbyte,
  0)+coalesce(rcvbyte, 0))>0 order by bandwidth desc)###) t group by domain order by
  bandwidth desc

```

Dataset Name	Description	Log Category
webfilter-Top-Blocked-Web-Categories	Webfilter top blocked web categories	webfilter

```
select
  catdesc,
  sum(requests) as requests
from
  (
    ###(select catdesc, count(*) as requests from $log-traffic where $filter and logid_
      to_int(logid) not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word',
        'web-content', 'command-block', 'script-filter') and catdesc is not null and
        utmaction='blocked' group by catdesc order by requests desc)### union all ###
    (select catdesc, count(*) as requests from $log-webfilter where $filter and
      (eventtype is null or logver>=52) and catdesc is not null and action='blocked'
      group by catdesc order by requests desc)###) t group by catdesc order by
    requests desc
```

Dataset Name	Description	Log Category
webfilter-Top-Allowed-Web-Categories	Webfilter top allowed web categories	webfilter

```
select
  catdesc,
  sum(requests) as requests
from
  (
    ###(select catdesc, count(*) as requests from $log-traffic where $filter and logid_
      to_int(logid) not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word',
        'web-content', 'command-block', 'script-filter') and catdesc is not null and
        utmaction!='blocked' group by catdesc order by requests desc)### union all ###
    (select catdesc, count(*) as requests from $log-webfilter where $filter and
      (eventtype is null or logver>=52) and catdesc is not null and action!='blocked'
      group by catdesc order by requests desc)###) t group by catdesc order by
    requests desc
```

Dataset Name	Description	Log Category
traffic-Top-50-Sites-By-Browsing-Time	Traffic top sites by browsing time	traffic

```
select
  hostname,
  string_agg(distinct catdesc, ', ') as agg_catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
```

```

sum(traffic_out) as traffic_out
from
###(select hostname, catdesc, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth)
as bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
(select hostname, catdesc, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte, 0)) as
traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and
logid_to_int(logid) not in (4, 7, 14) and hostname is not null and $browse_time is
not null group by hostname, catdesc) t group by hostname, catdesc order by ebtr_
value(ebtr_agg_flat(browsetime), null, null) desc)### t group by hostname order by
browsetime desc
    
```

Dataset Name	Description	Log Category
traffic-Top-50-Sites-By-Browsing-Time-Enhanced	Traffic top sites by browsing time enhanced	traffic

```

select
hostname,
string_agg(distinct catdesc, ', ') as agg_catdesc,
ebtr_value(
ebtr_agg_flat(browsetime),
null,
$timespan
) as browsetime,
sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in,
sum(traffic_out) as traffic_out
from
###(select hostname, catdesc, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth)
as bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
(select hostname, catdesc, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte, 0)) as
traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and
logid_to_int(logid) not in (4, 7, 14) and hostname is not null and $browse_time is
not null group by hostname, catdesc) t group by hostname, catdesc order by ebtr_
value(ebtr_agg_flat(browsetime), null, null) desc)### t group by hostname order by
browsetime desc
    
```

Dataset Name	Description	Log Category
traffic-Top-10-Categories-By-Browsing-Time	Traffic top category by browsing time	traffic

```

select
catdesc,
ebtr_value(
ebtr_agg_flat(browsetime),
null,
$timespan
) as browsetime,
sum(bandwidth) as bandwidth
from
###(select catdesc, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
bandwidth from (select catdesc, ebtr_agg_flat($browse_time) as browsetime, sum
(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth from $log where $filter
    
```

```
and logid_to_int(logid) not in (4, 7, 14) and catdesc is not null and $browse_time
is not null group by catdesc) t group by catdesc order by ebtr_value(ebtr_agg_flat
(browsetime), null, null) desc)### t group by catdesc order by browsetime desc
```

Dataset Name	Description	Log Category
traffic-Top-10-Categories-By-Browsing-Time-Enhanced	Traffic top category by browsing time enhanced	traffic

```
select
  catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
  bandwidth from (select catdesc, ebtr_agg_flat($browse_time) as browsetime, sum
  (coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth from $log where $filter
  and logid_to_int(logid) not in (4, 7, 14) and catdesc is not null and $browse_time
  is not null group by catdesc) t group by catdesc order by ebtr_value(ebtr_agg_flat
  (browsetime), null, null) desc)### t group by catdesc order by browsetime desc
```

Dataset Name	Description	Log Category
traffic-Top-Destination-Countries-By-Browsing-Time	Traffic top destination countries by browsing time	traffic

```
select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select dstcountry, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
  bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
  (select dstcountry, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
  (sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte, 0)) as
  traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and
  logid_to_int(logid) not in (4, 7, 14) and $browse_time is not null group by
  dstcountry) t group by dstcountry order by ebtr_value(ebtr_agg_flat(browsetime),
  null, null) desc)### t group by dstcountry order by browsetime desc
```

Dataset Name	Description	Log Category
traffic-Top-Destination-Countries-By-Browsing-Time-Enhanced	Traffic top destination countries by browsing time enhanced	traffic

```
select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select dstcountry, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
  bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
  (select dstcountry, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
  (sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte, 0)) as
  traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and
  logid_to_int(logid) not in (4, 7, 14) and $browse_time is not null group by
  dstcountry) t group by dstcountry order by ebtr_value(ebtr_agg_flat(browsetime),
  null, null) desc)### t group by dstcountry order by browsetime desc
```

Dataset Name	Description	Log Category
webfilter-Top-Search-Phrases	Webfilter top search phrases	webfilter

```
select
  keyword,
  count(*) as requests
from
  $log
where
  $filter
  and keyword is not null
group by
  keyword
order by
  requests desc
```

Dataset Name	Description	Log Category
Top-10-Users-Browsing-Time	Estimated browsing time	traffic

```
select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###(select user_src, ebtr_agg_flat(browsetime) as browsetime from (select coalesce
  (nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ebtr_agg_
  flat($browse_time) as browsetime from $log where $filter and logid_to_int(logid)
  not in (4, 7, 14) and $browse_time is not null group by user_src) t group by user_
  src order by ebtr_value(ebtr_agg_flat(browsetime), null, null) desc)### t group by
  user_src order by browsetime desc
```

Dataset Name	Description	Log Category
Top-10-Users-Browsing-Time-Enhanced	Estimated browsing time enhanced	traffic

```

select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###(select user_src, ebtr_agg_flat(browsetime) as browsetime from (select coalesce
  (nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ebtr_agg_
  flat($browse_time) as browsetime from $log where $filter and logid_to_int(logid)
  not in (4, 7, 14) and $browse_time is not null group by user_src) t group by user_
  src order by ebtr_value(ebtr_agg_flat(browsetime), null, null) desc)### t group by
  user_src order by browsetime desc

```

Dataset Name	Description	Log Category
Estimated-Browsing-Time	Estimated browsing time	traffic

```

select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###(select user_src, ebtr_agg_flat(browsetime) as browsetime from (select coalesce
  (nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ebtr_agg_
  flat($browse_time) as browsetime from $log where $filter and logid_to_int(logid)
  not in (4, 7, 14) and $browse_time is not null group by user_src) t group by user_
  src order by ebtr_value(ebtr_agg_flat(browsetime), null, null) desc)### t group by
  user_src order by browsetime desc

```

Dataset Name	Description	Log Category
Estimated-Browsing-Time-Enhanced	Estimated browsing time enhanced	traffic

```

select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from

```

```
###(select user_src, ebtr_agg_flat(browsetime) as browsetime from (select coalesce
(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, ebtr_agg_
flat($browse_time) as browsetime from $log where $filter and logid_to_int(logid)
not in (4, 7, 14) and $browse_time is not null group by user_src) t group by user_
src order by ebtr_value(ebtr_agg_flat(browsetime), null, null) desc)### t group by
user_src order by browsetime desc
```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Bandwidth	Top access point by bandwidth usage	traffic

```
select
  coalesce(ap, srcintf) as ap_srcintf,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and (
    srcssid is not null
    or dstssid is not null
  )
group by
  ap_srcintf
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Client	Top access point by client	traffic

```
select
  srcintf,
  count(distinct srcmac) as totalnum
from
  ###(select srcintf, srcssid, osname, osversion, devtype, srcmac, count(*) as subtotal
  from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and (srcssid is
  not null or dstssid is not null) and srcmac is not null group by srcintf, srcssid,
  osname, osversion, devtype, srcmac order by subtotal desc)### t group by srcintf
  order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Top-SSID-By-Bandwidth	Top SSIDs by bandwidth usage	traffic

```
select
  srcssid,
```

```

sum(
  coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
) as bandwidth
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and srcssid is not null
group by
srcssid
having
sum(
  coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
)> 0
order by
bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-SSID-By-Client	Top SSIDs by client	traffic

```

select
srcssid,
count(distinct srcmac) as totalnum
from
###(select srcintf, srcssid, osname, osversion, devtype, srcmac, count(*) as subtotal
from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and (srcssid is
not null or dstssid is not null) and srcmac is not null group by srcintf, srcssid,
osname, osversion, devtype, srcmac order by subtotal desc)### t where srcssid is
not null group by srcssid order by totalnum desc

```

Dataset Name	Description	Log Category
wifi-Top-App-By-Bandwidth	Top WiFi applications by bandwidth usage	traffic

```

select
appid,
app,
sum(
  coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
) as bandwidth
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and (
  srcssid is not null
  or dstssid is not null
)
and nullifna(app) is not null
group by
appid,
app

```

```

having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-Client-By-Bandwidth	Top WiFi client by bandwidth usage	traffic

```

select
  (
    coalesce(srcname, srcmac, 'unknown') || ' (' || coalesce(devtype, 'unknown') || ', '
    || coalesce(osname, '') || (
      case when osversion is null then '' else ' ' || osversion end
    ) || ')'
  ) as client,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and (
    srcssid is not null
    or dstssid is not null
  )
group by
  client
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-OS-By-Bandwidth	Top WiFi os by bandwidth usage	traffic

```

select
  (
    coalesce(osname, 'unknown') || ' ' || coalesce(osversion, '')
  ) as os,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)

```

```

    and (
        srcssid is not null
        or dstssid is not null
    )
group by
    os
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-OS-By-WiFi-Client	Top WiFi os by WiFi client	traffic

```

select
    (
        coalesce(osname, 'unknown') || ' ' || coalesce(osversion, '')
    ) as os,
    count(distinct srcmac) as totalnum
from
    ###(select srcintf, srcssid, osname, osversion, devtype, srcmac, count(*) as subtotal
        from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and (srcssid is
        not null or dstssid is not null) and srcmac is not null group by srcintf, srcssid,
        osname, osversion, devtype, srcmac order by subtotal desc)### t group by os order
        by totalnum desc

```

Dataset Name	Description	Log Category
wifi-Top-Device-By-Bandwidth	Top WiFi device by bandwidth usage	traffic

```

select
    devtype,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and logid_to_int(logid) not in (4, 7, 14)
    and (
        srcssid is not null
        or dstssid is not null
    )
    and devtype is not null
group by
    devtype
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by

```

bandwidth desc

Dataset Name	Description	Log Category
wifi-Top-Device-By-Client	Top WiFi device by client	traffic

```
select
  devtype,
  count(distinct srcmac) as totalnum
from
  ###(select srcintf, srcssid, osname, osversion, devtype, srcmac, count(*) as subtotal
    from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and (srcssid is
      not null or dstssid is not null) and srcmac is not null group by srcintf, srcssid,
      osname, osversion, devtype, srcmac order by subtotal desc)### t where devtype is
    not null group by devtype order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Overall-Traffic	WiFi overall traffic	traffic

```
select
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and (
    srcssid is not null
    or dstssid is not null
  )
```

Dataset Name	Description	Log Category
wifi-Num-Distinct-Client	WiFi num distinct client	traffic

```
select
  count(distinct srcmac) as totalnum
from
  ###(select srcintf, srcssid, osname, osversion, devtype, srcmac, count(*) as subtotal
    from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and (srcssid is
      not null or dstssid is not null) and srcmac is not null group by srcintf, srcssid,
      osname, osversion, devtype, srcmac order by subtotal desc)### t
```

Dataset Name	Description	Log Category
Top30-Subnets-by-Bandwidth-and-Sessions	Top subnets by application bandwidth	traffic

```
select
  ip_subnet(`srcip`) as subnet,
```

```

sum(
  coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
) as bandwidth,
sum(
  coalesce(rcvbyte, 0)
) as traffic_in,
sum(
  coalesce(sentbyte, 0)
) as traffic_out,
count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  subnet
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Application-Bandwidth	Top applications by bandwidth	traffic

```

select
  ip_subnet(`srcip`) as subnet,
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
group by
  subnet,
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Application-Sessions	Top applications by sessions	traffic

```

select
  ip_subnet(`srcip`) as subnet,
  app_group_name(app) as app_group,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
group by
  subnet,
  app_group
order by
  sessions desc

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Website-Bandwidth	Top websites and web category by bandwidth	traffic

```

select
  subnet,
  website,
  sum(bandwidth) as bandwidth
from
  ###(select ip_subnet(`srcip`) as subnet, hostname as website, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and hostname is not null and logid_to_int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is null or logver<52) and (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by subnet, website order by bandwidth desc)### t group by subnet, website order by bandwidth desc

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Website-Hits	Top websites and web category by sessions	traffic

```

select
  subnet,
  website,
  sum(hits) as hits
from
  (
    ###(select ip_subnet(`srcip`) as subnet, hostname as website, count(*) as hits from $log-traffic where $filter and hostname is not null and logid_to_int(logid) not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') group by subnet, website order by hits desc)### union all ###(select ip_subnet(`srcip`) as subnet, hostname as website, count(*) as hits from $log-webfilter where $filter and hostname is not null and (eventtype is null or logver>=52) group by subnet, website order by hits desc)###) t group by subnet, website order by hits desc

```

Dataset Name	Description	Log Category
Top30-Subnets-with-Top10-User-by-Bandwidth	Top users by bandwidth	traffic

```

select
  ip_subnet(`srcip`) as subnet,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and srcip is not null
group by
  subnet,
  user_src
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top30-Subnets-with-Top10-User-by-Sessions	Top users by sessions	traffic

```

select
  ip_subnet(`srcip`) as subnet,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  subnet,
  user_src
order by
  sessions desc

```

Dataset Name	Description	Log Category
app-Top-20-Category-and-Applications-by-Bandwidth	Top category and applications by bandwidth usage	traffic

```

select
  appcat,
  app,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  appcat,
  app
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
app-Top-20-Category-and-Applications-by-Session	Top category and applications by session	traffic

```

select
  appcat,
  app,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  appcat,
  app
order by
  sessions desc

```

Dataset Name	Description	Log Category
app-Top-500-Allowed-Applications-by-Bandwidth	Top allowed applications by bandwidth usage	traffic

```

select

```

```

from_itime(itime) as timestamp,
coalesce(
  nullifna(`user`),
  nullifna(`unauthuser`),
  ipstr(`srcip`)
) as user_src,
appcat,
app,
coalesce(
  root_domain(hostname),
  ipstr(dstip)
) as destination,
sum(
  coalesce(`sentbyte`, 0)+ coalesce(`rcvdbyte`, 0)
) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and action in ('accept', 'close', 'timeout')
group by
  timestamp,
  user_src,
  appcat,
  app,
  destination
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
app-Top-500-Blocked-Applications-by-Session	Top blocked applications by session	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  appcat,
  app,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and action in (
    'deny', 'blocked', 'reset', 'dropped'
  )
group by
  user_src,
  appcat,
  app

```

```
order by
sessions desc
```

Dataset Name	Description	Log Category
web-Detailed-Website-Browsing-Log	Web detailed website browsing log	traffic

```
select
  from dtme(dtime) as timestamp,
  catdesc,
  hostname as website,
  status,
  sum(bandwidth) as bandwidth
from
  ###(select dtime, catdesc, hostname, cast(utmaction as text) as status, sum(coalesce
  (sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter
  and hostname is not null and logid_to_int(logid) not in (4, 7, 14) and (countweb>0
  or ((logver is null or logver<52) and (hostname is not null or utmevent in
  ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter'))))
  group by dtime, catdesc, hostname, utmaction order by dtime desc)### t group by
  dtime, catdesc, website, status order by dtime desc
```

Dataset Name	Description	Log Category
web-Hourly-Category-and-Website-Hits-Action	Web hourly category and website hits action	traffic

```
select
  hod,
  website,
  sum(hits) as hits
from
  (
  ###(select $hour_of_day as hod, (hostname || ' (' || coalesce(`catdesc`, 'Unknown')
  || ')') as website, count(*) as hits from $log-traffic where $filter and
  hostname is not null and logid_to_int(logid) not in (4, 7, 14) and utmevent in
  ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
  group by hod, website order by hod, hits desc)### union all ###(select $hour_of_
  day as hod, (hostname || ' (' || coalesce(`catdesc`, 'Unknown') || ')') as
  website , count(*) as hits from $log-webfilter where $filter and hostname is not
  null and (eventtype is null or logver>=52) group by hod, website order by hod,
  hits desc)###) t group by hod, website order by hod, hits desc
```

Dataset Name	Description	Log Category
web-Top-20-Category-and-Websites-by-Bandwidth	Web top category and websites by bandwidth usage	traffic

```
select
  website,
  catdesc,
  sum(bandwidth) as bandwidth
from
```

```
###(select hostname as website, catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and hostname is not null and logid_to_int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is null or logver<52) and (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by website, catdesc order by bandwidth desc)### t group by website, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
web-Top-20-Category-and-Websites-by-Session	Web top category and websites by session	traffic

```
select
  website,
  catdesc,
  sum(hits) as hits
from
  (
    ###(select hostname as website, catdesc, count(*) as hits from $log-traffic where $filter and hostname is not null and logid_to_int(logid) not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') group by website, catdesc order by hits desc)### union all ### (select hostname as website, catdesc, count(*) as hits from $log-webfilter where $filter and hostname is not null and (eventtype is null or logver>=52) group by website, catdesc order by hits desc)###) t group by website, catdesc order by hits desc
```

Dataset Name	Description	Log Category
web-Top-500-Website-Sessions-by-Bandwidth	Web top website sessions by bandwidth usage	traffic

```
select
  from_dtime(dtime) as timestamp,
  user_src,
  website,
  catdesc,
  cast(
    sum(dura)/ 60 as decimal(18, 2)
  ) as dura,
  sum(bandwidth) as bandwidth
from
  ###(select dtime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, hostname as website, catdesc, sum(coalesce(duration, 0)) as dura, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and hostname is not null and logid_to_int(logid) not in (4, 7, 14) and action in ('accept', 'close', 'timeout') group by dtime, user_src, website, catdesc having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc)### t group by dtime, user_src, website, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
web-Top-500-User-Visted-Websites-by-Bandwidth	Web top user visted websites by bandwidth usage	traffic

```
select
  website,
  catdesc,
  sum(bandwidth) as bandwidth
from
  ###(select hostname as website, catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and hostname is not null and logid_to_int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is null or logver<52) and (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by hostname, catdesc having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc)### t group by website, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
web-Top-500-User-Visted-Websites-by-Session	Web top user visted websites by session	traffic

```
select
  website,
  catdesc,
  sum(sessions) as sessions
from
  (
    ###(select hostname as website, catdesc, count(*) as sessions from $log-traffic where $filter and hostname is not null and logid_to_int(logid) not in (4, 7, 14) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter') group by hostname, catdesc order by sessions desc)### union all
    ###(select hostname as website, catdesc, count(*) as sessions from $log-webfilter where $filter and hostname is not null and (eventtype is null or logver>=52) group by hostname, catdesc order by sessions desc)###) t group by website, catdesc order by sessions desc
```

Dataset Name	Description	Log Category
fct-Installed-Feature-Summary	Installed Feature Summary	fct-event

```
select
  clientfeature,
  count(*) as totalnum
from
  $log
where
  $filter
  and clientfeature is not null
group by
  clientfeature
order by
  totalnum desc
```

Dataset Name	Description	Log Category
fct-Device-by-Operating-System	Device by OS	fct-event

```

select
  os,
  count(distinct hostname) as totalnum
from
  ###(select hostname, os, fctver from $log where $filter group by hostname, os,
  fctver)### t where os is not null group by os order by totalnum desc

```

Dataset Name	Description	Log Category
fct-Installed-FortiClient-Version	FortiClient Version	fct-event

```

select
  fctver as fctver_short,
  count(distinct hostname) as totalnum
from
  ###(select hostname, os, fctver from $log where $filter group by hostname, os,
  fctver)### t where fctver is not null group by fctver order by totalnum desc

```

Dataset Name	Description	Log Category
fct-Endpoint-Profile-Deployment	Endpoint Profile Deployment	fct-event

```

select
  profile,
  count(distinct hostname) as totalnum
from
  ###(select hostname, coalesce(nullifna(usingpolicy), 'No Profile') as profile from $log
  where $filter group by hostname, profile)### t group by profile order by totalnum
  desc

```

Dataset Name	Description	Log Category
fct-Client-Summary	Client Summary	fct-event

```

select
  hostname,
  deviceip,
  os,
  profile,
  hostuser,
  fctver
from
  ###(select hostname, deviceip, os, nullifna(usingpolicy) as profile, nullifna(`user`)
  as hostuser, fctver from $log where $filter and os is not null group by hostname,
  deviceip, os, profile, hostuser, fctver)### t group by hostname, deviceip, os,
  profile, hostuser, fctver

```

Dataset Name	Description	Log Category
fct-Total-Threats-Found	Total Threats Found	fct-traffic

```

select
  utmevent_s as utmevent,

```

```
count(distinct threat) as totalnum
from
###(select coalesce(nullifna(lower(utmevent)), 'unknown') as utmevent_s, threat from
$log where $filter and threat is not null and utmaction='blocked' group by
utmevent_s, threat)### t group by utmevent order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Top10-AV-Threats-Detected	Top AV Threats Detected	fct-traffic

```
select
threat,
sum(totalnum) as totalnum
from
(
###(select threat, count(*) as totalnum from $log where $filter and threat is not
null and lower(utmevent)='antivirus' group by threat order by totalnum desc)###
union all ###(select virus as threat, count(*) as totalnum from $log-fct-event
where $filter and virus is not null group by threat order by totalnum desc)###)
t group by threat order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Top10-Infected-Devices-with-Botnet	Top Infected Devices with Botnet	fct-traffic

```
select
hostname,
count(*) as totalnum
from
$log
where
$filter
and hostname is not null
and lower(utmevent) in ('webfilter', 'appfirewall')
and lower(threat) like '%botnet%'
group by
hostname
order by
totalnum desc
```

Dataset Name	Description	Log Category
fct-Top10-Infected-Devices-with-Virus-Malware	Top Infected Devices with Virus Malware	fct-traffic

```
select
hostname,
sum(totalnum) as totalnum
from
(
###(select hostname, count(*) as totalnum from $log where $filter and hostname is
not null and lower(utmevent) in ('antivirus', 'antimalware') group by hostname
order by totalnum desc)### union all ###(select hostname, count(*) as totalnum
```

```

from $log-fct-event where $filter and hostname is not null and virus is not null
group by hostname order by totalnum desc)###) t group by hostname order by
totalnum desc

```

Dataset Name	Description	Log Category
fct-All-Antivirus-Antimalware-Detections	All Antivirus and Antimalware Detections	fct-traffic

```

select
  threat,
  hostname,
  hostuser,
  utmaction
from
  (
    ###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser,
      utmaction from $log where $filter and lower(utmevent) in ('antivirus',
        'antimalware') group by threat, hostname, hostuser, utmaction order by
      threat)### union all ###(select virus as threat, hostname, coalesce(nullifna
        (`user`), 'Unknown') as hostuser, action as utmaction from $log-fct-event where
        $filter and virus is not null group by threat, hostname, hostuser, utmaction
        order by threat)###) t group by threat, hostname, hostuser, utmaction order by
      threat

```

Dataset Name	Description	Log Category
fct-Web-Filter-Violations	Web Filter Violations	fct-traffic

```

select
  remotename,
  hostname,
  coalesce(
    nullifna(`user`),
    'Unknown'
  ) as hostuser,
  utmaction,
  count(*) as totalnum
from
  $log
where
  $filter
  and lower(utmevent)= 'webfilter'
  and utmaction = 'blocked'
group by
  remotename,
  hostname,
  hostuser,
  utmaction
order by
  totalnum desc

```

Dataset Name	Description	Log Category
fct-Application-Firewall	Application Firewall	fct-traffic

```

select
  threat,
  hostname,
  hostuser,
  utmaction
from
  ###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser,
  utmaction from $log where $filter and lower(utmevent)='appfirewall' and
  utmaction='blocked' group by threat, hostname, hostuser, utmaction)### t1 left join
  app_mdata t2 on t1.threat=t2.name group by threat, risk, hostname, hostuser,
  utmaction order by risk desc
    
```

Dataset Name	Description	Log Category
fct-Errors-and-Alerts	Errors and Alerts	fct-event

```

select
  msg,
  hostname,
  coalesce(
    nullifna(`user`),
    'Unknown'
  ) as hostuser
from
  $log
where
  $filter
  and level in ('error', 'alert')
group by
  msg,
  hostname,
  hostuser
    
```

Dataset Name	Description	Log Category
fct-Threats-by-Top-Devices	Threats by Top Devices	fct-traffic

```

select
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and hostname is not null
  and utmevent is not null
  and utmaction = 'blocked'
group by
  hostname
    
```

```
order by
totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Device-Vulnerabilities	Vulnerabilities Detected by User/Device	fct-netscan

```
select
vulnseverity,
count(distinct vulnname) as totalnum
from
###(select vulnseverity, vulnname from $log where $filter and nullifna(vulnseverity) is
not null and nullifna(vulnname) is not null group by vulnseverity, vulnname)### t
group by vulnseverity order by totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Category-Type-Vulnerabilities	Vulnerabilities Detected by Category Type	fct-netscan

```
select
vulncat,
count(distinct vulnname) as totalnum
from
###(select vulncat, vulnname from $log where $filter and nullifna(vulncat) is not null
and nullifna(vulnname) is not null group by vulncat, vulnname)### t group by
vulncat order by totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerabilities-by-OS	Forticlient Vulnerabilities by OS	fct-netscan

```
select
os,
count(distinct vulnname) as totalnum
from
###(select os, vulnname from $log where $filter and nullifna(os) is not null and
nullifna(vulnname) is not null group by os, vulnname)### t group by os order by
totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerabilities-by-Risk-Level	Number Vulnerability by Device and Risk Level	fct-netscan

```
select
vulnseverity,
(
case when vulnseverity = 'Critical' then 5 when vulnseverity = 'High' then 4 when
vulnseverity = 'Medium' then 3 when vulnseverity = 'Low' then 2 when
vulnseverity = 'Info' then 1 else 0 end
) as severity_number,
count(distinct vulnname) as vuln_num,
```

```
count(distinct devid) as dev_num
from
###(select vulnseverity, devid, vulnname from $log where $filter and nullifna
(vulnseverity) is not null and nullifna(vulnname) is not null and nullifna(devid)
is not null group by vulnseverity, vulnname, devid)### t group by vulnseverity
order by dev_num desc, severity_number desc
```

Dataset Name	Description	Log Category
fct-vuln-Device-by-Risk-Level	Number Vulnerability by Device and Risk Level	fct-netscan

```
select
vulnseverity,
(
case when vulnseverity = 'Critical' then 5 when vulnseverity = 'High' then 4 when
vulnseverity = 'Medium' then 3 when vulnseverity = 'Low' then 2 when
vulnseverity = 'Info' then 1 else 0 end
) as severity_number,
count(distinct vulnname) as vuln_num,
count(distinct devid) as dev_num
from
###(select vulnseverity, devid, vulnname from $log where $filter and nullifna
(vulnseverity) is not null and nullifna(vulnname) is not null and nullifna(devid)
is not null group by vulnseverity, vulnname, devid)### t group by vulnseverity
order by dev_num desc, severity_number desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerability-Trend	Vulnerability Trend	fct-netscan

```
select
$flex_timescale(timestamp) as hodex,
count(distinct vulnname) as total_num
from
###(select $flex_timestamp as timestamp, vulnname from $log where $filter and nullifna
(vulnname) is not null group by timestamp, vulnname order by timestamp desc)### t
group by hodex order by hodex
```

Dataset Name	Description	Log Category
fct-vuln-Details-by-Risk-Level-Device	Vulnerability Details for Each Risk Level by Device	fct-netscan

```
select
hostname,
os,
vulnseverity,
count(distinct vulnname) as vuln_num,
count(distinct products) as products,
count(distinct cve_id) as cve_count
from
###(select hostname, os, vulnname, vulnseverity, vulnid from $log where $filter and
vulnname is not null and vulnseverity is not null and hostname is not null group by
hostname, os, vulnname, vulnseverity, vulnid)### t1 left join fct_mdata t2 on
```

```
t1.vulnid=t2.vid::int group by hostname, os, vulnseverity order by vuln_num desc,
hostname
```

Dataset Name	Description	Log Category
fct-vuln-Details-by-Device-User	Vulnerability Details by Device User	fct-netscan

```
select
  hostname,
  (
    ,
    ' || vulnname || '
    ,
    ) as vulnname,
    vulnseverity,
    vulncat,
    string_agg(distinct products, ',') as products,
    string_agg(distinct cve_id, ',') as cve_list,
    (
      'Remediation Info'
    ) as vendor_link
from
  ###(select hostname, vulnname, vulnseverity, vulncat, vulnid from $log where $filter
  and vulnname is not null and hostname is not null group by hostname, vulnname,
  vulnseverity, vulncat, vulnid)### t1 inner join fct_mdata t2 on
  t1.vulnid=t2.vid::int group by hostname, vulnname, vulnseverity, vulncat order by
  hostname
```

Dataset Name	Description	Log Category
fct-vuln-Remediation-by-Device	Remediate The Vulnerability Found on Device	fct-netscan

```
select
  hostname,
  (
    ,
    ' || vulnname || '
    ,
    ) as vulnname,
    vulnseverity,
    string_agg(distinct vendor_link, ',') as vendor_link
from
  ###(select hostname, vulnname, vulnseverity, vulnid from $log where $filter and
  vulnname is not null and hostname is not null group by hostname, vulnname,
  vulnseverity, vulnid)### t1 inner join fct_mdata t2 on t1.vulnid=t2.vid::int group
  by hostname, vulnname, vulnseverity order by vulnseverity, hostname
```

Dataset Name	Description	Log Category
fct-vuln-Remediation-by-Vulnerability	Remediation by Vulnerability	fct-netscan

```
select
```

```

        (
            ' || vulnname || '
                ' || 'Description
' || description || '

' || 'Affected Products
' || products || '

' || 'Impact
' || impact || '

' || 'Recommended Actions
' || vendor_link || '

,

        ) as remediation
from
    ###(select devid, vulnname, vulnseverity, (case vulnseverity when 'low' then 1 when
        'info' then 2 when 'medium' then 3 when 'high' then 4 when 'critical' then 5 else 0
        end) as severity_level, vulnid from $log where $filter and vulnname is not null
        group by devid, vulnname, vulnseverity, severity_level, vulnid order by severity_
        level)### t1 inner join fct_mdata t2 on t1.vulnid=t2.vid::int group by remediation
        order by remediation

```

Dataset Name	Description	Log Category
fct-vuln-Top-30-Targeted-High-Risk-Vulnerabilities	Top 30 Targeted High Risk Vulnerabilities	fct-netscan

```

select
    t3.cve_id,
    score,
    string_agg(distinct products, ',') as products,
    (
        'Mitigation Infomation'
    ) as vendor_link
from
    ###(select vulnid from $log where $filter group by vulnid)### t1 inner join fct_mdata
    t2 on t2.vid=t1.vulnid::text inner join fct_cve_score t3 on strpos(t2.cve_id,
    t3.cve_id) > 0 group by t3.cve_id, score order by score desc, t3.cve_id

```

Dataset Name	Description	Log Category
os-Detect-OS-Count	Detected operation system count	traffic

```

select
    (
        coalesce(osname, 'Unknown')
    )

```

```

    ) as os,
    count(*) as totalnum
from
    $log
where
    $filter
    and logid_to_int(logid) not in (4, 7, 14)
group by
    os
order by
    totalnum desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Sessions-Table	Drilldown top applications by session count	traffic

```

select
    appid,
    app,
    sum(sessions) as sessions
from
    ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
    (`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
    sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
    $filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
    user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
    $filter-drilldown and nullifna(app) is not null group by appid, app order by
    sessions desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Sessions-Bar	Drilldown top applications by session count	traffic

```

select
    appid,
    app,
    sum(sessions) as sessions
from
    ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
    (`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
    sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
    $filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
    user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
    $filter-drilldown and nullifna(app) is not null group by appid, app order by
    sessions desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Bandwidth-Table	Drilldown top applications by bandwidth usage	traffic

```

select
    appid,

```

```

app,
sum(bandwidth) as bandwidth
from
###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
$filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
$filter-drilldown and nullifna(app) is not null group by appid, app having sum
(bandwidth)>0 order by bandwidth desc
    
```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Bandwidth-Bar	Drilldown top applications by bandwidth usage	traffic

```

select
appid,
app,
sum(bandwidth) as bandwidth
from
###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
$filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
$filter-drilldown and nullifna(app) is not null group by appid, app having sum
(bandwidth)>0 order by bandwidth desc
    
```

Dataset Name	Description	Log Category
drilldown-Top-Destination-By-Sessions-Table	Drilldown top destination by session count	traffic

```

select
dstip,
sum(sessions) as sessions
from
###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
$filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
$filter-drilldown and dstip is not null group by dstip order by sessions desc
    
```

Dataset Name	Description	Log Category
drilldown-Top-Destination-By-Bandwidth-Table	Drilldown top destination by bandwidth usage	traffic

```

select
dstip,
sum(bandwidth) as bandwidth
from
    
```

```
###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
$filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
$filter-drilldown and dstip is not null group by dstip having sum(bandwidth)>0
order by bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Sessions-Table	Drilldown top user by session count	traffic

```
select
  user_src,
  sum(sessions) as sessions
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
  (`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
  sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
  $filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
  user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
  $filter-drilldown and user_src is not null group by user_src order by sessions desc
```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Sessions-Bar	Drilldown top user by session count	traffic

```
select
  user_src,
  sum(sessions) as sessions
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
  (`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
  sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
  $filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
  user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
  $filter-drilldown and user_src is not null group by user_src order by sessions desc
```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Bandwidth-Table	Drilldown top user by bandwidth usage	traffic

```
select
  user_src,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
  (`srcip`)) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
  sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
  $filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
  user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
  $filter-drilldown and user_src is not null group by user_src having sum
  (bandwidth)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Bandwidth-Bar	Drilldown top user by bandwidth usage	traffic

```
select
  user_src,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`)), ipstr(
    `srcip`) as user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions,
    sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
    $filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) group by appid, app,
    user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t where
    $filter-drilldown and user_src is not null group by user_src having sum
    (bandwidth)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-Web-User-By-Visit-Table	Drilldown top web user by visit	traffic

```
select
  user_src,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`)), ipstr(`srcip`)) as
    user_src, hostname, count(*) as requests from $log-traffic where $filter-
    exclude-var and logid_to_int(logid) not in (4, 7, 14) and utmevent in
    ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
    and hostname is not null group by user_src, hostname order by requests desc)###
    union all ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src,
    hostname, count(*) as requests from $log-webfilter where $filter-exclude-var and
    (eventtype is null or logver>=52) and hostname is not null group by user_src,
    hostname order by requests desc)###) t where $filter-drilldown and user_src is
    not null group by user_src order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Web-User-By-Visit-Bar	Drilldown top web user by visit	traffic

```
select
  user_src,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`)), ipstr(`srcip`)) as
    user_src, hostname, count(*) as requests from $log-traffic where $filter-
    exclude-var and logid_to_int(logid) not in (4, 7, 14) and utmevent in
    ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
    and hostname is not null group by user_src, hostname order by requests desc)###
```

```
union all ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src,
hostname, count(*) as requests from $log-webfilter where $filter-exclude-var and
(eventtype is null or logver>=52) and hostname is not null group by user_src,
hostname order by requests desc)###) t where $filter-drilldown and user_src is
not null group by user_src order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Website-By-Request-Table	Drilldown top website by request	traffic

```
select
  hostname,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
user_src, hostname, count(*) as requests from $log-traffic where $filter-
exclude-var and logid_to_int(logid) not in (4, 7, 14) and utmevent in
('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
and hostname is not null group by user_src, hostname order by requests desc)###
union all ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src,
hostname, count(*) as requests from $log-webfilter where $filter-exclude-var and
(eventtype is null or logver>=52) and hostname is not null group by user_src,
hostname order by requests desc)###) t where $filter-drilldown and hostname is
not null group by hostname order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Website-By-Request-Bar	Drilldown top website by request	traffic

```
select
  hostname,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
user_src, hostname, count(*) as requests from $log-traffic where $filter-
exclude-var and logid_to_int(logid) not in (4, 7, 14) and utmevent in
('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
and hostname is not null group by user_src, hostname order by requests desc)###
union all ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src,
hostname, count(*) as requests from $log-webfilter where $filter-exclude-var and
(eventtype is null or logver>=52) and hostname is not null group by user_src,
hostname order by requests desc)###) t where $filter-drilldown and hostname is
not null group by hostname order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Sender-By-Volume	Drilldown top email sender by volume	traffic

```
select
  sender,
```

```

sum(bandwidth) as volume
from
(
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte,
    0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-
    var and logid_to_int(logid) not in (4, 7, 14) and service in ('smtp', 'SMTP',
    '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in ('general-
    email-log', 'spamfilter') group by sender, recipient order by requests desc)###
    union all ###(select `from` as sender, `to` as recipient, count(*) as requests,
    sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-
    emailfilter where $filter-exclude-var and service in ('smtp', 'SMTP', '25/tcp',
    '587/tcp', 'smtps', 'SMTPS', '465/tcp') and eventtype is null group by `from`,
    `to` order by requests desc)###) t where $filter-drilldown and sender is not
    null group by sender having sum(bandwidth)>0 order by volume desc

```

Dataset Name	Description	Log Category
drilldown-Top-Email-Send-Recipient-By-Volume	Drilldown top email send recipient by volume	traffic

```

select
    recipient,
    sum(bandwidth) as volume
from
(
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte,
    0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-
    var and logid_to_int(logid) not in (4, 7, 14) and service in ('smtp', 'SMTP',
    '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in ('general-
    email-log', 'spamfilter') group by sender, recipient order by requests desc)###
    union all ###(select `from` as sender, `to` as recipient, count(*) as requests,
    sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-
    emailfilter where $filter-exclude-var and service in ('smtp', 'SMTP', '25/tcp',
    '587/tcp', 'smtps', 'SMTPS', '465/tcp') and eventtype is null group by `from`,
    `to` order by requests desc)###) t where $filter-drilldown and recipient is not
    null group by recipient having sum(bandwidth)>0 order by volume desc

```

Dataset Name	Description	Log Category
drilldown-Top-Email-Sender-By-Count	Drilldown top email sender by count	traffic

```

select
    sender,
    sum(requests) as requests
from
(
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte,
    0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-
    var and logid_to_int(logid) not in (4, 7, 14) and service in ('smtp', 'SMTP',
    '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in ('general-
    email-log', 'spamfilter') group by sender, recipient order by requests desc)###
    union all ###(select `from` as sender, `to` as recipient, count(*) as requests,
    sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-
    emailfilter where $filter-exclude-var and service in ('smtp', 'SMTP', '25/tcp',
    '587/tcp', 'smtps', 'SMTPS', '465/tcp') and eventtype is null group by `from`,

```

```
`to` order by requests desc)###) t where $filter-drilldown and sender is not null group by sender order by requests desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Send-Recipient-By-Count	Drilldown top email send recipient by count	traffic

```
select
  recipient,
  sum(requests) as requests
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in ('general-email-log', 'spamfilter') group by sender, recipient order by requests desc)###
    union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and eventtype is null group by `from`, `to` order by requests desc)###) t where $filter-drilldown and recipient is not null group by recipient order by requests desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Recipient-By-Volume	Drilldown top email receiver by volume	traffic

```
select
  recipient,
  sum(bandwidth) as volume
from
  (
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and logid_to_int(logid) not in (4, 7, 14) and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by recipient, sender order by requests desc)### union all ###(select `to` as recipient, `from` as sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-var and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and eventtype is null group by `to`, `from` order by requests desc)###) t where $filter-drilldown and recipient is not null group by recipient having sum(bandwidth)>0 order by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Receive-Sender-By-Volume	Drilldown top email receive sender by volume	traffic

```
select
```

```

sender,
sum(bandwidth) as volume
from
(
###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and
logid_to_int(logid) not in (4, 7, 14) and service in ('pop3', 'POP3', '110/tcp',
'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S',
'995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by
recipient, sender order by requests desc)### union all ###(select `to` as
recipient, `from` as sender, count(*) as requests, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-
exclude-var and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP',
'143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and
eventtype is null group by `to`, `from` order by requests desc)###) t where
$filter-drilldown and sender is not null group by sender having sum(bandwidth)>0
order by volume desc

```

Dataset Name	Description	Log Category
drilldown-Top-Email-Recipient-By-Count	Drilldown top email receiver by count	traffic

```

select
recipient,
sum(requests) as requests
from
(
###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and
logid_to_int(logid) not in (4, 7, 14) and service in ('pop3', 'POP3', '110/tcp',
'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S',
'995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by
recipient, sender order by requests desc)### union all ###(select `to` as
recipient, `from` as sender, count(*) as requests, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-
exclude-var and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP',
'143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and
eventtype is null group by `to`, `from` order by requests desc)###) t where
$filter-drilldown and recipient is not null group by recipient order by requests
desc

```

Dataset Name	Description	Log Category
drilldown-Top-Email-Receive-Sender-By-Count	Drilldown top email receive sender by count	traffic

```

select
sender,
sum(requests) as requests
from
(
###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and
logid_to_int(logid) not in (4, 7, 14) and service in ('pop3', 'POP3', '110/tcp',
'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S',

```

```
'995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by
recipient, sender order by requests desc)### union all ###(select `to` as
recipient, `from` as sender, count(*) as requests, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-
exclude-var and service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP',
'143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and
eventtype is null group by `to`, `from` order by requests desc)###) t where
$filter-drilldown and sender is not null group by sender order by requests desc
```

Dataset Name	Description	Log Category
drilldown-Top-Attack-Destination	Drilldown top attack dest	attack

```
select
  dstip,
  sum(totalnum) as totalnum
from
  ###(select srcip, dstip, count(*) as totalnum from $log where $filter-exclude-var group
  by srcip, dstip order by totalnum desc)### t where $filter-drilldown and dstip is
  not null group by dstip order by totalnum desc
```

Dataset Name	Description	Log Category
drilldown-Top-Attack-Source	Drilldown top attack source	attack

```
select
  srcip,
  sum(totalnum) as totalnum
from
  ###(select srcip, dstip, count(*) as totalnum from $log where $filter-exclude-var group
  by srcip, dstip order by totalnum desc)### t where $filter-drilldown and srcip is
  not null group by srcip order by totalnum desc
```

Dataset Name	Description	Log Category
drilldown-Top-Attack-List	Drilldown top attack list	attack

```
select
  from_itime(itime) as timestamp,
  attack,
  srcip,
  dstip
from
  ###(select itime, attack, srcip, dstip from $log where $filter-exclude-var order by
  itime desc)### t where $filter-drilldown order by timestamp desc
```

Dataset Name	Description	Log Category
drilldown-Top-Virus	UTM top virus	virus

```
select
  virus,
  max(virusid) as virusid,
```

```
(
  case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then
    'Adware' else 'Virus' end
) as malware_type,
sum(totalnum) as totalnum
from
(
  ###(select virus, 0 as virusid, count(*) as totalnum from $log-traffic where $filter
  and logid_to_int(logid) not in (4, 7, 14) and utmevent is not null and virus is
  not null group by virus, virusid order by totalnum desc)### union all ###(select
  virus, virusid, count(*) as totalnum from $log-virus where $filter and
  (eventtype is null or logver>=52) and nullifna(virus) is not null group by
  virus, virusid order by totalnum desc)###) t group by virus, malware_type order
  by totalnum desc
```

Dataset Name	Description	Log Category
drilldown-Virus-Detail	Drilldown virus detail	traffic

```
select
  from_itime(itime) as timestamp,
  virus,
  user_src,
  dstip,
  hostname,
  recipient
from
(
  ###(select itime, virus, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
  (`srcip`)) as user_src, dstip, hostname, recipient from $log-traffic where
  $filter and logid_to_int(logid) not in (4, 7, 14) and utmevent is not null and
  virus is not null order by itime desc)### union all ###(select itime, virus,
  coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, dstip, cast(' ' as char)
  as hostname, cast(' ' as char) as recipient from $log-virus where $filter and
  (eventtype is null or logver>=52) and nullifna(virus) is not null order by itime
  desc)###) t where $filter-drilldown order by timestamp desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Blocked-Web-Sites-By-Requests	User drilldown top blocked web sites by requests	webfilter

```
select
  hostname,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, action,
  count(*) as requests from $log where $filter and hostname is not null group by
  user_src, hostname, action order by requests desc)### t where $filter-drilldown and
  action='blocked' group by hostname order by requests desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Allowed-Web-Sites-By-Requests	User drilldown top allowed web sites by requests	webfilter

```
select
  hostname,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, action,
  count(*) as requests from $log where $filter and hostname is not null group by
  user_src, hostname, action order by requests desc)### t where $filter-drilldown and
  action!='blocked' group by hostname order by requests desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Blocked-Web-Categories	User drilldown top blocked web categories	webfilter

```
select
  catdesc,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, catdesc, action,
  count(*) as requests from $log where $filter and catdesc is not null group by user_
  src, catdesc, action order by requests desc)### t where $filter-drilldown and
  action='blocked' group by catdesc order by requests desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Allowed-Web-Categories	User drilldown top allowed web categories	webfilter

```
select
  catdesc,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, catdesc, action,
  count(*) as requests from $log where $filter and catdesc is not null group by user_
  src, catdesc, action order by requests desc)### t where $filter-drilldown and
  action!='blocked' group by catdesc order by requests desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Attacks	User drilldown top attacks by name	attack

```
select
  attack,
  sum(attack_count) as attack_count
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, attack, (case when
  severity in ('critical', 'high') then 1 else 0 end) as high_severity, count(*) as
```

```

attack_count from $log where $filter and nullifna(attack) is not null group by
user_src, attack, high_severity order by attack_count desc)### t where $filter-
drilldown group by attack order by attack_count desc
    
```

Dataset Name	Description	Log Category
user-drilldown-Top-Attacks-High-Severity	User drilldown top attacks high severity	attack

```

select
  attack,
  sum(attack_count) as attack_count
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, attack, (case when
  severity in ('critical', 'high') then 1 else 0 end) as high_severity, count(*) as
  attack_count from $log where $filter and nullifna(attack) is not null group by
  user_src, attack, high_severity order by attack_count desc)### t where $filter-
  drilldown and high_severity=1 group by attack order by attack_count desc
    
```

Dataset Name	Description	Log Category
user-drilldown-Top-Virus-By-Name	User drilldown top virus	virus

```

select
  virus,
  max(virusid) as virusid,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, virusid,
  count(*) as totalnum from $log where $filter and nullifna(virus) is not null group
  by user_src, virus, virusid order by totalnum desc)### t where $filter-drilldown
  group by virus order by totalnum desc
    
```

Dataset Name	Description	Log Category
user-drilldown-Top-Virus-Receivers-Over-Email	User drilldown top virus receivers over email	virus

```

select
  receiver,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, `to` as receiver,
  count(*) as totalnum from $log where $filter and subtype='infected' and (service in
  ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') or service in
  ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp',
  'pop3s', 'POP3S', '995/tcp')) and nullifna(virus) is not null group by user_src,
  receiver order by totalnum desc)### t where $filter-drilldown group by receiver
  order by totalnum desc
    
```

Dataset Name	Description	Log Category
user-drilldown-Count-Spam-Activity-by-Hour-of-Day	User drilldown count spam activity by hour of day	emailfilter

```
select
  hourstamp,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, $hour_of_day as
  hourstamp, count(*) as totalnum from $log where $filter and `to` is not null and
  action in ('detected', 'blocked') group by user_src, hourstamp order by
  hourstamp)### t where $filter-drilldown group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
user-drilldown-Top-Spam-Sources	User drilldown top spam sources	emailfilter

```
select
  mf_sender,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, `from` as mf_sender,
  count(*) as totalnum from $log where $filter and `from` is not null and action in
  ('detected', 'blocked') group by user_src, mf_sender order by totalnum desc)### t
  where $filter-drilldown group by mf_sender order by totalnum desc
```

Dataset Name	Description	Log Category
event-Usage-CPU	Event usage CPU	event

```
select
  hourstamp,
  cast(
    sum(cpu_usage)/ sum(num) as decimal(6, 2)
  ) as cpu_avg_usage
from
  ###(select $hour_of_day as hourstamp, sum(cpu) as cpu_usage, count(*) as num from $log
  where $filter and subtype='system' and action='perf-stats' group by hourstamp)### t
  group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
event-Usage-Memory	Event usage memory	event

```
select
  hourstamp,
  cast(
    sum(mem_usage)/ sum(num) as decimal(6, 2)
  ) as mem_avg_usage
from
```

```
###(select $hour_of_day as hourstamp, sum(mem) as mem_usage, count(*) as num from $log
where $filter and subtype='system' and action='perf-stats' group by hourstamp)### t
group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
event-Usage-Sessions	Event usage sessions	event

```
select
hourstamp,
cast(
sum(sess_usage)/ sum(num) as decimal(10, 2)
) as sess_avg_usage
from
###(select $hour_of_day as hourstamp, sum(totalsession) as sess_usage, count(*) as num
from $log where $filter and subtype='system' and action='perf-stats' group by
hourstamp)### t group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
event-Usage-CPU-Sessions	Event usage CPU sessions	event

```
select
hourstamp,
cast(
sum(sess_usage)/ sum(num) as decimal(10, 2)
) as sess_avg_usage,
cast(
sum(cpu_usage)/ sum(num) as decimal(6, 2)
) as cpu_avg_usage
from
###(select $hour_of_day as hourstamp, sum(cpu) as cpu_usage, sum(totalsession) as sess_
usage, count(*) as num from $log where $filter and subtype='system' and
action='perf-stats' group by hourstamp)### t group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
App-Risk-Top-Users-By-Bandwidth	Top users by bandwidth usage	traffic

```
select
coalesce(
nullifna(`user`),
nullifna(`unauthuser`),
ipstr(`srcip`)
) as user_src,
srcip,
sum(
coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
) as bandwidth,
sum(
coalesce(rcvdbyte, 0)
) as traffic_in,
sum(
coalesce(sentbyte, 0)
```

```

    ) as traffic_out
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and srcip is not null
group by
  user_src,
  srcip
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
App-Risk-Top-User-Source-By-Sessions	Application risk top user source by session count	traffic

```

select
  srcip,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and srcip is not null
group by
  srcip,
  user_src
order by
  sessions desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Users-By-Reputation-Scores-Bar	Application risk reputation top users by scores	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(crscore % 65536) as scores
from

```

```

$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and crscore is not null
group by
user_src
having
sum(crscore % 65536) > 0
order by
scores desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Devices-By-Reputation-Scores	Application risk reputation top devices by scores	traffic

```

select
devtype,
coalesce(
nullifna(`srcname`),
nullifna(`srcmac`),
ipstr(`srcip`)
) as dev_src,
sum(crscore % 65536) as scores
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and crscore is not null
group by
devtype,
dev_src
having
sum(crscore % 65536) > 0
order by
scores desc

```

Dataset Name	Description	Log Category
App-Risk-Application-Usage-By-Category-With-Pie	Application risk application usage by category	traffic

```

select
appcat,
sum(
coalesce(sentbyte, 0) + coalesce(rcvdbyte, 0)
) as bandwidth
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and nullifna(appcat) is not null

```

```
group by
  appcat
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
App-Risk-App-Usage-by-Category	Application risk application usage by category	traffic

```
select
  appcat,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(appcat) is not null
group by
  appcat
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
Top-20-Categories-By-Bandwidth	Webfilter categories by bandwidth usage	webfilter

```
select
  catdesc,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from
  $log-traffic where $filter and logid_to_int(logid) not in (4, 7, 14) and
  (countweb>0 or ((logver is null or logver<52) and (hostname is not null or utmevent
  in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter'))))
  and catdesc is not null group by catdesc order by bandwidth desc)### t group by
  catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
App-Risk-Key-Applications-Crossing-The-Network	Application risk application activity	traffic

```
select
  app_group_name(app) as app_group,
  appcat,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  count(*) as num_session
from
  $log
```

```

where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
group by
  app_group,
  appcat
order by
  bandwidth desc
    
```

Dataset Name	Description	Log Category
App-Risk-Applications-Running-Over-HTTP	Application risk applications running over HTTP	traffic

```

select
  app_group_name(app) as app_group,
  service,
  count(*) as sessions,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and service in (
    '80/tcp', '443/tcp', 'HTTP', 'HTTPS',
    'http', 'https'
  )
group by
  app_group,
  service
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  )> 0
order by
  bandwidth desc
    
```

Dataset Name	Description	Log Category
App-Risk-Top-Web-Sites-Visited-By-Network-Users-Pie-Cha	Application risk web browsing summary category	traffic

```

select
  catdesc,
  sum(num_sess) as num_sess,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, count(*) as num_sess, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth from $log-traffic where $filter and logid_to_int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is null or logver<52) and (hostname is not null
    
```

```

or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block',
'script-filter')))) and catdesc is not null group by catdesc order by num_sess
desc)### t group by catdesc order by num_sess desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Web-Sites-Visited-By-Network-Users	Application risk web browsing summary category	traffic

```

select
  catdesc,
  sum(num_sess) as num_sess,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, count(*) as num_sess, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte,
  0)) as bandwidth from $log-traffic where $filter and logid_to_int(logid) not in (4,
  7, 14) and (countweb>0 or ((logver is null or logver<52) and (hostname is not null
  or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block',
  'script-filter')))) and catdesc is not null group by catdesc order by num_sess
  desc)### t group by catdesc order by num_sess desc

```

Dataset Name	Description	Log Category
App-Risk-Web-Browsing-Hostname-Category	Application risk web browsing activity hostname category	traffic

```

select
  domain,
  catdesc,
  sum(visits) as visits
from
  (
    ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, catdesc, count(*)
    as visits from $log-traffic where $filter and logid_to_int(logid) not in (4, 7,
    14) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block',
    'script-filter') and catdesc is not null group by domain, catdesc order by
    visits desc)### union all ###(select coalesce(nullifna(hostname), ipstr
    (`dstip`)) as domain, catdesc, count(*) as visits from $log-webfilter where
    $filter and (eventtype is null or logver>=52) and catdesc is not null group by
    domain, catdesc order by visits desc)###) t group by domain, catdesc order by
    visits desc

```

Dataset Name	Description	Log Category
Top-Destination-Countries-By-Browsing-Time	Traffic top destination countries by browsing time	traffic

```

select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,

```

```

sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in,
sum(traffic_out) as traffic_out
from
###(select dstcountry, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
(select dstcountry, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte, 0)) as
traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and
logid_to_int(logid) not in (4, 7, 14) and $browse_time is not null group by
dstcountry) t group by dstcountry order by ebtr_value(ebtr_agg_flat(browsetime),
null, null) desc)### t group by dstcountry order by browsetime desc

```

Dataset Name	Description	Log Category
Top-Destination-Countries-By-Browsing-Time-Enhanced	Traffic top destination countries by browsing time enhanced	traffic

```

select
dstcountry,
ebtr_value(
ebtr_agg_flat(browsetime),
null,
$timespan
) as browsetime,
sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in,
sum(traffic_out) as traffic_out
from
###(select dstcountry, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
(select dstcountry, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
(sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte, 0)) as
traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and
logid_to_int(logid) not in (4, 7, 14) and $browse_time is not null group by
dstcountry) t group by dstcountry order by ebtr_value(ebtr_agg_flat(browsetime),
null, null) desc)### t group by dstcountry order by browsetime desc

```

Dataset Name	Description	Log Category
App-Risk-Traffic-Top-Hostnames-By-Browsing-Time	Traffic top domains by browsing time	traffic

```

select
hostname,
ebtr_value(
ebtr_agg_flat(browsetime),
null,
$timespan
) as browsetime,
sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in,
sum(traffic_out) as traffic_out
from

```

```
###(select hostname, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
(select hostname, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in,
sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and logid_to_int
(logid) not in (4, 7, 14) and hostname is not null and $browse_time is not null
group by hostname) t group by hostname order by ebtr_value(ebtr_agg_flat
(browsetime), null, null) desc)### t group by hostname order by browsetime desc
```

Dataset Name	Description	Log Category
App-Risk-Traffic-Top-Hostnames-By-Browsing-Time-Enhanced	Traffic top domains by browsing time enhanced	traffic

```
select
hostname,
ebtr_value(
ebtr_agg_flat(browsetime),
null,
$timespan
) as browsetime,
sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in,
sum(traffic_out) as traffic_out
from
###(select hostname, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as
bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
(select hostname, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in,
sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and logid_to_int
(logid) not in (4, 7, 14) and hostname is not null and $browse_time is not null
group by hostname) t group by hostname order by ebtr_value(ebtr_agg_flat
(browsetime), null, null) desc)### t group by hostname order by browsetime desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Threat-Vectors-Crossing-The-Network	Application risk top threat vectors	attack

```
select
severity,
count(*) as totalnum
from
$log
where
$filter
group by
severity
order by
totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Critical-Threat-Vectors-Crossing-The-Network	Application risk top critical threat vectors	attack

```

select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity = 'critical'
  and nullifna(attack) is not null
group by
  attack,
  severity,
  ref
order by
  totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-High-Threat-Vectors-Crossing-The-Network	Application risk top high threat vectors	attack

```

select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity = 'high'
  and nullifna(attack) is not null
group by
  attack,
  severity,
  ref
order by
  totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Medium-Threat-Vectors-Crossing-The-Network	Application risk top medium threat vectors	attack

```

select

```

```

    attack,
    severity,
    ref,
    count(*) as totalnum
from
    $log
where
    $filter
    and severity = 'medium'
    and nullifna(attack) is not null
group by
    attack,
    severity,
    ref
order by
    totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Low-Threat-Vectors-Crossing-The-Network	Application risk top low threat vectors	attack

```

select
    attack,
    severity,
    ref,
    count(*) as totalnum
from
    $log
where
    $filter
    and severity = 'low'
    and nullifna(attack) is not null
group by
    attack,
    severity,
    ref
order by
    totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Info-Threat-Vectors-Crossing-The-Network	Application risk top info threat vectors	attack

```

select
    attack,
    severity,
    ref,
    count(*) as totalnum
from
    $log
where
    $filter
    and severity = 'info'

```

```

    and nullifna(attack) is not null
group by
    attack,
    severity,
    ref
order by
    totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Virus-By-Name	UTM top virus	virus

```

select
    virus,
    max(virusid) as virusid,
    (
        case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then
            'Adware' else 'Virus' end
    ) as malware_type,
    sum(totalnum) as totalnum
from
    (
        ###(select virus, 0 as virusid, count(*) as totalnum from $log-traffic where $filter
            and logid_to_int(logid) not in (4, 7, 14) and utmevent is not null and virus is
            not null group by virus, virusid order by totalnum desc)### union all ###(select
            virus, virusid, count(*) as totalnum from $log-virus where $filter and
            (eventtype is null or logver>=52) and nullifna(virus) is not null group by
            virus, virusid order by totalnum desc)###) t group by virus, malware_type order
            by totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Virus-Victim	UTM top virus user	traffic

```

select
    user_src,
    sum(totalnum) as totalnum
from
    (
        ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
            user_src, count(*) as totalnum from $log-traffic where $filter and logid_to_int
            (logid) not in (4, 7, 14) and utmevent is not null and virus is not null group
            by user_src order by totalnum desc)### union all ###(select coalesce(nullifna
            (`user`), ipstr(`srcip`)) as user_src, count(*) as totalnum from $log-virus
            where $filter and (eventtype is null or logver>=52) and nullifna(virus) is not
            null group by user_src order by totalnum desc)###) t group by user_src order by
            totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Data-Loss-Prevention-Type-Events	Application risk DLP UTM event	traffic

```

select

```

```

utmsubtype,
sum(number) as number
from
(
  ###(select utmsubtype, count(*) as number from $log-traffic where $filter and logid_
to_int(logid) not in (4, 7, 14) and utmevent='dlp' and utmsubtype is not null
group by utmsubtype order by number desc)### union all ###(select subtype::text
as utmsubtype, count(*) as number from $log-dlp where $filter and subtype is not
null group by subtype order by number desc)###) t group by utmsubtype order by
number desc

```

Dataset Name	Description	Log Category
App-Risk-Vulnerability-Discovered	Application risk vulnerability discovered	netscan

```

select
vuln,
vulnref as ref,
vulncat,
severity,
count(*) as totalnum
from
$log
where
$filter
and vuln is not null
group by
vuln,
vulnref,
vulncat,
severity
order by
totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Malware-Discovered	Application risk virus discovered	traffic

```

select
dom,
sum(totalnum) as totalnum
from
(
  ###(select $DAY_OF_MONTH as dom, count(*) as totalnum from $log-traffic where
$filter and logid_to_int(logid) not in (4, 7, 14) and utmevent is not null and
virus is not null_group by dom order by totalnum desc)### union all ###(select
$DAY_OF_MONTH as dom, count(*) as totalnum from $log-virus where $filter and
nullifna(virus) is not null and (eventtype is null or logver>=52) group by dom
order by totalnum desc)###) t group by dom order by totalnum desc

```

Dataset Name	Description	Log Category
App-Risk-Breakdown-Of-Risk-Applications	Application risk breakdown of risk applications	traffic

```
select
  unnest(
    string_to_array(behavior, ',')
  ) as d_behavior,
  count(*) as number
from
  $log t1
  inner join app_mdata t2 on t1.appid = t2.id
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  d_behavior
order by
  number desc
```

Dataset Name	Description	Log Category
App-Risk-Number-Of-Applications-By-Risk-Behavior	Application risk number of applications by risk behavior	traffic

```
select
  risk as d_risk,
  unnest(
    string_to_array(behavior, ',')
  ) as f_behavior,
  count(*) as number
from
  $log t1
  inner join app_mdata t2 on t1.appid = t2.id
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
group by
  risk,
  f_behavior
order by
  risk desc,
  number desc
```

Dataset Name	Description	Log Category
App-Risk-High-Risk-Application	Application risk high risk application	traffic

```
select
  risk as d_risk,
  behavior as d_behavior,
  t2.id,
  t2.name,
  t2.app_cat,
  t2.technology,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  count(*) as sessions
```

```

from
  $log t1
  inner join app_mdata t2 on t1.appid = t2.id
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and behavior is not null
group by
  t2.id
order by
  risk desc,
  sessions desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Severe-High-Risk-Application	Severe and high risk applications	traffic

```

select
  appcat,
  count(distinct app) as total_num
from
  ###(select appcat, app from $log where $filter and app is not null and appcat is not
  null and logid_to_int(logid) not in (4, 7, 14) and apprisk in ('critical', 'high')
  group by appcat, app)### t group by appcat order by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Threats-Prevention	Threat Prevention	app-ctrl

```

select
  threat_name,
  count(distinct threats) as total_num
from
  (
    ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name, app as threats
    from $log-app-ctrl where $filter and lower(appcat)='botnet' group by app)###
    union all ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name,
    virus as threats from $log-virus where $filter and nullifna(virus) is not null
    group by virus)### union all ###(select cast('Malicious & Phishing Sites' as
    char(32)) as threat_name, hostname as threats from $log-webfilter where $filter
    and cat in (26, 61) group by hostname)### union all ###(select cast('Critical &
    High Intrusion Attacks' as char(32)) as threat_name, attack as total_num from
    $log-attack where $filter and severity in ('critical', 'high') group by
    attack)###) t group by threat_name order by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Application-Vulnerability	Application vulnerabilities discovered	attack

```

select
  attack,
  attackid,

```

```

vuln_type,
cve,
severity_number,
count(distinct dstip) as victims,
count(distinct srcip) as sources,
sum(totalnum) as totalnum
from
###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then
5 when t1.severity='high' then 4 when t1.severity='medium' then 3 when
t1.severity='low' then 2 when t1.severity='info' then 1 else 0 end) as severity_
number, dstip, srcip, count(*) as totalnum from $log t1 left join ips_mdata t2 on
t1.attack=t2.name where $filter and nullifna(attack) is not null and t1.severity is
not null group by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip
)### t group by attack, attackid, vuln_type, severity_number, cve order by
severity_number desc, totalnum desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Breakdown-Of-High-Risk-Application	Severe and high risk applications	traffic

```

select
appcat,
count(distinct app) as total_num
from
###(select appcat, app from $log where $filter and app is not null and appcat is not
null and logid_to_int(logid) not in (4, 7, 14) and apprisk in ('critical', 'high')
group by appcat, app)### t group by appcat order by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-20-High-Risk-Application	Application risk high risk application	traffic

```

select
d_risk,
count(distinct f_user) as users,
id,
name,
app_cat,
technology,
sum(bandwidth) as bandwidth,
sum(sessions) as sessions
from
###(select risk as d_risk, coalesce(nullifna(t1.`user`), nullifna(t1.`unauthuser`),
ipstr(t1.`srcip`)) as f_user, t2.id , t2.name, t2.app_cat, t2.technology, sum
(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as sessions
from $log t1 inner join app_mdata t2 on t1.appid=t2.id where $filter and risk>='4'
and logid_to_int(logid) not in (4, 7, 14) group by f_user, t2.id , t2.name, t2.app_
cat, t2.technology, risk)### t group by id, d_risk, name, app_cat, technology order
by d_risk desc, sessions desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-High-Risk-Application-Behavioral	Application Behavioral Characteristics	traffic

```

select
  behavior,
  round(
    sum(total_num)* 100 / sum(
      sum(total_num)
    ) over (),
    2
  ) as percentage
from
  ###(select (case when lower(appcat)='botnet' then 'malicious' when lower
    (appcat)='remote.access' then 'tunneling' when lower(appcat) in ('storage.backup',
    'video/audio') then 'bandwidth-consuming' when lower(appcat)='p2p' then 'peer-to-
    peer' when lower(appcat)='proxy' then 'proxy' end) as behavior, count(*) as total_
    num from $log where $filter and lower(appcat) in ('botnet', 'remote.access',
    'storage.backup', 'video/audio', 'p2p', 'proxy') and logid_to_int(logid) not in (4,
    7, 14) and apprisk in ('critical', 'high') group by appcat)### t group by behavior
    order by percentage desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Key-Application-Crossing-The-Network	Key Application Crossing The Network	traffic

```

select
  d_risk,
  count(distinct f_user) as users,
  id,
  name,
  app_cat,
  technology,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###(select risk as d_risk, coalesce(nullifna(t1.`user`), nullifna(t1.`unauthuser`),
    ipstr(t1.`srcip`)) as f_user, t2.id, t2.name, t2.app_cat, t2.technology, sum
    (coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as sessions
    from $log t1 inner join app_mdata t2 on t1.appid=t2.id where $filter and logid_to_
    int(logid) not in (4, 7, 14) group by f_user, t2.id, t2.name, t2.app_cat,
    t2.technology, risk)### t group by id, name, app_cat, technology, d_risk order by
    bandwidth desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Risk-Application-Usage-By-Category-With-Pie	Application risk application usage by category	traffic

```

select
  appcat,

```

```

sum(
  coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
) as bandwidth
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and nullifna(appcat) is not null
group by
appcat
order by
bandwidth desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Category-Breakdown-By-Bandwidth	Category breakdown of all applications, sorted by bandwidth	traffic

```

select
  appcat,
  count(distinct app) as app_num,
  count(distinct f_user) as user_num,
  sum(bandwidth) as bandwidth,
  sum(num_session) as num_session
from
###(select appcat, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as f_user, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as
bandwidth, count(*) as num_session from $log where $filter and logid_to_int(logid)
not in (4, 7, 14) and nullifna(appcat) is not null group by appcat, app, f_user)###
t group by appcat order by bandwidth desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-Web-Applications-by-Bandwidth	Top 25 Web Categories by Bandwidth	traffic

```

select
  d_risk,
  id,
  name,
  technology,
  count(distinct f_user) as user_num,
  sum(bandwidth) as bandwidth,
  sum(num_session) as num_session
from
###(select risk as d_risk, t2.id, t2.name, t2.technology, coalesce(nullifna(t1.`user`),
nullifna(t1.`unauthuser`), ipstr(t1.`srcip`)) as f_user, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as num_session from $log t1 inner
join app_mdata t2 on t1.appid=t2.id where $filter and logid_to_int(logid) not in
(4, 7, 14) and nullifna(app) is not null and service in ('80/tcp', '443/tcp',
'HTTP', 'HTTPS', 'http', 'https') group by risk, t2.id, t2.name, t2.technology, f_
user)### t group by d_risk, id, name, technology order by bandwidth desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```
select
  catdesc,
  count(distinct f_user) as user_num,
  sum(sessions) as sessions,
  sum.bandwidth) as bandwidth
from
  ###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
  as f_user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))
  as bandwidth from $log-traffic where $filter and catdesc is not null and logid_to_
  int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is null or logver<52) and
  (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content',
  'command-block', 'script-filter')))) group by f_user, catdesc order by sessions
  desc)### t group by catdesc order by sessions desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Common-Virus-Botnet-Spyware	Common virus disvocered, the botnet communications and the spyware/adware	traffic

```
select
  virus_s as virus,
  (
    case when lower(appcat)= 'botnet' then 'Botnet C&C' else (
      case when virus_s like 'Riskware%' then 'Spyware' when virus_s like 'Adware%'
        then 'Adware' else 'Virus' end
    ) end
  ) as malware_type,
  appid,
  app,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  (
    ###(select app as virus_s, appcat, appid, app, dstip, srcip, count(*) as total_num
    from $log-traffic where $filter and logid_to_int(logid) not in (4, 7, 14) and
    lower(appcat)='botnet' group by virus_s, appcat, appid, dstip, srcip, app order
    by total_num desc)### union all ###(select unnest(string_to_array(virus, ','))
    as virus_s, appcat, appid, app, dstip, srcip, count(*) as total_num from $log-
    traffic where $filter and logid_to_int(logid) not in (4, 7, 14) and virus is not
    null group by virus_s, appcat, appid, dstip, srcip, app order by total_num
    desc)###) t group by virus, appid, app, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Zero-Day-Detected-On-Network	Zero-day malware detected on the network	traffic

```

select
  virus_s,
  appid,
  app,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  ###(select unnest(string_to_array(virus, ',')) as virus_s, appid, app, dstip, srcip,
  count(*) as total_num from $log where $filter and logid_to_int(logid) not in (4, 7,
  14) and virus like '%PossibleThreat.SB%' group by virus_s, dstip, srcip, appid, app
  )### t where virus_s like '%PossibleThreat.SB%' group by virus_s, appid, app order
  by total_num desc
    
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Files-Analyzed-By-FortiCloud-Sandbox	Files analyzed by FortiCloud Sandbox	virus

```

select
  $DAY_OF_MONTH as dom,
  count(*) as total_num
from
  $log
where
  $filter
  and nullifna(filename) is not null
  and logid_to_int(logid)= 9233
group by
  dom
order by
  dom
    
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Malicious-Files-Detected-By-FortiCloud-Sandbox	Files detected by FortiCloud Sandbox	virus

```

select
  filename,
  analyticscksum,
  count(distinct dstip) as victims,
  count(distinct srcip) as source
from
  ###(select filename, analyticscksum, dstip, srcip from $log where $filter and filename
  is not null and logid_to_int(logid)=9233 and analyticscksum is not null group by
  filename, analyticscksum, srcip, dstip)### t group by filename, analyticscksum
  order by victims desc, source desc
    
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-File-Transferred-By-Application	File transferred by applications on the network	app-ctrl

```

select
  appid,
  app,
  filename,
  cloudaction,
  max(filesize) as filesize
from
  $log
where
  $filter
  and filesize is not null
  and clouduser is not null
  and filename is not null
group by
  cloudaction,
  appid,
  app,
  filename
order by
  filesize desc

```

Dataset Name	Description	Log Category
appctrl-Top-Blocked-SCCP-Callers	Appctrl top blocked SCCP callers	app-ctrl

```

select
  srcname as caller,
  count(*) as totalnum
from
  $log
where
  $filter
  and lower(appcat)= 'voip'
  and app = 'sccp'
  and action = 'block'
  and srcname is not null
group by
  caller
order by
  totalnum desc

```

Dataset Name	Description	Log Category
appctrl-Top-Blocked-SIP-Callers	Appctrl top blocked SIP callers	app-ctrl

```

select
  srcname as caller,
  count(*) as totalnum
from
  $log
where
  $filter
  and srcname is not null
  and lower(appcat)= 'voip'
  and app = 'sip'

```

```

    and action = 'block'
group by
    caller
order by
    totalnum desc

```

Dataset Name	Description	Log Category
security-Top20-High-Risk-Application-In-Use	High risk application in use	traffic

```

select
    d_risk,
    count(distinct f_user) as users,
    name,
    app_cat,
    technology,
    sum(bandwidth) as bandwidth,
    sum(sessions) as sessions
from
    ###(select risk as d_risk, coalesce(nullifna(t1.`user`), nullifna(t1.`unauthuser`),
    ipstr(t1.`srcip`)) as f_user, t2.name, t2.app_cat, t2.technology, sum(coalesce
    (sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, count(*) as sessions from $log
    t1 inner join app_mdata t2 on t1.appid=t2.id where $filter and risk>='4' and logid_
    to_int(logid) not in (4, 7, 14) group by f_user, t2.name, t2.app_cat,
    t2.technology, risk)### t group by d_risk, name, app_cat, technology order by d_
    risk desc, sessions desc

```

Dataset Name	Description	Log Category
security-High-Risk-Application-By-Category	High risk application by category	traffic

```

select
    app_cat,
    count(distinct app) as total_num
from
    ###(select app_cat, app from $log t1 inner join app_mdata t2 on t1.appid=t2.id where
    $filter and risk>='4' and logid_to_int(logid) not in (4, 7, 14) group by app_cat,
    app)### t group by app_cat order by total_num desc

```

Dataset Name	Description	Log Category
security-Top10-Application-Categories-By-Bandwidth	Application risk application usage by category	traffic

```

select
    appcat,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
    ) as bandwidth
from
    $log
where

```

```

$filter
and logid_to_int(logid) not in (4, 7, 14)
and nullifna(appcat) is not null
group by
  appcat
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Security-Category-Breakdown-By-Bandwidth	Category breakdown of all applications, sorted by bandwidth	traffic

```

select
  appcat,
  count(distinct app) as app_num,
  count(distinct f_user) as user_num,
  sum(bandwidth) as bandwidth,
  sum(num_session) as num_session
from
  ###(select appcat, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as f_user, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as num_session from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and nullifna(appcat) is not null group by appcat, app, f_user)###
  t group by appcat order by bandwidth desc

```

Dataset Name	Description	Log Category
security-Top25-Web-Applications-By-Bandwidth	Top Web Applications by Bandwidth	traffic

```

select
  d_risk,
  name,
  app_cat,
  technology,
  count(distinct f_user) as users,
  sum(bandwidth) as bandwidth,
  sum(num_session) as sessions
from
  ###(select risk as d_risk, t2.app_cat, t2.name, t2.technology, coalesce(nullifna(t1.`user`), nullifna(t1.`unauthuser`), ipstr(t1.`srcip`)) as f_user, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as num_session from $log t1 inner join app_mdata t2 on t1.appid=t2.id where $filter and logid_to_int(logid) not in (4, 7, 14) and nullifna(app) is not null and service in ('80/tcp', '443/tcp', 'HTTP', 'HTTPS', 'http', 'https') group by risk, t2.app_cat, t2.name, t2.technology, f_user)###
  t group by d_risk, name, app_cat, technology order by bandwidth desc

```

Dataset Name	Description	Log Category
Security-Top25-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```
select
  catdesc,
  count(distinct f_user) as user_num,
  sum(sessions) as sessions,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`)), ipstr(`srcip`))
  as f_user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))
  as bandwidth from $log-traffic where $filter and catdesc is not null and logid_to_
  int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is null or logver<52) and
  (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content',
  'command-block', 'script-filter')))) group by f_user, catdesc order by sessions
  desc)### t group by catdesc order by sessions desc
```

Dataset Name	Description	Log Category
security-Top25-Malware-Virus-Botnet-Spyware	Malware: viruses, Bots, Spyware/Adware	traffic

```
select
  virus_s as virus,
  (
    case when lower(appcat)= 'botnet' then 'Botnet C&C' else (
      case when virus_s like 'Riskware%' then 'Spyware' when virus_s like 'Adware%'
        then 'Adware' else 'Virus' end
    ) end
  ) as malware_type,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  (
    ###(select app as virus_s, appcat, dstip, srcip, count(*) as total_num from $log-
    traffic where $filter and logid_to_int(logid) not in (4, 7, 14) and lower
    (appcat)='botnet' group by virus_s, appcat, dstip, srcip order by total_num
    desc)### union all ###(select unnest(string_to_array(virus, ',')) as virus_s,
    appcat, dstip, srcip, count(*) as total_num from $log-traffic where $filter and
    logid_to_int(logid) not in (4, 7, 14) and virus is not null group by virus_s,
    appcat, dstip, srcip order by total_num desc)###) t group by virus, malware_type
    order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Malware-Virus-Spyware	Malware: viruses, Spyware/Adware	virus

```
select
  virus,
  max(virusid) as virusid,
  malware_type,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
```

```
###(select virus, virusid, srcip, dstip, (case when virus like 'Riskware%' then
'Spyware' when virus like 'Adware%' then 'Adware' else 'Virus' end) as malware_
type, count(*) as total_num from $log where $filter and nullifna(virus) is not null
group by virus, virusid, srcip, dstip order by total_num desc)### t group by virus,
malware_type order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Malware-Botnet	Malware: Botnet	appctrl

```
select
  app,
  appid,
  malware_type,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  ###(select app, appid, cast('Botnet C&C' as char(32)) as malware_type, srcip, dstip,
  count(*) as total_num from $log where $filter and lower(appcat)='botnet' and
  nullifna(app) is not null group by app, appid, malware_type, srcip, dstip order by
  total_num desc)### t group by app, appid, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Victims-of-Malware	Victims of Malware	virus

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  virus as malware,
  count(*) as total_num
from
  $log
where
  $filter
  and virus is not null
group by
  user_src,
  malware
order by
  total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Victims-of-Phishing-Site	Victims of Phishing Site	webfilter

```
select
  coalesce(
    nullifna(`user`),
```

```

        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    (
        lower(service) || '://' || hostname || url
    ) as phishing_site,
    count(*) as total_num
from
    $log
where
    $filter
    and lower(service) in ('http', 'https')
    and hostname is not null
    and cat in (26, 61)
group by
    user_src,
    phishing_site
order by
    total_num desc

```

Dataset Name	Description	Log Category
security-Top25-Malicious-Phishing-Sites	Malicious Phishing Site	webfilter

```

select
    phishing_site,
    count(distinct dstip) as victims,
    count(distinct srcip) as source,
    sum(total) as total_num
from
    ###(select (lower(service) || '://' || hostname || url) as phishing_site, dstip, srcip,
        count(*) as total from $log where $filter and lower(service) in ('http', 'https')
        and hostname is not null and cat in (26, 61) group by phishing_site, dstip, srcip
        order by total desc)### t group by phishing_site order by total_num desc

```

Dataset Name	Description	Log Category
security-Application-Vulnerability	Application vulnerabilities discovered	attack

```

select
    attack,
    attackid,
    vuln_type,
    cve,
    severity_number,
    count(distinct dstip) as victims,
    count(distinct srcip) as sources,
    sum(totalnum) as totalnum
from
    ###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then
        5 when t1.severity='high' then 4 when t1.severity='medium' then 3 when
        t1.severity='low' then 2 when t1.severity='info' then 1 else 0 end) as severity_
        number, dstip, srcip, count(*) as totalnum from $log t1 left join ips_mdata t2 on
        t1.attack=t2.name where $filter and nullifna(attack) is not null and t1.severity is

```

```
not null group by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip
)### t group by attack, attackid, vuln_type, severity_number, cve order by
severity_number desc, totalnum desc
```

Dataset Name	Description	Log Category
security-Files-Analyzed-By-FortiCloud-Sandbox	Files analyzed by FortiCloud Sandbox	virus

```
select
  $day_of_week as dow,
  count(*) as total_num
from
  $log
where
  $filter
  and nullifna(filename) is not null
  and logid_to_int(logid)= 9233
group by
  dow
order by
  dow
```

Dataset Name	Description	Log Category
Security-Zero-Day-Detected-On-Net-work	Zero-day malware detected on the network	traffic

```
select
  virus_s,
  app,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  ###(select unnest(string_to_array(virus, ',')) as virus_s, app, dstip, srcip, count(*)
  as total_num from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and
  virus like '%PossibleThreat.SB%' group by virus_s, dstip, srcip, app)### t group by
  virus_s, app order by total_num desc
```

Dataset Name	Description	Log Category
security-Data-Loss-Incidents-By-Severity	Data loss incidents summary by severity	dlp

```
select
  initcap(severity :: text) as s_severity,
  count(*) as total_num
from
  $log
where
  $filter
  and severity is not null
group by
```

```

    s_severity
  order by
    total_num desc

```

Dataset Name	Description	Log Category
security-Data-Loss-Files-By-Service	Data Lass Files By Service	dlp

```

select
  filename,
  (
    case direction when 'incoming' then 'Download' when 'outgoing' then 'Upload' end
  ) as action,
  max(filesize) as filesize,
  service
from
  $log
where
  $filter
  and filesize is not null
group by
  filename,
  direction,
  service
order by
  filesize desc

```

Dataset Name	Description	Log Category
security-Endpoint-Security-Events-Summary	Endpoint Security Events summary	fct-traffic

```

select
  (
    case utmevent when 'antivirus' then 'Malware incidents' when 'webfilter' then
      'Malicious/phishing websites' when 'appfirewall' then 'Risk applications' when
      'dlp' then 'Data loss incidents' when 'netscan' then 'Vulnerability detected'
      else 'Others' end
  ) as events,
  count(*) as total_num
from
  $log
where
  $filter
  and utmevent is not null
group by
  events
order by
  total_num desc

```

Dataset Name	Description	Log Category
security-Top-Endpoing-Running-High-Risk-Application	Endpoints Running High Risk Application	fct-traffic

```

select
  coalesce(
    nullifna(`user`),
    ipstr(`srcip`),
    'Unknown'
  ) as f_user,
  coalesce(
    nullifna(hostname),
    'Unknown'
  ) as host_name,
  threat as app,
  t2.app_cat as appcat,
  risk as d_risk
from
  $log t1
  inner join app_mdata t2 on t1.threat = t2.name
where
  $filter
  and utmevent = 'appfirewall'
  and risk >= '4'
group by
  f_user,
  host_name,
  t1.threat,
  t2.app_cat,
  t2.risk
order by
  risk desc

```

Dataset Name	Description	Log Category
security-Top-Endpoints-Infected-With-Malware	Endpoints Infected With Malware	fct-event

```

select
  coalesce(
    nullifna(`user`),
    ipstr(`deviceip`),
    'Unknown'
  ) as f_user,
  coalesce(
    nullifna(hostname),
    'Unknown'
  ) as host_name,
  virus,
  file
from
  $log
where

```

```

$filter
and clientfeature = 'av'
and virus is not null
group by
  f_user,
  host_name,
  virus,
  file
    
```

Dataset Name	Description	Log Category
security-Top-Endpoints-With-Web-Violateions	Endpoints With Web Violations	fct-traffic

```

select
  f_user,
  host_name,
  remotename,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as f_user, coalesce(nullifna
(hostname), 'Unknown') as host_name, remotename, count(*) as total_num from $log
where $filter and utmevent='webfilter' and remotename is not null and
utmaction='blocked' group by f_user, host_name, remotename order by total_num
desc)### t group by f_user, host_name, remotename order by total_num desc
    
```

Dataset Name	Description	Log Category
security-Top-Endpoints-With-Data-Loss-Incidents	Endpoints With Data Loss Incidents	fct-event

```

select
  f_user,
  host_name,
  msg,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`user`), ipstr(`deviceip`), 'Unknown') as f_user, coalesce
(nullifna(hostname), 'Unknown') as host_name, msg, count(*) as total_num from $log
where $filter and clientfeature='dlp' group by f_user, host_name, msg order by
total_num desc)### t group by f_user, host_name, msg order by total_num desc
    
```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Call-Registrations-by-Hour-of-Day	Content count total SCCP call registrations by hour of day	content

```

select
  $hour_of_day as hourstamp,
  count(*) as totalnum
from
  $log
where
  $filter
    
```

```

    and proto = 'sccp'
    and kind = 'register'
group by
    hourstamp
order by
    hourstamp

```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Calls-Duration-by-Hour-of-Day	Content count total SCCP calls duration by hour of day	content

```

select
    $hour_of_day as hourstamp,
    sum(duration) as sccp_usage
from
    $log
where
    $filter
    and proto = 'sccp'
    and kind = 'call-info'
    and status = 'end'
group by
    hourstamp
order by
    hourstamp

```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Calls-per-Status	Content count total SCCP calls per status	content

```

select
    status,
    count(*) as totalnum
from
    $log
where
    $filter
    and proto = 'sccp'
    and kind = 'call-info'
group by
    status
order by
    totalnum desc

```

Dataset Name	Description	Log Category
content-Count-Total-SIP-Call-Registrations-by-Hour-of-Day	Content count total SIP call registrations by hour of day	content

```

select
    $hour_of_day as hourstamp,

```

```

    count(*) as totalnum
from
  $log
where
  $filter
  and proto = 'sip'
  and kind = 'register'
group by
  hourstamp
order by
  hourstamp

```

Dataset Name	Description	Log Category
content-Count-Total-SIP-Calls-per-Status	Content count total SIP calls per status	content

```

select
  status,
  count(*) as totalnum
from
  $log
where
  $filter
  and proto = 'sip'
  and kind = 'call'
group by
  status
order by
  totalnum desc

```

Dataset Name	Description	Log Category
content-Dist-Total-SIP-Calls-by-Duration	Content dist total SIP calls by duration	content

```

select
  (
    case when duration < 60 then 'LESS_ONE_MIN' when duration < 600 then 'LESS_TEN_MIN'
    when duration < 3600 then 'LESS_ONE_HOUR' when duration >= 3600 then 'MORE_ONE_HOUR' else 'unknown' end
  ) as f_duration,
  count(*) as totalnum
from
  $log
where
  $filter
  and proto = 'sip'
  and kind = 'call'
  and status = 'end'
group by
  f_duration
order by
  totalnum desc

```

Dataset Name	Description	Log Category
Botnet-Activity-By-Sources	Botnet activity by sources	traffic

```

select
  app,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as events
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and appcat = 'Botnet'
  and nullifna(app) is not null
group by
  app,
  user_src
order by
  events desc

```

Dataset Name	Description	Log Category
Botnet-Infected-Hosts	Botnet infected hosts	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  devtype,
  coalesce(srcname, srcmac) as host_mac,
  count(*) as events
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and appcat = 'Botnet'
group by
  user_src,
  devtype,
  host_mac
order by
  events desc

```

Dataset Name	Description	Log Category
Detected-Botnet	Detected botnet	traffic

```

select
  app,
  count(*) as events
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and appcat = 'Botnet'
  and nullifna(app) is not null
group by
  app
order by
  events desc

```

Dataset Name	Description	Log Category
Botnet-Sources	Botnet sources	traffic

```

select
  dstip,
  root_domain(hostname) as domain,
  count(*) as events
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and appcat = 'Botnet'
  and dstip is not null
group by
  dstip,
  domain
order by
  events desc

```

Dataset Name	Description	Log Category
Botnet-Victims	Botnet victims	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as events
from

```

```

$log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and appcat = 'Botnet'
  and srcip is not null
group by
  user_src
order by
  events desc

```

Dataset Name	Description	Log Category
Botnet-Timeline	Botnet timeline	traffic

```

select
  $flex_timescale(timestamp) as hodex,
  sum(events) as events
from
  ###(select $flex_timestamp as timestamp, count(*) as events from $log where $filter and
  logid_to_int(logid) not in (4, 7, 14) and appcat='Botnet' group by timestamp order
  by timestamp desc)### t group by hodex order by hodex

```

Dataset Name	Description	Log Category
Application-Session-History	Application session history	traffic

```

select
  $flex_timescale(timestamp) as hodex,
  sum(counter) as counter
from
  ###(select $flex_timestamp as timestamp, count(*) as counter from $log where $filter
  and logid_to_int(logid) not in (4, 7, 14) group by timestamp order by timestamp
  desc)### t group by hodex order by hodex

```

Dataset Name	Description	Log Category
Application-Usage-List	Detailed application usage	traffic

```

select
  appid,
  app,
  appcat,
  (
    case when (
      utmaction in ('block', 'blocked')
      or action = 'deny'
    ) then 'Blocked' else 'Allowed' end
  ) as custaction,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  count(*) as num_session
from

```

```

$log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and policyid != 0
group by
  appid,
  app,
  appcat,
  custaction
order by
  bandwidth desc
    
```

Dataset Name	Description	Log Category
PCI-DSS-Compliance-Summary	PCI DSS Compliance Summary	event

```

select
  status,
  num_reason as requirements,
  cast(
    num_reason * 100.0 / (
      sum(num_reason) over()
    ) as decimal(18, 2)
  ) as percent
from
  (
    select
      (
        case when fail_count > 0 then 'Non-Compliant' else 'Compliant' end
      ) as status,
      count(distinct reason) as num_reason
    from
      (
        select
          ftnt_pci_id,
          (
            sum(fail_count) over (partition by ftnt_pci_id)
          ) as fail_count,
          reason
        from
          ###(select ftnt_pci_id, (case when result='fail' then 1 else 0 end) as fail_
            count, reason from $log t1 inner join pci_dss_mdata t2 on
            t1.reason=t2.ftnt_id where $filter and subtype='compliance-check' group
            by ftnt_pci_id, result, reason)### t) t group by status) t order by
            status
    
```

Dataset Name	Description	Log Category
PCI-DSS-Non-Compliant-Requirements-By-Severity	PCI DSS Non-Compliant Requirements by Severity	event

with query as (
 select
 *

```

from
  (
    select
      ftnt_pci_id,
      severity,
      (
        sum(fail_count) over (partition by ftnt_pci_id)
      ) as fail_count,
      reason
    from
      ###(select ftnt_pci_id, severity, (case when result='fail' then 1 else 0 end)
        as fail_count, reason from $log t1 inner join pci_dss_mdata t2 on
        t1.reason=t2.ftnt_id where $filter and subtype='compliance-check' group by
        ftnt_pci_id, severity, result, reason)### t) t where fail_count>0) select
        t.severity, count(distinct t.reason) as requirements from (select distinct
        on (1) reason, severity from query order by reason, (case lower(severity)
        when 'high' then 4 when 'critical' then 3 when 'medium' then 2 when 'low'
        then 1 else 0 end) desc) t group by t.severity order by requirements desc
  
```

Dataset Name	Description	Log Category
PCI-DSS-Compliant-Requirements-By-Severity	PCI DSS Compliant Requirements by Severity	event

```

with query as (
  select
    *
  from
    (
      select
        ftnt_pci_id,
        severity,
        (
          sum(fail_count) over (partition by ftnt_pci_id)
        ) as fail_count,
        reason
      from
        ###(select ftnt_pci_id, severity, (case when result='fail' then 1 else 0 end)
          as fail_count, reason from $log t1 inner join pci_dss_mdata t2 on
          t1.reason=t2.ftnt_id where $filter and subtype='compliance-check' group by
          ftnt_pci_id, severity, result, reason)### t) t where fail_count=0) select
          t.severity, count(distinct t.reason) as requirements from (select distinct
          on (1) reason, severity from query order by reason, (case lower(severity)
          when 'high' then 4 when 'critical' then 3 when 'medium' then 2 when 'low'
          then 1 else 0 end) desc) t group by t.severity order by requirements desc
    )
  
```

Dataset Name	Description	Log Category
PCI-DSS-Fortinet-Security-Best-Practice-Summary	PCI DSS Fortinet Security Best Practice Summary	event

```

select
  status,
  num_reason as practices,
  cast(
    num_reason * 100.0 /(
  
```

```

        sum(num_reason) over()
    ) as decimal(18, 2)
) as percent
from
(
    select
        (
            case when result = 'fail' then 'Failed' else 'Passed' end
        ) as status,
        count(distinct reason) as num_reason
    from
        ###(select result, reason from $log where $filter and subtype='compliance-check'
            and result in ('fail','pass') group by result, reason)### t group by status)
        t order by status desc

```

Dataset Name	Description	Log Category
PCI-DSS-Failed-Fortinet-Security-Best-Practices-By-Severity	PCI DSS Failed Fortinet Security Best Practices by Severity	event

```

select
    status,
    num_reason as practices,
    cast(
        num_reason * 100.0 / (
            sum(num_reason) over()
        ) as decimal(18, 2)
    ) as percent
from
(
    select
        initcap(status) as status,
        count(distinct reason) as num_reason
    from
        ###(select status, reason from $log where $filter and subtype='compliance-check'
            and result='fail' group by status, reason)### t group by status) t order by
        status

```

Dataset Name	Description	Log Category
PCI-DSS-Passed-Fortinet-Security-Best-Practices-By-Severity	PCI DSS Passed Fortinet Security Best Practices by Severity	event

```

select
    status,
    num_reason as practices,
    cast(
        num_reason * 100.0 / (
            sum(num_reason) over()
        ) as decimal(18, 2)
    ) as percent
from
(
    select
        initcap(status) as status,

```

```

count(distinct reason) as num_reason
from
  ###(select status, reason from $log where $filter and subtype='compliance-check'
    and result='pass' group by status, reason)### t group by status) t order by
  status

```

Dataset Name	Description	Log Category
PCI-DSS-Requirements-Compliance-Details	PCI DSS Requirements Compliance Details	event

```

select
  ftnt_pci_id,
  left(
    string_agg(distinct ftnt_id, ','),
    120
  ) as practice,
  (
    case when sum(fail_count)> 0 then 'Non-Compliant' else 'Compliant' end
  ) as compliance,
  pci_requirement
from
  ###(select ftnt_pci_id, ftnt_id, (case when result='fail' then 1 else 0 end) as fail_
    count, pci_requirement from $log t1 inner join pci_dss_mdata t2 on
    t1.reason=t2.ftnt_id where $filter and subtype='compliance-check' group by ftnt_
    pci_id, ftnt_id, result, pci_requirement)### t group by ftnt_pci_id, pci_
    requirement order by ftnt_pci_id

```

Dataset Name	Description	Log Category
PCI-DSS-Fortinet-Security-Best-Practice-Details	PCI DSS Fortinet Security Best Practice Details	event

```

select
  reason as ftnt_id,
  msg,
  initcap(status) as status,
  module
from
  $log
where
  $filter
  and subtype = 'compliance-check'
group by
  reason,
  status,
  module,
  msg
order by
  ftnt_id

```

Dataset Name	Description	Log Category
DLP-Email-Activity-Details	Email DLP Violations Summary	dlp

```

select
  from_itime(itime) as timestamp,
  `from` as sender,
  `to` as receiver,
  regexp_replace(filename, '.*/', '') as filename,
  filesize,
  profile,
  action,
  direction
from
  $log
where
  $filter
  and (
    service in (
      'smtp', 'SMTP', '25/tcp', '587/tcp',
      'smtps', 'SMTPS', '465/tcp'
    )
    or service in (
      'pop3', 'POP3', '110/tcp', 'imap',
      'IMAP', '143/tcp', 'imaps', 'IMAPS',
      '993/tcp', 'pop3s', 'POP3S', '995/tcp'
    )
  )
order by
  timestamp desc

```

Dataset Name	Description	Log Category
Email-DLP-Chart	Email DLP Activity Summary	dlp

```

select
  profile,
  count(*) as total_num
from
  $log
where
  $filter
  and (
    service in (
      'smtp', 'SMTP', '25/tcp', '587/tcp',
      'smtps', 'SMTPS', '465/tcp'
    )
    or service in (
      'pop3', 'POP3', '110/tcp', 'imap',
      'IMAP', '143/tcp', 'imaps', 'IMAPS',
      '993/tcp', 'pop3s', 'POP3S', '995/tcp'
    )
  )
group by
  profile
order by
  total_num desc

```

Dataset Name	Description	Log Category
DLP-Web-Activity-Details	Web DLP Violations Summary	dlp

```

select
  from_itime(itime) as timestamp,
  srcip,
  dstip,
  hostname,
  profile,
  filename,
  filesize,
  action,
  direction
from
  $log
where
  $filter
  and lower(service) in ('http', 'https')
order by
  timestamp desc

```

Dataset Name	Description	Log Category
Web-DLP-Chart	Web DLP Activity Summary	dlp

```

select
  profile,
  count(*) as total_num
from
  $log
where
  $filter
  and lower(service) in ('http', 'https')
group by
  profile
order by
  total_num desc

```

Dataset Name	Description	Log Category
DLP-FTP-Activity-Details	Web DLP Violations Summary	dlp

```

select
  from_itime(itime) as timestamp,
  srcip,
  dstip,
  filename,
  profile,
  filesize,
  action,
  direction

```

```

from
  $log
where
  $filter
  and lower(service) in ('ftp', 'ftps')
order by
  timestamp desc
    
```

Dataset Name	Description	Log Category
FTP-DLP-Chart	FTP DLP Activity Summary	dlp

```

select
  profile,
  count(*) as total_num
from
  $log
where
  $filter
  and lower(service) in ('ftp', 'ftps')
group by
  profile
order by
  total_num desc
    
```

Dataset Name	Description	Log Category
top-users-by-browsetime	Top Users by website browsetime	traffic

```

select
  user_src,
  domain,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###(select user_src, domain, ebtr_agg_flat(browsetime) as browsetime from (select
  coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, coalesce(nullifna
  (hostname), ipstr(`dstip`)) as domain, ebtr_agg_flat($browse_time) as browsetime
  from $log where $filter and $browse_time is not null group by user_src, domain) t
  group by user_src, domain order by ebtr_value(ebtr_agg_flat(browsetime), null,
  null) desc)### t group by user_src, domain order by browsetime desc
    
```

Dataset Name	Description	Log Category
wifi-usage-by-hour-authenticated	Wifi Usage by Hour - Authenticated	event

```

select
  hod,
  count(distinct stamac) as totalnum
from
    
```

```
###(select $HOUR_OF_DAY as hod, stamac from $log where $filter and subtype='wireless'
and action='client-authentication' group by hod, stamac)### t group by hod order by
hod
```

Dataset Name	Description	Log Category
wifi-usage-authenticated-timeline	Wifi Usage Timeline - Authenticated	event

```
select
  $flex_timescale(timestamp) as hodex,
  count(distinct stamac) as totalnum
from
  ###(select $flex_timestamp as timestamp, stamac from $log where $filter and
  subtype='wireless' and action='client-authentication' group by timestamp, stamac
  order by timestamp desc)### t group by hodex order by hodex
```

Dataset Name	Description	Log Category
app-top-user-by-bandwidth	Top 10 Applications Bandwidth by User Drilldown	traffic

```
select
  app,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(`sentbyte`, 0)+ coalesce(`rcvdbyte`, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
group by
  app,
  user_src
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
app-top-user-by-session	Top 10 Application Sessions by User Drilldown	traffic

```
select
  app,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
```

```

from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
group by
  app,
  user_src
order by
  sessions desc
    
```

Dataset Name	Description	Log Category
traffic-Interface-Bandwidth-Usage	Interface Bandwidth Usage	traffic

with qry as (

```

select
  dom as dom_s,
  devid as devid_s,
  vd as vd_s,
  srcintf,
  dstintf,
  total_sent,
  total_rcvd
from
  ###(select $DAY_OF_MONTH as dom, devid, vd, srcintf, dstintf, sum(coalesce(sentbyte, 0)) as total_sent, sum(coalesce(rcvdbyte, 0)) as total_rcvd, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as total from $log where $filter and logid_to_int(logid) not in (4, 7, 14) and nullifna(srcintf) is not null and nullifna(dstintf) is not null group by dom, devid, vd, srcintf, dstintf having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by total desc)### t)
select dom, unnest(array['download', 'upload']) as type, unnest(array[sum(download), sum(upload)]) as bandwidth from (select coalesce(t1.dom_s, t2.dom_s) as dom, coalesce(t1.devid_s, t2.devid_s) as devid, coalesce(t1.vd_s, t2.vd_s) as vd, coalesce(t1.srcintf, t2.dstintf) as intf, sum(coalesce(t1.total_sent, 0)+coalesce(t2.total_rcvd, 0)) as download, sum(coalesce(t2.total_sent, 0)+coalesce(t1.total_rcvd, 0)) as upload from qry t1 full join qry t2 on t1.dom_s=t2.dom_s and t1.srcintf=t2.dstintf group by dom, devid, vd, intf) t where $filter-drilldown group by dom order by dom
    
```

Dataset Name	Description	Log Category
ctap-SB-Files-Needing-Inspection-vs-Others	Files Needing Inspection vs Others	virus

```

select
  (
    case when suffix in (
      'bat', 'cmd', 'exe', 'jar', 'msi', 'vbs',
      '7z', 'zip', 'gzip', 'lzw', 'tar',
      'rar', 'cab', 'doc', 'docx', 'xls',
      'xlsx', 'ppt', 'pptx', 'pdf', 'swf',
      'lnk', 'js'
    ) then 'Higher Risk File Types' else 'Excluded Files' end
  ) as files,
    
```

```

sum(total_num) as total_num
from
###(select file_name_ext(filename) as suffix, count(*) as total_num from $log where
$filter and dtype='fortisandbox' and nullifna(filename) is not null group by suffix
order by total_num desc)### t group by files order by total_num desc

```

Dataset Name	Description	Log Category
ctap-SB-Breakdown-of-File-Types	Breakdown of File Types	virus

```

select
(
case when suffix in (
'exe', 'msi', 'upx', 'vbs', 'bat', 'cmd',
'dll', 'ps1', 'jar'
) then 'Executable Files' when suffix in ('pdf') then 'Adobe PDF' when suffix in (
'swf') then 'Adobe Flash' when suffix in (
'doc', 'docx', 'rtf', 'dotx', 'docm',
'dotm', 'dot'
) then 'Microsoft Word' when suffix in (
'xls', 'xlsx', 'xltx', 'xlsm', 'xlsb',
'xlam', 'xlt'
) then 'Microsoft Excel' when suffix in (
'ppsx', 'ppt', 'pptx', 'potx', 'sldx',
'pptm', 'ppsm', 'potm', 'ppam', 'sldm',
'pps', 'pot'
) then 'Microsoft PowerPoint' when suffix in ('msg') then 'Microsoft Outlook' when
suffix in ('htm', 'js', 'url', 'lnk') then 'Web Files' when suffix in (
'cab', 'tgz', 'z', '7z', 'tar', 'lzh',
'kgb', 'rar', 'zip', 'gz', 'xz', 'bz2'
) then 'Archive Files' when suffix in ('apk') then 'Android Files' else 'Others' end
) as filetype,
sum(total_num) as total_num
from
###(select file_name_ext(filename) as suffix, count(*) as total_num from $log where
$filter and dtype='fortisandbox' and nullifna(filename) is not null group by suffix
order by total_num desc)### t group by filetype order by total_num desc

```

Dataset Name	Description	Log Category
ctap-SB-Top-Sandbox-Malicious-Exes		virus

```

select
(
case virus when 'malicious' then 5 when 'high risk' then 4 when 'medium risk' then 3
when 'low risk' then 2 else 1 end
) as risk,
filename,
service,
count(*) as total_num
from
$log
where
$filter

```

```

and dtype = 'fortisandbox'
and file_name_ext(filename)= 'exe'
and virus not in ('clean', 'submission failed')
group by
  filename,
  risk,
  service
order by
  risk desc,
  total_num desc,
  filename
    
```

Dataset Name	Description	Log Category
ctap-SB-Sources-of-Sandbox-Discovered-Malware	Sources of Sandbox Discovered Malware	virus

```

select
  srcip,
  count(*) as total_num
from
  $log
where
  $filter
  and dtype = 'fortisandbox'
  and nullifna(filename) is not null
  and virus not in ('clean', 'submission failed')
group by
  srcip
order by
  total_num desc
    
```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-High-Risk-Application	Application risk high risk application	traffic

```

select
  d_risk,
  count(distinct f_user) as users,
  id,
  name,
  app_cat,
  technology,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###(select risk as d_risk, coalesce(nullifna(t1.`user`), nullifna(t1.`unauthuser`)),
  ipstr(t1.`srcip`) as f_user, t2.id , t2.name, t2.app_cat, t2.technology, sum
  (coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as sessions
  from $log t1 inner join app_mdata t2 on t1.appid=t2.id where $filter and risk>='4'
  and logid_to_int(logid) not in (4, 7, 14) group by f_user, t2.id , t2.name, t2.app_
  cat, t2.technology, risk)### t group by id, d_risk, name, app_cat, technology order
  by d_risk desc, sessions desc
    
```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Application-Vulnerability	Application vulnerabilities discovered	attack

```

select
  attack,
  attackid,
  vuln_type,
  cve,
  severity_number,
  count(distinct dstip) as victims,
  count(distinct srcip) as sources,
  sum(totalnum) as totalnum
from
  ###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then
  5 when t1.severity='high' then 4 when t1.severity='medium' then 3 when
  t1.severity='low' then 2 when t1.severity='info' then 1 else 0 end) as severity_
  number, dstip, srcip, count(*) as totalnum from $log t1 left join ips_mdata t2 on
  t1.attack=t2.name where $filter and nullifna(attack) is not null and t1.severity is
  not null group by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip
  )### t group by attack, attackid, vuln_type, severity_number, cve order by
  severity_number desc, totalnum desc

```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Common-Virus-Botnet-Spyware	Common Virus Botnet Spyware	app-ctrl

```

select
  malware as virus,
  (
    case when lower(appcat)= 'botnet' then 'Botnet C&C' else (
      case when malware like 'Riskware%' then 'Spyware' when malware like 'Adware%'
        then 'Adware' else 'Virus' end
    ) end
  ) as malware_type,
  appid,
  app,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  (
    ###(select app as malware, appcat, appid, app, dstip, srcip, count(*) as total_num
    from $log-app-ctrl where $filter and lower(appcat)='botnet' group by malware,
    appcat, appid, app, dstip, srcip, app order by total_num desc)### union all ###
    (select (case when dtype='fortisandbox' then 'Unknown Malware' else virus end)
    as malware, 'null' as appcat, 0 as appid, service as app, dstip, srcip, count(*)
    as total_num from $log-virus where $filter and virus is not null and virus not
    in ('clean', 'submission failed') group by malware, appcat, app, appid, dstip,
    srcip order by total_num desc)###) t group by malware, malware_type, app, appid
    order by total_num desc

```

Dataset Name	Description	Log Category
ctap-App-Risk-Reputation-Top-Devices-By-Scores	Reputation Top Devices By-Scores	traffic

```

select
  coalesce(
    nullifna(`srcname`),
    ipstr(`srcip`),
    nullifna(`srcmac`)
  ) as dev_src,
  sum(crsscore % 65536) as scores
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and crsscore is not null
group by
  dev_src
having
  sum(crsscore % 65536) > 0
order by
  scores desc

```

Dataset Name	Description	Log Category
ctap-HTTP-SSL-Traffic-Ratio	HTTP SSL Traffic Ratio	traffic

```

select
  (
    case when service in ('80/tcp', 'HTTP', 'http') then 'HTTP' else 'HTTPS' end
  ) as service,
  sum(
    coalesce(sentbyte, 0) + coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and service in (
    '80/tcp', '443/tcp', 'HTTP', 'HTTPS',
    'http', 'https'
  )
group by
  service
having
  sum(
    coalesce(sentbyte, 0) + coalesce(rcvdbyte, 0)
  ) > 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-Source-Countries	Top Source Countries	traffic

```

select
  srccountry,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(srccountry) is not null
  and srccountry <> 'Reserved'
group by
  srccountry
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc,
  srccountry

```

Dataset Name	Description	Log Category
ctap-SaaS-Apps	CTAP SaaS Apps	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and lower(appcat)= 'storage.backup'
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-iaaS-Apps	CTAP IaaS Apps	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and lower(appcat)= 'cloud.it'
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-RAS-Apps	CTAP RAS Apps	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and lower(appcat)= 'remote.access'
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Proxy-Apps	CTAP Proxy Apps	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and lower(appcat)= 'proxy'
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-SocialMedia-App-By-Bandwidth	Top SocialMedia Applications by Bandwidth Usage	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and lower(appcat)= 'social.media'
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0

```

```

    )> 0
  order by
    bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-Streaming-App-By-Bandwidth	Top Streaming applications by bandwidth usage	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and lower(appcat)= 'video/audio'
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-Game-App-By-Bandwidth	Top Game applications by bandwidth usage	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log

```

```

where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and lower(appcat)= 'game'
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-P2P-App-By-Bandwidth	Top P2P applications by bandwidth usage	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and logid_to_int(logid) not in (4, 7, 14)
  and nullifna(app) is not null
  and lower(appcat)= 'p2p'
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Top-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```

select
  catdesc,
  count(distinct f_user) as user_num,
  sum(sessions) as sessions,

```

```

sum(bandwidth) as bandwidth
from
###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`))
as f_user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))
as bandwidth from $log-traffic where $filter and catdesc is not null and logid_to_
int(logid) not in (4, 7, 14) and (countweb>0 or ((logver is null or logver<52) and
(hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content',
'command-block', 'script-filter')))) group by f_user, catdesc order by sessions
desc)### t group by catdesc order by sessions desc
    
```

Dataset Name	Description	Log Category
ctap-App-Risk-Applications-Running-Over-HTTP	Application risk applications running over HTTP	traffic

```

select
app_group_name(app) as app_group,
service,
count(*) as sessions,
sum(
coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
) as bandwidth
from
$log
where
$filter
and logid_to_int(logid) not in (4, 7, 14)
and nullifna(app) is not null
and service in (
'80/tcp', '443/tcp', 'HTTP', 'HTTPS',
'http', 'https'
)
group by
app_group,
service
having
sum(
coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
)> 0
order by
bandwidth desc
    
```

Dataset Name	Description	Log Category
ctap-App-Risk-Web-Browsing-Activity-Hostname-Category	Application risk web browsing activity hostname category	traffic

```

select
domain,
catdesc,
sum(visits) as visits
from
(
###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, catdesc, count(*)
as visits from $log-traffic where $filter and logid_to_int(logid) not in (4, 7,
    
```

```
14) and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block',
'script-filter') and catdesc is not null group by domain, catdesc order by
visits desc)### union all ###(select coalesce(nullifna(hostname), ipstr
(`dstip`)) as domain, catdesc, count(*) as visits from $log-webfilter where
$filter and (eventtype is null or logver>=52) and catdesc is not null group by
domain, catdesc order by visits desc)###) t group by domain, catdesc order by
visits desc
```

Dataset Name	Description	Log Category
ctap-Top-Sites-By-Browsing-Time	Traffic top sites by browsing time	traffic

```
select
  hostname,
  string_agg(distinct catdesc, ', ') as agg_catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select hostname, catdesc, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth)
  as bandwidth, sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from
  (select hostname, catdesc, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
  (sentbyte, 0)+coalesce(rcvbyte, 0)) as bandwidth, sum(coalesce(rcvbyte, 0)) as
  traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and
  logid_to_int(logid) not in (4, 7, 14) and hostname is not null and $browse_time is
  not null group by hostname, catdesc) t group by hostname, catdesc order by ebtr_
  value(ebtr_agg_flat(browsetime), null, null) desc)### t group by hostname order by
  browsetime desc
```

Dataset Name	Description	Log Category
ctap-Average-Bandwidth-Hour	Average Bandwidth Hour	traffic

```
select
  hourstamp,
  sum(bandwidth)/ count(distinct daystamp) as bandwidth
from
  ###(select to_char(from_dtime(dtime), 'HH24:00') as hourstamp, to_char(from_dtime
  (dtime), 'DD Mon') as daystamp, sum(coalesce(sentbyte, 0)+coalesce(rcvbyte, 0)) as
  bandwidth from $log where $filter group by hourstamp, daystamp having sum(coalesce
  (sentbyte, 0)+coalesce(rcvbyte, 0))>0 order by hourstamp)### t group by hourstamp
  order by hourstamp
```

Dataset Name	Description	Log Category
ctap-Top-Bandwidth-Hosts	Top Bandwidth Hosts	traffic

```
select
  hostname,
  sum(
```

```

        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log - traffic
where
    $filter
    and hostname is not null
    and logid_to_int(logid) not in (4, 7, 14)
group by
    hostname
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) > 0
order by
    bandwidth desc
    
```

Dataset Name	Description	Log Category
saas-Application-Discovered	All Applications Discovered on the Network	traffic

```

select
    (
        case is_saas when 1 then 'SaaS Apps' else 'Other Apps' end
    ) as app_type,
    count(distinct app_s) as total_num
from
    ###(select app_s, (case when saas_s>=10 then 1 else 0 end) as is_saas from (select
        unnest(apps) as app_s, unnest(saasinfo) as saas_s from $log where $filter and apps
        is not null) t group by app_s, is_saas)### t group by is_saas order by is_saas
    
```

Dataset Name	Description	Log Category
saas-SaaS-Application-by-Category	Number of SaaS Applications by Category	traffic

```

select
    (
        case saas_cat when 0 then 'Sanctioned' else 'Unsanctioned' end
    ) as saas_cat_str,
    count(distinct app_s) as num_saas_app
from
    ###(select app_s, saas_s%10 as saas_cat, sum(sentbyte+rcvdbyte) as bandwidth, count(*)
        as total_app from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s,
        coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte from $log
        where $filter and apps is not null) t where saas_s>=10 group by app_s, saas_cat
        order by bandwidth desc)### t where saas_cat in (0, 1) group by saas_cat order by
        saas_cat
    
```

Dataset Name	Description	Log Category
saas-SaaS-Application-by-Bandwidth	Number of SaaS Applications by Bandwidth	traffic

```

select
    
```

```

(
  case saas_cat when 0 then 'Sanctioned' else 'Tolerated' end
) as saas_cat_str,
sum(bandwidth) as bandwidth
from
###(select app_s, saas_s%10 as saas_cat, sum(sentbyte+rcvdbyte) as bandwidth, count(*)
  as total_app from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s,
  coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte from $log
  where $filter and apps is not null) t where saas_s>=10 group by app_s, saas_cat
  order by bandwidth desc)### t where saas_cat in (0, 2) group by saas_cat order by
  saas_cat

```

Dataset Name	Description	Log Category
saas-SaaS-Application-by-Session	Number of SaaS Applications by Session	traffic

```

select
(
  case saas_cat when 0 then 'Sanctioned' else 'Tolerated' end
) as saas_cat_str,
sum(total_app) as total_app
from
###(select app_s, saas_s%10 as saas_cat, sum(sentbyte+rcvdbyte) as bandwidth, count(*)
  as total_app from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s,
  coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte from $log
  where $filter and apps is not null) t where saas_s>=10 group by app_s, saas_cat
  order by bandwidth desc)### t where saas_cat in (0, 2) group by saas_cat order by
  saas_cat

```

Dataset Name	Description	Log Category
saas-SaaS-App-Users-vs-Others	Number of Users of SaaS Apps vs Others	traffic

```

select
(
  case is_saas when 0 then 'Other Apps' else 'SaaS Apps' end
) as app_type,
count(distinct saasuser) as total_user
from
###(select saasuser, saas_s/10 as is_saas from (select coalesce(nullifna(`user`),
  nullifna(`clouduser`), nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as
  saasuser, unnest(saasinfo) as saas_s from $log where $filter and apps is not null)
  t group by saasuser, is_saas)### t group by app_type

```

Dataset Name	Description	Log Category
saas-SaaS-App-Users	Number of Users of SaaS Apps	traffic

```

select
(
  case saas_cat when 0 then 'Sanctioned' when 1 then 'Unsanctioned' else 'Others' end
) as app_type,
count(distinct saasuser) as total_user
from

```

```
###(select saasuser, saas_s%10 as saas_cat from (select coalesce(nullifna(`user`),
nullifna(`clouduser`), nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as
saasuser, unnest(saasinfo) as saas_s from $log where $filter and apps is not null)
t where saas_s>=10 group by saasuser, saas_cat)### t group by saas_cat order by
saas_cat
```

Dataset Name	Description	Log Category
saas-Top-SaaS-User-by-Bandwidth-Session	Top SaaS Users by Bandwidth and Session	traffic

```
select
  saasuser,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
    sum(sessions)- sum(session_block)
  ) as session_pass,
  count(distinct app_s) as total_app
from
  ###(select saasuser, app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as
  traffic_in, sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as
  session_block from (select coalesce(nullifna(`user`), nullifna(`clouduser`),
  nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as app_
  s, unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce
  (rcvdbyte, 0) as rcvdbyte, (CASE WHEN (action IN ('deny', 'ip-conn', 'dns') OR
  (utmaction IN ('block', 'blocked', 'reset', 'dropped'))) THEN 1 ELSE 0 END) as is_
  blocked from $log where $filter and apps is not null) t where saas_s>=10 group by
  saasuser, app_s order by bandwidth desc)### t group by saasuser order by bandwidth
  desc
```

Dataset Name	Description	Log Category
saas-Top-Category-by-SaaS-Application-Usage	Top Categories by SaaS Application Usage	traffic

```
select
  app_cat,
  (
    case saas_cat when 0 then 'Sanctioned' else 'Unsanctioned' end
  ) as saas_cat_str,
  count(distinct app_s) as total_app
from
  ###(select app_s, saas_s%10 as saas_cat from (select unnest(apps) as app_s, unnest
  (saasinfo) as saas_s from $log where $filter and apps is not null) t where saas_
  s>=10 group by app_s, saas_cat)### t1 inner join app_mdata t2 on t1.app_s=t2.name
  where saas_cat in (0, 1) group by app_cat, saas_cat order by total_app desc
```

Dataset Name	Description	Log Category
saas-Top-SaaS-Category-by-Number-of-User	Top SaaS Categories by Number of Users	traffic

```
select
  app_cat,
  (
    case saas_cat when 0 then 'Sanctioned' else 'Unsanctioned' end
  ) as saas_cat_str,
  count(distinct saasuser) as total_user
from
  ###(select app_s, saas_s%10 as saas_cat, saasuser from (select unnest(apps) as app_s,
  unnest(saasinfo) as saas_s, coalesce(nullifna(`user`), nullifna(`clouduser`),
  nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser from $log where
  $filter and apps is not null) t where saas_s>=10 group by app_s, saas_cat,
  saasuser)### t1 inner join app_mdata t2 on t1.app_s=t2.name where saas_cat in (0,
  1) group by app_cat, saas_cat order by total_user desc
```

Dataset Name	Description	Log Category
saas-Top-User-by-Number-of-SaaS-Application	Top Users by Number of SaaS Applications	traffic

```
select
  saasuser,
  (
    case saas_cat when 0 then 'Sanctioned' else 'Unsanctioned' end
  ) as saas_cat_str,
  count(distinct app_s) as total_app
from
  ###(select app_s, saas_s%10 as saas_cat, saasuser from (select unnest(apps) as app_s,
  unnest(saasinfo) as saas_s, coalesce(nullifna(`user`), nullifna(`clouduser`),
  nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser from $log where
  $filter and apps is not null) t where saas_s>=10 group by app_s, saas_cat,
  saasuser)### t where saas_cat in (0, 1) group by saasuser, saas_cat order by total_app desc
```

Dataset Name	Description	Log Category
saas-Top-SaaS-Application-by-Bandwidth-Session	Top SaaS Applications by Sessions and Bandwidth	traffic

```
select
  t2.id as app_id,
  app_s,
  app_cat,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
```

```

        sum(sessions)- sum(session_block)
    ) as session_pass
from
    ###(select app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as traffic_in, sum
        (sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_block
    from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s, coalesce(sentbyte,
        0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN (action IN ('deny',
        'ip-conn', 'dns') OR (utmaction IN ('block', 'blocked', 'reset', 'dropped')) THEN
        1 ELSE 0 END) as is_blocked from $log where $filter and apps is not null) t where
        saas_s>=10 group by app_s)### t1 inner join app_mdata t2 on t1.app_s=t2.name group
        by app_id, app_s, app_cat order by bandwidth desc
    
```

Dataset Name	Description	Log Category
saas-Top-Tolerated-SaaS-Application-by-Bandwidth	Top Tolerated SaaS Applications by Bandwidth	traffic

```

select
    app_s,
    sum(sentbyte + rcvdbyte) as bandwidth
from
    (
        select
            unnest(apps) as app_s,
            unnest(saasinfo) as saas_s,
            coalesce(sentbyte, 0) as sentbyte,
            coalesce(rcvdbyte, 0) as rcvdbyte
        from
            $log
        where
            $filter
            and apps is not null
    ) t
where
    saas_s = 12
group by
    app_s
order by
    bandwidth desc
    
```

Dataset Name	Description	Log Category
saas-drilldown-Top-Tolerated-SaaS-Application	Top Tolerated SaaS Applications	traffic

```

select
    app_s,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out,
    sum(sessions) as sessions,
    sum(session_block) as session_block,
    (
        sum(sessions)- sum(session_block)
    ) as session_pass
    
```

```

from
  ###(select saasuser, app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as
  traffic_in, sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as
  session_block from (select coalesce(nullifna(`user`), nullifna(`clouduser`),
  nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as app_
  s, unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce
  (rcvdbyte, 0) as rcvdbyte, (CASE WHEN (action IN ('deny', 'ip-conn', 'dns') OR
  (utmaction IN ('block', 'blocked', 'reset', 'dropped'))) THEN 1 ELSE 0 END) as is_
  blocked from $log where $filter and apps is not null) t where saas_s=12 group by
  saasuser, app_s order by bandwidth desc)### t where $filter-drilldown group by app_
  s order by bandwidth desc

```

Dataset Name	Description	Log Category
saas-Top-User-by-Tolerated-SaaS-Application-Drilldown	Top Users by Tolerated SaaS Applications	traffic

```

select
  saasuser,
  count(distinct app_s) as total_app
from
  ###(select saasuser, app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as
  traffic_in, sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as
  session_block from (select coalesce(nullifna(`user`), nullifna(`clouduser`),
  nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as app_
  s, unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce
  (rcvdbyte, 0) as rcvdbyte, (CASE WHEN (action IN ('deny', 'ip-conn', 'dns') OR
  (utmaction IN ('block', 'blocked', 'reset', 'dropped'))) THEN 1 ELSE 0 END) as is_
  blocked from $log where $filter and apps is not null) t where saas_s=12 group by
  saasuser, app_s order by bandwidth desc)### t group by saasuser order by total_app
  desc

```

Dataset Name	Description	Log Category
saas-drilldown-Top-File-Sharing-SaaS-Application-Detail	Top File Sharing SaaS Applications Detail	traffic

```

select
  saasuser,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
    sum(sessions) - sum(session_block)
  ) as session_pass
from
  ###(select app_group_name(app_s) as app_group, saasuser, sum(sentbyte+rcvdbyte) as
  bandwidth, sum(rcvdbyte) as traffic_in, sum(sentbyte) as traffic_out, count(*) as
  sessions, sum(is_blocked) as session_block from (select coalesce(nullifna(`user`),
  nullifna(`clouduser`), nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as
  saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_s, coalesce(sentbyte, 0)
  as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN (action IN ('deny', 'ip-
  conn', 'dns') OR (utmaction IN ('block', 'blocked', 'reset', 'dropped'))) THEN 1
  ELSE 0 END) as is_blocked from $log where $filter and apps is not null) t where

```

```
saas_s>=10 group by app_group, saasuser order by bandwidth desc)### t where
$filter-drilldown group by saasuser order by sessions desc
```

Dataset Name	Description	Log Category
saas-Top-File-Sharing-SaaS-Application	Top File Sharing Applications	traffic

```
select
  t2.id as appid,
  (
    case t2.risk when '5' then 'Critical' when '4' then 'High' when '3' then 'Medium'
      when '2' then 'Info' else 'Low' end
  ) as risk,
  app_group,
  bandwidth,
  traffic_in,
  traffic_out,
  sessions,
  session_block,
  session_pass,
  total_user
from
  (
    select
      app_group,
      count(distinct saasuser) as total_user,
      sum(bandwidth) as bandwidth,
      sum(traffic_in) as traffic_in,
      sum(traffic_out) as traffic_out,
      sum(sessions) as sessions,
      sum(session_block) as session_block,
      (
        sum(sessions)- sum(session_block)
      ) as session_pass
    from
      ###(select app_group_name(app_s) as app_group, saasuser, sum(sentbyte+rcvdbyte)
        as bandwidth, sum(rcvdbyte) as traffic_in, sum(sentbyte) as traffic_out,
        count(*) as sessions, sum(is_blocked) as session_block from (select coalesce
        (nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`), srcname,
        ipstr(`srcip`)) as saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_
        s, coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte,
        (CASE WHEN (action IN ('deny', 'ip-conn', 'dns') OR (utmaction IN ('block',
        'blocked', 'reset', 'dropped')) THEN 1 ELSE 0 END) as is_blocked from $log
        where $filter and apps is not null) t where saas_s>=10 group by app_group,
        saasuser order by bandwidth desc)### t group by app_group) t1 inner join app_
        mdata t2 on t1.app_group=t2.name where t2.app_cat='Storage.Backup' order by
        total_user desc, bandwidth desc
```

Dataset Name	Description	Log Category
saas-Top-File-Sharing-SaaS-Application-Drilldown	Top File Sharing Applications	traffic

```
select
```

```

t2.id as appid,
(
  case t2.risk when '5' then 'Critical' when '4' then 'High' when '3' then 'Medium'
  when '2' then 'Info' else 'Low' end
) as risk,
app_group,
bandwidth,
traffic_in,
traffic_out,
sessions,
session_block,
session_pass,
total_user
from
(
  select
    app_group,
    count(distinct saasuser) as total_user,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out,
    sum(sessions) as sessions,
    sum(session_block) as session_block,
    (
      sum(sessions)- sum(session_block)
    ) as session_pass
  from
    ###(select app_group_name(app_s) as app_group, saasuser, sum(sentbyte+rcvbyte)
    as bandwidth, sum(rcvbyte) as traffic_in, sum(sentbyte) as traffic_out,
    count(*) as sessions, sum(is_blocked) as session_block from (select coalesce
    (nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`)), srcname,
    ipstr(`srcip`)) as saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_
    s, coalesce(sentbyte, 0) as sentbyte, coalesce(rcvbyte, 0) as rcvbyte,
    (CASE WHEN (action IN ('deny', 'ip-conn', 'dns') OR (utmaction IN ('block',
    'blocked', 'reset', 'dropped'))) THEN 1 ELSE 0 END) as is_blocked from $log
    where $filter and apps is not null) t where saas_s>=10 group by app_group,
    saasuser order by bandwidth desc)### t group by app_group) t1 inner join app_
    mdata t2 on t1.app_group=t2.name where t2.app_cat='Storage.Backup' order by
    total_user desc, bandwidth desc

```

Dataset Name	Description	Log Category
360-degree-security-Application-Visibility-and-Control-Summary	Application Visibility and Control Summary	app-ctrl

```

select
  appcat,
  count(distinct app) as total_num
from
  ###(select appcat, app from $log where $filter and app is not null and appcat is not
  null and logid_to_int(logid) not in (4, 7, 14) group by appcat, app)### t group by
  appcat order by total_num desc

```

Dataset Name	Description	Log Category
360-degree-security-Threats-Detection-and-Prevention-Summary	Threat Prevention	app-ctrl

```

select
  threat_name,
  count(distinct threats) as total_num
from
  (
    ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name, app as threats
      from $log-app-ctrl where $filter and lower(appcat)='botnet' group by app)###
    union all ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name,
      virus as threats from $log-virus where $filter and nullifna(virus) is not null
      group by virus)### union all ###(select cast('Malicious & Phishing Sites' as
      char(32)) as threat_name, hostname as threats from $log-webfilter where $filter
      and cat in (26, 61) group by hostname)### union all ###(select cast('Critical &
      High Intrusion Attacks' as char(32)) as threat_name, attack as total_num from
      $log-attack where $filter and severity in ('critical', 'high') group by
      attack)###) t group by threat_name order by total_num desc

```

Dataset Name	Description	Log Category
360-degree-security-Data-Exfiltration-Detection-and-Prevention-Summary	Data Exfiltration Summary	dlp

```

select
  data_loss,
  count(*) as total_num
from
  (
    select
      (
        case when severity = 'critical' then 'Critical Data Exfiltration' else (
          case when coalesce(
            nullifna(`user`),
            ipstr(`srcip`)
          ) is not null then 'User Associated Data Loss' else NULL end
        ) end
      ) as data_loss
    from
      $log
    where
      $filter
  ) t
where
  data_loss is not null
group by
  data_loss
order by
  total_num desc

```

Dataset Name	Description	Log Category
360-degree-security-Endpoint-Protection-Summary	Endpoint Protection	fct-traffic

```

select
  blocked_event,
  count(*) as total_num
from
  (
    select
      (
        case utmevent when 'antivirus' then 'Malware Deteced and Blocked' when
          'appfirewall' then 'Risk Application Blocked' when 'webfilter' then (
            case when coalesce(
              nullifna(`user`),
              ipstr(`srcip`)
            ) is not null then 'Web Sites Violation Blocked' else 'Non User Initiated
              Web Visits' end
          ) else NULL end
        ) as blocked_event
      from
        $log
      where
        $filter
        and utmaction in ('blocked', 'quarantined')
      ) t
    where
      blocked_event is not null
  )
group by
  blocked_event
order by
  total_num desc

```

Macro Reference List

The following table lists the available predefined macros that can be used in a report layout to display the log data as text (XML format) dynamically.

Macro Name	Description	Dataset Used	Log Category
Application Category with Highest Session Count	Application category with the highest session count	App-Sessions-By-Category	Traffic
Application with Highest Bandwidth	Application with the highest bandwidth usage	Top-App-By-Bandwidth	Traffic
Application with Highest Session Count	Applications with the highest session count	Top-App-By-Sessions	Traffic
Attack with Highest Session Count	Attack with highest session count	Utm-Top-Attack-Source	Attack
Botnet with Highest Session Count	Botnet with the highest session count	Detected-Botnet	Traffic
Destination with Highest Bandwidth	Destination with the highest bandwidth usage	Top-Destinations-By-Bandwidth	Traffic
Destination with Highest Session Count	Destination with the highest session count	Top-Destinations-By-Sessions	Traffic
Highest Bandwidth Consumed (Application) Category	Highest bandwidth consumed by application category	App-Risk-App-Usage-By-Category	Traffic
Highest Bandwidth Consumed (Application)	Highest bandwidth consumed by application	Top-App-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Destination)	Highest bandwidth consumed by destination	Top-Destinations-By-Bandwidth	Traffic
Highest Bandwidth Consumed (P2P Application)	Highest bandwidth consumed by P2P application	Top-P2P-App-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Source)	Highest bandwidth consumed by source	Top-Users-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Web Category)	Highest bandwidth consumed by website category	Top-Web-Category-By-Bandwidth	Web Filter
Highest Bandwidth Consumed (Website)	Highest bandwidth consumed by website	Top-Web-Sites-by-Bandwidth	Web Filter

Macro Name	Description	Dataset Used	Log Category
Highest Risk Application with Highest Bandwidth	Highest risk application with the highest bandwidth usage	High-Risk-Application-By-Bandwidth	Traffic
Highest Risk Application with Highest Session Count	Highest risk application with the highest session count	High-Risk-Application-By-Sessions	Traffic
Highest Session Count by Application Category	Highest session count by application category	App-Sessions-By-Category	Traffic
Highest Session Count by Application	Highest session count by application	Top-App-By-Sessions	Traffic
Highest Session Count by Attack	Highest session count by attack	Utm-Top-Attack-Source	Attack
Highest Session Count by Botnet	Highest session count by botnet	Detected-Botnet	Traffic
Highest Session Count by Destination	Highest session count by destination	Top-Destinations-By-Sessions	Traffic
Highest Session Count by Highest Severity Attack	Highest session count by highest severity attack	Threat-Attacks-By-Severity	Attack
Highest Session Count by P2P Application	Highest session count by P2P application	Top-P2P-App-By-Sessions	Traffic
Highest Session Count by Source	Highest session count by source	Top-User-Source-By-Sessions	Traffic
Highest Session Count by Virus	Highest session count by virus	Utm-Top-Virus	Traffic
Highest Session Count by Web Category	Highest session count by website category	Top-Web-Category-by-Sessions	Web Filter
Highest Session Count by Website	Highest session count by website	Top-Web-Sites-by-Sessions	Web Filter
Highest Severity Attack with Highest Session Count	Highest severity attack with the highest session count	Threat-Attacks-By-Severity	Attack
P2P Application with Highest Bandwidth	P2P applications with the highest bandwidth usage	Top-P2P-App-By-Bandwidth	Traffic
P2P Application with Highest Session Count	P2P applications with the highest session count	Top-P2P-App-By-Sessions	Traffic

Macro Name	Description	Dataset Used	Log Category
Source with Highest Bandwidth	Source with the highest bandwidth usage	Top-Users-By-Bandwidth	Traffic
Source with Highest Session Count	Source with the highest session count	Top-User-Source-By-Sessions	Traffic
Total Number of Attacks	Total number of attacks detected	Total-Attack-Source	Attack
Total Number of Botnet Events	Total number of botnet events	Total-Number-of-Botnet-Events	Traffic
Total Number of Viruses	Total number of viruses detected	Total-Number-of-Viruses	Traffic
User Details	User details of traffic	Traffic-User-Detail	Traffic
Virus with Highest Session Count	Virus with the highest session count	Utm-Top-Virus	Traffic
Web Category with Highest Bandwidth	Web filtering category with the highest bandwidth usage	Top-Web-Category-by-Bandwidth	Web Filter
Web Category with Highest Session Count	Web filtering category with the highest session count	Top-Web-Category-by-Sessions	Web Filter
Website with Highest Bandwidth	Website with the highest bandwidth usage	Top-Web-Sites-by-Bandwidth	Web Filter
Website with Highest Session Count	Website with the highest session count	Top-Web-Sites-by-Sessions	Web Filter