



FortiSwitchOS - Log Reference

Version 6.4.5

FORTINET DOCUMENT LIBRARY

<https://docs.fortinet.com>

FORTINET VIDEO GUIDE

<https://video.fortinet.com>

FORTINET BLOG

<https://blog.fortinet.com>

CUSTOMER SERVICE & SUPPORT

<https://support.fortinet.com>

FORTINET TRAINING & CERTIFICATION PROGRAM

<https://www.fortinet.com/support-and-training/training.html>

NSE INSTITUTE

<https://training.fortinet.com>

FORTIGUARD CENTER

<https://fortiguard.com/>

END USER LICENSE AGREEMENT

<https://www.fortinet.com/doc/legal/EULA.pdf>

FEEDBACK

Email: techdoc@fortinet.com



December 14, 2020

FortiSwitchOS 6.4.5 Log Reference

11-645-684431-20201214

TABLE OF CONTENTS

Change log	9
Introduction	10
Link log messages	11
Physical port active or inactive trunk member	11
DMI port changed	11
Trunk status	11
Loopback error	12
ICL ACL change	12
An MCLAG peer lost	12
Model mismatch of MCLAG peers	13
Model mismatch of MCLAG peers fixed	13
Software mismatch of MCLAG peers	13
Software mismatch of MCLAG peers fixed	14
One MCLAG peer link up	14
All MCLAG peer links down	14
MCLAG peer misconfigured	15
MCLAG peer misconfigured fixed	15
MCLAG misconfigured	15
MAC addresses unsynchronized in MCLAG peers	15
Switch port up	16
Switch port down	16
Switch interface link changed	16
Miscellaneous log messages	18
NTP server unreachable	18
NTP server reachable	18
NTP server resolvable	18
NTP server unresolvable	19
PoE log messages	20
PoE controller resynchronizing	20
PoE controller resynchronized	20
PoE system mask set	20
PoE port settings restored	21
PoE disabled on overloaded port	21
PoE guard band and power budget set	21
PoE settings saved	21
PoE factory reset	22
PoE unit test	22
PoE negotiation in LLDP-MED configuration	22
PoE port temperature exceeded threshold	23
Router log messages	24
Layer-3 hardware routing table full	24

Layer-3 egress/host routing table full	24
Gateway group state change or routing information changed	24
Router out of memory	25
Interface cannot be found	25
Interface uses Mobile IPv6 extensions	25
MinRtrAdvInterval or MaxRtrAdvInterval out of range	26
AdvLinkMTU out of range or too small	26
AdvReachableTime is too small	27
AdvCurHopLimit is too big	27
AdvCurHopLimit is out of range	27
HomeAgentLifetime out of range	28
AdvHomeAgentFlag not set	28
Prefix length too long	28
AdvValidLifetime less than AdvPreferredLifetime	29
RA daemon failed to create IPv6 socket	29
RA daemon failed to set IPv6 options	29
RA daemon failed to create query	30
RA daemon internal error	30
RA daemon cannot find a virtual interface	30
RA daemon unloaded or reloaded interface	31
RA daemon received packet without packet information	31
RA daemon received ICMPv6 packet with invalid length	31
RA daemon received unwanted ICMPv6 packet	32
RA daemon received ICMPv6 RA packet with invalid length	32
RA daemon received ICMPv6 RA packet with non-link-local source address	32
RA daemon received ICMPv6 RS packet with invalid length	33
RA daemon received ICMPv6 RS or RA packet with invalid code	33
RA daemon received ICMPv6 RS or RA packet with invalid hop limit	33
AdvCurHopLimit does not agree with remote site	34
AdvManagedFlag does not agree with remote site	34
AdvOtherConfigFlag does not agree with remote site	34
AdvReachableTime does not agree with remote site	35
Local AdvRetransTimer does not agree with remote site	35
RA daemon found extra data in RA packet	35
RA daemon found RA packet without option data	36
RA packet option length greater than total length	36
AdvLinkMTU does not agree with remote site	36
AdvValidLifetime does not agree with remote site	37
AdvPreferredLifetime does not agree with remote site	37
RA daemon found invalid option in RA packet from remote site	37
RA daemon starting or exiting	38
RA daemon receive message failed	38
RA daemon received invalid IPv6 hop limit	38
RA daemon received invalid IPv6 packet information	39

RA daemon failed when checking membership in all-routers multicast group	39
RA daemon send message failed	39
STP log messages	40
Interface shut down because BPDUs detected	40
BPDU guard resetting interface	40
STP loop protection detected BPDU loss on port	40
STP loop protection detected BPDUs resumed on port	41
STP root guard unblocked port	41
STP root guard blocked role transition	41
STP root guard detected superior BPDUs received	42
STP root guard detected superior BPDUs stopped	42
STP enabled on interface	42
STP disabled on interface	43
STP edge port enabled on interface	43
STP edge port disabled on interface	43
STP instance changed role or state	44
Port changed state in RPVST+ domain	44
Switch log messages	45
802.1x-authenticated port using MAB is unauthorized	45
802.1x-authenticated port using MAB is authorized	45
No authentication on port	45
802.1x-authenticated port reset to unauthorized mode	46
802.1x-authenticated port not authorized	46
RADIUS CoA disconnected the 802.1x-authenticated session	46
RADIUS CoA bounced the 802.1x-authenticated port	47
RADIUS CoA disabled the 802.1x-authenticated port	47
RADIUS CoA reauthorized the 802.1x-authenticated session	47
RADIUS CoA changed the 802.1x-authenticated session timeout	47
Maximum number of MAC sessions for system exceeded	48
MAC session counter is not synchronized	48
Dynamic ARP inspection messages	48
DHCP-snooping messages	49
Flap guard resetting port	49
Flap guard shutting down port	50
Loop guard shutting down interface	50
Loop guard resetting interface	51
Network monitoring started	51
Network monitoring stopped	51
Sticky MAC entries messages	51
Sticky MAC entries cannot be saved	52
Static MAC entries exceeds the learning limit	52
Deleting or adding an access VLAN failed	53
Automatic mirror configuration failed	53
Automatic mirror configuration completed	53

Mirroring might be interrupted	54
Automatic mirror configuration stopping	54
FortiGate nonblocking authentication daemon crashed	54
New MAC address learned	55
MAC address moved	55
MAC address deleted	55
IGMP-snooping group not added	56
Switch controller log messages	57
Switch controller connected with FortiGate	57
Switch port joined FortiGate trunk	57
Switch port left FortiGate uplink	57
FortiLink messages	58
TPID value changed	58
Echo failures	58
Switch controller disconnected or restarted	59
User deleted ISL trunk	59
ISL timing out	59
Port joined ISL	60
Port left ISL	60
FortiGate uplink trunk not created	60
Port not added to FortiGate uplink trunk	61
Port not deleted from FortiGate uplink trunk	61
AC discovery type changed	61
Switch controller waiting for HTTP/HTTPS daemon	62
Switch controller log storage 75-percent full	62
System log messages	63
Alarm created	63
Alarm acknowledged	63
Domain name in alert email cannot be resolved	63
FortiSwitch unit started	64
FortiSwitch unit rebooted or shut down	64
Daily FortiSwitch unit restart	64
CA certificate will be automatically updated	65
Local certificate will be automatically regenerated	65
Certificate failed to automatically update	65
Certificate failed to automatically regenerate	65
PKCS #12 certificate imported	66
CRL update requested	66
Power supply restored	66
Power supply failed	67
System configuration changed	67
System configuration changed using the GUI	67
System configuration restored	68
Restoring the configuration failed	68

System reset to factory settings	68
Global setting changed	69
System configuration backed up	69
Configuration revision uploaded	70
Database revision deleted	70
Revision item deleted from flash disk	70
Command failed	71
Adding a new entry failed	71
Failed to back up system configuration	71
Daemon started	72
Daemon shut down	72
Log information from the DHCP client module daemon	72
IP address too small	73
DHCP statistics	73
DHCP server used all of its leases	73
DHCP server used most of its leases	74
DHCP server sends a DDNS add query	74
DHCP server sends a DDNS delete query	74
DHCP server blocked the DHCP client	74
DHCP server sends a DHCP acknowledgment	75
DHCP server receives a DHCP release	75
Administrator logged in successfully	75
Administrator failed to log in	76
Administrator logged out	76
Admin login disabled because of login failures	76
Partitioning or formatting error	77
Log disk failure imminent	77
Lack of flash space	77
Disk formatting requested	78
Disk storage set up	78
Disk storage entry deleted	78
Fan failure detected	78
Fan tray not detected	79
Fan tray detected	79
Fan tray detection failed	79
Fan resumed working	80
Encryption failed	80
Decryption failed	80
Cannot extract FortiSwitch Private Key	81
FortiSwitch Cloud started or global time setting changed	81
FortiSwitch Cloud stopped	81
SSL connection to FortiSwitch Cloud established	82
SSL connection to FortiSwitch Cloud down	82
SSL connection to FortiSwitch Cloud not established	82

Packet capture stopped because of lack of storage	83
Corrupt MAC packet detected	83
Firmware image restored	83
Firmware image failures	84
Firmware image backed up to flash disk	84
New local user added	85
Setting changed for local user	85
Changes to static route or link monitor state	85
RADIUS IPC error	86
User viewed memory logs	86
Log full	86
Disk has rolled log maximum number of times	86
Log disk full	87
Log rotation	88
Logs cleared	88
Rolled log files deleted	88
User failed to view logs	89
Daily logging quota full	89
Logging file downloaded	89
Log backed up	89
Backing up all logs failed	90
All logs backed up	90
Log backup failed	90
Warning from monitor-and-alert daemon	91
Log test	91
PSU changes to good state	91
PSU changes to bad state	92
PSU connected	92
PSU not connected	92
PSU 1 is down	93
PSU 1 is up	93
PSU 2 is down	93
PSU 2 is up	93
Corrupt MAC packet detected or negotiation failed	94
Fan tray status	94
Alarm testing	95
Learning-limit violations reset	95
Learning-limit violations deleted	95
Learning-limit violation log enabled	96
Learning-limit violation log disabled	96
Learning limit exceeded	96
VM license file added	97
Failed to add VM license file	97
No more IP source guard entries can be added	97

Change log

Date	Change Description
December 14, 2020	Initial document release

Introduction

Logging is an integral component of the FortiSwitch system. This document provides the FortiSwitch event log messages and their meanings, organized by category.

Link log messages

The log messages in this chapter are for link issues.

Physical port active or inactive trunk member

ID	1000
Type	Event log
Subtype	Link
Severity	Notice
Message	<ul style="list-style-type: none">• msg="Physical port (<port_name>) became active member of trunk (<trunk_name>)"• msg="Physical port (<port_name>) became non-active member of trunk (<trunk_name>)"• msg="<port_name>"
Meaning	The specified physical port is now an active or inactive member of the specified trunk.

DMI port changed

ID	1050
Type	Event log
Subtype	Link
Severity	Notice
Message	msg="<port_name>"
Meaning	There was a change in the physical port used for the diagnostic monitoring interface (DMI).

Trunk status

ID	1200
Type	Event log
Subtype	Link

Severity	Warning
Message	msg=msg=\"<port_name>\"
Meaning	One of the members of a trunk is down.

Loopback error

ID	1250
Type	Event log
Subtype	Link
Severity	Warning
Message	msg=msg=\"An illegal loopback occurred on adapter (<port_name>)\nCheck the configuration to verify that all adapters are connected to 802.3ad compliant switch ports.\"
Meaning	A loopback occurred in a link aggregation group (LAG).

ICL ACL change

ID	1300
Type	Event log
Subtype	Link
Severity	Notice
Message	msg=msg=\"MCLAG: ICL ACL change ingress-port-bitmap=<port_name>, egress-block-port-bitmap=<port_name>\"
Meaning	There was a change in the access control list (ACL) policy used by the MCLAG ICL trunk.

An MCLAG peer lost

ID	1301
Type	Event log
Subtype	Link
Severity	Notice
Message	msg=msg=\"MCLAG: lost peer info for trunk(<trunk_name>) peer-timeout(<time>) sb(<split-brain>)\"

Meaning	The FortiSwitch unit cannot detect one of the MCLAG peers.
----------------	--

Model mismatch of MCLAG peers

ID	1302
Type	Event log
Subtype	Link
Severity	Warning
Message	msg=\"MCLAG: **Unsupported config, peer model mismatch local-model(<switch1_model>) peer-model(<peer_switch2_model>)\"
Meaning	The MCLAG peers are different FortiSwitch models.

Model mismatch of MCLAG peers fixed

ID	1303
Type	Event log
Subtype	Link
Severity	Notice
Message	msg=\"MCLAG: Cleared **Unsupported config, peer model mismatch local-model(<switch1_model>) peer-model(<switch2_model>)\"
Meaning	The MCLAG peers have been changed to be the same FortiSwitch model.

Software mismatch of MCLAG peers

ID	1304
Type	Event log
Subtype	Link
Severity	Warning
Message	msg=\"MCLAG: **peer software mismatch local-software(<switch1_firmware>) peer-software (<switch2_firmware>)\"
Meaning	The MCLAG peers are running different versions of FortiSwitchOS.

Software mismatch of MCLAG peers fixed

ID	1305
Type	Event log
Subtype	Link
Severity	Notice
Message	msg="MCLAG: Cleared **peer software mismatch local-software(<switch1_firmware>) peer-software(<switch2_firmware>)\"
Meaning	The MCLAG peers are now running the same version of FortiSwitchOS.

One MCLAG peer link up

ID	1306
Type	Event log
Subtype	Link
Severity	Notice
Message	msg="MCLAG: <trunk_name> at least one peer link up\"
Meaning	One or more of the MCLAG peer links is up.

All MCLAG peer links down

ID	1307
Type	Event log
Subtype	Link
Severity	Notice
Message	msg="MCLAG: <trunk_name> all peer link down\"
Meaning	All MCLAG peer links are down.

MCLAG peer misconfigured

ID	1308
Type	Event log
Subtype	Link
Severity	Notice
Message	msg=\"MCLAG: <trunk_name> peer misconfigured\"
Meaning	One of the MCLAG peers is misconfigured.

MCLAG peer misconfigured fixed

ID	1309
Type	Event log
Subtype	Link
Severity	Notice
Message	msg=\"MCLAG: <trunk_name> peer misconfiguration cleared\"
Meaning	The MCLAG peers are configured correctly now.

MCLAG misconfigured

ID	1310
Type	Event log
Subtype	Link
Severity	Critical
Message	msg=\"MCLAG: misconfigured out of LAG table entry\"
Meaning	The MCLAG is misconfigured.

MAC addresses unsynchronized in MCLAG peers

ID	1311
-----------	------

Type	Event log
Subtype	Link
Severity	Warning
Message	msg=\"MCLAG:<trunk_name> ports=<port_name> MAC mismatch local-mac= peer-mac=\"
Meaning	MAC addresses in MCLAG peers are not synchronized.

Switch port up

ID	1400
Type	Event log
Subtype	Link
Severity	Information
Message	msg=\"<switch_serial_number> switch port <port_name> has come up\"
Meaning	The specified FortiSwitch port is now up.

Switch port down

ID	1401
Type	Event log
Subtype	Link
Severity	Information
Message	msg=\"<switch_serial_number> switch port <port_name> has gone down\"
Meaning	The specified FortiSwitch port is now down.

Switch interface link changed

ID	1450
Type	Event log
Subtype	Link
Severity	Notice

Message	msg=\"interface <interface_name> link status is <status>\"
Meaning	The status of the specified interface link has changed.

Miscellaneous log messages

The log messages in this chapter are for miscellaneous issues.

NTP server unreachable

ID	34001
Type	Event log
Subtype	unknown
Severity	Notice
Message	msg="The <user_name> ntp server, <server_name> (<IP_address>), is determined <access_status> at <date_time>"
Meaning	The status of the NTP server has changed to unreachable.

NTP server reachable

ID	34002
Type	Event log
Subtype	unknown
Severity	Notice
Message	msg="The <user_name> ntp server, <server_name> (<IP_address>), is determined <access_status> at <date_time>"
Meaning	The status of the NTP server has changed to reachable.

NTP server resolvable

ID	34003
Type	Event log
Subtype	unknown

Severity	Notice
Message	msg="The <user_name> ntp server, <server_name> (<IP_address>), is determined <access_status> at <date_time>"
Meaning	The status of the NTP server has changed to resolvable.

NTP server unresolvable

ID	34004
Type	Event log
Subtype	unknown
Severity	Notice
Message	msg="The <user_name> ntp server, <server_name> (<IP_address>), is determined <access_status> at <date_time>"
Meaning	The status of the NTP server has changed to unresolvable.

PoE log messages

The log messages in this chapter are for power over Ethernet (PoE) issues.

PoE controller resynchronizing

ID	2000
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\" POE controller resync start.\\\"
Meaning	The PoE controller has started to resynchronize.

PoE controller resynchronized

ID	2001
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\" POE controller resync done.\\\"
Meaning	The PoE controller has finished resynchronizing.

PoE system mask set

ID	2002
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\" system mask <IP_address_netmask> has been set\\\"
Meaning	The PoE system mask was set.

PoE port settings restored

ID	2003
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\"PoE port settings been restored\"
Meaning	The PoE port settings were restored.

PoE disabled on overloaded port

ID	2004
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\"Port <port_name> Overload state. POE disabled\"
Meaning	PoE was disabled on the specified physical port because it was overloaded.

PoE guard band and power budget set

ID	2005
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\" guard band <number_of_Watts> and power budget <number_of_Watts> been set\"
Meaning	The PoE guard band and power budget were set globally.

PoE settings saved

ID	2006
-----------	------

Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\"PoE settings been saved\"
Meaning	The PoE settings were saved.

PoE factory reset

ID	2007
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\"PoE been factory reset\"
Meaning	The PoE settings were reset to factory default settings.

PoE unit test

ID	2008
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\" unit test been performed\"
Meaning	A PoE unit test was performed.

PoE negotiation in LLDP-MED configuration

ID	2010
Type	Event log
Subtype	PoE
Severity	Warning or information

Message	msg=\lldp poe info received from <port_name>\"
Meaning	PoE negotiation in LLDP- MED has been enabled or disabled for the specified port.

PoE port temperature exceeded threshold

ID	2011
Type	Event log
Subtype	PoE
Severity	Warning
Message	msg=\<temperature1 temperature2 temperature3 temperature4 temperature5 temperature6 temperature7 temperature8 temperature9 temperature10 temperature11 temperature12> \"
Meaning	The temperature sensor detected that the temperature specified PoE port exceeded the set threshold.

Router log messages

The log messages in this chapter are for router issues.

Layer-3 hardware routing table full

ID	3000
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=Hardware table full.Packets may get either covered by a less specific prefix or software forwarded\n
Meaning	The layer-3 routing table used for hardware-based layer-3 forwarding is full. Software-based forwarding or a less specific prefix will be used for packets.

Layer-3 egress/host routing table full

ID	3001
Type	Event log
Subtype	Router
Severity	Error
Message	msg=\"L3 egress/host table full\"
Meaning	The layer-3 egress/host routing table is full.

Gateway group state change or routing information changed

ID	3050
Type	Event log
Subtype	Router

Severity	Critical
Message	<ul style="list-style-type: none">• msg=\<code>"The status of <interface_name> for gateway group <IP_address> is <state>"</code>• msg=\<code>"<state>"</code>
Meaning	<ul style="list-style-type: none">• The state of the gateway group has changed.• The routing information has changed because the gateway has changed to up or down.

Router out of memory

ID	3100
Type	Event log
Subtype	Router
Severity	Critical
Message	msg=\ <code>"ravdv_iface_set_config() finds a pointer pointing to a wrong addressInterface <interface_name> Out of memory in <IP_address>"</code>
Meaning	The router is out of memory for the specified interface.

Interface cannot be found

ID	3101
Type	Event log
Subtype	Router
Severity	Critical
Message	msg=\ <code>"ravdv_iface_same_config() cannot find the corresponding interface by nameInterface <switch_interface_name> not found in <IP_address>"</code>
Meaning	The router cannot find the specified interface.

Interface uses Mobile IPv6 extensions

ID	3102
Type	Event log
Subtype	Router

Severity	Information
Message	msg=\\"An interface uses Mobile IPv6 extensionsusing Mobile IPv6 extensions\\"
Meaning	An interface uses Mobile IPv6 extensions.

MinRtrAdvInterval or MaxRtrAdvInterval out of range

ID	3103
Type	Event log
Subtype	Router
Severity	Critical
Message	<ul style="list-style-type: none"> • msg=\\\"MinRtrAdvInterval using Mobile Ipv6 extension is out of rangeMinRtrAdvInterval for <interface_name> must be between <value_1> and <value_2>\\\" • msg=\\\"MinRtrAdvInterval is out of rangeMinRtrAdvInterval must be between <value_1> and <value_2> for <interface_name>\\\" • msg=\\\"MaxRtrAdvInterval using Mobile Ipv6 extension is out of rangeMaxRtrAdvInterval for <interface_name> must be between <value_1> and <value_2>\\\" • msg=\\\"MaxRtrAdvInterval is out of rangeMaxRtrAdvInterval must be between <value_1> and <value_2> for <interface_name>\\\"
Meaning	The MinRtrAdvInterval or MaxRtrAdvInterval value is out of the specified range and must be changed.

AdvLinkMTU out of range or too small

ID	3105
Type	Event log
Subtype	Router
Severity	Critical
Message	<ul style="list-style-type: none"> • msg=\\\"AdvLinkMTU is out of rangeAdvLinkMTU must be zero or between <value_1> and <value_2> for <interface_name>\\\" • msg=\\\"AdvLinkMTU is too smallAdvLinkMTU must be zero or greater than <value> for <interface_name>\\\"
Meaning	The AdvLinkMTU value is out of range or too small and must be changed.

AdvReachableTime is too small

ID	3106
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="AdvReachableTime is too small AdvReachableTime must be less than <value> for <interface_name>"
Meaning	The AdvReachableTime value is too small and must be changed.

AdvCurHopLimit is too big

ID	3107
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="AdvCurHopLimit in Router Advertisement packet is too big AdvCurHopLimit must not be greater than <value> for <interface_name>"
Meaning	The AdvCurHopLimit value for the router advertisement packet is too large and must be changed.

AdvCurHopLimit is out of range

ID	3108
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="AdvCurHopLimit in Router Advertisement packet is out of range AdvDefaultLifetime for <interface_name> must be zero or between <value1> and <value2>"
Meaning	The AdvCurHopLimit value for the router advertisement packet is out of range and must be changed.

HomeAgentLifetime out of range

ID	3109
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="HomeAgentLifetime in Router Advertisement packet is out of rangeHomeAgentLifetime must be between <value_1> and <value_2> for <interface_name>\"
Meaning	The HomeAgentLifetime value for the router advertisement packet is out of range and must be changed.

AdvHomeAgentFlag not set

ID	3110
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="AdvHomeAgentFlag HomeAgentLifetime in Router Advertisement packet must be set with HomeAgentInfoAdvHomeAgentFlag must be set with HomeAgentInfo\"
Meaning	The AdvHomeAgentFlag has not been set.

Prefix length too long

ID	3111
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="prefix length is too longinvalid prefix length for <interface_name>\"
Meaning	The prefix length is invalid because it is too long.

AdvValidLifetime less than AdvPreferredLifetime

ID	3112
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="AdvValidLifetime is less than AdvPreferredLifetimeAdvValidLifetime must be greater than AdvPreferredLifetime for <interface_name>"
Meaning	The value for AdvValidLifetime must be greater than the value for AdvPreferredLifetime.

RA daemon failed to create IPv6 socket

ID	3113
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="radvd failed to create an IPv6 socket <IPv6_address>"
Meaning	The router advertisement (RA) daemon failed to create an IPv6 socket <IPv6_address>.

RA daemon failed to set IPv6 options

ID	3114
Type	Event log
Subtype	Router
Severity	Critical
Message	<ul style="list-style-type: none">• msg="Radvd failed to set IPV6_RECVPKTINFO option <IPv6_address>"• msg="Radvd failed to set IPV6_PKTINFO option: <IPv6_address>"• msg="Radvd failed to set IPV6_CHECKSUM option <IPv6_address>"• msg="Radvd failed to set IPV6_UNICAST_HOPS option <IPv6_address>"• msg="Radvd failed to set IPV6_MULTICAST_HOPS option: <IPv6_address>"• msg="Radvd failed to set IPV6_RECVHOPLIMIT option: <IPv6_address>"• msg="Radvd failed to set IPV6_HOPLIMIT option <IPv6_address>"• msg="Radvd failed to set ICMPV6_FILTER option <IPv6_address>"
Meaning	The RA daemon failed to set the specified IPv6 option.

RA daemon failed to create query

ID	3116
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="Radvd cannot create query to interface by using cmf_query_create()Can not create query to interface at <IP_address>\"
Meaning	The RA daemon failed to create the query for the interface.

RA daemon internal error

ID	3117
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="Radvd occurs an internal error when it uses cmf_query_for_each()\"
Meaning	There is an internal error when the RA daemon sends a query.

RA daemon cannot find a virtual interface

ID	3118
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="Radvd failed to find a virtual interface by interface indexInterface <interface_name> not found in the list!\"
Meaning	The router advertisement daemon cannot find the specified virtual interface.

RA daemon unloaded or reloaded interface

ID	3119
Type	Event log
Subtype	Router
Severity	Information
Message	<ul style="list-style-type: none">msg=\"Interface <interface_name> unloaded!\"msg=\"Radvd reloads a specific interface Interface <interface_name> reloaded!\"
Meaning	The RA daemon unloaded or reloaded the specified interface.

RA daemon received packet without packet information

ID	3120
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"Radvd received a packet with no pkt_info received packet with no pkt_info!\"
Meaning	The RA daemon received a packet that did not include any packet information.

RA daemon received ICMPv6 packet with invalid length

ID	3121
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"Radvd received an icmpv6 packet with invalid length received icmpv6 packet with invalid length: <packet_length>\"
Meaning	The RA daemon received an ICMPv6 packet with an invalid length.

RA daemon received unwanted ICMPv6 packet

ID	3122
Type	Event log
Subtype	Router
Severity	Critical
Message	msg=\"Radvd received an unwanted type of icmpv6 packeticmpv6 filter failed\"
Meaning	The ICMPv6 filter failed, and the RA daemon received an unwanted type of ICMPv6 packet.

RA daemon received ICMPv6 RA packet with invalid length

ID	3123
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"Radvd received icmpv6 RA packet with invalid lengthreceived icmpv6 RA packet with invalid length: <packet_length>\"
Meaning	The RA daemon received an ICMPv6 RA packet with an invalid length.

RA daemon received ICMPv6 RA packet with non-link-local source address

ID	3124
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"Radvd received icmpv6 RA packet with non-linklocal source addressreceived icmpv6 RA packet with non-linklocal source address\"
Meaning	The RA daemon received an ICMPv6 RA packet with a non-link-local source address.

RA daemon received ICMPv6 RS packet with invalid length

ID	3125
Type	Event log
Subtype	Router
Severity	Warning
Message	msg="Radvd received icmpv6 RS packet with invalid lengthreceived icmpv6 RS packet with invalid length: <packet_length>"
Meaning	The router advertisement daemon received an ICMPv6 router solicitation (RS) packet with an invalid length.

RA daemon received ICMPv6 RS or RA packet with invalid code

ID	3126
Type	Event log
Subtype	Router
Severity	Warning
Message	msg="Radvd received icmpv6 RS/RA packet with invalid codereceived icmpv6 RS/RA packet with invalid code: <code>"
Meaning	The RA daemon received an ICMPv6 RS or RA packet with an invalid code.

RA daemon received ICMPv6 RS or RA packet with invalid hop limit

ID	3127
Type	Event log
Subtype	Router
Severity	Warning
Message	msg="Radvd received icmpv6 RS/RA packet with wrong hoplimitreceived RS or RA with invalid hoplimit <hop_limit> from <interface_name>"
Meaning	The RA daemon received an ICMPv6 RS or RA packet with the wrong hop limit.

AdvCurHopLimit does not agree with remote site

ID	3128
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"AdvCurHopLimit on our interface does not agree with a remote siteour AdvCurHopLimit on <local_value> doesn't agree with <remote_value>\"
Meaning	The value for AdvCurHopLimit on the local interface is different than the value on a remote interface.

AdvManagedFlag does not agree with remote site

ID	3129
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"AdvManagedFlag on our interface does not agree with a remote siteour AdvManagedFlag on <local_value> doesn't agree with <remote_value>\"
Meaning	The value for AdvManagedFlag on the local interface is different than the value on a remote interface.

AdvOtherConfigFlag does not agree with remote site

ID	3130
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"AdvOtherConfigFlag on our interface does not agree with a remote siteour AdvOtherConfigFlag on <local_value> doesn't agree with <remote_value>\"
Meaning	The value for AdvOtherConfigFlag on the local interface is different than the value on a remote interface.

AdvReachableTime does not agree with remote site

ID	3131
Type	Event log
Subtype	Router
Severity	Warning
Message	msg="AdvReachableTime on our interface does not agree with a remote siteour AdvReachableTime on <local_value> doesn't agree with <remote_value>"
Meaning	The value for AdvReachableTime on the local interface is different than the value on a remote interface.

Local AdvRetransTimer does not agree with remote site

ID	3132
Type	Event log
Subtype	Router
Severity	Warning
Message	msg="AdvRetransTimer on our interface does not agree with a remote siteour AdvRetransTimer on <local_value> doesn't agree with <remote_value>"
Meaning	The value for AdvRetransTimer on the local interface is different than the value on a remote interface.

RA daemon found extra data in RA packet

ID	3133
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="Radvd finds extra data in RA packettrailing garbage in RA on <IP_address> from <IP_address>"
Meaning	The RA daemon found extra data in the RA packet.

RA daemon found RA packet without option data

ID	3134
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="Radvd finds a RA packet with no option datazero length option in RA on <IP_address> from <IP_address>\"
Meaning	The RA daemon found an RA packet without any option data.

RA packet option length greater than total length

ID	3135
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="option length is greater than total length in RA packetoption length greater than total length in RA on <IP_address> from <IP_address>\"
Meaning	The option length is greater than the total length in the RA packet.

AdvLinkMTU does not agree with remote site

ID	3136
Type	Event log
Subtype	Router
Severity	Warning
Message	msg="AdvLinkMTU on our interface does not agree with a remote siteour AdvLinkMTU on <local_value> doesn't agree with <remote_value>\"
Meaning	The value for AdvLinkMTU on the local interface is different than the value on a remote interface.

AdvValidLifetime does not agree with remote site

ID	3137
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"AdvValidLifetime on our interface does not agree with a remote siteour AdvValidLifetime on <IP_address> for <local_value> doesn't agree with <remote_value>\"
Meaning	The value for AdvValidLifetime on the local interface is different than the value on a remote interface.

AdvPreferredLifetime does not agree with remote site

ID	3138
Type	Event log
Subtype	Router
Severity	Warning
Message	msg=\"AdvPreferredLifetime on our interface does not agree with a remote siteour AdvPreferredLifetime on <IP_address> for <local_value> doesn't agree with <remote_value>\"
Meaning	The value for AdvPreferredLifetime on the local interface is different than the value on a remote interface.

RA daemon found invalid option in RA packet from remote site

ID	3139
Type	Event log
Subtype	Router
Severity	Critical
Message	msg=\"Radvd finds an invalid option in RA packet from a remote siteinvalid option <option_name> in RA on <local_interface> from <remote_interface>\"
Meaning	The RA daemon found an invalid option in an RA packet from a remote site.

RA daemon starting or exiting

ID	3140
Type	Event log
Subtype	Router
Severity	Information
Message	<ul style="list-style-type: none">msg="Radvd daemon is ready to serve radvd started\"msg="Exit signal (<signal>) rcvd. Radvd daemon is exiting.\"
Meaning	The RA daemon is ready to start or is exiting.

RA daemon receive message failed

ID	3141
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="Recvmsg() in radvd failed recvmsg: <date_time>\"
Meaning	The RA daemon's receive message failed.

RA daemon received invalid IPv6 hop limit

ID	3142
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="Radvd received a packet with a wrong IPV6_HOPLIMITreceived a bogus IPV6_HOPLIMIT from the kernel! len=<packet_length>, data=<hop_limit>\"
Meaning	The RA daemon received a packet with the wrong IPv6 hop limit.

RA daemon received invalid IPv6 packet information

ID	3143
Type	Event log
Subtype	Router
Severity	Critical
Message	msg="Radvd received a packet with a wrong IPV6_PKTINFOreceived a bogus IPV6_PKTINFO from the kernel! len=<packet_length>, index=<packet_index>\\"
Meaning	The RA daemon received a packet with the wrong IPv6 packet information.

RA daemon failed when checking membership in all-routers multicast group

ID	3144
Type	Event log
Subtype	Router
Severity	Warning
Message	msg="Radvd failed to check whether we've joined the all-routers multicast groupproblem checking all-routers membership on <IP_address>\\"
Meaning	The RA daemon failed when it was checking membership in the all-routers multicast group.

RA daemon send message failed

ID	3145
Type	Event log
Subtype	Router
Severity	Warning
Message	msg="sendmsg () in radvd failedsendmsg: <date_time>\\"
Meaning	The RA daemon's send message failed.

STP log messages

The log messages in this chapter are for Spanning Tree Protocol (STP) issues.

Interface shut down because BPDUs detected

ID	8000
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"BPDU Guard: BPDU detected on <interface_name>. Shutting down <interface_name>.\"
Meaning	Bridge protocol data units (BPDUs) were detected on the specified interface, which will be shut down.

BPDU guard resetting interface

ID	8001
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"BPDU Guard: Resetting <interface_name>.\"
Meaning	BPDU guard detected BPDUs on the specified interface, which will be reset.

STP loop protection detected BPDU loss on port

ID	8100
Type	Event log
Subtype	Spanning tree
Severity	Notice

Message	msg=\"STP Loop Protection: BPDU loss detected on Port <port_name> (changed state to discarding)\"
Meaning	The STP loop-protection feature detected BPDU loss on the specified port.

STP loop protection detected BPDUs resumed on port

ID	8101
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"STP Loop Protection: BPDUs resumed on Port <port_name>\"
Meaning	The STP loop-protection feature detected that BPDUs have resumed on the specified port.

STP root guard unblocked port

ID	8102
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"STP Root Guard: Un-blocking Port <port_name> (STP instance <STP_instance_ID>)\"
Meaning	The STP root-guard feature unblocked the specified port.

STP root guard blocked role transition

ID	8103
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"STP Root Guard: Blocking Role Transition on Port<port_name> (STP instance <STP_instance_ID>)\"
Meaning	The STP root-guard feature blocked a change in the role on the specified port.

STP root guard detected superior BPDUs received

ID	8150
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg="STP Root Guard: Superior BPDUs received on Port <port_name> (STP instance <STP_instance_ID>)"
Meaning	The STP root-guard feature detected that the specified port received superior BPDUs.

STP root guard detected superior BPDUs stopped

ID	8151
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg="STP Root Guard: Superior BPDUs stopped on Port <port_name> (STP instance <STP_instance_ID>)"
Meaning	The STP root-guard feature stopped the specified port from receiving superior BPDUs.

STP enabled on interface

ID	8250
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg="user <user_name> enabled STP on <FortiSwitch_serial_number> interface <interface_name>"
Meaning	The specified user enabled STP on the specified switch interface.

STP disabled on interface

ID	8251
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"user <user_name> disabled STP on <FortiSwitch_serial_number> interface <interface_name>\"
Meaning	The specified user enabled STP on the specified switch interface.

STP edge port enabled on interface

ID	8252
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"user <user_name> enabled STP on <FortiSwitch_serial_number> interface <interface_name>\"
Meaning	The specified user enabled an STP edge port on the specified switch interface.

STP edge port disabled on interface

ID	8253
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"user <user_name> disabled STP on <FortiSwitch_serial_number> interface <interface_name>\"
Meaning	The specified user disabled an STP edge port on the specified switch interface.

STP instance changed role or state

ID	8255
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	<ul style="list-style-type: none">• msg=\"<port_name> port <STP_instance_ID> instance <user_name> changed role from <old_role> to <new_role>\"• msg=\"<port_name> port <STP_instance_ID> instance <user_name> changed state from <old_state> to <new_state>\"
Meaning	The specified user changed the role or state of the STP instance.

Port changed state in RPVST+ domain

ID	8256
Type	Event log
Subtype	Spanning tree
Severity	Notice
Message	msg=\"STP RPVST: port id <port_name> state changed to <state>\"
Meaning	The specified port changed state in a per-VLAN RSTP (Rapid PVST+ or RPVST+) domain.

Switch log messages

The log messages in this chapter are issues related to switching functionality.

802.1x-authenticated port using MAB is unauthorized

ID	10000
Type	Event log
Subtype	Switch
Severity	Notice
Message	msg=\"mac: on port <port_name> MAB mode=<status> unauthorized \"
Meaning	An 802.1x-authenticated port using MAC authentication bypass (MAB) is unauthorized.

802.1x-authenticated port using MAB is authorized

ID	10001
Type	Event log
Subtype	Switch
Severity	Notice
Message	msg=\"user: <user_name> mac: <MAC_address> on port<port_name> <MAB> mode=<mode> authorized set <authorization>=<status> \"
Meaning	An 802.1x-authenticated port is authorized.

No authentication on port

ID	10002
Type	Event log
Subtype	Switch
Severity	Notice

Message	No authentication on port <port_name>
Meaning	The dynamic VLAN identifier and MAC address already exist in the static MAC address entry table.

802.1x-authenticated port reset to unauthorized mode

ID	10003
Type	Event log
Subtype	Switch
Severity	Notice
Message	msg=\"802.1x port <port_name> reset to unauthorized mode and native_vlan =<VLAN_ID>\"
Meaning	The 802.1x-authenticated port was reset to unauthorized mode and to the specified native VLAN identifier.

802.1x-authenticated port not authorized

ID	10004
Type	Event log
Subtype	Switch
Severity	Notice
Message	msg=\"user:<user_name> mac: <MAC_address> on port <port_name> <MAB> mode=<mode> unauthorized set <authorization_status>=<failure>\"
Meaning	The 802.1x-authenticated port is not authorized.

RADIUS CoA disconnected the 802.1x-authenticated session

ID	10005
Type	Event log
Subtype	Switch
Severity	Notice
Message	msg=\"802.1x port session <MAC_address>: disconnected\"
Meaning	RADIUS change of authorization (CoA) was used to disconnect the 802.1x-authenticated session.

RADIUS CoA bounced the 802.1x-authenticated port

ID	10006
Type	Event log
Subtype	Switch
Severity	Notice
Message	<ul style="list-style-type: none">• msg=\"802.1x port<port_name> link down\\\"• msg=\"802.1x port<port_name> link up.\\\"
Meaning	RADIUS CoA was used to bounce the 802.1x-authenticated port.

RADIUS CoA disabled the 802.1x-authenticated port

ID	10007
Type	Event log
Subtype	Switch
Severity	Notice
Message	msg=\"802.1x port <port_name> link down\\\"
Meaning	RADIUS CoA was used to disable the 802.1x-authenticated port.

RADIUS CoA reauthorized the 802.1x-authenticated session

ID	10008
Type	Event log
Subtype	Switch
Severity	Notice
Message	msg=\"802.1x port session <MAC_address>: re-auth\\\"
Meaning	RADIUS CoA was used to reauthorize the 802.1x-authenticated session.

RADIUS CoA changed the 802.1x-authenticated session timeout

ID	10009
-----------	-------

Type	Event log
Subtype	Switch
Severity	Notice
Message	msg=\"802.1x port session <MAC_address>: session timeout change:<timeout_value>:\"
Meaning	RADIUS CoA was used to change the timeout setting of the 802.1x-authenticated session.

Maximum number of MAC sessions for system exceeded

ID	10010
Type	Event log
Subtype	Switch
Severity	Notice
Message	Exceed system max MAC sessions.\n
Meaning	The maximum number of MAC sessions for the system was exceeded.

MAC session counter is not synchronized

ID	10011
Type	Event log
Subtype	Switch
Severity	Notice
Message	ftnt_fswitch_resync_system_mac_session used mac session counter :<counter_ID>: not match with STA. Need to flush all interfaces.\n
Meaning	The MAC session counter is not synchronized. All interfaces must be flushed.

Dynamic ARP inspection messages

ID	10100
Type	Event log
Subtype	Switch

Severity	Warning
Message	<ul style="list-style-type: none"> • msg=" Arp-Insp-Drop: Source interface mismatch {mac=<MAC_address>, vlan=<VLAN_ID>, ip= <IP_address>}.\" • msg=" Arp-Insp-Drop: Source tuple lookup failed {mac=<MAC_address>, vlan=<VLAN_ID>, ip= <IP_address>}.\" • msg=" Arp-Insp-Drop: dest interface mismatch for {mac=<MAC_address>, vlan=<VLAN_ID>, ip= <IP_address>}.\" • msg=" Arp-Insp-Drop: Tuple lookup failed for vlan {mac=<MAC_address>, vlan=<VLAN_ID>, ip= <IP_address>}.\"
Meaning	<ul style="list-style-type: none"> • Dynamic ARP inspection (DAI) found the source IP-MAC-address binding to be invalid. • DAI failed to find the source IP-MAC-address binding. • DAI found the destination IP-MAC-address binding to be invalid. • DAI failed to find the VLAN identifier for the IP-MAC-address binding.

DHCP-snooping messages

ID	10200
Type	Event log
Subtype	Switch
Severity	Notice
Message	<ul style="list-style-type: none"> • msg="Snoop database file is corrupt. Not restoring db.\" • msg="Snoop6 database file is corrupt. Not restoring db.\" • msg="snoop dhcp-server database overflow. \" • msg="snoop database overflow. \" • msg="<switch_interface>" "<status> \" • msg="Dhcp-Snoop: Incoming intf is not same as learned intf {in-intf=<incoming_interface>, listed-intf=<learned_interface>}.\"
Meaning	<ul style="list-style-type: none"> • The DHCP-snooping database file is corrupt and cannot be restored. • The DHCPv6-snooping database file is corrupt and cannot be restored. • The DHCP-snooping server database has overflowed. • The DHCP-snooping client database has overflowed. • The interface settings have changed. • The incoming interface differs from the learned interface.

Flap guard resetting port

ID	10300
-----------	-------

Type	Event log
Subtype	Switch
Severity	Warning
Message	<ul style="list-style-type: none">• msg=\"Flap Guard: Reseting <port_name>.\"• msg=\"Flap Guard: Retain disabled (previously triggered), putting switch port <port_number> as up\"
Meaning	<ul style="list-style-type: none">• Flap guard is resetting the specified port so that port's state will be up.• Flap guard keeps the "triggered" setting for the port when the port's state is changed to up.

Flap guard shutting down port

ID	10301
Type	Event log
Subtype	Switch
Severity	Warning
Message	<ul style="list-style-type: none">• msg=\"Flap Guard: putting switch port <port_name> as down\"• msg=\"Flap Guard: Retaining previously triggered switch port setting for <port_name> as down\"
Meaning	<ul style="list-style-type: none">• Flap guard is shutting down the specified port.• Flap guard keeps the "triggered" setting for the port when the port is shut down.

Loop guard shutting down interface

ID	10400
Type	Event log
Subtype	Switch
Severity	Warning
Message	msg=\"Loop Guard: <loop detected or loop detected with MAC move over threshold> on <switch_interface>. Shutting down <switch_interface>.\"
Meaning	Loop guard is resetting the specified port.

Loop guard resetting interface

ID	10401
Type	Event log
Subtype	Switch
Severity	Warning
Message	msg=\"Loop Guard: Reseting <switch_interface>.\"
Meaning	Loop guard is resetting the specified port.

Network monitoring started

ID	10500
Type	Event log
Subtype	Switch
Severity	Warning
Message	msg=\"network monitoring started by user.\"
Meaning	A user started network monitoring.

Network monitoring stopped

ID	10501
Type	Event log
Subtype	Switch
Severity	Warning
Message	msg=\"network monitoring stopped by user.\"
Meaning	A user stopped network monitoring.

Sticky MAC entries messages

ID	10600
-----------	-------

Type	Event log
Subtype	Switch
Severity	Warning or notice
Message	<ul style="list-style-type: none"> • msg="The number of saved Sticky MAC (<number_of_entries>) entries exceeds the learning limit (<learning_limit>) for VLAN ID <VLAN_ID>\" • msg="Sticky MAC entries saved = <number_of_entries>.\" • msg="Warning: Large number of Sticky MAC (<number_of_entries>) entries saved. Some entries may fail to load on reboot.\" • msg="Unsaved Sticky MAC entries flushed = <number_of_entries>.\"
Meaning	<ul style="list-style-type: none"> • The number of saved sticky MAC entries for the specified VLAN has exceeded the MAC address learning limit. • The specified number of sticky MAC entries have been saved. • Too many sticky MAC entries have been saved, and some might be lost when the switch is rebooted. • Unsaved sticky MAC entries have been deleted.

Sticky MAC entries cannot be saved

ID	10601
Type	Event log
Subtype	Switch
Severity	Warning
Message	<ul style="list-style-type: none"> • msg="Warning: <number_of_MAC_addresses> sticky MACs could not be saved because the static-MAC table is full.\" • msg="Warning: <number_of_MAC_addresses> sticky MACs could not be saved due to learning limit restrictions.\"
Meaning	The specified number of sticky MAC addresses cannot be saved either because the static MAC address table is full or because the MAC address learning limit has been reached.

Static MAC entries exceeds the learning limit

ID	10700
Type	Event log
Subtype	Switch
Severity	Warning

Message	msg="The number of saved Static MAC (<number_of_entries>) entries exceeds the learning limit (<learning_limit>) for switch interface <switch_interface>."
Meaning	The number of saved static MAC addresses exceeds the MAC address learning limit for the specified switch interface.

Deleting or adding an access VLAN failed

ID	10750
Type	Event log
Subtype	Switch
Severity	Error or information
Message	<ul style="list-style-type: none"> • msg="Access vlan delete failed" • msg="Access vlan delete failed entry-id <VLAN_ID>" • msg="Access vlan add failed" • msg="Access vlan add failed entry-id <VLAN_ID>" • msg="The Mirror auto-configuration session \'<mirror_session>\' with collector IP <IP_address> has begun auto-configuration."
Meaning	<ul style="list-style-type: none"> • Deleting an access VLAN failed. • Adding an access VLAN failed. • The automatic mirror configuration has started.

Automatic mirror configuration failed

ID	10751
Type	Event log
Subtype	Switch
Severity	Critical
Message	msg="The Mirror auto-configuration session \'<mirror_session>\' failed to resolve."
Meaning	The automatic mirror configuration has failed.

Automatic mirror configuration completed

ID	10752
-----------	-------

Type	Event log
Subtype	Switch
Severity	Information
Message	msg=\"The Mirror auto-configuration session '<mirror_session>' with collector IP <IP_address> has successfully been autoconfigured.\"
Meaning	The automatic mirror configuration has failed.

Mirroring might be interrupted

ID	10753
Type	Event log
Subtype	Switch
Severity	Critical
Message	msg=\"The Mirror auto-configuration session '<mirror_session>' is recalculating. Mirroring may be interrupted.\"
Meaning	Mirroring might be interrupting while the automatic mirror configuration is recalculating.

Automatic mirror configuration stopping

ID	10754
Type	Event log
Subtype	Switch
Severity	Critical
Message	msg=\"The Mirror auto-configuration session '<mirror_session>' is stopping.\"
Meaning	The automatic mirror configuration is stopping.

FortiGate nonblocking authentication daemon crashed

ID	10900
Type	Event log
Subtype	Switch

Severity	Warning
Message	<ul style="list-style-type: none">• msg=\"Session is NULL, sock is <status>\"• msg=\"session is <session_number>, TAC+ server num is <server_number>, sock is <status>\"
Meaning	The FortiGate nonblocking authentication daemon crashed.

New MAC address learned

ID	11100
Type	Event log
Subtype	Switch
Severity	Information
Message	msg=\"new <MAC_address> learned\"
Meaning	A new MAC address has been learned.

MAC address moved

ID	11101
Type	Event log
Subtype	Switch
Severity	Information
Message	<ul style="list-style-type: none">• msg=\"<MAC_address> moved new interface\"• msg=\"<MAC_address> deleted from old interface\"
Meaning	The MAC address is moved to a new switch interface and deleted from the old switch interface.

MAC address deleted

ID	11102
Type	Event log
Subtype	Switch
Severity	Information

Message	msg=\"<MAC_address> deleted\"
Meaning	The MAC address is deleted when the mac-aging-interval is reached.

IGMP-snooping group not added

ID	11120
Type	Event log
Subtype	Switch
Severity	Notice
Message	msg="IGMP Snooping: unable to program to hw"
Meaning	The IGMP-snooping group was not added to the hardware table because of a hash collision.

Switch controller log messages

The log messages in this chapter are for switch controller (FortiLink) issues.

Switch controller connected with FortiGate

ID	9000
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"Switch-Controller: connected with FortiGate\\\"
Meaning	The switch controller connected with a FortiGate unit.

Switch port joined FortiGate trunk

ID	9001
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"FortiLink: <port_name> joined Fortigate-uplink trunk-id(<trunk_name>)\\"
Meaning	The switch port joined the FortiGate uplink trunk.

Switch port left FortiGate uplink

ID	9002
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"FortiLink: <port_name> left Fortigate-uplink\\\"
Meaning	The switch port left the FortiGate uplink.

FortiLink messages

ID	9003
Type	Event log
Subtype	Switch controller
Severity	Critical or notice
Message	<ul style="list-style-type: none"> • msg="FortiLink: <port_name> in Fortigate-uplink ready now" • msg="FortiLink: disabled port <port_name> port-id=<port_ID> from b(<flags>) fwd(<0 1, if port is STP FORWARD>)" • msg="FortiLink: removed port<port_name> port-id=<port_ID>" • msg="FortiLink: enable port <port_name> port-id=<port_ID>"
Meaning	<ul style="list-style-type: none"> • The switch port in the FortiGate uplink is ready. • The specified port was disabled in FortiLink mode. • The specified port was removed in FortiLink mode. • The specified port was enabled in FortiLink mode.

TPID value changed

ID	9004
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg="FortiLink: tpid change old(<old_TPID_value>) new(<new_TPID_value>) fl-ports-bitmap (<port_name>)"
Meaning	The tag protocol identifier (TPID) value was changed.

Echo failures

ID	9005
Type	Event log
Subtype	Switch controller
Severity	Warning
Message	<ul style="list-style-type: none"> • msg="FortiLink: <IPv4_address> echo timed out" • msg="FortiLink: <IPv4_address> echo reply timing out echo-miss(<number_of_

- milliseconds>)\")
- msg=\"FortiLink: <IPv4_address> echo reply timed out\"
 - msg=\"FortiLink: <IPv4_address> invalid echo reply\"

Meaning The ICMP echo request (ping) failed.

Switch controller disconnected or restarted

ID	9006
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	<ul style="list-style-type: none">• msg=\"Switch-Controller: DTLS ALERT received <time_date>\"• msg=\"Switch-Controller: Restart caputp since SSL handshake failed <number_of_failures> times\"
Meaning	The switch controller was disconnected or restarted.

User deleted ISL trunk

ID	9007
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"FortiLink: user deleted ISL trunk <trunk_name>\"
Meaning	A user deleted the specified inter-switch link (ISL) trunk.

ISL timing out

ID	9008
Type	Event log
Subtype	Switch controller
Severity	Notice

Message	msg=\"FortiLink: ISL timing-out for trunk(<trunk_name>) member port-num(<port_ID>) <port_name> did not receive ISL pkt for(<number_of_seconds>) sec\"
Meaning	The ISL timed out because one of the trunk's ports did not receive the ISL packet for a certain number of seconds.

Port joined ISL

ID	9009
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"FortiLink: <port_name> joined ISL link <ISL_port_group>\"
Meaning	The specified port joined the ISL port group.

Port left ISL

ID	9010
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"FortiLink: <port_name> left ISL link <ISL_port_group>\"
Meaning	The specified port left the ISL port group.

FortiGate uplink trunk not created

ID	9011
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"FortiLink: Fortigate-uplink trunk create failed for member <port_name>\"
Meaning	The FortiGate uplink trunk was not created because of the specified port.

Port not added to FortiGate uplink trunk

ID	9012
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"FortiLink: Fortigate-uplink trunk member-add failed for member <port_name>\"
Meaning	The specified port was not added to the FortiGate uplink trunk.

Port not deleted from FortiGate uplink trunk

ID	9013
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	msg=\"FortiLink: <port_name> member-delete failed for Fortigate-uplink\"
Meaning	The specified port was not deleted from the FortiGate uplink trunk.

AC discovery type changed

ID	9014
Type	Event log
Subtype	Switch controller
Severity	Critical
Message	msg=\"FortiLink over L3 AC discovery-type changed old(<old_discovery_type>) new(<new_discovery_type>).\"
Meaning	The AC discovery type was changed; and the FortiLink daemon will be restarted.

Switch controller waiting for HTTP/HTTPS daemon

ID	9015
Type	Event log
Subtype	Switch controller
Severity	Notice
Message	<ul style="list-style-type: none">• msg=\"Switch-Controller: wating for httpsd to start uptime = <number_of_minutes>\"• msg=\"Switch-Controller: httpsd started uptime = <number_of_minutes>\"
Meaning	The switch controller is waiting for the HTTP and HTTPS daemon to start, or the HTTP and HTTPS daemon has started.

Switch controller log storage 75-percent full

ID	9016
Type	Event log
Subtype	Switch controller
Severity	Warning
Message	msg=\"Switch-Controller: Caputp store logs reached 75 percent of total storage capacity <total_storage> logs\"
Meaning	The allotted storage for switch-controller logs is 75-percent full.

System log messages

The log messages in this chapter are issues related to the overall operation of the FortiSwitch unit.

Alarm created

ID	30100
Type	Event log
Subtype	System
Severity	Alert
Message	msg=\"<alarm_ID>\"
Meaning	An alarm occurred.

Alarm acknowledged

ID	30101
Type	Event log
Subtype	System
Severity	Alert
Message	msg=\"<alarm_ID>\"
Meaning	The alarm was acknowledged.

Domain name in alert email cannot be resolved

ID	30150
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"Can't resolve the IP address of <alert_email_address_sender>\"
Meaning	The domain name of the sender of the alert email cannot be resolved.

FortiSwitch unit started

ID	30200
Type	Event log
Subtype	System
Severity	Information
Message	msg="FortiSwitch started <time>\"
Meaning	The FortiSwitch unit was started.

FortiSwitch unit rebooted or shut down

ID	30201
Type	Event log
Subtype	System
Severity	Critical
Message	<ul style="list-style-type: none">• msg="User <user_name> rebooted the device. The reason is 'restore configuration\""• msg="User <user_name> rebooted the device from <IP_address>\"• msg="User <user_name> shutdown the device from <IP_address>\"
Meaning	The specified user rebooted or shut down the FortiSwitch unit.

Daily FortiSwitch unit restart

ID	30202
Type	Event log
Subtype	System
Severity	Critical
Message	msg="System will reboot due to scheduled daily restart.\"
Meaning	The FortiSwitch unit is being rebooted because it was scheduled to restart daily.

CA certificate will be automatically updated

ID	30300
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"CA certificate <certificate_name> will auto-update in <number_of_days> days.\"
Meaning	The certificate authority (CA) certificate will automatically update in the specified number of days.

Local certificate will be automatically regenerated

ID	30301
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"Local certificate <certificate_name> will auto-regenerate in <number_of_days> days.\"
Meaning	The local certificate will automatically regenerate in the specified number of days.

Certificate failed to automatically update

ID	30302
Type	Event log
Subtype	System
Severity	Error
Message	msg=\"<certificate_name>\"
Meaning	The certificate failed to automatically update.

Certificate failed to automatically regenerate

ID	30303
-----------	-------

Type	Event log
Subtype	System
Severity	Error
Message	msg=\"<certificate_name>\"
Meaning	The certificate failed to automatically regenerate.

PKCS #12 certificate imported

ID	30304
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"User <user_name> imported the certificate from <path>\"
Meaning	The specified user imported a PKCS #12 certificate.

CRL update requested

ID	30306
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"User <user_name> requested a CRL update from <URL>\"
Meaning	The specified user requested an update for a certificate revocation list (CRL).

Power supply restored

ID	30400
Type	Event log
Subtype	System
Severity	Critical

Message	msg=\"Power supply <unit_ID> restore\"
Meaning	The specified power supply unit was restored.

Power supply failed

ID	30401
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"Power supply <unit_ID> failure\"
Meaning	The specified power supply unit failed.

System configuration changed

ID	30500
Type	Event log
Subtype	System
Severity	Alert
Message	<ul style="list-style-type: none">• msg=\"<user_name> made a change from <module>:<submodule>\"• msg=\"Configuration is changed in the admin session\"
Meaning	The specified user changed the system configuration.

System configuration changed using the GUI

ID	30501
Type	Event log
Subtype	System
Severity	Varies
Message	msg=\"User <user_name> made a change via <GUI>: <submodule>\"
Meaning	The specified user changed the system configuration from the GUI.

System configuration restored

ID	30502
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"User <user_name> restored the configuration from <IP_address>\"
Meaning	The specified user restored the system configuration.

Restoring the configuration failed

ID	30503
Type	Event log
Subtype	System
Severity	Warning or notice
Message	<ul style="list-style-type: none">• msg=\"User <user_name> failed to restore the configuration from <IP_address>\"• msg=\"User <user_name> restored the <file_name> file <file_name> from management station\"
Meaning	The specified user failed to restore the system configuration.

System reset to factory settings

ID	30507
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"User <user_name> reset to the factory settings from <IP_address>\"
Meaning	The specified user reset the system to factory default settings.

Global setting changed

ID	30514
Type	Event log
Subtype	System
Severity	Notice
Message	<ul style="list-style-type: none"> • msg="User <user_name> changed global setting from <old_value>" • msg="User <user_name> changed hostname global setting to <new_value> from <old_value>" • msg="User <user_name> changed timeout global setting to <new_value> from <old_value>" • msg="User <user_name> changed detection-interval global setting to <new_value> from <old_value>" • msg="User <user_name> changed fail_times global setting to <new_value> from <old_value>" • msg="User <user_name> changed dst global setting to <new_value> from <old_value>"
Meaning	<ul style="list-style-type: none"> • The specified user changed a global setting. • The specified user changed the global host name setting. • The specified user changed the global timeout setting. • The specified user changed the global detection-interval setting. • The specified user changed the global failtime setting. • The specified user changed the global destination setting.

System configuration backed up

ID	30515
Type	Event log
Subtype	System
Severity	Alert, warning, or notice
Message	<ul style="list-style-type: none"> • msg="User <user_name> backed up the configuration from <IP_address>" • msg="User <user_name> backed up the configuration from <IP_address> to management station" • msg="User <user_name> backed up the configuration from <IP_address> to flash disk" • msg="Automatic configuration backup to flash disk succeeded" • msg="User <user_name> backed up the configuration by SCP" • msg="Configuration backed up to flash disk after system upgrading"
Meaning	<ul style="list-style-type: none"> • The specified user backed up the system configuration. • The specified user backed up the system configuration to the management station.

- The specified user backed up the system to a flash drive.
- The system configuration was successfully automatically backed up to a flash disk.
- The specified user backed up the system configuration using the Secure Copy Protocol (SCP).
- After the system was upgraded, the system configuration was backed up to a flash disk.

Configuration revision uploaded

ID	30516
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"User <user_name> upload the <file_name> from <IP_address> to flash disk\"
Meaning	The specified user uploaded the configuration revision to the flash disk.

Database revision deleted

ID	30518
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"<item>: <revision_number> has been deleted from revision data base\"
Meaning	The item has been deleted from the revision database.

Revision item deleted from flash disk

ID	30520
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"User <user_name> delete the <item> from <path> from flash disk\"
Meaning	The specified user deleted the revision item from the flash disk.

Command failed

ID	30522
Type	Event log
Subtype	System
Severity	Notice
Message	msg="Command failed: <user_name>. Return code <code_number>"
Meaning	The command failed.

Adding a new entry failed

ID	30523
Type	Event log
Subtype	System
Severity	Notice
Message	msg="Adding new entry failed: vdom property limit has been reached when user <user_name> adds <property> from <IP_address>"
Meaning	Adding a new entry failed because the VDOM property limit has been reached.

Failed to back up system configuration

ID	30524
Type	Event log
Subtype	System
Severity	Error or notice
Message	<ul style="list-style-type: none">• msg="User <user_name> failed to backup the configuration from <IP_address> to management station"• msg="User <user_name> failed to backup the configuration from <IP_address> to flash disk"• msg="Automatic configuration backup to flash disk failed(<IP_address>)"• msg="Failed to backup configuration after system upgrading: <IP_address>"
Meaning	<ul style="list-style-type: none">• The specified user failed to back up the system configuration to the management station.• The specified user failed to back up the system configuration to the flash disk.

- Automatically backing up the system configuration to the flash disk failed.
- After the system was upgraded, the system configuration backup failed.

Daemon started

ID	30700
Type	Event log
Subtype	System
Severity	Information
Message	msg=\"Daemon <daemon_name> started\"
Meaning	The specified daemon was started.

Daemon shut down

ID	30701
Type	Event log
Subtype	System
Severity	Information
Message	msg=\"Daemon <daemon_name> shut down\"
Meaning	The specified daemon was shut down.

Log information from the DHCP client module daemon

ID	30900
Type	Event log
Subtype	System
Severity	Varies
Message	msg=\"<log_entry>\"
Meaning	The DHCP client module daemon reported information for the log.

IP address too small

ID	30901
Type	Event log
Subtype	System
Severity	Warning
Message	msg="Address for requested options is too small. Dump all config: \n timeout: <time>\n init_interval: <initial_interval>\n retry_interval: <retry_interval>\n select_interval: <select_interval>\n reboot_timeout: <reboot_timeout>\n backoff_cutoff: <backoff_cutoff>\n arpcheck_timeout: <ARP_check_timeout>\n requested_lease: <requested_lease>\n requested_options address: <IP_address>\n"
Meaning	The DHCP client module daemon reported crash information for the log because the IP address for the requested options is too small.

DHCP statistics

ID	31004
Type	Event log
Subtype	System
Severity	Information
Message	msg="\<how_much_of_total_is_used>\n"
Meaning	The system reports how much of DHCP-snooping binding database for the interface is used.

DHCP server used all of its leases

ID	31005
Type	Event log
Subtype	System
Severity	Warning
Message	msg="\\"DHCP server <IP_address> has used up all of its leases\\""
Meaning	The specified DHCP server has used all of its leases.

DHCP server used most of its leases

ID	31006
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"DHCP server <IP_address> has used up over 80%% of its leases\"
Meaning	The specified DHCP server has used over 80 percent of its leases.

DHCP server sends a DDNS add query

ID	31007
Type	Event log
Subtype	System
Severity	Information
Message	msg=\"DHCP server sends a DDNS add query\"
Meaning	The DHCP server is sending a DDNS add query.

DHCP server sends a DDNS delete query

ID	31008
Type	Event log
Subtype	System
Severity	Information
Message	msg=\"DHCP server sends a DDNS delete query\"
Meaning	The DHCP server is sending a DDNS delete query.

DHCP server blocked the DHCP client

ID	31009
-----------	-------

Type	Event log
Subtype	System
Severity	Information
Message	msg=\"DHCP client is blocked by the DHCP server\"
Meaning	The DHCP server blocked the DHCP client.

DHCP server sends a DHCP acknowledgment

ID	31010
Type	Event log
Subtype	System
Severity	Information
Message	msg=\"DHCP server sends a DHCPACK\"
Meaning	The DHCP server sends a DHCP acknowledgment message

DHCP server receives a DHCP release

ID	31011
Type	Event log
Subtype	System
Severity	Information
Message	msg=\"DHCP server receives a DHCPRELEASE\"
Meaning	The DHCP server receives a DHCP release message.

Administrator logged in successfully

ID	32001
Type	Event log
Subtype	System
Severity	Information

Message	msg=\"Administrator <user_name> logged in successfully from <IP_address>\"
Meaning	An administrator logged in successfully.

Administrator failed to log in

ID	32002
Type	Event log
Subtype	System
Severity	Alert
Message	<ul style="list-style-type: none">• msg=\"Alarm testing\"• msg=\"Administrator <user_name> login failed from <IP_address>\"
Meaning	An administrator failed to log in.

Administrator logged out

ID	32003
Type	Event log
Subtype	System
Severity	Information
Message	msg=\"Administrator <user_name> <action> <status>\"
Meaning	An administrator logged out.

Admin login disabled because of login failures

ID	32008
Type	Event log
Subtype	System
Severity	Alert
Message	<ul style="list-style-type: none">• msg=\"Login disabled from IP <IP_address> for <number_of_seconds> seconds because of <number_of_attempts> bad attempts\"• msg=\"Administrator <user_name> disabled from logging in for <number_of_seconds> seconds because of <number_of_attempts> bad attempts\"

Meaning	The admin login was disabled because of too many failed attempts to log in.
----------------	---

Partitioning or formatting error

ID	33000
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"Partitioning or formatting error (<error_number>, <error_message>) partition=<partition_name> format=<type> label=<label_name>\"
Meaning	A partitioning error or formatting error occurred.

Log disk failure imminent

ID	33001
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"Log disk failure is imminent, logs should be backed up\"
Meaning	This S.M.A.R.T. (Self-Monitoring, Analysis and Reporting Technology) error is erroneous.

Lack of flash space

ID	33002
Type	Event log
Subtype	System
Severity	Critical
Message	Cannot store config due to short of flash space: require <number_of_blocks> blocks, only <number_of_blocks> free blocks left on flash disk
Meaning	The system configuration cannot be saved because of lack of flash space.

Disk formatting requested

ID	33003
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"User <user_name> requested to format <disk_name> disk from <IP_address>\"
Meaning	The specified user requested that the disk to be formatted.

Disk storage set up

ID	33004
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"Administrator <user_name> <action> disk storage <disk_name> from <IP_address>\"
Meaning	The administrator set up the disk storage.

Disk storage entry deleted

ID	33005
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"user <user_name> delete disk storage entry\"
Meaning	The administrator deleted an entry in disk storage.

Fan failure detected

ID	33100
-----------	-------

Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"FAN failure detected\"
Meaning	A fan failure was detected.

Fan tray not detected

ID	33101
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"FAN TRAY undetected\"
Meaning	The fan tray was not detected.

Fan tray detected

ID	33102
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"FAN TRAY detected\"
Meaning	The fan tray was detected.

Fan tray detection failed

ID	33103
Type	Event log
Subtype	System
Severity	Warning

Message	msg=\"FAN TRAY detected\"
Meaning	The fan tray detection failed.

Fan resumed working

ID	33104
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"FAN resumes\"
Meaning	The fan has resumed working.

Encryption failed

ID	33302
Type	Event log
Subtype	System
Severity	Alert
Message	msg=\"EVP encryption failed\"
Meaning	Encryption has failed.

Decryption failed

ID	33303
Type	Event log
Subtype	System
Severity	Alert
Message	msg=\"EVP decryption failed\"
Meaning	Decryption has failed.

Cannot extract FortiSwitch Private Key

ID	33304
Type	Event log
Subtype	System
Severity	Alert
Message	msg="Failed to extract FortiSwitch Private Key\"
Meaning	The FortiSwitch Private Key cannot be extracted.

FortiSwitch Cloud started or global time setting changed

ID	34000
Type	Event log
Subtype	System
Severity	Warning or notice
Message	<ul style="list-style-type: none">• msg="\fsw_cloud service is started by user.\"• msg="\User <user_name> changed time from <old_time> to <new_time>\"• msg="\The ntp daemon step adjusted time from <old_time> to <new_time> (sync source: <NTP_server_IP_address>)\"
Meaning	<ul style="list-style-type: none">• The user started FortiSwitch Cloud.• The specified user changed the global time setting.• The NTP daemon changed the global time setting.

FortiSwitch Cloud stopped

ID	34001
Type	Event log
Subtype	System
Severity	Warning
Message	msg="\fsw_cloud service is stopped by user.\"
Meaning	The user stopped FortiSwitch Cloud.

SSL connection to FortiSwitch Cloud established

ID	34002
Type	Event log
Subtype	System
Severity	Warning
Message	msg="SSL connection to cloud-manager ip=<IP_address>, port=<port_name> is established."
Meaning	The SSL connection to the FortiSwitch Cloud has been established.

SSL connection to FortiSwitch Cloud down

ID	34003
Type	Event log
Subtype	System
Severity	Warning
Message	msg="SSL connection to cloud-manager ip=<IP_address>, port=<port_name> is down (reason=<reason>)."
Meaning	The SSL connection to FortiSwitch Cloud is down.

SSL connection to FortiSwitch Cloud not established

ID	34004
Type	Event log
Subtype	System
Severity	Warning
Message	msg="SSL connection to cloud-manager ip=<IP_address>, port=<port_number> not be established."
Meaning	The SSL connection to FortiSwitch Cloud cannot be established.

Packet capture stopped because of lack of storage

ID	34006
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"sniffer profile <profile_name> stopped due to storage error. (err=<error>).\"
Meaning	The packet capture stopped because there is not enough storage.

Corrupt MAC packet detected

ID	34200
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"Corrupted MAC packet detected\"
Meaning	A corrupt MAC packet was detected.

Firmware image restored

ID	34301
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"User <user_name> restored the image from <IP_address> (<old_version_number>,build <old_build_number>-> <new_version_number>,build <new_build_number>)\"
Meaning	The specified user restored the firmware image.

Firmware image failures

ID	34306
Type	Event log
Subtype	System
Severity	Critical or notice
Message	<ul style="list-style-type: none"> • msg="Failed to backup firmware image for system <IP_address>. The reason is: <reason>\" • msg="User <user_name> loaded a wrong image from <IP_address>.\" • msg="User <user_name> loaded an image from <IP_address>, the new image has an invalid CC signature.\" • msg="User <user_name> loaded an image from <IP_address>, the new image has an invalid RSA signature.\" • msg="User <user_name> loaded an image from <IP_address>, the new image does have a valid RSA signature with new public key.\" • msg="User <user_name> loaded an image from <IP_address>, the new image does have a valid RSA signature.\" • msg="User <user_name> loaded an image from <IP_address>, System upgrade failed due to file operation failure\" • msg="User <user_name> updated the image from <IP_address> (<old_build_number>-><new_build_number>)\\" • msg="Failed to writing image to flash.\"
Meaning	<ul style="list-style-type: none"> • Backing up the firmware image failed. • The user loaded the wrong firmware image. • The user loaded a firmware image with an invalid CC signature. • The user loaded a firmware image with an invalid RSA signature. • The user loaded a firmware image with a valid RSA signature with a new public key. • The user loaded a firmware image with a valid RSA signature. • The system upgrade failed because of a file operation failure. • The user updated the firmware image. • The system upgrade failed because the image could not be written to flash.

Firmware image backed up to flash disk

ID	34314
Type	Event log
Subtype	System
Severity	Notice
Message	msg="Firmware image backed up to flash disk for system <IP_address>\"
Meaning	The firmware image was backed up to a flash disk.

New local user added

ID	35000
Type	Event log
Subtype	System
Severity	Notice
Message	<ul style="list-style-type: none">• msg=\"User <user_name> added local user <local_user_name> from <IP_address>\"• msg=\"IP Conflict: conflict detected on system interface <interface_name> for IP address <IP_address>\"
Meaning	<ul style="list-style-type: none">• The specified user added a new local user.• An IP address conflict was detected on the specified system interface.

Setting changed for local user

ID	35001
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"User <user_name> changed local user <new_setting> setting from <old_setting>\"
Meaning	The specified user changed a setting for a local user.

Changes to static route or link monitor state

ID	35100
Type	Event log
Subtype	System
Severity	Critical or notice
Message	msg=\"<changes>\"
Meaning	Changes were made to a static route, or changes were made to the link monitor state.

RADIUS IPC error

ID	35200
Type	Event log
Subtype	System
Severity	Error
Message	msg="Unable to initialize RADIUS IPC (<IP_address>)"
Meaning	The RADIUS IPC could not be initialized.

User viewed memory logs

ID	35213
Type	Event log
Subtype	System
Severity	Notice
Message	msg="User <user_name> has viewed the memory logs from <log>"
Meaning	The specified user has viewed memory logs.

Log full

ID	35214
Type	Event log
Subtype	System
Severity	Warning or information
Message	msg="Memory <type> log is <percent> full"
Meaning	The memory log is full.

Disk has rolled log maximum number of times

ID	35215
-----------	-------

Type	Event log
Subtype	System
Severity	Emergency
Message	msg="Disk has rolled the max number of times.It will not roll logs again until deleting some of the old rolled logs.
Meaning	The disk has rolled the logs the maximum number of times. Some of the old rolled logs must be deleted before the disk will start rolling logs again.

Log disk full

ID	35217
Type	Event log
Subtype	System
Severity	Emergency, warning, or information
Message	<ul style="list-style-type: none"> • msg="Log disk is <percent> full.System will <action> when reaching <percent>.\" • msg="\<log_name> is <percent> full.System will stop <log_name> logging.\" • msg="\<log_name> is <percent> full.System will upload oldest 20%% logs.\" • msg="\<log_name> is <percent> full.System will delete oldest 20%% uploaded logs, and upload another oldest 20%% un-upload logs.\" • msg="Log disk is <percent> full\" • msg="\Disk logs exceed full final warning threshold. Deleted rolled log file <file_name>. • msg="\Disk logs exceed full final warning threshold. Deleted rolled packet directory <directory_name>. • msg="\Disk logs exceed full final warning threshold. Deleted rolled dlp-archive directory <directory_name>.
Meaning	<ul style="list-style-type: none"> • The log disk is full. The system will stop logging when reaching the specified percentage. • The log disk is full. The system will stop logging. • The log disk is full. The system will upload the oldest logs. • The log disk is full. The system will delete the oldest uploaded logs and then upload the oldest logs that have not been uploaded. • The log disk is full. • The size of the disk logs has exceeded the final warning threshold. The rolled log file has been deleted. • The size of the disk logs has exceeded the final warning threshold. The rolled packet directory has been deleted. • The size of the disk logs has exceeded the final warning threshold. The rolled DLP archive directory has been deleted.

Log rotation

ID	35218
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"Disk log has rolled.\\\"
Meaning	The disk has rolled the logs.

Logs cleared

ID	35222
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"User <user_name> has cleared logs () from <time_range>\\\"
Meaning	The specified user has cleared logs.

Rolled log files deleted

ID	35223
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"User <user_name> has deleted <number_of_logs> rolled <log_type> log file <file_name> (<IP_address>) from <IP_address>\\\"
Meaning	The specified user has deleted rolled log files.

User failed to view logs

ID	35227
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"User <user_name> failed to access the <log_type> logs from <IP_address>\"
Meaning	The specified user failed to access the logs.

Daily logging quota full

ID	35229
Type	Event log
Subtype	System
Severity	Alert
Message	msg=\" daily quota is reached.System stops logging until <number_of_seconds> sec later.\"
Meaning	The daily logging quota has been reached, and the system stops logging.

Logging file downloaded

ID	35230
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"<action> by user <user_name> via <interface>\"
Meaning	The specified user has used the GUI to download a logging file from the firewall.

Log backed up

ID	35231
-----------	-------

Type	Event log
Subtype	System
Severity	Notice
Message	<ul style="list-style-type: none"> • msg=\"User <user_name> backed up <log_type> memory log from <IP_address>\" • msg=\"User <user_name> backed up <log_type> log from <IP_address>\"
Meaning	The specified user has backed up the log.

Backing up all logs failed

ID	35232
Type	Event log
Subtype	System
Severity	Notice
Message	<ul style="list-style-type: none"> • msg=\"User <user_name> failed to back up <log_type> memory log from <IP_address>\" • msg=\"User <user_name> failed to back up all memory logs (<log_types>) from <IP_address>\" • msg=\"User <user_name> failed to backup all the logs from <IP_address>\"
Meaning	The specified user failed to back up all logs.

All logs backed up

ID	35233
Type	Event log
Subtype	System
Severity	Notice
Message	<ul style="list-style-type: none"> • msg=\"User <user_name> backed up all memory logs from <IP_address>\" • msg=\"User <user_name> backed up all the logs from <IP_address>\"
Meaning	The specified user backed up all logs.

Log backup failed

ID	35236
-----------	-------

Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"User <user_name> failed to backup <log_type> log from <IP_address>\"
Meaning	The specified user failed to back up a log.

Warning from monitor-and-alert daemon

ID	35242
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"<message_text>.\"
Meaning	The monitor-and-alert daemon sent a warning.

Log test

ID	36000
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"user admin logged into the fw - <action>\"
Meaning	Log test

PSU changes to good state

ID	36100
Type	Event log
Subtype	System
Severity	Warning

Message	msg=\"<PSU> changes to good state\"
Meaning	The power supply unit (PSU) is now in a good state.

PSU changes to bad state

ID	36101
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"<PSU> changes to bad state\"
Meaning	The PSU is now in a bad state.

PSU connected

ID	36103
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"<PSU> connected\"
Meaning	The PSU is now connected.

PSU not connected

ID	36104
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"<PSU> not connected\"
Meaning	The PSU is now disconnected.

PSU 1 is down

ID	36106
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"PSU 1 is down\"
Meaning	PSU 1 is down.

PSU 1 is up

ID	36107
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"PSU 1 is up\"
Meaning	PSU 1 is up.

PSU 2 is down

ID	36108
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"PSU 2 is down\"
Meaning	PSU 2 is down.

PSU 2 is up

ID	36109
-----------	-------

Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"PSU 2 is up\"
Meaning	PSU 2 is up.

Corrupt MAC packet detected or negotiation failed

ID	36250
Type	Event log
Subtype	System
Severity	Error or warning
Message	<ul style="list-style-type: none">• msg=\"Corrupted MAC packet detected\"• msg=\"Negotiation failed: <IP_address>. Their offer: <IP_address>.\"• msg=\"Negotiation failed: <IP_address>.\"• msg=\"SSH server rekey\"
Meaning	<ul style="list-style-type: none">• A corrupt MAC packet was detected.• Negotiation failed.• The SSH server needs rekeying.

Fan tray status

ID	36300
Type	Event log
Subtype	System
Severity	Warning
Message	Varies
Meaning	The fan tray status is reported.

Alarm testing

ID	36350
Type	Event log
Subtype	System
Severity	Emergency
Message	msg=\"Alarm testing\"
Meaning	The alarm is being tested.

Learning-limit violations reset

ID	42000
Type	Event log
Subtype	System
Severity	Notice
Message	<ul style="list-style-type: none"> • msg=\"Learn Limit Violation: Resetting violations for VLAN ID <VLAN_ID>.\" • msg=\"Learn Limit Violation: Resetting violations for interface <interface_name>.\" • msg=\"Learn Limit Violation: Resetting all violations.\"
Meaning	<ul style="list-style-type: none"> • The learning-limit violation log was cleared for a specific interface. • The learning-limit violation log was cleared for a specific VLAN. • All learning-limit violation logs were cleared.

Learning-limit violations deleted

ID	42001
Type	Event log
Subtype	System
Severity	Notice
Message	<ul style="list-style-type: none"> • msg=\"Learn Limit Violation: Clearing (deleting) violations for interface <interface_name>.\" • msg=\"Learn Limit Violation: Clearing (deleting) violations for VLAN ID <VLAN_ID>.\" • msg=\"Learn Limit Violation: Clearing (deleting) all violations.\"
Meaning	<ul style="list-style-type: none"> • The learning-limit violations were deleted for a specific interface. • The learning-limit violations were deleted for a specific VLAN. • All learning-limit violations were deleted.

Learning-limit violation log enabled

ID	42002
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"Enabled learning limit violation records.\"
Meaning	The learning-limit violation log has been enabled.

Learning-limit violation log disabled

ID	42003
Type	Event log
Subtype	System
Severity	Notice
Message	msg=\"Disabled learning limit violation records.\"
Meaning	The learning-limit violation log has been disabled.

Learning limit exceeded

ID	42004
Type	Event log
Subtype	System
Severity	Notice
Message	<ul style="list-style-type: none">msg=\"VLAN MAC learning limit exceeded, MAC <MAC_address> on VLAN <VLAN_ID> (RX Interface: <interface_name>).\"msg=\"Interface MAC learning limit exceeded, MAC <MAC_address> on <interface_name> (Packet VID: <VLAN_ID>).\"
Meaning	The learning limit was exceeded on the specified VLAN or interface.

VM license file added

ID	42100
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"User <user_name> added VM license file.\\\"
Meaning	The specified user added a VM license file.

Failed to add VM license file


ID	42101
Type	Event log
Subtype	System
Severity	Critical
Message	msg=\"User <user_name> failed to add VM license file.\\\"
Meaning	The specified user failed to add a VM license file.

No more IP source guard entries can be added

ID	42200
Type	Event log
Subtype	System
Severity	Warning
Message	msg=\"Not install entry <IP_address> on <switch_interface> due to \\\"FULL\\\" error code.\\\"
Meaning	No more IP source guard entries can be added because the maximum number of entries has been added.



FORTINET®



Copyright© 2020 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. In no event does Fortinet make any commitment related to future deliverables, features or development, and circumstances may change such that any forward-looking statements herein are not accurate. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.