

# FortiClient Configurator Tool



This tool is deprecated and only supported FortiClient 6.0 and earlier versions.

---

The free FortiClient Configurator Tool is used to create custom FortiClient installation files. Starting with FortiClient 5.6.0, an account for the [Fortinet Developer Network](#) is required to access the free tool. You do not need a license key to use the tool.

The FortiClient Configurator Tool is available for Microsoft Windows and macOS operating systems.

---



The FortiClient Configurator Tool version must be the same as the FortiClient version. For example, if using FortiClient 6.0.1, you must use FortiClient Configurator Tool 6.0.1. You cannot use FortiClient Configurator Tool 6.0.0 or 6.0.2 with FortiClient 6.0.1.

---

## Overview

Following is an overview of using the FortiClient Configurator Tool:

1. Log into your FNDN account, and download the tool from FNDN. See [Downloading the tool on page 1](#).
2. (Optional) Prepare configuration files and Telemetry gateway IP lists. See [Preparing configuration files on page 2](#). You have the option to add a FortiClient configuration file and/or Telemetry gateway IP list to the FortiClient installer. Before you create the installer, you should get these files ready for selection.
3. Create a custom FortiClient installer. See [Creating custom FortiClient installation files on page 4](#).
4. Deploy the custom FortiClient installation packages. See [Deploying custom FortiClient installation packages on page 11](#).

## Downloading the tool

Download the free FortiClient Configurator Tool from the Fortinet Developer Network site.

---



You must have an account to access the [Fortinet Developer Network](#).

---

**To download the tool:**

1. Log in to your FNDN account on the [Fortinet Developer Network](#).  
If you do not have an account for FNDN, you must create an account at [Registration - Fortinet Developer Network](#).  
When you create an FNDN account, you must include the email address for two Fortinet sponsors. Fortinet sponsors are Fortinet employees who can verify that you are a Fortinet customer. Contact your sales representative or sales engineer for email addresses for Fortinet sponsors.
2. Go to *Tools > Personal Toolkit*, and download the FortiClient Configurator Tool.

## Preparing configuration files

You can select the following file types in the FortiClient Configurator Tool when you create a custom FortiClient installer:

- Configuration file
- Gateway IP list

This section describes how to retrieve and edit the files to prepare them for use with the FortiClient Configurator Tool.



You can use an XML editor to make changes to the FortiClient configuration file and Telemetry gateway IP list. For more information on FortiClient XML configuration, see the [FortiClient XML Reference](#).

---

## Retrieving FortiClient configuration files

You can retrieve a configuration file from FortiClient. The configuration file contains the settings for FortiClient. After you retrieve the configuration file, you can use an XML editor to make changes to the configuration file. Then you can select the FortiClient configuration file in the FortiClient Configurator Tool.

**To retrieve FortiClient configuration files:**

1. In FortiClient, go to *Settings*.
2. In the *System* area, click *Backup*.
3. Select a destination, and click *Save*.

## Configuring Telemetry gateway IP lists

You can retrieve a configuration file from FortiClient to access the XML elements for the Telemetry gateway IP list.



If you are using FortiClient EMS (Enterprise Management Server), you can export a gateway IP list from FortiClient EMS. See the *FortiClient EMS Administration Guide*.

---

The Telemetry gateway IP list contains IP addresses for FortiGate and/or FortiClient EMS. FortiClient uses the Telemetry gateway IP list to connect FortiClient Telemetry to FortiGate or FortiClient EMS.

After you retrieve the configuration file, you can use an XML editor to locate the elements for the Telemetry gateway IP list and modify them.

**To configure Telemetry gateway IP lists:**

1. In FortiClient, retrieve the configuration. See [Retrieving FortiClient configuration files on page 2](#).
2. Open the configuration file in an XML editor.
3. Remove all elements, except the elements needed to configure the Telemetry gateway IP list. See [Example XML of Telemetry gateway IP list on page 4](#).
4. Add IP addresses to the configuration file by using an XML editor.  
When using only FortiGate for endpoint control, use the `<fortigate>` element to identify one or more IP addresses for FortiGate devices.  
When using FortiGate integrated with EMS, use the `<fortigate>` element to identify one or more IP addresses for FortiGate devices, and use the `<notification_server>` element to identify the IP address for EMS.  
When using only EMS for endpoint management and no FortiGate is involved, set `<fortigate>` and `<notification_server>` with the same value.
5. Save the configuration file.

## Example XML of Telemetry gateway IP list

Following is an example XML file for a Telemetry gateway IP list. In this example, endpoints will connect Telemetry to FortiGate by using the IP addresses in the <fortigate> element and send notifications to FortiClient EMS by using the <notification\_server> element.

```
<?xml version="1.0" encoding="UTF-8" ?>
  <forticlient_configuration>
    <endpoint_control>
      <enabled>1</enabled>
      <disable_unregister>0</disable_unregister>
      <silent_registration>1</silent_registration>
      <fortigates>
        <fortigate>
          <serial_number>fgt_sn0</serial_number>
          <name>fgt_name</name>
          <registration_password>Enc
            da7e6495841d8fc9c61067f81ef4cac01d697bb7e160c24d</registration_password>
          <addresses>172.30.254.150:8013</addresses>
        </fortigate>
        <fortigate>
          <serial_number>fgt_sn1</serial_number>
          <name>fgt_name</name>
          <registration_password>Enc
            6c9f088323beef31ea969c1c31c6db0e766273cb21851e68</registration_password>
          <addresses>172.30.254.174:8013</addresses>
        </fortigate>
        <fortigate>
          <serial_number>fgt_sn2</serial_number>
          <name>fgt_name</name>
          <registration_password>Enc
            7e819fa80a68ca2b602fdad54ba76190f03777c70399471d</registration_password>
          <addresses>172.30.254.158:8013</addresses>
        </fortigate>
      </fortigates>
      <notification_server>
        <address>us-ems1.myfortinet.com:8013</address>
      </notification_server>
    </fortigates>
  </endpoint_control>
</forticlient_configuration>
```

## Creating custom FortiClient installation files

The following section provides instructions on creating a custom installer file using the FortiClient Configurator Tool.

You have the option to select a FortiClient configuration file and/or Telemetry gateway IP list when you create a custom FortiClient installer. See [Preparing configuration files on page 2](#).

Ensure that you select all modules in the FortiClient installer that you want installed on endpoints. To enable other features after FortiClient is installed, you must uninstall FortiClient from endpoints, and reinstall an MSI file with the desired features included in the FortiClient installer.

If you're using FortiClient EMS to deploy and manage FortiClient endpoints, you can create a FortiClient installer that includes most or all modules, and you can use a profile from FortiClient EMS to disable and enable modules without uninstalling and reinstalling FortiClient.

## Using FortiClient Configurator Tool for Windows



Windows has a hard limit of 260 characters on file path length. It is recommended to run the FortiClient Configurator Tool in a shallow directory structure, such as c:\temp\, to avoid hitting the hard limit.

### To create a custom FortiClient installation file:

1. Double-click the *FortiClientConfigurator.exe* application file to launch the tool. The *Configuration File* page displays with the following options.

<b>Select Config File (optional)</b>	Select a FortiClient configuration file (.conf, .sconf) to include in the installer file.
<b>Password</b>	If the FortiClient configuration file is encrypted (.sconf), enter the password used to encrypt the file.
<b>FortiClient Telemetry Gateway IP List (optional)</b>	Select a FortiClient Telemetry gateway IP list to include in the installer file.

Locate and select the FortiClient configuration file on your management computer, and click *Next*. If you do not want to include settings from a configuration file, click *Skip* to continue. The *Settings* page displays.


The following options are available for custom installations:

### Features to Install

<b>Security Fabric Agent</b>	<p>Selected by default to support Fortinet Security Fabric. FortiClient Telemetry is always installed to support integration of FortiClient into the Security Fabric as follows:</p> <ul style="list-style-type: none"> <li>• Participate in compliance</li> <li>• Send user ID, avatar, and email address to FortiGate</li> <li>• Be managed by EMS</li> </ul> <p>Along with the Vulnerability Scan component (also included in this agent), this provides the Security Fabric administrators an overview of the endpoint state. Clear the checkbox to exclude the <i>Compliance</i> and <i>Vulnerability Scan</i> tabs from the FortiClient installation file.</p>
<b>Secure Remote Access</b>	Select to include SSL and IPsec VPN modules in the FortiClient installation file.
<b>Advanced Persistent Threat (APT) Components</b>	Select to include FortiSandbox detection and quarantine modules in the FortiClient installation file.
<b>Additional Security Features</b>	<p>Select to include one or more of the following modules in the FortiClient installation file:</p> <ul style="list-style-type: none"> <li>• AntiVirus</li> <li>• Web Filtering</li> <li>• Single Sign On</li> <li>• Application Firewall</li> </ul>
<b>Options</b>	
<b>Desktop Shortcut</b>	Select to create a FortiClient desktop icon on the endpoint.
<b>Start Menu</b>	Select to add FortiClient to the start menu on the endpoint.
<b>Enable Software Update</b>	Select to enable FortiClient software updates via FortiGuard Distribution Network on endpoints.
<b>Configure Single Sign-On mobility agent</b>	Select to configure Single Sign-On mobility agent for use with FortiAuthenticator. You must select the <i>Single Sign On</i> checkbox in the <i>Features to Install</i> area first.

2. Select the features to install and options, and click *Next* to continue.

If you selected the *Configure Single Sign-On mobility agent* checkbox, the *Single Sign-On Mobility Agent Settings* page displays.




The screenshot shows a dialog box titled "Single Sign-On Mobility Agent Settings". It contains the following fields and controls:

- SSO server settings**
  - Server IP/FQDN:** A text input field.
  - Port number:** A text input field with the value "8001" entered.
  - Pre-Shared Key:** A text input field.
  - Confirm Pre-Shared Key:** A text input field.
- At the bottom, there are three buttons: "< Back", "Next >", and "Cancel".

3. Configure the following settings:

<b>Server IP/FQDN</b>	Enter the FortiAuthenticator server's IP address or FQDN.
<b>Port number</b>	Enter the port number. The default port is 8001.
<b>Pre-Shared Key</b>	Enter the FortiAuthenticator pre-shared key.
<b>Confirm Pre-Shared Key</b>	Enter the FortiAuthenticator pre-shared key confirmation.

4. Click *Next* to continue. The *Package Signing* page displays.



The screenshot shows a dialog box titled "Package Signing". It contains the following fields and controls:

- A message: "If you have a Code Signing certificate, you can use it to digitally sign the installer packages this tool generates."
- Select Code Signing Certificate (optional):** A text input field with a browse button (three dots) and a "Clear" button.
- Password:** A text input field.
- At the bottom, there are three buttons: "< Back", "Skip >", and "Cancel".

5. Configure the following settings:


**Select Code Signing Certificate (optional)**

If you have a code signing certificate, you can use it to digitally sign the installer package this tool generates.

**Password**

If the certificate file is password protected, enter the password.

6. (Optional) Browse and select the code signing certificate on your management computer. If you do not want to digitally sign the installer package, select *Skip* to continue. The *Execution* page displays.



This page provides details of the installer file creation and the location of files for Active Directory deployment and manual distribution. The tool creates files for both 32-bit (x86) and 64-bit (x64) operating systems.

7. When you click *Finish*, the folder containing the newly created MSI file will open when the *Browse to installation files upon exit* checkbox is selected.



Before deploying the custom MSI files, it is recommended that you test the packages to confirm that they install correctly. An `.exe` installation file is created for manual distribution.




Installation files are organized in folders within the folder where you placed the `.exe` file for the FortiClient Configurator Tool. Folder names identify the type of installation files that were created and the creation date.

## Using FortiClient Configurator Tool for macOS

### To create a custom FortiClient installation file:

1. Double-click the *FortiClientConfigurator\_6.0.x.xxxx.dmg* application file, and double-click the FortiClientConfigurator icon to launch the tool.




**2. Configure the following settings, and click *Next*:**The screenshot shows the FortiClient Configurator (6.0.0.15) window. It has a title bar with standard macOS window controls. The main area contains two labeled text input fields: "Source:" and "Destination:". Each field has a small "..." button to its right. At the bottom of the window, there are three buttons: "< Back", "Next >", and "Cancel".**Source**

Select the FortiClient Installer file on your management computer.  
You must use the full installer file, otherwise FortiClient Configurator Tool will fail to create a custom installation file.  
The FortiClient Installer version and FortiClient Configurator Tool version must match, otherwise the Configurator will fail to create a custom installation file.

**Destination**

Enter a name for the custom installation file and select a destination to save the file on your management computer.

**3. (Optional) Configure the following settings, and click *Next*:**The screenshot shows the FortiClient Configurator (6.0.0.15) window at the optional settings step. It has a title bar with standard macOS window controls. The main area contains two labeled text input fields: "Select Config File (optional):" and "Select IP List File (optional):". Each field has a small "..." button to its right. At the bottom of the window, there are three buttons: "< Back", "Next >", and "Cancel".**Select Config File (optional)**


Select a FortiClient configuration file (`.conf`, `.sconf`) to include in the installer file.

**Password**

If the FortiClient configuration file is encrypted (`.sconf`), enter the password used to encrypt the file.

**Select IP List File (optional)**

Select a FortiClient Telemetry gateway IP list to include in the installer file.

**4. Configure the following settings, and click *Start*:****Features to Install****Security Fabric Agent**

Selected by default to support Fortinet Security Fabric. FortiClient Telemetry is always installed to support integration of FortiClient into the Security Fabric as follows:

- Participate in compliance
- Send user ID, avatar and email address to FortiGate
- Be managed by EMS

Along with the Vulnerability Scan component (also included in this agent), this provides the Security Fabric administrators an overview of the state of the endpoint.

Clear the checkbox to exclude the *Compliance* tab and *Vulnerability Scan* tab from the FortiClient installation file.

**Secure Remote Access**

Select to include SSL and IPsec VPN modules in the FortiClient installation file.

**Additional Security Features**

Select to include one or more of the following modules in the FortiClient installation file:

- AntiVirus
- Web Filtering
- Single Sign On
- Application Firewall

**Options****Enable Software Update**

Select to enable FortiClient software updates via FortiGuard Distribution Network on endpoints.

**Configure Single Sign-On mobility agent**

Select to configure Single Sign-On mobility agent for use with FortiAuthenticator.

5. If you selected the *Configure Single Sign-On mobility agent* checkbox, the *Single Sign-On Mobility Agent Settings* page displays. Configure the following settings:

<b>Server IP/FQDN</b>	Enter the FortiAuthenticator server's IP address or FQDN.
<b>Port number</b>	Enter the port number. The default port is 8001.
<b>Pre-Shared Key</b>	Enter the FortiAuthenticator pre-shared key.
<b>Confirm Pre-Shared Key</b>	Enter the FortiAuthenticator pre-shared key confirmation.

6. Click *Start*.
7. Click *Done*. You can now deploy the repackaged FortiClient .dmg file to your macOS systems.

## Deploying custom FortiClient installation packages

This section includes information about deploying FortiClient (Windows) installation packages and FortiClient (macOS) installation files.

### Deploying FortiClient (Windows) installation packages

After the FortiClient Configurator Tool generates the custom installation packages, you can use the custom installation packages to deploy FortiClient (Windows) software manually or using Active Directory. Both options can be found in the *.../FortiClient\_packaged* directory. Files are created for both x86 (32-bit) and x64 (64-bit) operating systems.

If you are using Active Directory to deploy FortiClient (Windows), you can use the custom installer with the MST file found in the *.../ActiveDirectory* folder.

For manual distribution, use the .exe file in the *.../ManualDistribution* folder.

## Deploying FortiClient (macOS) installation files

After the FortiClient Configurator Tool generates the custom installation file ( .dmg file), you can use the custom installation file to deploy FortiClient (macOS) software.