

Linux Agent Installation Guide

FortiSIEM 7.2.0



FORTINET DOCUMENT LIBRARY

<https://docs.fortinet.com>

FORTINET VIDEO LIBRARY

<https://video.fortinet.com>

FORTINET BLOG

<https://blog.fortinet.com>

CUSTOMER SERVICE & SUPPORT

<https://support.fortinet.com>

FORTINET TRAINING & CERTIFICATION PROGRAM

<https://www.fortinet.com/training-certification>

FORTINET TRAINING INSTITUTE

<https://training.fortinet.com>

FORTIGUARD LABS

<https://www.fortiguard.com>

END USER LICENSE AGREEMENT

<https://www.fortinet.com/doc/legal/EULA.pdf>

FEEDBACK

Email: techdoc@fortinet.com



06/02/2025

FortiSIEM 7.2.0 Linux Agent Installation Guide

TABLE OF CONTENTS

Change Log	4
FortiSIEM Linux Agent	5
Prerequisites	5
Supported Operating Systems	5
Software Requirements	6
Hardware Requirements	7
Communication Ports	7
Installing Linux Agent	7
Installing Linux Agent Without Supervisor Communication	9
Step 1: Setup the Collector as an HTTPS Proxy	9
Step 2: Install Agents to Work with the Collector	10
Managing Linux Agent	10
Uninstalling Linux Agent	11
Upgrading Linux Agent with FortiSIEM 6.4.0 and Higher	11
Adding Permissions for Linux Agent FIM	11
REST APIs used for Communication	12
Troubleshooting from Linux Agent	13
Log Rotating /var/log/messages to Prevent Filling Up the Root Disk	13

Change Log

Date	Change Description
06/05/2023	Release of FortiSIEM - Linux Agent Installation Guide for 7.0.0.
11/06/2023	Release of FortiSIEM - Linux Agent Installation Guide for 7.1.0.
12/13/2023	Release of FortiSIEM - Linux Agent Installation Guide for 7.1.1.
01/12/2024	Release of FortiSIEM - Linux Agent Installation Guide for 7.1.2.
01/24/2024	Release of FortiSIEM - Linux Agent Installation Guide for 7.1.3.
03/05/2024	Release of FortiSIEM - Linux Agent Installation Guide for 7.1.4.
05/02/2024	Added "Adding Permissions for Linux Agent FIM".
06/07/2024	Release of FortiSIEM - Linux Agent Installation Guide for 7.2.0.
06/26/2024	Release of FortiSIEM - Linux Agent Installation Guide for 7.2.1.
08/14/2024	Release of FortiSIEM - Linux Agent Installation Guide for 7.2.2.
09/05/2024	Updated Software Requirements section.
09/12/2024	Release of FortiSIEM - Linux Agent Installation Guide for 7.2.3.
11/04/2024	Release of FortiSIEM - Linux Agent Installation Guide for 7.2.4.
12/05/2024	Added Oracle Linux support information.
02/03/2025	Release of FortiSIEM - Linux Agent Installation Guide for 7.2.5.
03/31/2025	Release of FortiSIEM - Linux Agent Installation Guide for 7.2.6.
06/02/2025	Updated Installing Linux Agent Without Supervisor Communication > Step 1: Setup the Collector as an HTTPS Proxy > agent-proxy.conf content.

FortiSIEM Linux Agent

FortiSIEM Linux Agents provides a scalable way to collect logs and other telemetry from Linux systems in a secure and optimized manner.

Note: FortiSIEM Linux Agent will not do file integrity monitoring on `/root` directory.

This section describes how to install, setup, maintain and troubleshoot FortiSIEM Linux Agent.

- [Prerequisites](#)
- [Installing Linux Agent](#)
- [Installing Linux Agent Without Supervisor Communication](#)
- [Managing Linux Agent](#)
- [Uninstalling Linux Agent](#)
- [Upgrading Linux Agent with FortiSIEM 6.4.0 and Higher](#)
- [Adding Permissions for Linux Agent FIM](#)
- [REST APIs used for Communication](#)
- [Troubleshooting from Linux Agent](#)
- [Log Rotating `/var/log/messages` to Prevent Filling Up the Root Disk](#)

Prerequisites

Ensure that the following prerequisites are met before installing FortiSIEM Linux Agent:

- [Supported Operating Systems](#)
- [Software Requirements](#)
- [Hardware Requirements](#)
- [Communication Ports](#)

Supported Operating Systems

FortiSIEM Linux Agent has been tested to run on the following Linux Operating Systems:

- Rocky Linux 8, 9
- CentOS 7, 8, 9
- CentOS Stream 8, 9
- Oracle Linux 8, 9
- Red Hat Enterprise Linux 7, 8, 9
- Ubuntu 14, 16, 18, 20, 22, 24
- Amazon Linux 1 and Amazon Linux 2
- Debian 10, 11, 12
- SuSE Enterprise Linux (SLES) 12 and 15

For CentOS and Red Hat, the version requirements are:

- curl version later than 7.19.7
- nss.x86_64 version later than 3.36.0

If curl and nss versions are out of date, run `yum update -y nss curl lib curl` to upgrade.

Software Requirements

Make sure that `rsyslog` service is running before installing or re-installing FortiSIEM Linux Agent.

- To check the service status, run:
`systemctl status rsyslog.service`
- If `rsyslog` service is down, start the service by running:
`systemctl start rsyslog.service`

The following packages must be installed before FortiSIEM Linux Agents can run:

OS name	Package name	Install command
Ubuntu 14, 16, 18, 20, 22, 24	libcap2-bin auditd rsyslog logrotate at	<code>apt-get install <package_name></code> or <code>apt install <package_name></code>
CentOS 7, 8, 9 RHEL 7, 8, 9 Amazon Linux 1 and 2	libcap audit rsyslog logrotate at perl bind-utils audispd-plugins If SELinux is enabled, then the following packages also must be installed: policycoreutils-python libselinux-utils setools-console	<code>yum install <package_name></code>
Oracle Linux 8, 9	libcap audispd-plugins	<code>yum install <package_name></code>
SuSE 12 and 15	libcap-progs audit audit-audispd-plugins rsyslog logrotate	<code>zypper install <package_name></code>

Hardware Requirements

Component	Requirement
CPU	1 vCPU, x64 at 1.5 GHz or higher
RAM	512 MB or higher (FortiSIEM Linux Agent uses <100 MB)
Disk	1 GB or higher (FortiSIEM Linux Agent uses 300 MB)

Communication Ports

FortiSIEM Linux Agent communicates outbound via HTTPS with Supervisor and Collectors. The Agent registers to the Supervisor and periodically receives monitoring template updates, if any. The events are forwarded to the Collectors.



If using IPV6, ensure IPV6 is turned on for the Linux server by modifying the `/etc/sysctl.conf` file.

Change:

```
net.ipv6.conf.all.disable_ipv6 = 1
net.ipv6.conf.default.disable_ipv6 = 1
```

To:

```
net.ipv6.conf.all.disable_ipv6 = 0
net.ipv6.conf.default.disable_ipv6 = 0
```

Installing Linux Agent

FortiSIEM Linux Agent is available as a Linux installation script: `fortisiem-linux-agent-installer-7.2.0.0237.sh` from the Fortinet Support website <https://support.fortinet.com>. See "Downloading FortiSIEM Products" for more information on downloading products from the support website.

During installation, the Linux Agent will register with FortiSIEM Supervisor.

The required parameters are:

- **SUPER_IP**: IP Address or Host name/FQDN of Supervisor node
- **ORG_ID**: FortiSIEM Organization Id to which this Agent belongs
- **ORG_NAME**: FortiSIEM Organization Name
- **AGENT_USER**: Agent user name (for registration only)
- **AGENT_PASSWORD**: Agent password (for registration only)
- **HOST_NAME**: This name will be displayed in FortiSIEM CMDB. FortiSIEM recommends using a Fully Qualified Domain Name (FQDN), especially if SNMP or WMI is also going to be used against this device. FQDN allows for standardized naming convention.

The optional parameters are:

- **VERIFY**: a flag indicating whether agent will verify Super and Collector SSL Certificate using TLS handshake
- **CERT**: the full path where the CA Certificate is located

For Service Provider installations, the Agent user name and password is defined in the Organization. See [here](#) for details.

For Enterprise installations, Organization ID is "1", Organization Name is "Super", and Agent user name and password are defined in the **CMDB > User** page. You must create a user and check Agent Admin. See [here](#) for details.



- Before installing FortiSIEM Agent on FortSIEM Nodes, you must do detailed performance testing since FortSIEM nodes consume significant CPU to process a high volume of events in real-time.

- To run FortiSIEM Linux Agent on FortSIEM nodes:

- a. Add this line to the `/etc/rsyslog.conf` file:

```
$IncludeConfig /etc/rsyslog.d/fsm-*.conf
```

- b. Install the Linux Agent.

- c. Restart the `phParser` module:

```
su admin
phtools --stop phParser
phtools --start phParser
```

Follow the steps below to install FortiSIEM Linux Agent:

1. Find the FortiSIEM Linux Agent download location.
2. Find the Organization ID, Organization Name and Agent Registration Credentials:
 - a. Log in to FortiSIEM in Super Global mode as Admin user.
 - b. Go to **ADMIN > Setup > Organizations** and locate the Organization (ID, Name) to which this Agent belongs. If not present, then create an Organization.
 - c. Locate the Agent Registration User and Password for the Organization. If not present, define them.
3. Make sure the Templates and Host to Template association policies are defined for this Host:
 - a. Log in to FortiSIEM in Super Global mode.
 - b. Go to **ADMIN > Setup > Linux Agent** tab and make sure the templates and host to template associations are defined. One of the host-to-template association policies must match this Agent. The first matched policy will be selected.
4. Install the Agent:
 - a. SSH to the host as `root`.
 - b. Based on the information from steps #1 and #2 above, follow one of the options below:

- 2-Step Install

- i. Download the installer using the command:

```
wget https://<FortiSIEM_Download_Location>/fortisiem-linux-agent-installer-7.2.0.0237.sh
```

- ii. Install the Agent:

Notes on using special characters in password:

- Choose characters from the set published here: <https://owasp.org/www-community/password-special-characters>
- The password needs to be enclosed in single quotes if the single quote character (') is NOT used as part of the password itself.
- If the password contains single quote('), then use Backslash(\) to escape.

Example if you want the password `Password'11`

Use: `./fortisiem-linux-agent-installer-6.5.0.1501.sh -s 172.30.57.23 -i 1`

```
-o super -u test -p Password\`11
Example if you want the password Password*11
Use ./fortisiem-linux-agent-installer-6.5.0.1501.sh -s 172.30.57.23 -i 1 -
o super -u test -p `Password*11`
```

```
bash fortisiem-linux-agent-installer-7.2.0.0237.sh -s <SUPER_IP> -i <ORG_ID>
-o <ORG_NAME> -u <AGENT_USER> -p <AGENT_PWD> -n <HOST_NAME>
```

If certificate verification is required, then run:

```
bash fortisiem-linux-agent-installer-7.2.0.0237.sh -s <SUPER_IP> -i <ORG_ID>
-o <ORG_NAME> -u <AGENT_USER> -p <AGENT_PWD> -n <HOST_NAME> -v
```

- Download and install the Agent using the command:

```
wget https://<FortiSIEM_Download_Location>/fortisiem-linux-agent-installer-
7.2.0.0237.sh && chmod +x fortisiem-linux-agent-installer-7.2.0.0237.sh &&
./fortisiem-linux-agent-installer-7.2.0.0237.sh -s <SUPER_IP> -i <ORG_ID> -o
<ORG_NAME> -u <AGENT_USER> -p <AGENT_PWD> -n <HOST_NAME>
```

If certificate verification is required, then run:

```
wget https://<FortiSIEM_Download_Location>/fortisiem-linux-agent-installer-
7.2.0.0237.sh && chmod +x fortisiem-linux-agent-installer-7.2.0.0237.sh &&
./fortisiem-linux-agent-installer-7.2.0.0237.sh -s <SUPER_IP> -i <ORG_ID> -o
<ORG_NAME> -u <AGENT_USER> -p <AGENT_PWD> -n <HOST_NAME> -v
```

If the installation is successful, `INSTALLATION SUCCESS` message will appear in the standard output. The Agent will register to the Supervisor and start running.

5. Check **CMDB** for successful registration:
 - a. Log in to FortiSIEM in Super Global mode as Admin user.
 - b. Go to **CMDB** and search for the Agent Host name.
 - c. Check the **Status** column to see the registration status.

Installing Linux Agent Without Supervisor Communication

In typical installations, FortiSIEM Agents register to the Supervisor node, but send the events by using the Collector. In many MSSP situations, customers do not want Agents to directly communicate with the Supervisor node. This requirement can be satisfied by setting up the Collector as an HTTPS proxy between the Agent and the Supervisor. This section describes the required configurations.

- [Step 1: Setup the Collector as an HTTPS Proxy](#)
- [Step 2: Install Agents to Work with the Collector](#)

Step 1: Setup the Collector as an HTTPS Proxy

Follow these steps to setup the Collector as an HTTPS proxy:

1. Log in to the Collector.
2. Go to `/etc/httpd/conf.d`.
3. Create the configuration file `agent-proxy.conf` with the content [below](#).

4. Restart httpd, for example:

```
service httpd restart
```

agent-proxy.conf Content

```
ProxyPassMatch /LinuxAgentUpgrade/.* https://{actual IP address of the Supervisor
node}:443

ProxyPassReverse /LinuxAgentUpgrade/.* https://{actual IP address of the Supervisor
node}:443

ProxyPass /phoenix/rest/register/linuxAgent https://{actual IP address of the Supervisor
node}/phoenix/rest/register/linuxAgent
ProxyPassReverse /phoenix/rest/register/linuxAgent https://{actual IP address of the
Supervisor node}/phoenix/rest/register/linuxAgent

ProxyPass /phoenix/rest/linuxAgent/update https://{actual IP address of the Supervisor
node}/phoenix/rest/linuxAgent/update
ProxyPassReverse /phoenix/rest/linuxAgent/update https://{actual IP address of the
Supervisor node}/phoenix/rest/linuxAgent/update

SSLProxyEngine on
SSLProxyVerify none
SSLProxyCheckPeerCN off
SSLProxyCheckPeerExpire off
```

Step 2: Install Agents to Work with the Collector

Follow these steps to install the Linux Agents to work with the Collector.

1. If you already have agents registered with the Supervisor, then uninstall them.
2. Re-install the Linux Agents, following the instructions [here](#). During installation, set the Supervisor IP to the IP address of the Collector node.

Managing Linux Agent

Follow the sections below to manage FortiSIEM Linux Agent:

Displaying Agent Status

1. SSH to the host as `root`.
2. Run the command to display the Agent Status: `service fortisiem-linux-agent status`
The Agent status will be displayed in the standard output.

Starting Agent

1. SSH to the host as `root`.
2. Run the command to start the Agent: `service fortisiem-linux-agent start`

Stopping Agent

1. SSH to the host as `root`.
2. Run the command to stop the Agent: `service fortisiem-linux-agent stop`

Changing FortiSIEM Linux Agent IP Address

If you change the IP address of your Linux Agent, you must restart the Linux Agent Service by running the following command:

```
systemctl restart fortisiem-linux-agent
```

Uninstalling Linux Agent

Follow the steps below to uninstall Linux Agent:

1. SSH to the host as `root`
2. Run the command: `/opt/fortinet/fortisiem/linux-agent/bin/fortisiem-linux-agent-uninstall.sh`

If uninstall is successful, `UNINSTALL success` message will appear in the standard output.

Upgrading Linux Agent with FortiSIEM 6.4.0 and Higher

If you have FortiSIEM 6.4.0 or higher, upgrades can be performed from the Supervisor.

Take the following steps:

1. Navigate to **ADMIN > Settings > System > Image Server**.
2. Follow the steps [here](#).

Adding Permissions for Linux Agent FIM

The following permission instructions allow FortiSIEM Agent to monitor files and directories owned by root.

Option 1: Modify File and Directory Permissions in a broad way



This change is simple, but other users also have access.

1. Add execute(x) permission to parent directory.
 - `chmod +x <parent_dir>`
2. For monitoring a file, add read(r) permission to the target file.

- `chmod +r <target_file>`

3. For monitoring a directory, add read and execute(rx) permission to the target directory.

- `chmod +rx <target_dir>`

Example 1: Monitor file: `/etc/audit/rules.d/audit.rules`

Issue the following commands.

- `chmod +x /etc/audit`
- `chmod +x /etc/audit/rules.d`
- `chmod +r /etc/audit/rules.d/audit.rules`

Example 2: Monitor a directory: `/etc/audit/rules.d`

Issue the following commands.

- `chmod +x /etc/audit/rules.d`
- `chmod -R +rx /etc/audit/rules.d`

Example 3: Monitor files `/etc/password` and `/etc/resolv.conf`

Issue the following commands.

- `chmod +x /etc`
- `chmod +r /etc/password`
- `chmod +r /etc/resolv.conf`

Option 2: Modify File and Directory Permissions only for fsmadmin user

1. Set acl to parent dirs, parent directories need 'x' permission.

- `setfacl -m u:fsmadmin:x <path_to_parent_dir>`

2. For monitoring a file, just need 'r' permission.

- `setfacl -m u:fsmadmin:r <path_to_file>`

3. For monitoring a directory, need to recursively set "r+x" permission.

- `setfacl -R -m u:fsmadmin:rx <path_to_target_dir>`

REST APIs used for Communication

A Linux Agent uses the following REST APIs:

Purpose	URL	Notes
Registration to Supervisor	<code>https://<SuperFQDN>:<port>/phoenix/rest/register/linuxAgent</code>	Supported Port is 443
Status update to Supervisor	<code>https://<SuperFQDN>:<port>/phoenix/rest/linuxAgent/update</code>	Supported Port is 443
Event Upload to Collectors	<code>https://<CollectorFQDNorIP>:<port>/linuxupload</code>	Supported Port is 443

Troubleshooting from Linux Agent

The debugging information is available in two log files:

- Agent Service logs are located in `/opt/fortinet/fortisiem/linux-agent/log/fortisiem-linux-agent.log`
- Agent Application log files are located in `/opt/fortinet/fortisiem/linux-agent/log/phoenix.log`

Log Rotating `/var/log/messages` to Prevent Filling Up the Root Disk

When FSM Linux agent is installed on a Linux machine, the agent also requires the installation of `auditd` process, and configuration of `auditd` to monitor audit activity on the machine. The `auditd` process can generate logs in `/var/log/messages`, which can grow quickly, potentially filling up the disk in the root (`/`) partition. Linux systems have log rotating policies to rotate `/var/log/messages`. However, these policies are not aggressive enough to prevent the disk from getting full. It is necessary to add a new log rotate configuration to aggressively rotate `/var/log/messages` every 30 minutes to prevent the disk from becoming full. Follow the steps below to add this new log rotate configuration.

1. As `sudo/root` user, install the log rotate software package on Linux if it is not installed already:
 - a. For CentOS/Redhat/Amazon Linux:

```
# yum install -y logrotate
```
 - b. Debian Linux/Ubuntu:

```
# apt-get install logrotate
```
2. As `sudo/root` user, add the log rotate configuration file `logrotate-linuxagent.conf` under the `/etc/logrotate.d` directory as illustrated below:

```
# cd /etc/logrotate.d
# cat > logrotate-linuxagent.conf
/var/log/messages {
size 50M
copytruncate
dateext dateformat-%Y-%m-%d-%s
compress
delaycompress
notifempty
rotate 10
missingok
postrotate
/usr/bin/systemctl kill -s HUP rsyslog.service >/dev/null 2>&1 || true
endscript
}
```

3. As `sudo/root` user, make sure `crond` `systemd` service is active.

```
# systemctl status crond
```

- `crond.service` - Command Scheduler

```
Loaded: loaded (/usr/lib/systemd/system/crond.service; enabled; vendor preset:
```

```
enabled)
  Active: active (running) since Tue 2021-02-16 15:26:02 PST; 1 day 23h ago
Main PID: 1861 (crond)
  Tasks: 1 (limit: 820669)
  Memory: 98.6M
  CGroup: /system.slice/crond.service
          └─1861 /usr/sbin/crond -n
.....
```

4. As sudo/root user, create a crontab configuration file to run logrotate with the above configuration file every 30 minutes:

```
# cd /etc/cron.d
# cat > crond-logrotate.conf
*/30 * * * * root /usr/sbin/logrotate /etc/logrotate.d/logrotate-linuxagent.conf
```

5. Verify whether log files are rotated in a busy system after FSM Linux agent is installed.

```
\> cd /var/log
\>ls -arlu messages*
-rw----- 1 root root 71944 Feb 19 08:30 messages-2021-02-19-1613752201
-rw----- 1 root root 6081 Feb 19 08:00 messages-2021-02-19-1613750401.gz
-rw----- 1 root root 5426 Feb 19 07:30 messages-2021-02-19-1613748601.gz
-rw----- 1 root root 6176 Feb 19 07:00 messages-2021-02-19-1613746801.gz
-rw----- 1 root root 5387 Feb 19 06:30 messages-2021-02-19-1613745001.gz
-rw----- 1 root root 6085 Feb 19 06:00 messages-2021-02-19-1613743201.gz
-rw----- 1 root root 5062 Feb 19 05:30 messages-2021-02-19-1613741401.gz
-rw----- 1 root root 5606 Feb 19 05:00 messages-2021-02-19-1613739601.gz
-rw----- 1 root root 5432 Feb 19 04:30 messages-2021-02-19-1613737801.gz
-rw----- 1 root root 6072 Feb 19 04:00 messages-2021-02-19-1613736001.gz
-rw----- 1 root root 533638 Feb 19 08:30 messages
```



www.fortinet.com

Copyright© 2025 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's Chief Legal Officer, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.