

# CLI Reference

FortiMail 7.2.8



**FORTINET DOCUMENT LIBRARY**

<https://docs.fortinet.com>

**FORTINET VIDEO LIBRARY**

<https://video.fortinet.com>

**FORTINET BLOG**

<https://blog.fortinet.com>

**CUSTOMER SERVICE & SUPPORT**

<https://support.fortinet.com>

**FORTINET TRAINING & CERTIFICATION PROGRAM**

<https://www.fortinet.com/training-certification>

**FORTINET TRAINING INSTITUTE**

<https://training.fortinet.com>

**FORTIGUARD LABS**

<https://www.fortiguard.com>

**END USER LICENSE AGREEMENT**

<https://www.fortinet.com/doc/legal/EULA.pdf>

**FEEDBACK**

Email: [techdoc@fortinet.com](mailto:techdoc@fortinet.com)



July 08, 2025

FortiMail 7.2.8 CLI Reference

06-728-000000-20250708

# TABLE OF CONTENTS

<b>Change Log</b> .....	<b>17</b>
<b>Using the CLI</b> .....	<b>18</b>
Connecting to the CLI .....	18
Local console connection and initial configuration .....	19
Enabling access to the CLI through the network (SSH or Telnet) .....	21
Connecting to the CLI using SSH .....	22
Connecting to the CLI using Telnet .....	23
Logging out from the CLI console .....	24
Command syntax .....	24
Terminology .....	25
Indentation .....	26
Notation .....	26
Sub-commands .....	28
Permissions .....	31
Tips and tricks .....	35
Help .....	36
Shortcuts and key commands .....	36
Command abbreviation .....	37
Environment variables .....	37
Special characters .....	37
Language support .....	38
Screen paging .....	39
Baud rate .....	39
Editing the configuration file on an external host .....	39
<b>config</b> .....	<b>40</b>
antispam adult-image-analysis .....	41
Syntax .....	41
antispam behavior-analysis .....	42
Syntax .....	42
Related topics .....	42
antispam bounce-verification .....	42
Syntax .....	42
Related topics .....	43
antispam deepheader-analysis .....	43
Syntax .....	43
Related topics .....	44
antispam dmarc-report .....	44
Syntax .....	44
antispam endpoint reputation blacklist .....	45
Syntax .....	45
Related topics .....	45
antispam endpoint reputation exempt .....	45
Syntax .....	45
Related topics .....	46

antispam greylist exempt .....	46
Syntax .....	46
Related topics .....	47
antispam quarantine-report .....	47
Syntax .....	48
Related topics .....	48
antispam settings .....	49
Syntax .....	49
Related topics .....	57
antispam trusted .....	57
Syntax .....	57
Related topics .....	57
archive account .....	58
Syntax .....	58
Related topics .....	60
archive exempt-policy .....	60
Syntax .....	60
Related topics .....	61
archive journal .....	61
Syntax .....	61
archive policy .....	62
Syntax .....	62
Related topics .....	63
calendar server .....	63
Syntax .....	63
customized-message .....	64
Syntax .....	64
Related topics .....	65
alert-email .....	66
as-sender-rate-notify .....	66
attachment-filtering-notify .....	67
content-disarm-reconstruct .....	68
custom-webmail-login .....	69
disclaimer-insertion .....	69
email-template-av-repack .....	70
email-template-notify-generic .....	71
ibe-login-page .....	72
ibe-notify-account-delete .....	73
ibe-notify-account-expiry .....	73
ibe-notify-account-expiry-alert .....	74
ibe-notify-account-lock .....	75
ibe-notify-account-reset .....	76
ibe-notify-account-reset-done .....	77
ibe-notify-activation .....	77
ibe-notify-config-change .....	78
ibe-notify-password-reset .....	79
ibe-notify-password-reset-done .....	80
ibe-notify-pull-message .....	81

ibe-notify-push-message .....	81
ibe-notify-user-register-done .....	82
ibe-notify-wread-notif .....	83
ibe-notify-wunread-rcpt .....	84
ibe-notify-wunread-sender .....	85
ibe-password-reset-page .....	85
ibe-register-page .....	86
ibe-tfa-email-verify .....	87
ibe-tfa-register-page .....	87
ibe-tfa-sms-verify .....	88
log-report .....	89
login-disclaimer .....	89
reject-content-attachment .....	90
reject-content-message .....	91
reject-delivery .....	91
reject-endpoint-reputation .....	92
reject-spam .....	93
reject-virus-message .....	93
reject-virus-suspicious .....	94
replace-content-attachment .....	95
replace-content-body .....	95
replace-content-subject .....	96
replace-dlp-body .....	97
replace-dlp-subject .....	97
replace-virus-message .....	98
replace-virus-suspicious .....	99
report-active-mailbox-summary .....	99
report-quarantine-summary .....	100
url-protection-allow-with-confirmation .....	101
url-protection-block .....	101
url-protection-remove .....	102
url-protection-url-evaluation .....	103
dlp scan-rules .....	103
Syntax .....	104
domain .....	105
Syntax .....	105
config cal resource .....	106
config customized-message .....	106
config domain-info .....	107
config domain-setting .....	108
config policy recipient .....	118
config profile account-sync .....	121
config user mail .....	123
domain-association .....	124
Syntax .....	125
Related topics .....	125
file content-disarm-reconstruct .....	125
Syntax .....	126
file decryption password .....	127

Syntax .....	127
file filter .....	127
Syntax .....	127
file signature .....	128
Syntax .....	128
<b>log setting cloud .....</b>	<b>129</b>
Syntax .....	129
log setting remote .....	132
Syntax .....	132
Related topics .....	134
log setting local .....	134
Syntax .....	134
Related topics .....	136
log alertemail recipient .....	136
Syntax .....	137
Example .....	137
Related topics .....	137
log alertemail setting .....	137
Syntax .....	137
Related topics .....	138
mailsetting email-addr-handling .....	139
Syntax .....	139
mailsetting email-continuity .....	139
Syntax .....	139
mailsetting host-mapping .....	140
Syntax .....	140
Related topics .....	140
mailsetting mail-scan-options .....	141
Syntax .....	141
Related topics .....	141
mailsetting preference .....	142
Syntax .....	142
mailsetting proxy-smtp .....	143
Syntax .....	143
Related topics .....	144
mailsetting quarantine-rescan-options .....	144
Syntax .....	144
mailsetting relay-host-list .....	145
Syntax .....	145
Related topics .....	146
mailsetting sender-rewriting-scheme .....	146
Syntax .....	147
mailsetting smtp-rcpt-verification .....	147
Syntax .....	147
mailsetting storage central-ibe .....	148
Syntax .....	148
mailsetting storage central-quarantine .....	149

Syntax .....	149
Related topics .....	150
mailsetting storage config .....	150
Syntax .....	150
Related topics .....	152
mailsetting systemquarantine .....	152
Syntax .....	152
Related topics .....	153
ms365 account .....	153
Syntax .....	153
ms365 policy .....	155
Syntax .....	155
ms365 profile action .....	157
Syntax .....	157
ms365 profile antispam .....	158
ms365 profile antivirus .....	158
ms365 profile bec .....	159
Syntax .....	159
Syntax .....	159
ms365 profile content .....	160
ms365 profile dlp .....	160
ms365 setting .....	160
Syntax .....	161
policy access-control receive .....	161
Syntax .....	162
Related topics .....	166
policy access-control delivery .....	166
Syntax .....	166
Related topics .....	168
policy delivery-control .....	168
Syntax .....	168
policy ip .....	169
Syntax .....	169
Related topics .....	171
policy recipient .....	171
Syntax .....	171
Related topics .....	174
profile access-control .....	174
Syntax .....	175
profile antispam .....	178
Syntax .....	178
Related topics .....	190
profile antispam-action .....	190
Syntax .....	190
Related topics .....	193
profile antivirus .....	194
Syntax .....	194

Related topics .....	196
profile antivirus-action .....	196
Syntax .....	196
Related topics .....	200
profile authentication .....	200
Syntax .....	201
Related topics .....	203
profile bec .....	204
Syntax .....	204
Related topics .....	205
profile certificate-binding .....	205
Syntax .....	205
Related topics .....	206
profile content .....	206
Syntax .....	206
Related topics .....	212
profile content-action .....	213
Syntax .....	213
Related topics .....	217
profile cousin-domain .....	217
Syntax .....	217
profile dictionary .....	218
Syntax .....	218
Related topics .....	220
profile dictionary-group .....	220
Syntax .....	220
Related topics .....	221
profile dlp .....	221
Syntax .....	221
profile email-address-group .....	222
Syntax .....	222
Related topics .....	222
profile encryption .....	222
Syntax .....	222
Related topics .....	223
profile geoip-group .....	223
Syntax .....	223
profile impersonation .....	224
Syntax .....	224
profile ip-address-group .....	225
Syntax .....	225
Related topics .....	225
profile ip-pool .....	226
Syntax .....	226
profile ldap .....	226
Syntax .....	227
Email address mapping .....	240

Related topics .....	242
profile mail-routing .....	242
Syntax .....	242
profile notification .....	243
Syntax .....	243
profile replacement-message .....	243
Syntax .....	244
profile resource .....	244
Syntax .....	244
profile session .....	247
Syntax .....	247
Related topics .....	259
profile tls .....	259
Syntax .....	259
Related topics .....	261
profile url-filter .....	261
Syntax .....	261
<b>report domain-mail-stats .....</b>	<b>262</b>
Syntax .....	262
report mail .....	262
Syntax .....	262
Related topics .....	265
report mailbox .....	265
Syntax .....	265
sensitive data .....	266
Syntax .....	266
system accprofile .....	267
Syntax .....	268
Related topics .....	270
system admin .....	270
Syntax .....	270
Related topics .....	272
system advanced-management .....	272
Syntax .....	272
Related topics .....	273
system appearance .....	274
Syntax .....	274
Related topics .....	275
system backup-restore-mail .....	275
Syntax .....	276
Related topics .....	277
system certificate ca .....	277
Syntax .....	278
Related topics .....	278
system certificate crl .....	278
Syntax .....	278
Related topics .....	278

system certificate local .....	279
Syntax .....	279
Related topics .....	280
system certificate remote .....	280
Syntax .....	280
Related topics .....	280
system config-control .....	280
Syntax .....	281
system csf .....	281
Syntax .....	281
system ddns .....	282
Syntax .....	282
Related topics .....	283
system disclaimer .....	283
Syntax .....	284
Related topics .....	285
system disclaimer-exclude .....	286
Syntax .....	286
Related topics .....	286
system dns .....	286
Syntax .....	287
Related topics .....	288
system domain-group .....	288
Syntax .....	288
Related topics .....	288
system encryption ibe .....	289
Syntax .....	289
Related topics .....	292
system encryption ibe-auth .....	292
Syntax .....	292
Related topics .....	293
system fortiguard antivirus .....	293
Syntax .....	293
Related topics .....	295
system fortiguard antispam .....	295
Syntax .....	296
Related topics .....	297
system fortiguard url-protection .....	298
Syntax .....	298
system fortisandbox .....	299
Syntax .....	300
system geoup-override .....	302
Syntax .....	302
system global .....	302
Syntax .....	302
Related topics .....	306
system ha .....	306

Syntax .....	306
Related topics .....	315
system interface .....	316
Syntax .....	316
Related topics .....	321
system link-monitor .....	321
Syntax .....	321
system mailserv .....	321
Syntax .....	321
Related topics .....	327
system password-policy .....	328
Syntax .....	328
Related topics .....	328
system port-forwarding .....	329
Syntax .....	329
system route .....	329
Syntax .....	329
Related topics .....	330
system saml .....	330
Syntax .....	330
system scheduled-backup .....	331
Syntax .....	331
system security crypto .....	331
Syntax .....	331
system security authserver .....	332
Syntax .....	332
system snmp community .....	333
Syntax .....	333
Related topics .....	333
system snmp sysinfo .....	333
Syntax .....	333
Related topics .....	334
system snmp threshold .....	334
Syntax .....	334
Related topics .....	335
system snmp user .....	335
Syntax .....	335
Related topics .....	337
system time manual .....	337
Syntax .....	337
Related topics .....	338
system time ntp .....	338
Syntax .....	338
Related topics .....	339
system wccp settings .....	339
Syntax .....	339
system web-service .....	339

Syntax .....	340
Related topics .....	341
system webfilter local-category .....	341
Syntax .....	342
system webfilter local-rating .....	342
Syntax .....	342
system webmail-language .....	342
Syntax .....	343
Related topics .....	343
user alias .....	343
Syntax .....	344
Related topics .....	344
user map .....	344
Syntax .....	346
Related topics .....	347
user pki .....	347
Syntax .....	348
Related topics .....	349
<b>execute .....</b>	<b>350</b>
backup .....	350
Syntax .....	351
Optionally encrypt backup content .....	351
Related topics .....	352
backup-restore .....	352
Syntax .....	352
Related topics .....	353
blocklist .....	353
Syntax .....	353
Related topics .....	354
certificate .....	354
Syntax .....	354
Related topics .....	356
checklogdisk .....	356
Syntax .....	356
Related topics .....	356
checkmaildisk .....	356
Syntax .....	357
Related topics .....	357
cleanqueue .....	357
Syntax .....	357
Related topics .....	357
create .....	357
Syntax .....	357
Related topics .....	359
date .....	359
Syntax .....	359
Related topics .....	359

db	359
Syntax	360
Related topics	360
dlp	360
Syntax	361
endpoint	361
Syntax	361
erase-filesystem	361
Syntax	361
factoryreset	362
Syntax	362
Example	362
Related topics	362
factoryreset config	362
Syntax	363
Related topics	363
factoryreset config2	363
Syntax	363
Related topics	363
factoryreset disk	363
Syntax	363
Related topics	363
factoryreset keeplicense	364
Syntax	364
Related topics	364
factoryreset shutdown	364
Syntax	364
Related topics	364
factoryreset2	364
Syntax	365
Example	365
factoryreset2 keeplicense	365
Syntax	365
Related topics	365
fips	365
Syntax	366
Related topics	366
formatlogdisk	366
Syntax	367
Example	367
Related topics	367
formatmaildisk	367
Syntax	368
Example	368
Related topics	368
formatmaildisk-backup	368
Syntax	368

Related topics .....	368
forticloud .....	369
Syntax .....	369
ha commands .....	369
Syntax .....	369
Related topics .....	370
ibe data .....	370
Syntax .....	370
Related topics .....	370
ibe user .....	370
Syntax .....	371
Related topics .....	371
license .....	371
Syntax .....	371
lvm .....	371
Syntax .....	372
maintain .....	372
Syntax .....	372
Example .....	372
Related topics .....	373
nslookup .....	373
Syntax .....	373
Example .....	374
Related topics .....	374
partitionlogdisk .....	374
Syntax .....	375
Related topics .....	375
ping .....	375
Syntax .....	375
Example .....	375
Example .....	376
Related topics .....	376
ping-option .....	376
Syntax .....	376
Example .....	377
Related topics .....	378
ping6 .....	378
Syntax .....	378
Related topics .....	378
ping6-option .....	378
Syntax .....	379
Related topics .....	379
raid .....	380
Syntax .....	380
Example .....	380
Related topics .....	380
reboot .....	380

Syntax .....	380
Example .....	381
Related topics .....	381
reload .....	381
Syntax .....	382
Related topics .....	382
restore as .....	382
Syntax .....	382
Related topics .....	382
restore av .....	382
Syntax .....	382
Related topics .....	383
restore config .....	383
Syntax .....	383
Example .....	384
Example .....	384
Related topics .....	384
restore image .....	385
Syntax .....	385
Example .....	385
Related topics .....	385
restore mail-queues .....	386
Syntax .....	386
Related topics .....	386
safelist .....	386
Syntax .....	386
Related topics .....	387
sched-backup .....	387
Syntax .....	388
shutdown .....	388
Syntax .....	388
Example .....	388
Related topics .....	388
smtptest .....	389
Syntax .....	389
Example .....	389
Related topics .....	389
ssh .....	390
Syntax .....	390
storage .....	390
Syntax .....	390
telnettest .....	390
Syntax .....	391
Example .....	391
Related topics .....	391
traceroute .....	391
Syntax .....	391
Example .....	392

---

Example .....	392
Example .....	392
Related topics .....	393
update .....	393
Syntax .....	393
Related topics .....	393
user-config .....	393
Syntax .....	393
Related topics .....	394
vm .....	394
Syntax .....	394
<b>get .....</b>	<b>395</b>
system performance .....	396
Syntax .....	396
Example .....	396
Related topics .....	396
system status .....	397
Syntax .....	397
Example .....	397
Related topics .....	398
<b>show &amp; show full-configuration .....</b>	<b>399</b>

# Change Log

Date	Change Description
2023-11-02	Initial release.
2024-12-09	Fix to safe-relay action in <a href="#">policy access-control receive on page 161</a> .

# Using the CLI

The command line interface (CLI) is an alternative to the web user interface (web UI).

Both can be used to configure the FortiMail unit. However, to perform the configuration, in the web UI, you would use buttons, icons, and forms, while, in the CLI, you would either type lines of text that are commands, or upload batches of commands from a text file, like a configuration script.

If you are new to Fortinet products, or if you are new to the CLI, this section can help you to become familiar.

This section contains the following topics:

- [Connecting to the CLI on page 18](#)
- [Command syntax on page 24](#)
- [Sub-commands on page 28](#)
- [Permissions on page 31](#)
- [Tips and tricks on page 35](#)

## Connecting to the CLI

You can access the CLI in two ways:

- **Locally** — Connect your computer directly to the FortiMail unit's console port.
- **Through the network** — Connect your computer through any network attached to one of the FortiMail unit's network ports. The network interface must have enabled Telnet or Secure Shell (SSH) administrative access if you will connect using an SSH/Telnet client, or HTTP/HTTPS administrative access if you will connect using the **CLI Console** widget in the web-based manager.

Local access is required in some cases.

If you are installing your FortiMail unit for the first time and it is not yet configured to connect to your network, unless you reconfigure your computer's network settings for a peer connection, you may only be able to connect to the CLI using a local serial console connection.

Restoring the firmware utilizes a boot interrupt. Network access to the CLI is not available until **after** the boot process has completed, and therefore local CLI access is the only viable option.

Before you can access the CLI through the network, you usually must enable SSH and/or HTTP/HTTPS and/or Telnet on the network interface through which you will access the CLI.

This section includes:

- [Local console connection and initial configuration](#)
- [Enabling access to the CLI through the network \(SSH or Telnet\) on page 21](#)
- [Connecting to the CLI using SSH on page 22](#)
- [Connecting to the CLI using Telnet on page 23](#)
- [Logging out from the CLI console on page 24](#)

## Local console connection and initial configuration

Local console connections to the CLI are formed by directly connecting your management computer or console to the FortiMail unit, using its DB-9 or RJ-45 console port.

### Requirements

- a computer with an available serial communications (COM) port
- the RJ-45-to-DB-9 or null modem cable included in your FortiMail package
- terminal emulation software such as [PuTTY](#)



The following procedure describes connection using PuTTY software; steps may vary with other terminal emulators.

### To connect to the CLI using a local serial console connection

1. Using the null modem or RJ-45-to-DB-9 cable, connect the FortiMail unit's console port to the serial communications (COM) port on your management computer.
2. On your management computer, start PuTTY.
3. In the **Category** tree on the left, go to **Connection > Serial** and configure the following:

Serial line to connect to	COM1 (or, if your computer has multiple serial ports, the name of the connected serial port)
Speed (baud)	9600
Data bits	8
Stop bits	1
Parity	None
Flow control	None

4. In the **Category** tree on the left, go to **Session** (not the sub-node, **Logging**) and from **Connection type**, select **Serial**.
5. Click **Open**.
6. Press the Enter key to initiate a connection.
7. The login prompt appears.
8. Type a valid administrator account name (such as `admin`) and press Enter.
9. Type the password for that administrator account then press Enter (in its default state, there is no password for the `admin` account).
10. The CLI displays the following text, followed by a command line prompt:  
welcome!

## Initial configurations

Once you've physically connected your computer to the FortiMail unit, you can configure the basic FortiMail system settings through the CLI. For more information on other CLI commands, see the FortiMail CLI Guide.

### To change the admin password:

```
config system admin
  edit <admin_name>
    set password <new_password>
end
```

### To change the operation mode:

```
config system global
  set operation-mode {gateway | server | transparent}
end
```

### To configure the interface IP address:

```
config system interface
  edit <interface_name>
    set ip <ip_address>
end
```

### To configure the system route/gateway:

```
config system route
  edit <route_int>
    set destination <destination_ip4mask>
    set gateway <gateway_ipv4>
    set interface <interface_name>
end
```

### To configure the DNS servers:

```
config system dns
  set primary <ipv4_address>
  set secondary <ipv4_address>
end
```

### To configure the NTP time synchronization:

```
config system time ntp
  set ntpserver {<address_ipv4 | <fqdn_str>}
  set ntpsync {enable | disable}
  set syncinterval <interval_int>
end
```

### To configure the SNMP v3 user settings:

```
config system snmp user
  edit <user_name>
    set query-status {enable | disable}
end
```

```

set queryport <port_number>
set security-level {authnopriv | authpriv | noauthnopriv}
set auth-proto {sha1 | md5}
set auth-pwd <password>
set status {enable | disable}
set trap-status {enable | disable}
set trapevent {cpu | deferred-queue | ha | ip-change | logdisk | maildisk | mem | raid |
  remote-storage | spam | system | virus}
set trapport-local <port_number>
set trapport-remote <port_number>
config host
  edit <host_no>
    set ip <class_ip>
  end
end

```

## Enabling access to the CLI through the network (SSH or Telnet)

SSH, Telnet, or **CLI Console** widget (via the web UI) access to the CLI requires connecting your computer to the FortiMail unit using one of its RJ-45 network ports. You can either connect directly, use a peer connection between the two, or through any intermediary network.



If you do not want to use an SSH/Telnet client and you have access to the web UI, you can alternatively access the CLI through the network using the **CLI Console** widget in the web UI. For details, see the [FortiMail Administration Guide](#).



If you do not want to use an SSH/Telnet client and you have access to the web-based manager, you can alternatively access the CLI through the network using the **CLI Console** widget in the web-based manager. For details, see the [FortiMail Administration Guide](#).

You must enable SSH and/or Telnet on the network interface associated with that physical network port. If your computer is **not** connected directly or through a switch, you must also configure the FortiMail unit with a static route to a router that can forward packets from the FortiMail unit to your computer.

You can do this using either:

- a local console connection (see the following procedure)
- the web manager (see the [FortiMail Administration Guide](#))

### Requirements

- a computer with an available serial communications (COM) port and RJ-45 port
- terminal emulation software such as [PuTTY](#)
- the RJ-45-to-DB-9 or null modem cable included in your FortiMail package
- a crossover or straight-through network cable autosensing ports
- prior configuration of the operating mode, network interface, and static route

## To enable SSH or Telnet access to the CLI using a local console connection

Using the network cable, connect the FortiMail unit's network port either directly to your computer's network port, or to a network through which your computer can reach the FortiMail unit.

Note the number of the physical network port.

Using a local console connection, connect and log into the CLI. For details, see [Local console connection and initial configuration on page 19](#).

Enter the following commands:

```
config system interface
  edit <interface_name>
    set allowaccess {http https ping snmp ssh telnet}
  end
```

where:

<interface\_str> is the name of the network interface associated with the physical network port, such as port1

Enter the administrative access protocols you wish to permit in a space-delimited format, such as https ssh telnet; omit protocols that you do not want to permit.

For example, to exclude HTTP, SNMP, and Telnet, and allow only HTTPS, ICMP ECHO (ping), and SSH administrative access on port1:

```
config system interface
  edit "port1"
    set allowaccess https ping ssh
  next
end
```



Telnet is not a secure access method. SSH should be used to access the CLI from the Internet or any other untrusted network.

---

To confirm the configuration, enter the command to view the access settings for the interface.

```
show system interface <interface_name>
```

The CLI displays the settings, including the management access settings, for the interface.

To connect to the CLI through the network interface, see [Connecting to the CLI using SSH on page 22](#) or [Connecting to the CLI using Telnet on page 23](#).

## Connecting to the CLI using SSH

Once the FortiMail unit is configured to accept SSH connections, you can use an SSH client on your management computer to connect to the CLI.

SSH provides both secure authentication and secure communications to the CLI. Supported SSH protocol versions, ciphers, and bit strengths vary by whether or not you have enabled FIPS-CC mode, but generally include SSH version 2 with AES-128, 3DES, Blowfish, and SHA-1.

## Requirements

- a FortiMail network interface configured to accept SSH connections (see [Enabling access to the CLI through the network \(SSH or Telnet\) on page 21](#))
- terminal emulation software such as PuTTY

## To connect to the CLI using SSH

1. On your management computer, start PuTTY.
2. In **Host Name (or IP Address)**, type the IP address of a network interface on which you have enabled SSH administrative access.
3. In **Port**, type 22.
4. From **Connection type**, select **SSH**.
5. Click **Open**.

The SSH client connects to the FortiMail unit.

The SSH client may display a warning if this is the first time you are connecting to the FortiMail unit and its SSH key is not yet recognized by your SSH client, or if you have previously connected to the FortiMail unit but it used a different IP address or SSH key. If your management computer is directly connected to the FortiMail unit with no network hosts between them, this is normal.

6. Click **Yes** to verify the fingerprint and accept the FortiMail unit's SSH key. You will not be able to log in until you have accepted the key.  
The CLI displays a login prompt.
7. Type a valid administrator account name (such as `admin`) and press **Enter**.



You can alternatively log in using an SSH key. For details, see [system admin on page 270](#).

8. Type the password for this administrator account and press **Enter**.



If four (three for FortiWeb) incorrect login or password attempts occur in a row, you will be disconnected. Wait one minute, then reconnect to attempt the login again.

---

The CLI displays a command line prompt (by default, its host name followed by a #). You can now enter CLI commands.

## Connecting to the CLI using Telnet

Once the FortiMail unit is configured to accept Telnet connections, you can use a Telnet client on your management computer to connect to the CLI.



Telnet is not a secure access method. SSH should be used to access the CLI from the Internet or any other untrusted network.

---

## Requirements

- a FortiMail network interface configured to accept Telnet connections (see [Enabling access to the CLI through the network \(SSH or Telnet\) on page 21](#))
- terminal emulation software such as PuTTY

## To connect to the CLI using Telnet

1. On your management computer, start PuTTY.
2. In **Host Name (or IP Address)**, type the IP address of a network interface on which you have enabled Telnet administrative access.
3. In **Port**, type 23.
4. From **Connection type**, select **Telnet**.
5. Click **Open**.  
The CLI displays a login prompt.
6. Type a valid administrator account name (such as `admin`) and press **Enter**.
7. Type the password for this administrator account and press **Enter**.



If three incorrect login or password attempts occur in a row, you will be disconnected. Wait one minute, then reconnect to attempt the login again.

---

The CLI displays a command line prompt (by default, its host name followed by a #). You can now enter CLI commands.

## Logging out from the CLI console

No matter how you connect to the FortiMail CLI console (direct console connection, SSH, or Telnet), to exit the console, enter the `exit` command.

## Command syntax

When entering a command, the command line interface (CLI) requires that you use valid syntax, and conform to expected input constraints. It will reject invalid commands.

Fortinet documentation uses the following conventions to describe valid command syntax.

### See also

[Using the CLI](#)

## Terminology

Each command line consists of a command word that is usually followed by words for the configuration data or other specific item that the command uses or affects:

```
get system admin
```

To describe the function of each word in the command line, especially if that nature has changed between firmware versions, Fortinet uses terms with the following definitions.

```
config system interface
  edit <port_name>
    set status {up | down}
    set ip <interface_ipv4mask>
  next
end
```

### Command syntax terminology:

1	2		1 Command
		config system interface	2 Object
		3 edit <port_name>	3 Subcommand
		set status {up   down}	4 Table
		set ip <interface_ipv4mask>	5 Option
		next	6 Field
		end	7 Value

- **Command** — A word that begins the command line and indicates an action that the FortiMail unit should perform on a part of the configuration or host on the network, such as `config` or `execute`. Together with other words, such as fields or values, that end when you press the Enter key, it forms a command line. Exceptions include multi-line command lines, which can be entered using an escape sequence (See [Shortcuts and key commands on page 36](#)).

Valid command lines must be unambiguous if abbreviated (see [Command abbreviation on page 37](#)). Optional words or other command line permutations are indicated by syntax notation (See [Notation on page 26](#)).



This CLI reference is organized alphabetically by object for the `config` command, and by the name of the command for remaining top-level commands.

- **Object** — A part of the configuration that contains tables and/or fields. Valid command lines must be specific enough to indicate an individual object.
- **Subcommand** — A kind of command that is available only when nested within the scope of another command. After entering a command, its applicable sub-commands are available to you until you exit the scope of the command, or until you descend an additional level into another sub-command. Indentation is used to indicate levels of nested commands (See [Indentation on page 26](#)).

Not all top-level commands have sub-commands. Available sub-commands vary by their containing scope (See [Sub-commands on page 28](#)).

- **Table** — A set of fields that is one of possibly multiple similar sets which each have a name or number, such as an administrator account, policy, or network interface. These named or numbered sets are sometimes

referenced by other parts of the configuration that use them (See [Notation on page 26](#)).

- **Option** — A kind of value that must be one or more words from of a fixed set of options (See [Notation on page 26](#)).
- **Field** — The name of a setting, such as `ip` or `hostname`. Fields in some tables must be configured with values. Failure to configure a required field will result in an invalid object configuration error message, and the FortiMail unit will discard the invalid table.
- **Value** — A number, letter, IP address, or other type of input that is usually your configuration setting held by a field. Some commands, however, require multiple input values which may not be named but are simply entered in sequential order in the same command line. Valid input types are indicated by constraint notation (See [Notation on page 26](#)).

## Indentation

Indentation indicates levels of nested commands, which indicate what other sub-commands are available from within the scope.

For example, the `edit` sub-command is available only within a command that affects tables, and the next sub-command is available only from within the `edit` sub-command:

```
config system interface
  edit port1
    set status up
  next
end
```

For information about available sub-commands, see [Sub-commands on page 28](#).

### See also

[Terminology](#)

[Notation](#)

## Notation

Brackets, braces, and pipes are used to denote valid permutations of the syntax. Constraint notations, such as `<address_ipv4>`, indicate which data types or string patterns are acceptable value input.

### Command syntax notation:

Convention	Description
Square brackets [ ]	A non-required word or series of words. For example: [verbose {1   2   3}] indicates that you may either omit or type both the verbose word and its accompanying option, such as: verbose 3
Angle brackets < >	A word constrained by data type.

Convention	Description
	<p>To define acceptable input, the angled brackets contain a descriptive name followed by an underscore ( <code>_</code> ) and suffix that indicates the valid data type. For example: <code>&lt;retries_int&gt;</code></p> <p>indicates that you should enter a number of retries, such as 5.</p> <p>Data types include:</p> <ul style="list-style-type: none"> <li>• <code>&lt;xxx_name&gt;</code>: A name referring to another part of the configuration, such as <code>policy_A</code>.</li> <li>• <code>&lt;xxx_index&gt;</code>: An index number referring to another part of the configuration, such as <code>0</code> for the first static route.</li> <li>• <code>&lt;xxx_pattern&gt;</code>: A regular expression or word with wild cards that matches possible variations, such as <code>*@example.com</code> to match all email addresses ending in <code>@example.com</code>. If the pattern does not, for example, accept regular expressions, but requires wild cards only, note that in the Description column.</li> <li>• <code>&lt;xxx_fqdn&gt;</code>: A fully qualified domain name (FQDN), such as <code>mail.example.com</code>.</li> <li>• <code>&lt;xxx_email&gt;</code>: An email address, such as <code>admin@mail.example.com</code>.</li> <li>• <code>&lt;xxx_url&gt;</code>: A uniform resource locator (URL) and its associated protocol and host name prefix, which together form a uniform resource identifier (URL), such as <code>http://www.fortinet./com/</code>.</li> <li>• <code>&lt;xxx_ipv4&gt;</code>: An IPv4 address, such as <code>192.168.1.99</code>.</li> <li>• <code>&lt;xxx_v4mask&gt;</code>: A dotted decimal IPv4 netmask, such as <code>255.255.255.0</code>.</li> <li>• <code>&lt;xxx_ipv4mask&gt;</code>: A dotted decimal IPv4 address and netmask separated by a space, such as <code>192.168.1.99 255.255.255.0</code>.</li> <li>• <code>&lt;xxx_ipv4/mask&gt;</code>: A dotted decimal IPv4 address and CIDR-notation netmask separated by a slash, such as <code>192.168.1.99/24</code>.</li> <li>• <code>&lt;xxx_ipv4range&gt;</code>: A hyphen ( <code>-</code> ) delimited inclusive range of IPv4 addresses, such as <code>192.168.1.1-192.168.1.255</code>.</li> <li>• <code>&lt;xxx_ipv6&gt;</code>: A colon ( <code>:</code> )-delimited hexadecimal IPv6 address, such as <code>3f2e:6a8b:78a3:0d82:1725:6a2f:0370:6234</code>.</li> <li>• <code>&lt;xxx_v6mask&gt;</code>: An IPv6 netmask, such as <code>/96</code>.</li> <li>• <code>&lt;xxx_ipv6mask&gt;</code>: An IPv6 address and netmask separated by a space.</li> <li>• <code>&lt;xxx_str&gt;</code>: A string of characters that is <b>not</b> another data type, such as <code>P@sw0rd</code>. Strings containing spaces or special characters must be surrounded in quotes or use escape sequences. See <a href="#">Special characters on page 37</a>.</li> <li>• <code>&lt;xxx_int&gt;</code>: An integer number that is <b>not</b> another data type, such as 15 for the number of minutes.</li> </ul>
Curly braces { }	<p>A word or series of words that is constrained to a set of options delimited by either vertical bars or spaces.</p> <p>You must enter at least one of the options, unless the set of options is surrounded by square brackets [ ].</p>
Options delimited by vertical bars	<p>Mutually exclusive options. For example: <code>{enable   disable}</code></p> <p>indicates that you must enter either <code>enable</code> or <code>disable</code>, but must not enter both.</p>

Convention	Description
Options delimited by spaces	<p>Non-mutually exclusive options. For example: {http https ping snmp ssh telnet}</p> <p>indicates that you may enter all or a subset of those options, in any order, in a space-delimited list, such as: ping https ssh</p> <p><b>Note:</b> To change the options, you must re-type the entire list. For example, to add snmp to the previous example, you would type: ping https snmp ssh</p> <p>If the option adds to or subtracts from the existing list of options, instead of replacing it, or if the list is comma-delimited, the exception will be noted.</p>

**See also**[Indentation](#)[Terminology](#)

## Sub-commands

Once you have connected to the CLI, you can enter commands.

Each command line consists of a command word that is usually followed by words for the configuration data or other specific item that the command uses or affects:

```
get system admin
```

Sub-commands are available from within the scope of some commands. When you enter a sub-command level, the command prompt changes to indicate the name of the current command scope. For example, after entering:

```
config system admin
```

the command prompt becomes:

```
(admin)#
```

Applicable sub-commands are available to you until you exit the scope of the command, or until you descend an additional level into another sub-command.

For example, the `edit` sub-command is available only within a command that affects tables; the next sub-command is available only from within the `edit` sub-command:

```
config system interface
  edit port1
    set status up
    next
  end
```



Sub-command scope is indicated in this guide by indentation. See [Indentation on page 26](#).

Available sub-commands vary by command. From a command prompt within `config`, two types of sub-commands might become available:

- commands affecting fields
- commands affecting tables



Syntax examples for each top-level command in this guide do not show all available sub-commands. However, when nested scope is demonstrated, you should assume that sub-commands applicable for that level of scope are available.

### Commands for tables:

<code>delete &lt;table_name&gt;</code>	<p>Remove a table from the current object.</p> <p>For example, in <code>config system admin</code>, you could delete an administrator account named <code>newadmin</code> by typing <code>delete newadmin</code> and pressing Enter. This deletes <code>newadmin</code> and all its fields, such as <code>newadmin</code>'s name and email-address.</p> <p><code>delete</code> is only available within objects containing tables.</p>
<code>edit &lt;table_name&gt;</code>	<p>Create or edit a table in the current object.</p> <p>For example, in <code>config system admin</code>:</p> <ul style="list-style-type: none"> <li>• edit the settings for the default <code>admin</code> administrator account by typing <code>edit admin</code>.</li> <li>• add a new administrator account with the name <code>newadmin</code> and edit <code>newadmin</code>'s settings by typing <code>edit newadmin</code>.</li> </ul> <p><code>edit</code> is an interactive sub-command: further sub-commands are available from within <code>edit</code>. <code>edit</code> changes the prompt to reflect the table you are currently editing.</p> <p><code>edit</code> is only available within objects containing tables.</p>
<code>end</code>	<p>Save the changes to the current object and exit the <code>config</code> command. This returns you to the top-level command prompt.</p>
<code>get</code>	<p>List the configuration of the current object or table.</p> <ul style="list-style-type: none"> <li>• In objects, <code>get</code> lists the table names (if present), or fields and their values.</li> <li>• In a table, <code>get</code> lists the fields and their values.</li> </ul>
<code>purge</code>	<p>Remove all tables in the current object.</p> <p>For example, in <code>config forensic user</code>, you could type <code>get</code> to see the list of user names, then type <code>purge</code> and then <code>y</code> to confirm that you want to delete all users.</p> <p><code>purge</code> is only available for objects containing tables.</p> <p><b>Caution:</b> Back up the FortiMail unit before performing a purge. <code>purge</code> cannot be undone. To restore purged tables, the configuration must be restored from a backup. For details, see <a href="#">backup on page 350</a>.</p> <p><b>Caution:</b> Do not purge <code>system interface</code> or <code>system admin</code> tables. <code>purge</code> does not provide default tables. This can result in being unable to connect or log in, requiring the FortiMail unit to be formatted and restored.</p>
<code>rename &lt;table_name&gt; to &lt;table_name&gt;</code>	<p>Rename a table.</p> <p>For example, in <code>config system admin</code>, you could rename <code>admin3</code> to <code>fwadmin</code> by typing <code>rename admin3 to fwadmin</code>.</p> <p><code>rename</code> is only available within objects containing tables.</p>

show	Display changes to the default configuration. Changes are listed in the form of configuration commands.
------	---

### Example of table commands:

From within the `system admin` object, you might enter:

```
edit admin_1
```

The CLI acknowledges the new table, and changes the command prompt to show that you are now within the `admin_1` table:

```
new entry 'admin_1' added
(admin_1)#
```

### Commands for fields:

abort	Exit both the <code>edit</code> and/or <code>config</code> commands without saving the fields.
chattr	Show which of the command's attributes are synchronized for HA. Use the <code>sync-disable</code> and <code>sync-unset</code> subcommands to change the attributes ( <code>chattr</code> ) that you wish to be synchronized across HA cluster members.



Only administrators with super admin privileges may configure the feature on the primary HA unit while it is operating either in primary or config-primary mode.

To define HA attribute synchronization, configure the following:

```
config <command>
  chattr sync-disable ...
  chattr sync-unset ...
end
```

Use `chattr sync-disable` to disable any attributes from being synchronized across the HA cluster.

Use `chattr sync-unset` to reset the attribute's default synchronization behavior.

You can also enter `chattr` without an argument within a `config` command to display all attributes that can be configured for HA attribute synchronization.

Additionally, use the following `diagnose` commands:

- `diagnose system ha show-sync-disable-cfg`  
Display all attributes that have been modified/disabled by the administrator.
- `diagnose system ha show-sync-disable-cfg all`  
Display all attributes that are not synchronized, including both system default and settings disabled by the administrator.
- `diagnose system ha unset-sync-disable-cfg`  
Change all modified/disabled attributes to the default synchronize action. Note that this command should be entered for both primary/config-primary and secondary/config-secondary units, as it may cause desynchronization between the cluster members.

end	Save the changes made to the current table or object fields, and exit the <code>config</code> command (to exit without saving, use <code>abort</code> instead).
-----	---

<code>get</code>	List the configuration of the current object or table. <ul style="list-style-type: none"> <li>In objects, <code>get</code> lists the table names (if present), or fields and their values.</li> <li>In a table, <code>get</code> lists the fields and their values.</li> </ul>
<code>next</code>	Save the changes you have made in the current table's fields, and exit the <code>edit</code> command to the object prompt (to save and exit completely to the root prompt, use <code>end</code> instead). <code>next</code> is useful when you want to create or edit several tables in the same object, without leaving and re-entering the <code>config</code> command each time. <code>next</code> is only available from a table prompt; it is not available from an object prompt.
<code>set &lt;field_name&gt; &lt;value&gt;</code>	Set a field's value. For example, in <code>config system admin</code> , after typing <code>edit admin</code> , you could type <code>set passwd newpass</code> to change the password of the <code>admin</code> administrator to <code>newpass</code> . <b>Note:</b> When using <code>set</code> to change a field containing a space-delimited list, type the whole new list. For example, <code>set &lt;field&gt; &lt;new-value&gt;</code> will replace the list with the <code>&lt;new-value&gt;</code> rather than appending <code>&lt;new-value&gt;</code> to the list.
<code>show</code>	Display changes to the default configuration. Changes are listed in the form of configuration commands.
<code>unset &lt;field_name&gt;</code>	Reset the table or object's fields to default values. For example, in <code>config system admin</code> , after typing <code>edit admin</code> , typing <code>unset passwd</code> resets the password of the <code>admin</code> administrator account to the default (in this case, no password).

**Example of field commands:**

From within the `admin_1` table, you might enter:

```
set passwd my1stExamplePassword
```

to assign the value `my1stExamplePassword` to the `passwd` field. You might then enter the `next` command to save the changes and edit the next administrator's table.

## Permissions

Depending on the account that you use to log in to the FortiMail unit, you may not have complete access to all CLI commands or areas of the web UI.

Access profiles and domain assignments together control which commands and areas an administrator account can access. **Permissions result from an interaction of the two.**

The domain to which an administrator is assigned can be either:

- **System:** Can access areas regardless of whether an item pertains to the FortiMail unit itself or to a protected domain. The administrator's permissions are restricted only by his or her access profile.
- **A protected domain:** Can **only** access areas that are specifically assigned to that protected domain. The administrator **cannot** access system-wide settings, files or statistics, nor most settings that can affect other protected domains, regardless of whether access to those items would otherwise be allowed by his or her access profile. The administrator **cannot** access the CLI, nor the basic mode of the web UI (For more information on the display modes of the GUI, see the [FortiMail Administration Guide](#)).



IP-based policies, the global blocklist, and the global safelist, the blocklist action, and the global Bayesian database are exceptions to this rule. Domain administrators can configure them, regardless of the fact that they could affect other domains. If you do not want to allow this, do **not** provide **Read-Write** permission to those categories in domain administrators' access profiles.

### Areas of the GUI (advanced mode) that cannot be accessed by domain administrators:

- **System > Maintenance**
- **Monitor** except for the **Personal quarantine** tab
- **System** except for the **Administrator** tab
- **System > Mail Settings** except for the domain, its subdomains, and associated domains
- **Domain & User > User > PKI User**
- **Policy > Access Control > Receiving**
- **Policy > Access Control > Delivery**
- **Profile > Authentication**
- **Profile > AntiSpam**
- **Email Archiving**
- **Log & Report**

Access profiles assign either read, write, or no access to each area of the FortiMail software. To view configurations, you must have read access. To make changes, you must have write access. For more information on configuring an access profile that administrator accounts can use, see [sensitive data on page 266](#).

There are three possible permission types for an administrator account:

- **Administrator** (also known as **all**)
- **Read & Write**
- **Read Only**

### Administrator account permissions by domain assignment:

Permission	Domain: system	Domain: example.com
<b>Administrator</b>	<ul style="list-style-type: none"> <li>• Can create, view and change all other administrator accounts except the admin administrator account</li> <li>• Can view and change all parts of the FortiMail unit's configuration, including uploading configuration backup files and restoring firmware default settings.</li> <li>• Can release and delete quarantined email messages for all protected domains.</li> <li>• Can back up and restore databases.</li> <li>• Can manually update firmware and</li> </ul>	<ul style="list-style-type: none"> <li>• Can create, view and change other administrator accounts with <b>Read &amp; Write</b> and <b>Read Only</b> permissions in its own protected domain.</li> <li>• Can only view and change settings, including profiles and policies, in its own protected domain.</li> <li>• Can only view profiles and policies created by an administrator whose <b>Domain</b> is <b>system</b>.</li> <li>• Can be only one per protected domain.</li> </ul>

Permission	Domain: system	Domain: example.com
	antivirus definitions. • Can restart and shut down the FortiMail unit.	
<b>Read &amp; Write</b>	• Can only view and change its own administrator account. • Can view and change parts of the FortiMail unit's configuration at the system and protected domain levels. • Can release and delete quarantined email messages for all protected domains. • Can back up and restore databases.	• Can only view and change its own administrator account. • Can only view and change parts of the FortiMail unit's configuration in its own protected domain. • Can only view profiles and policies created by an administrator whose <b>Domain</b> is <b>system</b> . • Can release and delete quarantined email messages in its own protected domain.
<b>Read Only</b>	• Can only view and change its own administrator account. • Can view the FortiMail unit configuration at the system and protected domain levels • Can release and delete quarantined email messages for all protected domains. • Can back up databases.	• Can only view and change its own administrator account. • Can only view settings in its own protected domain. • Can only view profiles and policies created by an administrator whose <b>Domain</b> is <b>system</b> .

**Areas of control in access profiles:**

Access control area name		Grants access to...
<b>In the web UI</b>	<b>In the CLI</b>	For each config command, there is an equivalent get/show command, unless otherwise noted.  config access requires write permission. get/show access requires read permission.
<b>Policy</b>	policy	<b>Monitor &gt; Mail Queue ...</b> <b>Monitor &gt; Greylist ...</b> <b>Monitor &gt; Reputation &gt; Sender Reputation</b> <b>Domain &amp; User &gt; Domain &gt; Domain</b> <b>System &gt; Mail Setting &gt; Proxies</b> <b>Domain &amp; User &gt; User ...</b> <b>Policy ...</b> <b>Profile ...</b> <b>AntiSpam &gt; Greylist ...</b> <b>AntiSpam &gt; Bounce Verification &gt; Settings</b> <b>AntiSpam &gt; Endpoint Reputation ...</b> <b>AntiSpam &gt; Bayesian ...</b>

Access control area name		Grants access to...
		For each config command, there is an equivalent get/show command, unless otherwise noted.
<b>In the web UI</b>	<b>In the CLI</b>	config access requires write permission. get/show access requires read permission.
		config antispam greylist exempt config antispam bounce-verification key config antispam settings config antispam trusted ... config domain config mailsetting proxy-smtp config policy ... config profile ... config user ... diagnose ... execute ... config mailsetting relayserver
<b>Block/Safelist</b>	block-safe-list	<b>Monitor &gt; Endpoint Reputation &gt; Auto blocklist</b> <b>Maintenance &gt; AntiSpam &gt; Block/Safelist Maintenance</b> <b>AntiSpam &gt; Block/Safelist ...</b>
		N/A diagnose ... execute ... get system status get system raid-performance get system performance
<b>Quarantine</b>	quarantine	<b>Monitor &gt; Quarantine ...</b> <b>AntiSpam &gt; Quarantine &gt; Quarantine Report</b> <b>AntiSpam &gt; Quarantine &gt; System Quarantine Setting</b> <b>AntiSpam &gt; Quarantine &gt; Control Account</b>
		diagnose ... execute ... config antispam quarantine-report config mailsetting systemquarantine
<b>Others</b>	others	<b>Monitor &gt; System Status ...</b> <b>Monitor &gt; Archive &gt; Email Archives</b> <b>Monitor &gt; Log ...</b> <b>Monitor &gt; Report ...</b> <b>Maintenance ... except the Block/Safelist Maintenance tab</b> <b>System ...</b> <b>Mail Settings &gt; Settings ...</b> <b>Mail Settings &gt; Address Book &gt; Address Book</b> <b>User &gt; User Alias &gt; User Alias</b> <b>User &gt; Address Map &gt; Address Map</b> <b>Email Archiving ...</b>

Access control area name		Grants access to...
In the web UI	In the CLI	<p>For each config command, there is an equivalent get/show command, unless otherwise noted.</p> <p>config access requires write permission. get/show access requires read permission.</p>
		<p><b>Log and Report ...</b></p> <pre> config archive ... config log ... config mailsetting relayserver config mailsetting storage config report config system ... config user alias config user map diagnose ... execute ... get system status </pre>

Unlike other administrator accounts whose **Access profile** is **super\_admin\_prof** and **Domain** is **System**, the **admin** administrator account exists by default and cannot be deleted. The **admin** administrator account is similar to a root administrator account. This administrator account always has full permission to view and change all FortiMail configuration options, including viewing and changing **all** other administrator accounts. It is the only administrator account that can reset another administrator's password without being required to enter the existing password. As such, it is the **only** account that can reset another administrator's password if that administrator forgets his or her password. Its name, permissions, and assignment to the **System** domain cannot be changed.



Set a strong password for the **admin** administrator account, and change the password regularly. By default, this administrator account has no password. Failure to maintain the password of the **admin** administrator account could compromise the security of your FortiMail unit.

For complete access to all commands, you must log in with the administrator account named **admin**. For access to the CLI, you must log in with a **System**-level administrator account.

## Tips and tricks

Basic features and characteristics of the CLI environment provide support and ease of use for many CLI tasks.

This section includes:

- [Help](#)
- [Shortcuts and key commands](#)
- [Command abbreviation](#)
- [Environment variables](#)
- [Special characters](#)
- [Language support](#)

- [Screen paging](#)
- [Baud rate](#)
- [Editing the configuration file on an external host](#)

## Help

To display brief help during command entry, press the question mark (?) key.

Press the question mark (?) key at the command prompt to display a list of the commands available and a description of each command.

Type a word or part of a word, then press the question mark (?) key to display a list of valid word completions or subsequent words, and to display a description of each.

## Shortcuts and key commands

### Shortcuts and key commands:

Action	Keys
List valid word completions or subsequent words. If multiple words could complete your entry, display all possible completions with helpful descriptions of each.	?
Complete the word with the next available match. Press the key multiple times to cycle through available matches.	Tab
Recall the previous command. Command memory is limited to the current session.	Up arrow, or Ctrl + P
Recall the next command.	Down arrow, or Ctrl + N
Move the cursor left or right within the command line.	Left or Right arrow
Move the cursor to the beginning of the command line.	Ctrl + A
Move the cursor to the end of the command line.	Ctrl + E
Move the cursor backwards one word.	Ctrl + B
Move the cursor forwards one word.	Ctrl + F
Delete the current character.	Ctrl + D
Abort current interactive commands, such as when entering multiple lines. If you are not currently within an interactive command such as <code>config</code> or <code>edit</code> , this closes the CLI connection.	Ctrl + C
Continue typing a command on the next line for a multi-line command. For each line that you want to continue, terminate it with a backslash (\). To complete the command line, terminate it by pressing the spacebar and then the Enter key, without an immediately preceding backslash.	\ then Enter

## Command abbreviation

In most cases, you can abbreviate words in the command line to their smallest number of non-ambiguous characters. For example, the command `get system status` could be abbreviated to `g sy st`.

Some commands may not be abbreviated. See the notes in the specific commands.

## Environment variables

The CLI supports the following environment variables. Variable names are case-sensitive.

<code>\$USERFROM</code>	The management access type ( <code>ssh</code> , <code>telnet</code> , <code>jsconsole</code> for the <b>CLI Console</b> widget and so on) and the IP address of the administrator that configured the item.
<code>\$USERNAME</code>	The account name of the administrator that configured the item.
<code>\$SerialNum</code>	The serial number of the FortiMail unit.

For example, the FortiMail unit's host name can be set to its serial number.

```
config system global
  set hostname $SerialNum
end
```

As another example, you could log in as `admin1`, then configure a restricted secondary administrator account for yourself named `admin2`, whose `first-name` is `admin1` to indicate that it is another of your accounts:

```
config system admin
  edit admin2
    set first-name $USERNAME
```

## Special characters

The characters `<`, `>`, `(`, `)`, `#`, `'`, and `"` are not permitted in most CLI fields. These characters are special characters, sometimes also called reserved characters.

You may be able to enter a special character as part of a string's value by using a special command, enclosing it in quotes, or preceding it with an escape sequence — in this case, a backslash (`\`) character.

### Entering special characters:

Character	Keys
<code>?</code>	Ctrl + V then <code>?</code>
Tab	Ctrl + V then Tab
Space (to be interpreted as part of a string value, not to end the string)	Enclose the string in quotation marks: <code>"Security Administrator"</code> . Enclose the string in single quotes: <code>'Security Administrator'</code> . Precede the space with a backslash: <code>Security\ Administrator</code> .

Character	Keys
' (to be interpreted as part of a string value, not to end the string)	\'
" (to be interpreted as part of a string value, not to end the string)	\"
\	\\

## Language support

Characters such as ñ, é, symbols, and ideographs are sometimes acceptable input. Support varies by the nature of the item being configured.

For example, the host name must not contain special characters, and so the web UI and CLI will not accept most symbols and non-ASCII encoded characters as input when configuring the host name. This means that languages other than English often are not supported. However, some configuration items, such as names and comments, may be able to use the language of your choice. But dictionary profiles support terms encoded in UTF-8, and therefore support a number of languages.

In addition, names of items in the configuration entered using non-ASCII encodings may not display correctly in event log messages.

It is simplest to use only US-ASCII characters when configuring the FortiMail unit using the web UI or CLI. Using only ASCII, you do not need to worry about:

- mail transfer agent (MTA) encoding support
- mail user agent (MUA) language support
- web browser language support
- Telnet and/or SSH client support
- font availability
- compatibility of your input's encoding with the encoding/language setting of the web UI
- switching input methods when entering a command word such as get in ASCII but a setting that uses a different encoding



If you choose to configure parts of the FortiMail unit using non-ASCII characters, verify that all systems interacting with the FortiMail unit also support the same encodings. You should also use the same encoding throughout the configuration if possible in order to avoid needing to switch the language settings of the web UI and your web browser or Telnet/SSH client while you work.

## Screen paging

You can configure the CLI to, when displaying multiple pages' worth of output, pause after displaying each page's worth of text. When the display pauses, the last line displays --More--. You can then either:

- Press the spacebar to display the next page.
- Type Q to truncate the output and return to the command prompt.

This may be useful when displaying lengthy output, such as the list of possible matching commands for command completion, or a long list of settings. Rather than scrolling through or possibly exceeding the buffer of your terminal emulator, you can simply display one page at a time.

To configure the CLI display to pause when the screen is full:

```
config system console
  set output more
end
```

## Baud rate

You can change the default baud rate of the local console connection. For more information, see the [FortiMail Administration Guide](#).

## Editing the configuration file on an external host

You can edit the FortiMail configuration on an external host by first backing up the configuration file to a TFTP server. Then edit the configuration file and restore it to the FortiMail unit.

Editing the configuration on an external host can be time-saving if you have many changes to make, especially if your plain text editor provides advanced features such as batch changes.

### To edit the configuration on your computer:

Use [backup](#) on [page 350](#) to download the configuration file to a TFTP server, such as your management computer.

Edit the configuration file using a plain text editor that supports Unix-style line endings.



Do not edit the first line. The first line(s) of the configuration file (preceded by a # character) contains information about the firmware version and FortiMail model. If you change the model number, the FortiMail unit will reject the configuration file when you attempt to restore it.

---

Use [restore config](#) on [page 383](#) to upload the modified configuration file back to the FortiMail unit.

The FortiMail unit downloads the configuration file and checks that the model information is correct. If it is, the FortiMail unit loads the configuration file and checks each command for errors. If a command is invalid, the FortiMail unit ignores the command. If the configuration file is valid, the FortiMail unit restarts and loads the new configuration.

# config

config commands configure your FortiMail settings.

This chapter describes the following config commands:

<a href="#">antispam adult-image-analysis on page 41</a>	<a href="#">mailsetting host-mapping on page 140</a>	<a href="#">profile dictionary-group on page 220</a>
<a href="#">antispam behavior-analysis on page 42</a>	<a href="#">mailsetting mail-scan-options on page 141</a>	<a href="#">profile encryption on page 222</a>
<a href="#">antispam bounce-verification on page 42</a>	<a href="#">mailsetting preference on page 142</a>	<a href="#">profile impersonation on page 224</a>
<a href="#">antispam deepheader-analysis on page 43</a>	<a href="#">mailsetting proxy-smtp on page 143</a>	<a href="#">profile ip-address-group on page 225</a>
<a href="#">antispam endpoint reputation blacklist on page 45</a>	<a href="#">mailsetting relay-host-list on page 145</a>	<a href="#">profile ip-pool on page 226</a>
<a href="#">antispam endpoint reputation exempt on page 45</a>	<a href="#">mailsetting smtp-rcpt-verification on page 147</a>	<a href="#">profile ldap on page 226</a>
<a href="#">antispam greylist exempt on page 46</a>	<a href="#">mailsetting storage central-ibe on page 148</a>	<a href="#">profile notification on page 243</a>
<a href="#">antispam quarantine-report on page 47</a>	<a href="#">mailsetting storage central-quarantine on page 149</a>	<a href="#">profile resource on page 244</a>
<a href="#">antispam settings on page 49</a>	<a href="#">mailsetting storage config on page 150</a>	<a href="#">profile session on page 247</a>
<a href="#">antispam trusted on page 57</a>	<a href="#">mailsetting systemquarantine on page 152</a>	<a href="#">profile tls on page 259</a>
<a href="#">antispam url-fgas-exempt-list</a>	<a href="#">ms365 account on page 153</a>	<a href="#">profile url-filter on page 261</a>
<a href="#">archive account on page 58</a>	<a href="#">ms365 profile action on page 157</a>	<a href="#">report domain-mail-stats on page 262</a>
<a href="#">archive exempt-policy on page 60</a>	<a href="#">ms365 profile antispam on page 158</a>	<a href="#">report mail on page 262</a>
<a href="#">archive journal on page 61</a>	<a href="#">ms365 profile antivirus on page 158</a>	<a href="#">report mailbox on page 265</a>
<a href="#">archive policy on page 62</a>	<a href="#">ms365 profile content on page 160</a>	<a href="#">sensitive data on page 266</a>
<a href="#">customized-message on page 64</a>	<a href="#">ms365 profile dlp on page 160</a>	<a href="#">system accprofile on page 267</a>
<a href="#">dlp scan-rules on page 103</a>	<a href="#">policy access-control delivery on page 166</a>	<a href="#">system admin on page 270</a>
<a href="#">domain</a>	<a href="#">config policy delivery-control on page 168</a>	<a href="#">system appearance on page 274</a>
<a href="#">domain-association</a>	<a href="#">policy ip on page 169</a>	<a href="#">system backup-restore-mail on page 275</a>
<a href="#">file content-disarm-reconstruct on page 125</a>	<a href="#">policy recipient on page 171</a>	<a href="#">system central-management</a>
<a href="#">file decryption password on page 127</a>	<a href="#">profile antispam on page 178</a>	<a href="#">system certificate ca on page 277</a>
<a href="#">file filter on page 127</a>	<a href="#">profile antispam-action on page 190</a>	<a href="#">system certificate crl on page 278</a>
<a href="#">file signature on page 128</a>	<a href="#">profile antivirus on page 194</a>	<a href="#">system certificate local on page 279</a>
<a href="#">log setting cloud on page 129</a>	<a href="#">profile antivirus-action on page 196</a>	<a href="#">system certificate remote on page 280</a>
<a href="#">log setting remote on page 132</a>	<a href="#">profile authentication on page 200</a>	<a href="#">system ddns on page 282</a>
<a href="#">log setting local on page 134</a>		<a href="#">system disclaimer on page 283</a>
<a href="#">log alertemail recipient on page 136</a>		<a href="#">system disclaimer-exclude on page 286</a>
		<a href="#">system dns on page 286</a>
		<a href="#">system encryption ibe on page 289</a>

log alertemail setting on page 137	profile certificate-binding on page 205	system encryption ibe-auth on page 292
mailsetting email-addr-handling on page 139	profile encryption on page 222 on page 206	system fortiguard antivirus on page 293
system geoip-override on page 302	profile content-action on page 213	system fortiguard antispam on page 295
system global on page 302	profile dictionary on page 218	system fortisandbox on page 299
system ha on page 306	system saml on page 330	system time ntp on page 338
system interface on page 316	system scheduled-backup on page 331	system webmail-language on page 342
system link-monitor on page 321	system security crypto on page 331	system wccp settings on page 339
system mailserv on page 321	system security authserver on page 332	user alias on page 343
system password-policy on page 328	system snmp community on page 333	user map
system port-forwarding on page 329	system snmp sysinfo on page 333	user pki on page 347
system route on page 329	system snmp threshold on page 334	
	system snmp user on page 335	
	system time manual on page 337	

## antispam adult-image-analysis

Use this command to configure the scanning behavior of FortiMail to detect adult images.

### Syntax

```
config antispam adult-image-analysis
  set max-size on page 41
  set min-size on page 41
  set rating-sensitivity on page 41
  set score-threshold on page 41
  set status {enable | disable} on page 42
end
```

Variable	Description	Default
max-size	Set the maximum image size for the unit to analyze (KB). The valid range is 1-50000.	500
min-size	Set the minimum image size for the unit to analyze (KB). The valid range is 1-1000.	10
rating-sensitivity	Set the rating-sensitivity. The higher the number the higher the sensitivity. The valid range is 0-100.	75
score-threshold	Set the score threshold. The valid range is 1-9999.	600

Variable	Description	Default
status {enable   disable}	Enable or disable adult image analysis.	enable

## antispam behavior-analysis

Use this command to analyze the similarity of uncertain email against those well-known spam messages which are received recently.

### Syntax

```
config antispam behavior-analysis
  set status {enable | disable}
  set analysis-level{high | medium | low}
end
```

Variable	Description	Default
status {enable   disable}	Enable or disable behavior analysis service.	enable
analysis-level {high   medium   low}	Enter the analysis level.	medium

### Related topics

- [antispam deepheader-analysis on page 43](#)
- [antispam greylist exempt on page 46](#)
- [antispam quarantine-report on page 47](#)
- [antispam settings on page 49](#)
- [antispam trusted on page 57](#)

## antispam bounce-verification

Use this command to configure bounce address tagging and verification.

### Syntax

```
config antispam bounce-verification ...
```

```

key
tag-exempt-list
verify-exempt-list
end

```

Variable	Description	Default
key	Enter a new or existing key.	
tag-exempt-list	Exempt domain list for BATV tagging.	
verify-exempt-list	Exempt host name of reverse DNS lookup of sending IP for BATB verification.	

## Related topics

[antispam deepheader-analysis on page 43](#)

[antispam greylist exempt on page 46](#)

[antispam quarantine-report on page 47](#)

[antispam settings on page 49](#)

[antispam trusted on page 57](#)

## antispam deepheader-analysis

Use this command to configure global deepheader-analysis scan settings used by antispam profiles.

Deepheader analysis examines the entire message header for spam characteristics.

Not all headers may be checked, depending on your configuration of [antispam trusted on page 57](#).

## Syntax

```

config antispam deepheader-analysis
set confidence <percent_float>
set greyscale-level <level_int>
end

```

Variable	Description	Default
confidence	Type the confidence percentage above which a message will be considered spam.	95.000000
<percent_float>	The deep header scan examines each message and calculates a confidence value based on the results of the decision-tree analysis. The higher the calculated confidence value, the more likely the message is considered spam. The deep header scan adds an X-FEAS-DEEPHEADER: line to the message header that includes the message's calculated confidence value.	

Variable	Description	Default
greyscale-level <level-int>	Type the grey scale threshold above which the deepheader scan will be skipped. FortiGuard antispam service uses the grey scale of 1-9 to determine spam. 1-4 means the email is a spam for sure, while 9 is not a spam for sure. Therefore, increasing this grey scale level will increase the probability to scan the email. This may increase spam catch rate but also increase false positives.	7

## Related topics

[profile antispam on page 178](#)

[antispam trusted on page 57](#)

[antispam greylist exempt on page 46](#)

[antispam settings on page 49](#)

## antispam dmarc-report

Use this command to determine which, and how many, Domain-based Message Authentication, Reporting & Conformance (DMARC) author domains may receive DMARC reports. Administrators may use these reports to determine the effectiveness of their DMARC policies.

## Syntax

```
config antispam dmarc-report
  set status {enable | disable | monitor-only}
  set max-num-of-to-domain <integer>
  set from-addr-localpart <string>
end
```

Variable	Description	Default
status {enable   disable   monitor-only}	Enable to send DMARC reports to DMARC author domains of emails that went through DMARC check. Set to <code>monitor-only</code> to collect DMARC data only.	disable
max-num-of-to-domain <integer>	Enter the maximum number of DMARC author domains you wish to send DMARC reports to per day. Set the value between 1 to 300, with the maximum limit being FortiMail platform dependent: <ul style="list-style-type: none"> <li>Up to VM02: 100</li> <li>VM02-VM04: 150</li> <li>VM04-VM08: 200</li> <li>VM08-VM16: 250</li> </ul>	100

Variable	Description	Default
	<ul style="list-style-type: none"><li>VM16-End: 300</li></ul>	
from-addr-localpart <string>	Enter the local part of the sender email address you wish to send DMARC reports from.	noreply

## antispam endpoint reputation blocklist

Use this command to manually blocklist carrier end points by MSISDN.

MSISDN numbers listed on the blocklist will have their email or text messages blocked as long as their identifier appears on the blocklist.

### Syntax

```
config antispam endpoint reputation blocklist
  edit <msisdn>
end
```

Variable	Description	Default
<msisdn>	Type the MSISDN number to blocklist carrier end point.	

## Related topics

[profile antispam on page 178](#)

[antispam trusted on page 57](#)

## antispam endpoint reputation exempt

Use this command to manually exempt carrier end points by MSISDN from automatic blocklisting due to their endpoint reputation score.

### Syntax

```
config antispam endpoint reputation exempt
  edit <msisdn>
end
```

Variable	Description	Default
<msisdn>	Type the MSISDN number to exempt carrier end point.	

## Related topics

[antispam endpoint reputation blocklist on page 45](#)

## antispam greylist exempt

Use this command to configure the greylist exempt list.

Greylist scanning blocks spam based on the behavior of the sending server, rather than the content of the messages. When receiving an email from an unknown server, the FortiMail unit will temporarily reject the message. If the mail is legitimate, the originating server will try to send it again later ([RFC 2821](#)), at which time the FortiMail unit will accept it. Spam senders rarely attempt a retry.

## Syntax

```
config antispam greylist exempt
edit <entry_index>
set recipient-pattern <recipient_pattern>
set recipient-pattern-regexp {enable | disable}
set reverse-dns-pattern <reverse-dns_pattern>
set reverse-dns-pattern-regexp {enable | disable}
set sender-ip <client_ipv4/mask>
set sender-pattern <sender_pattern>
set sender-pattern-regexp {enable | disable}
next
end
```

Variable	Description	Default
<entry_index>	Greylist exempt rule ID.	
recipient-pattern <recipient_ pattern>	Enter a pattern that defines recipient email addresses which match this rule, surrounded in slashes and single quotes (such as \ '*\ ' ).	
recipient-pattern- regexp {enable   disable}	Enter <b>enable</b> if you used regular expression syntax to define the pattern. Enter <b>disable</b> if you did <b>not</b> use regular expression syntax to define the pattern (that is, you entered a complete email address, or you entered a pattern using simple wild card characters * or ?).	disable

Variable	Description	Default
reverse-dns-pattern <reverse-dns_pattern>	Enter a pattern that defines reverse DNS query responses which match this rule, surrounded in slashes and single quotes (such as \ '*\ ' ).	
reverse-dns-pattern-regex {enable   disable}	Enter <code>enable</code> if you used regular expression syntax to define the pattern. Enter <code>disable</code> if you did <b>not</b> use regular expression syntax to define the pattern (that is, you entered a complete email address, or you entered a pattern using simple wild card characters * or ?).	disable
sender-ip <client_ip v4/mask>	Enter the IP address and netmask of the SMTP client. To match SMTP sessions from any SMTP client, enter <code>0.0.0.0/0</code> (set by default).	0.0.0.0/0
sender-pattern <sender_pattern>	Enter a pattern that defines sender email addresses which match this rule, surrounded in slashes and single quotes (such as \ '*@example.com\ ' ).	
sender-pattern-regex {enable   disable}	Enter <code>enable</code> if you used regular expression syntax to define the pattern. Enter <code>disable</code> if you did <b>not</b> use regular expression syntax to define the pattern (that is, you entered a complete email address, or you entered a pattern using simple wild card characters * or ?).	disable

## Related topics

[antispam bounce-verification on page 42](#)

[antispam deepheader-analysis on page 43](#)

[antispam quarantine-report on page 47](#)

[antispam settings on page 49](#)

[antispam trusted on page 57](#)

## antispam quarantine-report

Use these commands to configure global settings for quarantine reports.

Quarantine reports notify email users of email added to their per-recipient quarantine, and allow them to release or delete email from the quarantine.

Alternatively, you can configure quarantine report settings specifically for each protected domain. For details, see [config domain-setting on page 108](#).

By default, insecure clear text HTTP requests to access the quarantine are redirected to secure HTTPS. See [alsohttps-redirect-status {enable | disable} on page 340](#).

## Syntax

```

config antispam quarantine-report
  set report-template-name {default | default-with-icons} on page 48
  set schedule-days {monday tuesday wednesday thursday friday saturday sunday} on page 48
  set schedule-hours {<hour_int>,...} on page 48
  set web-release-hostname <fortimail_fqdn> on page 48
  set web-release-unauth-expiry <hour_int>
end

```

Variable	Description	Default
report-template-name {default   default-with-icons}	Enter a report template.	default
schedule-days {monday tuesday wednesday thursday friday saturday sunday}	Enter a space-delimited list of days of the week on which the FortiMail unit will generate spam reports.	monday tuesday wednesday thursday friday saturday sunday
schedule-hours {<hour_int>,...}	Enter a comma-delimited list of numbers corresponding to the hours of the day on which the FortiMail unit will generate spam reports.  For example, to generate spam reports on 1:00 AM, 2:00 PM, and 11:00 PM, you would enter 1, 14, 23.  Valid numbers are from 0 to 23, based upon a 24-hour clock.	12
web-release-hostname <fortimail_fqdn>	Enter an alternate resolvable fully qualified domain name (FQDN) to use in web release hyperlinks that appear in spam reports.	
web-release-unauth-expiry <hour_int>	Expiry time, in hours, of time limited webmail access to quarantine email without authorization.  Valid values are from 0 to 720. To disable expiry, enter 0.	0

## Related topics

[antispam bounce-verification on page 42](#)

[antispam deepheader-analysis on page 43](#)

[antispam greylist exempt on page 46](#)

[antispam settings on page 49](#)

[antispam trusted on page 57](#)

# antispam settings

Use these commands to configure global antispam settings.

## Syntax

```
config antispam settings
  set backend-verify <time_str>
  set bayesian-is-not-spam <local-part_str>
  set bayesian-is-spam <local-part_str>
  set bayesian-learn-is-not-spam <local-part_str>
  set bayesian-learn-is-spam <local-part_str>
  set bayesian-training-group <local-part_str>
  set blacklist-action {as-profile | discard | reject}
  set bounce-verification-action {as-profile | discard | reject}
  set bounce-verification-auto-delete-policy {never | one-month | one-year | six-months | three-
    months}
  set bounce-verification-status {enable | disable}
  set bounce-verification-tagexpiry <days_int>
  set carrier-endpoint-acct-response {enable | disable}
  set carrier-endpoint-acct-secret <password_str>
  set carrier-endpoint-acct-validate {enable | disable}
  set carrier-endpoint-attribute {Acct-Authentic ... Vendor-Specific}
  set carrier-endpoint-blocklist-window-size {15m | 30m | 60m | 90m | 120m | 240m | 360m | 480m
    | 1440m}
  set carrier-endpoint-framed-ip-attr {Framed-IP-Address | Login-IP-Host | Login-IPv6-Host |
    NAS-IP-Address | NAS-IPv6-Address}
  set carrier-endpoint-framed-ip-order {host-order | network-order}
  set carrier-endpoint-radius-port <port_int>
  set carrier-endpoint-status {enable | disable}
  set delete-ctrl-account <local-part_str>
  set dmarc-failure-action {use-policy-action | use-profile-action | use-profile-action-with-
    none}
  set dynamic-safe-list-domain <domain_str>
  set dynamic-safe-list-state {enable | disable}
  set greylist-capacity <maximum_int>
  set greylist-check-level {disable | enable | low | high}
  set greylist-delay <minutes_int>
  set greylist-init-expiry-period <hours_int>
  set greylist-ttl <ttl_int>
  set impersonation-analysis {manual | dynamic}
  set impersonation-analysis-level {aggressive | strict}
  set qr-code-image-max-size <kb_int>
  set qr-code-url-scan-status {enable | disable}
  set release-ctrl-account <local-part_str>
  set safe-block-list-entry-auto-aging-status {enable | disable}
  set safe-block-list-entry-retention safe <days>
  set safe-block-list-precedence {system session domain personal}
  set safe-block-list-tracking {enable | disable}
  set safelist-bypass-sender-auth {enable | disable}
  set scan-action-preference {single-action | multi-action}
  set session-profile-rate-control-interval <minutes>
```

```

set url-checking {strict | aggressive | extreme}
end

```

Variable	Description	Default
backend-verify <time_str>	Enter the time of day at which the FortiMail unit will automatically remove invalid per-recipient quarantines. Use the format hh:mm:ss, where hh is the hour according to a 24-hour clock, mm is the minute, and ss is the second. For example, to begin automatic invalid quarantine removal at 5:30 PM, enter 17:30:00.	4:0:0
bayesian-is-not-spam <local-part_str>	Enter the local-part portion of the email address at which the FortiMail unit will receive email messages that correct false positives. For example, if the local domain name of the FortiMail unit is example.com and you want to correct the assessment of a previously scanned spam that was actually legitimate email by sending control messages to is-not-spam@example.com, you would enter is-not-spam.	is-not-spam
bayesian-is-spam <local-part_str>	Enter the local-part portion of the email address at which the FortiMail unit will receive email messages that correct false negatives. For example, if the local domain name of the FortiMail unit is example.com and you want to correct the assessment of a previously scanned email that was actually spam by sending control messages to is-spam@example.com, you would enter is-spam.	is-spam
bayesian-learn-is-not-spam <local-part_str>	Enter the local-part portion of the email address at which the FortiMail unit will receive email messages that train it to recognize legitimate email. Unlike the is-not-spam email address, this email address will receive email that has <b>not</b> been previously seen by the Bayesian scanner. For example, if the local domain name of the FortiMail unit is example.com and you want to train the Bayesian database to recognize legitimate email by sending control messages to learn-is-not-spam@example.com, you would enter learn-is-not-spam.	learn-is-not-spam
bayesian-learn-is-spam <local-part_str>	Enter the local-part portion of the email address at which the FortiMail unit will receive email messages that train it to recognize spam. Unlike the is-spam email address, this email address will receive spam that has <b>not</b> been previously seen by the Bayesian scanner. For example, if the local domain name of the FortiMail unit is example.com and you want to train the Bayesian database to recognize spam by sending control messages to learn-is-spam@example.com, you would enter learn-is-spam.	learn-is-spam
bayesian-training-group <local-part_str>	Enter the local-part portion of the email address that FortiMail administrators can use as their sender email address when forwarding email to the "learn is spam" email address or "learn is not spam" email address. Training messages sent from this sender email address will be used to train the global or per-domain Bayesian database (whichever is selected in the protected domain) but will <b>not</b> train any per-user Bayesian database.	default-grp

Variable	Description	Default
	In contrast, if a FortiMail administrator were to forward email using their own email address (rather than the training group email address) as the sender email address, and per-user Bayesian databases were enabled in the corresponding incoming antispam profile, the FortiMail unit would also apply the training message to their own per-user Bayesian database.	
blocklist-action {as-profile   discard   reject}	<p>Use these commands to select the action that the FortiMail unit performs when an email message arrives from or, in the case of per-session profile recipient blocklists, is destined for a blocklisted email address, mail domain, or IP address. This setting affects email matching any system-wide, per-domain, per-session profile, or per-user blocklist.</p> <p>For email messages involving a blocklisted email address, domain, or IP address, select one of the following options:</p> <ul style="list-style-type: none"> <li>• <code>as-profile</code>: Apply the action selected in the antispam profile being applied to the email message. For details, see <a href="#">profile antispam-action on page 190</a>.</li> <li>• <code>discard</code>: Accept the message but delete and do not deliver it, without notifying the SMTP client.</li> <li>• <code>reject</code>: Reject the message, returning an SMTP error code to the SMTP client.</li> </ul>	discard
bounce-verification-action {as-profile   discard   reject}	<p>Enter the action that the FortiMail unit will perform if it receives a bounce address tag that is invalid.</p> <ul style="list-style-type: none"> <li>• <code>as-profile</code>: Perform the action selected in the antispam profile.</li> <li>• <code>discard</code>: Accept the message but then delete it without notifying the SMTP client.</li> <li>• <code>reject</code>: Reject the message, replying to the SMTP client with an SMTP rejection code.</li> </ul>	as-profile
bounce-verification-auto-delete-policy {never   one-month   one-year   six-months   three-months}	<p>Inactive keys will be removed after being unused for the selected time period.</p> <ul style="list-style-type: none"> <li>• <code>never</code>: Never automatically delete an unused key.</li> <li>• <code>one-month</code>: Delete a key when it hasn't been used for 1 month.</li> <li>• <code>three-months</code>: Delete a key when it hasn't been used for 3 months.</li> <li>• <code>six-months</code>: Delete a key when it hasn't been used for 6 months.</li> <li>• <code>one-year</code>: Delete a key when it hasn't been used for 12 months.</li> </ul> <p>The active key will not be automatically removed.</p>	never
bounce-verification-status {enable   disable}	<p>Enable to activate bounce address tagging and verification. Tag verification can be bypassed in IP profiles and protected domains.</p>	disable
bounce-verification-tagexpiry <days-int>	<p>Enter the number of days an email tag is valid. When this time elapses, the FortiMail unit will treat the tag as invalid. Valid range is from 3 to 30 days.</p>	7

Variable	Description	Default
carrier-endpoint-acct-response {enable   disable}	Enable/disable endpoint account validation on the RADIUS server.	disable
carrier-endpoint-acct-secret <password_str>	Type the shared secret for RADIUS account response/request validation.	
carrier-endpoint-acct-validate {enable   disable}	Enable/disable validating shared secret of account requests.	disable
carrier-endpoint-attribute {Acct-Authentic ... Vendor-Specific}	<p>Type the RADIUS account attribute associated with the endpoint user ID. If you have more than one RADIUS server and each server uses different account attribute for the endpoint user ID, you can specify up to five attributes with this command. For example, a 3G network may use the "Calling-Station-ID" attribute while an ADSL network may use the "User-Name" attribute.</p> <p>A carrier end point is any device on the periphery of a carrier's or Internet service provider's (ISP) network. It could be a subscriber's GSM cellular phone, wireless PDA, or computer using DSL service.</p> <p>Unlike MTAs, computers in homes and small offices and mobile devices such as laptops and cellular phones that send email may not have a static IP address. Cellular phones' IP addresses especially may change very frequently. After a device leaves the network or changes its IP address, its dynamic IP address may be reused by another device. Because of this, a sender reputation score that is directly associated with an SMTP client's IP address may not function well. A device sending spam could start again with a clean sender reputation score simply by rejoining the network to get another IP address, and an innocent device could be accidentally blocklisted when it receives an IP address that was previously used by a spammer.</p>	Calling-Station-Id (RADIUS attribute 31)
carrier-endpoint-blocklist-window-size {15m   30m   60m   90m   120m   240m   360m   480m   1440m}	<p>Enter the amount of previous time, in minutes, whose score-increasing events will be used to calculate the current endpoint reputation score.</p> <p>For example, if the window is 15m (15 minutes), detections of spam or viruses 0-15 minutes ago would count towards the current score; detections of spam or viruses older than 15 minutes ago would not count towards the current score.</p>	15m
carrier-endpoint-framed-ip-attr {Framed-IP-Address   Login-IP-Host   Login-IPv6-Host   NAS-IP-Address   NAS-IPv6-Address}	<p>Specify the RADIUS attribute whose value will be used as the endpoint user IP address.</p> <p>By default, the endpoint user IP address uses the value of RADIUS attribute 8 (framed IP address).</p> <p>However, if the endpoint IP address uses the value from different RADIUS attribute/number other than attribute 8, you can specify the corresponding attribute number with this command.</p> <p>You can use the "diagnose debug application msisdh" command to capture RADIUS packets and find out what attribute name/number is used to hold the IP address value.</p>	Framed-IP-Address

Variable	Description	Default
	Note that you can specify multiple values, such as both IPv4 and IPv6 attributes.	
carrier-endpoint-framed-ip-order {host-order   network-order}	Select one of the following methods for endpoint IP address formatting: <ul style="list-style-type: none"> <li>host-order: format an IP address in host order, that is, the host portion is at the beginning. For example, 1.1.168.192.</li> <li>network-order: sorts IP addresses in the network order, that is, the network portion is at the beginning. For example, 192.168.1.1.</li> </ul>	host-order
carrier-endpoint-radius-port <port_int>	Type the RADIUS server port for carrier endpoint account requests.	1813
carrier-endpoint-status {enable   disable}	Enable endpoint reputation scan for traffic examined by the session profile. This command starts the endpoint reputation daemon. You must start this daemon for the endpoint reputation feature to work.	enable
delete-ctrl-account <local_part_str>	Use this command to configure the email addresses through which email users can delete email from their per-recipient quarantines. Enter the local-part portion of the email address at which the FortiMail unit will receive email messages that control deletion of email from per-recipient quarantines. For example, if the local domain name of the FortiMail unit is example.com and you want to delete email by sending control messages to quar_delete@example.com, you would enter quar_delete.	delete-ctrl
dmARC-failure-action {use-policy-action   use-profile-action   use-profile-action-with-none}	Set a DMARC failure action: <ul style="list-style-type: none"> <li>use-policy-action: Respect all actions specified in the DMARC record.</li> <li>use-profile-action: Use the action specified in the antispam profile.</li> <li>use-profile-action-with-none: Respect p=none sender policy in the DMARC record, and use the antispam profile action otherwise.</li> </ul>	use-profile-action-with-none
dynamic-safe-list-domain <domain_str>	Enter the domain name of the dynamic safe list.	
dynamic-safe-list-state {enable   disable}	Enable the dynamic safe list.	disable
greylist-capacity <maximum_int>	Enter the maximum number of greylist items in the greylist. New items that would otherwise cause the greylist database to grow larger than the capacity will instead overwrite the oldest item. To determine the default value and acceptable range for your FortiMail model, enter a question mark (?).	Varies by model

Variable	Description	Default
greylist-check-level {disable   enable   low   high}	<p>Greylist scanning blocks spam based on the behavior of the sending server, rather than the content of the messages. When receiving an email from an unknown server, the FortiMail unit will temporarily reject the message. If the mail is legitimate, the originating server will try to send it again later (<a href="#">RFC 2821</a>), at which time the FortiMail unit will accept it. Spammers will typically abandon further delivery attempts in order to maximize spam throughput.</p> <p>Enable/disable greylist check, or set how aggressively to perform greylist check: high or low.</p> <p>The high level setting greylists all messages from unknown MTAs, while the low level setting will selectively greylist based on the age and reputation of the MTAs -- the trusted MTAs will not be greylisted whereas the new untrusted MTAs will be greylisted.</p>	high
greylist-delay <minutes_int>	<p>Enter the length in minutes of the greylist delay period.</p> <p>For the initial delivery attempt, if no manual greylist entry (exemption) matches the email message, the FortiMail unit creates a pending automatic greylist entry, and replies with a temporary failure code. During the greylist delay period after this initial delivery attempt, the FortiMail unit continues to reply to additional delivery attempts with a temporary failure code.</p> <p>After the greylist delay period elapses and before the pending entry expires (during the <code>initial_expiry_period</code>, also known as the greylist window), any additional delivery attempts will confirm the entry and convert it to an individual automatic greylist entry. The greylist scanner will then allow delivery of subsequent matching email messages.</p> <p>The valid range is between 1 and 120 minutes.</p>	10
greylist-init-expiry-period <hours_int>	<p>Enter the period of time in hours after the <code>greylistperiod</code>, during which pending greylist entries will be confirmed and converted into automatic greylist entries if the SMTP client retries delivery.</p> <p>The valid range is between 4 to 24 hours.</p>	4
greylist-ttl <ttl_int>	<p>Enter the time to live (TTL) that determines the maximum amount of time that unused automatic greylist entries will be retained.</p> <p>Expiration dates of automatic greylist entries are determined by adding the TTL to the date and time of the previous matching delivery attempt. Each time an email message matches the entry, the life of the entry is prolonged; in this way, entries that are in active use do not expire.</p> <p>If the TTL elapses without an email message matching the automatic greylist entry, the entry expires and the greylist scanner removes the entry.</p> <p>The valid range is between 1 to 60 days.</p>	30
impersonation-analysis {manual   dynamic}	<p>Email impersonation is one of the email spoofing attacks. It forges the email header to deceive the recipient because the message appears to be from a different source than the actual address.</p> <p>To fight against email impersonation, you can map display names with email addresses and check email for the mapping.</p>	manual

Variable	Description	Default
	<p>You can choose whether the impersonation analysis uses the manual mapping entries or dynamic entries. You can also use both types of entries.</p> <ul style="list-style-type: none"> <li><b>manual:</b> Use the entries you manually entered under <i>Profile &gt; AntiSpam &gt; Impersonation</i>.</li> <li><b>dynamic:</b> Use the entries automatically learned by the FortiMail mail statistics service. To enable this service, enable <code>mailstat-service</code> under <code>config system global</code>.</li> </ul>	
<code>impersonation-analysis-level</code> <code>{aggressive   strict}</code>	<ul style="list-style-type: none"> <li><b>aggressive:</b> Choose this option to check the display name email domain part in Header From.</li> <li><b>strict:</b> Choose this option not to check the display name email domain.</li> </ul> <p>For example, when you set an IA entry as:</p> <p>Display name: John Smith  Email address: john.smith@example.com</p> <p>While <code>example.com</code> is a protected domain.</p> <p>Aggressive setting will block all of the following three senders:</p> <ul style="list-style-type: none"> <li>"John Smith" &lt;spammer@abc.com&gt;</li> <li>"John.Smith@example.com" &lt;spammer@abc.com&gt;</li> <li>"OtherUser@example.com" &lt;spammer@abc.com&gt;</li> </ul> <p>But strict setting will only block the first two senders.</p>	aggressive
<code>qr-code-image-max-size</code> <kb_int>	Enter the maximum QR code image size (in kilobytes) to scan.	1000
<code>qr-code-url-scan-status</code> <code>{enable   disable}</code>	Enable or disable the scanning of QR code URLs.	disable
<code>release-ctrl-account</code> <local-part_str>	<p>Use this command to configure the email addresses through which email users can release email from their per-recipient quarantines.</p> <p>Enter the local-part portion of the email address at which the FortiMail unit will receive email messages that control deletion of email from per-recipient quarantines.</p> <p>For example, if the local domain name of the FortiMail unit is <code>example.com</code> and you want to delete email by sending control messages to <code>quar_delete@example.com</code>, you would enter <code>quar_delete</code>.</p>	
<code>safe-block-list-entry-auto-aging-status</code> <code>{enable   disable}</code>	<p>Enable to apply automatic purging of system and domain block and safe lists that are listed for a defined retention period (see <a href="#">safe-block-list-entry-retention safe &lt;days&gt;</a>).</p>	enable
<code>safe-block-list-entry-retention</code> <code>safe &lt;days&gt;</code>	Enter the retention period in days for safe and block list entries before they are automatically removed. Set the value between 1-365.	120

Variable	Description	Default
safe-block-list- precedence {system session domain personal}	By default, system safelists and blocklists have precedence over other safelists and blocklists. In some cases, you may want to change the precedence order. For example, you may want to allow a user to use their own lists to overwrite the system list. In this case, you can move “personal” ahead of “system”.	system session domain personal
safe-block-list- tracking {enable   disable}	Enable to track various system safelist and blocklist statistics, including creation time, last hit time, and hit count.  These statistics are tracked under <i>Security &gt; Block/Safe List &gt; System</i> and <i>Security &gt; Block/Safe List &gt; Domain</i> .	disable
safelist-bypass- sender-auth {enable   disable}	Enable to bypass sender authentication mechanism (SPF/DMARC/DKIM) for safelisted senders.  When disabled, if the scan result of SPF, DKIM, or DMARC is a failure, and the sender is safelisted, the result of SPF, DKIM, and DMARC takes precedence.	enable
scan-action- preference {single-action   multi-action}	Either apply only the first matching antispam filter, or multiple matching antispam filters, where each matching antispam filter action is applied until the final action is found.	multi-action
session-profile- rate-control- interval <minutes>	The rate control option enables you to control the rate at which email messages can be sent, by the number of connections, the number of messages, or the number recipients per client per period (in minutes).  This command sets the time period. Other values are set under the <code>config profile session</code> command.	30
url-checking {strict   aggressive   extreme}	When you configure an antispam profile under <i>Profile &gt; AntiSpam &gt; AntiSpam</i> , if you enable FortiGuard scan and SURBL scan, FortiMail will scan for blocklisted URLs in email bodies.  There are two types of URLs: <ul style="list-style-type: none"> <li>Absolute URLs strictly follow the URL syntax and include the URL scheme names, such as “http”, “https”, and “ftp”. For instance, <code>http://www.example.com</code>.</li> <li>Reference URLs do not contain the scheme names. For instance, <code>example.com</code>.</li> </ul> <p>In some cases, you may want to scans for both absolute and reference URLs to improve the catch rate.</p> <p>In some cases (for example, to lower false positive rates), you may want to scan for absolute URLs only.</p> <ul style="list-style-type: none"> <li><b>strict</b>: Choose this option to scan for absolute URLs only. Note that web sites without “http” or “https” but starting with “www” are also treated as absolute URLs. For instance, <code>www.example.com</code>.</li> <li><b>aggressive</b>: Choose this option to scan for both the absolute and reference URLs. Sender domains are also checked against FortiGuard.</li> </ul> <p><b>extreme</b>: Choose this option to scan for all URLs with or without schemes, including absolute URLs, reference URLs, URLs in text format, and sender domains.</p>	strict

## Related topics

[antispam bounce-verification on page 42](#)

[antispam deepheader-analysis on page 43](#)

[antispam greylist exempt on page 46](#)

[antispam quarantine-report on page 47](#)

[antispam trusted on page 57](#)

## antispam trusted

Use these commands to configure both the IP addresses of mail transfer agents (MTAs) that are trusted to insert genuine `Received:` message headers, and the IP addresses of MTAs that perform antispam scans before the FortiMail unit.

`Received:` message headers are inserted by each MTA that handles an email message in route to its destination. The IP addresses in those headers can be used as part of FortiGuard Antispam and DNSBL antispam checks, and SPF and DKIM sender validation. However, they should only be used if you trust that the `Received:` header added by an MTA is not fake — spam-producing MTAs sometimes insert fake headers containing the IP addresses of legitimate MTAs in an attempt to circumvent antispam measures.

If you trust that `Received:` headers containing specific IP addresses are always genuine, you can add those IP addresses to the `mta` list.

Note that private network addresses, defined in [RFC 1918](#), are never checked and do not need to be excluded using `config antispam trusted mta`.

Similarly, if you can trust that a previous mail hop has already scanned the email for spam, you can add its IP address to the `antispam-mta` list to omit deep header scans for email that has already been evaluated by that MTA, thereby improving performance.

## Syntax

```
config antispam trusted {mta | antispam-mta}
  edit <smtp_ipv4/mask>
end
```

Variable	Description	Default
<smtp_ipv4/mask>	Enter the IP address and netmask of an MTA.	

## Related topics

[antispam bounce-verification on page 42](#)

[antispam deepheader-analysis on page 43](#)

[antispam greylist exempt on page 46](#)

[antispam quarantine-report on page 47](#)

[antispam settings on page 49](#)

## archive account

Use this command to configure email archiving accounts.

This command applies only if email archiving is enabled.

### Syntax

```
config archive account
edit <account_name>
    set destination {local | remote}
    set forward-address <recipient_email>
    set imap-access {enable | disable}
    set index-type {full | header | none}
    set local-quota <quota_int>
    set local-quota-cache <cache_int>
    set password <password_str>
    set quota-full {overwrite | noarchive}
    set remote-directory <path_str>
    set remote-ip <ftp_ipv4>
    set remote-password <password_str>
    set remote-protocol {ftp | sftp}
    set remote-username <user_str>
    set retention-period <time_int>
    set rotation-hour <hour_int>
    set rotation-size <size_int>
    set rotation-time <time_int>
    set status {enable | disable}
end
```

Variable	Description	Default
<account_name>	Enter the email archiving account name.	archive
destination {local   remote}	Select whether to archive to the local disk or remote server.	local
forward-address <recipient_email>	Enter the email address to which all archived messages will also be forwarded. If no forwarding address exists, the FortiMail unit will not forward email when it archives it.	
imap-access {enable   disable}	Enable/disable IMAP access to the archive account.	disable

Variable	Description	Default
index-type {full   header   none}	Type full to index email by the whole email (header and body), and header by the email header only.	none
local-quota <quota_int>	Enter the local disk quota for email archiving in gigabytes (GB). The valid range depends on the amount of free disk space.	5
local-quota-cache <cache_int>	Enter the local disk quota for caching in gigabytes (GB). The valid range depends on the amount of free disk space.	5
password <password_str>	Enter the archiving account's password.	forti12356net
quota-full {overwrite   noarchive}	Enter either: noarchive: Discard the email message if the hard disk space is consumed and a new email message arrives. overwrite: Replace the oldest email message if the hard disk space is consumed and a new email message arrives.	overwrite
remote-directory <path_str>	Enter the directory path on the remote server where email archives will be stored.	
remote-ip <ftp_ip v4>	Enter the IP address of the remote server that will store email archives.	0.0.0.0
remote-password <password_Str>	Enter the password of the user account on the remote server.	
remote-protocol {ftp   sftp}	Enter either ftp or sftp to use that protocol when transferring email archives to the remote server.	sftp
remote-username <user_str>	Enter the name of a user account on the remote server.	
retention-period <time_int>	Enter the maximum age in days that rotated archive folders are kept before they are removed. The valid range is from 0 to 3650 days. The default value of 0 means no archive folders will be removed.	365
rotation-hour <hour_int>	Enter the hour of the day to start the mailbox rotation. See <a href="#">rotation-time &lt;time_int&gt;</a> .	0
rotation-size <size_int>	Enter the maximum size of the current email archiving mailbox in megabytes (MB). When the email archiving mailbox reaches either the maximum size or age, the email archiving mailbox is rolled (that is, the current email archiving mailbox is saved to a file with a new name, and a new email archiving mailbox is started). The valid range is from 10 to 800 MB.	200
rotation-time <time_int>	Enter the maximum age of the current email archiving mailbox in days.	7

Variable	Description	Default
	<p>When the email archiving mailbox reaches either the maximum size or age, the email archiving mailbox is rolled (that is, the current email archiving mailbox is saved to a file with a new name, and a new email archiving mailbox is started).</p> <p>The valid range is from 1 to 365 days.</p> <p>See <a href="#">rotation-hour &lt;hour_int&gt;</a></p>	
status {enable   disable}	Enable to activate email archiving.	enable

## Related topics

[archive exempt-policy on page 60](#)

[archive journal on page 61](#)

## archive exempt-policy

Use this command to configure the exemptions to email archiving.

This command applies only if email archiving is enabled.

## Syntax

```
config archive exempt-policy
edit <policy_id>
  set account <account_name>
  set pattern <string>
  set status {enable | disable}
  set type {sender | recipient | spam}
end
```

Variable	Description	Default
<policy_id>	<p>Enter the index number of the exemption policy.</p> <p>To view a list of existing entries, enter a question mark ( ? ).</p>	
account <account_name>	Enter the name of the email archive account that you want to apply the exemption policy to.	
pattern <string>	Enter a pattern, such as user*@example.com, that matches the attachment file name, text in the email body, text in the email subject, sender or recipient email addresses to which this exemption will apply.	*

Variable	Description	Default
status {enable   disable}	Enable to activate the email archiving exemption.	enable
type {sender   recipient   spam}	Enter one of the following exemption match types: sender: The sender email address will be evaluated for matches with pattern. recipient: The recipient email address will be evaluated for matches with pattern. spam: Do not archive spam emails.	sender

## Related topics

[archive journal on page 61](#)

[antispam url-fgas-exempt-list](#)

## archive journal

Microsoft Exchange servers can journal email and then send the journaled email to another server, such as FortiMail, for archiving.

## Syntax

```
config archive journal source
edit <journal_source_id>
    set comments
    set email-archive-status {enable | disable}
    set email-continuity-status {enable | disable}
    set host
    set recipient
    set scan-status {enable | disable}
    set sender
    set status {enable | disable}
end
```

Variable	Description	Default
<journal_source_id>	Enter the ID of the journal.	
comments	Enter general journal source comments.	
email-archive-status {enable   disable}	Enable or disable email archival of journal reports.	enable
email-continuity-status {enable   disable}	<b>Note:</b> This command is only available when the FortiMail unit is operating in either Gateway or Transparent mode.	disable

Variable	Description	Default
	Enable or disable email continuity, taking email from journal reports to users' mailboxes. When enabled, users can access inbound emails in instances where the email server behind the FortiMail unit goes offline.	
host	Enter the ip address or host name of the journal source.	
recipient	Enter the recipient email address.	
scan-status {enable   disable}	Enable or disable scanning of embedded emails within journal reports.	disable
sender	Enter the sender email address.	
status {enable   disable}	Enable or disable the journal source.	enable

## archive policy

Use this command to configure email archiving policies.

This command applies only if email archiving is enabled.

## Syntax

```
config archive policy
  edit <policy_id>
    set account <account_name>
    set pattern <string>
    set status {enable | disable}
    set type {attachment | body | deferral | recipient | sender | subject}
    set deferral-reason {spam-outbreak virus-outbreak sandbox}
  end
```

Variable	Description	Default
<policy_id>	Enter the index number of the policy. To view a list of existing entries, enter a question mark ( ? ).	
account <account_name>	Enter the name of the email archive account where you want to archive email.	
pattern <string>	Enter a pattern, such as user*@example.com, that matches the attachment file name, text in the email body, text in the email subject, sender or recipient email addresses to which this policy will apply.	*
status {enable   disable}	Enable to activate the email archiving policy.	enable

Variable	Description	Default
type {attachment   body   deferral   recipient   sender   subject}	Enter one of the following match types: <ul style="list-style-type: none"> <li>attachment: The attachment file name will be evaluated for matches with pattern.</li> <li>body: The body text will be evaluated for matches with pattern.</li> <li>deferral: The archive policy will be evaluated for matches with deferral-reason.</li> <li>recipient: The recipient email address will be evaluated for matches with pattern.</li> <li>sender: The sender email address will be evaluated for matches with pattern.</li> <li>subject: The email subject will be evaluated for matches with pattern.</li> </ul>	sender
deferral-reason {spam-outbreak virus-outbreak sandbox}	Note that this option is only available when type is set to deferral. Enter one or more of the following reasons for deferring emails for analysis: <ul style="list-style-type: none"> <li>fortisandbox: Defer email for sandbox scanning.</li> <li>spam-outbreak: Defer email for spam outbreak.</li> <li>virus-outbreak: Defer email for virus outbreak.</li> </ul>	

## Related topics

[archive exempt-policy on page 60](#)

[antispam url-fgas-exempt-list](#)

## calendar server

Use this command to enable WebDAV and CalDAV support, allowing the ability to share calendars.

## Syntax

```
config calendar server
  set webdav-status {enable | disable}
  set caldav-status {enable | disable}
end
```

Variable	Description	Default
webdav-status {enable   disable}	Enable or disable WebDAV support.	enable
caldav-status {enable   disable}	Enable or disable CalDAV support.	enable

## customized-message

Use this command to configure replacement messages.

When the FortiMail unit detects a virus in an email attachment, it replaces the attachment with a message that provides information about the virus and source of the email.

The FortiMail unit may also use replacement messages when notifying a recipient that it has blocked an email as spam or due to content filtering, or when sending a quarantine report.

You can customize the secure message notifications that secure email recipients receive when IBE encrypted email are sent to them, and configure simple network management protocol (SNMP) settings.

## Syntax

This command contains many sub-commands. Each sub-command, linked in the table below, is documented in subsequent sections.

```
config customized-message
  edit <message_name>
  next
end
```

Variable	Description	Default
<message_name>	Select the replacement message that you want to customize. The message names include: <a href="#">alert-email</a> <a href="#">as-sender-rate-notify</a> <a href="#">attachment-filtering-notify</a> <a href="#">content-disarm-reconstruct</a> <a href="#">custom-webmail-login</a> <a href="#">disclaimer-insertion</a> <a href="#">email-template-av-repack</a> <a href="#">email-template-notify-generic</a> <a href="#">ibe-login-page</a> <a href="#">ibe-notify-account-delete</a> <a href="#">ibe-notify-account-expiry</a> <a href="#">ibe-notify-account-expiry-alert</a> <a href="#">ibe-notify-account-lock</a> <a href="#">ibe-notify-account-reset</a> <a href="#">ibe-notify-account-reset-done</a> <a href="#">ibe-notify-activation</a> <a href="#">ibe-notify-config-change</a> <a href="#">ibe-notify-password-reset</a>	

Variable	Description	Default
	ibe-notify-password-reset-done	
	ibe-notify-pull-message	
	ibe-notify-push-message	
	ibe-notify-user-register-done	
	ibe-notify-wread-notif	
	ibe-notify-wunread-rcpt	
	ibe-notify-wunread-sender	
	ibe-password-reset-page	
	ibe-register-page	
	ibe-tfa-email-verify	
	ibe-tfa-register-page	
	ibe-tfa-sms-verify	
	log-report	
	login-disclaimer	
	reject-content-attachment	
	reject-content-message	
	reject-delivery	
	reject-endpoint-reputation	
	reject-spam	
	reject-virus-message	
	reject-virus-suspicious	
	replace-content-attachment	
	replace-content-body	
	replace-content-subject	
	replace-dlp-body	
	replace-dlp-subject	
	replace-virus-message	
	replace-virus-suspicious	
	report-active-mailbox-summary	
	report-quarantine-summary	
	url-protection-allow-with-confirmation	
	url-protection-block	
	url-protection-remove	
	url-protection-url-evaluation	

## Related topics

[config domain-setting](#)

[config policy recipient](#)

## alert-email

Use this sub-command to configure the variables and the default email template of the alert email.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit alert-email
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%MEETING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%MEETING%% can be weekly meeting.	
from <string>	Enter the replacement message for the from field of the event notification email.	
html-body <string>	Enter the replacement message for the email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the email body in text format.	

## as-sender-rate-notify

Use this sub-command to configure the variables and the default email template of the notifications for spam sender's sending rate.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit as-sender-rate-notify
  config variable
```

```

edit <name>
  set content
  set display-name
config email-template
edit default
  set env-from <string>
  set from <string>
  set html-body <string>
  set subject <string>
  set text-body <string>
  set to <string>
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%MEETING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%MEETING%% can be weekly meeting.	
env-from <string>	Enter the replacement message for the email Envelope From field.	
from <string>	Enter the replacement message for the email From field.	
html-body <string>	Enter the replacement email body in HTML format.	
subject <string>	Enter the replacement message for the email Subject header.	
text-body <string>	Enter the replacement email body in text format.	
to <string>	Enter the replacement message for the email To field.	

## attachment-filtering-notify

Use this sub-command to configure the variables and the default email template of the notification for attachment filtering.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```

edit attachment-filtering-notify
  config variable
  edit <name>
    set content
    set display-name
  config email-template
  edit default
    set env-from
    set env-to

```

```

    set from <string>
    set html-body <string>
    set subject <string>
    set text-body <string>
    set to <string>
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%MEETING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%MEETING%% can be weeklymeeting.	
env-from <string>	Enter the replacement message for the email Envelope From field.	
env-to <string>	Enter the replacement message for the email Envelope To field.	
from <string>	Enter the replacement message for the email From field.	
html-body <string>	Enter the replacement email body in HTML format.	
subject <string>	Enter the replacement message for the email Subject header.	
text-body <string>	Enter the replacement email body in text format.	
to <string>	Enter the replacement message for the email To field.	

## content-disarm-reconstruct

Use this sub-command to configure the variables and the default content of the notification message for Office and/or PDF attachment content disarm and reconstruction (CDR).

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```

edit content-disarm-reconstruct
  config variable
    edit <name>
      set content
      set display-name
    config message
      edit default
        set content <string>
        set format {html | multiline | text}
      end
    end
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Login.	
content <string>	Enter the replacement message for the webmail login.	
format {html   multiline   text}	Select the format for the webmail login.	html

## custom-webmail-login

Use this sub-command to configure the variables and the default content of the webmail login.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit custom-webmail-login
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Login.	
content <string>	Enter the replacement message for the webmail login.	
format {html   multiline   text}	Select the format for the webmail login.	html

## disclaimer-insertion

Use this sub-command to configure the variables and the default content of the disclaimer insertion message.

## Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit disclaimer-insertion
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Login.	
content <string>	Enter the replacement message for the webmail login.	
format {html   multiline   text}	Select the format for the webmail login.	html

## email-template-av-repack

Use this sub-command to configure the variables and the default content of the email template for antivirus action.

## Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit email-template-av-repack
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	

Variable	Description	Default
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Template.	
from <string>	Enter the replacement message for the email From field.	
html-body <string>	Enter the replacement email body in HTML format.	
subject <string>	Enter the replacement message for the email Subject field.	
text-body <string>	Enter the replacement email body in text format.	

## email-template-notify-generic

Use this sub-command to configure the variables and the default content of the email template for generic notifications.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit email-template-notify-generic
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set env-from <string>
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
      set to <string>
  end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Template.	
env-from <string>	Enter the replacement message for the email Envelope From field.	

Variable	Description	Default
from <string>	Enter the replacement message for the email From field.	
html-body <string>	Enter the replacement email body in HTML format.	
subject <string>	Enter the replacement message for the email Subject header.	
text-body <string>	Enter the replacement email body in text format.	
to <string>	Enter the replacement message for the email To field.	

## ibe-login-page

Use this sub-command to configure the variables and the default replacement message for the custom IBE login page.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-login-page
  config variable
    edit <name>
      set content
      set display-name
    config message
      edit default
        set content <string>
        set format {html | multiline | text}
  end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for suspicious email attachments.	
format {html   multiline   text}	Select the format for the replacement message of suspicious email attachments.	text

## ibe-notify-account-delete

Use this sub-command to configure the variables and the default email template of the IBE account delete notification.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-notify-account-delete
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-account-expiry

Use this sub-command to configure the variables and the default email template of the IBE account expiry notification.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-notify-account-expiry
```

```

config variable
  edit <name>
    set content
    set display-name
config email-template
  edit default
    set from <string>
    set html-body <string>
    set subject <string>
    set text-body <string>
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-account-expiry-alert

Use this sub-command to configure the variables and the default email template of the IBE account expiry alert notification.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```

edit ibe-notify-account-expiry-alert
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-account-lock

Use this sub-command to configure the variables and the default email template of the IBE account lock notification.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-notify-account-lock
  config variable
    edit <name>
      set content
      set display-name
    config email-template
      edit default
        set from <string>
        set html-body <string>
        set subject <string>
        set text-body <string>
      end
    end
  end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	

Variable	Description	Default
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-account-reset

Use this sub-command to configure the variables and the default email template of the IBE account reset notification.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit ibe-notify-account-reset
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-account-reset-done

Use this sub-command to configure the variables and the default email template of the IBE account reset completion notification.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit ibe-notify-account-reset-done
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set global-bayesian {enable | disable}
      set subject <string>
      set text-body <string>
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-activation

Use this sub-command to configure the variables and the default email template for the account activation notification.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit ibe-notify-activation
```

```

config variable
  edit <name>
    set content
    set display-name
config email-template
  edit default
    set env-from <string>
    set from <string>
    set html-body <string>
    set subject <string>
    set text-body <string>
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
env-from <string>	Enter the replacement message for the Envelope From field of the notification.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>		
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-config-change

Use this sub-command to configure the variables and the default email template of the IBE account security settings changed notification.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```

edit ibe-notify-config-change
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>

```

```
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-password-reset

Use this sub-command to configure the variables and the default email template of the IBE password reset notification.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-notify-password-reset
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	

Variable	Description	Default
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-password-reset-done

Use this sub-command to configure the variables and the default email template of the IBE password reset completion notification.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit ibe-notify-password-reset-done
  config variable
    edit <name>
      set content
      set display-name
    config email-template
      edit default
        set from <string>
        set html-body <string>
        set subject <string>
        set text-body <string>
      end
    end
  end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-pull-message

Use this sub-command to configure the variables and the default email template of the secure message notification containing a link which the Webmail users can click to read the message.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit ibe-notify-pull-message
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-push-message

Use this sub-command to configure the variables and the default email template of the secure message notification with an attachment containing the secure message.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit ibe-notify-push-message
```

```

config variable
  edit <name>
    set content
    set display-name
config email-template
  edit default
    set from <string>
    set html-body <string>
    set subject <string>
    set text-body <string>
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-user-register-done

Use this sub-command to configure the variables and the default email template of the IBE user registration notification.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```

edit ibe-notify-user-register-done
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-wread-notif

Use this sub-command to configure the variables and the default email template of the IBE “read” notification which is the first time the message is read.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit ibe-notify-wread-notif
  config variable
    edit <name>
      set content
      set display-name
    config email-template
      edit default
        set from <string>
        set html-body <string>
        set subject <string>
        set text-body <string>
      end
    end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	

Variable	Description	Default
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-wunread-rcpt

Use this sub-command to configure the variables and the default email template of the IBE “unread” notification to the recipient when a mail remains unread for a period of time.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit ibe-notify-wunread-rcpt
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-notify-wunread-sender

Use this sub-command to configure the variables and the default email template of the IBE “unread” notification to the sender when a mail remains unread for a period of time.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-notify-wread-notif
  config variable
    edit <name>
      set content
      set display-name
    config email-template
      edit default
        set from <string>
        set html-body <string>
        set subject <string>
        set text-body <string>
      end
    end
  end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-password-reset-page

Use this sub-command to configure the variables and the default content of the custom IBE password reset page.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-password-reset-page
  config variable
```

```

    edit <name>
      set content
      set display-name
    config message
      edit default
        set content <string>
        set format {html | multiline | text}
    end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Login.	
content <string>	Enter the replacement message for the webmail login.	
format {html   multiline   text}	Select the format for the webmail login.	text

## ibe-register-page

Use this sub-command to configure the variables and the default content of the custom IBE user registration page.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```

edit ibe-register-page
  config variable
    edit <name>
      set content
      set display-name
    config message
      edit default
        set content <string>
        set format {html | multiline | text}
  end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Login.	
content <string>	Enter the replacement message for the webmail login.	
format {html   multiline   text}	Select the format for the webmail login.	text

## ibe-tfa-email-verify

Use this sub-command to configure the variables and the default email template for the secure token notification.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-tfa-email-verify
  config variable
    edit <name>
      set content
      set display-name
    config email-template
      edit default
        set from <string>
        set html-body <string>
        set subject <string>
        set text-body <string>
      end
    end
  end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## ibe-tfa-register-page

Use this sub-command to configure the variables and the default content of the custom IBE user two-factor authentication registration page.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit ibe-tfa-register-page
  config variable
```

```

    edit <name>
      set content
      set display-name
    config message
      edit default
        set content <string>
        set format {html | multiline | text}
    end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Login.	
content <string>	Enter the replacement message for the webmail login.	
format {html   multiline   text}	Select the format for the webmail login.	text

## ibe-tfa-sms-verify

Use this sub-command to configure the variables and the default content of the custom IBE user two-factor authentication SMS verification.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```

edit ibe-tfa-sms-verify
  config variable
    edit <name>
      set content
      set display-name
    config message
      edit default
        set content <string>
        set format {html | multiline | text}
  end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%FILE%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%FILE%% can be Login.	
content <string>	Enter the replacement message for the webmail login.	
format {html   multiline   text}	Select the format for the webmail login.	text

## log-report

Use this sub-command to configure the variables and the default content of the FortiMail log report.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit log-report
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set env-from <string>
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
  end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Disclaimer.	
env-from <string>	Enter the replacement message for the email Envelope From field.	
from <string>	Enter the replacement message for the email From field.	
html-body <string>	Enter the replacement email body in HTML format.	
subject <string>	Enter the replacement message for the email Subject header.	
text-body <string>	Enter the replacement email body in text format.	

## login-disclaimer

Use this sub-command to configure the variables and the default content of the FortiMail system login disclaimer.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```

edit login-disclaimer
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Disclaimer.	
content <string>	Enter the replacement message for the login disclaimer.	
format {html   multiline   text}	Select the format for the login disclaimer.	html

## reject-content-attachment

Use this sub-command to configure the variables and the default content of the attachment filtering message. This message is sent when an email is rejected for containing banned attachments.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```

edit reject-content-attachment
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECTION%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECTION%% can be Notice.	

Variable	Description	Default
content <string>	Enter the replacement message for the attachment filtering message.	
format {html   multiline   text}	Select the format for the attachment filtering message.	html

## reject-content-message

Use this sub-command to configure the variables and the default content of the content filtering message. This message is sent when an email is rejected for containing sensitive content.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit reject-content-message
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECTION%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECTION%% can be Notice.	
content <string>	Enter the replacement message for the content filtering message.	
format {html   multiline   text}	Select the format for the content filtering message.	html

## reject-delivery

Use this sub-command to configure the variables and the default content of the message delivery failure message.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit reject-delivery
  config variable
```

```

    edit <name>
      set content
      set display-name
    config message
      edit default
        set content <string>
        set format {html | multiline | text}
    end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECTION%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECTION%% can be Notice.	
content <string>	Enter the replacement message for the delivery failure message.	
format {html   multiline   text}	Select the format for the delivery failure message.	html

## reject-endpoint-reputation

Use this sub-command to configure the variables and the default content of the content filtering message. This message is sent when an email is rejected for carrier endpoint reputation check.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```

edit reject-endpoint-reputation
  config variable
    edit <name>
      set content
      set display-name
    config message
      edit default
        set content <string>
        set format {html | multiline | text}
  end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECTION%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECTION%% can be Endpoint.	
content <string>	Enter the replacement message for the content filtering message.	
format {html   multiline   text}	Select the format for the content filtering message.	html

## reject-spam

Use this sub-command to configure the variables and the default content of the spam message. This message is sent when an email is rejected for being detected as spam.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit reject-spam
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECTION%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECTION%% can be Notice.	
content <string>	Enter the replacement message for the spam message.	
format {html   multiline   text}	Select the format for the spam message.	html

## reject-virus-message

Use this sub-command to configure the variables and the default content of the virus message. This message is sent when an email is rejected for being infected with virus.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit reject-virus-message
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
```

```
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECTION%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECTION%% can be Notice.	
content <string>	Enter the replacement message for the virus message.	
format {html   multiline   text}	Select the format for the virus message.	html

## reject-virus-suspicious

Use this sub-command to configure the variables and the default content of the suspicious message. This message is sent when an email is rejected for containing suspicious components.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit reject-virus-suspicious
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECTION%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECTION%% can be Notice.	
content <string>	Enter the replacement message for the suspicious message.	
format {html   multiline   text}	Select the format for the suspicious message.	html

## replace-content-attachment

Use this sub-command to create the variables for and replace the default content of the attachment filtering message. This message is sent when the attachment of an email is blocked.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit replace-content-attachment
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%BLOCK%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%BLOCK%% can be Notice.	
content <string>	Enter the replacement message for the attachment filtering message.	
format {html   multiline   text}	Select the format for the attachment filtering message.	html

## replace-content-body

Use this sub-command to create the variables for and replace the default body of the content filtering message. This message is sent when an email is rejected for containing corporate sensitive data.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit replace-content-body
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
```

```
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECT%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECT%% can be Notice.	
content <string>	Enter the replacement message for the body of the content filtering message.	
format {html   multiline   text}	Select the format for the body of the content filtering message.	html

## replace-content-subject

Use this sub-command to create the variables for and replace the default subject of the content filtering message. This message is sent when an email is rejected for containing corporate sensitive data.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit replace-content-subject
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%REJECT%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%REJECT%% can be Notice.	
content <string>	Enter the replacement message for the subject of the content filtering message.	
format {html   multiline   text}	Select the format for the subject of content filtering message.	html

## replace-dlp-body

Use this sub-command to configure the variables and the default replacement message body for email data loss prevention.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit replace-dlp-body
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for infected email attachments.	
format {html   multiline   text}	Select the format for the replacement message of infected email attachments.	multiline

## replace-dlp-subject

Use this sub-command to configure the variables and the default replacement message subject for email data loss prevention.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit replace-dlp-subject
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
```

```
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for infected email attachments.	
format {html   multiline   text}	Select the format for the replacement message of infected email attachments.	multiline

## replace-virus-message

Use this sub-command to configure the variables and the default replacement message for infected email attachments. This message is sent when an email's attachment is removed for being infected with a virus.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit replace-virus-message
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for infected email attachments.	
format {html   multiline   text}	Select the format for the replacement message of infected email attachments.	html

## replace-virus-suspicious

Use this sub-command to configure the variables and the default replacement message for suspicious email attachments. This message is sent when an email's attachment is removed for containing suspicious components.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit replace-virus-suspicious
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for suspicious email attachments.	
format {html   multiline   text}	Select the format for the replacement message of suspicious email attachments.	html

## report-active-mailbox-summary

Use this sub-command to configure the variables and the default email template of the mailbox statistic report.

### Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit report-active-mailbox-summary
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set env-from <string>
      set from <string>
      set html-body <string>
```

```

        set subject <string>
        set text-body <string>
    end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the notification.	
html-body <string>	Enter the replacement message for the notification email body in HTML code.	
subject <string>	Enter the replacement message for the subject field of the notification.	
text-body <string>	Enter the replacement message for the notification email body in text format.	

## report-quarantine-summary

Use this sub-command to configure the variables and the default email template of quarantine summary.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```

edit report-quarantine-summary
  config variable
    edit <name>
      set content
      set display-name
  config email-template
    edit default
      set from <string>
      set html-body <string>
      set subject <string>
      set text-body <string>
  end
end

```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	

Variable	Description	Default
from <string>	Enter the replacement message for the From field of the quarantine summary.	
html-body <string>	Enter the replacement message for the email body of the quarantine summary in HTML code.	
subject <string>	Enter the replacement message for the subject field of the quarantine summary.	
text-body <string>	Enter the replacement message for the email body of the quarantine summary in text format.	

## url-protection-allow-with-confirmation

Use this sub-command to configure the variables and the default replacement message for allowing suspicious URLs with user confirmation.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit url-protection-allow-with-confirmation
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for suspicious email attachments.	
format {html   multiline   text}	Select the format for the replacement message of suspicious email attachments.	text

## url-protection-block

Use this sub-command to configure the variables and the default replacement message for blocking suspicious URLs.

## Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit url-protection-block
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for suspicious email attachments.	
format {html   multiline   text}	Select the format for the replacement message of suspicious email attachments.	text

## url-protection-remove

Use this sub-command to configure the variables and the default replacement message for removed URLs.

## Syntax

This sub-command is available from within the command [customized-message on page 64](#).

```
edit url-protection-remove
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	

Variable	Description	Default
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for suspicious email attachments.	
format {html   multiline   text}	Select the format for the replacement message of suspicious email attachments.	text

## url-protection-url-evaluation

Use this sub-command to configure the variables and the default replacement message for click protection URL evaluation.

### Syntax

This sub-command is available from within the command [customized-message](#) on page 64.

```
edit url-protection-url-evaluation
  config variable
    edit <name>
      set content
      set display-name
  config message
    edit default
      set content <string>
      set format {html | multiline | text}
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%WARNING%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%WARNING%% can be Notice.	
content <string>	Enter the replacement message for suspicious email attachments.	
format {html   multiline   text}	Select the format for the replacement message of suspicious email attachments.	text

## dlp scan-rules

Use these commands to prevent sensitive data from leaving your network.

## Syntax

```

config dlp scan-rules
  edit <rule_name>
    config conditions
      edit <condition_id>
        set attribute {attachment | attachment_metadata | body | body_and_attachment |
          header | recipient | sender | sender_or_recipient | subject}
        set file-pattern {archive | audio | encrypted | executable_windows | image |
          msoffice | openoffice | script | video}
        set group-type {local | ldap}
        set ldap-profile <profile_name>
        set operator {contain | contain_file_pattern | contain_sensitive_data | empty |
          equal | external | internal | match | not_contain | not_equal | not_present |
          password_protected | present}
        set sensitive-data {...}
        set value <string>
      config exceptions
        edit <exception_id>
          set attribute {attachment | attachment_metadata | body | body_and_attachment |
            header | recipient | sender | sender_or_recipient | subject}
          set file-pattern {archive | audio | encrypted | executable_windows | image |
            msoffice | openoffice | script | video}
          set group-type {local | ldap}
          set ldap-profile <profile_name>
          set operator {contain | contain_file_pattern | contain_sensitive_data | empty |
            equal | external | internal | match | not_contain | not_equal | not_present |
            password_protected | present}
          set sensitive-data {...}
          set value <string>
        set description <string>
        set condition-relation {and | or}
      end
    end
  end

```

Variable	Description	Default
<rule_name>	Enter a descriptive name for the rule.	
description <string>	Enter a description for the DLP scan rule.	
condition-relation {and   or}	Define the relationship among conditions.	and
conditions	Configure matching or non-matching conditions to be scanned.	
exceptions	Configure email matching exceptions that will not be scanned.	
attribute {attachment   attachment_metadata   body   body_and_attachment   header   recipient   sender   sender_or_recipient   subject}	Select the condition/exception criteria attribute to be matched.	subject

Variable	Description	Default
file-pattern {archive   audio   encrypted   executable_ windows   image   msoffice   openoffice   script   video}	Enter a filename pattern to restrict fingerprinting to only those files that match the pattern.	
group-type {local   ldap}	Set whether the group is local or LDAP.	local
ldap-profile <profile_name>	Select your LDAP profile.	
operator {contain   contain_file_pattern   contain_sensitive_data   empty   equal   external   internal   match   not_contain   not_equal   not_present   password_protected   present}	Enter the scan conditions (for example, contain or not_contain). Options available depend on what attribute is set to.	contain
sensitive-data {...}	Enter a predefined sensitive information term.	
value <string>	Enter the attribute value in string format.	

## domain

Use these commands to configure a protected domain.

For more information on protected domains and when they are required, see the [FortiMail Administration Guide](#).

## Syntax

This command contains many sub-commands. Each sub-command, linked below, is documented in subsequent sections.

```
config domain
  edit <domain_name>
    config config cal resource...
    config config customized-message...
    config config domain-info...
    config config domain-setting...
    config file filter...
    config config policy recipient...
    config config profile account-sync...
    config profile antispam...
    config profile antispam-action...
    config profile antivirus...
    config profile antivirus-action...
    config profile authentication...
    config profile content...
    config profile content-action...
    config profile cousin-domain...
    config profile email-address-group ...
    config profile impersonation...
    config profile notification...
    config profile resource...
```

```

    config config user mail...
  next
end

```

Variable	Description	Default
<domain_name>	Type the fully qualified domain name (FQDN) of the protected domain. For example, to protect email addresses ending in "@example.com", type example.com.	

## config cal resource

Use this sub-command to configure the calendar resource of a protected domain for calendar sharing.

### Syntax

This sub-command is available from within the command `domain`.

```

config cal resource
  edit <resource_name>
    set description <string>
    set display-name <string>
    set management-users <user_email>
    set type {room | equipment}
  end

```

Variable	Description	Default
<resource_name>	Enter a name for the calendar resource. This name forms the local name of the calendar resource for the current domain, for example <resource_name@<domain_name>.com.	
description <string>	Enter a description for the calendar resource entry.	
display-name <string>	Enter a display name.	
management-users <user_email>	Enter the management users for the calendar resource in the format <user_name>@<domain_name>.com.	
type {room   equipment}	Set the resource type to either room or equipment.	room

## config customized-message

Use this sub-command to configure the variables and the default email template of quarantine summary of a protected domain.

## Syntax

This sub-command is available from within the command `domain`.

```
config customized-message
  edit report-quarantine-summary
    config variable
      edit <name>
        set content
        set display-name
    config email-template
      edit default
        set from <string>
        set html-body <string>
        set subject <string>
        set text-body <string>
  end
end
```

Variable	Description	Default
<name>	Enter a variable name that you want to add or edit, such as %%SENDER%%.	
content	Enter the content for the variable.	
display-name	Enter the display name for the variable. For example, the display name for %%SENDER%% can be From.	
from <string>	Enter the replacement message for the From field of the quarantine summary.	
html-body <string>	Enter the replacement message for the email body of the quarantine summary in HTML code.	
subject <string>	Enter the replacement message for the subject field of the quarantine summary.	
text-body <string>	Enter the replacement message for the email body of the quarantine summary in text format.	

## config domain-info

Use this sub-command to configure customer account information.

### Syntax

This sub-command is available from within the command `domain`.

```
config domain-info
  set account-limit <integer>
  set comment <string>
  set customer-email <string>
  set customer-name <string>
end
```

Variable	Description	Default
account-limit <integer>	Enter the user account limit (0 means no limit).	0
comment <string>	Optionally, enter a description.	
customer-email <string>	Enter the customer email address.	
customer-name <string>	Enter the customer name.	

## config domain-setting

Use this sub-command to configure the basic settings of a protected domain.

### Syntax

This sub-command is available from within the command `domain`.

```

config domain-setting
  config sender-addr-rate-ctrl-exempt
    edit <id>
      set sender-pattern <string>
      set pattern-type {default | regexp}
    end
  set addressbook {domain | none | system}
  set bypass-bounce-verification {enable | disable}
  set disclaimer-incoming-body-content
  set disclaimer-incoming-body-content-html
  set disclaimer-incoming-body-location
  set disclaimer-incoming-body-status {enable | disable}
  set disclaimer-incoming-header-insertion-name
  set disclaimer-incoming-header-insertion-value
  set disclaimer-incoming-header-status {enable | disable}
  set disclaimer-outgoing-body-content
  set disclaimer-outgoing-body-content-html
  set disclaimer-outgoing-body-location
  set disclaimer-outgoing-body-status {enable | disable}
  set disclaimer-outgoing-header-insertion-name
  set disclaimer-outgoing-header-insertion-value
  set disclaimer-outgoing-header-status {enable | disable}
  set dmarc-report-status {disable | enable | monitor-only | use-system-setting}
  set email-continuity-status {enable | disable}
  set fallback-host {<smtp-server_fqdn> | <smtp-server_ipv4>}
  set fallback-port <port_int>
  set fallback-use-smtps {enable | disable}
  set global-bayesian {enable | disable}
  set greeting-with-host-name {domainname | hostname | othername}
  set host <host_name>
  set ip-pool <pool_name>
  set ip-pool-direction {outgoing | incoming | both}
  set is-service-domain {enable | disable}
  set is-sub-domain {enable | disable}
  set ldap-asav-profile <ldap-profile_name>
  set ldap-asav-status {enable | disable}

```

```

set ldap-domain-routing-port <port_int>
set ldap-domain-routing-profile <ldap-profile_name>
set ldap-domain-routing-smtps {enable | disable}
set ldap-groupowner-profile <ldap-profile_name>
set ldap-routing-profile <ldap-profile_name>
set ldap-routing-status {enable | disable}
set ldap-user-profile <profile_name>
set max-message-size <limit_int>
set other-helo-greeting <string>
set port <smtp-port_int>
set quarantine-report-schedule-status {enable | disable}
set quarantine-report-status {enable | disable}
set quarantine-report-to-alt {enable | disable}
set quarantine-report-to-alt-addr <recipient_email>
set quarantine-report-to-individual {enable | disable}
set quarantine-report-to-ldap-groupowner {enable | disable}
set recipient-verification {disable | ldap | smtp}
set recipient-verification-background {disable | ldap | smtp}
set recipient-verification-background-profile <ldap-profile_name>
set recipient-verification-invalid-user-action {reject | discard}
set relay-type {host | ip-pool | ldap-domain-routing | mx-lookup | mx-lookup-alt-domain}
set remove-outgoing-received-header {enable | disable}
set sender-addr-rate-ctrl-action
set sender-addr-rate-ctrl-max-msgs <integer>
set sender-addr-rate-ctrl-max-msgs-state {enable | disable}
set sender-addr-rate-ctrl-max-recipients
set sender-addr-rate-ctrl-max-recipients-state {enable | disable}
set sender-addr-rate-ctrl-max-size <integer>
set sender-addr-rate-ctrl-max-size-state {enable | disable}
set sender-addr-rate-ctrl-max-spam
set sender-addr-rate-ctrl-max-spam-state {enable | disable}
set sender-addr-rate-ctrl-state {enable | disable}
set sender-addr-rate-notification-state {enable | disable}
set smtp-recipient-verification-command {rcpt | vrfy}
set smtp-recipient-verification-accept-reply-string <accept_string>
set tp-hidden {no | yes}
set tp-server-on-port <port_int>
set tp-use-domain-mta {yes | no}
set use-smtps {enable | disable}
set webmail-language <language_name>
set webmail-theme {IndigoDarkBlue | RedGrey | Standard | Use-System-Settings}
end

```

Variable	Description	Default
addressbook {domain   none   system} (server mode only)	Add newly created mail user to system address book, domain address book or not.	domain
bypass-bounce-verification {enable   disable}	Enable to omit bounce address tag verification of email incoming to this protected domain.  This bypass does not omit bounce address tagging of outgoing email.	disable
fallback-host {<smtp-server_fqdn>   <smtp-server_ipv4>}	Enter the fully qualified domain name (FQDN) or IP address of the secondary SMTP server for this protected domain.	

Variable	Description	Default
(transparent mode and gateway mode only)	This SMTP server will be used if the primary SMTP server is unreachable.	
fallback-port <port_int> (transparent mode and gateway mode only)	Enter the port number on which the failover SMTP server listens. If you enable Use SMTPS, Port automatically changes to the default port number for SMTPS, but can still be customized. The default SMTP port number is 25; the default SMTPS port number is 465.	25
fallback-use-smtps {enable   disable} (transparent mode and gateway mode only)	Enable to use SMTPS for connections originating from or destined for this protected server.	disable
global-bayesian {enable   disable}	Enable to use the global Bayesian database instead of the Bayesian database for this protected domain. If you do not need the Bayesian database to be specific to the protected domain, you may want to use the global Bayesian database instead in order to simplify database maintenance and training. Disable to use the per-domain Bayesian database. This option does not apply if you have enabled use of personal Bayesian databases in an incoming antispam profile, and if the personal Bayesian database is mature. Instead, the FortiMail unit will use the personal Bayesian database.	disable
greeting-with-host-name {domainname   hostname   othername}	Specify how the FortiMail unit will identify itself during the HELO or EHL0 greeting of outgoing SMTP connections that it initiates. <i>domainname</i> : The FortiMail unit will identify itself using the domain name for this protected domain. If the FortiMail unit will handle internal email messages (those for which both the sender and recipient addresses in the envelope contain the domain name of the protected domain), to use this option, you must also configure your protected SMTP server to use its host name for SMTP greetings. Failure to do this will result in dropped SMTP sessions, as both the FortiMail unit and the protected SMTP server will be using the same domain name when greeting each other. <i>hostname</i> : The FortiMail unit will identify itself using its own host name. By default, the FortiMail unit uses the domain name of the protected domain. If your FortiMail unit is protecting multiple domains and using IP pool addresses, select to use the system host name instead. This setting does not apply if email is incoming, according to the sender address in the envelope, from an unprotected domain.	hostname

Variable	Description	Default
	<p><i>othername</i>: If you select this option, another command set <code>other-helo-greeting &lt;string&gt;</code> will appear, allowing you enter a name other than the domain name or host name, for the HELO/EHELO greating.</p>	
<p>host &lt;host_name&gt; (transparent mode and gateway mode only)</p>	<p>The host name or IP address and port number of the mail exchanger (MX) for this protected domain.</p> <p>If Relay Type is MX Record (this domain) or MX Record (alternative domain), this information is determined dynamically by querying the MX record of the DNS server, and this field will be empty.</p>	
ip-pool <pool_name>	<p>You can use a pool of IP addresses as the source IP address when sending email from this domain, or as the destination IP address when receiving email destined to this domain, or as both the source and destination IP addresses.</p> <p>If you want to use the IP pool as the source IP address for this protected domain, according to the sender's email address in the envelope (MAIL FROM:), select the IP pool to use and select <b>outgoing</b> as the <code>ip-pool-direction</code>.</p> <p>If you want to use the IP pool as the destination IP address (virtual host) for this protected domain, according to the recipient's email address in the envelope (RCPT TO:), select the IP pool to use and select <i>incoming</i> as the <code>ip-pool-direction</code>. You must also configure the MX record to direct email to the IP pool addresses as well.</p> <p>This feature can be used to support multiple virtual hosts on a single physical interface, so that different profiles can be applied to different host and logging for each host can be separated as well.</p> <p>If you want to use the IP pool as both the destination and source IP address, select the IP pool to use and select <i>Both</i> as the <code>ip-pool-direction</code>.</p> <p>Each email that the FortiMail unit sends will use the next IP address in the range. When the last IP address in the range is used, the next email will use the first IP address.</p>	
<p>ip-pool-direction {outgoing   incoming   both}</p>	<p>Sets the direction for the <code>ip-pool</code> option. See description above.</p> <p>This option is only available after you configure the <code>ip-pool</code> option.</p>	
<p>is-sub-domain {enable   disable}</p>	<p>Enable to indicate the protected domain you are creating is a subdomain of an existing protected domain, then also configure Main domain.</p> <p>Subdomains, like their parent protected domains, can be selected when configuring policies specific to that subdomain. Unlike top-level protected domains, however, subdomains will be displayed as grouped under the parent protected domain when viewing the list of protected domains.</p> <p>This option is available only when another protected domain exists to select as the parent domain.</p>	disable

Variable	Description	Default
ldap-asav-profile <ldap-profile_name>	Specify the name of an LDAP profile which you have enabled and configured.	
ldap-asav-status {enable   disable}	Enable to query an LDAP server for an email user's preferences to enable or disable antispam and/or antivirus processing for email messages destined for them.	disable
ldap-domain-routing-port <port_int>	Enter the port number on which the SMTP servers in the LDAP profile listen. If you enable <code>ldap-domain-routing-smtps</code> , this setting automatically changes to the default port number for SMTPS, but can still be customized. The default SMTP port number is 25; the default SMTPS port number is 465. This option is valid when <code>relay-type</code> is <code>ldap-domain-routing</code> .	25
ldap-domain-routing-profile <ldap-profile_name>	Select the name of the LDAP profile that has the FQDN or IP address of the SMTP server you want to query. Also configure <a href="#">ldap-domain-routing-port &lt;port_int&gt; on page 112</a> and <a href="#">ldap-domain-routing-smtps {enable   disable} on page 112</a> . This option is valid when <code>relay-type</code> is set to <code>ldap-domain-routing</code> .	
ldap-domain-routing-smtps {enable   disable}	Enable to use SMTPS for connections originating from or destined for this protected server. This option is valid when <code>relay-type</code> is <code>ldap-domain-routing</code> .	disable
ldap-groupowner-profile <ldap-profile_name>	Select an LDAP profile to send the quarantine report to a group owner, rather than individual recipients.	
ldap-routing-profile <ldap-profile_name>	Select an LDAP profile for mail routing.	
ldap-routing-status {enable   disable}	Enable/disable LDAP mail routing.	disable
ldap-user-profile <profile_name>	Select the name of an LDAP profile in which you have configured, enabling you to authenticate email users and expand alias email addresses or replace one email address with another by using an LDAP query to retrieve alias members.	
max-message-size <limit_int>	Enable then type the limit in kilobytes (KB) of the message size. Email messages over the threshold size are rejected. Note: If both this option and <a href="#">expire-inactivity &lt;days_int&gt;</a> in the session profile are enabled, email size will be limited to whichever size is smaller.	204800KB
other-helo-greeting <string>	After you set the <code>greeting-with-hostname</code> to <code>othername</code> , use this command to specify the name to use for HELO/EHELO greeting.	
port <smtp-port_int>	Set the SMTP port number of the mail server.	25

Variable	Description	Default
(transparent mode and gateway mode only)		
quarantine-report-schedule-status {enable   disable}	Enable or disable domain-level quarantine report schedule setting. The quarantine report settings for a protected domain are a subset of the system-wide quarantine report settings. For example, if the system settings for schedule include only Monday and Thursday, when you are setting the schedule for the quarantine reports of the protected domain, you will only be able to select either Monday or Thursday.	disable
quarantine-report-status {enable   disable}	Enable or disable domain-level quarantine report.	disable
quarantine-report-to-alt {enable   disable}	Enable or disable sending domain-level quarantine report to a recipient other than the individual recipients or group owner. For example, you might delegate quarantine reports by sending them to an administrator whose email address is not locally deliverable to the protected domain, such as admin@lab.example.com.	disable
quarantine-report-to-alt-addr <recipient_email>	Enter the recipient's email address.	
quarantine-report-to-individual {enable   disable}	Enable to send quarantine reports to all recipients.	enable
quarantine-report-to-ldap-groupowner {enable   disable}	Enable to send quarantine reports to the LDAP group owner of the specified LDAP profile.	disable
recipient-verification {disable   ldap   smtp}	Select a method of confirming that the recipient email address in the message envelope (RCPT TO:) corresponds to an email user account that actually exists on the protected email server. If the recipient address is invalid, the FortiMail unit will reject the email. This prevents quarantine email messages for non-existent accounts, thereby conserving quarantine hard disk space. <b>disable:</b> Do not verify that the recipient address is an email user account that actually exists. <b>smtp:</b> Query the SMTP server using the SMTP RCPT command to verify that the recipient address is an email user account that actually exists. You can also choose to use the SMTP VRFY command to do the verification. This feature is available on the GUI when you create a domain. If you want to query an SMTP server other than the one you have defined as the protected SMTP server, also enable Use alternative server, then enter the IP address or FQDN of the server in the field next to it. Also configure Port with the TCP port number on which the SMTP server listens, and enable Use SMTPS if you want to use SMTPS for recipient address verification connections with the server.	disable

Variable	Description	Default
	<p><code>ldap</code>: Query an LDAP server to verify that the recipient address is an email user account that actually exists. Also select the LDAP profile that will be used to query the LDAP server.</p> <p><b>Note:</b> This option can cause a performance impact that may be noticeable during peak traffic times. For a lesser performance impact, you can alternatively periodically automatically remove quarantined email messages for invalid email user accounts, rather than actively preventing them during each email message.</p> <p><b>Note:</b> Spam often contains invalid recipient addresses. If you have enabled spam quarantining, but have not prevented or scheduled the periodic removal of quarantined email messages for invalid email accounts, the FortiMail hard disk may be rapidly consumed during peak traffic times, resulting in refused SMTP connections when the hard disk becomes full. To prevent this, enable either this option or the periodic removal of invalid quarantine accounts.</p>	
<code>recipient-verification-background {disable   ldap   smtp}</code>	<p>Select a method by which to periodically remove quarantined spam for which an email user account does not actually exist on the protected email server.</p> <p><code>disable</code>: Do not verify that the recipient address is an email user account that actually exists.</p> <p><code>smtp</code>: Query the SMTP server to verify that the recipient address is an email user account that actually exists.</p> <p><code>ldap</code>: Query an LDAP server to verify that the recipient address is an email user account that actually exists. Also select the LDAP profile that will be used to query the LDAP server.</p> <p>If you select either Use SMTP server or Use LDAP server, at 4:00 AM daily (unless configured for another time, using the CLI), the FortiMail unit queries the server to verify the existence of email user accounts. If an email user account does not currently exist, the FortiMail unit removes all spam quarantined for that email user account.</p> <p><b>Note:</b> If you have also enabled <code>recipient-verification</code>, the FortiMail unit is prevented from forming quarantine accounts for email user accounts that do not really exist on the protected email server. In that case, invalid quarantine accounts are never formed, and this option may not be necessary, except when you delete email user accounts on the protected email server. If this is the case, you can improve the performance of the FortiMail unit by disabling this option.</p>	

Variable	Description	Default
	<p><b>Note:</b> Spam often contains invalid recipient addresses. If you have enabled spam quarantining, but have not prevented or scheduled the periodic removal of quarantined email messages for invalid email accounts, the FortiMail hard disk may be rapidly consumed during peak traffic times, resulting in refused SMTP connections when the hard disk becomes full. To prevent this, enable either this option or verification of recipient addresses.</p>	
recipient-verification-invalid-user-action {reject   discard}	Action to take on invalid recipients.	reject
relay-type {host   ip-pool   ldap-domain-routing   mx-lookup   mx-lookup-alt-domain} (transparent mode and gateway mode only)	<p>Select from one of the following methods of defining which SMTP server will receive email from the FortiMail unit that is destined for the protected domain:</p> <p>host: Configure the connection to one protected SMTP server or, if any, one fallback.</p> <p>ldap-domain-routing: Query the LDAP server for the FQDN or IP address of the SMTP server. For more information about domain lookup, see <a href="#">domain-query &lt;query_str&gt; on page 234</a>.</p> <p>mx-lookup: Query the DNS server's MX record of the protected domain name for the FQDN or IP address of the SMTP server. If there are multiple MX records, the FortiMail unit will load balance between them.</p> <p>mx-lookup-alt-domain: Query the DNS server's MX record of a domain name you specify for the FQDN or IP address of the SMTP server. If there are multiple MX records, the FortiMail unit will load balance between them.</p> <p>ip-pool: Configure the connection to rotate among one or many protected SMTP servers.</p> <p><b>Note:</b> If an MX option is used, you may also be required to configure the FortiMail unit to use a private DNS server whose MX and/or A records differ from that of a public DNS server. Requirements vary by the topology of your network and by the operating mode of the FortiMail unit.</p> <p>Gateway mode: A private DNS server is required. On the private DNS server, configure the MX record with the FQDN of the SMTP server that you are protecting for this domain, causing the FortiMail unit to route email to the protected SMTP server. This is different from how a public DNS server should be configured for that domain name, where the MX record usually should contain the FQDN of the FortiMail unit itself, causing external SMTP servers to route email through the FortiMail unit. Additionally, if both the FortiMail unit and the SMTP server are behind a NAT device such as a router or firewall, on the private DNS server, configure the protected SMTP server's A record with its private IP address, while on the public DNS server, configure the FortiMail unit's A record with its public IP address.</p>	host

Variable	Description	Default
	Transparent mode: A private DNS server is required if both the FortiMail unit and the SMTP server are behind a NAT device such as a router or firewall. On the private DNS server, configure the protected SMTP server's A record with its private IP address. On the public DNS server, configure the protected SMTP server's A record with its public IP address. Do not modify the MX record.	
remove-outgoing-received-header {enable   disable}	<p>Enable to remove the <code>Received:</code> message headers from email whose:</p> <ul style="list-style-type: none"> <li>• sender email address belongs to this protected domain, and</li> <li>• recipient email address is outgoing (that is, does not belong to this protected domain); if there are multiple recipients, only the first recipient's email address is used to determine whether an email is outgoing.</li> </ul> <p>You can alternatively remove this header from any matching email using session profiles.</p>	disable
sender-addr-rate-ctrl-max-msgs <integer>	Enter the maximum number of messages per sender address per half an hour.	30
sender-addr-rate-ctrl-max-msgs-state {enable   disable}	Enable the option of maximum number of messages per sender address per half an hour.	disable
sender-addr-rate-ctrl-max-size <integer>	Enter the maximum number of megabytes per sender per half an hour.	100
sender-addr-rate-ctrl-max-size-state {enable   disable}	Enable the option of maximum number of megabytes per sender per half an hour.	disable
sender-addr-rate-ctrl-state {enable   disable}	Enable sender address rate control per sender email address.	disable
smtp-recipient-verification-command {rcpt   vrfy} (transparent mode and gateway mode only)	<p>Specify the command that the FortiMail unit uses to query the SMTP server to verify that the recipient address is an email user account that actually exists. The default command that the FortiMail unit uses is <code>rcpt</code>.</p> <p>For information about recipient verification, see <a href="#">recipient-verification {disable   ldap   smtp}</a></p> <p>This option is only available after you select <code>smtp</code> in <code>recipient-verification</code>.</p>	rcpt
smtp-recipient-verification-accept-reply-string <accept_string> (transparent mode and gateway mode only)	<p>When FortiMail queries the SMTP server for recipient verification:</p> <p>If the reply code of the VRFY command is 2xx, the recipient exists. If the reply code is non-2xx, FortiMail will try to match the accept string you specified with the reply string. If the strings match, the recipient exists.</p> <p>Otherwise, the recipient is unknown.</p> <p>For example, if the recipient is a group or mailing list, FortiMail will receive a 550 error code and a reply string. Depending on what reply string you get, you can specify a string to match the reply string.</p>	

Variable	Description	Default
	<p>For example, if the recipient is marketing@example.com, the reply string might say something like "marketing@example.com is a group". In this case, if you specify "is a group" as the accept string and thus this string matches the string or part of the string in the reply string, FortiMail will deem the query successful and pass the email.</p> <p>This command is available only when you set SMTP-recipient-verification-command to <code>vrfy</code>.</p>	
tp-hidden {no   yes} (transparent mode only)	<p>Enable to preserve the IP address or domain name of the SMTP client for incoming email messages in:</p> <ul style="list-style-type: none"> <li>the SMTP greeting (HELO/EHLO) in the envelope and in the Received: message headers of email messages</li> <li>the IP addresses in the IP header</li> </ul> <p>This masks the existence of the FortiMail unit to the protected SMTP server.</p> <p>Disable to replace the SMTP client's IP address or domain name with that of the FortiMail unit.</p> <p>For example, an external SMTP client might have the IP address 172.168.1.1, and the FortiMail unit might have the domain name fortimail.example.com. If the option is enabled, the message header would contain (difference highlighted in bold):</p> <p>Received: from 192.168.1.1 (EHLO <b>172.16.1.1</b>) (192.168.1.1) by smtp.external.example.com with SMTP; Fri, 24 Jul 2008 07:12:40 -0800</p> <p>Received: from smtpa ([172.16.1.2]) by [<b>172.16.1.1</b>] with SMTP id kAOFESEN001901 for &lt;user1@external.example.com&gt;; Fri, 24 Jul 2008 15:14:28 GMT</p> <p>But if the option is disabled, the message headers would contain:</p> <p>Received: from 192.168.1.1 (EHLO <b>fortimail.example.com</b>) (192.168.1.1) by smtp.external.example.com with SMTP; Fri, 24 Jul 2008 07:17:45 -0800</p> <p>Received: from smtpa ([172.16.1.2]) by <b>fortimail.example.com</b> with SMTP id kAOFJI4j002011 for &lt;user1@external.example.com&gt;; Fri, 24 Jul 2008 15:19:47 GMT</p> <p><b>Note:</b> This option does not apply to email messages sent from protected domains to protected domains, meaning that the FortiMail unit will not be hidden even if this option is enabled.</p>	no
tp-server-on-port <port_int> (transparent mode only)	<p>Select the network interface (physical port) to which the protected SMTP server is connected.</p> <p>Note: Selecting the wrong network interface will result in the FortiMail sending email traffic to the wrong network interface.</p>	0
tp-use-domain-mta {yes   no} (transparent mode only)	<p>Enable to proxy SMTP clients' incoming connections when sending outgoing email messages via the protected SMTP server.</p>	no

Variable	Description	Default
	<p>For example, if the protected domain example.com has the SMTP server 192.168.1.1, and an SMTP client for user1@example.com connects to it to send email to user2@external.example.net, enabling this option would cause the FortiMail unit to proxy the connection through to the protected SMTP server.</p> <p>Disable to relay email using the built-in MTA to either the defined SMTP relay, if any, or directly to the MTA that is the mail exchanger (MX) for the recipient email address's (RCPT TO:) domain. The email may not actually travel through the protected SMTP server, even though it was the relay originally specified by the SMTP client.</p> <p>This option does not affect incoming connections containing incoming email messages, which will always be handled by the built-in MTA.</p> <p>Note: This option will be ignored for email that matches an antispam or content profile where you have enabled <code>alternate-host {&lt;relay_fqdn&gt;   &lt;relay_ipv4&gt;}</code>.</p>	
use-stmps {enable   disable}	Enable to use SMTPS to relay email to the mail server.	disable
webmail-language <language_name>	Select either <b>Use system settings</b> , other language that the FortiMail unit will to display webmail and quarantine folder pages. By default, the FortiMail unit uses the same language as the web-based manager.	
webmail-theme {IndigoDarkBlue   RedGrey   Standard   Use-System-Settings}	Select the display theme that the FortiMail unit will to display webmail and quarantine folder pages. By default, the FortiMail unit uses the same display theme as the web-based manager.	Use-System-Settings

## config policy recipient

Use this sub-command to configure a recipient-based policy for a protected domain. To configure system-wide policies, use the config [policy recipient](#) command.

### Syntax

This sub-command is available from within the command [domain](#).

```
config policy recipient
  edit <policy_index>
    set auth-access-options {pop3 smtp-auth smtp-diff-identity web}
    set certificate-required {yes | no}
    set comment
    set direction
    set pkiauth {enable | disable}
    set pkiuser <user_name>
    set profile-antispam <antispam_name>
    set profile-antivirus <antivirus_name>
    set profile-auth-type {imap | local | ldap | pop3 | smtp | radius}
```

```

set profile-content <profile_name>
set profile-dlp
set profile-resource <profile_name>
set profile-ldap <profile_name>
set recipient-domain <domain>
set recipient-name <name_str>
set recipient-type {ldap-group | local-group | user}
set sender-domain <domain_name>
set sender-name <local-part_str>
set sender-type {ldap-group | local-group | user}
set smtp-diff-identity
set smtp-diff-identity
set smtp-diff-identity-ldap-profile
set status {enable | disable}
next
end

```

Variable	Description	Default
<policy_index>	Type the index number of the policy. To view a list of existing entries, enter a question mark ( ? ).	
auth-access- options {pop3 smtp-auth smtp-diff-identity web}	Type one or more of the following:  smtp-diff-identity: Allow email when the SMTP client authenticates with a different user name than the one that appears in the envelope's sender email address. You must also enter smtpauth for this option to have any effect.  web: Allow the email user to use FortiMail webmail (HTTP or HTTPS) to retrieve the contents of their per-recipient spam quarantine.  pop3: Allow the email user to use POP3 to retrieve the contents of their per-recipient spam quarantine.  smtp-auth: Use the authentication server selected in the authentication profile when performing SMTP authentication for connecting SMTP clients. Note: Entering this option allows, but does not require, SMTP authentication. To enforce SMTP authentication for connecting SMTP clients, ensure that all access control rules require authentication.	
certificate-required {yes   no} (transparent and gateway mode only)	If the email user's web browser does not provide a valid personal certificate, the FortiMail unit will fall back to standard user name and password-style authentication. To require valid certificates only and disallow password-style fallback, enable this option.	no
comment	Enter a comment for the recipient policy	
direction	Enter whether the direction of mail traffic is incoming or outgoing.	
pkiauth {enable   disable} (transparent and gateway mode only)	Enable if you want to allow email users to log in to their per-recipient spam quarantine by presenting a certificate rather than a user name and password.	disable
pkuser <user_ name> (transparent and gateway mode only)	Enter the name of the PKI user entry, or select a user you defined before.  This is not required to be the same as the administrator or email user's account name, although you may find it helpful to do so.	

Variable	Description	Default
	For example, you might have an administrator account named admin1. You might therefore find it most straightforward to <b>also</b> name the PKI user admin1, making it easy to remember which account you intended to use these PKI settings.	
profile-antispam <antispam_name>	Select a antispam profile that you want to apply to the policy.	
profile-antivirus <antivirus_name>	Select an antivirus profile that you want to apply to the policy.	
profile-auth-type {imap   local   ldap   pop3   smtp   radius}	If you want email users to be able to authenticate using an external authentication server, first specify the profile type (SMTP, POP3, IMAP, RADIUS, or LDAP), then specify which profile to use.  For example: set profile-auth-type ldap set profile-auth-ldap ldap_profile1	
profile-auth-imap <imap_name>	Type the name of an IMAP authentication profile.  This command is applicable only if you have enabled use of an IMAP authentication profile using <code>profile-auth-type {imap   local   ldap   pop3   smtp   radius}</code>	
profile-auth-ldap <ldap_name>	Type the name of an LDAP authentication profile.  This command is applicable only if you have enabled use of an LDAP authentication profile using <code>profile-auth-type {imap   local   ldap   pop3   smtp   radius}</code>	
profile-auth-pop3 <pop3_name>	Type the name of a POP3 authentication profile.  This command is applicable only if you have enabled use of a POP3 authentication profile using <code>profile-auth-type {imap   local   ldap   pop3   smtp   radius}</code>	
profile-auth-smtp <smtp_name>	Type the name of an SMTP authentication profile.  This command is applicable only if you have enabled use of an SMTP authentication profile using <code>profile-auth-type {imap   local   ldap   pop3   smtp   radius}</code> .	
profile-auth-radius <radius_name>	Type the name of a RADIUS authentication profile.  This command is applicable only if you have enabled use of a RADIUS authentication profile using <code>profile-auth-type {imap   local   ldap   pop3   smtp   radius}</code> .	
profile-content <profile_name>	Select which content profile you want to apply to the policy.	
profile-dlp	Enter the DLP profile for the policy.	
profile-resource <profile_name>	Select which resource profile you want to apply to the policy.  This option is only available in server mode.	
profile-ldap <profile_name>	If you set the recipient type as "ldap-group", you can select an LDAP profile.	

Variable	Description	Default
recipient-domain <domain>	Enter the domain part of the recipient email address.	
recipient-name <name_str>	Enter the local part of the recipient email address or a pattern with wild cards.	
recipient-type {ldap-group   local-group   user}	Select one of the following ways to define recipient (RCPT TO:) email addresses that match this policy. This setting applies to the incoming policies only.  user: Select this option and then use the above command to enter the local part of the recipient email address.  local-group: Select this option and then specify the local group under this domain.  ldap-group: Select this option and then select an LDAP profile.	user
sender-domain <domain_name>	Enter the domain part of the sender email address. For example, example.com.	
sender-name <local-part_str>	Enter the local part of the sender email address. For example, user1.	
sender-type {ldap-group   local-group   user}	Select one of the following ways to define which sender (MAIL FROM:) email addresses match this policy.  user: Select this option and then use the above command to enter the local part of the sender email address.  local-group: Select this option and then specify the local group under this domain.  ldap-group: Select this option and then select an LDAP profile.  Note: This setting applies to the outgoing policies only.	user
smtp-diff-identity	Rejects different smtp sender identity.	
smtp-diff-identity-ldap	Verify smtp sender identity with LDAP for authenticated email.	
smtp-diff-identity-ldap-profile	Ldap profile for smtp sender identity verification.	
status {enable   disable}	Enable or disable the policy.	enable

## config profile account-sync

Use this command to configure account synchronization settings for remote users from LDAP and Microsoft 365 servers.

### Syntax

This sub-command is available from within the command `domain`.

```
config profile account-sync
  edit <profile_name>
```

```

set base-dn <string>
set bind-dn <string>
set bind-password <password>
set description <string>
set group-display-name <string>
set group-primary-address <string>
set group-query <string>
set group-secondary-address <string>
set ldap-port <integer>
set ldap-secure {enable | disable}
set ldap-server <string>
set ldap-version {ver2 | ver3}
set ms365-application-id <string>
set ms365-application-secret <password>
set ms365-tenant-id <password>
set recurrence {daily | monthly | none | weekly}
set referrals-chase {enable | disable}
set schedule-hour <integer>
set scope {base | one | sub}
set timeout <integer>
set type {ldap | ms365}
set user-display-name <string>
set user-primary-address <string>
set user-query <string>
set user-secondary-address <string>
next
end

```

Variable	Description	Default
base-dn <string>	Enter the distinguished name (DN) of the part of the LDAP directory tree within which the FortiMail unit will search for user objects, such as <code>ou=People,dc=example,dc=com</code> . User objects should be child nodes of this location.	
bind-dn <string>	Enter the bind DN, such as <code>cn=FortiMailA,dc=example,dc=com</code> , of an LDAP user account with permissions to query the basedn.	
bind-password <password>	Enter the password of <code>bind-dn &lt;string&gt;</code> .	
description <string>	Enter a description.	
group-display-name <string>	Enter the LDAP group/mailling list display name attribute.	
group-primary-address <string>	Enter the LDAP group/mailling list primary email address attribute.	
group-query <string>	Enter the LDAP group/maillinglistquery string.	
group-secondary-address <string>	Enter the LDAP group/mailling list secondary email address attribute.	
ldap-port <integer>	Enter the TCP port number of the LDAP server.	389

Variable	Description	Default
	The standard port number for LDAP is 389. The standard port number for SSL-secured LDAP is 636.	
ldap-secure {enable   disable}	Enable or disable (by default) a secure encrypted connection to the LDAP server.	disable
ldap-server <string>	Enter the fully qualified domain name (FQDN) or IP address of the LDAP server.	
ldap-version {ver2   ver3}	Enter the LDAP server protocol version.	ver3
ms365-application-id <string>	Enter the Microsoft 365 application ID.	
ms365-application-secret <password>	Enter the Microsoft 365 application secret.	
ms365-tenant-id <password>	Enter the Microsoft 365 tenant ID.	
recurrence {daily   monthly   none   weekly}	Define the recurrence/schedule of the remote server synchronization.	none
referrals-chase {enable   disable}	Enable or disable (by default) chasing of referrals.	disable
schedule-hour <integer>	Enter the hour of the day at which synchronization will occur. Set the value between 0-23.	1
scope {base   one   sub}	Define the search scope of the LDAP server; either base, one level, or subtree (by default).	sub
timeout <integer>	Enter the query timeout limit in seconds. Set the value between 60-600.	60
type {ldap   ms365}	Enter the remote server profile type.	ldap
user-display-name <string>	Enter the LDAP user's display name attribute.	
user-primary-address <string>	Enter the LDAP user's primary email address attribute.	
user-query <string>	Enter the LDAP query string to get all users.	
user-secondary-address <string>	Enter the LDAP user's secondary email address attribute.	

## config user mail

Use this sub-command to configure email user accounts.

## Syntax

This sub-command is available from within the command `domain`.

```
config user mail
  rename <old_username> to <new_username> (see the note below)
  edit <user_name>
    set type {local | ldap}
    set type local
    set displayname <name_str>
    set password <pwd_str>
    set type ldap
    set displayname <name_str>
    set ldap-profile <ldap_name>
  next
end
```

Variable	Description	Default
<old_username>	The user account name you want to rename.	
<new_username>	The new user account name you want to change to.	
<user_name>	Enter the user name of an email user, such as user1. This is also the local-part portion of the email user's primary email address.	
type {local   ldap}	Enter the type of email user account you want to add. See <a href="#">set type local</a> and <a href="#">set type ldap</a> .	ldap
displayname <name_str>	Enter the display name of the local email user, such as 'User One'.	
password <pwd_str>	Enter the password of the local email user.	
displayname <name_str>	Enter the display name of the LDAP email user, such as 'User One'.	
ldap-profile <ldap_name>	Enter the name of an LDAP profile in which authentication queries are enabled.	



If you rename an existing user account to a new user account name, all the user's preferences and mail data will be ported to the new user. However, due to the account name change, the new user will not be able to decrypt and read the encrypted email that is sent to the old user name before.

## domain-association



This command applies only if the FortiMail unit is operating in gateway mode or transparent mode.

Use this command to configure domain associations. Associated domains use the settings of the protected domains or subdomains with which they are associated.

Domain associations can be useful for saving time when you have multiple domains for which you would otherwise need to configure protected domains with identical settings.

For example, if you have one SMTP server handling email for ten domains, you could create ten separate protected domains, and configure each with identical settings. Alternatively, you could create one protected domain, listing the nine remaining domains as domain associations. The advantage of using the second method is that you do not have to repeatedly configure the same things when creating or modifying the protected domains, saving time and reducing chances for error. Changes to one protected domain automatically apply to all of its associated domains.

Exceptions to settings that associated domains will re-use include DKIM keys and signing settings. Domain keys are by nature tied to the exact protected domain only, and cannot be used for any other protected domain, including associated domains.

Alternatively, you can configure LDAP queries to automatically add domain associations. For details, see [system link-monitor on page 321](#).

## Syntax

```
config domain-association
  edit <domain-association-fqdn>
    set main-domain <protected-domain-name>
  next
end
```

Variable	Description	Default
<domain-association-fqdn>	Enter the fully qualified domain name (FQDN) of a mail domain that you want to use the same settings as the same protected domain.	
<protected-domain-name>	Enter the name of the protected domain. The associated domain will use the settings of this domain.	

## Related topics

[system link-monitor on page 321](#)

## file content-disarm-reconstruct

Attachments may contain potentially hazardous tags and attributes, such as hyperlinks and scripts. FortiMail provides the ability to remove or neutralize these hazardous contents and reconstruct the attachment files.

## Syntax

```
config file content-disarm-reconstruct
  set component-type-options {...}
  set continue-sandbox-on-cdr {enable | disable}
  set deferred-scan-notification-option {disarm | remove}
  set deferred-scan-notification-status {enable | disable}
  set deferred-scan-verdict-option {clean | high | low | malicious | medium}
  set deferred-scan-verdict-status {enable | disable}
  set modification-notice-option {enable | disable}
end
```

Variable	Description	Default
component-type-options {...}	Enter the potentially hazardous content you wish to remove or neutralize from attachment files: <ul style="list-style-type: none"> <li>• office-action</li> <li>• office-dde</li> <li>• office-embedded-object</li> <li>• office-hyperlink</li> <li>• office-linked-object</li> <li>• office-macro</li> <li>• pdf-action-form</li> <li>• pdf-action-gotor</li> <li>• pdf-action-javascript</li> <li>• pdf-action-launch</li> <li>• pdf-action-movie</li> <li>• pdf-action-sound</li> <li>• pdf-action-url</li> <li>• pdf-embedded-file</li> <li>• pdf-hyperlink</li> <li>• pdf-javascript</li> </ul>	
continue-sandbox-on-cdr {enable   disable}	Enable or disable continuing the FortiSandbox scan on successful content disarm and reconstruct (CDR). Note that when FortiMail is running firmware 6.4, even on successful CDR, FortiSandbox scanning for this attachment will <b>not</b> be bypassed. When FortiMail is running firmware 7.0, the FortiSandbox scan on successful content disarm is bypassed by default. Enable <code>continue-sandbox-on-cdr</code> if you want to allow FortiSandbox to scan the attachment upon successful CDR.	disable
deferred-scan-notification-option {disarm   remove}	Either send notification email with disarmed attachment or with the attachment removed.	disarm
deferred-scan-notification-status {enable   disable}	Enable or disable sending the notification email on deferred scan.	disable

Variable	Description	Default
deferred-scan-verdict-option {clean   high   low   malicious   medium}	Determine the verdict threshold option to disarm on delivery.	clean
deferred-scan-verdict-status {enable   disable}	Enable or disable disarming the attachment of deferred email by verdict threshold.	enable
modification-notice-option {enable   disable}	Enable or disable appending the CDR disclaimer "Attachment has been reconstructed" for cleaned attachments.	disable

## file decryption password

For password-protected PDF and archive attachments, if you want to decrypt and scan them, you can specify what kind of passwords you want to use to decrypt the files.

### Syntax

```
config file decryption password
  edit <table_value>
    set password <string>
  end
```

Variable	Description	Default
<table_value>	Enter the table value you want to add or edit.	
password <string>	Enter the password you want to use to decrypt the file.	

## file filter

Use this sub-command to configure file filter options, including filtering by file extension type and Multipurpose Internet Mail Extension (MIME) type. File filters define the email attachment file types and file extensions to be scanned and are used in attachment scan rules.

### Syntax

```
config file filter
  edit <filter_type>
```

```

    set description <string>
    set extension <string>
    set mime-type <string>
end

```

Variable	Description	Default
<filter_type>	Enter the file attachment executable type to filter by.	
description <string>	Enter the description of the attachment filter.	
extension <string>	Enter an extension expressed as a wildcard, for example *.exe, or *.dll.	
mime-type <string>	<p>Enter a MIME type in the format &lt;nature&gt;/&lt;format&gt;, in order to filter by file nature and format.</p> <p>For example, to filter by image, and specifically for PNG, enter the following:            set mime-type image/png</p> <p>To filter for all video formats, enter the following:            set mime-type video/*</p>	

## file signature

If you already have the SHA-1 (Secure Hash Algorithm 1) hash values of some known virus-infected files, you can add these values as file signatures and then, in the antivirus profile, enable the actions against these files. Use this command to add or edit the file signatures.

## Syntax

```

config file signature
  edit <signature_type>
    config item <hexadecimal>
      edit <signature_value>
    next
  set comments <string>
  set status {enable | disable} on page 128
  set type {sha1 | sha256} on page 128
end

```

Variable	Description	Default
<signature_type>	Enter the file signature ID.	
comments <string>	Enter the general comments for the file signature.	
status {enable   disable}	Enable or disable the signature check.	enable
type {sha1   sha256}	Enter the type of signature.	sha1

# log setting cloud

Use this command to configure storing log messages to the FortiAnalyzer Cloud.

## Syntax

```
config log setting cloud
  set status {enable | disable} on page 129
  set loglevel {alert | critical | debug | emergency | error | information | notification |
  warning} on page 129
  set event-log-category {imap | pop3 | smtp | webmail}] on page 130
  set event-log-status {enable | disable} on page 130
  set syseventlog-category {admin | configuration | dns | ha | system | update}] on page 130
  set system-event-log-status {enable | disable} on page 131
  set antivirus-log-status {enable | disable} on page 131
  set antispam-log-status {enable | disable} on page 131
  set history-log-status {enable | disable} on page 131
  set encryption-log-status {enable | disable} on page 131
end
```

Variable	Description	Default
status {enable   disable}	Enable to send log types which are enabled to FortiAnalyzer Cloud.	enable
loglevel {alert   critical   debug   emergency   error   information   notification   warning}	Enter one or more of the following severity levels: <ul style="list-style-type: none"> <li>emergency</li> <li>alert</li> <li>critical</li> <li>error</li> <li>warning</li> <li>notification</li> <li>information</li> <li>debug</li> </ul> This log destination will receive log messages greater than or equal to this severity level. For details, see the <a href="#">FortiMail Administration Guide</a> .	information

Variable	Description	Default
event-log-category {imap   pop3   smtp   webmail}}	<p>Enter all of the mail log types and subtypes that you want to record to this storage location. Separate each type with a space.</p> <ul style="list-style-type: none"> <li>imap: Log all IMAP events.</li> <li>pop3: Log all POP3 events.</li> <li>smtp: Log all SMTP relay or proxy events.</li> <li>webmail: Log all FortiMail webmail events.</li> </ul>	webmail smtp
event-log-status {enable   disable}	Enable or disable event logging to FortiAnalyzer Cloud.	webmail smtp
syseventlog-category {admin   configuration   dns   ha   system   update}}	<p>Enter all of the system event log types and subtypes that you want to record to this storage location. Separate each type with a space.</p> <ul style="list-style-type: none"> <li>admin: Administrative events such as logins, viewing log messages, and resetting the configuration.</li> <li>configuration: Configuration changes by an administrator, such as policies, profiles, and domains.</li> <li>dns: DNS queries.</li> </ul>	admin configuration dns ha system update

Variable	Description	Default
	<ul style="list-style-type: none"> <li>ha: High availability (HA) activity.</li> <li>system: System events, such as rebooting the FortiMail unit or IP address configuration via DHCP. <b>Note:</b> This category does not include events from mail daemons, which are configured in event-log-category [{imap pop3 smtp webmail}].</li> <li>update: Both successful and unsuccessful attempts to download firmware and FortiGuard updates.</li> </ul>	
system-event-log-status {enable   disable}	Enable to log system events.	enable
antivirus-log-status {enable   disable}	Enable to log all antivirus events.	enable
antispam-log-status {enable   disable}	Enable to log all antispam events.	enable
history-log-status {enable   disable}	Enable to log both successful and unsuccessful attempts by the built-in MTA or proxies to deliver email.	enable
encryption-log-status {enable   disable}	Enable to log all IBE events.	enable

## log setting remote

Use this command to configure remote log message storage, either on a Syslog server or FortiAnalyzer unit.

### Syntax

```
config log setting remote
  edit <log-destination_index>
    set certificate <certificate>
    set comma-separated-value {enable | disable}
    set encryption-log-status {enable | disable}
    set event-log-category {admin configuration ha | imap pop3 smtp system update webmail}
    set event-log-status {enable | disable}
    set facility {alert | audit | auth | authpriv | clock | cron | daemon | ftp | kern |
      local0 | local1 | local2 | local3 | local4 | local5 | local6 | local7 | lpr | mail |
      news | ntp}
    set history-log-status {enable | disable}
    set loglevel {alert | critical | debug | emergency | error | information | notification |
      warning}
    set matched-session-status {enable | disable}
    set port <port_int>
    set protocol {syslog | cftps}
    set server <log_ipv4>
    set spam-log-status {enable | disable}
    set status {enable | disable}
    set sysevent-log-category {admin | configuration | dns | ha | system | update}
    set sysevent-log-status {enable | disable}
    set syslog-mode {tcp | tcp-tls | udp}
    set virus-log-status {enable | disable}
  end
```

Variable	Description	Default
<log-destination_index>	Type an index number to identify which remote Syslog server or FortiAnalyzer unit you are configuring.	
certificate <certificate>	The certificate used by the Syslog-TLS connection to encrypt the log before delivery to the remote Syslog server.  This option is only available when <code>syslog-mode</code> is set to <code>tcp-tls</code> .	
comma-separated-value {enable   disable}	Enable if you want to send log messages in comma-separated value (CSV) format.  <b>Note:</b> Do not enable this option if the log destination is a FortiAnalyzer unit. FortiAnalyzer units do not support CSV format logs.	disable
encryption-log-status {enable   disable}	Enable or disable IBE event logging to a remote Syslog server or FortiAnalyzer unit.	disable

Variable	Description	Default
event-log-category {admin configuration ha   imap pop3 smtp system update webmail}	Type all of the log types and subtypes that you want to record to this storage location. Separate each type with a space. <ul style="list-style-type: none"> <li>• admin: Log all administrative events, such as logins, resets, and configuration updates.</li> <li>• configuration: Enable to log configuration changes.</li> <li>• ha: Log all high availability (HA) activity.</li> <li>• imap: Log all IMAP events.</li> <li>• pop3: Log all POP3 events.</li> <li>• smtp: Log all SMTP relay or proxy events.</li> <li>• system: Log all system-related events, such as rebooting the FortiMail unit.</li> <li>• update: Log both successful and unsuccessful attempts to download FortiGuard updates.</li> <li>• webmail: Log all FortiMail webmail events.</li> </ul>	
event-log-status {enable   disable}	Enable or disable event logging to a remote Syslog server or FortiAnalyzer unit.	disable
facility {alert   audit   auth   authpriv   clock   cron   daemon   ftp   kern   local0   local1   local2   local3   local4   local5   local6   local7   lpr   mail   news   ntp}	Type the facility identifier that the FortiMail unit will use to identify itself when sending log messages to the first Syslog server.  To easily identify log messages from the FortiWeb unit when they are stored on the Syslog server, enter a unique facility identifier, and verify that no other network devices use the same facility identifier.	kern
history-log-status {enable   disable}	Enable to log both successful and unsuccessful attempts by the built-in MTA or proxies to deliver email.	disable
loglevel {alert   critical   debug   emergency   error   information   notification   warning}	Type one of the following severity levels: <ul style="list-style-type: none"> <li>• emergency</li> <li>• alert</li> <li>• critical</li> <li>• error</li> <li>• warning</li> <li>• notification</li> <li>• information</li> <li>• debug</li> </ul> This log destination will receive log messages greater than or equal to this severity level.	information
matched-session-status {enable   disable}	Enable to log only matched sessions.	disable

Variable	Description	Default
port <port_int>	If the remote host is a FortiAnalyzer unit, type 514. If the remote host is a Syslog server, type the UDP port number on which the Syslog server listens for connections.	514
protocol {syslog   cftps}	Enter the protocol used for remote logging.	syslog
server <log_ipv4>	Type the IP address of the Syslog server or FortiAnalyzer unit.	
spam-log-status {enable   disable}	Enable to log all antispam events.	disable
status {enable   disable}	Enable to send log messages to a remote Syslog server or FortiAnalyzer unit.	disable
sysevent-log-category {admin   configuration   dns   ha   system   update}	Enter the system event log category to log.	
sysevent-log-status {enable   disable}	Enable to log system events.	disable
syslog-mode {tcp   tcp-tls   udp}	Enter the protocol used for delivering the log to the remote Syslog server.	udp
virus-log-status {enable   disable}	Enable to log all antivirus events.	disable

## Related topics

[log setting local on page 134](#)

[log alertemail recipient on page 136](#)

[log alertemail setting on page 137](#)

## log setting local

Use this command to configure storing log messages to the local hard disk.

## Syntax

```
config log setting local
  set antispam-log-status {enable | disable}
  set antivirus-log-status {enable | disable}
  set disk-full {overwrite | nolog}
  set encryption-log-status {enable | disable}
  set event-log-category {admin configuration ha | imap pop3 smtp system update webmail}
  set event-log-status {enable | disable}
  set history-log-status {enable | disable}
  set loglevel {alert | critical | debug | emergency | error | information | notification |
  warning}
```

```

set retention-period <days>
set rotation-hour <hour_int>
set rotation-period <days_int>
set rotation-size <file-size_int>
set status {enable | disable}
set sysevent-log-category {admin | configuration | dns | ha | system | update}
set system-event-log-status
end

```

Variable	Description	Default
antispam-log-status {enable   disable}	Enable to log all antispam events.	enable
antivirus-log-status {enable   disable}	Enable to log all antivirus events.	enable
disk-full {overwrite   nolog}	Enter the action the FortiMail unit will perform when the local disk is full and a new log message is caused: <ul style="list-style-type: none"> <li>overwrite: Delete the oldest log file in order to free disk space, and store the new log message.</li> <li>nolog: Discard the new log message.</li> </ul>	overwrite
encryption-log-status {enable   disable}	Enable to log all IBE events.	enable
event-log-category {admin configuration ha   imap pop3 smtp system update webmail}	Type all of the log types and subtypes that you want to record to this storage location. Separate each type with a space. admin: Log all administrative events, such as logins, resets, and configuration updates. configuration: Enable to log configuration changes. ha: Log all high availability (HA) activity. imap: Log all IMAP events. pop3: Log all POP3 events. smtp: Log all SMTP relay or proxy events. system: Log all system-related events, such as rebooting the FortiMail unit. update: Log both successful and unsuccessful attempts to download FortiGuard updates. webmail: Log all FortiMail webmail events.	webmail smtp
event-log-status {enable   disable}	Enable or disable event logging to the local hard disk.	enable
history-log-status {enable   disable}	Enable to log both successful and unsuccessful attempts by the built-in MTA or proxies to deliver email.	enable
loglevel {alert   critical   debug   emergency   error   information   notification   warning}	Type one of the following severity levels: <ul style="list-style-type: none"> <li>emergency</li> <li>alert</li> <li>critical</li> <li>error</li> <li>warning</li> </ul>	information

Variable	Description	Default
	<ul style="list-style-type: none"> <li>notification</li> <li>information</li> <li>debug</li> </ul> This log destination will receive log messages greater than or equal to this severity level.	
retention-period <days>	Specify how long to keep the logs. Valid rang is 1 to 1461 days. Default value is 0, which means no limit.	0
rotation-hour <hour_int>	Enter the hour of the day when the rotation should start.	0
rotation-period <days_int>	Enter the maximum age of the current log file in days. When the log file reaches either the maximum size or age, the log file is rolled (that is, the current log file is saved to a file with a new name, and a new log file is started).	10
rotation-size <file-size_int>	Enter the maximum size of the current log file in megabytes (MB). The valid range is between 1 to 500. When the log file reaches either the maximum size or age, the log file is rolled (that is, the current log file is saved to a file with a new name, and a new log file is started).	100
status {enable   disable}	Enable to send log types which are enabled to the local hard disk.	enable
sysevent-log-category {admin   configuration   dns   ha   system   update}	Enter the system event log category to log.	configuration admin system ha update dns
system-event-log-status	Enable to log system events.	enable

## Related topics

[log setting remote on page 132](#)

[log alertemail recipient on page 136](#)

[log alertemail setting on page 137](#)

## log alertemail recipient

Use this command to add up to three email addresses that will receive alerts.

Before the FortiMail unit can send alert email messages, you must configure it with one or more recipients.

You must also configure which categories of events will cause the FortiMail unit to send alert email messages. For more information, see [log alertemail setting on page 137](#).

## Syntax

```
config log alertemail recipient
  edit <recipient_email>
  next
end
```

Variable	Description	Default
<recipient_email>	Type an email address that will receive alert email.	

## Example

The following example configures alert email to be sent to three email addresses.

```
config log alertemail recipient
  edit admin@example.com
  next
  edit support@example.com
  next
  edit helpdesk@example.com
  next
end
```

## Related topics

[log setting remote on page 132](#)

[log setting local on page 134](#)

[log alertemail setting on page 137](#)

## log alertemail setting

Use this command to configure which events will cause the FortiMail unit to send an alert email message.

Before the FortiMail unit can send an alert email message, you must select the event or events that will cause it to send an alert.

You must also configure alert email message recipients. For more information, see [log alertemail recipient on page 136](#).

## Syntax

```
config log alertemail setting
```

```

set categories {deferq-over-limit diskfull ha license-expire remote-storage-failure system
system-quota-full user-quota-full virus}
set deferq-interval <interval_int>
set deferq-trigger <trigger_int>
set license-interval <integer>
end

```

Variable	Description	Default
categories {deferq-over-limit diskfull ha license-expire remote-storage-failure system system-quota-full user-quota-full virus}	<p>Enter a list of one or more of the following event types that will cause alert email:</p> <ul style="list-style-type: none"> <li><code>deferq-over-limit</code>: The deferred mail queue has exceeded the number of messages during the interval specified in <code>deferq-interval &lt;interval_int&gt;</code> and <code>deferq-trigger &lt;trigger_int&gt;</code>.</li> <li><code>diskfull</code>: The FortiMail unit's hard disk is full.</li> <li><code>ha</code>: A high availability (HA) event such as failover has occurred.</li> <li><code>license-expire</code>: The license has expired.</li> <li><code>remote-storage-failure</code>: Email archiving to the remote host has failed.</li> <li><code>system</code>: The FortiMail unit has detected a system error.</li> <li><code>system-quota-full</code>: The FortiMail unit has reached its disk space quota.</li> <li><code>user-quota-full</code>: An email user account has reached its disk space quota.</li> <li><code>virus</code>: The FortiMail unit has detected a virus.</li> </ul> <p>Separate each option with a space.</p>	system
deferq-interval <interval_int>	Enter the interval in minutes between checks of deferred queue size. This can be any number greater than zero.	30
deferq-trigger <trigger_int>	Enter the size that the deferred email queue must reach to cause an alert email to be sent. The valid range is 1 to 99999.	10000
license-interval <integer>	Enter the number of days (1-100) the FortiGuard license is to expire. An alert email is sent on the expiry day.	30

## Related topics

[log setting remote on page 132](#)

[log setting local on page 134](#)

[log alertemail recipient on page 136](#)

## mailsetting email-addr-handling

Use this command to rewrite the unqualified sender addresses -- unqualified email address is a string without @ sign, such abc. If this feature is enabled, the Envelope sender (MAIL FROM:) will be rewritten to abc@host.domain, while the Header From and Reply-to will be rewritten to abc@domain. Host is the host name attribute of the FortiMail unit and domain is the local domain name attribute of the FortiMail unit.

Set the email address (sender and recipient) parsing mode:

- Strict mode requires that the local parts of the Envelope sender (MAIL FROM:) and the Envelope recipient (RCPT TO:) strictly follow the RFC requirements.
- Relaxed mode allows non-RFC compliant local parts, such as email addresses containing multiple consecutive "." in the local parts or before "@". For example, user...name@example.com, and username...@example.com.

### Syntax

```
config mailsetting email-addr-handling
  set rewrite-unqualified-sender-addr {enable | disable}
  set email-addr-parsing-mode {strict | relaxed}
end
```

Variable	Description	Default
rewrite-unqualified-sender-addr {enable   disable}	Enable or disable the unqualified email sender address rewriting feature.	disable
email-addr-parsing-mode {strict   relaxed}	Set the parsing mode to strict or relaxed.	strict

## mailsetting email-continuity

Use this command to permit end users to access inbound emails when the FortiMail unit is in either Gateway or Transparent mode.



The email continuity feature is license based. This command is only available with a valid purchased license from FortiGuard, and when the FortiMail unit is operating in either Gateway or Transparent mode.

### Syntax

```
config mailsetting email-continuity
  set auth-cache-period <days_int>
  set auth-cache-status {enable | disable}
  set status {enable | disable}
```

```

    set retention-period <days_int>
end

```

Variable	Description	Default
auth-cache-period <days_int>	Specify the number of days to preserve the authentication cache. The valid range is 1 to 60.	20
auth-cache-status {enable   disable}	Enable or disable authentication cache feature.	disable
retention-period <days_int>	Specify the number of days to keep emails in the folder. The valid range is 1 to 60. Note that the actual retention period is whichever is the smaller value of this setting and the auto-delete-old-mail sub-command under <a href="#">profile resource</a> .	20
status {enable   disable}	Enable or disable email continuity feature.	disable

## mailsetting host-mapping

Use this command to configure local host name mapping for email routing.

### Syntax

```

config mailsetting host-mapping
  edit <host_name>
    set name <name_string>
    set mapped-host <host_name_string>
  end

```

Variable	Description	Default
<host_name>	Enter the local host name.	
name <name_string>	Enter the name for host mapping.	
mapped-host <host_name_string>	Enter the IPaddress or host name of mapped host.	

### Related topics

[log setting remote on page 132](#)

[log setting local on page 134](#)

[log alertemail recipient on page 136](#)

# mailsetting mail-scan-options

Use this command to configure how to scan the compressed files.

## Syntax

```
config mailsetting mail-scan-options
  set content-scan-level {high | low | medium}
  set decompress-max-level <level_int>
  set decompress-max-size <size_in_MB>
  set scan-microsoft-msg {enable | disable}
  set scan-timeout-action {tempfail | passthrough}
  set scan-timeout-value <time-in-seconds>
end
```

Variable	Description	Default
content-scan-level {high   low   medium}	Set the scan level of dictionary and DLP rules. When set to <code>medium</code> or <code>high</code> , FortiMail carries out regex recursive matching, which consumes more resources.	medium
decompress-max-level <level_int>	Specify how many levels to decompress the archived files for antivirus and content scan. Valid range is 1 to 36.	12
decompress-max-size <size_in_MB>	Specify the maximum file size to scan after the archived files are decompressed. This applies to every single file after decompression. Bigger files will not be scanned.	10
scan-microsoft-msg {enable   disable}	Enable to scan Microsoft Transport Neutral Encapsulation format (TNEF) and MSG format attachments.	enable
scan-timeout-action {tempfail   passthrough}	When the email attachments are large and the email scanning has timed out, FortiMail can either send a temporary fail message to the sender or just let the message pass through without further scanning.	tempfail
scan-timeout-value <time-in-seconds>	Specify how long in seconds FortiMail should spend on scanning email contents. The valid range is 270 to 900. When the specified timeout has been reached, FortiMail will take the action specified above.	285

## Related topics

[mailsetting relay-host-list on page 145](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting systemquarantine on page 152](#)

## mailsetting preference

When you configure antispam, antivirus, and content action profiles, you may use the following actions:

- Deliver to alternate host
- Deliver to original host
- System quarantine
- Personal quarantine

For the above actions, you can choose to deliver or quarantine the original email or the modified email. For example, when the HTML content is converted to text, if you choose to deliver the unmodified copy, the HTML version will be delivered; if you choose to deliver the modified copy, the plain text version will be delivered.

## Syntax

```
config mailsetting preference
  set deliver-to-alternate-host {modified_copy | unmodified_copy}
  set deliver-to-original-host {modified_copy | unmodified_copy}
  set disclaimer-insertion {selected-message | all-message}
  set domain-quarantine {modified_copy | unmodified_copy}
  set enforce-delivery {enable | disable}
  set personal-quarantine {modified_copy | unmodified_copy}
  set personal-quarantine-attachment-scan {enable | disable}
  set subject-tag-location {beginning | end}
  set system-quarantine {modified_copy | unmodified_copy}
end
```

Variable	Description	Default
deliver-to-alternate-host {modified_copy   unmodified_copy}	Specify to use the modified email or the unmodified email.	modified_copy
deliver-to-original-host {modified_copy   unmodified_copy}	Specify to use the modified email or the unmodified email.	modified_copy
disclaimer-insertion {selected-message   all-message}	Define the email disclaimer insertion preference: <ul style="list-style-type: none"> <li>• selected-message: Disclaimer will not be added once again if the email is part of the existing email thread.</li> <li>• all-message: Disclaimer will always be added, whether the email is a reply or a new email.</li> </ul>	selected-message
domain-quarantine {modified_copy   unmodified_copy}	Specify to use the modified email or the unmodified email.	modified_copy
enforce-delivery {enable   disable}	Enforce delivery action if delivery to original/alternative host is enabled.	enable
personal-quarantine {modified_copy   unmodified_copy}	Specify to use the modified email or the unmodified email.	modified_copy
personal-quarantine-attachment-scan {enable   disable}	Enable or disable attachment scan for personal quarantined spam messages.	disable

Variable	Description	Default
subject-tag-location {beginning   end}	Select where to insert the subject tag.	beginning
system-quarantine {modified_copy   unmodified_copy}	Specify to use the modified email or the unmodified email.	modified_copy

## mailsetting proxy-smtp

Use this command to configure using the outgoing proxy instead of the built-in MTA for outgoing SMTP connections.



This command applies only if the FortiMail unit is operating in transparent mode.

## Syntax

```
config mailsetting proxy-smtp
  set proxy-original {enable | disable}
end
```

Variable	Description	Default
proxy-original {enable   disable}	<p>Enable to, for outgoing SMTP connections, use the outgoing proxy instead of the built-in MTA.</p> <p>This allows the client to send email using the SMTP server that they specify, rather than enforcing the use of the FortiMail unit's own built-in MTA. The outgoing proxy will refuse the connection if the client's specified destination SMTP server is not available. In addition, it will not queue email from the SMTP client, and if the client does not successfully complete the connection, the outgoing proxy will simply drop the connection, and will not retry. Since authentication profiles may not successfully complete, the outgoing proxy will also ignore any authentication profiles that may be configured in the IP-based policy. The built-in MTA would normally apply authentication on behalf of the SMTP server, but the outgoing proxy will instead pass any authentication attempts through to the SMTP server, allowing it to perform its own authentication.</p> <p>Disable to relay email using the built-in MTA to either the SMTP relay defined in <a href="#">mailsetting relay-host-list on page 145</a>, if any, or directly to the MTA that is the mail exchanger (MX) for the recipient email address's (RCPT TO:) domain. The email may not actually travel through the unprotected SMTP server, even though it was the relay originally specified by the SMTP client. For details, see the <a href="#">FortiMail Administration Guide</a>.</p> <p>Disclaimer messages require that this option be enabled. For more information, see <a href="#">system disclaimer on page 283</a>.</p>	disable

Variable	Description	Default
	 <p>If this option is enabled, consider also enabling <a href="#">session-prevent-open-relay {enable   disable}</a>. Failure to do so could allow clients to use open relays.</p> <p><b>Note:</b> If this option is disabled, and an SMTP client is configured to authenticate, you must configure and apply an authentication profile. Without the profile, authentication with the built-in MTA will fail. Also, the mail server must be explicitly configured to allow relay from the built-in MTA in this case.</p> <p><b>Note:</b> If this option is enabled, you will not be able to use IP pools. For more information, see <a href="#">profile ip-pool on page 226</a>.</p> <p><b>Note:</b> For security reasons, this option does not apply if there is no session profile selected in the applicable IP-based policy. For more information on configuring IP policies, see <a href="#">config policy delivery-control on page 168</a>.</p>	

## Related topics

[mailsetting relay-host-list on page 145](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting systemquarantine on page 152](#)

## mailsetting quarantine-rescan-options

Use this command to configure quarantined mail rescan options.

### Syntax

```
config mailsetting quarantine-rescan-options
  set type {antivirus | fortisandbox}
  set source {personal-quarantine | system-quarantine}
end
```

Variable	Description	Default
type {antivirus   fortisandbox}	Set the type to rescan mail either from AntiVirus or FortiSandbox.	
source {personal-quarantine   system-quarantine}	Set the source to rescan mail from either the personal quarantine or the system quarantine.	

## mailsetting relay-host-list

Use this command to configure the FortiMail unit's built-in MTA's connection to an SMTP relay, if any, to which the FortiMail unit will relay outgoing email. You can configure up to eight relays.

This is typically provided by your Internet service provider (ISP), but could be a mail relay on your internal network.

If the SMTP relay's domain name resolves to more than one IP address, for each SMTP session, the FortiMail unit will randomly select one of the IP addresses from the result of the DNS query, effectively load balancing between the SMTP relays.

If you do not configure a relay server, for outgoing email delivered by the built-in MTA, the FortiMail unit will instead query the DNS server for the MX record of the mail domain in the recipient's email address (RCPT TO:), and relay the email directly to that mail gateway.

You can also use MX records and IP groups as relay types.

For details, see the [FortiMail Administration Guide](#).



This option will be ignored for email that matches an antispam or content profile where you have enabled `alternate-host {<relay_fqdn> | <relay_ipv4>}`.

## Syntax

```
config mailsetting relay-host-list
  edit <relay-host-name>
    set auth-password <password_str>
    set auth-status {enable | disable}
    set auth-type {auto | plain | login | digest-md5 | cram-md5}
    set auth-username <user_str>
    set host-name on page 146
    set host-port on page 146
    set ip-group-profile on page 146
    set mx-lookup-domain-name on page 146
    set relay-type {host | ip-group | mx-lookup} on page 146
    set use-smtps {enable | disable}
  end
```

Variable	Description	Default
<relay-host-name>	Enter the host name or IP address of the relay server.	
auth-password <password_str>	If <code>auth-status {enable   disable}</code> is enable, enter the password of the FortiMail unit's user account on the SMTP relay.	

Variable	Description	Default
auth-status {enable   disable}	Enable if the SMTP relay requires authentication using the SMTP AUTH command. Also configure <code>auth-username &lt;user_str&gt;</code> , <code>auth-password &lt;password_str&gt;</code> , and <code>auth-type {auto   plain   login   digest-md5   cram-md5}</code> .	disable
auth-type {auto   plain   login   digest-md5   cram-md5}	If <code>auth-status {enable   disable}</code> is enable, enter either the SMTP authentication type required by the SMTP relay when the FortiMail unit sends the ESMTP AUTH command, or enter auto to automatically detect and use the most secure authentication type supported by the relay server.	auto
auth-username <user_str>	If <code>auth-status {enable   disable}</code> is enable, enter the name of the FortiMail unit's user account on the SMTP relay.	
host-name	Enter the relay host ip or host name.	
host-port	Enter the host port number.	25
ip-group-profile	Enter an IP group profile.	
mx-lookup-domain-name	Enter the domain name for MX record lookup.	
relay-type {host   ip-group   mx-lookup}	Enter the SMTP relay type: host, ip-group, or mx-lookup.	host
use-smtps {enable   disable}	Enable to initiate SSL- and TLS-secured connections to the SMTP relay if it supports SSL/TLS. When disabled, SMTP connections from the FortiMail unit's built-in MTA or proxy to the relay will occur as clear text, unencrypted. This option must be enabled to initiate SMTPS connections.	disable

## Related topics

[mailsetting proxy-smtp on page 143](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting systemquarantine on page 152](#)

## mailsetting sender-rewriting-scheme

Configure sender rewriting scheme (SRS) settings.

SRS is used to rewrite the envelope sender of an email address, so that emails may be forwarded by an MTA if necessary without being rejected by the receiving server which may have a strict SPF policy in place.

## Syntax

```
config mailsetting sender-rewriting-scheme
  config rewrite-exempt-list
    edit <domain-name>
  end
  set domain-for-rewrite {all | none | protected}
  set rewritten-addr-handling {reverse | none}
end
```

Variable	Description	Default
rewrite-exempt-list	Configure domain names that are to be exempted from sender rewriting.	
domain-for-rewrite {all   none   protected}	Select whether to rewrite external senders sending emails for all domains, for protected domains, or to not rewrite the sender at all.	none
rewritten-addr-handling {reverse   none}	For those recipients that are previously rewritten senders, set to reverse to reverse the recipient address and send the email to the original sender. Set to none to deny any recipient that is previously rewritten.	reverse

## mailsetting smtp-rcpt-verification

Microsoft 365 does not accept a blank MAIL FROM: , which is the FortiMail default setting for SMTP recipient verification. Use this command to add an envelope from address to solve the problem.

## Syntax

```
config mailsetting smtp-rcpt-verification
  set connection-type {auto | regular | secure}
  set mail-from-addr <email_address>
  set mode {regular | fail-open}
end
```

Variable	Description	Default
connection-type {auto   regular   secure}	Define the connection type for SMTP recipient verification: <ul style="list-style-type: none"> <li>auto: Attempt ESMTP protocol first, and fallback to SMTP protocol. ESMTP supports recipient verification for TLS-enforced backend connections.</li> </ul>	regular

Variable	Description	Default
	<ul style="list-style-type: none"> <li>regular: Use SMTP protocol (HELO without STARTTLS).</li> <li>secure: Use ESMTP protocol (EHLO with STARTTLS).</li> </ul>	
mail-from-addr <email_address>	Specify the envelope MAIL FROM: address to use.	
mode {regular   fail-open}	Define the recipient verification mode: <ul style="list-style-type: none"> <li>regular: Always perform recipient verification with the SMTP server.</li> <li>fail-open: Do not perform recipient verification if the SMTP server is unreachable.</li> </ul>	regular

## mailsetting storage central-ibe

Use this command to configure storage of IBE encrypted email.

To reduce the storage resources required on lower-end FortiMail units, you can configure them to store encrypted email on a high-end FortiMail unit that you have configured to act as a centralized storage server.

## Syntax

```
config mailsetting storage central-ibe
    set remote-storage-type {disable | from-client | to-server-over-ssl}
    set client-ip <client_ipv4>
    set server-host <server_ipv4>
    set server-name <name_str>
end
```

Variable	Description	Default
remote-storage-type {disable   from-client   to-server-over-ssl}	Enter one of the following centralized IBE types: <ul style="list-style-type: none"> <li>disable: Centralized IBE storage is disabled. The FortiMail unit stores its IBE messages locally, on its own hard disks.</li> <li>from-client: Select this option to allow the FortiMail unit to act as a central IBE storage server and receive IBE email from the client FortiMail units. Also configure <code>client-ip &lt;client_ipv4&gt;</code> for each FortiMail client. Note this feature is only available on the high-end FortiMail models (FortiMail 1000D and above).</li> <li>to-server-over-ssl: Select this option to allow the FortiMail unit to act as a central IBE storage client and send its IBE messages to the remote FortiMail server. Also configure <code>server-name &lt;name_str&gt;</code> and <code>server-host &lt;server_ipv4&gt;</code>. All FortiMail units can act as clients.</li> </ul>	disable
client-ip <client_ipv4>	This option applies only if <code>remote-storage-type</code> is set to <code>from-client</code> . Enter the IP address of the FortiMail unit that is allowed to store its IBE email on this high-end FortiMail unit.	

Variable	Description	Default
	For FortiMail 1000D, 2000A, 2000B, and VM04 models, you can enter a maximum of 10 IP addresses as clients. For FortiMail 3000C and above models, you can enter a maximum of 20 IP addresses.	
server-host <server_ipv4>	This option applies only if <code>remote-storage-type</code> is set to <code>to-server-over-ssl</code> . Enter the IP address of the FortiMail unit that is acting as the central IBE storage server.	
server-name <name_str>	This option applies only if <code>remote-storage-type</code> is set to <code>to-server-over-ssl</code> . Enter the name of the FortiMail unit that is acting as the central IBE storage server. This name may be the host name or any other name that uniquely identifies the central quarantine server.	

## mailsetting storage central-quarantine

Use this command to configure centralized storage of quarantined email. This command is only available on high-end models.

To reduce the storage resources required on lower-end FortiMail units, you can configure them to store quarantined email on a high-end FortiMail unit that you have configured to act as a centralized quarantine server.

### Syntax

```
config mailsetting storage central-quarantine
  set remote-storage-type {disable | from-client | to-server-over-ssl | to-server-plain |
    unknown}
  set client-ip <client_ipv4>
  set server-host <server_ipv4>
  set server-name <name_str>
end
```

Variable	Description	Default
remote-storage-type {disable   from-client   to-server-over-ssl   to-server-plain   unknown}	Enter one of the following centralized quarantine types: <ul style="list-style-type: none"> <li><code>disable</code>: Centralized quarantine storage is disabled. The FortiMail unit stores its quarantines locally, on its own hard disks.</li> <li><code>from-client</code>: Select this option to allow the FortiMail unit to act as a central quarantine server and receive quarantined messages from other client FortiMail units. Also configure <code>client-ip &lt;client_ipv4&gt;</code> of the FortiMail clients. Note this feature is only available on the high-end FortiMail models (FortiMail 1000D and above).</li> <li><code>to-server-over-ssl</code>: Same as <code>to-server-plain</code>, except the connection uses SSL.</li> <li><code>to-server-plain</code>: Select this option to allow the FortiMail unit to act as a central quarantine client and send quarantined messages to the remote</li> </ul>	disable

Variable	Description	Default
	<p>server in plain text. Also configure <code>server-name &lt;name_str&gt;</code> and <code>server-host &lt;server_ipv4&gt;</code> of the remote server. All FortiMail units can act as clients.</p> <ul style="list-style-type: none"> <li>unknown: Centralized quarantine storage is unknown.</li> </ul>	
<code>client-ip &lt;client_ipv4&gt;</code>	<p>This option applies only if <code>remote-storage-type</code> is set to <code>from-client</code>. Enter the IP address of the FortiMail unit that is allowed to store its quarantined email on this high-end FortiMail unit.</p> <p>For FortiMail 1000D, 2000A, 2000B, and VM04 models, you can enter a maximum of 10 IP addresses as clients. For FortiMail 3000C and above models, you can enter a maximum of 20 IP addresses.</p>	
<code>server-host &lt;server_ipv4&gt;</code>	<p>This option applies only if <code>remote-storage-type</code> is set to <code>to-server-over-ssl</code> or <code>to-server-plain</code>. Enter the IP address of the FortiMail unit that is acting as the central quarantine server.</p>	
<code>server-name &lt;name_str&gt;</code>	<p>This option applies only if <code>remote-storage-type</code> is set to <code>to-server-over-ssl</code> or <code>to-server-plain</code>. Enter the name of the FortiMail unit that is acting as the central quarantine server. This name may be the host name or any other name that uniquely identifies the central quarantine server.</p>	

## Related topics

[mailsetting proxy-smtp on page 143](#)

[mailsetting relay-host-list on page 145](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting systemquarantine on page 152](#)

[mailsetting storage central-quarantine on page 149](#)

## mailsetting storage config

Use these commands to configure the FortiMail unit to store mail data such as queues and email user mailboxes either on its local hard disks, or on a network file storage (NFS or iSCSI) server.

If the FortiMail unit is operating in an HA group, remote storage may be required or recommended. For more information, see the [FortiMail Administration Guide](#).

## Syntax

```
config mailsetting storage config
  set encryption-key
```

```

set folder <folder_str>
set host <host_str>
set iscsi-id <id_str>
set iscsi-use-initiator {enable | disable}
set nfs-version (auto | nfs-v3 | nfs-v4}
set password <password_str>
set port <port_int>
set protocol {nfs | iscsi_server}
set type {local | remote}
set username <user-name_str>
end

```

Variable	Description	Default
encryption-key	Enter the key that will be used to encrypt data stored on the iSCSI server. Valid key lengths are between 6 and 64 single-byte characters. Applies only when protocol is iscsi_server.	
folder <folder_str>	Enter the directory path of the NFS export on the NAS server where the FortiMail unit will store email. Applies only when protocol is nfs.	
host <host_str>	Enter the IP address or fully qualified domain name (FQDN) of the NFS or iSCSI server.	
iscsi-id <id_str>	Enter the iSCSI identifier in the format expected by the iSCSI server, such as an iSCSI Qualified Name (IQN), Extended Unique Identifier (EUI), or T11 Network Address Authority (NAA). Applies only when protocol is iscsi_server.	
iscsi-use-initiator {enable   disable}	Enable to use iSCSI initiator name as username.	disable
nfs-version (auto   nfs-v3   nfs-v4}	Use this command to control supported NFS versions. This command is helpful when NFS version 4 causes problems, you can specify to use NFS version 3.	auto
password <password_str>	Enter the password of the FortiMail unit's account on the iSCSI server. Applies only when protocol is iscsi_server.	
port <port_int>	Enter the TCP port number on which the NFS or iSCSI server listens for connections.	2049
protocol {nfs   iscsi_server}	Select the type of the NAS server: <ul style="list-style-type: none"> <li>nfs: A network file system (NFS) server. If you select this option, enter the following information:</li> <li>iscsi_server: An Internet SCSI (Small Computer System Interface), also called iSCSI, server. If you select this option, enter the following information:</li> </ul>	nfs
type {local   remote}	Select whether to store email locally or on an NFS server.	local
username <user-name_str>	Enter the user name of the FortiMail unit's account on the iSCSI server. Applies only when protocol is iscsi_server.	

## Related topics

[mailsetting proxy-smtp on page 143](#)

[mailsetting relay-host-list on page 145](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting systemquarantine on page 152](#)

## mailsetting systemquarantine

Use this command to configure the system quarantine account settings.

For more information on the system quarantine administrator account, see the [FortiMail Administration Guide](#).

## Syntax

```
config mailsetting systemquarantine
  config folders
    edit <folder_name>
      set description <description>
      set retention-period <days_int>
    end
  set account <name_str>
  set forward-address <recipient_str>
  set password <password_str>
  set rotation-period <day_integer>
  set rotation-status {enable | disable}
end
```

Variable	Description	Default
description <description>	Optional description of the folder.	
retention-period <days_int>	Number of days to keep messages in the folder. The valid range is 0 to 730 (0 means no limit).	30
account <name_str>	Enter the name for the system quarantine administrator account. Surround the account name with single quotes.	systemquarantine
forward-address <recipient_str>	Enter an email address to which all messages diverted to the system quarantine will be copied. Surround the email address with single quotes.	
password <password_str>	Enter the password for the system quarantine administrator account. Surround the password with single quotes. The password may be entered either literally, or as a pre-encoded string prefixed with "Enc <string>".	forti12356net

Variable	Description	Default
rotation-period <day_ integer>	Enter the period in days when the FortiMail unit rotates the current system quarantine folder ("Inbox"). The valid range is 1 to 90.  When the folder reaches this period, the FortiMail unit renames the current folder based upon its creation date and rename date, and creates a new "Inbox" folder.	7
rotation-status {enable   disable}	Enable or disable folder rotation.	enable

## Related topics

[mailsetting proxy-smtp on page 143](#)

[mailsetting relay-host-list on page 145](#)

[mailsetting storage central-quarantine on page 149](#)

[mailsetting storage central-quarantine on page 149](#)

## ms365 account

Use this command to connect to Microsoft 365 to access the user mailboxes. You must have domain administrator privileges to access Microsoft 365.

## Syntax

```
config ms365 account
  edit <name>
    config user-filter
      edit <name>
        set ad-group-attr {custom | displayname | mail}
        set ad-group-attr-name <string>
        set ad-group-attr-value <string>
        set email-group <group_name>
        set ldap-group <string>
        set ldap-profile <profile_name>
        set pattern <string>
        set status {enable | disable}
        set type {ad-group | email-group | imported-user | ldap-group | regex | wildcard}
      next
    end
    set application-id <string>
    set application-secret <password>
    set description <string>
    set service-endpoint {china | germany | global | us-dod | us-gov}
    set tenant <password>
```

end

Variable	Description	Default
<name>	Enter the name of the account profile.	
ad-group-attr {custom   displayname   mail}	<b>Note:</b> This option is only available when type is set to ad-group. Select the Azure AD group attribute.	displayname
ad-group-attr-name <string>	<b>Note:</b> This option is only available when type is set to ad-group and ad-group-attr is set to custom. Enter the custom Azure AD group attribute name.	
ad-group-attr-value <string>	<b>Note:</b> This option is only available when type is set to ad-group. Enter the Azure AD group attribute value.	
application-id <string>	Enter the application ID.	
application-secret <password>	Enter the application secret/password.	
description <string>	Enter a brief description of the account.	
email-group <group_name>	<b>Note:</b> This option is only available when type is set to email-group. Select an email group.	
ldap-group <string>	<b>Note:</b> This option is only available when type is set to ldap-group. Enter the LDAP group name.	
ldap-profile <profile_name>	<b>Note:</b> This option is only available when type is set to ldap-group. Select an LDAP group profile.	
pattern <string>	<b>Note:</b> This option is only available when type is set to regex or wildcard. Enter the user pattern.	
service-endpoint {china   germany   global   us-dod   us-gov}	Select a regional endpoint appropriate to your geographical location.	global
status {enable   disable}	Enable or disable this user filter.	disable
tenant <password>	Enter the Microsoft 365 tenant credentials.	
type {ad-group   email-group   imported-user   ldap-group   regex   wildcard}	Define the filter type as one of the following: <ul style="list-style-type: none"> <li>ad-group: Azure AD group.</li> <li>email-group: Email group.</li> <li>imported-user: Imported internal or external user.</li> <li>ldap-group: LDAP group.</li> <li>regex: User as regular expression.</li> <li>wildcard: User as wildcard.</li> </ul>	wildcard

## ms365 policy

Use this command to configure Microsoft 365 scan policies. You must have domain administrator privileges to access Microsoft 365.

### Syntax

```
config ms365 policy
  edit <name>
    set account <account_name>
    set profile-antispam <name>
    set profile-antivirus <name>
    set profile-content <name>
    set profile-dlp <name>
    set recipient-ad-group-attr {custom | displayname | mail}
    set recipient-ad-group-attr-name <string>
    set recipient-ad-group-attr-value <string>
    set recipient-domain <string>
    set recipient-email-group <group_name>
    set recipient-ldap-profile <profile_name>
    set recipient-name <string>
    set recipient-pattern-regex <string>
    set recipient-type {ad-group | email-group | ldap-group | regex | wildcard}
    set sender-ad-group-attr {custom | displayname | mail}
    set sender-ad-group-attr-name <string>
    set sender-ad-group-attr-value <string>
    set sender-domain <string>
    set sender-email-group <group_name>
    set sender-ldap-profile <profile_name>
    set sender-name <string>
    set sender-pattern-regex <string>
    set sender-type {ad-group | email-group | external | internal | ldap-group | regex |
      wildcard}
    set source-ip-address <ipv4mask>
    set source-type {geoip-group | ip-address | ip-group}
    set status {enable | disable}
  end
```

Variable	Description	Default
account <account_name>	Select a Microsoft 365 account.	
profile-antispam <name>	Assign an antispam profile to the real-time scan policy.	
profile-antivirus <name>	Assign an antivirus profile to the real-time scan policy.	
profile-content <name>	Assign an content profile to the real-time scan policy.	
profile-dlp <name>	Assign an DLP profile to the real-time scan policy.	
recipient-ad-group-attr {custom   displayname   mail}	<b>Note:</b> This option is only available when recipient-type is set to ad-group. Select the recipient Azure AD group attribute.	displayname

Variable	Description	Default
recipient-ad-group-attr-name <string>	<b>Note:</b> This option is only available when recipient-type is set to ad-group and recipient-ad-group-attr is set to custom. Enter the custom recipient Azure AD group attribute name.	
recipient-ad-group-attr-value <string>	<b>Note:</b> This option is only available when recipient-type is set to ad-group. Enter the recipient Azure AD group attribute value.	
recipient-domain <string>	Domain part of recipient email address.	
recipient-email-group <group_name>	<b>Note:</b> This option is only available when recipient-type is set to email-group. Select an email group.	
recipient-ldap-profile <profile_name>	<b>Note:</b> This option is only available when recipient-type is set to ldap-group. Select an LDAP group profile.	
recipient-name <string>	<b>Note:</b> This option is only available when recipient-type is set to wildcard. Local part of recipient email address.	
recipient-pattern-regex <string>	<b>Note:</b> This option is only available when recipient-type is set to regex. Enter the sender email address regular expression pattern.	
recipient-type {ad-group   email-group   ldap-group   regex   wildcard}	Define the recipient as one of the following: <ul style="list-style-type: none"> <li>ad-group: Azure AD group.</li> <li>email-group: Email group.</li> <li>ldap-group: LDAP group.</li> <li>regex: User as regular expression.</li> <li>wildcard: User as wildcard.</li> </ul>	wildcard
sender-ad-group-attr {custom   displayname   mail}	<b>Note:</b> This option is only available when sender-type is set to ad-group. Select the sender Azure AD group attribute.	displayname
sender-ad-group-attr-name <string>	<b>Note:</b> This option is only available when sender-type is set to ad-group and sender-ad-group-attr is set to custom. Enter the custom sender Azure AD group attribute name.	
sender-ad-group-attr-value <string>	<b>Note:</b> This option is only available when sender-type is set to ad-group. Enter the sender Azure AD group attribute value.	
sender-domain <string>	Domain part of sender email address.	

Variable	Description	Default
sender-email-group <group_name>	<b>Note:</b> This option is only available when sender-type is set to email-group. Select an email group.	
sender-ldap-profile <profile_name>	<b>Note:</b> This option is only available when sender-type is set to ldap-group. Select an LDAP group profile.	
sender-name <string>	<b>Note:</b> This option is only available when sender-type is set to wildcard. Local part of sender email address.	
sender-pattern-regex <string>	<b>Note:</b> This option is only available when sender-type is set to regex. Enter the recipient email address regular expression pattern.	
sender-type {ad-group   email-group   external   internal   ldap-group   regex   wildcard}	Define the sender as one of the following: <ul style="list-style-type: none"> <li>ad-group: Azure AD group.</li> <li>email-group: Email group.</li> <li>external: External sender.</li> <li>internal: Internal sender.</li> <li>ldap-group: LDAP group.</li> <li>regex: User as regular expression.</li> <li>wildcard: User as wildcard.</li> </ul>	wildcard
source-ip-address <ipv4mask>	Client IP address and netmask.	0.0.0.0/0
source-type {geoip-group   ip-address   ip-group}	Define the source as either GeoIP group, IP address and netmask, or IP group.	ip-address
status {enable   disable}	Enable or disable the policy.	disable

## ms365 profile action

Use this command to apply specific actions the unit takes when encountering an infected email. The actions applied on Microsoft 365 are different from those applied on the FortiMail unit itself.

### Syntax

```
config ms365 profile action
edit <name>
set final-action {discard | move | none | quarantine | quarantine-review}
set move-to-folder-name <string>
set notification-profile <profile-name>
set notification-status {enable | disable}
set replace-message <string>
```

```

    set replace-status {enable | disable}
end

```

Variable	Description	Default
<name>	Enter the name of the action profile or create a new one.	
final-action {discard   move   none   quarantine   quarantine-review}	Enter one of the following final actions to perform on infected emails: <ul style="list-style-type: none"> <li>discard: Move the email message from the user's inbox to the Junk folder on Microsoft 365.</li> <li>move: Move the email message from the user's inbox to a specified folder on Microsoft 365. See <a href="#">move-to-folder-name &lt;string&gt;</a>.</li> <li>none: No action is taken.</li> <li>quarantine: Create a bulk folder for the user on Microsoft 365 and move the email message from the user's inbox to their Bulk folder.</li> <li>quarantine: Send a copy to the FortiMail system quarantine folder and move the email message from the user's inbox to the Deleted items folder in Microsoft 365.</li> </ul>	
move-to-folder-name <string>	Enter the name of the folder that the email messages should be moved to. Only applicable when final-action is set to move.	
notification-profile <profile-name>	Enter to send out notifications to the recipients specified in the notification profile.	
notification-status {enable   disable}	Enable or disable the notification.	disable
replace-message <string>	Enter the name of the custom message for content replacement.	default
replace-status {enable   disable}	Enable or disable the content replacement.	disable

## ms365 profile antispam

Use this command to configure the antispam profile for the administrator account of the Microsoft 365 domain.

See [profile antispam](#) for more details on commands and descriptions.

## ms365 profile antivirus

Use this command to create antivirus profiles that you can select in a policy in order to scan email for viruses for the administrator account of the Microsoft 365 domain.

See [profile antivirus](#) for more details on commands and descriptions.

## ms365 profile bec

Use this command to configure business email compromise (BEC) profile rules for the administrator account of the Microsoft 365 domain. To avoid false positives and false negatives, assign scores to adjust the weight allocated to each of the most common BEC attack types, such as cousin domains, suspicious characters, sender alignment, action keywords, and URL categories.

Once configured, BEC profiles are then used in antispam profiles.

### Syntax

```
config profile bec
  edit <name>
    config rule
      set comment <string>
      edit <order-integer>
        set action <datasource>
        set action-keyword-score <float>
        set cousin-domain-score <float>
        set malformed-email-score <float>
        set name <string>
        set sender-alignment-score <float>
        set status {enable | disable}
        set suspicious-character-score <float>
        set threshold <float>
        set url-profile <datasource>
        set url-profile-score <float>
      next
    end
  end
end
```

### Syntax

Variable	Description	Default
action <datasource>	Enter an antispam action profile name for the rule.	
action-keyword-score <float>	Enter a weight-adjusted score for actions keywords.	10.000000
cousin-domain-score <float>	Enter a weight-adjusted score for cousin domains.	10.000000
malformed-email-score <float>	Enter a weight-adjusted score for malformed emails. Malformed emails are those emails that contain malformed data in the email structure, header, or body. For more information, see <a href="#">RFC 7103</a> .	10.000000
name <string>	Enter a name for the rule.	

Variable	Description	Default
sender-alignment-score <float>	Enter a weight-adjusted score for sender alignment. Sender alignment checks for a Header From and Envelope From domain mismatch.	10.000000
status {enable   disable}	Enable or disable the profile rule.	enable
suspicious-character-score <float>	Enter a weight-adjusted score for suspicious characters.	10.000000
threshold <float>	Define the threshold at which point actions are taken. This score is allocated to the other categories.	50.000000
url-profile <datasource>	Enter a URL profile to assign to the URL category (url-profile-score).	unrated
url-profile-score <float>	Enter a weight-adjusted score for URL profiles that analyze any phishing URLs contained within emails.	10.000000

## ms365 profile content

Use this command to create content profiles, which you can use to match email based upon its subject line, message body, and attachments.

See [profile content](#) for more details on commands and descriptions.

## ms365 profile dlp

Use this command after you configure the scan rules/conditions. Add the scan rules/conditions to the DLP profiles. In the profiles, you also specify what actions to take. Then you apply the DLP profiles to the IP or recipient based policies.

See [profile dlp](#) for more details on commands and descriptions.

## ms365 setting

Use this command to configure real-time scan settings.

## Syntax

```

config ms365 setting
  set hide-email-on-arrival {enable | disable}
  set push-notification-url-base <string>
  set realtime-scan-log {all | on-policy-match}
  set realtime-scan-status {enable | disable}
  set service-endpoint {china | germany | global | us-dod | us-gov}
end

```

Variable	Description	Default
hide-email-on-arrival {enable   disable}	Enable or disable moving email to hidden folder on arrival for real-time scan. When enabled, this feature helps to avoid users opening potentially dangerous email before the FortiMail unit has had the opportunity to scan the email, especially if the email contains large attachments. After the email is scanned and deemed safe, it is then removed from the hidden folder and placed into the user's mailbox.	disable
push-notification-url-base <string>	Define the base URL to receive notifications.	
realtime-scan-log {all   on-policy-match}	Enter a realtime scan log option. When set to on-policy-match, Microsoft 365 History, Mail Event, Antivirus, and Antispam log entries will only be logged upon policy match.	on-policy-match
realtime-scan-status {enable   disable}	Enable or disable real-time scan.	disable
service-endpoint {china   germany   global   us-dod   us-gov}	Enter the appropriate geographical Microsoft 365 service endpoint.	global

## policy access-control receive

Use this command to configure access control rules that apply to SMTP sessions being **received** by the FortiMail unit.

Access control rules, sometimes also called the access control list or ACL, specify whether the FortiMail unit will process and relay/proxy, reject, or discard email messages for SMTP sessions that are initiated by SMTP clients.

When an SMTP client attempts to deliver email through the FortiMail unit, the FortiMail unit compares each access control rule to the commands used by the SMTP client during the SMTP session, such as the envelope's sender email

address (MAIL FROM:), recipient email address (RCPT TO:), authentication (AUTH), and TLS (STARTTLS). Rules are evaluated for a match in the order of their list sequence, from top to bottom. If all the attributes of a rule match, the FortiMail unit applies the action selected in the matching rule to the SMTP session, and no subsequent access control rules are applied.

**Only one access control rule is ever applied to any given SMTP session.**



If no access control rules are configured, or no matching access control rules exist, **and** if the SMTP client is not configured to authenticate, the FortiMail unit will perform the default action, which varies by whether or not the recipient email address in the envelope (RCPT TO:) is a member of a protected domain.

For protected domains, the default action is **RELAY**.

For **un**protected domains, the default action is **REJECT**.

Without any configured access control rules, the FortiMail unit's access control prevents SMTP clients from using your protected server or FortiMail unit as an open relay: senders can deliver email incoming to protected domains, but cannot deliver email outgoing to unprotected domains.

If you want to allow SMTP clients such as your email users or email servers to send email to unprotected domains, you must configure at least one access control rule.

You may need to configure additional access control rules if, for example, you want to:

- discard or reject email from or to some email addresses, such as email addresses that no longer exist in your protected domain
- discard or reject email from some SMTP clients, such as a spammer that is not yet known to blocklists

Like IP-based policies, access control rules can reject connections based upon IP address.

Unlike IP-based policies, however, access control rules **cannot** affect email in ways that occur after the session's DATA command, such as by applying antispam profiles. Access control rules also cannot be overruled by recipient-based policies, and cannot match connections based upon the IP address of the SMTP server (by the nature of how the ACL controls access to or through the FortiMail unit, the SMTP server is always the FortiMail unit itself, **unless** the FortiMail unit is operating in transparent mode). For more information on IP-based policies, see the [FortiMail Administration Guide](#).

## Syntax

```
config policy access-control receive
  edit <rule_id>
    set action {bypass | discard | reject | relay}
    set authenticated {any | authenticated | not-authenticated}
    set comment <string>
    set recipient-pattern <pattern_str>
    set recipient-pattern-type {default | group | regexp}
    set recipient-pattern-regexp {yes | no}
    set recipient-pattern-group <group_name>
    set reverse-dns-pattern <pattern_str>
    set reverse-dns-pattern-regexp {yes | no}
    set sender-ip-group <ip_group_name>
    set sender-ip-mask <ip&netmask_str>
    set sender-ip-type {ip-group | ip-mask}
```

```

set sender-pattern <pattern_str>
set sender-pattern-type {default | group | regexp}
set sender-pattern-group <group_name>
set sender-pattern-regexp {yes | no}
set status {enable | disable}
set tls-profile <profile_str>
end

```

Variable	Description	Default
<rule_id>	Enter the number identifying the rule.	
action {bypass   discard   reject   relay}	<p>Enter the action the FortiMail unit will perform for SMTP sessions matching this access control rule.</p> <ul style="list-style-type: none"> <li>reject: Reject delivery of the email (SMTP reply code 550 Relaying denied).</li> <li>discard: Accept the email (SMTP reply code 250 OK), but then silently delete it and do not deliver it.</li> <li>relay: Accept the email (SMTP reply code 250 OK), regardless of authentication or protected domain. <b>Do not greylist</b>, but continue with remaining antispam and other scans.</li> <li>safe: Accept the email (SMTP reply code 250 OK) if the sender authenticates or recipient belongs to a protected domain. <b>Greylist</b>, but skip remaining antispam scans. Continue other scans such as antivirus.</li> </ul> <p>Otherwise, if the sender does not authenticate, or the recipient does not belong to a protected domain, then reject delivery of the email (SMTP reply code 554 5.7.1 Relaying denied).</p> <p>In older FortiMail versions, this setting was named bypass.</p> <ul style="list-style-type: none"> <li>safe-relay: Like relay, <b>do not greylist</b>, but also skip remaining antispam scans.</li> <li>receive: Like relay, but <b>greylist</b>, and require authentication or protected domain.</li> </ul> <p>Otherwise, if the sender does not authenticate or the recipient does not belong to a protected domain, then FortiMail rejects (SMTP reply code 554 5.7.1 Relaying denied).</p> <p><b>Tip:</b> receive is usually used when you need to apply a TLS profile, but do not want to safelist nor allow outbound, which relay does. If you do <b>not</b> need to apply a TLS profile, then a policy with this action is often not required because by default, email inbound to protected domains is relayed/proxied.</p>	relay
authenticated {any   authenticated   not-authenticated}	<p>Enter a value to indicate whether this rule applies only to messages delivered by clients that have authenticated with the FortiMail unit.</p> <p>any: Match or do not match this access control rule regardless of whether the client has authenticated with the FortiMail unit.</p> <p>authenticated: Match this access control rule only for clients that have authenticated with the FortiMail unit.</p> <p>not-authenticated: Match this access control rule only for clients that have <b>not</b> authenticated with the FortiMail unit.</p>	authenticated

Variable	Description	Default
comment <string>	Enter any comments for access control rules for receiving email.	
recipient-pattern <pattern_str>	Enter a pattern that defines recipient email addresses which match this rule, surrounded in slashes and single quotes (such as \'*\').	*
recipient-pattern-type {default   group   regexp}	Enter the pattern type. default: This is the user defined pattern. Also configure <code>recipient-pattern &lt;pattern_str&gt;</code> . group: If you enter this option, configure <code>recipient-pattern-group &lt;group_name&gt;</code> . regexp: If you enter this option, configure <code>recipient-pattern-regexp {yes   no}</code> .	default
recipient-pattern-regexp {yes   no}	Enter yes to use regular expression syntax instead of wildcards to specify the recipient pattern. This option is available only when <code>recipient-pattern-type {default   group   regexp}</code> is <code>regexp</code> .	no
recipient-pattern-group <group_name>	Enter the group name to specify the recipient pattern. This option is available only when <code>recipient-pattern-type {default   group   regexp}</code> is <code>group</code> .	
reverse-dns-pattern <pattern_str>	Enter a pattern to compare to the result of a reverse DNS look-up of the IP address of the SMTP client delivering the email message. Because domain names in the SMTP session are self-reported by the connecting SMTP server and easy to fake, the FortiMail unit does not trust the domain name that an SMTP server reports. Instead, the FortiMail does a DNS lookup using the SMTP server's IP address. The resulting domain name is compared to the reverse DNS pattern for a match. If the reverse DNS query fails, the access control rule match will also fail. If no other access control rule matches, the connection will be rejected with SMTP reply code 550 (Relaying denied). Wildcard characters allow you to enter partial patterns that can match multiple reverse DNS lookup results. An asterisk (*) represents one or more characters; a question mark (?) represents any single character. For example, the recipient pattern <code>mail*.com</code> will match messages delivered by an SMTP server whose domain name starts with "mail" and ends with ".com". Note: Reverse DNS queries for access control rules require that the domain name be a valid top level domain (TLD). For example, ".lab" is not a valid top level domain name, and thus the FortiMail unit cannot successfully perform a reverse DNS query for it.	*
reverse-dns-pattern-regexp {yes   no}	Enter yes to use regular expression syntax instead of wildcards to specify the reverse DNS pattern.	no
sender-ip-group <ip_group_name>	Enter the IP group of the SMTP client attempting to deliver the email message.	

Variable	Description	Default
	This option only appears if you enter ip-group in <code>sender-ip-type {ip-group   ip-mask}</code> .	
sender-ip-mask <ip&netmask_str>	Enter the IP address and netmask of the SMTP client attempting to deliver the email message. Use the netmask, the portion after the slash (/), to specify the matching subnet.  For example, enter <code>10.10.10.10/24</code> to match a 24-bit subnet, or all addresses starting with 10.10.10. This will appear as <b>10.10.10.0/24</b> in the access control rule table, with the 0 indicating that any value is matched in that position of the address.  Similarly, <code>10.10.10.10/32</code> will appear as 10.10.10.10/32 and match only the 10.10.10.10 address.  To match any address, enter <code>0.0.0.0/0</code> .	0.0.0.0 0.0.0.0
sender-ip-type {ip-group   ip-mask}	Select the method of the SMTP client attempting to deliver the email message. Also configure <code>sender-ip-mask &lt;ip&amp;netmask_str&gt;</code> and <code>sender-ip-group &lt;ip_group_name&gt;</code> .	ip-mask
sender-pattern <pattern_str>	Enter a pattern that defines sender email addresses which match this rule, surrounded in slashes and single quotes (such as <code>'*\'</code> ).  This option is only available if you enter default in <code>sender-pattern-type {default   group   regexp}</code> .	*
sender-pattern-type {default   group   regexp}	Enter the pattern type.  default: This is the user defined pattern. Also configure <code>sender-pattern &lt;pattern_str&gt;</code> .  group: If you enter this option, configure <code>sender-pattern-group &lt;group_name&gt;</code> .  regexp: If you enter this option, configure <code>sender-pattern-regexp {yes   no}</code> .	default
sender-pattern-group <group_name>	Enter the group name to match any email address in the group.  This option is only available if you enter group in <code>sender-pattern-type {default   group   regexp}</code> .	
sender-pattern-regexp {yes   no}	Enter yes to use regular expression syntax instead of wildcards to specify the sender pattern.  This option is only available if you enter regexp in <code>sender-pattern-type {default   group   regexp}</code> .	no
status {enable   disable}	Enter enable to activate this rule.	enable
tls-profile <profile_str>	Enter a TLS profile to allow or reject the connection based on whether the communication session attributes match the settings in the TLS profile.  If the attributes match, the access control action is executed.  If the attributes do <b>not</b> match, the FortiMail unit performs the <b>Failure</b> action configured in the TLS profile.  For more information on TLS profiles, see the <a href="#">FortiMail Administration Guide</a> .	

## Related topics

[policy access-control delivery on page 166](#)

[config policy delivery-control on page 168](#)

[policy recipient on page 171](#)

## policy access-control delivery

Use this command to configure delivery rules that apply to SMTP sessions being **initiated** by the FortiMail unit in order to deliver email.

Delivery rules enable you to require TLS for the SMTP sessions the FortiMail unit initiates when sending email to other email servers. They also enable you to apply identity-based encryption (IBE) in the form of secure MIME (S/MIME).

When initiating an SMTP session, the FortiMail unit compares each delivery rule to the domain name portion of the envelope recipient address (RCPT TO:), and to the IP address of the SMTP server receiving the connection. Rules are evaluated for a match in the order of their list sequence, from top to bottom. If a matching delivery rule does not exist, the email message is delivered. If a match is found, the FortiMail unit compares the TLS profile settings to the connection attributes and the email message is sent or the connection is not allowed, depending on the result; if an encryption profile is selected, its settings are applied. No subsequent delivery rules are applied. Only one delivery rule is ever applied to any given SMTP session.

## Syntax

```
config policy access-control delivery
  edit <rule_id>
    set comment <string>
    set destination <ip&netmask_str>
    set encryption-profile <profile_str>
    set ip-pool-profile
    set recipient-pattern <pattern_str>
    set sender-pattern <pattern_str>
    set status {enable | disable}
    set tls-profile <profile_str>
  end
```

Variable	Description	Default
<rule_id>	Enter the number identifying the rule.	
comment <string>	Enter any comments for email delivery rules.	
destination <ip&netmask_str>	Enter the IP address and netmask of the system to which the FortiMail unit is sending the email message. Use the netmask, the portion after the slash (/) to specify the matching subnet.	0.0.0.0 0.0.0.0

Variable	Description	Default
	<p>For example, enter <code>10.10.10.10/24</code> to match a 24-bit subnet, or all addresses starting with 10.10.10. This will appear as <b>10.10.10.0/24</b> in the access control rule table, with the 0 indicating that any value is matched in that position of the address.</p> <p>Similarly, <code>10.10.10.10/32</code> will appear as <b>10.10.10.10/32</b> and match only the 10.10.10.10 address.</p> <p>To match any address, enter <code>0.0.0.0/0</code>.</p>	
encryption-profile <profile_str>	<p>Enter an encryption profile to apply identity-based encryption, if a corresponding sender identity exists in the certificate bindings.</p> <p>For more information on encryption profiles, see the <a href="#">FortiMail Administration Guide</a>.</p>	
ip-pool-profile	<p>Enter the name of the IP pool profile.</p> <p>The IP pool profile will deliver incoming emails from FortiMail to the protected server.</p>	
recipient-pattern <pattern_str>	<p>Enter a complete or partial envelope recipient (RCPT TO:) email address to match.</p> <p>Wild card characters allow you to enter partial patterns that can match multiple recipient email addresses. The asterisk (*) represents one or more characters and the question mark (?) represents any single character.</p> <p>For example, the recipient pattern <code>*@example.???</code> will match messages sent to any email user at example.com, example.net, example.org, or any other "example" domain ending with a three-letter top-level domain name.</p>	
recipient-pattern-type	Enter the type of recipient pattern.	
sender-pattern <pattern_str>	<p>Enter a complete or partial envelope sender (MAIL FROM:) email address to match.</p> <p>Wild card characters allow you to enter partial patterns that can match multiple sender email addresses. The asterisk (*) represents one or more characters and the question mark (?) represents any single character.</p> <p>For example, the sender pattern <code>??@*.com</code> will match messages sent by any email user with a two letter email user name from any ".com" domain name.</p>	
sender-pattern-type	Enter the type of the sender-pattern.	
status {enable   disable}	Enter enable to activate this rule.	disable
tls-profile <profile_str>	<p>Enter a TLS profile to allow or reject the connection based on whether the communication session attributes match the settings in the TLS profile.</p> <p>If the attributes match, the access control action is executed.</p> <p>If the attributes do <b>not</b> match, the FortiMail unit performs the <b>Failure</b> action configured in the TLS profile.</p> <p>For more information on TLS profiles, see the <a href="#">FortiMail Administration Guide</a>.</p>	

## Related topics

[ms365 profile antivirus on page 158](#)

[config policy delivery-control on page 168](#)

[policy recipient on page 171](#)

## policy delivery-control

Use this command to configure email delivery control options.

### Syntax

```
config policy delivery-control
  edit <delivery rule id>
    set max-concurrent-connection on page 168
    set max-messages-per-connection on page 168
    set max-recipients-per-message
    set max-recipients-per-period on page 168
    set recipient-domain on page 168
    set status {enable | disable} on page 168
  end
```

Variable	Description	Default
max-concurrent-connection	Enter the maximum concurrent SMTP connections (0 to disable).	
max-messages-per-connection	Enter the maximum messages per SMTP connection (0 to disable).	
max-recipients-per-message	Enter the maximum recipients per message (0 to disable). The valid range is 0-1000.	100
max-recipients-per-period	Enter the maximum recipients per period (0 to disable).	
recipient-domain	Enter the recipient domain.	
status {enable   disable}	Enable the rule.	
file_name <file_str>	Enter the name of the language resource file, such as 'custom_french1'.	

## policy ip

Use this command to create policies that apply profiles to SMTP connections based upon the IP addresses of SMTP clients and/or servers.

### Syntax

```
config policy ip
edit <policy_int>
set action {proxy-bypass | reject | scan | temp-fail}
set client-ip-group <group_name>
set client <client_ipv4mask>
set client-type {ip-address | ip-group | ip-pool}
set comment
set exclusive {enable | disable}
set profile-antispam <antispam-profile_name>
set profile-antivirus <antivirus-profile_name>
set profile-auth-type {imap | ldap | none | pop3 | radius | smtp}
set profile-content <content-profile_name>
set profile-dlp
set profile-ip-pool <ip-pool_name>
set profile-session <session-profile_name>
set server-ip-group <group_name>
set server <smtp-server_ipv4mask>
set server-ip-pool <ip-pool_str>
set server-type {ip-address | ip-group | ip-pool}
set smtp-diff-identity {enable | disable}
set smtp-diff-identity-ldap
set smtp-diff-identity-ldap-profile
set status {enable | disable}
set use-for-smtp-auth {enable | disable}
end
```

Variable	Description	Default
<policy_int>	Enter the index number of the IP-based policy.	
action {proxy-bypass   reject   scan   temp-fail}	Enter an action for this policy: Proxy-bypass: Bypass the FortiMail unit's scanning. This action is for transparent mode only. scan: Accept the connection and perform any scans configured in the profiles selected in this policy. reject: Reject the email and respond to the SMTP client with SMTP reply code 550, indicating a permanent failure. Fail Temporarily: Reject the email and respond to the SMTP client with SMTP reply code 451, indicating and indicate a temporary failure.	scan
client-ip-group <group_name>	Enter the IP group of the SMTP client to whose connections this policy will apply.	

Variable	Description	Default
	This option only appears if you enter <code>ip-group</code> in <code>client-type {ip-address   ip-group   ip-pool}</code> .	
<code>client &lt;client_ip&gt;</code> <code>client_ipv4mask &lt;ipv4mask&gt;</code>	Enter the IP address and subnet mask of the SMTP client to whose connections this policy will apply. To match all clients, enter <code>0.0.0.0/0</code> .	192.168.224.15 255.255.255.255
<code>client-type {ip-address   ip-group   ip-pool}</code>	Enter the client type.	ip-address
<code>comment &lt;comment&gt;</code>	Enter a brief comment for the IP policy.	
<code>exclusive {enable   disable}</code>	Enable to omit evaluation of matches with recipient-based policies, causing the FortiMail unit to disregard applicable recipient-based policies and apply only the IP-based policy. Disable to apply any matching recipient-based policy in addition to the IP-based policy. Any profiles selected in the recipient-based policy will override those selected in the IP-based policy.	disable
<code>profile-antispam &lt;antispam-profile_name&gt;</code>	Enter the name of an outgoing antispam profile, if any, that this policy will apply.	
<code>profile-antivirus &lt;antivirus-profile_name&gt;</code>	Enter the name of an antivirus profile, if any, that this policy will apply.	
<code>profile-auth-type {imap   ldap   none   pop3   radius   smtp}</code>	Enter the type of the authentication profile that this policy will apply. The command <code>profile-auth-&lt;auth_type&gt;</code> appears for the type chosen. Enter the name of an authentication profile for the type.	none
<code>profile-content &lt;content-profile_name&gt;</code>	Enter the name of the content profile that you want to apply to connections matching the policy.	
<code>profile-dlp &lt;dlp-profile_name&gt;</code>	Enter the name of the DLP profile for this policy.	
<code>profile-ip-pool &lt;ip-pool_name&gt;</code>	Enter the name of the IP pool profile that you want to apply to connections matching the policy.	
<code>profile-session &lt;session-profile_name&gt;</code>	Enter the name of the session profile that you want to apply to connections matching the policy.	
<code>server-ip-group &lt;group_name&gt;</code>	Enter the name of the IP group profile that you want to apply to connections matching the policy. This option is only available when the <code>server-type</code> is <code>ip-group</code> .	
<code>server &lt;smtp-server_ip&gt;</code> <code>server_ipv4mask &lt;ipv4mask&gt;</code>	Enter the IP address and subnet mask of the SMTP server to whose connections this policy will apply. To match all servers, enter <code>0.0.0.0/0</code> .	0.0.0.0 0.0.0.0

Variable	Description	Default
	This option applies only for FortiMail units operating in transparent mode. For other modes, the FortiMail unit receives the SMTP connection, and therefore acts as the server.	
server-ip-pool <ip-pool_str>	Enter the name of the ip pool to whose connections this policy will apply. This option is only available when the server-type is ip-pool.	
server-type {ip-address   ip-group   ip-pool}	Enter the SMTP server type o whose connections this policy will apply. Also configure <code>server &lt;smtp-server_ipv4mask&gt;</code> , <code>server-ip-group &lt;group_name&gt;</code> , and <code>server-ip-pool &lt;ip-pool_str&gt;</code> .	ip-address
smtp-diff-identity {enable   disable}	Enable to allow the SMTP client to send email using a different sender email address (MAIL FROM:) than the user name that they used to authenticate.  Disable to require that the sender email address in the SMTP envelope match the authenticated user name.	disable
smtp-diff-identity-ldap	Verify SMTP sender identity with LDAP for authenticated email.	disable
smtp-diff-identity-ldap-profile	LDAP profile for SMTP sender identity verification.	disable
status {enable   disable}	Enable to apply this policy.	enable
use-for-smtp-auth {enable   disable}	Enable to authenticate SMTP connections using the authentication profile configured in <code>sensitive-data {...}</code> .	disable

## Related topics

[ms365 profile antivirus on page 158](#)

[policy access-control delivery on page 166](#)

[policy recipient on page 171](#)

## policy recipient

Use this command to create recipient-based policies based on the inbound or outbound directionality of an email message with respect to the protected domain.

## Syntax

```
config policy recipient
edit <policy_int>
set auth-access-options {pop3 | smtp-auth | smtp-diff-identity | web}
set certificate-required {yes | no}
```

```

set comment <comment>
set direction {incoming | outgoing}
set pkiauth {enable | disable}
set pkiuser <user_str>
set profile-antispam <antispam-profile_name>
set profile-antivirus <antivirus-profile_name>
set profile-auth-type {imap | ldap | none | pop3 | radius | smtp}
set profile-content <content-profile_name>
set profile-dlp <profile_name>
set profile-ldap-recipient <ldap-profile_name>
set profile-ldap-sender <ldap-profile_name>
set profile-resource <profile_name>
set recipient-domain <domain_str>
set recipient-name <local-part_str>
set recipient-pattern-regex <string>
set recipient-type {email-address-group | ldap-group | regexp | user}
set sender-domain <domain_str>
set sender-name <local-part_str>
set sender-pattern-regex <string>
set sender-type {email-address-group | ldap-group | regexp | user}
set smtp-diff-identity {enable | disable}
set smtp-diff-identity-ldap {enable | disable}
set smtp-diff-identity-ldap-profile <profile_name>
set status {enable | disable}
end

```

Variable	Description	Default
<policy_int>	Enter the index number of the recipient-based policy.	
auth-access-options {pop3   smtp-auth   smtp-diff-identity   web}	<p>Enter the method that email users matching this policy use to retrieve the contents of their per-recipient spam quarantine.</p> <p>pop3: Allow the email user to use POP3 to retrieve the contents of their per-recipient spam quarantine.</p> <p>smtp-auth: Use the authentication server selected in the authentication profile when performing SMTP authentication for connecting SMTP clients.</p> <p>smtp-diff-identity: Allow email when the SMTP client authenticates with a different user name than the one that appears in the envelope's sender email address. You must also enter smtp-auth for this option to have any effect.</p> <p>web: Allow the email user to use FortiMail webmail (HTTP or HTTPS) to retrieve the contents of their per-recipient spam quarantine.</p> <p><b>Note:</b> Entering this option allows, but does not require, SMTP authentication. To enforce SMTP authentication for connecting SMTP clients, ensure that all access control rules require authentication.</p>	
certificate-required {yes   no}	If the email user's web browser does not provide a valid personal certificate, the FortiMail unit will fall back to standard user name and password-style authentication. To require valid certificates only and disallow password-style fallback, enter yes.	no
comment <comment>	Optionally, enter a comment for the recipient policy.	

Variable	Description	Default
direction {incoming   outgoing}	Select the mail traffic direction.	incoming
pkiauth {enable   disable}	Enable if you want to allow email users to log in to their per-recipient spam quarantine by presenting a certificate rather than a user name and password.	disable
pkiauser <user_str>	If pkiauth is enable, enter the name of a PKI user, such as 'user1'. For information on configuring PKI users, see <a href="#">user pki on page 347</a> .	
profile-antispam <antispam-profile_name>	Enter the name of an antispam profile, if any, that this policy will apply.	
profile-antivirus <antivirus-profile_name>	Enter the name of an antivirus profile, if any, that this policy will apply.	
profile-auth-type {imap   ldap   none   pop3   radius   smtp}	Enter the type of the authentication profile that this policy will apply. The command profile-auth-<auth_type> appears for the type chosen. Enter the name of an authentication profile for the type.	none
profile-dlp <profile_name>	Enter the name of the DLP profile that you want to apply to connections matching the policy.	
profile-content <content-profile_name>	Enter the name of the content profile that you want to apply to connections matching the policy.	
profile-resource <profile_name>	Enter the name of the resource profile that you want to apply to connections matching the policy.	
profile-ldap-recipient <ldap-profile_name>	If recipient-type is ldap-group, enter the name of an LDAP profile in which the group owner query has been enabled and configured.	
profile-ldap-sender <ldap-profile_name>	If sender-type is ldap-group, enter the name of an LDAP profile in which the group owner query has been enabled and configured.	
recipient-domain <domain_str>	Enter the domain part of recipient email address to define recipient (RCPT TO:) email addresses that match this policy.	
recipient-name <local-part_str>	Enter the local part of recipient email address to define recipient (RCPT TO:) email addresses that match this policy.	
recipient-pattern-regex <string>	Define the recipient email address regular expression pattern. This option is only available when recipient-type is set to regexp.	.*
recipient-type {email-address-group   ldap-group   regexp   user}	Enter one of the following ways to define recipient (RCPT TO:) email addresses that match this policy. If you enter ldap-group, also configure profile-ldap by entering an LDAP profile in which you have enabled and configured a group query.	user
sender-pattern-regex <string>	Define the sender email address regular expression pattern. This option is only available when sender-type is set to regexp.	.*

Variable	Description	Default
sender-domain <domain_str>	Enter the domain part of sender email address to define sender (MAIL FROM:) email addresses that match this policy.	
sender-name <local-part_str>	Enter the local part of sender email address to define sender (MAIL FROM:) email addresses that match this policy.	
sender-type {email-address-group   ldap-group   regexp   user}	Enter one of the following ways to define sender (MAIL FROM:) email addresses that match this policy. If you enter <code>ldap-group</code> , also configure <code>profile-ldap</code> <code>profile-ldap</code> by entering an LDAP profile in which you have enabled and configured a group query.	user
smtp-diff-identity {enable   disable}	Enable to allow the SMTP client to send email using a different sender email address (MAIL FROM:) than the user name that they used to authenticate. Disable to require that the sender email address in the SMTP envelope match the authenticated user name. This option is applicable only if <code>smtp auth</code> is used.	enable
smtp-diff-identity-ldap {enable   disable}	Enable to allow the SMTP client to verify SMTP sender identity with LDAP for authenticated email. This option is applicable only if <code>smtp auth</code> is used.	disable
smtp-diff-identity-ldap-profile <profile_name>	Enter the LDAP profile name for SMTP sender identity verification. This option is applicable only if <code>smtp auth</code> is used.	
status {enable   disable}	Enable to apply this policy.	enable

## Related topics

[ms365 profile antivirus on page 158](#)

[policy access-control delivery on page 166](#)

[config policy delivery-control on page 168](#)

## profile access-control

Use this command to configure access control rules.



Note that all access control rules operate at the system level. Only system level profiles (for example, email groups) can be used by access control rules.

## Syntax

```

config profile access-control
  edit <profile_name>
    config access-control
      edit <id>
        set action {discard | receive | reject | relay | safe | safe-relay}
        set authenticated {any | authenticated | not-authenticated}
        set recipient-pattern <string>
        set recipient-pattern-ldap-groupname <group_name>
        set recipient-pattern-ldap-profile <profile_name>
        set recipient-pattern-group <group_name>
        set recipient-pattern-type {default | external | group | internal | ldap | ldap-query |
          regexp}
        set reverse-dns-pattern <string>
        set reverse-dns-pattern-regexp {yes | no}
        set sender-ip-mask <ipv4mask>
        set sender-ip-type {geoip-group | ip-group | ip-mask}
        set sender-pattern <string>
        set sender-pattern-group <group_name>
        set sender-pattern-ldap-groupname <group_name>
        set sender-pattern-ldap-profile <profile_name>
        set sender-pattern-type {default | external | group | internal | ldap | ldap-query |
          regexp}
        set status {enable | disable}
        set tls-profile <profile_name>
      end
    end
  end
end

```

Variable	Description	Default
action {discard   receive   reject   relay   safe   safe-relay}	<p>Enter an action for the profile:</p> <ul style="list-style-type: none"> <li>reject: Reject delivery of the email (SMTP reply code 550 Relaying denied).</li> <li>discard: Accept the email (SMTP reply code 250 OK), but then silently delete it and do not deliver it.</li> <li>relay: Accept the email (SMTP reply code 250 OK), regardless of authentication or protected domain. <b>Do not greylist</b>, but continue with remaining antispam and other scans.</li> <li>safe: Accept the email (SMTP reply code 250 OK) if the sender authenticates or recipient belongs to a protected domain. <b>Greylist</b>, but skip remaining antispam scans. Continue other scans such as antivirus. Otherwise, if the sender does not authenticate, or the recipient does not belong to a protected domain, then reject delivery of the email (SMTP reply code 554 5.7.1 Relaying denied). In older FortiMail versions, this setting was named bypass.</li> <li>safe-relay: Like relay, <b>do not greylist</b>, but also skip remaining antispam scans.</li> <li>receive: Like relay, but <b>greylist</b>, and require authentication or protected domain. Otherwise, if the sender does not authenticate or the recipient does not</li> </ul>	reject

Variable	Description	Default
	<p>belong to a protected domain, then FortiMail rejects (SMTP reply code 554 5.7.1 Relaying denied).</p> <p><b>Tip:</b> receive is usually used when you need to apply a TLS profile, but do not want to safelist nor allow outbound, which relay does. If you do <b>not</b> need to apply a TLS profile, then a policy with this action is often not required because by default, email inbound to protected domains is relayed/proxied.</p>	
authenticated {any   authenticated   not-authenticated}	<p>Enter whether or not to match this access control rule based on client authentication:</p> <ul style="list-style-type: none"> <li>any: Match or do not match this access control rule regardless of whether the client has authenticated with the FortiMail unit.</li> <li>authenticated: Match this access control rule only for clients that have authenticated with the FortiMail unit.</li> <li>not-authenticated: Match this access control rule only for clients that have not authenticated with the FortiMail unit.</li> </ul>	any
recipient-pattern <string>	Enter a pattern that defines recipient email addresses which match this rule, surrounded in slashes and single quotes (such as \'*\').	*
recipient-pattern-ldap-groupname <group_name>	Enter the LDAP group name to specify the recipient pattern. This option is only available when recipient-pattern-type is set to ldap.	
recipient-pattern-ldap-profile <profile_name>	Enter the LDAP profile name to specify the recipient pattern. This option is only available when recipient-pattern-type is set to either ldap or ldap-query.	
recipient-pattern-group <group_name>	Enter the group name to specify the recipient pattern. This option is only available when recipient-pattern-type is set to group.	
recipient-pattern-type {default   external   group   internal   ldap   ldap-query   regexp}	<p>Enter the pattern type:</p> <ul style="list-style-type: none"> <li>default: This is the user defined pattern. Also configure <a href="#">recipient-pattern &lt;string&gt;</a>.</li> <li>external: Set for external recipients.</li> <li>group: If you enter this option, configure <a href="#">recipient-pattern-group &lt;group_name&gt;</a>.</li> <li>internal: Set for internal recipients.</li> <li>ldap: If you enter this option, configure <a href="#">recipient-pattern-ldap-groupname &lt;group_name&gt;</a> and <a href="#">recipient-pattern-ldap-profile &lt;profile_name&gt;</a>.</li> <li>ldap-query: If you enter this option, configure <a href="#">recipient-pattern-ldap-profile &lt;profile_name&gt;</a>.</li> <li>regexp: Use regular expression syntax instead of wildcards for the pattern.</li> </ul>	default
reverse-dns-pattern <string>	Enter a pattern to compare to the result of a reverse DNS look-up of the IP address of the SMTP client delivering the email message.	*

Variable	Description	Default
	<p>Because domain names in the SMTP session are self-reported by the connecting SMTP server and easy to fake, the FortiMail unit does not trust the domain name that an SMTP server reports. Instead, the FortiMail does a DNS lookup using the SMTP server's IP address. The resulting domain name is compared to the reverse DNS pattern for a match. If the reverse DNS query fails, the access control rule match will also fail. If no other access control rule matches, the connection will be rejected with SMTP reply code 550 (Relaying denied).</p> <p>Wildcard characters allow you to enter partial patterns that can match multiple reverse DNS lookup results. An asterisk (*) represents one or more characters; a question mark (?) represents any single character.</p> <p>For example, the recipient pattern <code>mail*.com</code> will match messages delivered by an SMTP server whose domain name starts with "mail" and ends with ".com".</p> <p><b>Note:</b> Reverse DNS queries for access control rules require that the domain name be a valid top level domain (TLD). For example, ".lab" is not a valid top level domain name, and thus the FortiMail unit cannot successfully perform a reverse DNS query for it.</p>	
<code>reverse-dns-pattern-regexp</code> {yes   no}	Enter yes to use regular expression syntax instead of wildcards to specify the reverse DNS pattern.	no
<code>sender-ip-mask</code> <ipv4mask>	Enter the sender's IP address.	0.0.0.0/0
<code>sender-ip-type</code> {geoip-group   ip-group   ip-mask}	Select the method of the SMTP client attempting to deliver the email message.	ip-mask
<code>sender-pattern</code> <string>	Enter a pattern that defines sender email addresses which match this rule, surrounded in slashes and single quotes (such as <code>'*@example.com'</code> ).	
<code>sender-pattern-group</code> <group_name>	Enter the group name to specify the sender pattern. This option is only available when <code>sender-pattern-type</code> is set to <code>group</code> .	
<code>sender-pattern-ldap-groupname</code> <group_name>	Enter the LDAP group name to specify the sender pattern. This option is only available when <code>sender-pattern-type</code> is set to <code>ldap</code> .	
<code>sender-pattern-ldap-profile</code> <profile_name>	Enter the LDAP profile name to specify the sender pattern. This option is only available when <code>sender-pattern-type</code> is set to either <code>ldap</code> or <code>ldap-query</code> .	
<code>sender-pattern-type</code> {default   external   group   internal   ldap   ldap-query   regexp}	Enter the pattern type: <ul style="list-style-type: none"> <li><code>default</code>: This is the user defined pattern. Also configure <code>sender-pattern &lt;string&gt;</code>.</li> <li><code>external</code>: Set for external senders.</li> <li><code>group</code>: If you enter this option, configure <code>sender-pattern-group &lt;group_name&gt;</code>.</li> </ul>	default

Variable	Description	Default
	<ul style="list-style-type: none"> <li><code>internal</code>: Set for internal senders.</li> <li><code>ldap</code>: If you enter this option, configure <code>sender-pattern-ldap-groupname &lt;group_name&gt;</code> and <code>sender-pattern-ldap-profile &lt;profile_name&gt;</code>.</li> <li><code>ldap-query</code>: If you enter this option, configure <code>sender-pattern-ldap-profile &lt;profile_name&gt;</code>.</li> <li><code>regex</code>: Use regular expression syntax instead of wildcards for the pattern.</li> </ul>	
<code>status {enable   disable}</code>	Enable or disable the access control rule.	enable
<code>tls-profile &lt;profile_name&gt;</code>	<p>Enter a TLS profile to allow or reject the connection based on whether the communication session attributes match the settings in the TLS profile.</p> <p>If the attributes match, the access control action is executed.</p> <p>If the attributes do <b>not</b> match, the FortiMail unit performs the <b>Failure</b> action configured in the TLS profile.</p> <p>For more information on TLS profiles, see the <a href="#">FortiMail Administration Guide</a>.</p>	

## profile antispam

Use this command to configure system-wide antispam profiles.

FortiMail units can use various methods to detect spam, such as the FortiGuard Antispam service, DNSBL queries, Bayesian scanning, and heuristic scanning. Antispam profiles contain settings for these features that you may want to vary by policy. Depending on the feature, before you configure antispam policies, you may need to enable the feature or configure its system-wide settings.

## Syntax

```
config profile antispam
  edit <profile_name>
    config bannedwords
      edit <word_str>
        set subject {enable | disable}
        set body {enable | disable}
    config dnsbl-server
      edit <server_name>
    config safelistwords
      edit <word_str>
        set subject {enable | disable}
        set body {enable | disable}
    config surbl-server
      edit <server_name>
    set action-banned-word <action_profile>
    set action-bayesian <action_profile_name>
    set action-behavior-analysis <action_profile_name>
    set action-bec <action_profile_name>
```

```
set action-deep-header <action-profile_name>
set action-default <action-profile_name>
set action-dictionary <action-profile_name>
set action-dkim-fail <action-profile_name>
set action-dkim-none <action-profile_name>
set action-dkim-pass <action-profile_name>
set action-dkim-temp-error <action-profile_name>
set action-dmarc-fail <action-profile_name>
set action-dmarc-none <action-profile_name>
set action-dmarc-pass <action-profile_name>
set action-dmarc-temp-error <action-profile_name>
set action-fortiguard <action-profile_name>
set action-fortiguard-blockip <action-profile-name>
set action-fortiguard-phishing-url <action-profile-name>
set action-grey-list <action-profile_name>
set action-heuristic <action-profile_name>
set action-image-spam <action-profile_name>
set action-impersonation-analysis <action>
set action-ip-reputation-level1 <action-profile_name>
set action-ip-reputation-level2 <action-profile_name>
set action-ip-reputation-level3 <action-profile_name>
set action-newsletter <action-profile_name>
set action-rbl <action-profile_name>
set action-spf-fail <action>
set action-spf-neutral <action>
set action-spf-none <action>
set action-spf-pass <action>
set action-spf-perm-error <action>
set action-spf-sender-alignment <action>
set action-spf-soft-fail <action>
set action-spf-temp-error <action>
set action-surbl <action-profile_name>
set action-suspicious-newsletter <action-profile_name>
set action-url-filter <action-profile_name>
set action-url-filter-secondary <action-profile_name>
set action-virus <action-profile_name>
set aggressive {enable | disable}
set apply-action-default {enable | disable}
set banned-word {enable | disable}
set bayesian {enable | disable}
set behavior-analysis {enable | disable}
set bayesian-autotraining {enable | disable}
set bayesian-user-db {enable | disable}
set bayesian-usertraining {enable | disable}
set behavior-analysis {enable | disable}
set bec-profile <domain_name>
set bec-status {enable | disable}
set cousin-domain {enable | disable}
set cousin-domain-profile <domain_name>
set cousin-domain-scan-option {auto-detection body-detection header-detection}
set deepheader-analysis {enable | disable}
set deepheader-check-ip {enable | disable}
set dict-score <score_int>
set dictionary {enable | disable}
set dictionary-profile
set dictionary-type
set dkim-checking {enable | disable}
```

```

set dkim-fail-status {enable | disable}
set dkim-none-status {enable | disable}
set dkim-pass-status {enable | disable}
set dkim-temp-error-status {enable | disable}
set dmarc-checking {enable | disable}
set dmarc-fail-status {enable | disable}
set dmarc-none-status {enable | disable}
set dmarc-pass-status {enable | disable}
set dmarc-temp-error-status {enable | disable}
set dnsbl {enable | disable}
set fortiguard-antispam {enable | disable}
set fortiguard-check-ip {enable | disable}
set fortiguard-phishing-url {enable | disable}
set greylist {enable | disable}
set heuristic {enable | disable}
set heuristic-lower <threshold_int>
set heuristic-rules-percent <percentage_int>
set heuristic-upper {threshold_int}
set image-spam {enable | disable}
set impersonation <profile_name>
set impersonation-analysis {enable | disable}
set impersonation-status {enable | disable}
set ip-reputation-level1-status {enable | disable}
set ip-reputation-level2-status {enable | disable}
set ip-reputation-level3-status {enable | disable}
set newsletter-status {enable | disable}
set scan-bypass-on-auth {enable | disable}
set scan-max-size <bytes_int>
set scan-pdf {enable | disable}
set spam-outbreak-protection {enable | disable | monitor-only}
set spf-checking {enable | disable}
set spf-fail-status {enable | disable}
set spf-neutral-status {enable | disable}
set spf-none-status {enable | disable}
set spf-pass-status {enable | disable}
set spf-sender-alignment-status {enable | disable}
set spf-perm-error-status {enable | disable}
set spf-soft-fail-status {enable | disable}
set spf-temp-error-status {enable | disable}
set surbl {enable | disable}
set suspicious-newsletter-status {enable | disable}
set url-filter <filter>
set url-filter-secondary <filter>
set url-filter-secondary-status {enable | disable}
set url-filter-status {enable | disable}
set virus {enable | disable}
set safelist-enable {enable | disable}
set safelist-word {enable | disable}
end

```

Variable	Description	Default
<profile_name>	Enter the name of an antispam profile.	

Variable	Description	Default
<word_str>	Enter the banned word. You can use wildcards in banned words. But regular expressions are not supported. For more information about wildcards and regular expressions, see the <a href="#">FortiMail Administration Guide</a> .	
subject {enable   disable}	Enable to check the subject line for the banned word.	disable
body {enable   disable}	Enable to check the message body for the banned word.	disable
<server_name>	Enter a DNSBL server name to perform a DNSBL scan. The FortiMail unit will query DNS blocklist servers.	
<server_name>	Enter a SURBL server name to perform a SURBL scan. The FortiMail unit will query SURBL servers.	
<word_str>	Enter the safelisted word to configure.	
subject {enable   disable}	Enable to check the subject line for the safelisted word.	disable
body {enable   disable}	Enable to check the message body for the safelisted word.	disable
action-banned-word <action_profile>	Enter the action profile that you want the FortiMail unit to use if the banned word scan determines that the email is spam.	
action-bayesian <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the Bayesian scan determines that the email is spam.	
action-behavior-analysis <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the behavior analysis scan determines that the email is spam.	
action-bec <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the BEC check determines that the email is spam.	
action-deep-header <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the deep header scan determines that the email is spam.	
action-default <action-profile_name>	Enter the default action profile that you want all scanners of the FortiMail unit to use. However, if you choose an action profile other than "default" for a scanner, this scanner will use the chosen profile.	
action-dictionary <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the heuristic scan determines that the email is spam.	
action-dkim-fail <action-profile_name>	Enter the action profile that you want the FortiMail unit to use for DKIM check failure.	

Variable	Description	Default
action-dkim-none <action-profile_ name>	Enter the action profile that you want the FortiMail unit to use if no DKIM DNS record is not found or parsed correctly.	
action-dkim-pass <action-profile_ name>	Enter the action profile that you want the FortiMail unit to use for DKIM check pass.	
action-dkim-temp- error <action- profile_name>	Enter the action profile that you want the FortiMail unit to use if DNS server returns Temp error when querying the DKIM DNS record.	
action-dmarc-fail <action-profile_ name>	Enter the action profile that you want the FortiMail unit to use for DMARC check failure.	
action-dmarc- none <action- profile_name>	Enter the action profile that you want the FortiMail unit to use if no DMARC DNS record is not found or parsed correctly.	
action-dmarc-pass <action-profile_ name>	Enter the action profile that you want the FortiMail unit to use for DMARC check pass.	
action-dmarc- temp-error <action-profile_ name>	Enter the action profile that you want the FortiMail unit to use if DNS server returns Temp error when querying the DMARC DNS record.	
action-fortiguard <action-profile_ name>	Enter the action profile that you want the FortiMail unit to use if the FortiGuard Antispam scan determines that the email is spam.	
action-fortiguard- blockip <action- profile-name>	Enter the action profile that you want the FortiMail unit to use if the FortiGuard block IP scan determines that the email is spam.	
action-fortiguard- phishing-url <action-profile- name>	Enter the action profile that you want the FortiMail unit to use if the FortiGuard phishing URL scan determines that the email is spam.	
action-grey-list <action-profile_ name>	Enter the action profile that you want the FortiMail unit to use if the grey list scan determines that the email is spam.	
action-heuristic <action-profile_ name>	Enter the action profile that you want the FortiMail unit to use if the heuristic scan determines that the email is spam.	
action- impersonation- analysis <action>	Enter the action profile that you want the FortiMail unit to use if the impersonation analysis determines the email is from someone impersonating a known email address.	

Variable	Description	Default
action-image-spam <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the image scan determines that the email is spam.	
action-ip-reputation-level1 <action-profile_name>	Enter the action profile that you want assigned to IP reputation level 1. See <a href="#">set ip-reputation-level1-status {enable   disable}</a> for more information. FortiGuard categorizes the blocklisted IP addresses into three levels, level 1 has the worst reputation and level 3 the best.	
action-ip-reputation-level2 <action-profile_name>	Enter the action profile that you want assigned to IP reputation level 2. See <a href="#">set ip-reputation-level2-status {enable   disable}</a> for more information. FortiGuard categorizes the blocklisted IP addresses into three levels, level 1 has the worst reputation and level 3 the best.	
action-ip-reputation-level3 <action-profile_name>	Enter the action profile that you want assigned to IP reputation level 3. See <a href="#">set ip-reputation-level3-status {enable   disable}</a> for more information. FortiGuard categorizes the blocklisted IP addresses into three levels, level 1 has the worst reputation and level 3 the best.	
action-newsletter <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the newsletter scan determines that the email is spam.	
action-rbl <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the RBL scan determines that the email is spam.	
action-spf-fail <action>	Enter the action FortiMail performs if the SPF fails, which means the host is not authorized to send messages.	
action-spf-neutral <action>	Enter the action FortiMail performs if SPF neutral fails, which means the SPF record is found but no definitive assertion.	
action-spf-none <action>	Enter the action FortiMail performs if SPF none fails, whichs means there is no SPF record.	
action-spf-pass <action>	Enter the action FortiMail performs if SPF pass fails, which means it discovers the host is not authorized to send a message.	
action-spf-perm-error <action>	Enter the action FortiMail performs if SPF perm error fails, which means the SPF records are invalid.	
action-spf-sender-alignment <action>	Enter the action FortiMail performs if SPF sender alignment fails, which means the header from the subject authorization domain mismatch.	
action-spf-soft-fail <action>	Enter the action Fortimail takes if spf soft fail fails, which means the host is not authorized to send messages but not a strong statement.	
action-spf-temp-error <action>	Enter the action FortiMail performs if action SPF temp error fails, which means there is a processing error.	
action-surbl <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the SURBL scan determines that the email is spam.	

Variable	Description	Default
action-suspicious-newsletter <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the suspicious newsletter scan determines that the email is spam.	
action-url-filter <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the URL filter scan determines that the email is spam.	
action-url-filter-secondary <action-profile_name>	Enter the action profile that you want the FortiMail unit to use if the URL filter scan determines that the email is spam.	
action-virus <action-profile_name>	Enter the action profile that requires the FortiMail unit to treat messages with viruses as spam.	
aggressive {enable   disable}	Enable this option to examine file attachments in addition to embedded images.  To improve performance, enable this option only if you do not have a satisfactory spam detection rate.	disable
apply-action-default {enable   disable}	Enable this option to apply default action to all messages.	disable
banned-word {enable   disable}	Enable this option to scan banned words for this antispam profile.	disable
bayesian {enable   disable}	Enable this option to activate Bayesian scan for this antispam profile.	disable
behavior-analysis {enable   disable}	Enable this option to activate behavior analysis scan for this antispam profile.	disable
bayesian-autotraining {enable   disable}	Enable to use FortiGuard Antispam and SURBL scan results to train per-user Bayesian databases that are not yet mature (that is, they have not yet been trained with 200 legitimate email and 100 spam in order to recognize spam).	enable
bayesian-user-db {enable   disable}	Enable to use per-user Bayesian databases.  If disabled, the Bayesian scan will use either the global or the per-domain Bayesian database, whichever is selected for the protected domain.	disable
bayesian-usertraining {enable   disable}	Enable to accept email forwarded from email users to the Bayesian control email addresses in order to train the Bayesian databases to recognize spam and legitimate email.	enable
behavior-analysis {enable   disable}	Enable to analyze the similarities between uncertain email and known email in the behavior analysis (BA) database to determine whether the uncertain email is spam.  See also <a href="#">antispam behavior-analysis on page 42</a> to adjust the BA aggressiveness level.	disable

Variable	Description	Default
bec-profile <domain_name>	Enter the BEC profile used by this profile to prevent spam attacks.	
bec-status {enable   disable}	Enable the business email compromise (BEC) check.	
cousin-domain {enable   disable}	<b>Note:</b> For this subcommand to take effect, <code>impersonation-status</code> must be set to <code>enable</code> . Enable the cousin domain feature to mitigate business email compromise (BEC) email-impersonation risks due to domain names being deliberately misspelled.	disable
cousin-domain-profile <domain_name>	Enter the cousin domain profile used by this profile to prevent domain name impersonation.	
cousin-domain-scan-option {auto-detection body-detection header-detection}	Enter cousin domain scan options for detecting misspelled domain names either automatically, within the email body, and/or the email header. Separate each option with a space for multiple scan options.	header-detection body-detection auto-detection
deepheader-analysis {enable   disable}	Enable to inspect all message headers for known spam characteristics. If the FortiGuard Antispam scan is enabled, this option uses results from that scan, providing up-to-date header analysis. For more information, see <a href="#">"set as profile modify fortishield" on page 184</a> .	disable
deepheader-check-ip {enable   disable}	Enable to query for the blocklist status of the IP addresses of all SMTP servers appearing in the <code>Received:</code> lines of header lines. If this option is disabled, the FortiMail unit checks only the IP address of the current SMTP client. This option applies only if you have also configured either or both FortiGuard Antispam scan and DNSBL scan. For more information, see <a href="#">"set as profile modify fortishield" on page 184</a> and <a href="#">"set as profile modify dnsbl" on page 181</a> .	disable
dict-score <score_int>	Enter the number of dictionary term matches above which the email will be considered to be spam.	
dictionary {enable   disable}	Enable to perform a dictionary scan for this profile.	disable
dictionary-profile	Enter the dictionary profile name.	
dictionary-type	Enter the type of dictionary profile.	
dkim-checking {enable   disable}	Enable to have the unit perform email authentication with DKIM checking. If either SPF check or DKIM check passes, DMARC check will pass. If both fail, DMARC fails.	disable
dkim-fail-status {enable   disable}	Enable or disable checking invalid DKIM body hash or signature.	enable

Variable	Description	Default
dkim-none-status {enable   disable}	Enable or disable checking for instances where no DKIM DNS record is found, or the record could not be correctly parsed.	disable
dkim-pass-status {enable   disable}	Enable or disable DKIM check passing.	disable
dkim-temp-error-status {enable   disable}	Enable or disable checking for instances where DNS server returns Temp error when querying the DKIM DNS record.	disable
dmARC-checking {enable   disable}	Enable to have the unit perform email authentication with SPF and DKIM checking. If either SPF check or DKIM check passes, DMARC check will pass. If both fail, DMARC fails.	enable
dmARC-fail-status {enable   disable}	Enable or disable DMARC check failing.	enable
dmARC-none-status {enable   disable}	Enable or disable checking for instances where no DMARC DNS record is found, or the record could not be correctly parsed.	disable
dmARC-pass-status {enable   disable}	Enable or disable DMARC check passing.	disable
dmARC-temp-error-status {enable   disable}	Enable or disable checking for instances where DNS server returns Temp error when querying the DMARC DNS record.	disable
dnsbl {enable   disable}	Enable to perform a DNSBL scan for this profile. The FortiMail unit will query DNS blocklist servers defined using " <a href="#">set out_profile profile modify deepheader</a> " on page 405.	disable
fortiGuard-antispam {enable   disable}	Enable to let the FortiMail unit query the FortiGuard Antispam service to determine if any of the uniform resource identifiers (URL) in the message body are associated with spam. If any URL is blocklisted, the FortiMail unit considers the email to be spam, and you can select the action that the FortiMail unit will perform.	disable
fortiGuard-check-ip {enable   disable}	Enable to include whether or not the IP address of the SMTP client is blocklisted in the FortiGuard Antispam query.	disable
fortiGuard-phishing-url {enable   disable}	Enable to include whether or not the phishing URL is blocklisted in the FortiGuard Antispam query.	disable
greylist {enable   disable}	Enable to perform a greylist scan.	disable
heuristic {enable   disable}	Enable to perform a heuristic scan.	disable
heuristic-lower <threshold_int>	Enter the score equal to or below which the FortiMail unit considers an email to <b>not</b> be spam.	-20.000000

Variable	Description	Default
heuristic-rules-percent <percentage_int>	<p>Enter the percentage of the total number of heuristic rules that will be used to calculate the heuristic score for an email message.</p> <p>The FortiMail unit compares this total score to the upper and lower level threshold to determine if an email is:</p> <ul style="list-style-type: none"> <li>spam</li> <li>not spam</li> <li>indeterminable (score is between the upper and lower level thresholds)</li> </ul> <p>To improve system performance and resource efficiency, enter the lowest percentage of heuristic rules that results in a satisfactory spam detection rate.</p>	100
heuristic-upper {threshold_int}	Enter the score equal to or above which the FortiMail unit considers an email to be spam.	10.000000
image-spam {enable   disable}	Enable to perform an image spam scan.	disable
impersonation <profile_name>	Enter the impersonation profile used by this profile to prevent email spoofing attacks.	
impersonation-analysis {enable   disable}	<p><b>Note:</b> For this subcommand to take effect, <code>impersonation-status</code> must be set to <code>enable</code>.</p> <p>Enable sender impersonation analysis to automatically learn and track the mapping of display names and internal email addresses to prevent spoofing attacks.</p>	disable
impersonation-status {enable   disable}	<p>Enable the sender impersonation feature.</p> <p>Once enabled, <code>cousin-domain</code>, <code>impersonation-analysis</code>, and <code>spf-sender-alignment-status</code> can take effect.</p>	disable
ip-reputation-level1-status {enable   disable}	<p>Enable IP reputation to enable the FortiMail unit to query the FortiGuard Antispam service to determine if the public IP address of the SMTP client is blocklisted.</p> <p>FortiGuard categorizes the blocklisted IP addresses into three levels, level 1 has the worst reputation and level 3 the best.</p>	disable
ip-reputation-level2-status {enable   disable}	<p>Enable IP reputation to enable the FortiMail unit to query the FortiGuard Antispam service to determine if the public IP address of the SMTP client is blocklisted.</p> <p>FortiGuard categorizes the blocklisted IP addresses into three levels, level 1 has the worst reputation and level 3 the best.</p>	disable
ip-reputation-level3-status {enable   disable}	<p>Enable IP reputation to enable the FortiMail unit to query the FortiGuard Antispam service to determine if the public IP address of the SMTP client is blocklisted.</p> <p>FortiGuard categorizes the blocklisted IP addresses into three levels, level 1 has the worst reputation and level 3 the best.</p>	disable
newsletter-status {enable   disable}	Enable detection of newsletters to make sure newsletters and other marketing campaigns are not spam.	
spf-fail-status {enable   disable}	Enable to make the FortiMail unit check if the host is not authorized to send messages.	

Variable	Description	Default
	If the client IP address fails the SPF check, FortiMail takes the antispam action entered in <code>action-spf-fail</code> .	
<code>spf-neutral-status</code> {enable   disable}	Enable to make the FortiMail unit check if the SPF record is found but no definitive assertion. If the client IP address fails the SPF check, FortiMail takes the antispam action entered in <code>action-spf-neutral</code> .	
<code>spf-none-status</code> {enable   disable}	Enable to make the FortiMail unit check if there is no SPF record. If the client IP address fails the SPF check, FortiMail takes the antispam action entered in <code>action-spf-none</code> .	
<code>spf-pass-status</code> {enable   disable}	Enable to make the FortiMail unit check if the host is authorized to send messages. If the client IP address fails the SPF check, FortiMail takes the antispam action configured in <code>action-spf-pass</code> .	
<code>spf-sender-alignment-status</code> {enable   disable}	<b>Note:</b> For this subcommand to take effect, <code>impersonation-status</code> must be set to <code>enable</code> . Enable to make the FortiMail unit check if the header from the authorization domain is mismatched. If the client IP address fails the SPF check, FortiMail takes the desired action entered in <code>action-spf-sender-alignment</code> .	
<code>spf-perm-error-status</code> {enable   disable}	Enable to make the FortiMail unit check if the SPF records are invalid. If the client IP address fails the SPF check, FortiMail takes the antispam action entered in <code>action-spf-perm-error</code> .	
<code>spf-soft-fail-status</code> {enable   disable}	Enable to make the FortiMail unit check if the host is not authorized to send messages but not a strong statement. If the client IP address fails the SPF check, FortiMail takes the antispam action entered in <code>action-spf-soft-fail</code> .	
<code>spf-temp-error-status</code> {enable   disable}	Enable to make the FortiMail unit check if there is a processing error. If the client IP address fails the SPF check, FortiMail takes the antispam action entered in <code>action-spf-temp-error</code> .	
<code>scan-bypass-on-auth</code> {enable   disable}	Enable to omit antispam scans when an SMTP sender is authenticated.	disable
<code>scan-max-size</code> <bytes_int>	Enter the maximum size, in bytes, that the FortiMail unit will scan for spam. Messages exceeding the limit will not be scanned for spam. To scan all email regardless of size, enter 0.	1204 bytes for predefined profiles  600 bytes for user-defined profiles

Variable	Description	Default
scan-pdf {enable   disable}	Enable to scan the first page of PDF attachments using heuristic, banned word, and image spam scans, if they are enabled.	disable
spam-outbreak-protection {enable   disable   monitor-only}	<p>Enable to temporarily hold suspicious email for a certain period of time (configurable with <code>outbreak-protection-period</code> under config <a href="#">system fortiguard antispam on page 295</a>) if the enabled FortiGuard antispam check (block IP and/or URL filter) returns no result. After the specified time interval, FortiMail will query the FortiGuard server for the second time. This provides an opportunity for the FortiGuard antispam service to update its database in cases a spam outbreak occurs.</p> <p>When set to <code>monitor-only</code>, email is not deferred. Instead, "X-FEAS-Spam-outbreak: monitor-only" is inserted as its header, and the email is logged.</p>	disable
spf-checking {enable   disable}	<p>Enable to have the FortiMail unit perform the action configured in this antispam profile, instead of the action configured in the session profile. See <a href="#">spf-validation {enable   disable} on page 258</a>.</p> <p>Starting from 6.0.3 release, you can also specify different actions toward defferent SPS check results:</p> <ul style="list-style-type: none"> <li>• <b>spf-fail-status:</b> the host is not authorized to send messages.</li> <li>• <b>spf-soft-fail-status:</b> the host is not authorized to send messages but not a strong statement.</li> <li>• <b>spf-sender-alignment-status:</b> Header From and authorization domain mismatch.</li> <li>• <b>spf-perm-error-status:</b> the SPF records are invalid.</li> <li>• <b>spf-temp-error-status:</b> Temporary processing error.</li> <li>• <b>spf-pass-status:</b> the host is authorized to send messages.</li> <li>• <b>spf-neutral-status:</b> SPF record is found but no definitive assertion.</li> <li>• <b>spf-none-status:</b> No SPF record.</li> </ul>	disable
surbl {enable   disable}	Enable to perform a SURBL scan. The FortiMail unit will query SURBL servers defined using " <a href="#">set out_profile profile modify surblserver</a> " on page 421.	disable
suspicious-newsletter-status {enable   disable}	Enable the detection of newsletters.	disable
url-filter <filter>	Specify the URL filter to use.	
url-filter-secondary <filter>	To take different actions towards different URL filters/categories, you can specify a primary and a secondary filter, and specify different actions for each filter. If both URL filters match an email message, the primary filter action will take precedence.	
url-filter-secondary-status {enable   disable}	Enable or disable the secondaryURI filter scan.	disable
url-filter-status {enable   disable}	Enable or disable URL filter scan.	disable

Variable	Description	Default
virus {enable   disable}	Enable to treat email with viruses as spam. When enabled, instead of performing the action configured in the antivirus profile, the FortiMail unit will instead perform either the general or individualized action in the antispam profile. For details, see “ <a href="#">set out_profile profile modify individualaction</a> ” on page 415 and “ <a href="#">set out_profile profile modify actions</a> ” on page 400.	disable
safelist-enable {enable   disable}	Enable to automatically update personal safelist database from sent email.	disable
safelist-word {enable   disable}	Enable to perform a safelist word scan. The scan will examine the email for words configured in “ <a href="#">set out_profile profile modify safelistwordlist</a> ” on page 426.	disable

## Related topics

[profile antispam-action](#) on page 190

[profile antivirus](#) on page 194

## profile antispam-action

Use this command to configure antispam action profiles.

## Syntax

```
config profile antispam-action
edit <profile_name>
  set action {discard | domain-quarantine | none | personal-quarantine | reject | rewrite-rcpt | system-quarantine}
  set alternate-host {<relay_fqdn> | <relay_ipv4>}
  set alternate-host-status {enable | disable}
  set archive-account <account_name>
  set archive-status {enable | disable}
  set bcc-addr <recipient_email>
  set bcc-env-from-addr <message_str>
  set bcc-env-from-status {enable | disable}
  set bcc-status {enable | disable}
  set deliver-to-original-host {enable | disable}
  set disclaimer-insertion {enable | disable}
  set disclaimer-insertion-content <message_name>
  set disclaimer-insertion-location {beginning | end}
  set header-insertion-name <name_str>
  set header-insertion-status {enable | disable}
  set header-insertion-value <header_str>
  set notification-profile <profile_name>
  set notification-status {enable | disable}
```

```

set rewrite-rcpt-local-type {none | prefix | replace | suffix}
set rewrite-rcpt-local-value <value_str>
set rewrite-rcpt-domain-type {none-prefix | replace | suffix}
set rewrite-rcpt-domain-value <value_str>
end

```

Variable	Description	Default
<profile_name>	Enter the name of an antispam action profile.	
action {discard   domain-quarantine   none   personal-quarantine   reject   rewrite-rcpt   system-quarantine}	<p>Enter an action for the profile.</p> <ul style="list-style-type: none"> <li>• <b>discard</b>: Enter to accept the email, but then delete it instead of delivering the email, without notifying the SMTP client.</li> <li>• <b>domain-quarantine</b>: Enter to redirect spam to the per-domain quarantine. For more information, see the <a href="#">FortiMail Administration Guide</a>. Note that this option is only available with a valid advanced management license.</li> <li>• <b>none</b>: Apply any configured header or subject line tags, if any.</li> <li>• <b>personal-quarantine</b>: Enter to redirect spam to the per-recipient quarantine. For more information, see the <a href="#">FortiMail Administration Guide</a>. This option is available only for incoming profiles.</li> <li>• <b>reject</b>: Enter to reject the email and reply to the SMTP client with SMTP reply code 550.</li> <li>• <b>rewrite-rcpt</b>: Enter to change the recipient address of any email message detected as spam. Configure rewrites separately for the local-part (the portion of the email address before the '@' symbol, typically a user name) and the domain part (the portion of the email address after the '@' symbol). If you enter this option, also configure <a href="#">rewrite-rcpt-local-type {none   prefix   replace   suffix}</a>, <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a>, <a href="#">rewrite-rcpt-domain-type {none-prefix   replace   suffix}</a>, and <a href="#">rewrite-rcpt-domain-value &lt;value_str&gt;</a>.</li> <li>• <b>system-quarantine</b>: Enter to redirect spam to the system quarantine. For more information, see the <a href="#">FortiMail Administration Guide</a>.</li> </ul>	none
alternate-host {<relay_fqdn>   <relay_ipv4>}	<p>Type the fully qualified domain name (FQDN) or IP address of the alternate relay or SMTP server.</p> <p>This field applies only if <code>alternate-host-status</code> is enable.</p>	
alternate-host-status {enable   disable}	<p>Enable to route the email to a specific SMTP server or relay. Also configure <a href="#">alternate-host {&lt;relay_fqdn&gt;   &lt;relay_ipv4&gt;}</a>.</p> <p><b>Note:</b> If you enable this setting, for all email that matches the profile, the FortiMail unit will use this destination and ignore <a href="#">mailsetting relay-host-list on page 145</a> and the protected domain's <code>tp-use-domain-mta {yes   no}</code>.</p>	disable
archive-account <account_name>	<p>Type the email archive account name where you want to archive the spam.</p> <p>Enable <a href="#">archive-status {enable   disable}</a> to make this function work.</p>	

Variable	Description	Default
	For more information about archive accounts, see <a href="#">antispam url-fgas-exempt-list</a> .	
archive-status {enable   disable}	Enable to allow the <a href="#">archive-account &lt;account_name&gt;</a> function to work.	disable
bcc-addr <recipient_email>	Type the blind carbon copy (BCC) recipient email address. This field applies only if <code>bcc-status</code> is enable.	
bcc-env-from-addr <message_str>	Specify an envelope from BCC address. In the case that email is not deliverable and bounced back, the email is returned to the specified envelope from address instead of the original sender. This is helpful when you want to use a specific email to collect bounce notifications. This field applies only if <code>bcc-env-from-status</code> is enable.	
bcc-env-from-status {enable   disable}	Enable to specify an envelope from address.	disable
bcc-status {enable   disable}	Enable to send a BCC of the email. Also configure <a href="#">bcc-addr &lt;recipient_email&gt;</a> .	disable
deliver-to-original-host {enable   disable}	Enable to deliver the message to the original host.	disable
disclaimer-insertion {enable   disable}	Enable to insert disclaimer.	disable
disclaimer-insertion-content <message_name>	Specify the content name to be inserted.	default
disclaimer-insertion-location {beginning   end}	Insert the disclaimer at the	beginning
header-insertion-name <name_str>	<p>Enter the message header key. The FortiMail unit will add this text to the message header of the email before forwarding it to the recipient.</p> <p>Many email clients can sort incoming email messages into separate mailboxes, including a spam mailbox, based on text appearing in various parts of email messages, including the message header. For details, see the documentation for your email client.</p> <p>Message header lines are composed of two parts: a key and a value, which are separated by a colon. For example, you might enter: X-Custom-Header: Detected as spam by profile 22.</p> <p>If you enter a header line that does not include a colon, the FortiMail unit will automatically append a colon, causing the entire text that you enter to be the key.</p> <p><b>Note:</b> Do not enter spaces in the key portion of the header line, as these are forbidden by <a href="#">RFC 2822</a>.</p> <p>See <a href="#">header-insertion-value &lt;header_str&gt;</a>.</p>	
header-insertion-status {enable   disable}	Enable to add a message header to detected spam. See <a href="#">header-insertion-value &lt;header_str&gt;</a> .	disable

Variable	Description	Default
header-insertion-value <header_str>	<p>Enter the message header value.</p> <p>Message header lines are composed of two parts: a key and a value, which are separated by a colon. For example, you might enter: X-Custom-Header: Detected as spam by profile 22.</p> <p>If you enter a header line that does not include a colon, the FortiMail unit will automatically append a colon, causing the entire text that you enter to be the key.</p> <p><b>Note:</b> Do not enter spaces in the key portion of the header line, as these are forbidden by <a href="#">RFC 2822</a>.</p> <p>See <a href="#">header-insertion-name &lt;name_str&gt;</a>.</p>	
notification-profile <profile_name>	Type the name of the notification profile used for sending notifications.	
notification-status {enable   disable}	Enable sending notifications using a notification profile.	disable
rewrite-rcpt-local-type {none   prefix   replace   suffix}	<p>Change the local part (the portion of the email address before the '@' symbol, typically a user name) of the recipient address of any email message detected as spam.</p> <p>none: No change.</p> <p>prefix: Enter to prepend the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a>.</p> <p>suffix: Enter to append the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a>.</p> <p>replace: Enter to substitute the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a>.</p>	none
rewrite-rcpt-local-value <value_str>	Enter the text for the option (except none) you choose in <a href="#">rewrite-rcpt-local-type {none   prefix   replace   suffix}</a> .	
rewrite-rcpt-domain-type {none-prefix   replace   suffix}	<p>Change the domain part (the portion of the email address after the '@' symbol) of the recipient address of any email message detected as spam.</p> <p>none: No change.</p> <p>prefix: Enter to prepend the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;value_str&gt;</a>.</p> <p>suffix: Enter to append the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;value_str&gt;</a>.</p> <p>replace: Enter to substitute the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;value_str&gt;</a>.</p>	none
rewrite-rcpt-domain-value <value_str>	Enter the text for the option (except none) you choose in <a href="#">rewrite-rcpt-domain-type {none-prefix   replace   suffix}</a> .	

## Related topics

[profile antispam on page 178](#)

## profile antivirus

Use this command to create antivirus profiles that you can select in a policy in order to scan email for viruses.

The FortiMail unit scans email header, body, and attachments (including compressed files, such as ZIP, PKZIP, LHA, ARJ, and RAR files) for virus infections. If the FortiMail unit detects a virus, it will take actions as you define in the antivirus action profiles.

## Syntax

```
config profile antivirus
  edit <profile_name>
    set action-default { predefined_av_discard | predefined_av_reject}
    set action-file-signature
    set action-heuristic {predefined_av_discard | predefined_av_reject}
    set action-outbreak <action>
    set action-sandbox-high <action>
    set action-sandbox-low <action>
    set action-sandbox-medium <action>
    set action-sandbox-noresult <action>
    set action-sandbox-url-high <action>
    set action-sandbox-url-low <action>
    set action-sandbox-url-medium <action>
    set action-sandbox-url-noresult <action>
    set action-sandbox-url-virus <action>
    set action-sandbox-virus <action>
    set file-signature-check {enable | disable}
    set grayware-scan {enable | disable}
    set heuristic {enable | disable}
    set malware-outbreak-protection {enable | disable}
    set sandbox-analysis {enable | disable}
    set sandbox-analysis-url{enable | disable}
    set sandbox-scan-mode {submit-and-wait | submit-only}
    set scanner {enable | disable}
  end
```

Variable	Description	Default
<profile_name>	Enter the name of the profile. To view a list of existing entries, enter a question mark ( ? ).	
action-default { predefined_av_discard   predefined_av_reject}	Type a predefined antivirus action. predefined_av_discard: Accept infected email, but then delete it instead of delivering the email, without notifying the SMTP client. predefined_av_reject: Reject infected email and reply to the SMTP client with SMTP reply code 550.	
action-file-signature	Type a predefined scan for file signature action. predefined_av_discard: predefined_av_reject:	

Variable	Description	Default
action-heuristic {predefined_av_ discard   predefined_ av_reject}	Type a predefined heuristic scanning action on infected email.  predefined_av_discard: Accept email suspected to be infected, but then delete it instead of delivering the email, without notifying the SMTP client.  predefined_av_reject: Reject email suspected to be infected, and reply to the SMTP client with SMTP reply code 550.	
action-outbreak <action>	Type to determine the action to take if the FortiSandbox analysis determines that the email message has an outbreak.	
action-sandbox-high <action>	Type to determine the action to take if the FortiSandbox attachment analysis determines that the email messages have high probability of viruses or other threat qualities.	default
action-sandbox-low <action>	Type to determine the action to take if the FortiSandbox attachment analysis determines that the email messages have low probability of viruses or other threat qualities.	default
action-sandbox-medium <action>	Type to determine the action to take if the FortiSandbox attachment analysis determines that the email messages have medium probability of viruses or other threat qualities.	default
action-sandbox-virus <action>	Type to determine the action to take if the FortiSandbox attachment analysis determines that the email messages definitely have viruses or other threat qualities.	default
action-sandbox-noreturn <action>	Type to determine the action to take if the FortiSandbox attachment analysis returns no results.	None
action-sandbox-url-high <action>	Type to determine the action to take if the FortiSandbox URL analysis determines that the email messages have high probability of viruses or other threat qualities.	default
action-sandbox-url-low <action>	Type to determine the action to take if the FortiSandbox URL analysis determines that the email messages have low probability of viruses or other threat qualities.	default
action-sandbox-url-medium <action>	Type to determine the action to take if the FortiSandbox URL determines that the email messages have medium probability of viruses or other threat qualities.	default
action-sandbox-url-virus <action>	Type to determine the action to take if the FortiSandbox URL analysis determines that the email messages definitely have viruses or other threat qualities.	default
action-sandbox-url-noreturn <action>	Type to determine the action to take if the FortiSandbox URL analysis returns no results.	None
file-signature-check {enable   disable}	Enable to scan for file signatures.	disable
grayware-scan {enable   disable}	Enable to scan for grayware as well when performing antivirus scanning.	enable

Variable	Description	Default
heuristic {enable   disable}	Enable to use heuristics when performing antivirus scanning.	enable
malware-outbreak-protection {enable   disable}	Instead of using virus signatures, malware outbreak protection uses data analytics from the FortiGuard Service. For example, if a threshold volume of previously unknown attachments are being sent from known malicious sources, they are treated as suspicious viruses.  This feature can help quickly identify new threats.  Because the infected email is treated as virus, the virus replacement message will be used, if the replacement action is triggered.	
sandbox-analysis {enable   disable}	Enable to send suspicious email attachments to FortiSandbox for inspection. For details about FortiSandbox, see <a href="#">system fortisandbox on page 299</a> .	disable
sandbox-analysis-url {enable   disable}	Enable or disable sending suspicious attachment content to FortiSandbox for analysis.	disable
sandbox-scan-mode {submit-and-wait   submit-only}	Edits how the email is handled by the FortiSandbox	submit-and-wait
scanner {enable   disable}	Enable to perform antivirus scanning for this profile.	disable

## Related topics

[profile antispam on page 178](#)

## profile antivirus-action

Use this command to configure antivirus action profiles.

### Syntax

```
config profile antivirus-action
edit <profile_name>
  config header-insertion-list
  edit <header-name>
    set header-insertion-value <string>
  next
end
set action {discard | domain-quarantine | none | reject | repackage | repackage-with-cmsg |
  rewrite-rcpt | system-quarantine}
set alternate-host {<relay_fqdn> | <relay_ipv4>}
set alternate-host-status {enable | disable}
set archive-account
```

```

set archive-status
set bcc-addr <recipient_email>
set bcc-env-from-addr <message_str>
set bcc-env-from-status {enable | disable}
set bcc-status {enable | disable}
set deliver-to-original-host {enable | disable}
set disclaimer-insertion {enable | disable}
set disclaimer-insertion-content <message_name>
set disclaimer-insertion-location {beginning | end}
set header-insertion-name <name_str>
set header-insertion-status {enable | disable}
set header-insertion-value <header_str>
set notification-profile <profile_name>
set notification-status {enable | disable}
set remove-url-status {enable | disable}
set replace-infected-status {enable | disable}
set rewrite-rcpt-local-type {none | prefix | replace | suffix}
set rewrite-rcpt-local-value <value_str>
set rewrite-rcpt-domain-type {none-prefix | replace | suffix}
set rewrite-rcpt-domain-value <value_str>
set subject-tagging-status {enable | disable}
set subject-tagging-text <tag_str>

end

```

Variable	Description	Default
<profile_name>	Enter the name of an antivirus action profile.	
action {discard   domain-quarantine   none   reject   repackage   repackage-with-cmsg   rewrite-rcpt   system-quarantine}	<p>Enter an action for the profile.</p> <ul style="list-style-type: none"> <li>discard: Enter to accept the email, but then delete it instead of delivering the email, without notifying the SMTP client.</li> <li>domain-quarantine: Enter to redirect virus to the per-domain quarantine. For more information, see the <a href="#">FortiMail Administration Guide</a>. Note that this option is only available with a valid advanced management license.</li> <li>none: Apply any configured header or subject line tags, if any.</li> <li>reject: Enter to reject the email and reply to the SMTP client with SMTP reply code 550.</li> <li>repackage: Forward the infected email as an attachment but the original email body will still be used without modification.</li> <li>repackage-with-cmsg: Forward the infected email as an attachment with the customized email body that you define in the custom email template. For example, in the template, you may want to say "The attached email is infected by a virus".</li> <li>rewrite-rcpt: Enter to change the recipient address of any email message detecting a virus. Configure rewrites separately for the local-part (the portion of the email address before the "@" symbol, typically a user name) and the domain part (the portion of the email address after the "@" symbol). If you enter this option, also configure <a href="#">rewrite-rcpt-local-type</a> {none   prefix   replace   suffix}, <a href="#">rewrite-rcpt-local-value</a> &lt;value_str&gt;, <a href="#">rewrite-rcpt-domain-type</a> {none-prefix   replace   suffix}, and</li> </ul>	none

Variable	Description	Default
	<p><a href="#">rewrite-rcpt-domain-value &lt;value_str&gt;</a>.</p> <ul style="list-style-type: none"> <li><b>system-quarantine:</b> Enter to redirect virus to the system quarantine. For more information, see the <a href="#">FortiMail Administration Guide</a>.</li> </ul>	
<code>alternate-host {&lt;relay_fqdn&gt;   &lt;relay_ipv4&gt;}</code>	<p>Type the fully qualified domain name (FQDN) or IP address of the alternate relay or SMTP server.</p> <p>This field applies only if <code>alternate-host-status</code> is enable.</p>	
<code>alternate-host-status {enable   disable}</code>	<p>Enable to route the email to a specific SMTP server or relay. Also configure <a href="#">alternate-host {&lt;relay_fqdn&gt;   &lt;relay_ipv4&gt;}</a>.</p> <p><b>Note:</b> If you enable this setting, for all email that matches the profile, the FortiMail unit will use this destination and ignore <a href="#">mailsetting relay-host-list on page 145</a> and the protected domain's <a href="#">tp-use-domain-mta {yes   no}</a>.</p>	disable
<code>archive-account</code>	Enter the archive account.	
<code>archive-status</code>	Enable or disable message archiving.	disable
<code>bcc-addr &lt;recipient_email&gt;</code>	<p>Type the blind carbon copy (BCC) recipient email address.</p> <p>This field applies only if <code>bcc-status</code> is enable.</p>	
<code>bcc-env-from-addr &lt;message_str&gt;</code>	<p>Specify an envelope from BCC address. In the case that email is not deliverable and bounced back, the email is returned to the specified envelope from address instead of the original sender. This is helpful when you want to use a specific email to collect bounce notifications.</p> <p>This field applies only if <code>bcc-env-from-status</code> is enable.</p>	
<code>bcc-env-from-status {enable   disable}</code>	Enable to specify an envelope from address.	disable
<code>bcc-status {enable   disable}</code>	<p>Enable to send a BCC of the email. Also configure <a href="#">bcc-addr &lt;recipient_email&gt;</a>.</p>	disable
<code>deliver-to-original-host {enable   disable}</code>	Enable to deliver the message to the original host.	disable
<code>disclaimer-insertion {enable   disable}</code>	Enable to insert disclaimer.	disable
<code>disclaimer-insertion-content &lt;message_name&gt;</code>	Specify the content name to be inserted.	default
<code>disclaimer-insertion-location {beginning   end}</code>	Insert the disclaimer at the beginning or end.	beginning
<code>header-insertion-name &lt;name_str&gt;</code>	<p>Enter the message header key. The FortiMail unit will add this text to the message header of the email before forwarding it to the recipient.</p> <p>Many email clients can sort incoming email messages into separate mailboxes based on text appearing in various parts of email messages, including the message header. For details, see the documentation for your email client.</p>	

Variable	Description	Default
	<p>Message header lines are composed of two parts: a key and a value, which are separated by a colon. For example, you might enter:</p> <p>X-Custom-Header: Detected as virus by profile 22.</p> <p>If you enter a header line that does not include a colon, the FortiMail unit will automatically append a colon, causing the entire text that you enter to be the key.</p> <p><b>Note:</b> Do not enter spaces in the key portion of the header line, as these are forbidden by <a href="#">RFC 2822</a>.</p> <p>See <a href="#">header-insertion-value &lt;header_str&gt;</a>.</p>	
header-insertion-status {enable   disable}	<p>Enable to add a message header to detected virus.</p> <p>See <a href="#">header-insertion-value &lt;header_str&gt;</a>.</p>	disable
header-insertion-value <header_str>	<p>Enter the message header value.</p> <p>Message header lines are composed of two parts: a key and a value, which are separated by a colon. For example, you might enter:</p> <p>X-Custom-Header: Detected as virus by profile 22.</p> <p>If you enter a header line that does not include a colon, the FortiMail unit will automatically append a colon, causing the entire text that you enter to be the key.</p> <p><b>Note:</b> Do not enter spaces in the key portion of the header line, as these are forbidden by <a href="#">RFC 2822</a>.</p> <p>See <a href="#">header-insertion-name &lt;name_str&gt;</a>.</p>	
notification-profile <profile_name>	Type the name of the notification profile used for sending notifications.	
notification-status {enable   disable}	Enable sending notifications using a notification profile.	disable
remove-url-status {enable   disable}	Enable to remove URL detected by FortiSandbox.	enable
replace-infected-status {enable   disable}	Enable or disable the option to replace infected body or attachment.	disable
rewrite-rcpt-local-type {none   prefix   replace   suffix}	<p>Change the local part (the portion of the email address before the '@' symbol, typically a user name) of the recipient address of any email message detecting a virus.</p> <p>none: No change.</p> <p>prefix: Enter to prepend the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a>.</p> <p>suffix: Enter to append the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a>.</p> <p>replace: Enter to substitute the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a>.</p>	none
rewrite-rcpt-local-value <value_str>	Enter the text for the option (except none) you choose in <a href="#">rewrite-rcpt-local-type {none   prefix   replace   suffix}</a> .	

Variable	Description	Default
rewrite-rcpt-domain-type {none-prefix   replace   suffix}	Change the domain part (the portion of the email address after the '@' symbol) of the recipient address of any email message detecting a virus.  none: No change.  prefix: Enter to prepend the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;value_str&gt;</a> .  suffix: Enter to append the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;value_str&gt;</a> .  replace: Enter to substitute the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;value_str&gt;</a> .	none
rewrite-rcpt-domain-value <value_str>	Enter the text for the option (except none) you choose in <a href="#">rewrite-rcpt-domain-type {none-prefix   replace   suffix}</a> .	
subject-tagging-status {enable   disable}	Enable to prepend text defined using <a href="#">subject-tagging-text &lt;tag_str&gt;</a> ("tag") to the subject line on detected virus.	disable
subject-tagging-text <tag_str>	Enter the text that will appear in the subject line of the email, such as "[VIRUS] ". The FortiMail unit will prepend this text to the subject line of virus before forwarding it to the recipient.	

## Related topics

[profile antivirus on page 194](#)

## profile authentication

Use this command to configure the FortiMail unit to connect to an external SMTP server in order to authenticate email users.

FortiMail units support the following authentication methods:

- IMAP
- POP3
- RADIUS
- SMTP



When the FortiMail unit is operating in server mode, only local and RADIUS authentication are available.

In addition to authenticating email users for SMTP connections, SMTP profiles can be used to authenticate email users making webmail (HTTP or HTTPS) or POP3 connections to view their per-recipient quarantine, and when authenticating with another SMTP server to deliver email.

Depending on the mode in which your FortiMail unit is operating, you may be able to apply authentication profiles through inbound recipient-based policies, IP-based policies, and email user accounts.

For more information, see the [FortiMail Administration Guide](#).

## Syntax

```

config profile authentication imap
  edit <profile_name>
    set auth-type {auto | cram-md5 | digest-md5 | login | ntlm | plain}
    set option {ssl secure tls senddomain}
    set port <port_int>
    set server {<fqdn_str> | <host_ipv4>}
config profile authentication pop3
  edit <profile_name>
    set auth-type {auto | cram-md5 | digest-md5 | login | ntlm | plain}
    set option {ssl secure tls senddomain}
    set port <port_int>
    set server {<fqdn_str> | <host_ipv4>}
config profile authentication radius
  edit <profile_name>
    set access-override {enable | disable}
    set access-override-attribute <integer>
    set access-override-vendor <integer>
    set auth-prot {auto | chap | mschap | mschap2 | pap}
    set domain-override {enable | disable}
    set domain-override-attribute <integer>
    set domain-override-vendor <integer>
    set nas-ip <ip_addr>
    set port <port_int>
    set secret <password_str>
    set send-domain {enable | disable}
    set server {<fqdn_str> | <host_ipv4>}
config profile authentication smtp
  edit <profile_name>
    set auth-type {auto | cram-md5 | digest-md5 | login | ntlm | plain}
    set option {ssl secure tls senddomain}
    set server {<fqdn_str> | <host_ipv4>}
    set port <port_int>
    set try-ldap-mailhost {enable | disable}

end

```

Variable	Description	Default
<profile_name>	Enter the name of the profile. To view a list of existing entries, enter a question mark ( ? ).	
auth-type {auto   cram-md5   digest-md5   login   ntlm   plain}	Enter an authentication type.	auto

Variable	Description	Default
access-override {enable   disable}	Enable to override the access profile you specify when you add an administrator with the value of the remote attribute returned from the RADIUS server, if the returned value matches an existing access profile.	disable
access-override-attribute <integer>	Enter the attribute ID of a vender for remote access permission override. The attribute should hold an access profile name that exists on FortiMail. The default ID is 6, which is Fortinet-Access-Profile.	6
access-override-vendor <integer>	Enter the vender's registered RADIUS ID for remote access permission override. The default ID is 12356, which is Fortinet.	12356
option {ssl secure tls senddomain}	Enter one or more of the following in a space-delimited list: <ul style="list-style-type: none"> <li>senddomain: Enable if the IMAP server requires both the user name and the domain when authenticating.</li> <li>ssl: Enables secure socket layers (SSL) to secure message transmission.</li> <li>secure: Enables secure authentication.</li> <li>tls: Enables transport layer security (TLS) to ensure privacy between communicating application.</li> </ul>	
port <port_int>	Enter the TCP port number of the IMAP server. The standard port number for SSL-secured IMAP is 993.	143
server {<fqdn_ str>   <host_ipv4>}	Enter the IP address or fully qualified domain name (FQDN) of the IMAP server.	
option {ssl secure tls senddomain}	If you want to enable any of the following options, enter them in a space-delimited list: <ul style="list-style-type: none"> <li>domain: Enable if the POP3 server requires both the user name and the domain when authenticating.</li> <li>ssl: Enables secure socket layers (SSL) to secure message transmission.</li> <li>secure: Enables secure authentication.</li> <li>tls: Enables transport layer security (TLS) to ensure privacy between communicating application.</li> </ul>	
port <port_int>	Enter the TCP port number of the POP3 server. The standard port number for SSL-secured POP3 is 995.	110
server {<fqdn_ str>   <host_ipv4>}	Enter the IP address or fully qualified domain name (FQDN) of the POP3 server.	
auth-prot {auto   chap   mschap   mschap2   pap}	Enter the authentication method for the RADIUS server.	mschap2
domain-override {enable   disable}	Enable to override the domain you specify when you add an administrator with the value of the remote attribute returned from the RADIUS server, if the returned value matches an existing protected domain.	disable
domain-override-attribute <integer>	Enter the attribute ID of a vender for remote domain override. The attribute should hold a domain name that exists on FortiMail. The default ID is 3, which is Fortinet-Vdom-Name.	3

Variable	Description	Default
domain-override-vendor <integer>	Enter the vendor's registered RADIUS ID for remote domain override. The default ID is 12356, which is Fortinet.	12356
nas-ip <ip_addr>	Enter the NAS IP address and Called Station ID (for more information about RADIUS Attribute 31, see RFC 2548 Microsoft Vendor-specific RADIUS Attributes). If you do not enter an IP address, the IP address that the FortiMail interface uses to communicate with the RADIUS server will be applied.	0.0.0.0
port <port_int>	If the RADIUS server listens on a nonstandard port number, enter the port number of the RADIUS server.	1812
secret <password_str>	Enter the password for the RADIUS server.	
send-domain {enable   disable}	Enable if the RADIUS server requires both the user name and the domain when authenticating.	disable
server {<fqdn_str>   <host_ipv4>}	Enter the IP address or fully qualified domain name (FQDN) of the RADIUS server.	
option {ssl secure tls senddomain}	If you want to enable any of the following options, enter them in a space-delimited list: <ul style="list-style-type: none"> <li>senddomain: Enable if the SMTP server requires both the user name and the domain when authenticating.</li> <li>ssl: Enables secure socket layers (SSL) to secure message transmission.</li> <li>secure: Enables secure authentication.</li> <li>tls: Enables transport layer security (TLS) to ensure privacy between communicating application</li> </ul>	
server {<fqdn_str>   <host_ipv4>}	Enter the IP address or fully qualified domain name (FQDN) of the SMTP server.	
port <port_int>	Enter the TCP port number of the SMTP server. The standard port number for SSL-secured SMTP is 465.	25
try-ldap-mailhost {enable   disable}	Enable if your LDAP server has a mail host entry for the generic user. If you select this option, the FortiMail unit will query the generic LDAP server first to authenticate email users. If no results are returned for the query, the FortiMail unit will query the server you entered in the server field.	enable

## Related topics

[profile certificate-binding on page 205](#)

[profile encryption on page 222](#)

## profile bec

Use this command to configure business email compromise (BEC) profile rules. To avoid false positives and false negatives, assign scores to adjust the weight allocated to each of the most common BEC attack types, such as cousin domains, suspicious characters, sender alignment, action keywords, and URL categories.

Once configured, BEC profiles are then used in antispam profiles.

## Syntax

```
config profile bec
  edit <name>
    config rule
      set comment <string>
      edit <order-integer>
        set action <datasource>
        set action-keyword-score <float>
        set cousin-domain-score <float>
        set malformed-email-score <float>
        set name <string>
        set sender-alignment-score <float>
        set status {enable | disable}
        set suspicious-character-score <float>
        set threshold <float>
        set url-profile <datasource>
        set url-profile-score <float>
      next
    end
  end
end
```

Variable	Description	Default
action <datasource>	Enter an antispam action profile name for the rule.	
action-keyword-score <float>	Enter a weight-adjusted score for actions keywords.	10.000000
cousin-domain-score <float>	Enter a weight-adjusted score for cousin domains.	10.000000
malformed-email-score <float>	Enter a weight-adjusted score for malformed emails. Malformed emails are those emails that contain malformed data in the email structure, header, or body. For more information, see <a href="#">RFC 7103</a> .	10.000000
name <string>	Enter a name for the rule.	
sender-alignment-score <float>	Enter a weight-adjusted score for sender alignment. Sender alignment checks for a Header From and Envelope From domain mismatch.	10.000000

Variable	Description	Default
status {enable   disable}	Enable or disable the profile rule.	enable
suspicious-character-score <float>	Enter a weight-adjusted score for suspicious characters.	10.000000
threshold <float>	Define the threshold at which point actions are taken. This score is allocated to the other categories.	50.000000
url-profile <datasource>	Enter a URL profile to assign to the URL category (url-profile-score).	unrated
url-profile-score <float>	Enter a weight-adjusted score for URL profiles that analyze any phishing URLs contained within emails.	10.000000

## Related topics

[profile antispam](#)

## profile certificate-binding

Use this command to create certificate binding profiles, which establish the relationship between an email address and the certificate that:

- proves an individual's identity
- provides their public (and, for protected domains, private) keys for use with encryption profiles

This relationship and information can then be used for secure MIME (S/MIME).

If an email is **incoming** to a protected domain and it uses S/MIME encryption, the FortiMail unit compares the sender's identity with the list of certificate bindings to determine if it has a key that can decrypt the email. If it has a matching public key, it will decrypt the email before forwarding it. If it does **not**, it forwards the still-encrypted email to the recipient; the recipient's MUA in that case must support S/MIME and possess the sender's public key.

If an email is **outgoing** from a protected domain, and you have selected an encryption profile in the message delivery rule that applies to the session, the FortiMail unit compares the sender's identity with the list of certificate bindings to determine if it has a certificate and private key. If it has a matching private key, it will encrypt the email using the algorithm specified in the encryption profile. If it does **not**, it performs the failure action indicated in the encryption profile.

## Syntax

```
config profile certificate-binding
edit <profile_id>
set address-pattern <pattern_str>
```

```

set key-private <key_str>
set key-public <key_str>
set key-usage {both | encryption | signing}
set password <pwd_str>
end

```

Variable	Description	Default
<profile_id>	Enter the ID number of the certificate binding profile.	
address-pattern <pattern_str>	Enter the email address or domain associated with the identity represented by the personal or server certificate.	
key-private <key_str>	Enter the private key associated with the identity, used to encrypt and sign email from that identity.	
key-public <key_str>	Enter the public key associated with the identity, used to encrypt and sign email from that identity.	
key-usage {both   encryption   signing}	Use the key for encryption, signing, or both.	encryption
password <pwd_str>	Enter the password for the personal certificate files.	

## Related topics

[profile authentication on page 200](#)

[profile encryption on page 222](#)

## profile content

Use this command to create content profiles, which you can use to match email based upon its subject line, message body, and attachments.

Unlike antispam profiles, which deal primarily with spam, content profiles match any other type of email.

Content profiles can be used to apply content-based encryption to email. They can also be used to restrict prohibited content, such as words or phrases, file names, and file attachments that are not permitted by your network usage policy. As such, content profiles can be used both for email that you want to protect, and for email that you want to prevent.

## Syntax

```

config profile content
edit <profile_name>
config attachment-scan
edit <index_number>
set action <action>
set operator {is | is-not}

```

```

    set patterns {archive | audio | encrypted | executable_windows | image | msoffice |
        openoffice | script | video}
    set status {enable | disable}
config monitor
    edit monitor <index_int>
        set action <profile_name>
        set dict-score <score_int>
        set dictionary-group <dictionary-group_name>
        set dictionary-profile <dictionary-profile_name>
        set dictionary-type {group | profile}
        set scan-msoffice {enable | disable}
        set scan-pdf {enable | disable}
        set status {enable | disable}
    set action-cdr <action_profile>
    set action-default <action_profile>
    set action-image-analysis <action_profile>
    set action-max-size <action_profile>
    set archive-scan-options {block-on-failure-to-decompress | block-password-protected |
        block-recursive}
    set cdr-file-type-options {msoffice | pdf}
    set decrypt-password-archive {enable | disable}
    set decrypt-password-num-of-words <number>
    set decrypt-password-office {enable | disable}
    set decrypt-password-options {built-in-password-list | user-defined-password-list | words-
        in-email-content}
    set defersize <size-in-kb>
    set embedded-scan-options {check-msoffice | check-msoffice-vba | check-msvisio | check-
        openoffice | check-pdf}
    set html-content-action {convert-to-text | modify-content}
    set html-content-url-action {click-protection | click-protection-isolator | isolator | keep
        | remove}
    set html-content-url-selection {tag-attribute | tag-content}
    set image-analysis-scan {enable | disable}
    set max-num-of-attachment <number>
    set max-size <size-in-kb>
    set max-size-option {message | attachment}
    set max-size-status {enable | disable}
    set remove-active-content {enable | disable}
    set scan options block-fragmented-email
    set scan options block-password-protected-office
    set scan options check-archive-content
    set scan options check-embedded-content
    set scan options bypass-on-smtp-auth
    set scan options check-html-content
    set scan options check-max-num-of-attachment
    set scan options check-text-content
    set scan options defer-message-delivery
    set text-content-action {remove-url | click-protection}
end

```

Variable	Description	Default
<profile_name>	Enter the name of the profile. To view a list of existing entries, enter a question mark (?).	
action <action>	Specify the action to use.	

Variable	Description	Default
operator {is   is-not}	Specify the operator.	is
patterns {archive   audio   encrypted   executable_   windows   image   msoffice   openoffice   script   video}	Enter the pattern/s that match the email attachment names that you want the content profile to match. For multiple patterns, separate each entry with a space.	
status {enable   disable}	Enable or disable a pattern that matches the email attachment names that you want the content profile to match.	enable
monitor <index_int>	Enter the index number of the monitor profile. If the monitor profile does not currently exist, it will be created.	
action <profile_name>	Enter the action profile for this monitor profile. The FortiMail unit will perform the actions if the content of the email message matches words or patterns from the dictionary profile that the monitor profile uses.	
dict-score <score_int>	Enter the number of times that an email must match the content monitor profile before it will receive the antispam action.	1
dictionary-group <dictionary-group_name>	Enter the dictionary profile group that this monitor profile will use. The FortiMail unit will compare content in the subject line and message body of the email message with words and patterns in the dictionary profiles. If it locates matching content, the FortiMail unit will perform the actions configured for this monitor profile. For information on dictionary profiles, see the <a href="#">FortiMail Administration Guide</a> .	
dictionary-profile <dictionary-profile_name>	Enter the dictionary profile that this monitor profile will use. The FortiMail unit will compare content in the subject line and message body of the email message with words and patterns in the dictionary profile. If it locates matching content, the FortiMail unit will perform the actions configured for this monitor profile in <a href="#">profile content-action on page 213</a> . For information on dictionary profiles, see the <a href="#">FortiMail Administration Guide</a> .	
dictionary-type {group   profile}	Enter profile to detect content based upon a dictionary profile, or group to detect content based upon a group of dictionary profiles.	group
scan-msoffice {enable   disable}	Enable or disable MS Word document scanning for this profile.	disable
scan-pdf {enable   disable}	Enable or disable PDF document scanning for this profile.	disable
status {enable   disable}	Enable or disable this monitor profile.	disable
action-cdr <action_profile>	Specify the action profile to use.	

Variable	Description	Default
action-default <action_profile>	Enter a content action profile to be used by all the content filters except for the encrypted email, which can have its own action. See below for details.	
action-image-analysis <action_profile>	For the image email file type, you can use a content action profile to overwrite the default action profile used in the content profile.	
action-max-size <action-profile>	Specify the action profile to use for message over maximum size.	
block-on-failure-to-decompress	Enter to apply the action configured in <a href="#">profile content-action on page 213</a> if an attached archive cannot be successfully decompressed in order to scan its contents.	
block-password-protected	Enter to apply the action configured in <a href="#">profile content-action on page 213</a> if an attached archive is password-protected.	
block-recursive	Enable to block archive attachments whose depth of nested archives exceeds <a href="#">archive-max-recursive-level &lt;depth_int&gt; on page 209</a> .	
archive-max-recursive-level <depth_int>	Enter the nesting depth threshold. Depending upon each attached archive's depth of archives nested within the archive, the FortiMail unit will use one of the following methods to determine whether it should block or pass the email. <ul style="list-style-type: none"> <li>The <code>archive-max-recursive-level</code> is 0, or attachment's depth of nesting equals or is less than <code>archive-max-recursive-level</code>: If the attachment contains a file that matches one of the other MIME file types, perform the action configured for that file type, either block or pass.</li> <li>The attachment's depth of nesting is greater than <code>archive-max-recursive-level</code>: Apply the block action, unless you have disabled <a href="#">block-recursive on page 209</a>, in which case it will pass the MIME file type content filter. Block actions are specified in the <a href="#">profile content-action on page 213</a>.</li> </ul>	12
cdr-file-type-options {msoffice   pdf}	Specify the file type for content disarm and reconstruction.	
decrypt-password-archive {enable   disable}	Enable or disable to decrypt password protected archives.	disable
decrypt-password-num-of-words <number>	Specify the number of words adjacent to the keyword to try for archive decryption.	5
decrypt-password-office {enable   disable}	Enable to decrypt password protected Office files.	disable

Variable	Description	Default
decrypt-password-options {built-in-password-list   user-defined-password-list   words-in-email-content}	Specify which kind of password to use to decrypt the archives.	words-in-email-content
defersize <size-in-kb>	Bigger size will be deferred. 0 means no limit.	0
embedded-scan-options {check-msoffice   check-msoffice-vba   check-msvisio   check-openoffice   check-pdf}	Documents, similar to an archive, can sometimes contain video, graphics, sounds, and other files that are used by the document. By embedding the required file within itself instead of linking to such files externally, a document becomes more portable. However, it also means that documents can be used to hide infected files that are the real attack vector. Enable to, for MIME types such as Microsoft Office, Microsoft Visio, OpenOffice.org, and PDF documents, scan files that are encapsulated within the document itself.	
html-content-action {convert-to-text   modify-content}	Specify the action towards hypertext markup language (HTML) tags in email messages: <ul style="list-style-type: none"> <li>• <code>convert-to-text</code>: Convert the HTML content to text only content.</li> <li>• <code>modify-content</code>: Set to determine active content handling and URL processing (see <code>html-content-url-selection</code> and <code>remove-active-content</code> respectively).</li> </ul>	modify-content
html-content-url-action {click-protection   click-protection-isolator   isolator   keep   remove}	Specify HTML content URL tag handling in email messages: <ul style="list-style-type: none"> <li>• <code>click-protection</code>: Rewrite the URLs and in case the user clicks on the URLs, scan the URLs and then take the configured actions.</li> <li>• <code>click-protection-isolator</code>: Redirect to Click Protection and Fortisolator. If the rewritten URL matched Fortisolator URL category and passed Click Protection handling category, it is opened in Fortisolator.</li> <li>• <code>isolator</code>: Redirect to Fortisolator.</li> <li>• <code>keep</code>: Keep URL tags.</li> <li>• <code>remove</code>: Remove URL tags.</li> </ul>	click-protection
html-content-url-selection {tag-attribute   tag-content}	Select URLs to process from specified parts of HTML. This field applies only if <code>html-content-action</code> is <code>modify-content</code> .	tag-attribute
image-analysis-scan {enable   disable}	If you have purchase the adult image scan license, you can enable it to scan for adult images. You can also configure the scan sensitivity and image sizes under Security > Other > Adult Image Analysis.	disable
max-num-of-attachment <number>	Specify how many attachments are allowed in one email message. The valid range is between 1 and 100. The default value is 10.	10

Variable	Description	Default
max-size <size-in-kb>	Enter the size threshold in kilobytes. Delivery of email messages greater than this size will be deferred until the period configured for oversized email. To disable deferred delivery, enter 0.	10240
max-size-option {message   attachment}	Specify either the message or attachment for the size limit.	message
max-size-status {enable   disable}	Enable to apply the maximum size limits.	disable
remove-active-content {enable   disable}	Enable to remove active content. This field applies only if <code>html-content-action</code> is <code>modify-content</code> .	enable
block-fragmented-email	Enable to detect and block fragmented email. Some mail user agents, such as Outlook, are able to fragment big emails into multiple sub-messages. This is used to bypass oversized limits/scanning.	disable
block-password-protected-office	Enable to apply the block action configured in the content action profile if an attached MS Office document is password-protected, and therefore cannot be decompressed in order to scan its contents.	disable
check-archive-content	Enable to check for archived attachments.	
check-embedded-content	Enable to check for embedded contents. Documents, similar to an archive, can sometimes contain video, graphics, sounds, and other files that are used by the document. By embedding the required file within itself instead of linking to such files externally, a document becomes more portable. However, it also means that documents can be used to hide infected files that are the real attack vector.	
bypass-on-smtp-auth	Enable to omit antispam scans when an SMTP sender is authenticated.	disable
check-html-content	Enable to detect hypertext markup language (HTML) tags and, if found: apply the action profile add <code>X-FEAS-ATTACHMENT-FILTER: Contains HTML tags.</code> to the message headers This option can be used to mitigate potentially harmful HTML content such as corrupted images or files, or phishing URLs that have been specially crafted for a targeted attack, and therefore not yet identified by the FortiGuard Antispam service. Depending on the action profile, for example, you could warn email users by tagging email that contains potentially dangerous HTML content, or, if you have removed the HTML tags, allow users to safely read the email to decide whether or not it is legitimate first, <b>without</b> automatically displaying and executing potentially dangerous scripts, images, or other files (automatic display of HTML content is a risk on some email clients).	

Variable	Description	Default
	<p><b>Caution: Unless</b> you also select <code>replace</code> for the action in the content action profile, HTML will <b>not</b> be removed, and the email will <b>not</b> be converted to plain text. Instead, the FortiMail unit will only apply whichever other action profile “block” action you have selected.</p> <p><b>To actually remove HTML tags, you must also select replace.</b></p> <p>If you select <b>Replace</b>, all HTML tags will be removed, except for the minimum required by the HTML document type definition (DTD):</p> <pre>&lt;html&gt; &lt;head&gt; &lt;body&gt;</pre> <p>Stripped body text will be surrounded by <code>&lt;pre&gt;</code> tags, which is typically rendered in a monospace font, causing the appearance to mimic plain text.</p> <p>For linked files, which are hosted on an external web site for subsequent download rather than directly attached to the email, the FortiMail unit will download and attach the file to the email <b>before</b> removing the <code>&lt;img&gt;</code> or <code>&lt;embed&gt;</code> tag. In this way, while the format is converted to plain text, attachments and linked files which may be relevant to the content are still preserved.</p> <p>For example, in an email that is a mixture of HTML and plain text (Content-Type: <code>multipart/alternative</code>), and if the action profile’s “block” action is <code>replace</code>, the FortiMail unit would remove hyperlink, font, and other HTML tags in the sections labeled with Content-Type: <code>text/html</code>. Linked images would be converted to attachments (The MIME Content-Type: <code>text/html</code> label itself, however, would <b>not</b> be modified).</p>	
<code>check-max-num-of-attachment</code>	Enable to specify how many attachments are allowed in one email message. The valid range is between 1 and 100. The default value is 10.	
<code>check-text-content</code>	Enable to check the URL in the text part of the messages.	
<code>defer-message-delivery</code>	Enable to defer mail delivery from specific senders configured in policy to conserve peak time bandwidth at the expense of sending low priority, bandwidth consuming traffic at scheduled times. For example, you can apply this function to senders of marketing campaign emails or mass mailing.	
<code>text-content-action {remove-url   click-protection}</code>	Remove URLs: Removes URLs in the text parts of email messages. Click Protection: Rewrite the URLs and in case the user clicks on the URLs, scan the URLs and then take the configured action.	<code>remove-url</code>

## Related topics

[profile content-action on page 213](#)

## profile content-action

Use this command to define content action profiles. Content action profiles can be used to apply content-based encryption.

Alternatively, content action profiles can define one or more things that the FortiMail unit should do if the content profile determines that an email contains prohibited words or phrases, file names, or file types.

For example, you might have configured most content profiles to match prohibited content, and therefore to use a content action profile named `quar_profile` which quarantines email to the system quarantine for review.

However, you have decided that email that does not pass the dictionary scan named `financial_terms` is **always** prohibited, and should be rejected so that it does not require manual review. To do this, you would first configure a second action profile, named `rejection_profile`, which rejects email. You would then override `quar_profile` specifically for the dictionary-based content scan in each profile by selecting `rejection_profile` for content that matches `financial_terms`.

## Syntax

```
config profile content-action
  edit <profile_name>
    config header-insertion-list
      edit <header-insertion-name>
        set header-insertion-value <value_str>
      end
    config header-removal-list
      edit <header-removal-name>
        next
      end
    set action {discard | domain-quarantine | encryption | none | personal-quarantine | reject
              | rewrite-rcpt | system-quarantine | treat-as-spam}
    set alternate-host {<relay_fqdn> | <relay_ipv4>}
    set alternate-host-status {enable | disable}
    set archive-account <account_name>
    set archive-status {enable | disable}
    set bcc-addr <recipient_email>
    set bcc-env-from-addr <message_str>
    set bcc-env-from-status {enable | disable}
    set bcc-status {enable | disable}
    set deliver-to-original-host {enable | disable}
    set disclaimer-insertion {enable | disable}
    set disclaimer-insertion-content <message_name>
    set disclaimer-insertion-location {beginning | end}
    set notification-profile <profile_name>
    set notification-status {enable | disable}
    set remove-header {enable | disable}
    set replace-content {enable | disable}
    set replace-content-message
    set rewrite-rcpt-domain-type {none | prefix | replace | suffix}
    set rewrite-rcpt-domain-value <case_str>
    set rewrite-rcpt-local-type {none | prefix | replace | suffix}
    set rewrite-rcpt-local-value <value_str>
```

```

set subject-tagging-text <text_str>
set tagging type {insert-header | tag-subject}
end

```

Variable	Description	Default
<profile_name>	Enter the name of the profile. To view a list of existing entries, enter a question mark ( ? ).	
action {discard   domain-quarantine   encryption   none   personal-quarantine   reject   rewrite-rcpt   system-quarantine   treat-as-spam}	Enter the action that the FortiMail unit will perform if the content profile determines that an email contains prohibited words or phrases, file names, or file types. <ul style="list-style-type: none"> <li>discard: Accept the email, but then delete it instead of delivering the email, without notifying the SMTP client.</li> <li>domain-quarantine: Enter to redirect email to the per-domain quarantine. For more information, see the <a href="#">FortiMail Administration Guide</a>. Note that this option is only available with a valid advanced management license.</li> <li>encryption: Apply an encryption profile.</li> <li>none: Apply any configured header or subject line tags, if any.</li> <li>personal-quarantine: Divert the email to the per-recipient quarantine.</li> <li>reject: Reject the email, replying with an SMTP error code to the SMTP client.</li> <li>rewrite-rcpt: Enter to change the recipient address of any email that matches the content profile. Also configure <a href="#">rewrite-rcpt-domain-type</a> {none   prefix   replace   suffix}, <a href="#">rewrite-rcpt-domain-value</a> &lt;case_str&gt;, <a href="#">rewrite-rcpt-local-type</a> {none   prefix   replace   suffix}, and <a href="#">rewrite-rcpt-local-value</a> &lt;value_str&gt;.</li> <li>system-quarantine: Divert the email to the system quarantine.</li> <li>treat-as-spam: Apply the action selected in the antispam profile.</li> </ul>	none
alternate-host {<relay_fqdn>   <relay_ipv4>}	Type the fully qualified domain name (FQDN) or IP address of the alternate relay or SMTP server. This field applies only if <code>alternate-host-status</code> is enable.	
archive-account <account_name>	Type the email archive account name where you want to archive the email. Enable <code>archive-status</code> {enable   disable} to make this function work. For more information about archive accounts, see <a href="#">antispam url-fgas-exempt-list</a> .	
archive-status {enable   disable}	Enable to allow the <code>archive-account</code> <account_name> function to work.	disable
alternate-host-status {enable   disable}	Enable to route the email to a specific SMTP server or relay. Also configure <code>alternate-host</code> {<relay_fqdn>   <relay_ipv4>}.	disable

Variable	Description	Default
	Note: If you enable this setting, for all email that matches the profile, the FortiMail unit will use this destination and ignore <a href="#">mailsetting relay-host-list on page 145</a> and the protected domain's <a href="#">tp-use-domain-mta {yes   no}</a> .	
bcc-addr <recipient_email>	Type the blind carbon copy (BCC) recipient email address. This field applies only if <code>bcc-status</code> is enable.	
bcc-env-from-addr <message_str>	Specify an envelope from BCC address. In the case that email is not deliverable and bounced back, the email is returned to the specified envelope from address instead of the original sender. This is helpful when you want to use a specific email to collect bounce notifications. This field applies only if <code>bcc-env-from-status</code> is enable.	
bcc-env-from-status {enable   disable}	Enable to specify an envelope from address.	disable
bcc-status {enable   disable}	Enable to send a BCC of the email. Also configure <a href="#">suspicious-newsletter-status {enable   disable}</a> .	disable
deliver-to-original-host {enable   disable}	Enable to deliver the message to the original host.	disable
disclaimer-insertion {enable   disable}	Enable to insert disclaimer.	disable
disclaimer-insertion-content <message_name>	Specify the content name to be inserted.	default
disclaimer-insertion-location {beginning   end}	Insert the disclaimer at the beginning or end of the message.	beginning
header-insertion-name	Enter the message header key. The FortiMail unit will add this text to the message header of the email before forwarding it to the recipient.  Many email clients can sort incoming email messages into separate mailboxes based on text appearing in various parts of email messages, including the message header. For details, see the documentation for your email client.  Message header lines are composed of two parts: a key and a value, which are separated by a colon. For example, you might enter: X-Content-Filter: Contains banned word.  If you enter a header line that does not include a colon, the FortiMail unit will automatically append a colon, causing the entire text that you enter to be the key.  <b>Note:</b> Do not enter spaces in the key portion of the header line, as these are forbidden by <a href="#">RFC 2822</a> . Also configure <a href="#">tagging type {insert-header   tag-subject}</a> .	
header-removal-name	Enter the message header name to be removed.	

Variable	Description	Default
header-insertion-value <value_str>	Enter the message header value. The FortiMail unit will add this value to the message header of the email before forwarding it to the recipient. Also configure <a href="#">tagging type {insert-header   tag-subject}</a> .	
notification-profile <profile_name>	Type the name of the notification profile used for sending notifications.	
notification-status {enable   disable}	Enable sending notifications using a notification profile.	disable
remove-header {enable   disable}	Enable removing headers defined in the header removal list. Once enabled, configure <a href="#">header-removal-name</a> under <code>config header-removal-list</code> .	disable
replace-content {enable   disable}	Enable or disable content replacement.	disable
replace-content-message	Enter the name of the custom message for content replacement.	
rewrite-rcpt-domain-type {none   prefix   replace   suffix}	Change the domain part (the portion of the email address after the '@' symbol) of the recipient address of any email that matches the content profile. none: No change. prefix: Enter to prepend the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;case_str&gt;</a> . suffix: Enter to append the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;case_str&gt;</a> . replace: Enter to substitute the part with new text. Also configure <a href="#">rewrite-rcpt-domain-value &lt;case_str&gt;</a> .	none
rewrite-rcpt-domain-value <case_str>	Enter the text for the option (except none) you choose in <a href="#">rewrite-rcpt-domain-type {none   prefix   replace   suffix}</a> .	
rewrite-rcpt-local-type {none   prefix   replace   suffix}	Change the local part (the portion of the email address before the '@' symbol, typically a user name) of the recipient address of any email that matches the content profile. none: No change. prefix: Enter to prepend the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a> . suffix: Enter to append the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a> . replace: Enter to substitute the part with new text. Also configure <a href="#">rewrite-rcpt-local-value &lt;value_str&gt;</a> .	none
rewrite-rcpt-local-value <value_str>	Enter the text for the option (except none) you choose in <a href="#">rewrite-rcpt-local-type {none   prefix   replace   suffix}</a> .	
subject-tagging-text <text_str>	Enter the text that will appear in the subject line of the email, such as "[PROHIBITED-CONTENT]". The FortiMail unit will prepend this text to the subject line of the email before forwarding it to the recipient.	

Variable	Description	Default
	Many email clients can sort incoming email messages into separate mailboxes based on text appearing in various parts of email messages, including the subject line. For details, see the documentation for your email client. Also configure <code>tagging type {insert-header   tag-subject}</code> .	
<code>tagging type {insert-header   tag-subject}</code>	Enter the type of tagging for this profile.	

## Related topics

[profile encryption on page 222 on page 206](#)

## profile cousin-domain

Use this command to mitigate business email compromise (BEC) email-impersonation risks. Domain names may be deliberately misspelled, either by character removal, substitution, and/or transposition, in order to make emails look as though they originate from trusted internal sources.

Configure cousin domains to define those domain names that should be subjected to cousin domain scanning and those domains that are exempt from scanning.

Once created, cousin domain profiles can be referenced in antispam profiles. In addition, cousin domain scan options can be set within antispam profiles. See [set cousin-domain-scan-option {auto-detection body-detection header-detection}](#) for more information.

## Syntax

```
config profile cousin-domain
  edit <profile_name>
    config entry
      edit <entry_int>
        set domain-name <string>
        set domain-name-type {wildcard | regex}
      next
    end
  config exempt
    edit <exempt_int>
      set domain-name <string>
      set domain-name-type {wildcard | regex}
    next
  end
end
```

Variable	Description	Default
<profile_name>	Enter the name of the cousin profile.	
<entry_int>	Enter the entry number of the cousin domain profile. If the entry profile does not currently exist, it will be created.	
<exempt_int>	Enter the entry number of the cousin domain profile. If the exempt profile does not currently exist, it will be created.	
domain-name <string>	Enter the domain name string of the entry rule/exempt rule either as a wildcard or regular expression.	
domain-name-type {wildcard   regex}	Select the domain name type of the entry rule/exempt rule.	regex

## profile dictionary

Use this command to configure dictionary profiles.

Unlike banned words, dictionary terms are UTF-8 encoded, and may include characters other than US-ASCII characters, such as é or ñ.

Dictionary profiles can be grouped or used individually by antispam or content profiles to detect spam, banned content, or content that requires encryption to be applied.

## Syntax

```

config profile dictionary
  edit <profile_name>
    config item
      edit <item_int>
        set pattern <pattern_str>
        set pattern-comments <comment_str>
        set pattern-type {ABAROUTING | CANSIN | CUSIP | CreditCard | ISIN | USSSN | regex |
          wildcard}
        set pattern-weight <weight_int>
        set pattern-scan-area {header | body}
        set pattern-status {enable | disable}
        set pattern-max-weight <weight_int>
        set pattern-max-limit {enable | disable}
      end
    end
  end

```

Variable	Description	Default
<profile_name>	Enter the name of the profile.	
<item_int>	Enter the index number for the pattern entry where you can add a word or phrase to the dictionary.	

Variable	Description	Default
pattern <pattern_str>	<p>For a predefined pattern, enter a value to change the predefined pattern name.</p> <p>For a use-defined pattern, enter a word or phrase that you want the dictionary to match, expressed either verbatim, with wild cards, or as a regular expression. Regular expressions do not require slash (/) boundaries. For example, enter: <code>v[i1]agr?a</code></p> <p>Matches are case insensitive and can occur over multiple lines as if the word were on a single line (that is, Perl-style match modifier options <code>i</code> and <code>s</code> are in effect).</p> <p>The FortiMail unit will convert the encoding and character set into UTF-8, the same encoding in which dictionary patterns are stored, before evaluating an email for a match with the pattern. Because of this, your pattern must match the UTF-8 string, not the originally encoded string. For example, if the original encoded string is:  <code>=?iso-8859-1?B?U2UgdHJhdGEgZGVsIHNwYW0uCG==?=</code>  the pattern must match:  Se trata del spam.  Entering the pattern <code>*iso-8859-1*</code> would <b>not</b> match.</p>	
pattern-comments <comment_str>	Enter any description for the pattern.	
pattern-type {ABAROUTING   CANSIN   CUSIP   CreditCard   ISIN   USSSN   regex   wildcard}	<p>Enter <code>ABAROUTING</code>, <code>CANSIN</code>, <code>CUSIP</code>, <code>CreditCard</code>, <code>ISIN</code>, or <code>USSSN</code> for predefined patterns.</p> <p><code>ABAROUTING</code>: A routing transit number (RTN) is a nine digit bank code, used in the United States, which appears on the bottom of negotiable instruments such as checks identifying the financial institution on which it was drawn.</p> <p><code>CANSIN</code>: Canadian Social Insurance Number. The format is three groups of three digits, such as 649 242 666.</p> <p><code>CUSIP</code>: CUSIP typically refers to both the Committee on Uniform Security Identification Procedures and the 9-character alphanumeric security identifiers that they distribute for all North American securities for the purposes of facilitating clearing and settlement of trades.</p> <p><code>CreditCard</code>: Major credit card number formats.</p> <p><code>ISIN</code>: An International Securities Identification Number (ISIN) uniquely identifies a security. Securities for which ISINs are issued include bonds, commercial paper, equities and warrants. The ISIN code is a 12-character alpha-numerical code that does not contain information characterizing financial instruments but serves for uniform identification of a security at trading and settlement.</p> <p><code>USSSN</code>: United States Social Security number. The format is a nine digit number, such as 078051111.</p> <p>For user-defined patterns, enter either:  <code>wildcard</code>: Pattern is verbatim or uses only simple wild cards (<code>?</code> or <code>*</code>).  <code>regex</code>: Pattern is a Perl-style regular expression.</p>	regex
pattern-weight <weight_int>	Enter a number by which an email's dictionary match score will be incremented for each word or phrase it contains that matches this pattern.	1

Variable	Description	Default
	The dictionary match score may be used by content monitor profiles to determine whether or not to apply the content action.	
pattern-scan-area {header   body}	Enter header to match occurrences of the pattern when it is located in an email's message headers, including the subject line, or body to match occurrences of the pattern when it is located in an email's message body.	
pattern-status {enable   disable}	Enable or disable a pattern in a profile.	disable
pattern-max-weight <weight_int>	Enter the maximum by which matches of this pattern can contribute to an email's dictionary match score.	1
pattern-max-limit {enable   disable}	Enable if the pattern must not be able to increase an email's dictionary match score more than the amount configured in <a href="#">pattern-max-weight &lt;weight_int&gt;</a> .	disable

## Related topics

[profile dictionary-group on page 220](#)

## profile dictionary-group

Use this command to create groups of dictionary profiles.

Dictionary groups can be useful when you want to use multiple dictionary profiles during the same scan.

For example, you might have several dictionaries of prohibited words — one for each language — that you want to use to enforce your network usage policy. Rather than combining the dictionaries or creating multiple policies and multiple content profiles to apply each dictionary profile separately, you could simply group the dictionaries, then select that group in the content monitor profile.

Before you can create a dictionary group, you must first create one or more dictionary profiles. For more information about dictionary profiles, see [profile dictionary on page 218](#).

## Syntax

```
config profile dictionary-group
  edit <group_name>
    config dictionaries
      edit <dictionary_name>
    end
  end
```

Variable	Description	Default
<group_name>	Enter the name of the dictionary group.	
<dictionary_name>	Enter the dictionary that you want to include in the dictionary group.	

## Related topics

[profile dictionary on page 218](#)

## profile dlp

Use this command to add scan rules/conditions to Data Loss Prevention (DLP) profiles. Specify what actions to take and then apply DLP profiles to IP or recipient based policies.

## Syntax

```

config profile dlp
  edit <profile name>
    config content-scan
      edit <rule_order>
        set action {Discard | Encrypt_Pull | Reject | Replace | SystemQuarantine |
                  UserQuarantine}
        set name <scan_rule_name>
        set status {enable | disable}
      end
      set comment <string>
      set action-default {Discard | Encrypt_Pull | Reject | Replace | SystemQuarantine |
                        UserQuarantine}
    end
  end
end

```

Variable	Description	Default
action {Discard   Encrypt_Pull   Reject   Replace   SystemQuarantine   UserQuarantine}	Specify the action for this rule.	
name <scan_rule_name>	Enter a scan rule name.	
status {enable   disable}	Enable or disable this rule.	enable
comment <string>	Enter optional comments for the profile.	
action-default {Discard   Encrypt_Pull   Reject   Replace   SystemQuarantine   UserQuarantine}	Specify the default action for this profile.	

## profile email-address-group

Use this command to create groups of email addresses.

Email groups include groups of email addresses that are used when configuring access control rules. For information about access control rules, see [ms365 profile antivirus on page 158](#).

### Syntax

```
config profile email-address-group
  edit <group_name>
    config member
      edit <email_address>
    end
  end
```

Variable	Description	Default
<group_name>	Enter the name of the email address group.	
<email_address>	Enter the email address that you want to include in the email group.	

### Related topics

[ms365 profile antivirus](#)

## profile encryption

Use this command to create encryption profiles, which contain encryption settings for secure MIME (S/MIME).

Encryption profiles, unlike other types of profiles, are applied through message delivery rules, not policies.

### Syntax

```
config profile encryption
  edit password <password_str>
    set encryption-algorithm {aes128 | aes192 | aes256 | cast5 | tripledes}
    set action-on-failure {drop | send | tls}
    set max-push-size <size_int>
    set protocol {smime | ibe}
    set retrieve-action {push | pull}
  end
```

Variable	Description	Default
<profile_name>	Enter the name of the encryption profile.	
encryption-algorithm {aes128   aes192   aes256   cast5   tripledes}	Enter the encryption algorithm that will be used with the sender's private key in order to encrypt the email.	aes128
action-on-failure {drop   send   tls}	Enter the action the FortiMail unit takes when identity-based encryption cannot be used, either:  drop: Send a delivery status notification (DSN) email to the sender's email address, indicating that the email is permanently undeliverable.  send: Deliver the email without encryption.	drop
max-push-size <size_int>	The maximum message size (in KB) of the secure mail delivered (or pushed) to the recipient. Messages that exceed this size are delivered via pull. The size cannot exceed 10240KB.  This option applies to the IBE protocol only.	2048
protocol {smime   ibe}	The protocol used for this profile, S/MIME or IBE.	smime
retrieve-action {push   pull}	The action used by the mail recipients to retrieve IBE messages.  push: A notification and a secure mail is delivered to the recipient who needs to go to the FortiMail unit to open the message. The FortiMail unit does not store the message.  pull: A notification is delivered to the recipient who needs to go to the FortiMail unit to open the message. The FortiMail unit stores the message.  This option applies to the IBE protocol only.	push

## Related topics

[profile authentication on page 200](#)

## profile geoip-group

Use this command to create groups of GeoIP addresses.

FortiMail utilizes the GeoIP database to map the geolocations of client IP addresses. You can use GeoIP groups in access control rules and IP-based policies to geo-targeting spam and virus devices.

## Syntax

```
config profile geoip-group
  edit <profile_name>
    set description "<comment_str>"
    set country {ZZ | 01 | AD | ...}
  end
```

Variable	Description	Default
<profile_name>	Enter the name of the profile.	
description "<comment_str>"	Enter a description or comment.	
country {ZZ   O1   AD  ...}	Assign countries to the GeoIP address group. Enter set country ? to display all available countries. For multiple countries, separate each entry with a space.	

## profile impersonation

Email impersonation is one of the email spoofing attacks. It forges the email header to deceive the recipient because the message appears to be from a different source than the actual address.

To fight against email impersonation, you can map high valued target display names with correct email addresses and FortiMail can check for the mapping. For example, an external spammer wants to impersonate the CEO of your company(ceo@company.com). The spammer will put "CEO ABC <ceo@external.com>" in the Email header From, and send such email to a user(victim@company.com). If FortiMail has been configured with a manual entry "CEO ABC"/"ceo@company.com" in an impersonation analysis profile to indicate the correct display name/email pair, or it has learned display name/email pair through the dynamic process, then such email will be detected by impersonation analysis, because the spammer uses an external email address and an internal user's display name.

You can also add empty entries to force the FortiMail to skip impersonation analysis.

There are two ways to do the mapping:

- **Manual:** you manually enter mapping entries and create impersonation analysis profiles as described below.
- **Dynamic:** FortiMail Mail Statistics Service can automatically learn the mapping.

## Syntax

```
config impersonation
  edit <name> on page 225
    config entry
      edit <entry> on page 225
        set display-name on page 225
        set display-name-type on page 225
        set email-address on page 225
      config exempt
        edit <entry>
          set display-name on page 225
          set display-name-type on page 225
          set email-address on page 225
        end
    end
  end
```

Variable	Description	Default
<name>	Enter the profile name.	
<entry>	Enter the profile entry	
display-name	Enter the display name to be mapped to the email address. You can use the wildcard or regular expression.	
display-name-type	Enter the display name pattern	
email-address	Enter the email address to be mapped to the display name. The email address can be from protected/internal domains or unprotected/external domains.	

## profile ip-address-group

Use this command to create groups of IP addresses.

IP groups include groups of IP addresses that are used when configuring access control rules. For information about access control rules, see [ms365 profile antivirus on page 158](#).

## Syntax

```
config profile ip-address-group
  edit <name>
    config member
      edit <ip/mask>
        set comment <string>
    end
end
```

Variable	Description	Default
<name>	Enter the name of the IP address group.	
<ip/mask>	<p>Enter the Enter the IP address and netmask that you want to include in the email group. Use the netmask, the portion after the slash (/), to specify the matching subnet.</p> <p>For example, enter 10.10.10.10/24 to match a 24-bit subnet, or all addresses starting with 10.10.10. This will appear as 10.10.10.0/24 in the access control rule table, with the 0 indicating that any value is matched in that position of the address.</p> <p>Similarly, 10.10.10.10/32 will appear as 10.10.10.10/32 and match only the 10.10.10.10 address.</p> <p>To match any address, enter 0.0.0.0/0.</p>	

## Related topics

[ms365 profile antivirus](#)

## profile ip-pool

Use this command to define a range of IP addresses. IP pools can be used in multiple ways:

- To define destination IP addresses of multiple protected SMTP servers if you want to load balance **incoming** email between them.
- To define source IP addresses used by the FortiMail unit if you want **outgoing** email to originate from a range of IP addresses.

Each email that the FortiMail unit sends will use the next IP address in the range. When the last IP address in the range is used, the next email will use the first IP address.

For more information, see the [FortiMail Administration Guide](#).

## Syntax

```
config profile ip-pool
  edit <profile_name>
    set iprange {enable | disable}
end
```

Variable	Description	Default
<profile_name>	Enter the name of the IP pool profile.	
iprange {enable   disable}	Enter the first and last IP address in each contiguous range included in the profile.	

## profile ldap

Use this command to configure LDAP profiles which can query LDAP servers for authentication, email address mappings, and more.



Before using an LDAP profile, verify each LDAP query and connectivity with your LDAP server. When LDAP queries do not match with the server's schema and/or contents, unintended mail processing behaviors can result, including bypassing antivirus scans. For details on preparing an LDAP directory for use with FortiMail LDAP profiles, see the [FortiMail Administration Guide](#).

LDAP profiles each contain one or more queries that retrieve specific configuration data, such as user groups, from an LDAP server.

## Syntax

```
config profile ldap
edit <profile_name>
    set access-override {enable | disable}
    set access-override-attribute <attribute_str>
    set address-map-state {enable | disable}
    set alias-base-dn <dn_str>
    set alias-bind-dn <bind_dn_str>
    set alias-bind-password <bindpw_str>
    set alias-dereferencing {never | always | search | find}
    set alias-expansion-level <limit_int>
    set alias-group-expansion-state {enable | disable}
    set alias-group-member-attribute <attribute_str>
    set alias-group-query <query_str>
    set alias-member-mail-attribute <attribute_str>
    set alias-member-query <query_str>
    set alias-schema {activedirectory | dominoperson | inetlocalmailrcpt | inetorgperson |
        userdefined}
    set alias-scope {base one | sub}
    set alias-state {enable | disable}
    set antisppam <attribute_str>
    set webmail-language <language_name>
    set asav-state {enable | disable}
    set auth-bind-dn {cnid | none | searchuser | upn}
    set authstate {enable | disable}
    set base-dn <basedn_str>
    set bind-dn <binddn_str>
    set bind-password <bindpw_str>
    set cache-state {enable | disable}
    set cache-ttl <tll_int>
    set set chain
    set set chain-status {enable | disable}
    set cnid-name <cnid_str>
    set content <string>
    set dereferencing {never | always | search | find}
    set display-name
    set domain-antispam-attr <attribute_str>
    set domain-antivirus-attr <attribute_str>
    set domain-content-attr
    set domain-override {enable | disable}
    set domain-override-attribute
    set domain-parent-attr <attribute_str>
    set domain-query <query_str>
    set domain-routing-mail-host-attr <attribute_str>
    set domain-state {enable | disable}
    set external-address <attribute_str>
    set fallback-port <port_int>
    set fallback-server {<fqdn_str> | <server_ipv4>}
    set group-base-dn <basedn_str>
    set group-expansion-level
    set group-membership-attribute <attribute_str>
    set quarantine-report-to-ldap-groupowner {enable | disable}
    set group-owner {enable | disable}
    set group-owner-address-attribute <attribute_str>
    set group-owner-attribute <attribute_str>
```

```

set group-relative-name {enable | disable}
set server-name <name_str>
set groupstate {enable | disable}
set internal-address <attribute_str>
set port <port_int>
set query <query_str>
set rcpt-vrfy-bypass {enable | disable}
set referrals-chase {enable | disable}
set routing-mail-host <attribute_str>
set routing-mail-addr <attribute_str>
set routing-state {enable | disable}
set schema {activedirectory | dominoperson | inetlocalmailrcpt | inetorgperson |
  userdefined}
set scope {base | one | sub}
set secure {none | ssl}
set server <name_str>
set timeout <timeout_int>
set unauth-bind {enable | disable}
set upn-suffix <upns_str>
set version {ver2 | ver3}
set webmail-password-change {enable | disable}
set webmail-password-schema {openldap | activedirectory}
end

```

Variable	Description	Default
<profile_name>	Enter the name of the LDAP profile.	
access-override {enable   disable}	Enable to override the access profile you specify when you add an administrator with the value of the remote attribute returned from the LDAP server, if the returned value matches an existing access profile. If there is no match, the specified access profile will still be used. Also specify the access profile attribute.	disable
access-override-attribute <attribute_str>	Specify the access profile attribute.	
address-map-state {enable   disable}	Enable to query the LDAP server defined in the LDAP profile for user objects' mappings between email addresses.	disable
alias-base-dn <dn_str>	Enter the distinguished name (DN) of the part of the LDAP directory tree within which the FortiMail will search for either alias or user objects. User or alias objects should be child nodes of this location. Whether you should specify the base DN of either user objects or alias objects varies by your LDAP schema style. Schema may resolve alias email addresses directly or indirectly (using references).	

Variable	Description	Default
	<p>Direct resolution: Alias objects directly contain one or more email address attributes, such as <code>mail</code> or <code>rfc822MailMember</code>, whose values are user email addresses such as <code>user@example.com</code>, and that resolves the alias. The Base DN, such as <code>ou=Aliases,dc=example,dc=com</code>, should contain alias objects.</p> <p>Indirect resolution: Alias objects do <b>not</b> directly contain an email address attribute that can resolve the alias; instead, in the style of LDAP group-like objects, the alias objects contain only references to user objects that are “members” of the alias “group.” User objects’ email address attribute values, such as <code>user@example.com</code>, actually resolve the alias. Alias objects refer to user objects by possessing one or more “member” attributes whose value is the DN of a user object, such as <code>uid=user,ou=People,dc=example,dc=com</code>. The FortiMail unit performs a first query to retrieve the distinguished names of “member” user objects, then performs a second query using those distinguished names to retrieve email addresses from each user object. The Base DN, such as <code>ou=People,dc=example,dc=com</code>, should contain user objects.</p>	
<code>alias-bind-dn &lt;bind_dn_str&gt;</code>	<p>Enter the bind DN, such as <code>cn=FortiMailA,dc=example,dc=com</code>, of an LDAP user account with permissions to query the basedn.</p> <p>This command may be optional if your LDAP server does not require the FortiMail unit to authenticate when performing queries, and if you have enabled <code>unauth-bind {enable   disable}</code>.</p>	
<code>alias-bind-password &lt;bindpw_str&gt;</code>	Enter the password of <code>alias-bind-dn &lt;bind_dn_str&gt;</code> .	
<code>alias-dereferencing {never   always   search   find}</code>	<p>Select the method to use, if any, when dereferencing attributes whose values are references:</p> <ul style="list-style-type: none"> <li>• <code>never</code>: Do not dereference.</li> <li>• <code>always</code>: Always dereference.</li> <li>• <code>search</code>: Dereference only when searching.</li> <li>• <code>find</code>: Dereference only when finding the base search object.</li> </ul>	never
<code>alias-expansion-level &lt;limit_int&gt;</code>	Enter the maximum number of alias nesting levels that aliases the FortiMail unit will expand.	0
<code>alias-group-expansion-state {enable   disable}</code>	Enable if your LDAP schema resolves email aliases indirectly. For more information on direct vs. indirect resolution, see <code>alias-base-dn &lt;dn_str&gt;</code> .	disable

Variable	Description	Default
	<p>When this option is <b>disabled</b>, alias resolution occurs using <b>one</b> query. The FortiMail unit queries the LDAP directory using the <code>basedn</code> and the <code>alias-member-query</code>, and then uses the value of each <code>alias-member-mail-attribute</code> to resolve the alias.</p> <p>When this option is <b>enabled</b>, alias resolution occurs using <b>two</b> queries:</p> <p>The FortiMail unit first performs a preliminary query using the <code>basedn</code> and <code>alias-group-query</code>, and uses the value of each <code>alias-group-member-attribute</code> as the base DN for the second query.</p> <p>The FortiMail unit performs a second query using the distinguished names from the preliminary query (instead of the <code>basedn</code>) and the <code>alias-member-query</code>, and then uses the value of each <code>alias-member-mail-attribute</code> to resolve the alias.</p> <p>The two-query approach is appropriate if, in your schema, alias objects are structured like group objects and contain references in the form of distinguished names of member user objects, rather than directly containing email addresses to which the alias resolves. In this case, the FortiMail unit must first "expand" the alias object into its constituent user objects before it can resolve the alias email address.</p>	
<code>alias-group-member-attribute &lt;attribute_str&gt;</code>	<p>Enter the name of the attribute for the group member, such as <code>member</code>, whose value is the DN of a user object.</p> <p>This attribute must be present in alias objects only if they do not contain an email address attribute specified in <a href="#">alias-member-mail-attribute &lt;attribute_str&gt;</a>.</p>	
<code>alias-group-query &lt;query_str&gt;</code>	<p>Enter an LDAP query filter that selects a set of alias objects, represented as a group of member objects in the LDAP directory.</p> <p>The query filter string filters the result set, and should be based upon any attributes that are common to all alias objects but also exclude non-alias objects.</p> <p>For example, if alias objects in your directory have two distinguishing characteristics, their <code>objectClass</code> and <code>proxyAddresses</code> attributes, the query filter might be: <code>(&amp;(objectClass=group) (proxyAddresses=smtp:\$m))</code> where <code>\$m</code> is the FortiMail variable for an email address.</p>	
<code>alias-member-mail-attribute &lt;attribute_str&gt;</code>	<p>Enter the name of the attribute for the alias member's mail address, such as <code>mail</code> or <code>rfc822MailMember</code>, whose value is an email address to which the email alias resolves, such as <code>user@example.com</code>.</p>	

Variable	Description	Default
	This attribute must be present in either alias or user objects, as determined by your schema and whether it resolves aliases directly or indirectly.	
alias-member-query <query_str>	<p>Enter an LDAP query filter that selects a set of either user or email alias objects, whichever object class contains the attribute you configured in <a href="#">alias-member-mail-attribute &lt;attribute_str&gt;</a>, from the LDAP directory.</p> <p>The query filter string filters the result set, and should be based upon any attributes that are common to all user/alias objects but also exclude non-user/alias objects.</p> <p>For example, if user objects in your directory have two distinguishing characteristics, their objectClass and mail attributes, the query filter might be: ( &amp; (objectClass=alias) (mail=\$m) ) where \$m is the FortiMail variable for a user's email address.</p>	
alias-schema {activedirectory   dominoperson   inetlocalmailrcpt   inetorgperson   userdefined}	Enter either the name of the LDAP directory's schema, or enter userdefined to indicate a custom schema.	inetorgperson
alias-scope {base   one   sub}	<p>Enter which level of depth to query:</p> <ul style="list-style-type: none"> <li>base: Query the basedn level.</li> <li>one: Query only the one level directly below the basedn in the LDAP directory tree.</li> <li>sub: Query recursively all levels below the basedn in the LDAP directory tree.</li> </ul>	sub
alias-state {enable   disable}	Enable to query user objects for email address aliases.	disable
antispam <attribute_str>	Enter the name of the attribute, such as antispam, whose value indicates whether or not to perform antispam processing for that user.	
antivirus <attribute_str>	Enter the name of the attribute, such as antivirus, whose value indicates whether or not to perform antivirus processing for that user.	
asav-state {enable   disable}	Enable to query user objects for mappings between internal and external email addresses.	disable
auth-bind-dn {cnid   none   searchuser   upn}	<p>Enter either none to not define a user authentication query, or one of the following to define a user authentication query:</p> <p>cnid: Enter the name of the user objects' common name attribute, such as cn or uid.</p>	searchuser

Variable	Description	Default
	<p>searchuser: Enter to form the user's bind DN by using the DN retrieved for that user</p> <p>This command applies only if <code>schema</code> is <code>userdefined</code> in <a href="#">"set ldap_profile profile user" on page 2407..</a></p> <p>upn: Enter to form the user's bind DN by prepending the user name portion of the email address (<code>\$u</code>) to the User Principle Name (UPN, such as <code>example.com</code>). By default, the FortiMail unit will use the mail domain as the UPN. If you want to use a UPN other than the mail domain, also configure <code>upn-suffix &lt;upns_str&gt;</code>.</p>	
authstate {enable   disable}	Enable to perform user authentication queries.	disable
base-dn <basedn_str>	<p>Enter the distinguished name (DN) of the part of the LDAP directory tree within which the FortiMail unit will search for user objects, such as <code>ou=People,dc=example,dc=com</code>.</p> <p>User objects should be child nodes of this location.</p>	
bind-dn <binddn_str>	<p>Enter the bind DN, such as <code>cn=FortiMailA,dc=example,dc=com</code>, of an LDAP user account with permissions to query the <code>basedn</code>.</p> <p>This command may be optional if your LDAP server does not require the FortiMail unit to authenticate when performing queries, and if you have enabled <code>unauth-bind {enable   disable}</code>.</p>	
bind-password <bindpw_str>	Enter the password of <code>bind-dn &lt;binddn_str&gt;</code> .	
cache-state {enable   disable}	<p>Enable to cache LDAP query results.</p> <p>Caching LDAP queries can introduce a delay between when you update LDAP directory information and when the FortiMail unit begins using that new information, but also has the benefit of reducing the amount of LDAP network traffic associated with frequent queries for information that does not change frequently.</p> <p>If this option is enabled but queries are not being cached, inspect the value of TTL. Entering a TTL value of <code>0</code> effectively disables caching.</p>	disable
cache-ttl <tll_int>	Enter the amount of time, in minutes, that the FortiMail unit will cache query results. After the TTL has elapsed, cached results expire, and any subsequent request for that information causes the FortiMail unit to query the LDAP server, refreshing the cache.	1440

Variable	Description	Default
	The default TTL value is 1,440 minutes (one day). The maximum value is 10,080 minutes (one week). Entering a value of 0 effectively disables caching.	
set chain	Enter the LDAP profile you wish to add the group of other LDAP profiles to create a chain query.	
set chain-status {enable   disable}	Enable the chain query.	disable
cnid-name <cnid_str>	Enter the name of the user objects' common name attribute, such as cn or uid.	
content <string>	Enter the name of the attribute, such as genericContent, whose value is the name of the content profile assigned to the domain.  The name of this attribute may vary by the schema of your LDAP directory.  If you do not specify this attribute at all (that is, leave this field blank), the content profile in the matched recipient-based policy will be used.	
dereferencing {never   always   search   find}	Select the method to use, if any, when dereferencing attributes whose values are references. <ul style="list-style-type: none"> <li>• never: Do not dereference.</li> <li>• always: Always dereference.</li> <li>• search: Dereference only when searching.</li> <li>• find: Dereference only when finding the base search object.</li> </ul>	never
display-name	Enter the LDAP address mapping display name attribute.	
domain-antispam-attr <attribute_str>	Enter the name of the antispam profile attribute, such as businessCategory, whose value is the name of the antispam profile assigned to the domain.  The name of this attribute may vary by the schema of your LDAP directory.	
domain-antivirus-attr <attribute_str>	Enter the name of the antivirus profile attribute, such as preferredLanguage, whose value is the name of the antivirus profile assigned to the domain.  The name of this attribute may vary by the schema of your LDAP directory.	
domain-content-attr	Enter the content attribute name.	
domain-override {enable   disable}	Enable or disable system admin domain override.	
domain-override-attribute	Enter the system admin domain override attribute.	

Variable	Description	Default
domain-parent-attr <attribute_str>	<p>Enter the name of the parent domain attribute, such as <code>description</code>, whose value is the name of the parent domain from which a domain inherits the specific RCPT check settings and quarantine report settings.</p> <p>The name of this attribute may vary by the schema of your LDAP directory.</p>	
domain-query <query_str>	<p>Enter an LDAP query filter that selects a set of domain objects, whichever object class contains the attribute you configured for this option, from the LDAP directory.</p> <p>For details on query syntax, refer to any standard LDAP query filter reference manual.</p> <p>For this option to work, your LDAP directory should contain a single generic user for each domain. Wildcard users (e.g. <code>*@\$d</code>) are also supported for domain query, in cases where there is no generic domain user.</p> <p>The user entry should be configured with attributes to represent the following:</p> <ul style="list-style-type: none"> <li>parent domain from which a domain inherits the specific RCPT check settings and quarantine report settings. For example, <code>description=parent.com</code></li> <li>IP address of the backend mail server hosting the mailboxes of the domain. For example, <code>mailHost=192.168.1.105</code></li> <li>antispam profile assigned to the domain. For example, <code>businessCategory=parentAntispam</code></li> <li>antivirus profile assigned to the domain. For example, <code>preferredLanguage=parentAntivirus</code></li> </ul>	
domain-routing-mail-host-attr <attribute_str>	<p>Enter the name of the mail host attribute, such as <code>mailHost</code>, whose value is the name of the IP address of the backend mail server hosting the mailboxes of the domain.</p> <p>The name of this attribute may vary by the schema of your LDAP directory.</p>	
domain-state {enable   disable}	<p>Enable or disable the domain lookup option.</p> <p>For more information about domain lookup, see <a href="#">domain-query &lt;query_str&gt; on page 234</a>.</p>	disable
external-address <attribute_str>	<p>Enter the name of the attribute, such as <code>externalAddress</code>, whose value is an email address in the same or another protected domain.</p>	extAddress

Variable	Description	Default
	<p>This email address will be rewritten into the value of <code>internal-address &lt;attribute_str&gt;</code> according to the match conditions and effects described in <a href="#">Match evaluation and rewrite behavior for email address mappings: on page 241</a>.</p> <p>The name of this attribute may vary by the schema of your LDAP directory.</p>	
fallback-port <port_int>	<p>If you have configured a backup LDAP server that listens on a nonstandard port number, enter the TCP port number.</p> <p>The standard port number for LDAP is 389. The standard port number for SSL-secured LDAP is 636.</p> <p>The FortiMail unit will use SSL-secured LDAP to connect to the server if <code>secure</code> is <code>ssl</code>.</p>	389
fallback-server {<fqdn_str>   <server_ipv4>}	<p>Enter either the fully qualified domain name (FQDN) or IP address of the backup LDAP server.</p> <p>If there is no fallback server, enter an empty string ( " ).</p>	
group-base-dn <basedn_str>	<p>Enter the base DN portion of the group's full DN, such as <code>ou=Groups,dc=example,dc=com</code>.</p> <p>This command applies only if <code>group-relative-name</code> is <code>enable</code>.</p>	
group-expansion-level	<p>Enter how many levels of nested groups will be expanded for lookup. Valid range is 1-6.</p>	1
group-membership-attribute <attribute_str>	<p>Enter the name of the attribute, such as <code>memberOf</code> or <code>gidNumber</code>, whose value is the group number or DN of a group to which the user belongs.</p> <p>This attribute must be present in user objects.</p> <p>Whether the value must use common name, group number, or DN syntax varies by your LDAP server schema. For example, if your user objects use both <code>inetOrgPerson</code> and <code>posixAccount</code> schema, user objects have the attribute <code>gidNumber</code>, whose value must be an integer that is the group ID number, such as <code>10000</code>.</p>	
group-name-attribute <attribute_str>	<p>Enter the name of the attribute, such as <code>cn</code>, whose value is the group name of a group to which the user belongs.</p> <p>This command applies only if <code>group-relative-name</code> is <code>enable</code>.</p>	

Variable	Description	Default
group-owner {enable   disable}	Enable to query the group object by its distinguished name (DN) to retrieve the DN of the group owner, which is a user that will receive that group's spam reports. Using that user's DN, the FortiMail unit will then perform a second query to retrieve that user's email address, where the spam report will be sent. For more information on sending spam reports to the group owner, see <a href="#">config domain-setting on page 108</a> .	disable
group-owner-address-attribute <attribute_str>	Enter the name of the attribute, such as mail, whose value is the group owner's email address. If group-owner is enable, this attribute must be present in user objects.	
group-owner-attribute <attribute_str>	Enter the name of the attribute, such as groupOwner, whose value is the distinguished name of a user object. You can configure the FortiMail unit to allow that user to be responsible for handling the group's spam report. If group-owner is enable, this attribute must be present in group objects.	
group-relative-name {enable   disable}	Enable to specify the base distinguished name (DN) portion of the group's full distinguished name (DN) in the LDAP profile. By specifying the group's base DN and the name of its group name attribute in the LDAP profile, you will only need to supply the group name value when configuring each feature that uses this query. For example, you might find it more convenient in each recipient-based policy to type only the group name, admins, rather than typing the full DN, cn=admins,ou=Groups,dc=example,dc=com. In this case, you could enable this option, then basedn (ou=Groups,dc=example,dc=com) and groupnameattribute (cn). When performing the query, the FortiMail unit would assemble the full DN by inserting the common name that you configured in the recipient-based policy between the groupnameattribute and the basedn configured in the LDAP profile. Note: Enabling this option is appropriate <b>only if</b> your LDAP server's schema specifies that the group membership attribute's value must use DN syntax. It is <b>not</b> appropriate if this value uses another type of syntax, such as a number or common name.	disable

Variable	Description	Default
	<p>For example, if your user objects use both <code>inetOrgPerson</code> and <code>posixAccount</code> schema, user objects have the attribute <code>gidNumber</code>, whose value must be an integer that is the group ID number, such as <code>10000</code>. Because a group ID number does not use DN syntax, you would not enable this option.</p>	
<code>group-virtual</code> {enable   disable}	<p>Enable to use objects within the base DN of <code>base-dn &lt;basedn_str&gt;</code> as if they were members of a user group object.</p> <p>For example, your LDAP directory might not contain user group objects. In that sense, groups do not really exist in the LDAP directory. However, you could mimic a group's presence by enabling this option to treat all users that are child objects of the base DN in the user object query as if they were members of such a group.</p>	disable
<code>groupstate</code> {enable   disable}	Enable to perform LDAP group queries.	disable
<code>internal-address</code> <attribute_str>	<p>Enter the name of the LDAP attribute, such as <code>internalAddress</code>, whose value is an email address in the same or another protected domain.</p> <p>This email address will be rewritten into the value of <code>external-address &lt;attribute_str&gt;</code> according to the match conditions and effects described in <a href="#">Match evaluation and rewrite behavior for email address mappings: on page 241</a>.</p> <p>The name of this attribute may vary by the schema of your LDAP directory.</p>	intAddress
<code>port &lt;port_int&gt;</code>	<p>If you have configured a backup LDAP server that listens on a nonstandard port number, enter the TCP port number.</p> <p>The standard port number for LDAP is 389. The standard port number for SSL-secured LDAP is 636.</p>	389
<code>query &lt;query_str&gt;</code>	<p>Enter an LDAP query filter, enclosed in single quotes ( ' ), that selects a set of user objects from the LDAP directory. The query filter string filters the result set, and should be based upon any attributes that are common to all user objects but also exclude non-user objects.</p> <p>For example, if user objects in your directory have two distinguishing characteristics, their <code>objectClass</code> and <code>mail</code> attributes, the query filter might be: ( &amp; ( objectClass=inetOrgPerson ) ( mail=\$m ) ) where <code>\$m</code> is the FortiMail variable for a user's email address.</p>	( & ( objectClass=inetOrgPerson ) ( mail=\$m ) )

Variable	Description	Default
	<p>If the email address (\$m) as it appears in the message header is different from the user's email address as it appears in the LDAP directory, such as when you have enabled recipient tagging, a query for the user by the email address (\$m) may fail. In this case, you can modify the query filter to subtract prepended or appended text from the user name portion of the email address before performing the LDAP query. For example, to subtract "-spam" from the <b>end</b> of the user name portion of the recipient email address, you could use the query filter:</p> <pre>(&amp; (objectClass=inetOrgPerson) (mail=\$m\$ {-spam}))</pre> <p>where \${-spam} is the FortiMail variable for the tag to remove before performing the query. Similarly, to subtract "spam-" from the <b>beginning</b> of the user name portion of the recipient email address, you could use the query filter: <pre>(&amp; (objectClass=inetOrgPerson) (mail=\$m\$ {^spam-}))</pre> <p>where \${^spam-} is the FortiMail variable for the tag to remove before performing the query.</p> <p>For some schemas, such as Microsoft Active Directory-style schemas, this query will retrieve both the user's primary email address and the user's alias email addresses. If your schema style is different, you may want to also configure an alias query to resolve aliases.</p> <p>For details on query syntax, refer to any standard LDAP query filter reference manual.</p> <p>This command applies only if schema is userdefined.</p> </p>	
rcpt-vrfy-bypass {enable   disable}	If you have selected using LDAP server to verify recipient address and your LDAP server is down, enabling this option abandons recipient address verification and the FortiMail unit will continue relaying email.	disable
referrals-chase {enable   disable}	Enable chase referrals.	disable
routing-mail-host <attribute_str>	Enter the name of the LDAP attribute, such as mailHost, whose value is the fully qualified domain name (FQDN) or IP address of the email server that stores email for the user's email account.	mailHost
routing-mail-addr <attribute_str>	Enter the name of the LDAP attribute, such as mailRoutingAddress, whose value is the email address of a deliverable user on the email server, also known as the mail host.	mailRoutingAddress

Variable	Description	Default
	<p>For example, a user may have many aliases and external email addresses that are not necessarily known to the email server. These addresses would all map to a real email account (mail routing address) on the email server (mail host) where the user's email is actually stored.</p> <p>A user's recipient email address located in the envelope or header portion of each email will be rewritten to this address.</p>	
routing-state {enable   disable}	Enable to perform LDAP queries for mail routing.	disable
schema {activedirectory   dominoperson   inetlocalmailrcpt   inetorgperson   userdefined}	<p>Enter either the name of the LDAP directory's schema, or enter <code>userdefined</code> to indicate a custom schema.</p> <p>If you enter <code>userdefined</code>, you must configure query.</p>	inetorgperson
scope {base   one   sub}	<p>Enter which level of depth to query:</p> <p>base: Query the basedn level.</p> <p>one: Query only the one level directly below the basedn in the LDAP directory tree.</p> <p>sub: Query recursively all levels below the basedn in the LDAP directory tree.</p>	sub
secure {none   ssl}	<p>Enter a value to indicate whether or not to connect to the LDAP server(s) using an encrypted connection.</p> <p>none: Use a non-secure connection.</p> <p>SSL: Use an SSL-secured (LDAPS) connection.</p> <p>Note: If your FortiMail unit is deployed in server mode, and you want to enable <a href="#">webmail-password-change {enable   disable}</a> using an LDAP server that uses a Microsoft ActiveDirectory-style schema, you must select <b>SSL</b>. ActiveDirectory servers require a secure connection for queries that change user passwords.</p>	none
server <name_str>	Enter the fully qualified domain name (FQDN) or IP address of the LDAP server.	
timeout <timeout_ int>	Enter the maximum amount of time in seconds that the FortiMail unit will wait for query responses from the LDAP server.	10
unauth-bind {enable   disable}	An unauthenticated bind is a bind where the user supplies a user name with no password. Some LDAP servers (such as Active Directory) allow unauthenticated bind by default. For better security, FortiMail does not accept empty password when doing LDAP authentication even if the backend LDAP server allows it.	disable

Variable	Description	Default
	<p>In some cases, such as allowing all members of a distribution list to access their quarantined email in gateway and transparent mode, this option needs to be enabled in the LDAP profile, so that FortiMail can accept LDAP authentication requests with empty password (user name must not be empty), and forward such requests to the backend LDAP server. If unauthenticated bind is permitted by the LDAP server, AND if the user exists on the server, FortiMail will consider authentication successful and grant access to the user.</p> <p>It is highly recommended that a dedicated LDAP profile (with this option enabled) is used for the above case. All other users should use separate LDAP profiles with this option disabled (this is the default setting) to maintain maximum security.</p> <p><b>Note:</b> This option is available in CLI only. And it only takes effect for webmail access in gateway and transparent mode.</p>	
upn-suffix <upns_str>	If you want to use a UPN other than the mail domain, enter that UPN. This can be useful if users authenticate with a domain other than the mail server's principal domain name.	
version {ver2   ver3}	Enter the version of the protocol used to communicate with the LDAP server.	ver3
webmail-password-change {enable   disable}	Enable to perform password change queries for FortiMail webmail users.	disable
webmail-password-schema {openldap   activedirectory}	<p>Enter one of the following to indicate the schema of your LDAP directory:</p> <p>openldap: The LDAP directory uses an OpenLDAP-style schema.</p> <p>activedirectory: The LDAP directory uses a Microsoft Active Directory-style schema.</p> <p>Note: Microsoft Active Directory requires that password changes occur over an SSL-secured connection.</p>	openldap

## Email address mapping

Address mappings are bidirectional, one-to-one or many-to-many mappings. They can be useful when:

- you want to hide a protected domain's true email addresses from recipients
- a mail domain's domain name is not globally DNS-resolvable, and you want to replace the domain name with one that is
- you want to rewrite email addresses

Like aliases, address mappings translate email addresses. They do not translate many email addresses into a single email address. However, **unlike** aliases:

- Mappings cannot translate one email address into many.
- Mappings cannot translate an email address into one that belongs to an unprotected domain (this restriction applies to locally defined address mappings only; it is not enforced for mappings defined on an LDAP server).
- Mappings are applied bidirectionally, when an email is outgoing as well as when it is incoming to the protected domain.
- Mappings may affect both sender and recipient email addresses, and may affect those email addresses in both the message envelope and the message header, depending on the match condition.

The following table illustrates the sequence in which parts of each email are compared with address mappings for a match, and which locations' email addresses are translated if a match is found.



Both RCPT TO: and MAIL FROM: email addresses are always evaluated for a match with an address mapping. If both RCPT TO: and MAIL FROM: contain email addresses that match the mapping, both mapping translations will be performed.

### Match evaluation and rewrite behavior for email address mappings:

Order of evaluation	Match condition	If yes...	Rewrite to...
1	Does RCPT TO: match an <b>external</b> email address?	Replace RCPT TO:.	Internal email address
2	Does MAIL FROM: match an <b>internal</b> email address?	For each of the following, if it matches an internal email address, replace it: MAIL FROM: RCPT TO: From: To: Return-Path: Cc: Reply-To: Return-Receipt-To: Resent-From: Resent-Sender: Delivery-Receipt-To: Disposition-Notification-To:	External email address

For example, you could create an address mapping between the internal email address user1@marketing.example.net and the external email address sales@example.com. The following effects would be observable on the simplest case of an outgoing email and an incoming reply:

For email from user1@marketing.example.net to others: user1@marketing.example.net in both the message envelope (MAIL FROM:) and many message headers (From:, etc.) would then be replaced with sales@example.com. Recipients would only be aware of the email address sales@example.com.

For email to sales@example.com from others: The recipient address in the message envelope (RCPT TO:), but **not** the message header (To:), would be replaced with user1@marketing.example.net. user1@marketing.example.net would be aware that the sender had originally sent the email to the mapped address, sales@example.com.

Alternatively, you can configure an LDAP profile to query for email address mappings.

## Related topics

[profile authentication on page 200](#)

# profile mail-routing

Use this command to configure email routing profiles, including MTA advanced control.

## Syntax

```
config profile mail-routing
  edit <profile_name>
    config entry
      edit <id_entry>
        set recipient-pattern <string>
        set relay-to-host <string>
        set relay-to-port <integer>
        set relay-type {host | mx-lookup | mx-lookup-matched-domain | relay-host}
        set sender-pattern <string>
      next
    end
  next
end
```

Variable	Description	Default
recipient-pattern <string>	Enter the recipient pattern.	
relay-to-host <string>	Enter a pre-defined relay host.	
relay-to-port <integer>	Enter the SMTP port number.	25
relay-type {host   mx-lookup   mx-lookup-matched-domain   relay-host}	Set the relay type: <ul style="list-style-type: none"> <li>host: Relay matched session to specified SMTP server.</li> <li>mx-lookup: Query the DNS server's MX record of a domain name you specify for the FQDN or IP address of the SMTP server.</li> </ul> If there are multiple MX records, FortiMail will load balance between them. <ul style="list-style-type: none"> <li>mx-lookup-match-domain: Relay through the MX record lookup of the matched recipient domain.</li> </ul>	host

Variable	Description	Default
	<ul style="list-style-type: none"> <li>relay-host: Relay to a pre-defined relay host.</li> </ul>	
sender-pattern <string>	Enter the sender pattern.	

## profile notification

Use this command configure a notification profile.



Note that domain users may only create one notification profile per domain.

## Syntax

```
config profile notification
edit <profile_name>
set attach-original-message {enable | disable}
set email-template <template_name>
set other <recipient_address>
set recipient {none | other | recipient | sender}
set type {generic | sender_addr_rate_ctrl}
end
```

Variable	Description	Default
<profile_name>	Enter the name of the notification profile.	
attach-original-message {enable   disable}	Enable to include the original message as attachment in the notification email.	disable
email-template <template_name>	Specify the email template to use.	default
other <recipient_address>	Specify the recipient address for the notification email.	
recipient {none   other   recipient   sender}	Specify who you want to send the notification to.	none
type {generic   sender_addr_rate_ctrl}	Specify the type of notification profile.	generic

## profile replacement-message

Use this command to configure custom replacement messages for the subject, body, or attachments to be used for content and DLP scanning.

## Syntax

```

config profile replacement-message
  edit <name>
    config member
      edit ...
        set content <string>
        set comment <string>
      next
    end
  set comment
next
end

```

Variable	Description	Default
edit ...	Configure the various email replacement message types: <ul style="list-style-type: none"> <li>• content-subject</li> <li>• content-body</li> <li>• content-attachment-blocked</li> <li>• content-attachment-number-limit-exceeded</li> <li>• content-attachment-size-limit-exceeded</li> <li>• content-size-limit-exceeded</li> <li>• dlp-subject</li> <li>• dlp-body</li> <li>• dlp-attachment</li> <li>• virus-body</li> <li>• virus-attachment-infected</li> <li>• virus-attachment-suspicious</li> </ul>	
content <string>	Enter the content of the specific replacement message. Note there is a 8191 character limit for each replacement message.	

## profile resource

Use this command configure a resource profile.



This command only applies in the server mode.

## Syntax

```
config profile resource
```

```

edit <profile_name>
  set auto-check-message
  set auto-delete-old-mail <days>
  set auto-delete-sent-folder <days>
  set auto-delete-trash-folder <days>
  set auto-forward {enable | disable}
  set auto-reply {enable | disable}
  set email-continuity-status {enable | disable}
  set idle-timeout {enable | disable}
  set message-filter {enable | disable}
  set mobile-access {enable | disable}
  set outbound-safelist
  set quarantine-bcc-addr
  set quarantine-bcc-status
  set quarantine-days
  set quarantine-report {enable | disable}
  set quota <number_mb>
  set release-auto-safelist
  set release-through-email
  set release-through-web
  set status {enable | disable}
  set webmail-access {enable | disable}
  set webmail-addressbook-access {domain | none | system}
  set webmail-user-preference {enable | disable}
end

```

Variable	Description	Default
auto-check-message	Enable or disable auto checking new messages in webmail.	enable
<profile_name>	Enter the name of the notification profile.	
auto-delete-old-mail <days>	Enter the number of days after which the FortiMail unit will automatically delete email that is locally hosted. 0 means not to delete email.	0
auto-delete-sent-folder <days>	Enter the number of days after which the FortiMail unit will automatically delete email in the sent folder. 0 means not to delete email.	0
auto-delete-trash-folder <days>	Enter the number of days after which the FortiMail unit will automatically empty the trash folder. 0 means not to delete email.	14
auto-forward {enable   disable}	Enable to allow auto forward in webmail.	enable
auto-reply {enable   disable}	Enable to allow auto reply in webmail.	enable
email-continuity-status {enable   disable}	Enable or disable email continuity (license based). When the SMTP server is detected as inaccessible, recipient verification is skipped and emails are put into the email continuity queue. When the SMTP server is accessible again, the email is delivered. Note there is no DSN if the email is from an unknown user.	enable

Variable	Description	Default
idle-timeout {enable   disable}	Enable to enforce an idle timeout in webmail	enable
message-filter {enable   disable}	Enable to allow message filtering in webmail.	enable
mobile-access {enable   disable}	Enable to allow mobile users to access their email via webmail.	enable
outbound- safelist	Enable or disable automatically updating personal safelists from sent emails.	disable
quarantine-bcc- addr	Enter the comma separated email address of BCC.	
quarantine-bcc- status	Enable or disable bcc messages to specified emails when quarantined emails released.	disable
quarantine-days	Enter the number of days a quarantined message is kept. Enter 0 for indefinitely.	14
quarantine- report {enable   disable}	Enable or disable the generation of summary reports of the quarantined emails.	enable
quota <number_ mb>	Enter the user's disk space quota in Megabytes.	1000
release-auto- safelist	Automatically add sender of a released message to personal safelist.	enable
release- through-email	Enable or disable auto release quarantined emails through email	disable
release- through-web	Enable or disable auto release quarantined emails through the web.	enable
status {enable   disable}	Enable or disable the user account.	enable
webmail-access {enable   disable}	Enable or disable user's webmail access.	enable
webmail- addressbook- access {domain   none   system}	Enable or disable user access to system and/or domain address book.	
webmail-user- preference {enable   disable}	Enable or disable the webmail user preference option.	enable

## profile session

Use this command to create session profiles.

While, like antispam profiles, session profiles protect against spam, session profiles focus on the connection and envelope portion of the SMTP session, rather than the message header, body, or attachments.

Similar to access control rules or delivery rules, session profiles control aspects of sessions in an SMTP connection.

## Syntax

```
config profile session
edit <profile_name>
    set access-control <profile_name>
    set block_encrypted {enable | disable}
    set bypass-bounce-verification {enable | disable}
    set check-client-ip-quick {enable | disable}
    set conn-blocklisted {enable | disable}
    set conn-concurrent <connections_int>
    set conn-hiden {enable | disable}
    set conn-idle-timeout <timeout_int>
    set conn-total <connections_int>
    set dkim-signing {enable | disable}
    set dkim-signing-authenticated-only {enable | disable}
    set dkim-validation {enable | disable}
    set domain-key-validation {enable | disable}
    set email-addr-rewrite-options {envelope-from | envelope-from-as-key | envelope-to |
        header-from | header-to | reply-to}
    set email-queue {default | incoming | no-preference | outgoing}
    set endpoint-reputation {enable | disable}
    set endpoint-reputation-action {reject | monitor}
    set endpoint-reputation-blocklist-duration <duration_int>
    set endpoint-reputation-blocklist-trigger <trigger_int>
    set eom-ack {enable | disable}
    set error-drop-after <errors_int>
    set error-penalty-increment <penalty-increment_int>
    set error-penalty-initial <penalty-initial_int>
    set error-penalty-threshold <threshold_int>
    set fortiguard-ip-check-mode {as-profile | as-profile-no-auth | client-connect | disable}
    set limit-NOOPs <limit_int>
    set limit-RSETs <limit_int>
    set limit-email <limit_int>
    set limit-helo <limit_int>
    set limit-max-header-size <limit_int>
    set limit-max-message-size <limit_int>
    set limit-recipient <limit_int>
    set mail-route <profile_name>
    set number-of-messages <limit_int>
    set number-of-recipients <limit_int>
    set recipient-blocklist-status {enable | disable}
    set recipient-rewrite-map <profile_name>
    set recipient-safelist-status {enable | disable}
    set remote-log <profile_name>
```

```

set remove-current-headers {enable | disable}
set remove-headers {enable | disable}
set remove-received-headers {enable | disable}
set sender-blocklist-status {enable | disable}
set sender-reputation-reject-score <threshold_int>
set sender-reputation-status {enable | disable}
set sender-reputation-tempfail-score <threshold_int>
set sender-reputation-throttle-number <rate_int>
set sender-reputation-throttle-percentage <percentage_int>
set sender-reputation-throttle-score <threshold_int>
set sender-rewrite-map <profile_name>
set sender-safelist-status {enable | disable}
set sender-verification {enable | disable}
set sender-verification-profile <profile_name>
set session-3way-check {enable | disable}
set session-action <content-action_profile>
set session-action-msg-type {accepted | all}
set session-allow-pipelining {yes | no}
set session-command-checking {enable | disable}
set session-disallow-encrypted {enable | disable}
set session-helo-char-validation {enable | disable}
set session-helo-domain-check {enable | disable}
set session-helo-rewrite-clientip {enable | disable}
set session-helo-rewrite-custom {enable | disable}
set session-helo-rewrite-custom-string <helo_str>
set session-prevent-open-relay {enable | disable}
set session-recipient-domain-check {enable | disable}
set session-reject-empty-domain {enable | disable}
set session-sender-domain-check {enable | disable}
set spf-validation {enable | disable}
set splice-status {enable | disable}
set splice-threshold
set splice-unit {seconds | kilobytes}
config header-removal-list
  edit <key_str>
config recipient-blocklist
  edit <recipient_address_str>
config recipient-safelist
  edit <recipient_address_str>
config sender-blocklist
  edit <sender_address_str>
config sender-safelist
  edit <sender_address_str>
next
end

```

Variable	Description	Default
<profile_name>	Enter the name of the session profile.	
<key_str>	Enter a header key to remove it from email messages.	
<recipient_address_str>	Enter a blocklisted recipient email address to which this profile is applied.	
<recipient_address_str>	Enter a safelisted recipient email address to which this profile is applied.	

Variable	Description	Default
<sender_address_str>	Enter a blocklisted sender email address to which this profile is applied.	
<sender_address_str>	Enter a safelisted sender email address to which this profile is applied.	
access-control <profile_name>	<b>Note:</b> This feature is only available as part of the MTA advanced control feature. See <code>mta-adv-ctrl-status</code> under <a href="#">system global on page 302</a> Enter an access control profile to be used in a session profile.	
block_encrypted {enable   disable}	Enable to block TLS/MD5 commands so that email must pass unencrypted, enabling the FortiMail unit to scan the email for viruses and spam. Disable to pass TLS/MD5 commands, allowing encrypted email to pass. The FortiMail unit cannot scan encrypted email for viruses and spam. This option applies only if the FortiMail unit is operating in transparent mode.	disable
bypass-bounce-verification {enable   disable}	Select to, if bounce verification is enabled, omit verification of bounce address tags on incoming bounce messages. This bypass does not omit bounce address tagging of outgoing email. Alternatively, you can omit bounce verification according to the protected domain. For details, see <a href="#">config domain-setting on page 108</a> . For information on enabling bounce address tagging and verification (BATV), see <a href="#">antispam bounce-verification on page 42</a> .	disable
check-client-ip-quick {enable   disable}	Enable to query the FortiGuard Antispam Service to determine if the IP address of the SMTP server is blocklisted. This action will happen during the connection phase. In an antispam profile, you can also enable FortiGuard block-IP checking. But that action happens after the entire message has been received by FortiMail. Therefore, if this feature is enabled in a session profile and the action is reject, the performance will be improved.	disable
conn-blocklisted {enable   disable}	Enable to prevent clients from using SMTP servers that have been blocklisted in antispam profiles or, if enabled, the FortiGuard AntiSpam service. This option applies only if the FortiMail unit is operating in transparent mode.	disable
conn-concurrent <connections_int>	Enter a limit to the number of concurrent connections per SMTP client. Additional connections are rejected. To disable the limit, enter 0.	0
conn-hiden {enable   disable}	Enter either of the following transparency behaviors: <b>enable:</b> Be transparent. Preserve the IP address or domain name in: the SMTP greeting (HELO/EHLO) in the envelope, the Received: Message headers of email messages, and the IP addresses in the IP header source and destination. This masks the existence of the FortiMail unit to the protected SMTP server. <b>disable:</b> Do not be transparent. Replace the SMTP client's IP addresses or domain names with that of the FortiMail unit.	disable

Variable	Description	Default
	<p>This option applies only if the FortiMail unit is operating in transparent mode. For more information about the proxies and built-in MTA transparency, see the <a href="#">FortiMail Administration Guide</a>.</p> <p><b>Note:</b> Unless you have enabled <code>exclusive {enable   disable}</code> in <a href="#">config policy delivery-control on page 168</a>, the <code>hide (tp-hidden {no   yes} )</code> option in <a href="#">config domain-setting on page 108</a> has precedence over this option, and may prevent it from applying to incoming email messages.</p> <p><b>Note:</b> For full transparency, also set the <code>hide (tp-hidden {no   yes} )</code> option in <a href="#">config domain-setting on page 108</a> to <code>yes</code>.</p>	
<code>conn-idle-timeout &lt;timeout_int&gt;</code>	<p>Enter a limit to the number of seconds a client may be inactive before the FortiMail unit drops the connection.</p> <p>Set the value between 5-1200.</p>	30
<code>conn-rate-number &lt;connections_int&gt;</code>	<p>This is a rate limit to the number of messages sent per client IP address per time interval (the default value is 30 minutes).</p> <p>You set the time interval using the command:</p> <pre>config antisppam settings     set session-profile-rate-control-interval &lt;minutes&gt; end</pre> <p>To disable the limit, enter 0.</p>	0
<code>conn-total &lt;connections_int&gt;</code>	<p>Enter a limit to the total number of concurrent connections from all sources.</p> <p>To disable the limit, enter 0.</p>	0
<code>dkim-signing {enable   disable}</code>	<p>Enable to sign outgoing email with a DKIM signature.</p> <p>This option requires that you first generate a domain key pair and publish the public key in the DNS record for the domain name of the protected domain. If you do not publish the public key, destination SMTP servers will not be able to validate your DKIM signature. For details on generating domain key pairs and publishing the public key, see the <a href="#">FortiMail Administration Guide</a>.</p>	disable
<code>dkim-signing-authenticated-only {enable   disable}</code>	<p>Enable to sign outgoing email with a DKIM signature only if the sender is authenticated.</p> <p>This option is available only if <code>dkim-signing</code> is <code>enable</code>.</p>	disable
<code>dkim-validation {enable   disable}</code>	<p>Enable to, if a DKIM signature is present, query the DNS server that hosts the DNS record for the sender's domain name to retrieve its public key to decrypt and verify the DKIM signature.</p> <p>An invalid signature increases the client sender reputation score and affect the deep header scan. A valid signature decreases the client sender reputation score.</p> <p>If the sender domain DNS record does not include DKIM information or the message is not signed, the FortiMail unit omits the DKIM signature validation.</p>	disable
<code>domain-key-validation {enable   disable}</code>	<p>Enable if the DNS record for the domain name of the sender lists DomainKeys.</p> <p>An unauthorized client IP address increases the client sender reputation score. An authorized client IP address decreases the client sender reputation score.</p>	disable

Variable	Description	Default
	If the DNS record for the domain name of the sender does not publish DomainKeys information, the FortiMail unit omits the DomainKeys client IP address validation.	
email-addr-rewrite-options {envelope-from   envelope-from-as-key   envelope-to   header-from   header-to   reply-to}	Specify which elements of the sender and recipient addresses to rewrite. For more details, see the session profile section in the <a href="#">FortiMail Administration Guide</a> .	
email-queue {default   incoming   no-preference   outgoing}	<b>Note:</b> This feature is only available as part of the MTA advanced control feature. See <code>mta-adv-ctrl-status</code> under <a href="#">system global on page 302</a> Enter the email queue to use for the matching sessions.	no-preference
endpoint-reputation {enable   disable}	Enable to accept, monitor, or reject email based upon endpoint reputation scores. This option is designed for use with SMTP clients with dynamic IP addresses. It requires that your RADIUS server provide mappings between dynamic IP addresses and MSISDNs/subscriber IDs to the FortiMail unit. If this profile governs sessions of SMTP clients with static IP addresses, instead consider <a href="#">sender-reputation-status {enable   disable}</a> .	disable
endpoint-reputation-action {reject   monitor}	Enter either: <b>reject:</b> Reject email and MMS messages from MSISDNs/subscriber IDs whose MSISDN reputation scores exceed <b>Auto blacklist score trigger value</b> . <b>monitor:</b> Log, but do not reject, email and MMS messages from MSISDNs/subscriber IDs whose MSISDN reputation scores exceed <code>endpoint-reputation-blocklist-trigger</code> value. Log entries appear in the history log.	reject
endpoint-reputation-blocklist-duration <duration_int>	Enter the number of minutes that an MSISDN/subscriber ID will be prevented from sending email or MMS messages after they have been automatically blocklisted.	0
endpoint-reputation-blocklist-trigger <trigger_int>	Enter the MSISDN reputation score over which the FortiMail unit will add the MSISDN/subscriber ID to the automatic blacklist. The trigger score is relative to the period of time configured as the automatic blacklist window.	5
eom-ack {enable   disable}	Enable to acknowledge the end of message (EOM) signal immediately after receiving the carriage return and line feed (CRLF) characters that indicate the EOM, rather than waiting for antispam scanning to complete.	disable

Variable	Description	Default
	If the FortiMail unit has not yet completed antispam scanning by the time that four (4) minutes has elapsed, it will return SMTP reply code 451(Try again later), resulting in no permanent problems, as according to RFC 2281, the minimum timeout value should be 10 minutes. However, in rare cases where the server or client's timeout is shorter than 4 minutes, the sending client or server could time-out while waiting for the FortiMail unit to acknowledge the EOM command. Enabling this option prevents those rare cases.	
error-drop-after <errors_int>	Enter the total number of errors the FortiMail unit will accept before dropping the connection.	5
error-penalty-increment <penalty-increment_int>	Enter the number of seconds by which to increase the delay for each error after the first delay is imposed.	1
error-penalty-initial <penalty-initial_int>	Enter the delay penalty in seconds for the first error after the number of "free" errors is reached.	1
error-penalty-threshold <threshold_int>	Enter the number of number of errors permitted before the FortiMail unit will penalize the SMTP client by imposing a delay.	1
fortiguard-ip-check-mode {as-profile   as-profile-no-auth   client-connect   disable}	Specify the FortiGuard IP reputation check mode: <ul style="list-style-type: none"> <li>as-profile: Uses the settings of the FortiGuard IP reputation in the antispam profile.</li> <li>as-profile-no-auth: Uses the settings of the FortiGuard IP reputation in the antispam profile, but disable SMTP authentication when the client IP reputation score triggers the threshold.</li> <li>client-connect: Checks FortiGuard IP reputation the moment a client connects.</li> <li>disable: Disables FortiGuard IP reputation check.</li> </ul>	as-profile
limit-NOOPs <limit_int>	Enter the limit of NOOP commands that are permitted per SMTP session. Some spammers use NOOP commands to keep a long session alive. Legitimate sessions usually require few NOOPs. Enter 0 to reset to the default value.	10
limit-RSETs <limit_int>	Enter the limit of RSET commands that are permitted per SMTP session. Some spammers use RSET commands to try again after receiving error messages such as unknown recipient. Legitimate sessions should require few RSETs. To disable the limit, enter 0.	20
limit-email <limit_int>	Enter the limit of email messages per session to prevent mass mailing. To disable the limit, enter 0.	10

Variable	Description	Default
limit-helo <limit_int>	Enter the limit of SMTP greetings that a connecting SMTP server or client can perform before the FortiMail unit terminates the connection. Restricting the number of SMTP greetings allowed per session makes it more difficult for spammers to probe the email server for vulnerabilities, as a greater number of attempts results in a greater number of terminated connections, which must then be re-initiated. Enter 0 to reset to the default value.	3
limit-max-header-size <limit_int>	Enter the limit of the message header size. If enabled, messages with headers over the threshold size are rejected.	32
limit-max-message-size <limit_int>	Enter the limit of the message size. If enabled, messages over the threshold size are rejected.	10240
limit-max-message-size <limit_int>	Enter the limit of message size in kilobytes (KB) . If enabled, messages over the threshold size are rejected. <b>Note:</b> If both this option and <code>max-message-size &lt;limit_int&gt;</code> in the protected domain are enabled, email size will be limited to whichever size is smaller.	10240KB
limit-recipient <limit_int>	Enter the limit of recipients to prevent mass mailing.	500
mail-route <profile_name>	Enter a mail routing profile to be used in a session profile.	
number-of-messages <limit_int>	Enter the number of message per client per time interval (the default value is 30 minutes). You set the time interval using the command: <pre>config antispam settings     set session-profile-rate-control-interval &lt;minutes&gt; end</pre> Enter 0 to disable the limit.	0
number-of-recipients <limit_int>	Enter the number of recipients per client per time interval (the default value is 30 minutes). You set the time interval using the command: <pre>config antispam settings     set session-profile-rate-control-interval &lt;minutes&gt; end</pre> Enter 0 to disable the limit.	0
recipient-blocklist-status {enable   disable}	Enable to use an envelope recipient (RCPT TO:) blocklist in SMTP sessions to which this profile is applied, then define blocklisted email addresses using <code>&lt;recipient_address_str&gt;</code> .	disable
recipient-rewrite-map <profile_name>	<b>Note:</b> This feature is only available as part of the MTA advanced control feature. See <code>mta-adv-ctrl-status</code> under <a href="#">system global on page 302</a> Enter an address rewrite profile to be used in a session profile.	

Variable	Description	Default
recipient-safelist-status {enable   disable}	Enable to use an envelope recipient (RCPT TO:) safelist in SMTP sessions to which this profile is applied, then define safelisted email addresses using <a href="#">&lt;recipient_address_str&gt;</a> .	disable
remote-log <profile_name>	<b>Note:</b> This feature is only available as part of the MTA advanced control feature. See <code>mta-adv-ctrl-status</code> under <a href="#">system global on page 302</a> Enter a remote logging profile. Note that the remote logging profiles used here are the same as the system-wide remote logging profiles.	
remove-current-headers {enable   disable}	Enable to remove headers that are inserted by the current unit. <b>Note:</b> This command is enabled by default for backwards compatibility with related subcommands <code>remove-headers</code> and <code>remove-received-headers</code> .	enable
remove-headers {enable   disable}	Enable to remove other configured headers from email messages.	disable
remove-received-headers {enable   disable}	Enable to remove all Received: message headers from email messages.	disable
sender-blocklist-status {enable   disable}	Enable to use an envelope sender (MAIL FROM:) blocklist in SMTP sessions to which this profile is applied, then define the blocklisted email addresses using <a href="#">&lt;sender_address_str&gt; on page 249</a> .	disable
sender-reputation-reject-score <threshold_int>	Enter a sender reputation score over which the FortiMail unit will return a rejection error code when the SMTP client attempts to initiate a connection. This option applies only if <a href="#">sender-reputation-status {enable   disable}</a> is enabled.	80
sender-reputation-status {enable   disable}	Enable to reject email based upon sender reputation scores.	disable
sender-reputation-tempfail-score <threshold_int>	Enter a sender reputation score over which the FortiMail unit will return a temporary failure error code when the SMTP attempts to initiate a connection. This option applies only if <a href="#">sender-reputation-status {enable   disable}</a> is enabled.	55
sender-reputation-throttle-number <rate_int>	Enter the maximum number of email messages per hour that the FortiMail unit will accept from a throttled SMTP client.	5
sender-reputation-throttle-percentage <percentage_int>	Enter the maximum number of email messages per hour that the FortiMail unit will accept from a throttled SMTP client, as a percentage of the number of email messages that the sender sent during the previous hour.	1
sender-reputation-throttle-score <threshold_int>	Enter the sender reputation score over which the FortiMail unit will rate limit the number of email messages that can be sent by this SMTP client.	15

Variable	Description	Default
	<p>The enforced rate limit is either <code>sender-reputation-throttle-number &lt;rate_int&gt;</code> or <code>sender-reputation-throttle-percentage &lt;percentage_int&gt;</code> whichever value is greater.</p> <p>This option applies only if <code>sender-reputation-status {enable   disable}</code> is enabled.</p>	
<code>sender-rewrite-map &lt;profile_name&gt;</code>	<p><b>Note:</b> This feature is only available as part of the MTA advanced control feature. See <code>mta-adv-ctrl1-status</code> under <a href="#">system global on page 302</a></p> <p>Enter an address rewrite profile to be used in a session profile.</p>	
<code>sender-safelist-status {enable   disable}</code>	<p>Enable to use an envelope sender (MAIL FROM:) safelist in SMTP sessions to which this profile is applied, then define safelisted email addresses using <code>&lt;sender_address_str&gt;</code>.</p>	disable
<code>sender-verification {enable   disable}</code>	<p>Enable sender address verification with LDAP.</p>	disable
<code>sender-verification-profile &lt;profile_name&gt;</code>	<p>Select the LDAP profile to use for sender address verification.</p>	
<code>session-3way-check {enable   disable}</code>	<p>Enable to reject the email if the domain name in the SMTP greeting (HELO/EHLO) and recipient email address (RCPT TO:) match, but the domain name in the sender email address (MAIL FROM:) does not.</p> <p>Mismatching domain names is sometimes used by spammers to mask the true identity of their SMTP client.</p> <p>This check only affects unauthenticated sessions.</p>	disable
<code>session-action &lt;content-action_profile&gt;</code>	<p>Select a content action profile to apply upon session policy match.</p>	
<code>session-action-msg-type {accepted   all}</code>	<p>Define the message type to take session action.</p>	all
<code>session-allow-pipelining {yes   no}</code>	<p>Select one of the following behaviors for ESMTP command pipelining, which causes some SMTP commands to be accepted and processed as a batch, increasing performance over high-latency connections.</p> <p>When set to no, FortiMail unit accepts only one command at a time during an SMTP session and will not accept the next command until it completes processing of the previous command.</p> <p>This option is available for gateway, server, and transparent mode.</p>	yes
<code>session-command-checking {enable   disable}</code>	<p>Enable to return SMTP reply code 503, rejecting the SMTP command, if the client or server uses SMTP commands that are syntactically incorrect.</p> <p>EHLO or HELO, MAIL FROM:, RCPT TO: (can be multiple), and DATA commands must be in that order. AUTH, STARTTLS, RSET, NOOP commands can arrive at any time. Other commands, or commands in an unacceptable order, return a syntax error.</p> <p>In the following example, the invalid commands are highlighted in bold:</p>	disable

Variable	Description	Default
	<pre>220 FortiMail-400.localdomain ESMTP Smtpd; Wed, 14 Feb 2008 13:41:15 GMT EHLO example.com 250-FortiMail-400.localdomain Hello [192.168.1.1], pleased to meet you <b>RCPT TO: &lt;user1@example.com&gt;</b> 503 5.0.0 Need MAIL before RCPT</pre>	
session-disallow-encrypted {enable   disable}	<p>Enable to block TLS/MD5 commands so that email must pass unencrypted, enabling the FortiMail unit to scan the email for viruses and spam.</p> <p>Clear to pass TLS/MD5 commands, allowing encrypted email to pass. The FortiMail unit cannot scan encrypted email for viruses and spam.</p> <p><b>Note:</b> This option applies only if the FortiMail unit is operating in transparent mode.</p>	disable
session-helo-char-validation {enable   disable}	<p>Enable to return SMTP reply code 501, rejecting the SMTP greeting, if the client or server uses a greeting that contains a domain name with invalid characters.</p> <p>To avoid disclosure of a real domain name, spammers sometimes spoof an SMTP greeting domain name with random characters, rather than using a genuine, valid domain name. If this option is enabled, such connections are rejected.</p> <p>In the following example, the invalid command is highlighted in bold:</p> <pre>220 FortiMail-400.localdomain ESMTP Smtpd; Wed, 14 Feb 2008 13:30:20 GMT <b>EHLO ^^&amp;^^^#\$\$</b> 501 5.0.0 Invalid domain name</pre> <p>Valid characters for domain names include:</p> <ul style="list-style-type: none"> <li>• alphanumerics (A to Z and 0 to 9)</li> <li>• brackets ( [ and ] )</li> <li>• periods ( . )</li> <li>• dashes ( - )</li> <li>• underscores ( _ )</li> <li>• number symbols( # )</li> <li>• colons ( : )</li> </ul>	disable
session-helo-domain-check {enable   disable}	<p>Enable to return SMTP reply code 501, rejecting the SMTP greeting, if the client or server uses a greeting that contains a domain name with invalid characters.</p> <p>To avoid disclosure of a real domain name, spammers sometimes spoof an SMTP greeting domain name with random characters, rather than using a genuine, valid domain name. If this option is enabled, such connections are rejected.</p> <p>In the following example, the invalid command is highlighted in bold:</p> <pre>220 FortiMail-400.localdomain ESMTP Smtpd; Wed, 14 Feb 2008 13:30:20 GMT</pre>	disable

Variable	Description	Default
	<p>EHLO ^&amp;^&amp;^#&amp;#&amp;\$</p> <p>501 5.0.0 Invalid domain name</p> <p>Valid domain characters include:</p> <ul style="list-style-type: none"> <li>• alphanumerics (A to Z and 0 to 9)</li> <li>• brackets ( [ and ] )</li> <li>• periods ( . )</li> <li>• dashes ( - )</li> <li>• underscores ( _ )</li> <li>• number symbols( # )</li> <li>• colons (:)</li> </ul>	
session-helo-rewrite-clientip {enable   disable}	<p>Enable to rewrite the HELO/EHLO domain to the IP address of the SMTP client to prevent domain name spoofing.</p> <p>This option applies only if the FortiMail unit is operating in transparent mode.</p>	disable
session-helo-rewrite-custom {enable   disable}	<p>Enable to rewrite the HELO/EHLO domain, then enter the replacement text using <a href="#">session-helo-rewrite-custom-string &lt;helo_str&gt;</a>.</p> <p>This option applies only if the FortiMail unit is operating in transparent mode.</p>	disable
session-helo-rewrite-custom-string <helo_str>	<p>Enter the replacement text for the HELO/EHLO domain.</p>	
session-prevent-open-relay {enable   disable}	<p>Enable to block unauthenticated outgoing connections to unprotected mail servers in order to prevent clients from using open relays to send email. If clients from your protected domains are permitted to use open relays to send email, email from your domain could be blocklisted by other SMTP servers.</p> <p>This feature:</p> <ul style="list-style-type: none"> <li>• applies only if the FortiMail unit is operating in transparent mode,</li> <li>• only affects unauthenticated sessions, and</li> <li>• is applicable only if you allow clients to use an unprotected SMTP server for outgoing connections. For details, see <a href="#">mailsetting proxy-smtp on page 143</a>.</li> </ul>	disable
session-recipient-domain-check {enable   disable}	<p>Enable to return SMTP reply code 550, rejecting the SMTP command, if the domain name portion of the recipient address is not a domain name that exists in either MX or A records.</p> <p>In the following example, the invalid command is highlighted in bold:</p> <pre>220 FortiMail-400.localdomain ESMTP Smtpd; Wed, 14 Feb 2008 14:48:32 GMT EHLO example.com 250-FortiMail-400.localdomain Hello [192.168.1.1], pleased to meet you MAIL FROM:&lt;user1@fortinet.com&gt; 250 2.1.0 &lt;user1@fortinet.com&gt;... Sender ok <b>RCPT TO:&lt;user2@example.com&gt;</b> 550 5.7.1 &lt;user2@example.com&gt;... Relaying denied. IP name lookup failed [192.168.1.1]</pre>	disable

Variable	Description	Default
session-reject-empty-domain {enable   disable}	<p>This check only affects unauthenticated sessions.</p> <p>Enable to return SMTP reply code 553, rejecting the SMTP command, if a domain name does not follow the "@" symbol in the sender email address. Because the sender address is invalid and therefore cannot receive delivery status notifications (DSN), you may want to disable this feature.</p> <p>In the following example, the invalid command is highlighted in bold:</p> <pre>220 FortiMail-400.localdomain ESMTP Smtpd; Wed, 14 Feb 2007 14:48:32 GMT EHLO example.com 250-FortiMail-400.localdomain Hello [192.168.171.217], pleased to meet you <b>MAIL FROM:&lt;john@&gt;</b> 553 5.1.3 &lt;john@&gt;... Hostname required</pre> <p>This check only affects unauthenticated sessions.</p>	disable
session-sender-domain-check {enable   disable}	<p>Enable to return SMTP reply code 421, rejecting the SMTP command, if the domain name portion of the sender address is not a domain name that exists in either MX or A records.</p> <p>In the following example, the invalid command is highlighted in bold:</p> <pre>220 FortiMail-400.localdomain ESMTP Smtpd; Wed, 14 Feb 2008 14:32:51 GMT EHLO 250-FortiMail-400.localdomain Hello [192.168.1.1], pleased to meet you <b>MAIL FROM:&lt;user1@example.com&gt;</b> 421 4.3.0 Could not resolve sender domain.</pre>	disable
spf-validation {enable   disable}	<p>Enable to, if the sender domain DNS record lists SPF authorized IP addresses, compare the client IP address to the IP addresses of authorized senders in the DNS record.</p> <p>An unauthorized client IP address increases the client sender reputation score. An authorized client IP address decreases the client sender reputation score.</p> <p>If the DNS record for the domain name of the sender does not publish SPF information, the FortiMail unit omits the SPF client IP address validation.</p>	disable
splice-status {enable   disable}	<p>Enable to permit splicing.</p> <p>Splicing enables the FortiMail unit to simultaneously scan an email and relay it to the SMTP server. This increases throughput and reduces the risk of a server timeout.</p> <p>If the FortiMail unit detects spam or a virus, it terminates the server connection and returns an error message to the sender, listing the spam or virus name and infected file name.</p> <p><b>Note:</b> This option applies only if the FortiMail unit is operating in transparent mode.</p>	disable
splice-threshold	<p>Enter a threshold value to switch to splice mode based on time (seconds) or data size (kilobytes) using <code>splice-unit {seconds   kilobytes}</code>.</p>	0

Variable	Description	Default
<integer>	<b>Note:</b> This option applies only if the FortiMail unit is operating in transparent mode.	
splice-unit {seconds   kilobytes}	Enter the time (seconds) or data size (kilobytes) for the splice threshold. <b>Note:</b> This option applies only if the FortiMail unit is operating in transparent mode.	seconds

## Related topics

[profile encryption on page 222 on page 206](#)

## profile tls

Use this command to configure TLS profiles that can be used by receive rules (also called access control rules) and delivery rules. Note that many subcommands are only available when level is set to either preferred or secure.

## Syntax

```
config profile tls
  edit <profile_name>
    set level {none | preferred | secure}
    set action {fail | tempfail}
    set ca-name <string>
    set cert-subject <string>
    set check-ca-name {enable | disable}
    set check-ca-type {match | substring | wildcard}
    set check-cert-subject {enable | disable}
    set check-cert-type {match | substring | wildcard}
    set check-encryption-strength {enable | disable}
    set check-ssl-version {enable | disable}
    set dane-support {mandatory | none | opportunistic}
    set encryption-strength <integer>
    set min-ssl-version {ssl3 | tls1_0 | tls1_1 | tls1_2 | tls1_3}
    set mtasts-status {enable | monitor | none}
  end
```

Variable	Description	Default
<profile_name>	Enter the name of the TLS profile.	
level {none   preferred   secure}	Enter the security level of the TLS connection. <ul style="list-style-type: none"> <li><code>none</code>: Disables TLS. Requests for a TLS connection will be ignored.</li> <li><code>preferred</code>: Allow a simple TLS connection, but do not require it. Data is not encrypted, nor is the identity of the server validated with a certificate.</li> </ul>	none

Variable	Description	Default
	<ul style="list-style-type: none"> <li><code>secure</code>: Requires a certificate-authenticated TLS connection. CA certificates must be installed on the FortiMail unit before they can be used for secure TLS connections. For information on installing CA certificates, see the <a href="#">FortiMail Administration Guide</a>.</li> </ul>	
action {fail   tempfail}	Select the action the FortiMail unit takes when a TLS connection cannot be established. This option does not apply for profiles whose level is preferred.	tempfail
ca-name <string>	Enter the name of the CA issuer. This option is only available when level is set to secure.	
cert-subject <string>	Enter the certification subject. This option is only available when level is set to secure.	
check-ca-name {enable   disable}	Enable to check the CA issuer name. This option is only available when level is set to secure.	disable
check-ca-type {match   substring   wildcard}	Select a CA issuer check type. This option is only available when level is set to secure.	match
check-cert-subject {enable   disable}	Enable to check the certificate subject name. This option is only available when level is set to secure.	disable
check-cert-type {match   substring   wildcard}	Select a certificate check type. This option is only available when level is set to secure.	match
check-encryption-strength {enable   disable}	Enable to check encryption key length.	disable
check-ssl-version {enable   disable}	Enable to check the SSL/TLS version.	disable
dane-support {mandatory   none   opportunistic}	Assign a DNS-based Authentication of Named Entities (DANE) support level. Note that mandatory is only applicable when level is set to secure. For more information, see <a href="#">RFC 7929</a> .	none
encryption-strength <integer>	Enter the encryption key length.	256

Variable	Description	Default
min-ssl-version	Enter the minimum required SSL/TLS version.	tls1_1
{ssl3   tls1_0   tls1_1   tls1_2   tls1_3}	This option is only available when check-ssl-version is set to enable.	
mtasts-status	<b>Note:</b> The MTA-STS status may only be set when smtp-mtasts-status is enabled under <a href="#">system mailserv</a> .	none
{enable   monitor   none}	Enable MTA Strict Transport Security (MTA-STS) domain checking. This option is only available when level is set to either preferred or secure.	

## Related topics

[ms365 profile antivirus on page 158](#)

## profile url-filter

Use this command to configure FortiGuard URL filter profiles.

## Syntax

```
config profile url-filter
  edit <profile_name>
    set category <filter_category>
  end
```

Variable	Description	Default
<profile_name>	Enter the name of the URL profile.	
category <filter_category>	Specify the FortiGuard URL category to use for the filter. To view all available categories, enter set category ?.	child-abuse drug-abuse adult-materials nudity-risque pornography spam-urls phishing malicious-web

# report domain-mail-stats

Use this command to configure domain-level mail statistics report.

## Syntax

```
config report domain-mail-stats
  set status {enable | disable}
  set report-by-email {enable | disable}
  set domains {all | <protected-domain_name>}
  set schedule-frequency {daily | monthly | weekly}
  set schedule-hour <hour_int>
end
```

Variable	Description	Default
status {enable   disable}	Enable to generate domain mail statistics reports.	disable
report-by-email {enable   disable}	Enable to send report emails for selected domains	disable
domains {all   <protected-domain_name>}	Enter either all to include all protected domains in the report, or enter a list of one or more protected domains. Separate each protected domain with a comma (,).	all
schedule-frequency {daily   monthly   weekly}	Frequency of the scheduled report.	monthly
schedule-hour <hour_int>	Hour of the day to generate the report, between 0 - 23.	23

## report mail

Use this command to configure report profiles that define what information will appear in generated reports.

In addition to log files, FortiMail units require a report profile to be able to generate a report. A report profile is a group of settings that contains the report name, file format, subject matter, and other aspects that the FortiMail unit considers when generating the report.

## Syntax

```
config report mail
  edit <profile_name>
```

```

set dest-ip-mask <ip/netmask_str>
set dest-ip-type {ip-group | ip-mask}
set direction {both | incoming | outgoing}
set domains {all | <protected-domain_str>}
set file-format {html | pdf}
set period-absolute-from <start_str>
set period-absolute-to <end_str>
set period-relative {last-2-weeks | last-7-days | last-14-days | last-30-days | last-N-days
| last-N-hours | last-N-weeks | last-month | last-quarter | last-week | not-used |
this-month | this-quarter | this-week | this-year | today | yesterday}
set period-relative-value <n_int>
set query-status <query_str>
set recipients <recipient_str>
set schedule {daily | dates | none | weekdays}
set schedule-dates <dates_str>
set schedule-hour <time_int>
set schedule-weekdays <days_str>
set sender-domains
end

```

Variable	Description	Default
<profile_name>	Enter the name of the report profile.	
dest-ip-mask <ip/netmask_str>	Enter the IP address to which reports on logged email messages are destined.	0.0.0.0/32
dest-ip-type {ip-group   ip-mask}	Enter the type of the IP address for sending reports on logged email messages.	ip-mask
direction {both   incoming   outgoing}	Enter one of the following: both: Report on both incoming and outgoing email. incoming: Report only on email whose recipient is a member of a protected domain. outgoing: Report only on email whose recipient is <b>not</b> a member of a protected domain.	both
domains {all   <protected-domain_str>}	Enter either ALL to include all protected domains in the report, or enter a list of one or more protected domains. Separate each protected domain with a comma ( , ).	all
file-format {html   pdf}	Enter the file format of the generated report.	pdf
period-absolute-from <start_str>	Enter the beginning of the time range in the format yyyy-mm-dd-hh, where yyyy is the year, mm is the month, dd is the day, and hh is the hour in 24-hour clock format. For example, entering 2008-10-24-09 includes log messages as early as 9 AM on October 24, 2008.	

Variable	Description	Default
period-absolute-to <end_str>	<p>Enter the end of the time range in the format yyyy-mm-dd-hh, where yyyy is the year, mm is the month, dd is the day, and hh is the hour in 24-hour clock format.</p> <p>For example, entering 2009-10-24-17 includes log messages as late as 5 PM on October 24, 2009.</p>	
period-relative {last-2-weeks   last-7-days   last-14-days   last-30-days   last-N-days   last-N-hours   last-N-weeks   last-month   last-quarter   last-week   not-used   this-month   this-quarter   this-week   this-year   today   yesterday}	<p>Enter the time span of log messages from which to generate the report. If you entered last-N-days, last-N-hours, or last-N-weeks also configure <code>period-relative-value &lt;n_int&gt;</code>.</p>	
period-relative-value <n_int>	<p>If you entered last-N-days, last-N-hours, or last-N-weeks as the value for <code>period-relative</code>, enter the value of n.</p>	
query-status <query_str>	<p>Enter the name of a query whose result you want to include in the report, such as Mail_Stat_Viruses.</p> <p>To display a list of available query names, enter a question mark ( ? )</p>	
recipients <recipient_str>	<p>Enter a list of one or more recipient email addresses that will receive the report generated from the report profile. Separate each recipient with a comma ( , ).</p>	
schedule {daily   dates   none   weekdays}	<p>Enter a value to schedule when the report is automatically generated, or to disable generating reports on schedule if you want to initiate them only manually.</p> <p>daily: Generate the report every day.</p> <p>dates: Generate the report on certain dates in the month. Also configure <code>schedule-dates &lt;dates_str&gt;</code>.</p> <p>none: If you do not want to automatically generate the report according to a schedule, enter none.</p> <p>You can still manually initiate the FortiMail unit to generate a report at any time.</p> <p>weekdays: Generate the report on certain days of the week. Also configure <code>schedule-weekdays &lt;days_str&gt;</code>.</p>	

Variable	Description	Default
schedule-dates <dates_str>	Enter the dates to generate the reports. Separate each date with a comma ( , ). For example, to generate a report on the first and fourteenth of each month, you would enter 1, 14.	
schedule-hour <time_int>	If you want to automatically generate the report according to a schedule, enter the hour of the day, according to a 24-hour clock, at which you want to generate the report. Also configure the days on which you want to generate the report. For example, to generate reports at 5 PM, you would enter 17.	
schedule-weekdays <days_str>	Enter the days to generate the reports. Separate each day with a comma ( , ). For example, to generate a report on Friday and Wednesday, you would enter wednesday, friday.	
sender-domains	Enter the selected sender domain names (empty means ALL)	

## Related topics

[log alertemail setting on page 137](#)

## report mailbox

Note that this command is only available when `mailbox-service` is enabled under [system global](#).

Use this command to configure mailbox report schedules.



The mailbox service feature is license based. This command is only available with a valid purchased advanced management license from FortiGuard.

## Syntax

```
config report mailbox
edit <report_name>
set domains <domain_str>
set mailbox-list {enable | disable}
set period {last_month | this_month | today | yesterday}
set recipients <email_addr_str>
set schedule-frequency {daily | monthly | none | weekly}
```

```

set schedule-hour <hour_int>
set schedule-weekdays {friday | monday | saturday | sunday | thursday | tuesday |
    wednesday}
set schedule-dates {1 | 2 | ... | 30 | 31}
end

```

Variable	Description	Default
<report_name>	Enter the name of the mailbox report schedule.	
domains <domain_str>	List of domains to be reported.	
mailbox-list {enable   disable}	Enable to include mailbox lists in reports.	disable
period {last_month   this_month   today   yesterday}	Period of report coverage.	today
recipients <email_addr_str>	List of email recipients of the report.	
schedule-frequency {daily   monthly   none   weekly}	Frequency of the scheduled report.	none
schedule-hour <hour_int>	Hour of the day to generate the report, between 0 - 23.	12
schedule-weekdays {friday   monday   saturday   sunday   thursday   tuesday   wednesday}	<b>Note:</b> This option is only available when schedule-frequency is set to weekly. Days of the week to generate the report.	
schedule-dates {1   2   ...   30   31}	<b>Note:</b> This option is only available when schedule-frequency is set to monthly. Dates of the month to generate the report.	

## sensitive data

Use this command to configure sensitive data.

## Syntax

```

config sensitive-data fingerprint
  edit <fingerprint data name>
    config document
      edit <document id>
        set filename
        set signature
config sensitive-data fingerprint-source
  edit <DLP server name>
    set file-path
    set file-pattern
    set keep-modified
    set password
    set period
    set remove-deleted
    set scan-subdirectories
    set server

```

```

    set server-type
    set username
edit linux
    set file-path
    set file-pattern
    set keep-modified
    set password
    set period
    set remove-deleted
    set scan-subdirectories
    set server
    set server-type
    set username
end

```

Variable	Description	Default
<fingerprint data name>	Enter the name of the fingerprint data you want to configure.	
document	Enter to examine a list of created document IDs.	
<document id>	Enter the name of the document you want to modify.	
filename	Enter the filename of the fingerprint document.	
signature	Enter the signature of the file.	
fingerprint-source	Enter to configure the fingerprint source.	
<DLP server name>	Enter the name of the DLP server.	
linux	Enter the Linux identifier.	
file-path	Enter the file path on the server.	
file-pattern	Enter the file patterns to fingerprint.	
keep-modified	Keep previous fingerprints for modified files (enable or disable).	
password	Enter the login password.	
period	Select periodic server checking.	
remove-deleted	Remove fingerprints for deleted files (enable or disable).	
scan-subdirectories	Fingerprint files in subdirectories (enable or disable).	
server	Enter the IP address of the server.	
server-type	Enter the DLP server type.	
username	Enter the login username.	

## system accprofile

Use this command to configure access profiles that, in conjunction with the domain to which an administrator account is assigned, govern which areas of the web-based manager and CLI that an administrator can access, and whether or not they have the permissions necessary to change the configuration or otherwise modify items in each area.

## Syntax

```

config system accprofile
  edit <profile_name>
    config menuitem
      edit <name>
        set permission {custom | none | read | read-write}
        set content-detail {enable | disable}
      next
    end
    set admin {none | read | read-write}
    set archive {none | read | read-write}
    set block-safe-list {none | read | read-write}
    set granular-group {all}
    set greylist {none | read | read-write}
    set log {none | read | read-write}
    set ms365 {none | read | read-write}
    set others {none | read | read-write}
    set personal-quarantine {none | read | read-write}
    set policy {none | read | read-write}
    set privilege-level {high | low | medium}
    set queue {none | read | read-write}
    set system {none | read | read-write}
    set system-diagnostics {enable | disable}
    set system-quarantine {none | read | read-write}
  end
end

```

Variable	Description	Default
<profile_name>	Enter the name of the access profile.	
<name>	Enter the name of the menu item you wish to configure administrative permissions: <ul style="list-style-type: none"> <li>• archive_grp</li> <li>• cluster_grp</li> <li>• content_grp</li> <li>• dashboard_grp</li> <li>• domain_grp</li> <li>• encryption_grp</li> <li>• fortiview_grp</li> <li>• log_grp</li> <li>• monitor_grp</li> <li>• ms365_grp</li> <li>• others_grp</li> <li>• policy_grp</li> <li>• profile_grp</li> <li>• security_grp</li> <li>• system_grp</li> </ul>	

Variable	Description	Default
permission {custom   none   read   read-write}	Apply a permission across all access control configurations.	none
content-detail {enable   disable}	Note that this is only available for archive_grp.	enable
admin {none   read   read-write}	For the admin configuration, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
archive {none   read   read-write}	For the archiving configuration, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
block-safe-list {none   read   read- write}	For the block and safelist configuration, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
granular-group {all}	Access permission for granular control.	all
greylist {none   read   read-write}	For the greylist configuration, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
log {none   read   read-write}	For the log configuration, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
ms365 {none   read   read-write}	For the Microsoft 365 configuration, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
others {none   read   read-write}	For the rest of the configurations except policy, block-safe-list, and quarantine, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
personal- quarantine {none   read   read-write}	For personal quarantine, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
policy {none   read read-write}	For the policy configuration, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
privilege-level {high   low   medium}	Set the access profile's privilege level. Any administrators assigned a low privilege level cannot run diagnose or config system commands.	medium
queue {none   read   read-write}	For the queue configuration, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
system {none   read   read-write}	For system settings, enter the permissions that will be granted to administrator accounts associated with this access profile.	none
system- diagnostics {enable   disable}	Enable or disable permission to run system diagnostic commands.	enable
system-quarantine {none   read   read- write}	For system quarantine, enter the permissions that will be granted to administrator accounts associated with this access profile.	none

## Related topics

system admin on page 270

# system admin

Use this command to configure FortiMail administrator accounts.

By default, FortiMail units have a single administrator account, admin. For more granular control over administrative access, you can create additional administrator accounts that are restricted to being able to configure a specific protected domain and/or with restricted permissions. For more information, see the [FortiMail Administration Guide](#).

## Syntax

```
config system admin
  edit <name_str>
    set access-profile <profile_name>
    set auth-strategy {ldap | local | local-plus-radius | pki | radius}
    set is-system-domain {no | yes}
    set language <lang_str>
    set ldap-profile <profile_name>
    set password <password_str>
    set pkiuser <pkiuser_str>
    set radius-permission-check {enable | disable}
    set radius-profile <profile_int>
    set radius-subtype-id <subtype_int>]
    set radius-vendor-id <vendor_int>
    set sshkey <key_str>
    set status {enable | disable}
    set theme
    set theme <theme_str>
    set trusthosts <host_ipv4mask>
    set webmode (basic | advanced)
  end
```

Variable	Description	Default
<name_str>	Enter the name of the administrator account.	
access-profile <profile_name>	Enter the name of an access profile that determines which functional areas the administrator account may view or affect.	
auth-strategy {ldap   local   local-plus-radius   pki   radius}	Select the local or remote type of authentication that the administrator will be able to use: ldap local radius	local

Variable	Description	Default
	radius-plus-local pki	
is-system-domain {no   yes}	Enter yes to indicate that the administrator account may view all settings on the FortiMail unit.	yes
language <lang_str>	Enter this administrator account's preference for the display language of the web-based manager. Available languages vary by whether or not you have installed additional language resource files. To view a list of languages, enter a question mark ( ? ).	english
ldap-profile <profile_name>	If auth-strategy is ldap, enter the LDAP profile you want to use.	
password <password_str>	If auth-strategy is local or radius-plus-local, enter the password for the administrator account. Caution: Do not enter a FortiMail administrator password less than six characters long. For better security, enter a longer password with a complex combination of characters and numbers, and change the password regularly. Failure to provide a strong password could compromise the security of your FortiMail unit.	
pkiuser <pkiuser_str>	If auth-strategy is pki, enter the name of a PKI user. Whether the administrator is required to log in only with a valid personal certificate or password-style authentication fallback is allowed varies by your configuration of <a href="#">pki-mode {enable   disable}</a> .	
radius-permission-check {enable   disable}	If auth-strategy is local or radius-plus-local, enable to query the RADIUS server for the permissions attribute.	disable
radius-profile <profile_int>	If auth-strategy is local or radius-plus-local, enter the index number of a RADIUS authentication profile.	
radius-subtype-id <subtype_int>]	If auth-strategy is local or radius-plus-local, and radius-permission-check is enable, enter the RADIUS subtype identifier.	0
radius-vendor-id <vendor_int>	If auth-strategy is local or radius-plus-local, and radius-permission-check is enable, enter the RADIUS vendor identifier.	0
sshkey <key_str>	Enter the SSH key string surrounded in single straight quotes ( ' ). When connecting from an SSH client that presents this key, the administrator will not need to provide their account name and password in order to log in to the CLI.	
status {enable   disable}	Enable to activate the admin user.	disable
theme	Enter the system admin GUI theme.	
theme <theme_str>	Enter this administrator account's preference for the display theme when logging in.	

Variable	Description	Default
trusthosts <host_ ipv4mask>	Enter one to three IP addresses and netmasks from which the administrator can log in to the FortiMail unit. Separate each IP address and netmask pair with a comma ( , ).  To allow the administrator to authenticate from any IP address, enter 0.0.0.0/0.0.0.0.	0.0.0.0/0.0.0.0
webmode (basic   advanced)	Enter which display mode will initially appear when the administrator logs in to the web-based manager.  The administrator may switch the display mode during their session; this affects only the initial state of the display.	basic

## Related topics

[sensitive data on page 266](#)

## system advanced-management

Use this command to control advanced management features that are designed for deployments such as managed security service providers (MSSP).



Advanced management options require a valid advanced management feature license. Some subcommands are only available as part of the MTA advanced control feature. See [mta-adv-ctrl-status {enable | disable} on page 304](#)

## Syntax

```
config system advanced-management
  set domain-admin-log-status {enable | disable}
  set domain-group-status {enable | disable}
  set domain-mail-stats-status {enable | disable}
  set ha-central-monitor-status {enable | disable}
  set intra-domain-protection-status {enable | disable}
  set mailbox-accounting-status {enable | disable}
  set user-management {enable | disable}
end
```

Variable	Description	Default
domain-admin-log-status {enable   disable}	Enable or disable domain-level administrator log access.	enable

Variable	Description	Default
domain-group-status {enable   disable}	Enable or disable domain group support.	enable
domain-mail-stats-status {enable   disable}	Enable or disable domain-level mail statistics.	disable
ha-central-monitor-status {enable   disable}	Enable or disable HA central monitoring.	disable
intra-domain-protection-status {enable   disable}	<p>Enable or disable applying both inbound and outbound policies when an email is sent between protected domains.</p> <p>When this setting is disabled, if an email is sent between two protected domains, then FortiMail only applies the matching inbound policy. This means that, for example, an inbound policy with antispam would apply, but not an outbound policy with DLP. This behavior may be correct if all protected domains belong to the same company. However for an MSSP with multiple tenants, both policies should apply. In that case, enabled this setting so that FortiMail applies <b>both</b> inbound and outbound policies.</p>	disable
mailbox-accounting-status {enable   disable}	Enable or disable the mailbox accounting service.	disable
user-management {enable   disable}	Enable or disable user management.	disable

## Related topics

[report mailbox](#)

[system domain-group](#)

[system global](#)

[system ha](#)

## system appearance

Use this command to customize the appearance of the web-based manager, FortiMail webmail, and per-recipient quarantine of the FortiMail unit.

### Syntax

```
config system appearance
  set admin-sso-login-option {normal | sso-only}
  set comment <string>
  set customized-login-status {enable | disable}
  set fallback-charset <language_code>
  set login-page-language <lang_str>
  set login-page-theme
  set product <product-name_str>
  set webmail-help-status {enable | disable}
  set webmail-help-url <url_str>
  set webmail-lang <language_str>
  set webmail-login <login_str>
  set webmail-login-hint <login_hint_str>
  set webmail-sort-option {order-received | time-received}
  set webmail-sso-login-option {normal | sso-only}
  set webmail-theme {IndigoDarkBlue | RedGrey | Standard}
  set webmail-theme-status {enable | disable}
end
```

Variable	Description	Default
admin-sso-login-option {normal   sso-only}	Define administrator SSO login handling: <ul style="list-style-type: none"> <li>normal: Require both SSO and username/password.</li> <li>sso-only: Require SSO only.</li> </ul>	normal
comment <string>	Optional comment for the system appearance.	
customized-login-status {enable   disable}	Enable to edit a graphic that will appear at the top of all webmail pages. The image's dimensions must be 314 pixels wide by 36 pixels tall.	disable
fallback-charset <language_code>	Enter the fallback charset for non <a href="#">RFC 2047</a> compliant message.	english
login-page-language <lang_str>	Enter the default language for the display of the login page of the web manager. To view a list of languages, enter a question mark ( ? ). Note that the setting only affect the login page, not the entire web-based manager.	english
login-page-theme	Enter the default display theme of the login page.	
product <product-name_str>	Enter the text that will precede 'Administrator Login' on the login page of the web-based manager.	FortiMail

Variable	Description	Default
webmail-help-status {enable   disable}	Enable to display the help button in the webmail interface. The default help contents are provided by Fortinet.	enable
webmail-help-url <url_str>	If you want to provide your own help to the webmail users, you can enter the URL of the help file.	
webmail-lang <language_str>	Enter the name of the language in English, such as ' French ', that will be used when an email user initially logs in to FortiMail webmail/per-recipient quarantine.  The email user may switch the display language in their preferences; this affects only the initial state of the display.  Available languages vary by whether or not you have installed additional language resource files.	English
webmail-login <login_str>	Enter a word or phrase that will appears on top of the webmail login page, such as Webmail Login.	Login
webmail-login-hint <login_hint_str>	Enter a hint for the user name, such as Your Email Address. This hint will appear as a mouse-over display on the login name field.	address
webmail-sort-option {order-received   time-received}	Define the email sorting option on webmail: <ul style="list-style-type: none"> <li>• <code>order-received</code>: Sorted by the order in which emails are delivered to the mailbox folder.</li> <li>• <code>time-received</code>: Sorted by the time that emails are received by the mail server.</li> </ul>	time-received
webmail-sso-login-option {normal   sso-only}	Define webmail SSO login handling: <ul style="list-style-type: none"> <li>• <code>normal</code>: Require both SSO and username/password.</li> <li>• <code>sso-only</code>: Require SSO only.</li> </ul>	normal
webmail-theme {IndigoDarkBlue   RedGrey   Standard}	Select a theme for the webmail GUI.	RedGrey
webmail-theme-status {enable   disable}	Enable or disable webmail theme change.	enable

## Related topics

[system geoip-override on page 302](#)

## system backup-restore-mail

Use this command to configure backup and restoration of email user's mailboxes.

For the initial backup, whether manually or automatically initiated, the FortiMail unit will make a full backup. For subsequent backups, the FortiMail unit will make the number of incremental backups, then make another full backup,

and repeat this until it reaches the maximum number of full backups to keep on the backup media, which you selected in `full <full-backups_int>`. At that point, it will overwrite the oldest full backup.

For example, if `full <full-backups_int>` is 3 and `monthly-incremental-days` is 4, the FortiMail unit would make a full backup, then 4 incremental backups. It would repeat this two more times for a total of 3 backup sets, and then overwrite the oldest full backup when creating the next backup.

## Syntax

```
config system backup-restore-mail
  set encryption-key <key>
  set folder <path_str>
  set full <full-backups_int>
  set host <fortimail-fqdn_str>
  set hour-of-day <hours_int>
  set monthly-day-of-month
  set monthly-incremental-days
  set number-of-backups
  set port <port_int>
  set protocol {ext-usb | ext-usb-auto | iscsi_server | nfs | smb-winservice | ssh}
  set status {enable | disable}
end
```

Variable	Description	Default
encryption-key <key>	Enter the encryption key for backup/restore.	
folder <path_str>	Enter the path of the folder on the backup server where the FortiMail unit will store the mailbox backups, such as: /home/fortimail/mailboxbackups This field appears only if the backup media is an NFS server or SSH server.	FortiMail-mail-data-backup
full <full-backups_int>	Enter the total number of full backups to keep on the backup media. Valid values are between 1 and 10.	3
host <fortimail-fqdn_str>	If you want to restore all mailboxes from a backup labeled with the fully qualified domain name (FQDN) of a previous FQDN, or that of another FortiMail unit, enter the FQDN of the backup that you want to restore. For example, to restore the most recent backup made by a FortiMail unit named fortimail.example.com, enter fortimail.example.com.	
hour-of-day <hours_int>	Enter the hour of the day, according to a 24-hour clock, on the days of the week at which to make backups. For example, to make backups at 9 PM, enter 21.	23
monthly-day-of-month	Enter the day of the month to perform the full backup.	
monthly-incremental-days	Enter how often to perform the monthly incremental backup.	

Variable	Description	Default
number-of-backups	Enter the number of full backups to keep.	
port <port_int>	Enter the TCP port number on which the backup server listens for connections. This field does not appear if the backup media is a USB disk.	22
protocol {ext-usb   ext-usb-auto   iscsi_server   nfs   smb-winserv   ssh}	Enter one of the following types of backup media: ext-usb: An external hard drive connected to the FortiMail unit's USB port. ext-usb-auto: An external disk connected to the FortiMail unit's USB port. Unlike the previous option, this option only creates a backup when you connect the USB disk, or when you manually initiate a backup rather than according to a schedule. iscsi_server: An Internet SCSI (Small Computer System Interface), also called iSCSI, server. nfs: A network file system (NFS) server. smb/winserv: A Windows-style file share. ssh: A server that supports secure shell (SSH) connections. Other available options vary by your choice of backup media.	nfs
status {enable   disable}	Enable to allow backups and restoration to occur, whether manually initiated or automatically performed on schedule. Also configure the backup media in <code>protocol {ext-usb   ext-usb-auto   iscsi_server   nfs   smb-winserv   ssh}</code> and, if applicable to the type of the media, configure a schedule in <code>encryption-key &lt;key&gt;</code> and <code>hour-of-day &lt;hours_int&gt;</code> <b>Note:</b> You should enable backups/restoration <b>after</b> configuring the other options if a scheduled backup will occur before you configure <code>protocol {ext-usb   ext-usb-auto   iscsi_server   nfs   smb-winserv   ssh}</code> . Failure to do so would result in a failed backup attempt, requiring you to wait for the failed attempt to terminate before you can continue to configure this feature.	disable

## Related topics

[system link-monitor](#) on page 321

## system certificate ca

Use this command to import certificates for certificate authorities (CA).

Certificate authorities validate and sign other certificates in order to indicate to third parties that those other certificates may be trusted to be authentic.

CA certificates are required by connections that use transport layer security (TLS). For more information, see the [FortiMail Administration Guide](#).

## Syntax

```
config system certificate ca
  edit <name_str>
    set certificate <cert_str>
  end
```

Variable	Description	Default
<name_str>	Enter a name for this certificate.	
certificate <cert_str>	Enter or paste the certificate in PEM format to import it.	

## Related topics

[system certificate crl on page 278](#)

[system certificate local on page 279](#)

[system certificate remote on page 280](#)

## system certificate crl

Use this command to import certificate revocation lists.

To ensure that your FortiMail unit validates only certificates that have not been revoked, you should periodically upload a current certificate revocation list, which may be provided by certificate authorities (CA). Alternatively, you can use online certificate status protocol (OCSP) to query for certificate statuses. For more information, see the [FortiMail Administration Guide](#).

## Syntax

```
config system certificate crl
  edit <name_str>
    set crl <cert_str>
  end
```

Variable	Description	Default
<name_str>	Enter a name for this certificate revocation list.	
crl <cert_str>	Enter or paste the certificate in PEM format to import it.	

## Related topics

[system central-management](#)

[system certificate local on page 279](#)

[system certificate remote on page 280](#)

## system certificate local

Use this command to import signed certificates and certificate requests in order to install them for local use by the FortiMail unit.

FortiMail units require a local server certificate that it can present when clients request secure connections, including:

- the web-based manager (HTTPS connections only)
- webmail (HTTPS connections only)
- secure email, such as SMTPS, IMAPS, and POP3S



When using this command to import a local certificate, you must enter the commands in the order described in the following syntax. This is because `private-key` will need the password to decrypt the private key if it was encrypted and `certificate` will try to find a matched private key file.

## Syntax

```
config system certificate local
  edit <name_str>
    set password
    set private-key
    set certificate <cert_str>
    set csr <csr_str>
    set comments <comment_str>
  end
```

Variable	Description	Default
<name_str>	Enter a name for the certificate to be imported.	
password	Enter a password for the certificate.	
private-key	Enter a private key for the certificate. <b>Note:</b> A random password is used to encrypt the private key, to prevent the private key from becoming visible when using the <code>show</code> command.	
certificate <cert_str>	Enter or paste the certificate in PEM format to import it.	
csr <csr_str>	Enter or paste the certificate signing request in PEM format to import it.	
comments <comment_str>	Enter any comments for this certificate.	

## Related topics

[system central-management](#)  
[system certificate crl on page 278](#)  
[system certificate remote on page 280](#)

# system certificate remote

Use this command to import the certificates of the online certificate status protocol (OCSP) servers of your certificate authority (CA).

OCSP enables you to revoke or validate certificates by query, rather than by importing certificate revocation lists (CRL).

Remote certificates are required if you enable OCSP for PKI users.

## Syntax

```
config system certificate remote
  edit <name_str>
    set certificate <cert_str>
  end
```

Variable	Description	Default
<name_str>	Enter a name for the certificate to be imported.	
certificate <cert_str>	Enter or paste the certificate in PEM format to import it.	

## Related topics

[system central-management](#)  
[system certificate crl on page 278](#)  
[system certificate local on page 279](#)

# system config-control

Use this command to configure control and table templates.

## Syntax

```
config system config-control
  set base-config-name <string>
  set base-config-status {enable | disable}
  set domain-admin-restriction {enable | disable}
end
```

Variable	Description	Default
base-config-name <string>	Enter the name of the base table entry that the new table entry will take values from.	
base-config-status {enable   disable}	Enable to allow table entry creation, such as antispam profiles, to take values from base-config-name.	enable
domain-admin-restriction {enable   disable}	Enable to restrict domain-level administrators from making changes to certain settings.	disable

## system csf

Use this command to configure the FortiMail unit as a Security Fabric member.

## Syntax

```
config system csf
  set configuration-sync {local | sync}
  set group-name <string>
  set group-password <password>
  set management-ip <string>
  set management-port <integer>
  set status {enable | disable}
  set upstream-ip <string>
  set upstream-port <integer>
end
```

Variable	Description	Default
configuration-sync {local   sync}	Configuration synchronization mode.	local
group-name <string>	Security Fabric group name.	
group-password <password>	Security Fabric group name password.	
management-ip <string>	Management IP address of the unit to join the Security Fabric.	

Variable	Description	Default
management-port <integer>	Management port number of the unit to join the Security Fabric. Set the value between 1-65535.	443
status {enable   disable}	Enable or disable Security Fabric configuration.	enable
upstream-ip <string>	IP address of upstream.	172.20.141.151
upstream-port <integer>	Upstream port number.	8013

## system ddns

Use this command to configure the FortiMail unit to update a dynamic DNS (DDNS) service with its current public IP address.

## Syntax

```
config system ddns
  edit <ddns-service_str>
    config domain
      edit domain <domain_str>\
        set ipmode {auto | bind | static}
        set interface <interface_str>
        set ip <host_ipv4>
        set status {enable | disable}
        set type {custom | dynamic | static}
      set password <password_str>
      set timeout <time_int>
      set username <username_str>
    end
  end
```

Variable	Description	Default
<ddns-service_str>	Enter one of the following DDNS update servers: <ul style="list-style-type: none"> <li>members.dhs.org</li> <li>dipdnserver.dipdns.com</li> <li>www.dnsart.com</li> <li>members.dyndns.org</li> <li>www.dyns.net</li> <li>ip.todayisp.com</li> <li>ods.org</li> <li>rh.tzo.com</li> <li>ph001.oray.net</li> </ul> <b>Note:</b> You must have an account with this DDNS service provider.	

Variable	Description	Default
domain <domain_str>	Enter the domain name that is tied to this username and server.	
ipmode {auto   bind   static}	Select the method of determining the IP address: auto: Automatically detect the public IP address of the FortiMail unit and use that as the IP address to which <code>domain &lt;domain_str&gt;</code> will resolve. bind: Use the IP address of a specific network interface as the IP address to which <code>domain &lt;domain_str&gt;</code> will resolve. Also configure <code>interface &lt;interface_str&gt;</code> . static: Use the public IP address to which <code>domain &lt;domain_str&gt;</code> will resolve. Also configure <code>ip &lt;host_ipv4&gt;</code> .	auto
interface <interface_str>	Enter the specific network interface of which the IP address is used as the IP address to which <code>domain &lt;domain_str&gt;</code> will resolve.	
ip <host_ipv4>	Enter the public IP address to which <code>domain &lt;domain_str&gt;</code> will resolve.	
status {enable   disable}	Enable to notify a DDNS service provider to update public DNS records when the public IP address of the FortiMail unit changes.	disable
type {custom   dynamic   static}	Enter a service type for this domain.	
password <password_str>	Enter the password of the DDNS account.	
timeout <time_int>	Enter the amount of time in hours after which your FortiMail unit will contact the DDNS server to reaffirm its current IP address.	
username <username_str>	Enter the user name of your account with the DDNS service provider.	

## Related topics

[system dns on page 286](#)

## system disclaimer

Use this command to configure system-wide disclaimer messages.

A disclaimer message is text that is generally attached to email to warn the recipient that the email contents may be confidential. For disclaimers added to outgoing messages, you need to configure an IP-based policy or an outgoing recipient-based policy.

Disclaimer messages can be appended for either or both incoming or outgoing email messages. For information on determining the directionality of an email message, see the [FortiMail Administration Guide](#).

## Syntax

```

config system disclaimer
  set exclude-status {enable | disable}
  set incoming-body-content <disclaimer_str>
  set incoming-body-content-html
  set incoming-body-location
  set incoming-body-status {enable | disable}
  set incoming-external-email-only {enable | disable}
  set incoming-header-insertion-name
  set incoming-header-insertion-value
  set incoming-header-status {enable | disable}
  set incoming-subject-tagging-status {enable | disable}
  set incoming-subject-tagging-value <string>
  set outgoing-body-content <disclaimer_str>
  set outgoing-body-content-html
  set outgoing-body-location
  set outgoing-body-status {enable | disable}
  set outgoing-header-insertion-name
  set outgoing-header-insertion-value
  set outgoing-header-status {enable | disable}
  set outgoing-subject-tagging-status {enable | disable}
  set outgoing-subject-tagging-value <string>
end

```

Variable	Description	Default
exclude-status {enable   disable}	If you do not want to insert disclaimers to the email messages from certain senders or to certain recipients, you can enable this option. For information about how to configure the disclaimer exclusion list, see <a href="#">system disclaimer-exclude on page 286</a> .	disable
incoming-body-content <disclaimer_str>	Enter the text that comprises the disclaimer message that appends to the message body of each incoming email.	
incoming-body-content-html	Enter the text that comprises the content of the HTML incoming disclaimer in the message body.	
incoming-body-location	Enter an incoming disclaimer at the beginning or end of a message body.	
incoming-body-status {enable   disable}	Enable to append a disclaimer to the message body of each incoming email. Also configure <a href="#">incoming-body-content &lt;disclaimer_str&gt;</a> .	disable
incoming-external-email-only {enable   disable}	Enable to insert incoming disclaimer warning of any emails that come from outside the organization (for external email only).	disable
incoming-header-insertion-name	Enter the name of the header to be inserted for incoming disclaimer.	

Variable	Description	Default
incoming-header-insertion-value	Enter the value of the header to be inserted for incoming disclaimer.	
incoming-header-status {enable   disable}	Enable to insert a disclaimer to the message header of each incoming email. Also configure <a href="#">system disclaimer</a> .	disable
incoming-subject-tagging-status {enable   disable}	Enable to insert subject tag for incoming email.	
incoming-subject-tagging-value <string>	Enter the subject tag text that is prepended to the subject line of incoming email.	
outgoing-body-content <disclaimer_str>	Enter the text that comprises the disclaimer message that appends to the message body of each outgoing email.	
outgoing-body-content-html	Enter the content of html outgoing disclaimer in the message body.	
outgoing-body-location	Enter the outgoing disclaimer at the beginning or ending of the message body.	
outgoing-body-status {enable   disable}	Enable to append a disclaimer to the message body of each outgoing email. Also configure <a href="#">outgoing-body-content &lt;disclaimer_str&gt;</a> .	disable
outgoing-header-insertion-name	Enter the name of the header to be inserted for outgoing disclaimer.	
outgoing-header-insertion-value	Enter the value of the header to be inserted for outgoing disclaimer.	
outgoing-header-status {enable   disable}	Enable to insert a disclaimer to the message header of each outgoing email. Also configure <a href="#">outgoing-body-content &lt;disclaimer_str&gt;</a> .	disable
outgoing-subject-tagging-status {enable   disable}	Enable to insert subject tag for outgoing email.	
outgoing-subject-tagging-value <string>	Enter the subject tag text that is prepended to the subject line of outgoing email.	

## Related topics

[system disclaimer-exclude on page 286](#)

## system disclaimer-exclude

In some cases, you may not want to insert disclaimers to some email messages. For example, you may not want to insert disclaimers to paging text or SMS text messages. To do this, you add the specific senders, sender domains, recipients, or recipients domains to the exclusion list, and when you configure the global disclaimer settings (see [system disclaimer](#)), you can enable the exclusion list.

### Syntax

```
config system disclaimer-exclude
  edit <id>
    set recipient-pattern <string>
    set sender-pattern <string>
    set source-ip <ipv4mask>
  end
```

Variable	Description	Default
<id>	Enter a table ID.	
recipient-pattern <string>	Enter a recipient pattern. For example, if you add *@example.com, all messages to example.com users will be exempted from disclaimer insertion.	
sender-pattern <string>	Enter a sender pattern. For example, if you add *@example.com, all messages from example.com users will be exempted from disclaimer insertion.	
source-ip <ipv4mask>	Define the source IP address and netmask to exclude from disclaimers.	0.0.0.0/0

### Related topics

[system disclaimer on page 283](#)

## system dns

Use this command to configure the IP addresses of the primary and secondary DNS servers that the FortiMail unit will query to resolve domain names into IP addresses.

You can also configure up to three other DNS servers for protected domains' (and their domain associations) MX record query only. This is useful if the protected domains' MX record or A record are resolved differently on internal DNS servers. This feature is only applicable to gateway mode and transparent mode and when you select MX record as the relay type in domain settings.

Note that if you configure DNS servers for protected domains (such as example.com), FortiMail will also use the same DNS server for all queries that are in the form of anysub.example.com, so that the recursive queries for the returned MX record (mx.example.com) or other records can be directed to the same server.

## Syntax

```
config system dns
  set cache {enable | disable}
  set cache-min-ttl <time-in-seconds>
  set primary <ipv4_address>
  set protected-domain-dns-servers <ipv4_address>
  set protected-domain-dns-state {enable | disable}
  set ptr-query-option {enable | disable| public-ip-only}
  set secondary <dns_ipv4>
  set truncate-handling {disable | tcp-retry}
end
```

Variable	Description	Default
cache {enable   disable}	Enable to cache DNS query results to improve performance. Disable the DNS cache to free memory if you are low on memory.	enable
cache-min-ttl <time-in-seconds>	Use this command to overwrite the TTL of the cached DNS records in case the TTL of the records is very short. However, the newly set TTL value is only effective if it is longer than the original TTL.  For example, if you set it to 30 seconds while the original TTL is 10 seconds, then the actual record TTL will become 30 seconds. If you set it to 30 seconds while the original TTL is 60 seconds, then the actual record TTL remains to be 60 seconds.	300
primary <ipv4_address>	Enter the IP address of the primary DNS server.	0.0.0.0
protected-domain-dns-servers <ipv4_address>	Enter the IP address of the DNS servers that you want to use to resolve the protected domain names (including their subdomains) and the MX Record (alternative domain). You can enter up to 3 addresses/DNS servers.	0.0.0.0
protected-domain-dns-state {enable   disable}	Either enable or disable the protected domain DNS servers.	disable
ptr-query-option {enable   disable  public-ip-only}	Enable to perform reverse DNS lookups on both private network IP addresses and public IP addresses. However, PTR queries may cause delays when the DNS server has no response. In this situation, you may choose to disable the querying.  In some cases, the DNS server may not have PTR records for your private network's IP addresses. Failure to contain records for those IP addresses may increase DNS query time. In this situation, you can choose to query on public IP addresses only.	public-ip-only

Variable	Description	Default
secondary <dns_ ipv4>	Enter the IP address of the secondary DNS serve.	0.0.0.0
truncate-handling {disable   tcp-retry}	Specify how to handle truncated UDP replies of DNS queries: select either disable (meaning no retries) or tcp-try (meaning retry in TCP mode).	tcp-retry

## Related topics

[system ddns on page 282](#)

## system domain-group



The configuration of domain groups for administrators is license based. If you do not purchase the advanced management license, this feature is not available.

Use this command to associate a domain-level administrator to a domain group, allowing administrators to potentially manage multiple domains and all associated log entries.

## Syntax

```
config system domain-group
  edit <id>
    set domain <string>
  end
```

Variable	Description	Default
<id>	Enter a table ID.	
domain <string>	Enter the domain name(s) that you want to associate to the current administrator.	

## Related topics

[system encryption ibe on page 289](#)

# system encryption ibe

Use this command to configure, enable or disable Identity-Based Encryption (IBE) services, which control how secured mail recipients use the mail IBE function.

## Syntax

```
config system encryption ibe
  set account-notification {activation deletion expiration registration-confirmation reset-confirmation}
  set auth-mode {password | token | two-factor}
  set custom-user-control-status {enable | disable}
  set expire-alert <days_int>
  set expire-emails <days_int>
  set expire-inactivity <days_int>
  set expire-passwd-reset <hours_int>
  set expire-registration <days_int>
  set read-notification {enable | disable}
  set secure-compose {enable | disable}
  set secure-reply {enable | disable}
  set secure-forward {enable | disable}
  set secure-token-ttl <minutes>
  set service-name <name_str>
  set sms-account-id <id>
  set sms-auth-key <key>
  set sms-from-number <number>
  set sms-provider <provider>
  set status {enable | disable}
  set two-factor-auth-max-attempt <attempts_int>
  set two-factor-auth-method {email | sms}
  set unread-days
  set unread-notif-rcpt
  set unread-notif-sender
  set unread-notification {enable | disable}
  set url-about <url_str>
  set url-base <url_str>
  set url-custom-user-control <url_str>
  set url-forgot-pwd <psw_str>
  set url-help <url_str>
end
```

Variable	Description	Default
account-notification {activation deletion expiration registration- confirmation reset- confirmation}	Enter the types of account notifications you wish to be sent to users. Optionally, for multiple account notifications, separate each entry with a space.	activation expiration

Variable	Description	Default
auth-mode {password   token   two-factor}	Select the IBE user authentication mode.	password
custom-user- control-status {enable   disable}	If your corporation has its own user authentication tools, enable this option and enter the URL. Also configure <code>url-custom-user-control</code> and <code>url-forgot-pwd</code> .	disable
expire-alert <days_ int>	Enter the number of days before the user account's expiry date to send an alert email notification to the user. The valid range is 0 to 7, where 0 means the account is expired.  Optionally, for multiple alert email intervals, separate each entry with a space. For example, the default value (1 7) will send an alert email seven days and one day before the expiry date.	17
expire-emails <days_int>	Enter the number of days that the secured mail will be saved on the FortiMail unit.	180
expire-inactivity <days_int>	Enter the number of days the secured mail recipient can access the FortiMail unit without registration. For example, if you set the value to 30 days and if the mail recipient did not access the FortiMail unit for 30 days after they registers on the unit, the recipient will need to register again if another secured mail is sent to them. If the recipient accessed the FortiMail unit on the 15th days, the 30-day limit will be recalculated from the 15th day onwards.	90
expire-passwd- reset <hours_int>	Enter the password reset expiry time in hours. This is for the recipients who have forgotten their login passwords and request for new ones. The secured mail recipient must reset their password within this time limit to access the FortiMail unit.	24
expire-registration <days_int>	Enter the number of days that the secured mail recipient has to register on the FortiMail unit to view the mail before the registration expires. The starting date is the date when the FortiMail unit sends out the first notification to a mail recipient.	30
read-notification {enable   disable}	Enable to send the read notification the first time the mail is read.	disable
secure-compose {enable   disable}	Select to allow the secure mail recipient to compose an email. The FortiMail unit will use policies and mail delivery rules to determine if this mail needs to be encrypted.  For encrypted email, the domain of the composed mail's recipient must be a protected one, otherwise an error message will appear and the mail will not be delivered.	disable
secure-reply {enable   disable}	Allow the secured mail recipient to reply to the email with encryption.	disable
secure-forward {enable   disable}	Allow the secured mail recipient to forward the email with encryption	disable

Variable	Description	Default
secure-token-ttl <minutes>	Enter the secure token timeout value in minutes. Set the value between 1-1440.	30
service-name <name_str>	Enter the name for the IBE service. This is the name the secured mail recipients will see once they access the FortiMail unit to view the mail.	
sms-account-id <id>	Enter the account or service plan ID provided by your SMS provider.	
sms-auth-key <key>	The authentication token, or API key, provided by your SMS provider.	
sms-from-number <number>	Enter the phone number from which to send SMS messages.	
sms-provider <provider>	SMS provider for two-factor authentication.	twilio
status {enable   disable}	Enable the IBE service you have configured.	disable
two-factor-auth-max-attempt <attempts_int>	Enter the maximum number of attempts a user is allowed for a two-factor authenticated session.	3
two-factor-auth-method {email   sms}	<b>Note:</b> This option is only available when auth-mode is set to either token or two-factor. Enter the verification method for two-factor authentication: email or SMS.	email
unread-days	<b>Note:</b> This option is only available when unread-notification is set to enable. Enter the unread notification days.	14
unread-notif-rcpt	<b>Note:</b> This option is only available when unread-notification is set to enable. Enable to send the unread notification to the recipient.	disable
unread-notif-sender	<b>Note:</b> This option is only available when unread-notification is set to enable. Enable to send the unread notification to the sender.	disable
unread-notification {enable   disable}	Enable to send the unread notification if the message remains unread for 14 days by default.	disable
url-about <url_str>	You can create a file about the FortiMail IBE encryption and enter the URL for the file. The mail recipient can click the "About" link from the secure mail notification to view the file.  If you leave this option empty, a link for a default file about the FortiMail IBE encryption will be added to the secure mail notification.	
url-base <url_str>	Enter the FortiMail unit URL, for example, https://192.168.100.20, where a mail recipient can register or authenticate to access the secured mail.	

Variable	Description	Default
url-custom-user-control <url_str>	Enter the URL where you can check for user existence. This command appears after you enable <code>custom-user-control-status</code> .	
url-forgot-pwd <psw_str>	Enter the URL where users get authenticated. This command appears after you enable <code>custom-user-control-status</code> .	
url-help <url_str>	You can create a help file on how to access the FortiMail secure email and enter the URL for the file. The mail recipient can click the "Help" link from the secure mail notification to view the file.  If you leave this option empty, a default help file link will be added to the secure mail notification.	

## Related topics

[system encryption ibe-auth](#)

## system encryption ibe-auth

When mail recipients of the IBE domains access the FortiMail unit after receiving a secure mail notification:

- recipients of the IBE domains without LDAP authentication profiles need to register to view the email.
- recipients of the IBE domains with LDAP authentication profiles just need to authenticate because the FortiMail unit can query the LDAP servers for authentication information based on the LDAP profile.

In both cases, the FortiMail unit will record the domain names of the recipients who register or authenticate on it under the *User > IBE User > IBE Domain* tab.

Use this command to bind domains with LDAP authentication profiles with which the FortiMail unit can query the LDAP servers for authentication, email address mappings, and more. For more information about LDAP profiles, see ["profile ldap on page 226"](#).

## Syntax

```
config system encryption ibe-auth
  edit <id>
    set domain-pattern <string>
    set ldap-profile <profile_name>
    set status {enable | disable}
  end
```

Variable	Description	Default
<id>	Enter a table ID.	

Variable	Description	Default
domain-pattern <string>	Enter a domain name that you want to bind to an LDAP authentication profile. If you want all IBE users to authenticate through an LDAP profile and do not want other non-LDAP-authenticated users to get registered on FortiMail, you can use wildcard * for the domain name and then bind it to an LDAP profile.	
ldap-profile <profile_name>	Enter a profile name from the available LDAP profile list, which you want to use to authenticate the domain users.	
status {enable   disable}	Enable or disable the rule.	disable

## Related topics

[system encryption ibe on page 289](#)

## system fortiguard antivirus

Use this command to configure how the FortiMail unit will retrieve the most recent updates to FortiGuard Antivirus engines, antivirus definitions, and antispam definitions (the heuristic antispam rules only). FortiMail can get antivirus updates either directly from a Fortinet Distribution Network (FDN) server or via a web proxy.

## Syntax

```
config system fortiguard antivirus
  set override-server-address <virtual-ip_ipv4>
  set override-server-status {enable | disable}
  set push-update-override-address <virtual-ip_ipv4>
  set push-update-override-port <port_int>
  set push-update-override-status {enable | disable}
  set push-update-status {enable | disable}
  set scheduled-update-day <day_int>
  set scheduled-update-frequency {daily | every | weekly}
  set scheduled-update-status {enable | disable}
  set scheduled-update-time <time_str>
  set tunneling-address <host_ipv4>
  set tunneling-password <password_str>
  set <document id>
  set tunneling-status {enable | disable}
  set tunneling-username <username_str>
  set virus-db {default | extended | extreme}
  set virus-outbreak {disable | enable | enable-with-defer}
  set virus-outbreak-protection-period <minutes>
```

end

Variable	Description	Default
override-server-address <virtual-ip_ipv4>	If <code>override-server-status</code> is <code>enable</code> , enter the IP address of the public or private FortiGuard Distribution Server (FDS) that overrides the default FDS to which the FortiMail unit connects for updates.	
override-server-status {enable   disable}	Enable to override the default FDS to which the FortiMail unit connects for updates.	disable
push-update-override-address <virtual-ip_ipv4>	If <code>push-update-override-status</code> is <code>enable</code> , enter the public IP address that will forward push updates to the FortiMail unit. Usually, this is a virtual IP address on the external interface of a NAT device such as a firewall or router.	
push-update-override-port <port_int>	If <code>push-update-override-status</code> is <code>enable</code> , enter the port number that will forward push updates to UDP port 9443 the FortiMail unit. Usually, this is a port forward on the external interface of a NAT device such as a firewall or router.	
push-update-override-status {enable   disable}	Enable to override the default IP.	disable
push-update-status {enable   disable}	Enable to allow the FortiMail unit to receive notifications of available updates, which trigger it to download FortiGuard Antivirus packages from the FDN.	disable
scheduled-update-day <day_int>	Enter the day of the week at which the FortiMail unit will request updates where the range is from 0-6 and 0 means Sunday and 6 means Saturday.	
scheduled-update-frequency {daily   every   weekly}	Enter the frequency at which the FortiMail unit will request updates. Also configure <code>scheduled-update-day &lt;day_int&gt;</code> and <code>scheduled-update-time &lt;time_str&gt;</code> .	weekly
scheduled-update-status {enable   disable}	Enable to perform updates according to a schedule.	enable
scheduled-update-time <time_str>	Enter the time of the day at which the FortiMail unit will request updates, in the format <code>hh:mm</code> , where <code>hh</code> is the number of hours and <code>mm</code> is the number of minutes after the hour in 15 minute intervals.	01:00
tunneling-address <host_ipv4>	If <code>tunneling-status</code> is <code>enable</code> , enter the IP address of the web proxy.	
tunneling-password <password_str>	If <code>tunneling-status</code> is <code>enable</code> , enter the password of the account on the web proxy.	
tunneling-port <port_int>	If <code>tunneling-status</code> is <code>enable</code> , enter the TCP port number on which the web proxy listens.	
tunneling-status {enable   disable}	Enable to tunnel update requests through a web proxy.	disable

Variable	Description	Default
tunneling-username <username_str>	If <code>tunneling-status</code> is enable, enter the user name of the FortiMail unit's account on the web proxy.	
virus-db {default   extended   extreme}	<p>Depending on your models, FortiMail supports three types of antivirus databases:</p> <ul style="list-style-type: none"> <li>• Default: The default FortiMail virus database contains most commonly seen viruses and should be sufficient enough for regular antivirus protection. For the current release, FortiMail VM00 model supports the default virus database only.</li> <li>• Extended: Some high-end FortiMail models support the usage of an extended virus database, which contains viruses that are not active any more. For the current release, FortiMail VM01/VM02/200F/400F models support both the default and extended virus databases.</li> <li>• Extreme: Some high-end models also support the usage of an extreme virus database, which contains more virus signatures than the default and extended databases. For the current release, FortiMail VM04/900F and above models support all three types of virus databases.</li> </ul>	default
virus-outbreak {disable   enable   enable-with-defer}	<p>When a virus outbreak occurs, the FortiGuard antivirus database may need some time to get updated. Therefore, you can choose to defer the delivery of the suspicious email messages and scan them for the second time:</p> <ul style="list-style-type: none"> <li>• Disable: Do not query FortiGuard antivirus service.</li> <li>• Enable: Query FortiGuard antivirus service.</li> <li>• Enable with Defer: If the first query returns no results, defer the email for the specified time and do the second query.</li> </ul>	enable-with-defer
virus-outbreak-protection-period <minutes>	If you specify Enable with Defer in the above field, specify how many minutes later a second query will be done.	20

## Related topics

[system fortiguard antispam on page 295](#)  
update

## system fortiguard antispam

Use this command to configure how the FortiMail unit will connect to the FortiGuard servers to query for antispam signatures. Unlike the antivirus updates, FortiMail cannot query FortiGuard antispam service via a web proxy. If there is a web proxy before FortiMail, you have to use a FortiManager unit locally as an override server.

## Syntax

```

config system fortiguard antis spam
  set cache-mpercent <percentage_int>
  set cache-status {enable | disable}
  set cache ttl <tll_int>
  set hostname {<fqdn_str> | <host_ipv4>}
  set outbreak-protection-level {disable | high | low | medium}
  set outbreak-protection-period <minutes>
  set port {443 | 53 | 8888}
  set protocol {udp | https}
  set query-timeout <timeout_int>
  set action-rbl <action-profile_name>
  set server-override-ip <ipv4>
  set server-override-status {enable | disable}
  set status {enable | disable}
  set threshold-ip-connect <integer> on page 297
  set url-redirect-lookup {enable | disable}
end

```

Variable	Description	Default
cache-mpercent <percentage_int>	Enter the percentage of memory the antis spam cache is allowed to use in percentage. The range is 1-15%.	2
cache-status {enable   disable}	Enable cache and specify the cache time to live (TTL) to improve performance.	enable
cache ttl <tll_int>	Enter the TTL in seconds for cache entries.	300
hostname {<fqdn_str>   <host_ipv4>}	Enter an IP address or a fully qualified domain name (FQDN) to override the default FortiGuard Antis spam query server.	antis spam.fortigate.com
outbreak-protection-level {disable   high   low   medium}	Specify a spam outbreak protection level. Higher levels mean stricter filtering.  This feature temporarily holds email for a certain period of time (see outbreak-protection-period) if the enabled FortiGuard antis spam check (block-IP and/or URL filter) returns no result. After the specified time interval, FortiMail will query the FortiGuard server for the second time. This provides an opportunity for the FortiGuard antis spam service to update its database in cases a spam outbreak occurs.  Conversely, in order to reduce the types of email to be deferred for outbreak, set this command to low.	medium
outbreak-protection-period <minutes>	Specify how long (in minutes) FortiMail will hold email before it query the FortiGuard server for the second time.	30
port {443   53   8888}	Enter the port number used to communicate with the FortiGuard Antis spam query servers.	53
protocol {udp   https}	Enter the protocol used to communicate with the FortiGuard servers.	

Variable	Description	Default
query-timeout <timeout_int>	Enter the timeout value for the FortiMail unit to query the FortiGuard Antispam query server.	7
server-location	Limit the FortiGuard servers to certain locations.	
server-override-ip <ipv4>	If server-override-status is enable, enter the IP address of the public or private FortiGuard Antispam query server that overrides the default query server to which the FortiMail unit connects.	
server-override-status {enable   disable}	Enable to override the default FortiGuard Antispam query server to which the FortiMail unit connects to and checks for antispam signatures.	disable
status {enable   disable}	Enable to query to the FortiGuard Distribution Network (FDN) for FortiGuard Antispam ratings.  This option must be enabled for antispam profiles where the FortiGuard Antispam scan is enabled to have an effect.	enable
threshold-ip-connect <integer>	When you configure the FortiGuard IP reputation check under Sender Reputation in a session profile, if you choose the "When client connect" option, that means you want the FortiGuard Antispam Service to determine if the IP address of the SMTP server is blocklisted during the connection phase.  FortiGuard categorizes the blocklisted IP addresses into three levels -- level 3 has bad reputation; level 2 has worse reputation; and level 1 has the worst reputation. To help prevent false positives, you can choose to this command to specify which level to block.  <integer> is the level number: 1, 2, or 3. The default setting is 3, which means all levels will be blocked. If you want to block level 1 and level 2 but not level 3, you set it to 2.	3
url-redirect-lookup {enable   disable}	If an email contains a shortened URL that redirects to another URL, the FortiMail unit is able to send a request to the shortened URL to get the redirected URL and scan it against the FortiGuard AntiSpam database. By default, this function is enabled. To use it, you need to open your HTTP port to allow the FortiMail unit to send request for scanning the redirected URL.	enable

## Related topics

[system fortiguard antivirus on page 293](#)  
update

# system fortiguard url-protection

Use this command to configure content disarm and reconstruction (CDR) URL click protection options.

## Syntax

```
config system fortiguard url-protection
  set click-action {allow-with-confirmation | block}
  set click-category {all | default | phishing | unrated}
  set isolator-category {all | default | phishing | unrated}
  set isolator-url-base <string>
  set malformed-html-tag-content-action {remove | rewrite}
  set neutralize-category {all | default | phishing | unrated}
  set remove-category {all | default | phishing | unrated}
  set rewrite-category {all | default | phishing | unrated}
  set rewrite-url-base <string>
  set sandbox-click-action {allow-with-confirmation | block | submit-only}
  set sandbox-status {enable | disable}
  set sandbox-timeout <integer>
  set sandbox-timeout-action {allow | allow-with-confirmation | block}
end
```

Variable	Description	Default
click-action {allow-with-confirmation   block}	Set the FortiSandbox scan action for the click handling category.	block
click-category {all   default   phishing   unrated}	Set the URL filter category profile used to authorize URLs on click.	default
isolator-category {all   default   phishing   unrated}	Set the URL filter category profile used to identify URLs to be rewritten by Fortisolator.	unrated
isolator-url-base <string>	Define the rewrite URL base. Enter the prefix <code>https://</code> followed by the Fortisolator FQDN or IP address.	
malformed-html-tag-content-action {remove   rewrite}	Set the malformed HTML tag content action: remove or rewrite URLs that are not exempted.	remove
neutralize-	Set the URL filter category profile used to identify URLs to neutralize.	unrated

Variable	Description	Default
category {all   default   phishing   unrated}		
remove-category {all   default   phishing   unrated}	Set the URL filter category profile used to identify URLs to remove.	default
rewrite-category {all   default   phishing   unrated}	Set the URL filter category profile used to identify URLs to rewrite.	unrated
rewrite-url-base <string>	Define the rewrite URL base. Enter the prefix <code>https://</code> followed by the FortiMail FQDN or IP address.	
sandbox-click-action {allow-with-confirmation   block   submit-only}	Set the FortiSandbox click action: <ul style="list-style-type: none"> <li><code>allow-with-confirmation</code>: Allow access with a warning.</li> <li><code>block</code>: Block access.</li> <li><code>submit-only</code>: Allows access while sending the URLs for scanning.</li> </ul>	allow-with-confirmation
sandbox-status {enable   disable}	Enable or disable FortiSandbox scanning.	disable
sandbox-timeout <integer>	Specify how long (in seconds) you want to wait for FortiSandbox scan results before you take block, allow, or allow with confirmation actions.	5
sandbox-timeout-action {allow   allow-with-confirmation   block}	Set the FortiSandbox timeout action. When URLs are sent to FortiSandbox for scanning, it may take a while to get the results back. It's recommended to specify how long you want to wait for the results (see <a href="#">sandbox-timeout &lt;integer&gt;</a> ) before an action is taken.	allow

## system fortisandbox

The FortiSandbox unit is used for automated sample tracking, or sandboxing. You can send suspicious email attachments to FortiSandbox for inspection when you configure antivirus profiles. If the file exhibits risky behavior, or is found to contain a virus, the result will be sent back to FortiMail and a new virus signature is created and added to

the FortiGuard antivirus signature database. For more information about FortiSandbox, please visit Fortinet's web site at <https://www.fortinet.com>.

## Syntax

```
config system fortisandbox
  config file-pattern
    edit <table_value>
      set pattern <string>
    end
  config file-types
    edit {adobe-flash | archive | html | jar | javascript | pdf | msoffice-document | windows-executable}
      set status {enable | disable}
    end
  set admin-email <email_str>
  set bypass-one-time-url {enable | disable}
  set host <hostname_or_ip>
  set max-file-size <integer_value>
  set max-file-size-status {enable | disable}
  set max-url-per-email
  set scan-mode {scan-and-wait | scan-only}
  set scan-order {antispam-content-sandbox | antispam-sandbox-content | sandbox-antispam-content}
  set scan-result-retention
  set scan-timeout
  set service-type {appliance | cloud | cloud-enhanced}
  set statistics-interval <minutes>
  set status {enable | disable}
  set url-scan-category
  set url-scan-email-selection
  set url-scan-on-rating-error {enable | disable}
end
```

Variable	Description	Default
file-pattern	Enter the file patterns to upload to FortiSandbox	
<table_value>	Enter the item number to edit.	
pattern <string>	Enter the pattern value.	
file-types	Enter the file types to upload to FortiSandbox for scanning.	
edit <file_types>	Enter the desired attachment type to include in the FortiSandbox unit's scanning.	
status {enable   disable}	Enable or disable the selected file type from the FortiSanbox unit's scanning.	
admin-email <email_str>	Enter the administrator's email address to receive reports and notifications.	
bypass-one-time-url {enable   disable}	Enable to automatically exempt common one-time URLs, such as password reset URLs, from FortiSandbox scanning.	enable

Variable	Description	Default
host <hostname_or_ip>	Enter the host name or IP address of the FortiSandbox.	
max-file-size <integer_value>	Enter the maximum size in kilobytes for files uploaded to FortiSandbox.	
max-file-size-status {enable   disable}	Enable or disable the maximum size for files uploaded to FortiSandbox.	
max-url-per-email	Maximum number of URLs per email to be scanned. Range between 1-12.	3
scan-mode {scan-and-wait   scan-only}	scan-and-wait means to submit the suspicious email to FortiSandbox and wait for the results. scan-only means just to submit the suspicious email without waiting for the results.	scan-and-wait
scan-order {antispam-content-sandbox   antispam-sandbox-content   sandbox-antispam-content}	Set the order of scanners. Sending files to FortiSandbox usually takes more bandwidth and thus it is better to use is as the last resort.	antispam-content-sandbox
scan-result-retention	Scan result retention period in minutes (0 means no retention).	60
scan-timeout	Timeout value before discarding unfinished scan tasks.	30
service-type {appliance   cloud   cloud-enhanced}	Use either FortiSandbox appliance, FortiSandbox regular cloud service, or FortiSandbox enhanced cloud service. The enhanced cloud service provides a dedicated service for faster performance.	appliance
statistics-interval <minutes>	Specify how long in minutes FortiMail should wait to retrieve some high level statistics from FortiSandbox. The statistics include how much malware is detected and how many files are clean among all the files submitted. Set the value between 1 to 30.	5
status {enable   disable}	Either enable or disable the usage of the unit.	disable
url-scan-category	Category of the URL to be scanned: <ul style="list-style-type: none"> <li>• Security-Risk</li> <li>• all</li> <li>• default</li> <li>• phishing</li> <li>• unrated</li> </ul>	unrated
url-scan-email-selection	Selection of email for URL scan.	
url-scan-on-rating-error {enable   disable}	Sometimes, FortiMail may not be able to get results from the FortiGuard queries (for example, ratings errors due to network connection failures). In this case, you can choose whether to upload the those URLs to FortiSandbox for scanning. Choosing not to upload those URLs may help improving the FortiSandbox performance.	disable

# system geoip-override

Use this command to override the GeoIP lookup by manually specifying the geolocations of some IP addresses/IP ranges.

## Syntax

```
config system geoip-override
  set description
  set country-code
end
```

Variable	Description	Default
description	Enter a description.	
country-code	Enter the two letter country code (for example US, CA).	

# system global

Use this command to configure many FortiMail system-wide configurations.

## Syntax

```
config system global
  set admin-idle-timeout <timeout_int>
  set admin-lockout-duration on page 303
  set admin-lockout-threshold on page 303
  set admin-maintainer {enable | disable}
  set default-certificate <name_str>
  set dh-params <params_int>
  set disclaimer-per-domain {enable | disable}
  set disk-monitor {enable | disable}
  set email-migration-status {enable | disable}
  set hostname <host_str>
  set iscsi-initiator-name <name_str>
  set lcd-pin <pin_int>
  set lcd-protection {enable | disable}
  set ldap-server-sys-status {enable | disable}
  set ldap-sess-cache-state {enable | disable}
  set local-domain-name <name_str>
  set mailstat-service {enable | disable}
  set max-admin-per-domain <integer>
  set mta-adv-ctrl-status {enable | disable}
  set operation-mode {gateway | server | transparent}
  set pki-certificate-req {yes | no}
```

```

set pki-mode {enable | disable}
set port-http <port_int>
set port-https <port_int>
set port-ssh <port_int>
set port-telnet <port_int>
set post-login-banner {admin | ibe | webmail}
set pre-login-banner admin
set ssl-versions {ssl3 tls1_0 | tls1_1 | tls1_2 | tls1_3}
set strong-crypto {enable | disable}
set tftp {enable | disable}
end

```

Variable	Description	Default
admin-idle-timeout <timeout_int>	Enter the amount of time in minutes after which an idle administrative session will be automatically logged out. The maximum idle time out is 480 minutes (eight hours). To improve security, do not increase the idle timeout.	5
admin-lockout-duration	Enter the lockout duration in minutes after the failed login threshold is reached.	3
admin-lockout-threshold	Enter the number of failed login attempts before being locked out.	4
admin-maintainer {enable   disable}	Enable or disable the maintainer administrator login. When enabled, the maintainer account can be used to log in from the console after a hard reboot. The password is \ 'bcpb\ ' followed by the unit serial number. Note that there is a limited time to complete this login. If you attempt to disable admin-maintainer, a message appears warning that the password recovery mechanism will be lost. Do not disable this option if you do not have a backup plan for recovery.	enable
default-certificate <name_str>	Enter the name of a local certificate to use it as the "default" (that is, currently chosen for use) certificate. FortiMail units require a local server certificate that it can present when clients request secure connections.	factory
dh-params <params_int>	Enter the minimum size of Diffie-Hellman prime for SSH/HTTPS.	1024
disclaimer-per-domain {enable   disable}	Enable to allow individualized disclaimers to be configured for each protected domain.	
disk-monitor {enable   disable}	Enable to monitor the hard disk status of the FortiMail unit. If a problem is found, an alert email is sent to the administrator.	disable
email-migration-status {enable   disable}	Enable the email migration from external server.	
hostname <host_str>	Enter the host name of the FortiMail unit.	Varies by model.

Variable	Description	Default
hsts-max-age <days>	Set the HTTP Strict Transport Security (HSTS) max-age. 0 means to disable.	365
iscsi-initiator-name <name_str>	Enter the FortiMail iSCSI client name used to communicate with the iSCSI server for centralized quarantine storage. This is only used to change the name generated by the FortiMail unit automatically.	
lcd-pin <pin_int>	Enter the 6-digit personal identification number (PIN) that administrators must enter in order to access the FortiMail LCD panel. The PIN is used only when <code>lcdprotection</code> is enable.	Encoded value varies.
lcd-protection {enable   disable}	Enable to require that administrators enter a PIN in order to use the buttons on the front LCD panel. Also configure <code>lcdpin</code> .	disable
ldap-server-sys-status {enable   disable}	Enable or disable the LDAP server for serving organizational information.	enable
ldap-sess-cache-state {enable   disable}	Enable to keep the continuity of the connection sessions to the LDAP server. Repeated session connections waste network resources.	enable
local-domain-name <name_str>	Enter the local domain name of the FortiMail unit.	
mailstat-service {enable   disable}	Enable the mail statistic service. After you enable this service, a new tab called Top User Statistics will appear under FortiView on the GUI.	disable
max-admin-per-domain <integer>	Set the maximum number of admins per domain. The valid range is 1 to 10.	3
mta-adv-ctrl-status {enable   disable}	Enable to configure advanced session-specific MTA settings (see <a href="#">profile session on page 247</a> ) and overwrite the global settings configured elsewhere. <b>Note:</b> The MTA advanced control feature requires a valid feature license.	enable
operation-mode {gateway   server   transparent}	Enter one of the following operation modes: <ul style="list-style-type: none"> <li>gateway: The FortiMail unit acts as an email gateway or MTA, but does not host email accounts.</li> <li>server: The FortiMail unit acts as a standalone email server that hosts email accounts and acts as an MTA.</li> <li>transparent: The FortiMail unit acts as an email proxy.</li> </ul> <b>Note:</b> Only administrators with <code>super_admin</code> privileges may change the FortiMail unit's operation mode.	gateway
pki-certificate-req {yes   no}	If the administrator's web browser does not provide a valid personal certificate for PKI authentication, the FortiMail unit will fall back to standard user name and password-style authentication. To require valid certificates only and disallow password-style fallback, enter yes. To allow password-style fallback, enter no.	no
pki-mode {enable   disable}	Enable to allow PKI authentication for FortiMail administrators. For more information, see <a href="#">user pki on page 347</a> and <a href="#">system admin on page 270</a> .	disable

Variable	Description	Default
	<p>Also configure <code>pki-certificate-req {yes   no}</code>.</p> <p><b>Caution:</b> Before disabling PKI authentication, select another mode of authentication for FortiMail administrators and email users that are currently using PKI authentication. Failure to first select another authentication method before disabling PKI authentication will prevent them from being able to log in.</p>	
port-http <port_ int>	Enter the HTTP port number for administrative access on all interfaces.	80
port-https <port_ int>	Enter the HTTPS port number for administrative access on all interfaces.	443
port-ssh <port_ int>	Enter the SSH port number for administrative access on all interfaces.	22
port-telnet <port_ int>	Enter the TELNET port number for administrative access on all interfaces.	23
post-login-banner {admin   ibe   webmail}	<p>Enable or disable the legal disclaimer.</p> <p><b>admin:</b> Select to display the disclaimer message <b>after</b> the administrator logs into the FortiMail web UI.</p> <p><b>webmail:</b> Select to display the disclaimer message after the user logs into the FortiMail webmail.</p> <p><b>ibe:</b> Select to display the disclaimer message after the user logs into the FortiMail unit to view IBE encrypted email.</p>	admin
pre-login-banner admin	Enable or disable the legal disclaimer <b>before</b> the administrator logs into the FortiMail web UI.	admin
ssl-versions {ssl3   tls1_0   tls1_1   tls1_2   tls1_3}	<p>Specify which SSL/TLS versions you want to support for the HTTPS and SMTP access to FortiMail. Currently, TLS 1.0, TLS 1.1, TLS 1.2, and TLS 1.3 are supported.</p> <p>In 6.0.0 release, <code>strong-crypto</code> is enabled and TLS 1.0 is disabled by default. Because some old versions of email clients (for example, MS Outlook 2007 and older) and MTAs only support TLS 1.0, they may have issues connecting to FortiMail. To fix the issue, disable <code>strong-crypto</code> and add TLS 1.0 support. Starting from 6.0.1 release, both <code>strong-crypto</code> and TLS 1.0 are enabled by default.</p> <p>Starting from 6.2.0, when <code>strong-crypto</code> is enabled, TLS 1.0 is disabled.</p> <p>When <code>strong-crypto</code> is enabled, SSL 3.0 is only supported in 5.4 releases, not in 6.0 and 6.2 releases.</p>	ssl3 tls1_0, tls1_1, tls1_2 tls1_3
strong-crypto {enable   disable}	<p>Enable to use strong encryption and only allow strong ciphers (AES) and digest (SHA1) for HTTPS/SSH admin access.</p> <p>When strong encryption is enabled, HTTPS is supported by the following web browsers: Netscape 7.2, Netscape 8.0, Firefox, and Microsoft Internet Explorer 7.0 (beta) and higher.</p> <p>Note that Microsoft Internet Explorer 5.0 and 6.0 are not supported in strong encryption.</p>	enable

Variable	Description	Default
tftp {enable   disable}	Enable to allow use of TFTP in FIPS mode.	enable

## Related topics

[config domain-setting on page 108](#)

## system ha

Use this command to configure the FortiMail unit to act as a member of a high availability (HA) cluster in order to increase processing capacity or availability. It also enables you to monitor the HA cluster.

## Syntax

```
config system ha
  config interface
    edit <interface_name>
      set status {enable | disable}
      set heartbeat-status <disable | primary | secondary>
      set peer-ip <ipv4_netmask>
      set peer-ip6 <ipv6_netmask>
      set port-monitor {enable | disable}
      set virtual-ip <ipv4_netmask>
      set virtual-ip6 <ipv6_netmask>
  config service
    edit <remote-smtp>
      set check-interval <integer>
      set check-timeout <integer>
      set ip <ip_addr>
      set port <port_num>
      set retries <integer>
      set status {enable | disable}
    edit <remote-imap>
      set check-interval <integer>
      set check-timeout <integer>
      set ip <ip_addr>
      set port <port_num>
      set retries <integer>
      set status {enable | disable}
    edit <remote-pop>
      set check-interval <integer>
      set check-timeout <integer>
      set ip <ip_addr>
      set port <port_num>
      set retries <integer>
```

```

    set status {enable | disable}
edit <remote-http>
    set check-interval <integer>
    set check-timeout <integer>
    set ip <ip_addr>
    set port <port_num>
    set retries <integer>
    set status {enable | disable}
edit <local-ports>
    set check-interval <integer>
    set retries <integer>
    set status {enable | disable}
edit <local-hd>
    set check-interval <integer>
    set retries <integer>
    set status {enable | disable}
set system ha
set config-peer-ip <ip_addr>
set failover <interface_str> {add | bridge | ignore | set}<address_ipv4mask>
set hard-drives-check {enable | disable}
set hb-base-port <interface_int>
set hb-lost-threshold
set heartbeat-1-interface <interface_int>
set heartbeat-1-ip <local_ipv4mask>
set heartbeat-1-peer <primary-peer_ipv4>
set heartbeat-2-interface <interface_str>
set heartbeat-2-ip <secondary-local_ipv4mask>
set heartbeat-2-peer <secondary-peer_ipv4>
set mail-data-sync {enable | disable}
set mailqueue-data-sync {enable | disable}
set mode {config-primary | config-secondary | primary | off | secondary}
set on-failure {off | restore-role | become-secondary}
set password <password_str>
set remote-services-as-heartbeat {enable | disable}
end

```

Variable	Description	Default
<interface_name>	Enter the interface name of which you want to configure the virtual IP.	
action-on-primary {ignore-vip   use- vip}	Select whether and how to configure the IP addresses and netmasks of the primary FortiMail unit: <ul style="list-style-type: none"> <li>ignore-vip: Do not change the network interface configuration on failover, and do not monitor.</li> <li>use-vip: Add the specified virtual IP address and netmask to the network interface on failover. Normally, you will configure your network (MX records, firewall policies, routing and so on) so that clients and mail services use the virtual IP address. Both originating and reply traffic uses the virtual IP address. This option results in the network interface having two IP addresses: the actual and the virtual.</li> </ul>	ignore-vip
heartbeat-status <disable   primary   secondary>	Specify if this interface will be used for HA heartbeat and synchronization. <ul style="list-style-type: none"> <li>disable: Do not use this interface for HA heartbeat and synchronization.</li> <li>primary: Select the primary network interface for heartbeat and</li> </ul>	

Variable	Description	Default
	<p>synchronization traffic.</p> <p>This network interface must be connected directly or through a switch to the <b>Primary heartbeat</b> network interface of other members in the HA group.</p> <ul style="list-style-type: none"> <li>• <b>secondary</b>: Select the secondary network interface for heartbeat and synchronization traffic.</li> </ul> <p>The secondary heartbeat interface is the backup heartbeat link between the units in the HA group. If the primary heartbeat link is functioning, the secondary heartbeat link is used for the HA heartbeat. If the primary heartbeat link fails, the secondary link is used for the HA heartbeat and for HA synchronization.</p> <p>This network interface must be connected directly or through a switch to the <b>Secondary heartbeat</b> network interfaces of other members in the HA group.</p> <p><b>Caution:</b> Using the same network interface for both HA synchronization/heartbeat traffic and other network traffic could result in issues with heartbeat and synchronization during times of high traffic load, and is not recommended.</p> <p><b>Note:</b> In general, you should isolate the network interfaces that are used for heartbeat traffic from your overall network. Heartbeat and synchronization packets contain sensitive configuration information, are latency-sensitive, and can consume considerable network bandwidth.</p>	
peer-ip <ipv4_netmask>	<p>Enter the IP address of the matching heartbeat network interface of the other member of the HA group.</p> <p>For example, if you are configuring the primary unit's primary heartbeat network interface, enter the IP address of the secondary unit's primary heartbeat network interface.</p> <p>Similarly, for the secondary heartbeat network interface, enter the IP address of the other unit's secondary heartbeat network interface.</p> <p>This option appears only for active-passive HA.</p>	
peer-ip6 <ipv6_netmask>	Enter the peer IPv6 address in the active-passive HA group.	
port-monitor {enable   disable}	<p>Enable to monitor a network interface for failure. If the port fails, the primary unit will trigger a failover.</p> <p>This option applies only if local network interface monitoring is enabled.</p>	
virtual-ip <ipv4_netmask>	<p>Enter the virtual IP address and netmask for this interface.</p> <p>This option is available only if <code>status {enable   disable}</code> is set.</p>	0.0.0.0/0
virtual-ip6 <ipv6_netmask>	<p>Enter the virtual IPv6 address and netmask for this interface.</p> <p>This option is available only if <code>status {enable   disable}</code> is set.</p>	0.0.0.0/0
<remote-smtp>	Enter to configure the remote SMTP service monitoring.	
check-interval <integer>	Enter the time interval between service checks in seconds.	120

Variable	Description	Default
check-timeout <integer>	Enter the timeout for remote service check in seconds.	30
ip <ip_addr>	Enter the SMTP server IP address for service check.	0.0.0.0
port <port_num>	Enter the SMTP server port number for service check.	25
retries <integer>	Enter the number of attempts to try before considering the SMTP server a failure.	3
status {enable   disable}	Enable to start the remote SMTP service monitoring.	disable
<remote-imap>	Enter to configure the remote IMAP service monitoring.	
check-interval <integer>	Enter the time interval between service checks in seconds.	120
check-timeout <integer>	Enter the timeout for remote service check in seconds.	30
ip <ip_addr>	Enter the IMAP server IP address for service check.	0.0.0.0
port <port_num>	Enter the IMAP server port number for service check.	143
retries <integer>	Enter the number of attempts to try before considering the IMAP server a failure.	3
status {enable   disable}	Enable to start the remote IMAP service monitoring.	disable
<remote-pop>	Enter to configure the remote POP service monitoring.	
check-interval <integer>	Enter the time interval between service checks in seconds.	120
check-timeout <integer>	Enter the timeout for remote service check in seconds.	30
ip <ip_addr>	Enter the POP server IP address for service check.	0.0.0.0
port <port_num>	Enter the POP server port number for service check.	110
retries <integer>	Enter the number of attempts to try before considering the POP server a failure.	3
status {enable   disable}	Enable to start the remote POP service monitoring.	disable
<remote-http>	Enter to configure the remote HTTP service monitoring.	
check-interval <integer>	Enter the time interval between service checks in seconds.	120
check-timeout <integer>	Enter the timeout for remote service check in seconds.	30
ip <ip_addr>	Enter the HTTP server IP address for service check.	0.0.0.0
port <port_num>	Enter the HTTP server port number for service check.	80

Variable	Description	Default
retries <integer>	Enter the number of attempts to try before considering the HTTP server a failure.	3
status {enable   disable}	Enable to start the remote HTTP service monitoring.	disable
<local-ports>	Enter to configure the local network interfaces service monitoring.	
check-interval <integer>	Enter the time interval between service checks in seconds.	120
retries <integer>	Enter the number of attempts to try before considering the local network interface a failure.	3
status {enable   disable}	Enable to start the local network interface service monitoring.	disable
<local-hd>	Enter to configure the local hard drives service monitoring.	
check-interval <integer>	Enter the time interval between service checks in seconds.	120
retries <integer>	Enter the number of attempts to try before considering the hard drive a failure.	3
status {enable   disable}	Enable to start the local hard drive service monitoring.	disable
config-peer-ip <ip_addr>	Enter the IP address of the secondary FortiMail unit.	0.0.0.0
failover <interface_ str> {add   bridge   ignore   set}<address_ ipv4mask>	<p>Use this option to configure whether and how to configure the IP addresses and netmasks of the primary FortiMail unit.</p> <p>For example, a primary unit might be configured to receive email traffic through port1 and receive heartbeat and synchronization traffic through port5 and port6. In that case, you would configure the primary unit to set the IP addresses or add virtual IP addresses for port1 of the backup unit upon failover in order to mimic that of the primary unit.</p> <p>This option applies only for FortiMail units operating in the active-passive HA mode, as a primary unit (The configuration of this command is synchronized to the backup unit for use when it assumes the role of the primary unit).</p> <p>Enter the name of a network interface, such as port6, or enter mgmt to configure the management IP address (transparent mode only), then enter one of the following behaviors of the network interface when this FortiMail unit is acting as the primary unit:</p> <p>ignore: Do not change the network interface configuration upon failover, and do not monitor. For details on service monitoring for network interfaces, see <a href="#">local-service {ports   hd} &lt;interval_int&gt; &lt;retries_int&gt;</a>.</p> <p>Primary and secondary heartbeat network interfaces must use this option.</p> <p>set: Change the network interface to use the specified IP address and netmask upon failover.</p>	

Variable	Description	Default
	<p><b>add:</b> Add the specified virtual IP address and netmask to the network interface upon failover. Normally, you will configure your network (MX records, firewall policies, routing and so on) so that clients and mail services use the virtual IP address. Both originating and reply traffic uses the virtual IP address. All replies to sessions with the virtual IP address include the virtual IP address as the source address. Originating traffic, however, will use the network interface's actual IP address as the source address.</p> <p><b>bridge:</b> Include the network interface in the Layer 2 bridge. While the effective operating mode is secondary, the interface is deactivated and cannot process traffic, preventing Layer 2 loops. Then, when the effective operating mode becomes primary, the interface is activated again and can process traffic. This option applies only if the FortiMail unit is operating in transparent mode, and for mail interfaces that are already members of the bridge. For information on configuring bridging network interfaces, see <a href="#">system interface on page 316</a>.</p> <p>Network interface(s) configured as the primary heartbeat and secondary heartbeat network interface are required to maintain their IP addresses for heartbeat and synchronization purposes, and cannot be configured with the type set or bridge.</p> <p>After entering a network interface behavior, enter the IP address and netmask.</p> <p>If you have entered bridge or ignore for the previous keyword, because those behaviors do not use IP addresses, you may enter <code>0.0.0.0 0.0.0.0</code>.</p>	
hard-drives-check {enable   disable}	Enable to test the responsiveness of the hard drives.	disable
hb-base-port <interface_int>	<p>Enter the first of four total TCP port numbers that will be used for:</p> <ul style="list-style-type: none"> <li>the heartbeat signal</li> <li>synchronization control</li> <li>data synchronization</li> <li>configuration synchronization</li> </ul> <p><b>Note:</b> For active-passive groups, in addition or alternatively to configuring the heartbeat, you can configure service monitoring.</p>	20000
hb-lost-threshold	<p>Enter the total span of time, in seconds, for which the primary unit can be unresponsive before it triggers a failover and the backup unit assumes the role of the primary unit.</p> <p>The heartbeat will continue to check for availability once per second. To prevent premature failover when the primary unit is simply experiencing very heavy load, configure a total threshold of three (3) seconds or more to allow the backup unit enough time to confirm unresponsiveness by sending additional heartbeat signals.</p> <p>This option appears only for active-passive groups.</p>	15

Variable	Description	Default
	<p><b>Note:</b> If the failure detection time is too short, the backup unit may falsely detect a failure when during periods of high load.</p> <p><b>Caution:</b> If the failure detection time is too long the primary unit could fail and a delay in detecting the failure could mean that email is delayed or lost. Decrease the failure detection time if email is delayed or lost because of an HA failover.</p>	
heartbeat-1-interface <interface_int>	Enter the name of the network interface that will be used for the primary heartbeat, and that is connected directly or through a switch to the primary heartbeat interface of the other FortiMail unit(s) in the HA group.	Varies by model (the network interface with the highest number).
heartbeat-1-ip <local_ipv4mask>	Enter the IP address and netmask of the primary network interface, separated by a space.  Use this IP address as the value of the peer IP address when configuring <a href="#">heartbeat-1-peer &lt;primary-peer_ipv4&gt;</a> for the other FortiMail units in the HA group.	10.0.0.1 255.255.255.0
heartbeat-1-peer <primary-peer_ipv4>	Enter the IP address of the primary heartbeat network interface on the other FortiMail unit in the HA group.  For example, if the primary heartbeat network interface on the other FortiMail unit has an IP address of 10.0.0.1, enter 10.0.0.1.	10.0.0.2
heartbeat-2-interface <interface_str>	Enter the name of a network interface: Use this network interface as the secondary heartbeat network interface. It must be connected to the secondary heartbeat network interface on the other FortiMail unit in the HA group. Also configure <a href="#">heartbeat-2-ip &lt;secondary-local_ipv4mask&gt;</a> on page 312.	Varies by model (the network interface with the highest number).
heartbeat-2-ip <secondary-local_ipv4mask>	Enter the IP address and netmask of the secondary network interface, separated by a space.  Use this IP address as the value of the peer IP address when configuring <a href="#">heartbeat-2-peer &lt;secondary-peer_ipv4&gt;</a> for the other FortiMail units in the HA group.	0.0.0.0 0.0.0.0
heartbeat-2-peer <secondary-peer_ipv4>	Enter the IP address of the secondary heartbeat network interface on the other FortiMail unit in the HA group.  For example, if the secondary heartbeat network interface on the other FortiMail unit has an IP address of 10.0.0.3, enter 10.0.0.3.	0.0.0.0
local-service {ports   hd} <interval_int> <retries_int>	Enter a local service to monitor.  If you enter ports, continue entering:  <interval_int>: Enter the amount of time in seconds between each network interface check.  The valid range is between 1 and 60 seconds, or 0 to disable checking. The default value is 0.	PORTS 10 3 HD 10 3

Variable	Description	Default
	<p>&lt;retries_int&gt;: Enter the number of times a network interface must consecutively fail to respond in order to trigger a failover. The valid range is 1 to a very high number. The default value is 0.</p> <p>If you enter hd, continue entering:</p> <p>&lt;interval_int&gt;: Enter the amount of time in seconds between each hard drive check. The valid range is between 1 and 60 seconds, or 0 to disable checking. The default value is 0.</p> <p>&lt;retries_int&gt;: Enter the number of times a hard drive must consecutively fail to respond in order to trigger a failover. The valid range is 1 to a very high number. The default value is 0.</p> <p>During local service monitoring, the primary unit in an active-passive HA group monitors its own network interfaces and hard drives. If either of these local services fails, the primary unit triggers a failover by switching its effective operating mode to "off," and no longer responding to the heartbeat of the backup unit. The backup unit then becomes the new primary unit.</p> <p>If service monitoring detects a failure, the effective operating mode of the primary unit switches to OFF or FAILED (depending on the "On failure" setting) and, if configured, the FortiMail units send HA event alert email, record HA event log messages, and send HA event SNMP traps. A failover then occurs, and the effective operating mode of the backup unit switches to primary.</p> <p>This command applies only if the FortiMail unit is operating in an active-passive HA group, as the primary unit.</p>	
mail-data-sync {enable   disable}	<p>Enable to synchronize system quarantine, email archives, email users' mailboxes (server mode only), preferences, and per-recipient quarantines. Unless the HA cluster stores its mail data on a NAS server, you should configure the HA cluster to synchronize mail directories. This option applies only for active-passive groups.</p>	enable
mailqueue-data-sync {enable   disable}	<p>Enable to synchronize the mail queue of the FortiMail unit. This option applies only for active-passive groups.</p> <p>Caution: If the primary unit experiences a hardware failure and you cannot restart it, if this option is disabled, MTA spool directory data could be lost.</p> <p>Note: Enabling this option is not recommended. Periodic synchronization can be processor and bandwidth-intensive. Additionally, because the content of the MTA spool directories is very dynamic, periodically synchronizing MTA spool directories between FortiMail units may not guarantee against loss of all email in those directories. Even if MTA spool directory synchronization is disabled, after a failover, a separate synchronization mechanism may successfully prevent loss of MTA spool data.</p>	disable

Variable	Description	Default
mode {config-primary   config-secondary   primary   off   secondary}	<p>Enter one of the following HA operating modes:</p> <p>config-primary: Enable HA and operate as the primary unit in a config-only HA group.</p> <p>config-secondary: Enable HA and operate as the backup unit in a config-only HA group.</p> <p>primary: Enable HA and operate as the primary unit in an active-passive HA group.</p> <p>off: Disable HA. Each FortiMail unit operates independently.</p> <p>secondary: Enable HA and operate as the backup unit in an active-passive HA group.</p> <p><b>Caution:</b> For config-only HA, if the FortiMail unit is operating in server mode, you must store mail data externally, on a NAS server. Failure to store mail data externally could result in mailboxes and other data scattered over multiple FortiMail units. For details on configuring NAS, see the <a href="#">FortiMail Administration Guide</a>.</p>	off
network-intf-check {enable   disable}	<p>Enable to test the responsiveness of network interfaces.</p> <p>Network interface monitoring tests all active network interfaces whose: <a href="#">failover &lt;interface_str&gt; {add   bridge   ignore   set}&lt;address_ipv4mask&gt;</a> setting is <b>not</b> ignore and <a href="#">port-monitor {enable   disable}</a> setting is enable.</p>	enable
on-failure {off   restore-role   become-secondary}	<p>Enter one of the following behaviors of the primary unit when it detects a failure.</p> <p>off: Do not process email or join the HA group until you manually select the effective operating mode.</p> <p>restore-role: On recovery, the failed primary unit's effective operating mode resumes its configured operating mode. This behavior may be useful if the cause of failure is temporary and rare, but may cause problems if the cause of failure is permanent or persistent.</p> <p>become-secondary: On recovery, the failed primary unit's effective operating mode becomes secondary (backup), and it then synchronizes the content of its MTA spool directories with the current primary unit. The new primary unit can then deliver email that existed in the former primary unit's MTA spool at the time of the failover.</p> <p>In most cases, you should enter become-secondary.</p> <p>For details on the effects of this option on the effective operating mode, see the <a href="#">FortiMail Administration Guide</a>. This option applies only if the FortiMail unit is operating in an active-passive HA group, as a primary unit.</p>	
password <password_str>	<p>Enter a password for the HA group. The password must be the same on the primary and backup FortiMail unit(s). The password must be a least 1 character.</p>	change_me

Variable	Description	Default
remote-service {smtp   pop   imap   http} <interface_ ipv4> <port_int> <interval_int> <wait_int> <retries_int>	<p>Enter a remote service to monitor. Then enter the subsequent values in order:</p> <p>&lt;interface_ipv4&gt;: Enter the IP address to contact when testing the availability of the service. The default value is 0.0.0.0.</p> <p>&lt;port_int&gt;: Enter the TCP port number on which the remote FortiMail unit listens for connections of that service type. The default value is 0. For example, if you have configured the primary FortiMail unit to listen for SMTP connections on TCP port 25, you would enter 25.</p> <p>&lt;interval_int&gt;: Enter the interval in minutes between each remote service availability test. The valid range is 1 to 60 minutes, or 0 to disable remote service monitoring. The default value is 0.</p> <p>&lt;wait_int&gt;: Enter the amount of time in seconds to wait for the primary unit to respond to the remote service availability test. The valid range is 1 to a very high number of seconds, or 0 to disable remote service monitoring. The default value is 0.</p> <p>&lt;retries_int&gt;: Enter the number of consecutive availability test failures after which the primary unit is deemed unresponsive and a failover occurs. The valid range is 1 to a very high number, or 0 to disable remote service monitoring. The default value is 0.</p> <p>This option applies only if the FortiMail unit is operating in an active-passive HA group, as a backup unit.</p>	
remote-services- as-heartbeat {enable   disable}	<p>Enable to use remote service monitoring as a tertiary heartbeat signal. This option applies only for FortiMail units operating in the active-passive HA mode, and requires that you also configure remote service monitoring using.</p>	
<wait_int>	<p>Enter the amount of time in seconds to wait for the primary unit to respond to the remote service availability test. The valid range is 1 to a very high number of seconds, or 0 to disable remote service monitoring.</p>	0
<retries_int>	<p>Enter the number of consecutive availability test failures after which the primary unit is deemed unresponsive and a failover occurs. The valid range is 1 to a very high number, or 0 to disable remote service monitoring.</p>	0
smtp-check {enable   disable}	<p>Enable to test the connection responsiveness of SMTP.</p>	disable

## Related topics

[system geoip-override on page 302](#)

[system ha](#)

## system interface

Use this command to configure allowed and denied administrative access protocols, maximum transportation unit (MTU) size, SMTP proxy, and up or down administrative status for the network interfaces of a FortiMail unit.

Proxy and built-in MTA behaviors are configured separately based upon whether the SMTP connection is considered to be incoming or outgoing. Because a network connection considers the network layer rather than the application layer when deciding whether to intercept a connection, the concept of incoming and outgoing connections is based upon slightly different things than that of incoming and outgoing email messages: directionality is determined by IP addresses of connecting clients and servers, rather than the email addresses of recipients.

Incoming connections consist of those destined for the SMTP servers that are protected domains of the FortiMail unit. For example, if the FortiMail unit is configured to protect the SMTP server whose IP address is 10.1.1.1, the FortiMail unit treats all SMTP connections destined for 10.1.1.1 as incoming. For information about configuring protected domains, see [config domain-setting on page 108](#).

Outgoing connections consist of those destined for SMTP servers that the FortiMail unit has not been configured to protect. For example, if the FortiMail unit is **not** configured to protect the SMTP server whose IP address is 192.168.1.1, all SMTP connections destined for 192.168.1.1 will be treated as outgoing, regardless of their origin.

## Syntax

```
config system interface
  edit <physical_interface_str>, <logical_interface_str>, or loopback
    set allowaccess {ping http https snmp ssh telnet}
    set connection {enable | disable}
    set defaultgw {enable | disable}
    set bridge-member {enable | disable}
    set ip <ipv4mask>
    set ip6 <ipv6mask>
    set mac-addr <xx.xx.xx.xx.xx.xx>
    set mailaccess {imap | imaps | pop3 | pop3s | smtp | smtps}
    set mode {static | dhcp}
    set mtu <mtu_int>
    set proxy-smtp-in-mode {pass-through | drop | proxy}
    set proxy-smtp-local status {enable | disable}
    set proxy-smtp-out-mode {pass-through | drop | proxy}
    set speed {auto | 10full | 10half | 100full | 100half | 1000full}
    set status {down | up}
    set type {vlan | redundant}
    set vlanid <int>
    set webaccess
    set redundant-link-monitor {mii-link | arp-link}
    set redundant-arp-ip <ip_addr>
    set redundant-member <member_interface_str>
  end
```

Variable	Description	Default
<physical_interface_str>	Enter the name of the physical network interface, such as port1.	
<logical_interface_str>	Enter a name for the VLAN or redundant interface. Then set the interface type.	
loopback	<p>A loopback interface is a logical interface that is always up (no physical link dependency) and the attached subnet is always present in the routing table. The FortiMail's loopback IP address does not depend on one specific external port, and is therefore possible to access through several physical or VLAN interfaces. In the current release, you can only add one loopback interface on the FortiMail unit.</p> <p>The loopback interface is useful when you use a layer 2 load balancer in front of several FortiMail units. In this case, you can set the FortiMail loopback interface's IP address the same as the load balancer's IP address and thus the FortiMail unit can pick up the traffic forwarded to it from the load balancer.</p>	
allowaccess {ping http https snmp ssh telnet}	<p>Enter one or more of the following protocols to add them to the list of protocols permitted to administratively access the FortiMail unit through this network interface:</p> <ul style="list-style-type: none"> <li>ping: Allow ICMP ping responses from this network interface.</li> <li>http: Allow HTTP access to the web-based manager, webmail, and per-recipient quarantines. <b>Caution:</b> HTTP connections are <b>not</b> secure and can be intercepted by a third party. To reduce risk to the security of your FortiMail unit, enable this option only on network interfaces connected directly to your management computer.</li> <li>https: Allow secure HTTP (HTTPS) access to the web-based manager, webmail, and per-recipient quarantines.</li> <li>snmp: Allow SNMP v2 access. For more information, see <a href="#">system snmp community on page 333</a>, <a href="#">system snmp sysinfo on page 333</a>, and <a href="#">system snmp threshold on page 334</a>.</li> <li>ssh: Allow SSH access to the CLI.</li> <li>telnet: Allow Telnet access to the CLI.</li> </ul> <p>To control SMTP access, configure access control rules and session profiles. For details, see <a href="#">ms365 profile antivirus on page 158</a> and <a href="#">profile session on page 247</a>.</p> <p><b>Caution:</b> Telnet connections are <b>not</b> secure and can be intercepted by a third party. To reduce risk to the security of your FortiMail unit, enable this option only on network interfaces connected directly to your management computer.</p>	Varies by network interface.
connection {enable   disable}	<p><b>Note:</b> This command is only available when mode is set to dhcp.</p> <p>Enable for the FortiMail unit to attempt to obtain DHCP addressing information from the DHCP server.</p> <p>Disable this option if you are configuring the network interface offline, and do not want the unit to attempt to obtain addressing information at this time.</p>	disable

Variable	Description	Default
defaultgw {enable   disable}	<p><b>Note:</b> This command is only available when mode is set to dhcp.</p> <p>Enable to retrieve both the default gateway and DNS addresses from the DHCP server, replacing any manually configured values.</p>	disable
bridge-member {enable   disable}	<p><b>Note:</b> This command is only available when the FortiMail unit is operating in Transparent mode, and only for non-management ports.</p> <p>Enable to bridge the port to the management IP. See Editing network interfaces for information on bridged networks in transparent mode.</p> <p>Bridging is the default configuration for network interfaces when the FortiMail unit operates in transparent mode, and the FortiMail unit will bridge all connections occurring through it from the network to the protected email servers.</p> <p>In cases where the email servers that are protected by the FortiMail unit are located on different subnets, you must connect those email servers through separate physical ports on the FortiMail unit, and configure the network interfaces associated with those ports, assigning IP addresses and removing them from the bridge.</p>	enable
ip <ipv4mask>	<p>Enter the IP address and netmask of the network interface.</p> <p>If the FortiMail unit is in transparent mode, <b>IP/Netmask</b> may alternatively display <b>bridging</b>. This means that the network interface is acting as a Layer 2 bridge. If high availability (HA) is also enabled, <b>IP</b> and <b>Netmask</b> may alternatively display <b>bridged (isolated)</b> while the effective operating mode is <b>secondary</b> and therefore the network interface is currently disconnected from the network, or <b>bridging (waiting for recovery)</b> while the effective operating mode is <b>failed</b> and the network interface is currently disconnected from the network but a failover may soon occur, beginning connectivity.</p>	
ipv6 <ipv6mask>	<p>Enter the IPv6 address and netmask of the network interface.</p> <p>If the FortiMail unit is in transparent mode, <b>IP/Netmask</b> may alternatively display <b>bridging</b>. This means that the network interface is acting as a Layer 2 bridge. If high availability (HA) is also enabled, <b>IP</b> and <b>Netmask</b> may alternatively display <b>bridged (isolated)</b> while the effective operating mode is <b>secondary</b> and therefore the network interface is currently disconnected from the network, or <b>bridging (waiting for recovery)</b> while the effective operating mode is <b>failed</b> and the network interface is currently disconnected from the network but a failover may soon occur, beginning connectivity.</p>	
mac-addr <xx.xx.xx.xx.xx.xx>	<p>Override the factory set MAC address of this interface by specifying a new MAC address. Use the form xx:xx:xx:xx:xx:xx.</p>	Factory set
mailaccess {imap   imaps   pop3   pop3s   smtp   smtps}	<p>Allow mail access with the interface.</p>	
mode {static   dhcp}	<p>Enter the interface mode.</p> <p>If configuring for DHCP, see connection and defaultgw.</p> <p>DHCP mode applies only if the FortiMail unit is operating in gateway mode or server mode.</p>	static

Variable	Description	Default
mtu <mtu_int>	<p>Enter the maximum packet or Ethernet frame size in bytes.</p> <p>If network devices between the FortiMail unit and its traffic destinations require smaller or larger units of traffic, packets may require additional processing at each node in the network to fragment or defragment the units, resulting in reduced network performance. Adjusting the MTU to match your network can improve network performance.</p> <p>The valid range is from 576 to 1500 bytes.</p>	1500
proxy-smtp-in-mode {pass-through   drop   proxy}	<p>Enter how the proxy or built-in MTA will handle SMTP connections on each network interface that are incoming to the IP addresses of email servers belonging to a protected domain:</p> <ul style="list-style-type: none"> <li>pass-through: Permit but do not proxy or relay. Because traffic is not proxied or relayed, no policies will be applied.</li> <li>drop: Drop the connection.</li> <li>proxy: Proxy or relay the connection. Once intercepted, policies determine any further scanning or logging actions. For more information, see <a href="#">config policy delivery-control on page 168</a>, <a href="#">policy recipient on page 171</a>, and <a href="#">config policy recipient on page 118</a>.</li> </ul> <p><b>Note:</b> Depending on your network topology, you may want to verify that email is not being scanned twice. This could result if, due to mail routing, an email would travel through the FortiMail unit multiple times in order to reach its final destination, and you have entered proxy more than once for each interface and/or directionality. For an example, see the <a href="#">FortiMail Administration Guide</a>. This option is only available in transparent mode.</p>	proxy
proxy-smtp-local status {enable   disable}	<p>Enable to allow connections destined for the FortiMail unit itself.</p> <p>This option is only available in transparent mode.</p>	disable
proxy-smtp-out-mode {pass-through   drop   proxy}	<p>Enter how the proxy or built-in MTA will handle SMTP connections on each network interface that are incoming to the IP addresses of email servers belonging to a protected domain:</p> <ul style="list-style-type: none"> <li>pass-through: Permit but do not proxy or relay. Because traffic is not proxied or relayed, no policies will be applied.</li> <li>drop: Drop connections.</li> <li>proxy: Proxy or relay connections. Once intercepted, policies determine any further scanning or logging actions. For more information, see <a href="#">config policy delivery-control on page 168</a>.</li> </ul> <p><b>Note:</b> Depending on your network topology, you may want to verify that email is not being scanned twice. This could result if, due to mail routing, an email would travel through the FortiMail unit multiple times in order to reach its final destination, and you have entered proxy more than once for each interface and/or directionality. For an example, see the <a href="#">FortiMail Administration Guide</a>. This option is only available in transparent mode.</p>	pass-through
redundant-arp-ip <ip_addr>	<p>Enter the redundant interface ARP monitoring IP target.</p> <p>This option is only available when you choose the arp-link monitoring parameter. See <a href="#">redundant-link-monitor {mii-link   arp-link}</a>.</p>	

Variable	Description	Default
type {vlan   redundant}	<p>vlan: A Virtual LAN (VLAN) subinterface, also called a VLAN, is a virtual interface on a physical interface. The subinterface allows routing of VLAN tagged packets using that physical interface, but it is separate from any other traffic on the physical interface.</p> <p>Virtual LANs (VLANs) use ID tags to logically separate devices on a network into smaller broadcast domains. These smaller domains forward packets only to devices that are part of that VLAN domain. This reduces traffic and increases network security.</p> <p>One example of an application of VLANs is a company's accounting department. Accounting computers may be located at both main and branch offices. However, accounting computers need to communicate with each other frequently and require increased security. VLANs allow the accounting network traffic to be sent only to accounting computers and to connect accounting computers in different locations as if they were on the same physical subnet.</p> <p>Also configure <a href="#">redundant-link-monitor {mii-link   arp-link}</a> and <a href="#">redundant-member &lt;member_interface_str&gt;</a>.</p> <p>redundant: On the FortiMail unit, you can combine two or more physical interfaces to provide link redundancy. This feature allows you to connect to two or more switches to ensure connectivity in the event one physical interface or the equipment on that interface fails.</p> <p>In a redundant interface, traffic is only going over one interface at any time. This differs from an aggregated interface where traffic is going over all interfaces for increased bandwidth. This difference means redundant interfaces can have more robust configurations with fewer possible points of failure. This is important in a fully-meshed HA configuration.</p> <p>Also configure <a href="#">vlanid &lt;int&gt;</a>.</p>	
redundant-link-monitor {mii-link   arp-link}	<p>Configure the parameters to monitor the connections of the redundant interfaces. This option is only available when you choose the redundant interface type.</p> <p><b>mii-link:</b> Media Independent Interface is an abstract layer between the operating system and the NIC which detects whether the failover link is running.</p> <p><b>arp-link:</b> Address Resolution Protocol periodically checks whether the remote interface is reachable. Also configure <a href="#">redundant-arp-ip &lt;ip_addr&gt;</a>.</p>	mii-link
redundant-member <member_interface_str>	<p>Enter the redundant member for the failover configuration.</p> <p>This option is only available when you choose the redundant interface type.</p>	
vlanid <int>	<p>Enter the Vlan ID for logically separating devices on a network into smaller broadcast domains.</p> <p>This option is only available when you choose the vlan interface type.</p>	
webaccess	Allow web access with the interface.	
speed {auto   10full   10half   100full   100half   1000full}	<p>Enter the speed of the network interface.</p> <p><b>Note:</b> Some network interfaces may not support all speeds.</p>	auto

Variable	Description	Default
status {down   up}	Enter either up to enable the network interface to send and receive traffic, or down to disable the network interface.	up

## Related topics

[sensitive data on page 266](#)

[system admin on page 270](#)

## system link-monitor

Use this command to propagate status of a sort to other ports.

### Syntax

```
config system link-monitor
  set link-monitor-delay
  set link-monitor-interval
  set link-monitor-status {enable | disable}
end
```

Variable	Description	Default
link-monitor-delay	Enter in seconds the amount of time to delay after link state changes.	
link-monitor-interval	Enter in seconds the time the link monitor will perform an interval check.	
link-monitor-status {enable   disable}	Enable the link monitor.	8

## system mailserver

Use this command to configure the system-wide mail settings.

### Syntax

```
config system mailserver
  config mail-queue
```

```
edit {default | incoming | outgoing}
    set queue-dsn-timeout <timeout_int>
    set queue-retry <interval_int>
    set queue-timeout <timeout_int>
    set queue-warning <first-dsn_int>
end
set deadmail-expiry <time_int>
set default-auth-domain <domain_name>
set defer-delivery-starttime <time_str>
set defer-delivery-stoptime <time_str>
set delivery-esmtp {no | yes}
set delivery-failure-conditions {dns-failure | mta-failure-permanent | mta-failure-temporary |
    network-failure-connection | network-failure-other}
set delivery-failure-handling-option {normal | relay-to-host}
set delivery-failure-host <host_name>
set delivery-failure-min-age <minute_int>
set dsn-ehlo-option {host-name | domain-name | other-name} on page 323
set dsn-ehlo-other-name <name_str> on page 324
set dsn-sender-address <email_str>
set dsn-sender-displayname <name_str>
set dsn-status {enable | disable}
set imap-service {enable | disable}
set ip-pool-direction {all | exclude-internal-to-internal}
set ldap-domaincheck {enable | disable}
set ldap-domaincheck-auto-associate {enable | disable}
set ldap-domaincheck-internal-domain <domain_str>
set ldap-domaincheck-profile <profile_str>
set local-domain-name <local-domain_str>
set pop3-port <port_int>
set pop3-service {enable | disable}
set queue-dsn-timeout <timeout_int>
set queue-retry <interval_int>
set queue-timeout <timeout_int>
set queue-warning <first-dsn_int>
set relay-server-name <relay_name>
set relay-server-status {enable | disable}
set show-accept-cert-ca {enable | disable} on page 326
set smtp-auth {enable | disable}
set smtp-auth-over-tls {enable | disable}
set smtp-auth-smtps {enable | disable}
set smtp-delivery-addr-pref {ipv4-ipv6 | ipv6-ipv4 | ipv4 | ipv6}
set smtp-delivery-session-preference {domain | host}
set smtp-max-connections <connection_int>
set smtp-max-hop-count <number>
set smtp-msa {enable | disable}
set smtp-msa-port <port_int>
set smtp-mtasts-status {check-all-domain | check-external-domain | disable}
set smtp-port <port_int>
set smtp-service {enable | disable}
set smtps-port <port_int>
set smtps-tls-status {enable | disable}
set timeout-connect <seconds_int>
set timeout-greeting <seconds_int>
end
```

Variable	Description	Default
deadmail-expiry <time_int>	Enter the number of days to keep permanently undeliverable email in the dead mail folder. Dead mail has both incorrect recipient and sender email addresses, and can neither be delivered nor the sender notified. The valid range is from 1 to 365 days.	1
default-auth-domain <domain_name>	Enter the domain to use for default authentication.	
{default   incoming   outgoing}	Select the queue you want to configure.	default
defer-delivery-starttime <time_str>	Enter the time that the FortiMail unit will begin to process deferred oversized email, using the format hh:mm, where hh is the hour according to a 24-hour clock, and mm is the minutes.	00:00
defer-delivery-stoptime <time_str>	Enter the time that the FortiMail unit will stop processing deferred oversized email, using the format hh:mm, where hh is the hour according to a 24-hour clock, and mm is the minutes.	00:00
delivery-esmtp {no   yes}	Enter either: yes: Disable the FortiMail unit from delivering email using ESMTP, and use standard SMTP instead. no: Enable the FortiMail unit to deliver email using ESMTP if the SMTP server to which it is connecting supports the protocol.	no
delivery-failure-conditions {dns-failure   mta-failure-permanent   mta-failure-temporary   network-failure-connection   network-failure-other}	Specify the type of failed network connections the backup relay should take over and retry.	
delivery-failure-handling-option {normal   relay-to-host}	When email delivery fails, you can choose to use the mail queue settings to handle the temporary or permanent failures. You can also try another relay that you know might work. <ul style="list-style-type: none"> <li><code>normal</code>: Enter this option if you want to queue the email and use the mail queue settings.</li> <li><code>relay-to-host</code>: Enter another relay (backup relay) that you want to use for failed deliveries.</li> </ul>	normal
delivery-failure-host <host_name>	Enter a host to relay email when access to original mail host fails.	
delivery-failure-min-age <minute_int>	Enter the time in minutes the undelivered email should wait in the normal queue before trying the backup relay.	30
dsn-ehlo-option {host-name   domain-name   other-name}	Specify the DSN EHLO/HELO argument to use: <ul style="list-style-type: none"> <li><code>host-name</code>: use the host name of the FortiMail unit.</li> <li><code>domain-name</code>: use the local domain name of the FortiMail unit.</li> <li><code>other-name</code>: use the customized name. Then use the below command to specify the name.</li> </ul>	host-name

Variable	Description	Default
dsn-ehlo-other-name <name_str>	If you specify to use other-name in the above command, use this command to enter the customized name.	
dsn-sender-address <email_str>	Enter the sender email address in delivery status notification (DSN) email messages sent by the FortiMail unit to notify email users of delivery failure.  If this string is empty, the FortiMail unit sends DSN from the default sender email address of "postmaster@example.com", where "example.com" is the domain name of the FortiMail unit.	
dsn-sender-displayname <name_str>	Enter the display name of the sender email address for DSN. If this string is empty, the FortiMail unit uses the display name "postmaster".	
dsn-status {enable   disable}	Enable to allow DSN email generation.	disable
imap-service {enable   disable}	Enable to allow IMAP service.	enable
ip-pool-direction {all   exclude-internal-to-internal}	By default, IP pools in IP policies and domain settings will be applied to all email directions, including internal to internal, internal to external, external to internal, and external to external.  To exempt IP pool usage for internal-to-internal email, select <code>exclude-internal-to-internal</code> .  <b>Note:</b> IP pools in access delivery rules are still applied to internal-to-internal email.	
ldap-domaincheck {enable   disable}	Enable to verify the existence of domains that have not been configured as protected domains. Also configure <code>ldap-domaincheck-profile</code> <profile_str> and <code>ldap-domaincheck-auto-associate</code> {enable   disable}.  To verify the existence of unknown domains, the FortiMail unit queries an LDAP server for a user object that contains the email address. If the user object exists, the verification is successful, the action varies by configuration of <code>ldap-domaincheck-auto-associate</code> {enable   disable}.	disable
ldap-domaincheck-auto-associate {enable   disable}	If <code>ldap-domaincheck</code> is enable, select whether to enable or disable automatic creation of domain associations.  enable: The FortiMail unit automatically adds the unknown domain as a domain associated of the protected domain selected in <code>ldap-domaincheck-internal-domain</code> <domain_str>.  disable: If the DNS lookup of the unknown domain name is successful, the FortiMail unit routes the email to the IP address resolved for the domain name during the DNS lookup. Because the domain is not formally defined as a protected domain, the email is considered to be outgoing, and outgoing recipient-based policies are used to scan the email. For more information, see <a href="#">policy recipient on page 171</a> .	disable

Variable	Description	Default
ldap-domaincheck-internal-domain <domain_str>	If <code>ldap-domaincheck</code> is enable, and <code>ldap-domaincheck-auto-associate</code> is enable, enter name of the protected domain with which successfully verified domains will become associated.	
ldap-domaincheck-profile <profile_str>	If <code>ldap-domaincheck</code> is enable, enter the name of the LDAP profile to use when verifying unknown domains.	
local-domain-name <local-domain_str>	Enter the name of the domain to which the FortiMail unit belongs, such as <code>example.com</code> . This option applies only if the FortiMail unit is operating in server mode.	
pop3-port <port_int>	Enter the port number on which the FortiMail unit's POP3 server will listen for POP3 connections. The default port number is 110. This option applies only if the FortiMail unit is operating in server mode.	110
pop3-service {enable   disable}	Enable to allow POP3 service.	enable
queue-dsn-timeout <timeout_int>	Enter the maximum number of days a delivery status notification (DSN) message can remain in the mail queues. If the maximum time is set to zero (0) days, the FortiMail unit attempts to deliver the DSN only once. After the maximum time has been reached, the DSN email is moved to the dead mail folder. The valid range is from zero to ten days.	5
queue-retry <interval_int>	Enter the number of minutes between delivery retries for email messages in the deferred and spam mail queues. The valid range is from 10 to 120 minutes.	27
queue-timeout <timeout_int>	Enter the maximum number of hours that deferred email messages can remain in the deferred or spam mail queue, during which the FortiMail unit periodically retries to send the message. After the maximum time has been reached, the FortiMail unit will send a final delivery status notification (DSN) email message to notify the sender that the email message was undeliverable. The valid range is from 1 to 240 hours.	120
queue-warning <first-dsn_int>	Enter the number of hours after an initial failure to deliver an email message before the FortiMail unit sends the first delivery status notification (DSN) email message to notify the sender that the email message has been deferred. After sending this initial DSN, the FortiMail unit will continue to retry sending the email until reaching the limit configured in <code>timeout</code> . The valid range is from 1 to 24 hours.	4
relay-server-name <relay_name>	Specify the relay server to deliver outgoing email.	
relay-server-status {enable   disable}	If enabled, the relay server will be used to deliver outgoing email. If disabled, the FortiMail built-in MTA will be used.	disable

Variable	Description	Default
show-accept-cert-ca {enable   disable}	Enable to show acceptable client certificate ca.	enable
smtp-auth {enable   disable}	Enable to accept the AUTH command to authenticate email users for connections using SMTP.	enable
smtp-auth-over-tls {enable   disable}	Enable to accept the AUTH command to authenticate email users for connections using SMTP over TLS.	enable
smtp-auth-smtps {enable   disable}	Enable to accept the AUTH command to authenticate email users for connections using SMTPS (SMTP with SSL).	enable
smtp-delivery-addr-pref {ipv4-ipv6   ipv6-ipv4   ipv4   ipv6}	<p>When FortiMail delivers email to a host name, it does DNS AAAA and A record lookup.</p> <p>Use this command to specify the IPv4/IPv6 delivery preferences:</p> <ul style="list-style-type: none"> <li>• <code>ipv4-ipv6</code>: Try to deliver to the IPv4 address first. If the IPv4 address is not accessible, try the IPv6 address. Because most MTAs support IPv4, this is the default setting.</li> <li>• <code>ipv6-ipv4</code>: Try IPv6 first, then IPv4. However, if the AAAA record does not exist, the extra AAAA DNS lookup for IPv6 addresses will potentially cause email delivery delay.</li> <li>• <code>ipv4</code>: Try IPv4 only. This setting is not recommended.</li> <li>• <code>ipv6</code>: Try IPv6 only. This setting is not recommended.</li> </ul>	ipv4-ipv6
smtp-delivery-session-preference {domain   host}	<p>Google business email service does not accept multiple destination domains per SMTP transaction, resulting in repeated delivery attempts and delayed email. To work around this Google limitation, this command is added in 5.4.6 and 6.0.1 releases.</p> <p>Before 5.4.6 and 6.0. releases, the default setting is host. Multiple recipient domains that resolve to the same MTA are sent to the server in the same session.</p> <p>After 5.4.6 and 6.0.1 release, the default setting is changed to domain. Multiple recipient domains that resolve to the same MTA are sent to the server in separate sessions.</p>	domain
smtp-max-connections <connection_int>	Enter the maximum number of concurrent SMTP connections that FortiMail can accept from the SMTP clients.	Platform dependent
smtp-max-hop-count <number>	Enter the maximum number of hops that FortiMail can accept from the SMTP connections. Valid range is 1 to 200.	30
smtp-msa {enable   disable}	<p>Enable to allow your email clients to use SMTP for message submission on a separate TCP port number from deliveries or mail relay by MTAs.</p> <p>For details on message submission by email clients as distinct from SMTP used by MTAs, see <a href="#">RFC 2476</a>.</p>	disable
smtp-msa-port <port_int>	Enter the TCP port number on which the FortiMail unit listens for email clients to submit email for delivery.	587

Variable	Description	Default
smtp-mtasts-status {check-all-domain   check-external-domain   disable}	<p>Enable MTA Strict Transport Security (MTA-STS) domain checking:</p> <ul style="list-style-type: none"> <li>• <code>check-all-domain</code>: FortiMail checks recipient domain MTA-STS records (including TLS version, format, and MTA-STS policy) for outgoing email to both internal and external domains.</li> <li>• <code>check-external-domain</code>: FortiMail MTA-STS checking only when delivering outgoing emails to external domains.</li> <li>• <code>disable</code>: Disable MTA-STS domain checking.</li> </ul>	disable
smtp-port <port_int>	Enter the port number on which the FortiMail unit's SMTP server will listen for SMTP connections.	25
smtp-service {enable   disable}	Enable to allow SMTP service.	disable
smtps-port <port_int>	Enter the port number on which the FortiMail unit's built-in MTA listens for secure SMTP connections.	465
smtps-tls-status {enable   disable}	<p>Enable to allow SSL- and TLS-secured connections from SMTP clients that request SSL/TLS.</p> <p>When disabled, SMTP connections with the FortiMail unit's built-in MTA must occur as clear text, unencrypted.</p>	disable
timeout-connect <seconds_int>	<p>Enter the maximum amount of time to wait, after the FortiMail unit initiates it, for the receiving SMTP server to establish the network connection.</p> <p>The valid range is 10 to 120.</p> <p><b>Note:</b> This timeout applies to all SMTP connections, regardless of whether it is the first connection to that SMTP server or not.</p>	30
timeout-greeting <seconds_int>	<p>Enter the maximum amount of time to wait for an SMTP server to send SMTP reply code 220 to the FortiMail unit.</p> <p>The valid range is 10 to 360.</p> <p><b>Note:</b> RFC 2821 recommends a timeout value of 5 minutes (300 seconds). For performance reasons, you may prefer to have a smaller timeout value, which reduces the amount of time spent waiting for sluggish SMTP servers. However, if this causes your FortiMail unit to be unable to successfully initiate an SMTP session with some SMTP servers, consider increasing the timeout.</p>	30

## Related topics

[system route on page 329](#)

# system password-policy

Use this command to configure password policy for administrators, FortiMail Webmail users, and IBE encrypted email users.

## Syntax

```
config system password-policy
  set status {enable | disable}
  set apply-to {admin-user | ibe-user | local-mail-user}
  set minimum-length <minimum_int>
  set must-contain {upper-case-letter | lower-case-letter | number | non-alphanumeric}
  set allow-admin-empty-password {enable | disable}
end
```

Variable	Description	Default
status {enable   disable}	Select to enable the password policy.	
apply-to {admin-user   ibe-user   local-mail-user}	Select where to apply the password policy: <ul style="list-style-type: none"> <li>admin-user: Apply to administrator passwords. If any password does not conform to the policy, require that administrator to change the password at the next login.</li> <li>local-mail-user: Apply to FortiMail webmail users' passwords. If any password does not conform to the policy, require that user to change the password at the next login.</li> <li>ibe-user: Apply to the passwords of the users who access the FortiMail unit to view IBE encrypted email. If any password does not conform to the policy, require that user to change the password at the next login.</li> </ul>	
minimum-length <minimum_int>	Set the minimum acceptable length for passwords.	8
must-contain {upper-case-letter   lower-case-letter   number   non-alphanumeric}	Select any of the following special character types to require in a password. Each selected type must occur at least once in the password. <p>upper-case-letter — A, B, C, ... Z</p> <p>lower-case-letter — a, b, c, ... z</p> <p>number — 0, 1, 2, 3, 4, 5, 6, 7, 8, 9</p> <p>non-alphanumeric — punctuation marks, @, #, ... %</p>	
allow-admin-empty-password {enable   disable}	Enable to allow the admin password to be empty.	disable

## Related topics

[system link-monitor on page 321](#)

## system port-forwarding

FortiMail port forwarding allows remote computers, for example, computers on the Internet, to connect to a specific computer or service within a private local area network (LAN). Port Forwarding is useful when FortiMail is deployed as a gateway and you want external users to access an internal server via FortiMail.

For example, FortiMail port1 is connected to the Internet and its IP address 192.168.37.4, port 7000, is mapped to 10.10.10.42, port 8000, on a private network. Attempts to communicate with 192.168.37.4, port 7000, from the Internet are translated and sent to 10.10.10.42, port 8000, by the FortiMail unit. The computers on the Internet are unaware of this translation and see a single computer at 192.168.37.4, port 7000, rather than the 10.10.10.42 network behind the FortiMail unit.

Before you do the mapping, make sure both ports are open.

## Syntax

```
config system port-forwarding
  edit <route_int>
    set destination <destination_ipv4mask>
    set gateway <gateway_ipv4>
  end
```

Variable	Description	Default
<number>	Enter the index number of the entry.	
dst-host <calss_ip>	Enter the IP address of the host where the packets will be forwarded.	0.0.0.0
dst-port <port_number>	Enter the port number of the destination host.	0
host <class_ip>	Enter the IP address of the FortiMail interface where the packets are received.	0.0.0.0
port <port_number>	Enter the port number on the FortiMail interface where the packets are received.	0
protocol {tcp   udp   both}	Specify the protocol of the traffic.	tcp

## system route

Use this command to configure static routes.

## Syntax

```
config system route
```

```

edit <route_int>
  set destination <destination_ipv4mask>
  set gateway <gateway_ipv4>
  set interface <interface_name>
end

```

Variable	Description	Default
<route_int>	Enter the index number of the route in the routing table.	
destination <destination_ ipv4mask>	Enter the destination IP address and netmask of traffic that will be subject to this route, separated with a space. To indicate all traffic regardless of IP address and netmask, enter 0.0.0.0 0.0.0.0.	0.0.0.0 0.0.0.0
gateway <gateway_ ipv4>	Enter the IP address of the gateway router.	0.0.0.0
interface <interface_ name>	Enter the interface name that you want to add the static route to.	

## Related topics

[system link-monitor on page 321](#)

## system saml

Use this command to enable and configure SAML SSO.

## Syntax

```

config system saml
  set status {enable | disable}
  set idp-metadata-url <url>
end

```

Variable	Description	Default
status {enable   disable}	Enable or disable the feature.	disable
idp-metadata-url <url>	Specify the URL to retrieve the IDP metadata.	

# system scheduled-backup

Use this command to configure system backup.

## Syntax

```
config system scheduled-backup
  set destination...
end
```

Variable	Description	Default
destination...	Configure the destination server and schedule.	

# system security crypto

Use this command to modify protocol specific crypto configuration.

## Syntax

```
config system security crypto
  edit http
    set custom-ciphers <ciphers> on page 331
    set dh-params {1024 | 2048 | 3072 | 4096} on page 332
    set ssl-versions {tls1_0 | tls1_1 | tls1_2 | tls1_3} on page 332
    set status {enable | disable} on page 332
    set strong-crypto {enable | disable} on page 332
  edit mail
    set custom-ciphers <ciphers> on page 331
    set dh-params {1024 | 2048 | 3072 | 4096} on page 332
    set ssl-versions {tls1_0 | tls1_1 | tls1_2 | tls1_3} on page 332
    set status {enable | disable} on page 332
    set strong-crypto {enable | disable} on page 332
end
```

Variable	Description	Default
custom-ciphers <ciphers>	<p>Add ciphers by typing +cipher_names separated by spaces, such as +RC4-SHA +CAMELLIA256-SHA. Delete ciphers by typing -cipher_names separated by spaces, such as -RC4-SHA -CAMELLIA256-SHA.</p> <p>Type ? to see all the supported regular and strong ciphers. The available ciphers for addition are listed under <i>Available ciphers</i>; the <i>Selected ciphers</i> list the ones that have already been added. You can remove ciphers from the <i>Selected ciphers</i> list.</p>	

Variable	Description	Default
dh-params {1024   2048   3072   4096}	Enter the minimum size in bits of the Diffie-Hellman prime.	1024
ssl-versions {tls1_0   tls1_1   tls1_2   tls1_ 3}	Enter the SSL protocol version enabled.	tls1_1, tls1_2, tls1_3
status {enable   disable}	Enable the protocol specific crypto.	disable
strong- crypto {enable   disable}	Use strong ciphers and digests.	enable

## system security authserver

Use this command to modify the tracking functions used to prevent password guessing attempts. The sender IP addresses in the exempt list will bypass the security checking.

### Syntax

```
config system security authserver
  config exempt-list
    edit auth_exempt_id
      set sender-ip-mask
    end
  set access-group {cli mail web} on page 332
  set block-period <minutes> on page 332
  set status (disable | enable | monitor-only)
end
```

Variable	Description	Default
auth_exempt_id	Enter the ID for the list.	
sender-ip-mask	Enter the sender's IP address.	
access-group {cli mail web}	Enter the groups of access tracked by authserver.	cli mail web
block-period <minutes>	Enter the block period in minutes.	10
status (disable   enable   monitor-only)	Enable or disable this list.	enable

# system snmp community

Use this command to configure simple network management protocol (SNMP) v1/2 settings.

These commands apply only if the SNMP agent is enabled. For details, see [status {enable | disable}](#).

## Syntax

```
config system snmp community
  edit <index_int>
    config host
      edit <index_int>
        set ip <address_ipv4>
        set name <name_str>
        set queryportv1 <port_int>
        set queryportv2c <port_int>
        set queryv1-status {enable | disable}
        set queryv2c-status {enable | disable}
        set status {enable | disable}
        set trapevent {cpu | deferred-queue | ha | ip-change | logdisk | maildisk | mem | raid |
          remote-storage | spam | system | virus}
        set trapportv1_local <port_int>
        set trapportv1_remote <port_int>
        set trapportv2c_local <port_int>
        set trapportv2c_remote <port_int>
        set trapv1_status {enable | disable}
        set trapv2c_status {enable | disable}
      end
    end
  end
```

## Related topics

[system snmp sysinfo on page 333](#)

[system snmp threshold on page 334](#)

# system snmp sysinfo

Use this command to enable or disable the SNMP agent on the FortiMail unit, and to configure the location, description, engine ID, and contact information.

## Syntax

```
config system snmp sysinfo
  set contact <contact_str>
```

```

set description <description_str>
set port-https <port_int>
set location <location_str>
set status {enable | disable}
end

```

Variable	Description	Default
contact <contact_str>	Enter the contact information for the administrator of this FortiMail unit, such as 'admin@example.com'.	
description <description_str>	Enter a description for the FortiMail unit that will uniquely identify it to the SNMP monitor, such as 'FortiMail-400 Rack 1'.	
engine-id <id_str>	Enter the SNMP engine ID on the FortiMail unit.	
location <location_str>	Enter the location of this FortiMail unit, such as 'NOC_Floor2'.	
status {enable   disable}	Enable to activate the SNMP agent.	enable

## Related topics

[system snmp community on page 333](#)

[system snmp threshold on page 334](#)

## system snmp threshold

Use this command to configure the event types that trigger an SNMP trap.

## Syntax

```

config system snmp threshold
set {cpu | deferred-queue | logdisk | maildisk | mem | spam | virus} <trigger_int> <threshold_int> <sample_period_int> <sample_frequency_int>
end

```

Variable	Description	Default
{cpu   deferred-queue   logdisk   maildisk   mem   spam   virus} <trigger_int> <threshold_int> <sample_period_int> <sample_frequency_int>	Specify the trap event, such as cpu or spam, then specify the following threshold values:  trigger_int: You can enter either the percent of the resource in use or the number of times the trigger level must be reached before it is triggered. For example, using the default value, if the mailbox disk is 90% or more full, it will trigger.	cpu: 80 3 600 30  mem: 80 3 600 30

Variable	Description	Default
	threshold_int: Sets the number of triggers that will result in an SNMP trap. For example, if the CPU level exceeds the set trigger percentage once before returning to a lower level, and the threshold is set to more than one an SNMP trap will not be generated until that minimum number of triggers occurs during the sample period.	logdisk: 90 17200 3600
	sample_period_int: Sets the time period in seconds during which the FortiMail unit SNMP agent counts the number of triggers that occurred. This value should not be less than the Sample Frequency value.	maildisk: 90 17200 3600
	sample_frequency_int: Sets the interval in seconds between measurements of the trap condition. You will not receive traps faster than this rate, depending on the selected sample period. This value should be less than the Sample Period value.	virus: 10 600  spam: 60 600

## Related topics

[system snmp community on page 333](#)

[system snmp sysinfo on page 333](#)

## system snmp user

Use this command to configure SNMP v3 user settings.

SNMP v3 adds more security by using authentication and privacy encryption. You can specify an SNMP v3 user on FortiMail so that SNMP managers can connect to the FortiMail unit to view system information and receive SNMP traps.

## Syntax

```
config system snmp user
  edit <user_name>
    set query-status {enable | disable}
    set query-port <port_number>
    set security-level {authnopriv | authpriv | noauthnopriv}
    set auth-proto {sha1 | md5}
    set aut-pwd <password>
    set status {enable | disable}
    set trap-status {enable | disable}
    set trapevent {cpu | deferred-queue | ha | ip-change | logdisk | mem | raid | remote-
      storage | spam | system | virus}
    set trappport-local <port_number>
    set trappport-remote <port_number>
  config host
```

```

edit <host_no>
    set ip <class_ip>
end
end

```

Variable	Description	Default
<user_name>	Enter a name to identify the SNMP user on FortiMail.	
query-status {enable   disable}	Enable to allow SNMP v3 query from the SNMP managers. Also configure the query port as described below.	disable
query-port <port_number>	Specify the port number used to listen to queries from the SNMP manager.	161
security-level {authnopriv   authpriv   noauthnopriv}	Choose one of the three security levels for the communication between FortiMail and the SNMP manager. <ul style="list-style-type: none"> <li>noauthnotpriv (no authentication, no privacy): This option is similar to SNMP v1 and v2.</li> <li>authnopriv (authentication, no privacy): This option enables authentication only. The SNMP manager needs to supply a password that matches the password you specify on FortiMail. You must also specify the authentication protocol (either SHA1 or MD5).</li> <li>authpriv (authentication, privacy): This option enables both authentication and encryption. You must specify the protocols and passwords. Both the protocols and passwords on the SNMP manager and FortiMail must match.</li> </ul>	
auth-proto {sha1   md5}	Specify the authentication protocol if you choose authentication for the security level. Otherwise, this option is not displayed.	
aut-pwd <password>	Specify the authentication password if you choose authentication for the security level. Otherwise, this option is not displayed.	
status {enable   disable}	Enable or disable the SNMP v3 user on FortiMail.	disable
trap-status {enable   disable}	Enable to activate traps on FortiMail.	disable
trapevent {cpu   deferred-queue   ha   ip-change   logdisk   mem   raid   remote-storage   spam   system   virus}	Enter one or more of the following events that will generate a trap when the event occurs or when its threshold is reached: <ul style="list-style-type: none"> <li>cpu: CPU usage threshold</li> <li>deferred-queue: Deferred queue threshold</li> <li>ha: High availability (HA) event</li> <li>ip-change: Interface IP address change</li> <li>logdisk: Log disk space low threshold</li> <li>maildisk: Mail disk space low threshold</li> <li>mem: Memory low threshold</li> <li>raid: RAID event</li> <li>remote-storage: NAS storage related events</li> <li>spam: Spam threshold</li> <li>system: System events, such as a change in the state of hardware, power failure and so on.</li> <li>virus: Virus threshold</li> </ul>	cpu deferred-queue ha logdisk maildisk mem raid remote-storage system

Variable	Description	Default
	<p><b>Note:</b> Since FortiMail checks its status in a scheduled interval, not all the events will trigger traps. For example, FortiMail checks its hardware status every 60 seconds. This means that if the power is off for a few seconds but is back on before the next status check, no system event trap will be sent.</p> <p>To set SNMP trap thresholds for the event types that use them, see <a href="#">system snmp threshold on page 334</a>.</p> <p>Events apply only when traps are enabled in .</p>	
trapport-local <port_number>	Enter the local port number for sending traps.	162
trapport-remote <port_number>	Enter the remote port number that listens to SNMP traps on the SNMP manager.	162
<host_no>	Enter an index number for the SNMP manager.	
ip <class_ip>	Enter the IP address of the SNMP manager.	

## Related topics

[system snmp community on page 333](#)

[system snmp sysinfo on page 333](#)

## system time manual

Use this command to manually configure the system time of the FortiMail unit.

Accurate system time is required by many features of the FortiMail unit, including but not limited to log messages and SSL-secured connections.

This command applies only if NTP is disabled. Alternatively, you can configure the FortiMail unit to synchronize its system time with an NTP server. For details, see [system time ntp on page 338](#).

## Syntax

```
config system time manual
  set daylight-saving-time {disable | enable}
  set zone <zone_int>
end
```

Variable	Description	Default
daylight-saving-time {disable   enable}	Enable to automatically adjust the system time for daylight savings time (DST).	enable
zone <zone_int>	Enter the number that indicates the time zone in which the FortiMail unit is located.	12

## Related topics

[system time ntp on page 338](#)

## system time ntp

Use this command to configure the FortiMail unit to synchronize its system time with a network time protocol (NTP) server.

Accurate system time is required by many features of the FortiMail unit, including but not limited to log messages and SSL-secured connections.

Alternatively, you can manually configure the system time of the FortiMail unit. For details, see [system time manual on page 337](#).

## Syntax

```
config system time ntp
  set ntpserver {<address_ipv4> | <fqdn_str>}
  set ntpsync {enable | disable}
  set syncinterval <interval_int>
end
```

Variable	Description	Default
ntpserver {<address_ipv4>   <fqdn_str>}	Enter either the IP address or fully qualified domain name (FQDN) of an NTP server. You can add a maximum of 10 NTP servers. The FortiMail unit uses the first NTP server based on the selection mechanism of the NTP protocol. To locate a public NTP server, visit <a href="http://www.ntp.org/">http://www.ntp.org/</a> .	pool.ntp.org
ntpsync {enable   disable}	Enable to synchronize the FortiMail unit with an NTP server, instead of manually configuring the system time.	enable
syncinterval <interval_int>	Enter the interval in minutes between synchronizations of the system time with the NTP server. The valid range is from 1 to 1440 minutes.	60

## Related topics

[system time manual on page 337](#)

## system wccp settings

FortiMail and FortiGate support Web Cache Communication Protocol (WCCP) to redirect SMTP traffic from FortiGate to FortiMail. If the FortiGate unit is configured to redirect SMTP traffic to FortiMail for antispam scanning (for details, see the FortiGate documentation), on the FortiMail side, you must do corresponding configurations to accept the SMTP traffic from FortiGate.

## Syntax

```
config system wccp settings
  set authentication
  set id
  set local-ip
  set password
  set remote-ip
  set status
end
```

Variable	Description	Default
authentication	Enable or disable authentication.	
id	Enter the ID of the tunnel.	
local-ip	Enter the ip address of the local interface.	
password	Enter the authentication password.	
remote-ip	Enter the ip address of the remote server.	
status	Enable or disable WCCP mode.	
file_name <file_str>	Enter the name of the language resource file, such as 'custom_french1'.	

## system web-service

Use this command to configure the rate limit for REST APIs, including the maximum concurrent REST API requests (overall and for individual IP addresses), and how fast the system should perform, in terms of how many requests and responses are processed per second. It also configures connections for FortiMail webmail and per-user quarantines.



Valid value ranges for certain commands vary by FortiMail model.

## Syntax

```
config system web-service
  config exempt-list
    edit <list_index>
      set<client_ipv4mask>
      next
    end
  set https-redirect-status {enable | disable}
  set https-redirect-host <fortimail_fqdn>
  set max-active-session-admin <limit_int>
  set max-active-session-restful <limit_int>
  set max-concurrent-request-admin <limit_int>
  set max-concurrent-request-all <limit_int>
  set max-concurrent-request-ms365 <limit_int>
  set max-concurrent-request-per-ip <limit_int>
  set max-concurrent-request-restful <limit_int>
  set max-concurrent-request-webmail <limit_int>
  set max-request-rate-admin <limit_int>
  set max-request-rate-ms365 <limit_int>
  set max-request-rate-restful <limit_int>
  set max-request-rate-webmail <limit_int>
  set rest-api-status {enable | disable}
end
```

Variable	Description	Default
<list_index>	Configure exempt lists of IP addresses that you want to exempt from rate limits.	
<client_ipv4mask>	Enter an IP address and netmask that you want to exempt from rate limits.	
https-redirect-status {enable   disable}	<p>Enable to redirect insecure HTTP requests to secure access using HTTPS.</p> <p>This setting affects all FortiMail URLs: REST APIs, administrator GUI, FortiMail webmail, and per-user quarantines.</p> <p><b>Note:</b> For this setting to take effect, you must also enable both HTTP and HTTPS access protocols on the network interface(s) that receive these connections. FortiMail cannot redirect HTTP if it is not listening for it.</p>	enable
https-redirect-host <fortimail_fqdn>	Enter the fully qualified domain name (FQDN) to use in HTTPS redirects.	
max-active-session-admin <limit_int>	Enter the maximum number of active administrator sessions.	200

Variable	Description	Default
max-active-session-restful <limit_int>	Enter the maximum number of active RESTful sessions.	10
max-concurrent-request-admin <limit_int>	Enter the maximum number of concurrent admin portal requests.	50
max-concurrent-request-all <limit_int>	Enter the maximum number of concurrent HTTP requests from all clients.	0
max-concurrent-request-ms365 <limit_int>	Enter the maximum number of concurrent Microsoft Office 365 requests permitted.	100
max-concurrent-request-per-ip <limit_int>	Enter the maximum number of concurrent HTTP requests for a single IP address.	0
max-concurrent-request-restful <limit_int>	Enter the maximum number of concurrent RESTful requests.	20
max-concurrent-request-webmail <limit_int>	Enter the maximum number of concurrent webmail portal requests. The valid ranges and default settings vary depending on the platforms. For details, see <a href="#">FortiMail Maximum Values</a> .	
max-request-rate-admin <limit_int>	Enter the maximum request rate (per second) for administrators.	0
max-request-rate-ms365 <limit_int>	Enter the maximum request rate (per second) for Microsoft Office 365.	100
max-request-rate-restful <limit_int>	Enter the maximum request rate (per second) for the REST API.	50
max-request-rate-webmail <limit_int>	Enter the maximum request rate (per second) for webmail.	0
rest-api-status {enable   disable}	Enable or disable REST API access.	disable

## Related topics

[system interface on page 316](#)

## system webfilter local-category

Use this command to view custom FortiGuard URL local filter categories for URL override rating profiles.

Use the get sub-command to list the entries' group and id, which are otherwise only configurable within the GUI.

## Syntax

```
config system webfilter local-category
  edit <name>
    set description <description>
  next
end
```

Variable	Description	Default
description <description>	Optional description of the local category.	

## system webfilter local-rating

Use these commands to configure URL rating patterns (as either wildcard or regular expressions) and override to defined URL categories. URL override rating lists can be used as web filter categories.

## Syntax

```
config system webfilter local-rating
  edit <id>
    set category <datasource>
    set description <description>
    set pattern-type {wildcard | regex}
    set status {enable | disable}
    set url-pattern <string>
  next
end
```

Variable	Description	Default
category <datasource>	Enter a predefined category that the local rating overrides to. Enter <code>set category ?</code> to view the list of categories available.	local
description <description>	Optional description of the local rating.	
pattern-type {wildcard   regex}	Set the URL pattern type to either wildcard or regular expression.	wildcard
status {enable   disable}	Enable or disable the local rating.	enable
url-pattern <string>	Enter the URL pattern, as either wildcard or regular expression.	

## system webmail-language

Use this command to create or rename a webmail language.

When you create a webmail language, it is initialized using by copying the English language file. For example, the location in webmail whose resource ID is `mail_box` contains the value `Mail Box`. To finish creation of your webmail language, you must replace the English values with your translation or customized term by either:

- editing the resource values for each resource ID in the web-based manager
- downloading, editing, then uploading the language resource file

For information on how to edit a webmail language, see the [FortiMail Administration Guide](#).

## Syntax

```
config system webmail-language
  edit en_name <language-name-en_str>
    set name <language-name_str>
  end
```

Variable	Description	Default
en_name <language-name-en_str>	Enter the name of the language in English, such as 'French'. Available languages vary by whether or not you have installed additional language resource files.	
name <language-name_str>	Enter the name of the language, such as 'Français'.	
file_name <file_str>	Enter the name of the language resource file, such as 'custom_french1'.	

## Related topics

[config user mail on page 123](#)

## user alias

Use this command to configure email address aliases.

Aliases are sometimes also called distribution lists, and may translate one email address to the email addresses of several recipients, also called members, or may be simply a literal alias — that is, an alternative email address that resolves to the real email address of a single email user.

For example, `groupa@example.com` might be an alias that the FortiMail unit will expand to `user1@example.com` and `user2@example.com`, having the effect of distributing an email message to all email addresses that are members of that alias, while `john.smith@example.com` might be an alias that the FortiMail unit translates to `j.smith@example.com`. In both cases, the FortiMail unit converts the alias in the recipient fields of incoming email messages into the member email addresses of the alias, each of which are the email address of an email user that is locally deliverable on the SMTP server or FortiMail unit.

Resolving aliases to real email addresses enables the FortiMail unit to send a single spam report and maintain a single quarantine mailbox at each user's primary email account, rather than sending separate spam reports and maintaining separate quarantine mailboxes for each alias email address. For FortiMail units operating in server mode, this means that users need only log in to their primary account in order to manage their spam quarantine, rather than logging in to each alias account individually.

Alternatively, you can configure an LDAP profile in which the alias query is enabled. For details, see [profile ldap on page 226](#).

## Syntax

```
config user alias
  edit name <email-alias_str>
    set member <recipient_str>
  end
```

Variable	Description	Default
name <email-alias_str>	Enter the email address that is the alias, such as <code>alias1@example.com</code> .	
member <recipient_str>	Enter a recipient email addresses to which the alias will translate or expand. The email addresses may be members of either mail domains that are protected by the FortiMail unit, members of mail domains that are unprotected, or a mixture of the two. Separate each email address with a comma, and enclose the list in single quotes ( ' ).	

## Related topics

[user map on page 344](#)

[user pki on page 347](#)

## user map

Use this command to configure email address mappings.

Address mappings are bidirectional, one-to-one or many-to-many mappings. They can be useful when:

- you want to hide a protected domain's true email addresses from recipients
- a mail domain's domain name is not globally DNS-resolvable, and you want to replace the domain name with one that is
- you want to rewrite email addresses

Like aliases, address mappings translate email addresses. They do not translate many email addresses into a single email address.

Mappings cannot translate one email address into many.

Mappings cannot translate an email address into one that belongs to an unprotected domain (this restriction applies to locally defined address mappings only. This is not enforced for mappings defined on an LDAP server).

Mappings are applied bidirectionally, when an email is outgoing as well as when it is incoming to the protected domain.

Mappings may affect both sender and recipient email addresses, and may affect those email addresses in both the message envelope and the message header, depending on the match condition.

The following table illustrates the sequence in which parts of each email are compared with address mappings for a match, and which locations' email addresses are translated if a match is found.



Both RCPT TO: and MAIL FROM: email addresses are always evaluated for a match with an address mapping. If both RCPT TO: and MAIL FROM: contain email addresses that match the mapping, both mapping translations will be performed.

### Match evaluation and rewrite behavior for email address mappings:

Order of evaluation	Match condition	If yes...	Rewrite to...
1	Does RCPT TO: match an <b>external</b> email address?	Replace RCPT TO:.	Internal email address
2	Does MAIL FROM: match an <b>internal</b> email address?	For each of the following, if it matches an internal email address, replace it: MAIL FROM: RCPT TO: From: To: Return-Path: Cc: Reply-To: Return-Receipt-To: Resent-From: Resent-Sender: Delivery-Receipt-To: Disposition-Notification-To:	External email address

For example, you could create an address mapping between the internal email address user1@marketing.example.net and the external email address sales@example.com. The following effects would be observable on the simplest case of an outgoing email and an incoming reply:

For email from user1@marketing.example.net to others: user1@marketing.example.net in both the message envelope (MAIL FROM:) and many message headers (From:, etc.) would then be replaced with sales@example.com. Recipients would only be aware of the email address sales@example.com.

For email to sales@example.com from others: The recipient address in the message envelope (RCPT TO:), but **not** the message header (To:), would be replaced with user1@marketing.example.net. user1@marketing.example.net would be aware that the sender had originally sent the email to the mapped address, sales@example.com.

Alternatively, you can configure an LDAP profile to query for email address mappings. For details, see [profile ldap on page 226](#).

## Syntax

```
config user map
  edit encryption-profile <profile_str>
    set external-name <pattern_str>
end
```

Variable	Description	Default
internal-name <pattern_str>	<p>Enter either an email address, such as user1@example.com, or an email address pattern, such as *@example.com, that exists in a protected domain.</p> <p>This email address will be rewritten into <code>external-name &lt;pattern_str&gt;</code> according to the match conditions and effects described in <a href="#">Match evaluation and rewrite behavior for email address mappings: on page 345</a>.</p> <p><b>Note:</b> If you enter a pattern with a wild card (* or ?):</p> <p>You must enter a pattern using the same wild card in <code>external-name &lt;pattern_str&gt;</code>. The wild card indicates that the mapping could match many email addresses, but also indicates, during the rewrite, which substring of the original email address will be substituted into the position of the wild card in the external address. If there is no wild card in the other half of the mapping, or the wild card is not the same (that is, * mapped to ? or vice versa), this substitution will fail.</p> <p><code>external-name &lt;pattern_str&gt;</code> must not be within the same protected domain. This could cause situations where an email address is rewritten twice, by matching both the sender and recipient rewrite conditions, and the result is therefore the same as the original email address and possibly not deliverable.</p>	
external-name <pattern_str>	<p>Enter either an email address, such as user2@example.com, or an email address pattern, such as *@example.net, that exists in a protected domain.</p> <p>This email address will be rewritten into <code>encryption-profile &lt;profile_str&gt;</code> according to the match conditions and effects described in <a href="#">Match evaluation and rewrite behavior for email address mappings: on page 345</a>.</p> <p><b>Note:</b> If you enter a pattern with a wild card (* or ?):</p> <p>You must enter a pattern using the same wild card in <code>encryption-profile &lt;profile_str&gt;</code>. The wild card indicates that the mapping could match many email addresses, but also indicates, during the rewrite, which substring of the original email address will be substituted into the position of the wild card in the internal address. If there is no wild card in the other half of the mapping, or the wild card is not the same (that is, * mapped to ? or vice versa), this substitution will fail.</p> <p><code>encryption-profile &lt;profile_str&gt;</code> must not be within the same protected domain. This could cause situations where an email address is rewritten twice, by matching both the sender and recipient rewrite conditions, and the result is therefore the same as the original email address and possibly not deliverable.</p>	

## Related topics

[system wccp settings on page 339](#)

## user pki

Use this command to configure public key infrastructure (PKI) users.

A PKI user can be either an email user or a FortiMail administrator. PKI users can authenticate by presenting a valid client certificate, rather than by entering a user name and password.

When the PKI user connects to the FortiMail unit with his or her web browser, the web browser presents the PKI user's certificate to the FortiMail unit. If the certificate is valid, the FortiMail unit then authenticates the PKI user. To be valid, a client certificate must:

- Not be expired
- Not be revoked by either certificate revocation list (CRL) or, if enabled, online certificate status protocol (OCSP)
- Be signed by a certificate authority (CA), whose certificate you have imported into the FortiMail unit
- Contain a "ca" field whose value matches the CA certificate
- Contain a "issuer" field whose value matches the "subject" field in the CA certificate
- Contain a "subject" field whose value contains the subject, or is empty
- If `ldap-query` is enable, contain a common name (CN) or Subject Alternative field whose value matches the email address of a user object retrieved using the user query of the LDAP profile

If the client certificate is **not** valid, depending on whether you have configured the FortiMail unit to require valid certificates (see `certificate-required {yes | no}` in [config policy recipient on page 118](#) for email users, and `pki-certificate-req {yes | no}` in [system geoip-override on page 302](#) for FortiMail administrators), authentication will either fail absolutely, or fail over to a user name and password mode of authentication.

If the certificate is valid and authentication succeeds, the PKI user's web browser is redirected to either the web-based manager (for PKI users that are FortiMail administrators) or the mailbox folder that contains quarantined spam (for PKI users that are email users).

After using this command to configure a PKI user, you must also configure the following aspects of the FortiMail unit and the PKI user's computer:

- Import each PKI user's client certificate into the web browser of each computer from which the PKI user will access the FortiMail unit. For details on installing certificates, see the documentation for your web browser.



Control access to each PKI user's computer. Certificate-based PKI authentication controls access to the FortiMail unit based upon PKI certificates, which are installed on each email user or administrator's computer. If anyone can access the computers where those PKI certificates are installed, they can gain access to the FortiMail unit, which can compromise the security of your FortiMail unit.

- Import the CA certificate into the FortiMail unit. For information on uploading a CA certificate, see the [FortiMail Administration Guide](#). For more information, see "CA certificate".

- For PKI users that are FortiMail administrators, select the PKI authentication type and select a PKI user to which the administrator account corresponds. For more information, see [system admin on page 270](#).
- For PKI users that are email users, enable PKI user authentication for the recipient-based policies which match those email users.

This command takes effect only if PKI authentication is enabled by `pki-mode {enable | disable}` in the command [system geoip-override on page 302](#).

## Syntax

```
config user pki
  edit name <name_str>
    set ca <certificate_str>
    set domain <protected-domain_str>
    set ldap-field {cn | subjectalternative}
    set ldap-profile <profile_str>
    set ldap-query {enable | disable}
    set oosp-ca <remote-certificate_str>
    set oosp-check {enable | disable}
    set oosp-unavailable-action {revoke | ignore}
    set oosp-url <url_str>
    set subject <subject_str>
  end
```

Variable	Description	Default
name <name_str>	Enter the name of the PKI user.	
ca <certificate_str>	Enter the name of the CA certificate used when verifying the CA's signature of the client certificate. For information on uploading a CA certificate, see the <a href="#">FortiMail Administration Guide</a> . For more information, see "CA certificate". If you configure an empty string for this variable, you must configure <code>subject &lt;subject_str&gt;</code> .	
domain <protected-domain_str>	Enter the name of the protected domain to which the PKI user is assigned, or enter <code>system</code> if the PKI user is a FortiMail administrator and belongs to all domains configured on the FortiMail unit. For more information on protected domains, see <a href="#">dlp scan-rules on page 103</a> .	
ldap-field {cn   subjectalternative}	Enter the name of the field in the client certificate (either CN or Subject Alternative) which contains the email address of the PKI user, either <code>subjectalternative</code> (if the field is a Subject Alternative) or <code>cn</code> (if the field is a common name).  This email address will be compared with the value of the email address attribute for each user object queried from the LDAP directory to determine if the PKI user exists in the LDAP directory.  This variable is used only if <code>ldap-query</code> is <code>enable</code> .	subject
ldap-profile <profile_str>	Enter the LDAP profile to use when querying the LDAP server for the PKI user's existence. For more information on LDAP profiles, see <a href="#">profile ldap on page 226</a> .  This variable is used only if <code>ldap-query</code> is <code>enable</code> .	

Variable	Description	Default
ldap-query {enable   disable}	Enable to query an LDAP directory, such as Microsoft Active Directory, to determine the existence of the PKI user who is attempting to authenticate. Also configure <code>ldap-profile &lt;profile_str&gt;</code> and <code>ldap-field {cn   subjectalternative}</code> .	disable
ocsp-ca <remote-certificate_str>	Enter the name of the remote certificate that is used to verify the identity of the OCSP server. For information on uploading a remote (OCSP) certificate, see the <i>FortiMail Administration Guide</i> . For more information, see "Remote". This option applies only if <code>ocspverify</code> is enable.	
ocsp-check {enable   disable}	Enable to use an Online Certificate Status Protocol (OCSP) server to query whether the client certificate has been revoked. Also configure <code>ocsp-url &lt;url_str&gt;</code> , <code>[ocsp-ca &lt;remote-certificate_str&gt;</code> , and <code>ocsp-unavailable-action {revoke   ignore}</code> .	disable
ocsp-unavailable-action {revoke   ignore}	Enter the action to take if the OCSP server is unavailable. If set to ignore, the FortiMail unit allows the user to authenticate. If set to revoke, the FortiMail unit behaves as if the certificate is currently revoked, and authentication fails. This option applies only if <code>ocsp-check</code> is enable.	ignore
ocsp-url <url_str>	Enter the URL of the OCSP server. This option applies only if <code>ocsp-check</code> is enable.	
subject <subject_str>	Enter the value which must match the "subject" field of the client certificate. If empty, matching values are not considered when validating the client certificate presented by the PKI user's web browser. The FortiMail unit will use a CA certificate to authenticate a PKI user only if the subject string you enter here also appears in the CA certificate subject. If no subject is entered here, the subject not considered when the FortiMail unit selects the certificate to use. To disable Subject verification, enter an empty string surrounded by single quotes ( ' ' ). If you configure an empty string for this variable, you must configure <code>ca &lt;certificate_str&gt;</code> .	

## Related topics

[system wccp settings on page 339](#)

[user map on page 344](#)

# execute

execute commands perform immediate operations on the FortiMail unit.

This chapter describes the following execute commands:

<a href="#">backup on page 350</a>	<a href="#">maintain on page 372</a>
<a href="#">backup-restore on page 352</a>	<a href="#">nslookup on page 373</a>
<a href="#">blocklist</a>	<a href="#">partitionlogdisk on page 374</a>
<a href="#">certificate on page 354</a>	<a href="#">ping on page 375</a>
<a href="#">checklogdisk on page 356</a>	<a href="#">ping-option on page 376</a>
<a href="#">checkmaildisk on page 356</a>	<a href="#">ping6 on page 378</a>
<a href="#">cleanqueue on page 357</a>	<a href="#">ping6-option on page 378</a>
<a href="#">create on page 357</a>	<a href="#">raid on page 380</a>
<a href="#">date on page 359</a>	<a href="#">reboot on page 380</a>
<a href="#">db on page 359</a>	<a href="#">reload on page 381</a>
<a href="#">dlp on page 360</a>	<a href="#">restore as on page 382</a>
<a href="#">endpoint on page 361</a>	<a href="#">restore av on page 382</a>
<a href="#">erase-filesystem on page 361</a>	<a href="#">restore config on page 383</a>
<a href="#">factoryreset</a>	<a href="#">restore image on page 385</a>
<a href="#">factoryreset config</a>	<a href="#">restore mail-queues on page 386</a>
<a href="#">factoryreset disk on page 363</a>	<a href="#">safelist</a>
<a href="#">factoryreset keeplicense</a>	<a href="#">sched-backup on page 387</a>
<a href="#">factoryreset shutdown</a>	<a href="#">shutdown on page 388</a>
<a href="#">fips on page 365</a>	<a href="#">smtpptest on page 389</a>
<a href="#">formatlogdisk on page 366</a>	<a href="#">ssh on page 390</a>
<a href="#">formatmaildisk on page 367</a>	<a href="#">storage on page 390</a>
<a href="#">formatmaildisk-backup on page 368</a>	<a href="#">telnettest on page 390</a>
<a href="#">forticloud on page 369</a>	<a href="#">traceroute on page 391</a>
<a href="#">ha commands on page 369</a>	<a href="#">update on page 393</a>
<a href="#">ibe data on page 370</a>	<a href="#">user-config on page 393</a>
<a href="#">ibe user on page 370</a>	<a href="#">vm on page 394</a>
<a href="#">license on page 371</a>	
<a href="#">lvm on page 371</a>	

## backup

Use this command to back up the configuration file to an FTP, TFTP, SCP server or the local machine.



This command does **not** produce a complete backup. For information on how to back up other configuration files such as Bayesian databases, see the [FortiMail Administration Guide](#).

## Syntax

```
execute backup {config | full-config | ibe-data | mail-queue | user-config} {ftp | local | scp | tftp} on page 351
```

Variable	Description	Default
{config   full-config   ibe-data   mail-queue   user-config}	Type either: <ul style="list-style-type: none"> <li><code>config</code>: Back up configuration changes only. The default settings will not be backed up.</li> <li><code>full-config</code>: Back up the entire configuration file (no default settings either), including the IBE data and user config.</li> <li><code>ibe-data</code>: Back up the IBE data.</li> <li><code>mail-queue</code>: Back up the mail queues.</li> <li><code>user-config</code>: Back up the user-specific configurations, such as user preferences, personal block/safelists, and secondary addresses. Before backing up, you should update the user configuration file. To update the configurations, see <a href="#">user-config on page 393</a>.</li> </ul>	
{ftp   local   scp   tftp}	Specify the backup location and enter the file name and credentials if required.	

## Example

This example uploads a password-encrypted partial configuration backup to a TFTP server.

```
execute backup full-config tftp fortimail_backup.cfg 172.16.1. 1 P@ssword1
No user configuration available!
Do you want to continue? (y/n)y
No IBE data available!
Do you want to continue? (y/n)y
System time: Tue Sep 27 13:07:43 2011
Backup with current user defined configuration and ibe data. Do you want to continue? (y/n)y
Connect to tftp server 172.16.1.1 ...
Please wait...
```

## Optionally encrypt backup content

For improved confidence and privacy, you can protect the back up configuration file with an encryption password. This password must match when restoring the back up configuration.

## Example

```
execute backup config tftp config1.cfg 1.1.1.1
<Enter>|<passwd> Optional password to protect the backup content.
```

## Related topics

[restore config on page 383](#)

[user-config on page 393](#)

# backup-restore

Use this command to back up or restore email users' mailboxes. Before using this command, you must specify the backup destination or the restore location first. For details, see [system backup-restore-mail on page 275](#).

## Syntax

```
execute backup-restore all-restore
execute backup-restore check-device
execute backup-restore format-device
execute backup-restore old-restore <full_int> <increments_int> domain <domain_str> user <user_str>
execute backup-restore restore {domain <domain> user <user> | host <host>}
execute backup-restore start
execute backup-restore stop
```

Variable	Description	Default
all-restore	Use this command to restore mail data without deleting previous full restore while restoring incremental backup.	
check-device	Performs file system check on the backup device.	
format-device	Format the backup device as a preparation step before backup.	
old-restore <full_int> <increments_int> domain <domain_str> user <user_str>	<p>&lt;full_int&gt; is the full backup version you specify when you configure the backup settings.</p> <p>&lt;increments_int&gt; is the number of incremental backups to make between each full backup.</p> <p>&lt;domain_str&gt;: optionally specify which domain's mailbox will be restored.</p> <p>&lt;user_str&gt;: optionally specify which user's mailbox will be restored.</p> <p>For details, see <a href="#">system backup-restore-mail on page 275</a>.</p>	

Variable	Description	Default
restore {domain <domain> user <user>   host <host>} <host>}	<p>Restores mailboxes, or optionally, for the specified domain or user.</p> <p>If you want to restore mailboxes from backups identified by another FQDN, such as a previous FQDN or the FQDN of another FortiMail unit, specify the &lt;host&gt;, which is the FQDN.</p> <p>Usually, you should enter an FQDN of this FortiMail unit, but you may enter only the host name if the local domain name is not configured, or enter the FQDN of another FortiMail unit if you want to import that FortiMail unit's mailbox backup.</p> <p>For example, you may be upgrading to a FortiMail-2000 from a FortiMail-400. Previously, you have used a USB disk to store a backup of the mailboxes of the FortiMail-400, whose fully qualified domain name (FQDN) was fortimail.example.com. You have then configured the FortiMail-2000 to also use the USB disk as its backup media. You could then import the FortiMail-400's mailbox backup to the FortiMail-2000 by entering fortimail.example.com in this field on the FortiMail-2000's web UI.</p>	
start	Initiate an immediate backup. Note that all data on the backup device will be erased.	
stop	Stops any currently running backups.	

## Related topics

[restore config on page 383](#)

[backup on page 350](#)

## blocklist

Use this command to configure blocklist operations.

## Syntax

```
execute blocklist add
execute blocklist backup
execute blocklist purge
execute blocklist remove
execute blocklist restore
```

Variable	Description	Default
add	<p>Add a domain or user level blocklist, or system level blocklist, as shown below (respectively):</p> <pre>execute blocklist add [domain   user] &lt;domain-name   user-name&gt;   &lt;list-content&gt; execute blocklist add [system] &lt;list-content&gt;</pre>	

Variable	Description	Default
backup	Backup a domain or user level blocklist, or system level blocklist to a TFTP server, as shown below (respectively): <pre>execute blocklist backup [domain   user] &lt;domain-name   user-name&gt;     &lt;tftp-server-ip&gt; &lt;file-name&gt; execute blocklist backup [system] &lt;tftp-server-ip&gt; &lt;file-name&gt;</pre>	
purge	Purge a domain or user level blocklist, or system level blocklist, as shown below (respectively): <pre>execute blocklist purge [domain   user] &lt;domain-name-list   user- name-list&gt; execute blocklist purge [system]</pre>	
remove	Remove a domain or user level blocklist, or system level blocklist, as shown below (respectively): <pre>execute blocklist remove [domain   user] &lt;domain-name   user-name&gt;     &lt;list-content&gt; execute blocklist remove [system] &lt;list-content&gt;</pre>	
restore	Restore a domain or user level blocklist, or system level blocklist from a TFTP server, as shown below (respectively): <pre>execute blocklist restore [domain   user] &lt;domain-name   user-name&gt;     &lt;tftp-server-ip&gt; &lt;file-name&gt; execute blocklist restore [system] &lt;tftp-server-ip&gt; &lt;file-name&gt;</pre>	

## Related topics

[safelist](#)

## certificate

Use this command to upload and download certificates, and to generate certificate signing requests (CSR).

## Syntax

```
execute certificate ca import tftp <file_name> <tftp_ip>
execute certificate ca export tftp <cert_name> <file_name> <tftp_ip>
execute certificate config verify
execute certificate crl import tftp <file_name> <tftp_ip>
execute certificate crl export tftp <cert_name> <file_name> <tftp_ip>
execute certificate local export tftp <cert_name> <file_name> <tftp_ip>
execute certificate local generate <cert_name> <key_size> <subject> <country> <state>
    <organization> <unit> <email>
execute certificate local import tftp <file_name> <tftp_ip>
execute certificate local info <cert_name>
execute certificate local regenerate
execute certificate remote import tftp <file_name> <tftp_ip>
execute certificate remote export tftp <cert_name> <file_name> <tftp_ip>
```

Variable	Description	Default
ca import tftp <file_name> <tftp_ip>	Imports the certificate authority (CA) certificate from a TFTP server. Certificate authorities validate and sign other certificates in order to indicate to third parties that those other certificates may be trusted to be authentic.	
ca export tftp <cert_name> <file_name> <tftp_ip>	Exports the CA certificate to a TFTP server.	
config verify	Since FortiMail stores configuration information of CA certificates and local certificates in the configuration file and stores the certificates themselves in the file system, in some circumstances (such as a firmware upgrade or an abnormal system shutdown), the certificate configuration and the certificate may be out of sync.  Use this command to synchronize the certificate configuration in the configuration file with the certificate in the file system.	
crl import tftp <file_name> <tftp_ip>	Imports the certificate revocation list (CRL).  To ensure that your FortiMail unit validates only certificates that have not been revoked, you should periodically upload a current certificate revocation list, which may be provided by certificate authorities (CA). Alternatively, you can use online certificate status protocol (OCSP) to query for certificate statuses.	
crl export tftp <cert_name> <file_name> <tftp_ip>	Exports the CRL to a TFTP server.	
local export tftp <cert_name> <file_name> <tftp_ip>	Exports a certificate signing request or a local certificate to a TFTP server. Note that this command does not support exporting a certificate in PKCS#12 format. To do this, you must go to the web UI.	
local generate <cert_name> <key_size> <subject> <country> <state> <organization> <unit> <email>	Enter the information required to generate a certificate signing request. Certificate signing request files can then be submitted for verification and signing by a certificate authority (CA).	
local import tftp <file_name> <tftp_ip>	Imports a local certificate from a TFTP server. Note that this command does not support importing a certificate that is in PKCS#12 format. To do this, you must go to the web UI.  FortiMail units require a local server certificate that it can present when clients request secure connections, including: <ul style="list-style-type: none"> <li>• the web UI (HTTPS connections only)</li> <li>• webmail (HTTPS connections only)</li> <li>• secure email, such as SMTPS, IMAPS, and POP3S</li> </ul>	
local info <cert_name>	Shows the specified certificate information.	
local regenerate	Regenerates the local self certificate.	

Variable	Description	Default
remote import tftp <file_name> <tftp_ip>	Imports the certificate of the online certificate status protocol (OCSP) servers of your certificate authority (CA). OCSP enables you to revoke or validate certificates by query, rather than by importing certificate revocation lists (CRL).	
remote export tftp <cert_name> <file_name> <tftp_ip>	Exports the OCSP certificate to a TFTP server.	

## Related topics

[profile certificate-binding on page 205](#)

## checklogdisk

Use this command to find and correct errors on the log disk.



Use this command only when recommended by Fortinet Technical Support. Logging is suspended while this command is executing.

## Syntax

```
execute checklogdisk
```

## Related topics

[checkmaildisk on page 356](#)

## checkmaildisk

Use this command to find and correct errors on the mail disk. Actions are displayed at the command prompt. If the command cannot fix an error automatically, it displays a list of manual correction options from which you must select.



Use this command only when recommended by Fortinet Technical Support. Email-related functions are suspended while this command is executing.

---

## Syntax

```
execute checkmaildisk
```

## Related topics

[checklogdisk](#) on page 356

## cleanqueue

Select to remove all messages from the deferred queue.

## Syntax

```
execute cleanqueue
```

## Related topics

[maintain](#) on page 372

## create

This is a hidden command. Use this command to create various system-wide, domain-wide, and user-wide antispam settings.

## Syntax

```
execute create custom-message <domain> <message_content>  
execute create dkim-signing-key  
execute create ibe-system-key <content>
```

```

execute create resource-share
execute create system-custom-message <contents>
execute create system-favicon
execute create user-auto-forward <email_addr> <content>
execute create user-auto-reply <email_addr> <content>
execute create user-calendar <user_name>
execute create user-calendar-b64
execute create user-calendar-tag <email_addr> <content>
execute create user-email-tag <email_addr> <content>
execute create user-filter-custom
execute create user-filter-master
execute create user-filter-sieve
execute create user-preference <user_name> <content>
execute create user-primaryaddr <user_name> <content>
execute create user-secondaryaddr <user_name> <content>
execute create user-signature <user_name> <content>

```

Variable	Description	Default
custom-message <domain> <message_content>	Creates domain-wide custom messages.	
dkim-signing-key	Creates DomainKeys Identified Mail (DKIM) signing key.	
resource-share	Creates a resource share.	
ibe-system-key <content>	Creates IBE system key.	
system-custom-message <contents>	Creates system-wide custom messages.	
system-favicon	Creates a system use icon file.	
user-auto-forward <email_ addr> <content>	Creates an auto forward message for the user.	
user-auto-reply <email_addr> <content>	Creates an auto reply message for the user.	
user-calendar <user_name>	Creates a calendar for the user.	
user-calendar-b64	Creates a calendar base64 encoded.	
user-calendar-tag <email_ addr> <content>	Creates a user calendar tag.	
user-email-tag <email_addr> <content>	Creates a user email tag.	
user-filter-custom	Creates a user message filter custom file.	
user-filter-master	Creates a user message filter master file.	
user-filter-sieve	Creates a user message filter sieve file.	
user-preference <user_name> <content>	Configures the user preference settings. For details, see the User chapter in the <a href="#">FortiMail Administration Guide</a> .	
user-primaryaddr <user_ name> <content>	Configures the primary email account for the user.	

Variable	Description	Default
user-secondaryaddr <user_name> <content>	Configures the secondary email account for the user.	
user-signature <user_name> <content>	Configures the email signature for the user.	

## Related topics

[backup on page 350](#)

## date

Use this command to set the system date.

## Syntax

```
execute date <date_str>
```

Variable	Description	Default
<date_str>	Enter the system date in the format of mm/dd/yyyy.	

## Related topics

[system time manual on page 337](#)

[system time ntp on page 338](#)

## db

Use this command to repair, rebuild, or reset the following FortiMail databases:

- Address book
- Bayesian database
- Certificate database
- Customized messages
- Dictionaries
- DKIM key database

- Email migration database
- End point database
- End point sender reputation database
- Greylist database
- Greylist exempt database
- IBE database
- Sender reputation database
- User alias database
- User address mapping database

## Syntax

```
execute db dump
execute db force-recover
execute db info
execute db rebuild
execute db reset <database>
execute db restore
execute db transfer
```

Variable	Description	Default
dump	Dumps one database file for troubleshooting.	
force-recover	Try to repair all of the databases using force recovery.	
info	Provides database information.	
rebuild	Clean and rebuild all of the databases.	
reset <database>	Clean and rebuild one of the FortiMail databases. <database> is one of the above-listed databases.	
restore	Restores one database.	
transfer	Transfer last dumped db file to a remote server via FTP, SCP, or TFTP. Use the following format: execute db transfer {ftp-dump   scp-dump   tftp-dump} <file-name> <server-ip> <username> <password>	

## Related topics

[maintain on page 372](#)

## dlp

Use this command to refresh the DLP fingerprints from the fingerprint server.

## Syntax

```
execute dlp refresh <source_name>
```

Variable	Description	Default
<source_name>	Enter the source server address or host name.	

## endpoint

Use this command to configure carrier endpoint devices. A carrier end point is any device on the periphery of a carrier's or internet service provider's (ISP) network. It could be, for example, a subscriber's GSM cellular phone, wireless PDA, or computer using DSL service.

## Syntax

```
execute endpoint count
execute endpoint data backup tftp <ip_address>
execute endpoint delete <ip_address>
```

Variable	Description	Default
count	Count the total number of endpoint devices in the end point database.	
data backup tftp <ip_address>	Back up the end point database to the specified TFTP server.	
delete <ip_address>	Remove the IP address of an endpoint device from the end point database.	

## erase-filesystem

Securely erases a file system by filling with random data three times.

## Syntax

```
execute erase-filesystem
```

Variable	Description	Default
erase-filesystem		

# factoryreset

Use this command to reset the FortiMail unit to its default settings for the currently installed firmware version. If you have not upgraded or downgraded the firmware, this restores factory default settings.

This command also erases all the log files and mail data on the hard drive.



Back up your configuration and mail data before entering this command. This procedure resets all changes that you have made to the FortiMail unit's configuration file and reverts the system to the default values for the firmware version, including factory default settings for the IP addresses of network interfaces. For information on creating a backup, see the [FortiMail Administration Guide](#).

---

## Syntax

```
execute factoryreset
```

## Example

The following example resets the FortiMail unit to default settings for the currently installed firmware version.

```
execute factoryreset
```

The CLI displays the following:

```
This operation will change all settings to  
factory default! Do you want to continue? (y/n)
```

After you enter `y` (yes), the CLI displays the following and logs you out of the CLI:

```
System is resetting to factory default...
```

## Related topics

[restore config on page 383](#)

[backup on page 350](#)

# factoryreset config

Use this command to reset the system configuration to default settings.

## Syntax

```
execute factoryreset config
```

## Related topics

[backup on page 350](#)

## factoryreset config2

Use this command to reset the system configuration to default settings, while retaining the network settings and disk data.

## Syntax

```
execute factoryreset config2
```

## Related topics

[backup on page 350](#)

## factoryreset disk

Use this command to reset the RAID level and partition disk to default settings.

## Syntax

```
execute factoryreset disk
```

## Related topics

[backup on page 350](#)

## factoryreset keeplicense

Use this command to reset the FortiMail VM configuration to its factory default settings, but keep the VM license file.

### Syntax

```
execute factoryreset keeplicense
```

### Related topics

[backup on page 350](#)

## factoryreset shutdown

Use this command to reset the FortiMail unit's configuration and disk partition to its factory default settings and then shutdown the system.

### Syntax

```
execute factoryreset shutdown
```

### Related topics

[backup on page 350](#)

## factoryreset2

Use this command to reset the FortiMail unit to its default settings for the currently installed firmware version, while retaining all network settings. If you have not upgraded or downgraded the firmware, this restores factory default settings.

This command also erases all the log files and mail data on the hard drive.



Unlike `factoryreset` which resets all changes that you have made to the FortiMail unit's configuration file including its network settings, it is still recommended to back up your configuration and mail data before entering this command.

For information on creating a backup, see the [FortiMail Administration Guide](#).

---

## Syntax

```
execute factoryreset2
```

## Example

The following example resets the FortiMail unit's configuration and disk partition to its factory default settings, while keeping the network settings.

```
execute factoryreset2
```

## factoryreset2 keeplicense

Use this command to reset the FortiMail VM configuration to its factory default settings, while retaining the network settings and VM license file.

## Syntax

```
execute factoryreset2 keeplicense
```

## Related topics

[backup on page 350](#)

## fips

Use this command to enable Federal Information Processing Standards-Common Criteria (FIPS-CC) mode.

This enhanced security mode is required by some organizations, but may not be appropriate for others. It is valid only if you have installed a FIPS-certified firmware build. For more information on FIPS, or to obtain a certified build, contact [Fortinet Technical Support](#).

When switching to FIPS mode, you will be prompted to confirm, and must log in again.

To disable FIPS mode, restore the firmware default configuration using [factoryreset on page 362](#).



Back up the configuration before enabling FIPS mode. When you enable or disable FIPS-CC mode, all of the existing configuration is lost. For more information on making a complete backup, see the [FortiMail Administration Guide](#).

## Syntax

```
execute fips kat {3des | aes | configuration-test | integrity-test | rng | rsa | sha1-hmac | all}
```

Variable	Description	Default
{3des   aes   configuration-test   integrity-test   rng   rsa   sha1-hmac   all}	<p>3des: Triple-DES known answer test.</p> <p>aes: AES known answer test</p> <p>configuration-test: Configuration bypass test.</p> <p>integrity-test: Firmware integrity test.</p> <p>rng: RNG known answer test.</p> <p>rsa: RSA known answer test.</p> <p>sha1-hmac: SHA1-HMAC known answer test.</p> <p>all: All known answer tests.</p>	

## Related topics

[restore image on page 385](#)

## formatlogdisk

Use this command to reformat the local hard disk that contains log data.



Regularly format the hard disk to improve performance.



Back up all data on the disk before entering this command. Formatting hard disks deletes all files on that disk.

## Syntax

```
execute formatlogdisk
```

## Example

The following example formats the log disk.

```
execute formatlogdisk
```

The CLI displays the following:

```
This operation will erase all data on the log disk!  
Do you want to continue? (y/n)
```

After you enter `y` (yes), the CLI displays the following and logs you out of the CLI:

```
formatting disk, Please wait a few seconds!
```

## Related topics

[partitionlogdisk on page 374](#)

[formatmaildisk on page 367](#)

[formatmaildisk-backup on page 368](#)

## formatmaildisk

Use this command to reformat the local hard disk that contains email data, **without** first performing a backup.

You can alternatively perform a backup before formatting the mail disk. For details, see [formatmaildisk-backup on page 368](#).



Regularly format the hard disk to improve performance.



Back up all data on the disk before entering this command. Formatting hard disks deletes all files on that disk.

---

## Syntax

```
execute formatmaildisk
```

## Example

The following example formats the log disk.

```
execute formatmaildisk
```

The CLI displays the following:

```
This operation will erase all data on the mail disk!  
Do you want to continue? (y/n)
```

After you enter `y` (yes), the CLI displays the following and logs you out of the CLI:

```
formatting disk, Please wait a few seconds!
```

## Related topics

[formatmaildisk-backup on page 368](#)

[formatlogdisk on page 366](#)

## formatmaildisk-backup

Use this command to back up data contained on the mail disk to the log disk, and then format the local mail disk.

You can alternatively format the mail disk without performing a backup. For details, see [formatmaildisk on page 367](#).



Regularly format the hard disk to improve performance.

---

## Syntax

```
execute formatmaildisk-backup
```

## Related topics

[formatmaildisk on page 367](#)

[formatlogdisk on page 366](#)

## forticloud

Use this command to manage the FortiCloud account.

### Syntax

```
execute forticloud info
execute forticloud info-apt
execute forticloud join
execute forticloud login
execute forticloud sandbox-region
execute forticloud update-apt
```

Variable	Description	Default
info	Shows the FortiCloud account info if login in.	
info-apt	Show information about FortiCloud sandbox, including APT license, license expiration date, and region. DEBUG image shows cloud sandbox server IP.	
join	Joins an existing FortiCloud account. The device must be added to the account to work.	
login	Logs the user into the FortiCloud account.	
sandbox-region	Define the cloud sandbox region: <ul style="list-style-type: none"> <li>• 0: Global</li> <li>• 1: Europe</li> <li>• 2: Japan</li> <li>• 3: US</li> </ul>	
update-apt	Force refresh of FortiCloud sandbox server addresses.	

## ha commands

Use this command to help debugging FortiMail HA issues.



Type the full command names (such as `ha commands ...`), instead of the abbreviated names (such as `ha com ...`).

### Syntax

```
execute ha commands config-sync-start
execute ha commands config-sync-stop
execute ha commands failover-start
```

execute ha commands `failover-stop`

Variable	Description	Default
<code>config-sync-start</code>	Start synchronizing the HA cluster configuration.	
<code>config-sync-stop</code>	Stop the cluster from completing synchronizing its configuration.	
<code>failover-start</code>	Allow HA failover to happen.	
<code>failover-stop</code>	Prevent HA failover from happening.	

## Related topics

[cleanqueue on page 357](#)

## ibe data

Use this command to generate and view an IBE data file.

## Syntax

execute ibe data `export-to-file` on page 370  
execute ibe data `get-file-info` on page 370

Variable	Description	Default
<code>export-to-file</code>	Generate an IBE data file.	
<code>get-file-info</code>	Get current IBE data file information.	

## Related topics

[db on page 359](#)

## ibe user

Use this command to maintain the expired users.

## Syntax

```
execute ibe user purge-mail <user_name> <level> on page 371
execute ibe user clean-expired-user <user_name> <level> on page 371
```

Variable	Description	Default
purge-mail <user_name> <level>	Specify whose mail you want to purge/delete and also specify the verbose level.	
clean-expired-user <user_name> <level>	Specify which user you want to delete and also specify the verbose level.	

## Related topics

db on page 359

## license

Use this command to manage the central management license.

## Syntax

```
execute license central-mgmt import tftp <ip> <file_name>
execute license central-mgmt show
```

Variable	Description	Default
import tftp <ip> <file_name>		
show	Display the license information.	

## lvm

Use this command to control the logical volume manager (LVM) support on the FortiMail-VM platforms.

Since this feature is added in 5.2.0 release, if you're upgrading from older FortiMail-VM releases to 5.2.0 release, LVM is not enabled by default. If you want to enable it, you must be aware that all the mail data and log data will be erased.

## Syntax

```
execute lvm disable on page 372
execute lvm enable <percentage> on page 372
execute lvm extend <percentage> on page 372
execute lvm summary on page 372
```

Variable	Description	Default
disable	Stop LVM on the system.	
enable <percentage>	Start LVM on the system. Also specify how much percent of the hard disk space will be allocated to the log disk. The remaining will be assigned to the mail disk. If not specified, the default percentage is 20.	enable (for new install) 20
extend <percentage>	Use this command to add new drives to the system. See above for the usage of percentage.	20
summary	Displays the LVM status and details.	

## maintain

Use this command to perform maintenance on mail queues by deleting out-of-date messages.

## Syntax

```
execute maintain mailqueue clear age <time_str>
```

Variable	Description	Default
age <time_str>	Enter an age between 1 hour and 10 years. The FortiMail unit deletes mail messages in the mail queues greater than this age. The age consists of an integer appended to a letter that indicates the unit of time: h (hours), d (days), m (months), or y (years).	24h

## Example

This example will clear messages that are 23 days old and older.

```
execute maintain mailqueue clear age 23d
```

The CLI would display the following message:

Clearing messages in mail queues at least 23 days old.



Variable	Description	Default
	<port_number>: optionally specify the port number of the DNS server.	

## Example

You could use this command to determine the DNS resolution for the fully qualified domain name mail.example.com

```
execute nslookup name mail.example.com
```

The CLI would display the following:

```
Name: example.com  
Address: 192.168.1.15
```

Similarly, you could use this command to determine the domain name hosted on the IP address 192.168.1.15:

```
execute nslookup name 192.168.1.15 type ptr
```

The CLI would display the following:

```
Address: 192.168.1.15  
Name: mail.example.com
```

You could also use this command to determine the host that is mail exchanger (MX) for the domain example.com:

```
execute nslookup name example.com type mx
```

The CLI would display the following:

```
example.com mail exchanger = 10 mail.example.com.
```

## Related topics

[ping on page 375](#)

[traceroute on page 391](#)

[system dns on page 286](#)

## partitionlogdisk

Use this command to adjust the size ratio of the hard disk partitions for log and mail data.



Back up all data on the disks before beginning this procedure. Partitioning the hard disks deletes all files on those disks.

## Syntax

```
execute partitionlogdisk <logpercentage_str>
```

Variable	Description	Default
partitionlogdisk <logpercentage_str>	Enter an integer between 10 and 90 to create a partition for log files using that percentage of the total hard disk space.  The remaining partition (by default, 75% of the hard disk space) will be used for mail data.	20

## Related topics

[formatlogdisk on page 366](#)

## ping

Use this command to perform an ICMP ECHO request (also called a ping) to a host by specifying its fully qualified domain name (FQDN) or IP address, using the options configured by [ping-option on page 376](#).

Pings are often used to test connectivity.

## Syntax

```
execute ping {<fqdn_str> | <host_ipv4>}
```

Variable	Description	Default
ping {<fqdn_str>   <host_ipv4>}	Enter either the IP address or fully qualified domain name (FQDN) of the host.	

## Example

This example pings a host with the IP address 172.16.1.10.

```
execute ping 172.16.1.10
```

The CLI displays the following:

```
PING 172.16.1.10 (172.16.1.10): 56 data bytes
 64 bytes from 172.16.1.10: icmp_seq=0 ttl=128 time=0.5 ms
 64 bytes from 172.16.1.10: icmp_seq=1 ttl=128 time=0.2 ms
 64 bytes from 172.16.1.10: icmp_seq=2 ttl=128 time=0.2 ms
 64 bytes from 172.16.1.10: icmp_seq=3 ttl=128 time=0.2 ms
 64 bytes from 172.16.1.10: icmp_seq=4 ttl=128 time=0.2 ms
```

```
--- 172.16.1.10 ping statistics ---
  5 packets transmitted, 5 packets received, 0% packet loss
 round-trip min/avg/max = 0.2/0.2/0.5 ms
```

The results of the ping indicate that a route exists between the FortiWeb unit and 172.16.1.10. It also indicates that during the sample period, there was no packet loss, and the average response time was 0.2 milliseconds (ms).

## Example

This example pings a host with the IP address 10.0.0.1.

```
execute ping 10.0.0.1
```

The CLI displays the following:

```
PING 10.0.0.1 (10.0.0.1): 56 data bytes
```

After several seconds, no output has been displayed. The administrator halts the ping by pressing Ctrl + C. The CLI displays the following:

```
--- 10.0.0.1 ping statistics ---
  5 packets transmitted, 0 packets received, 100% packet loss
```

The results of the ping indicate that the host may be down, or that there is no route between the FortiMail unit and 10.0.0.1. To determine the cause, further diagnostic tests are required, such as [traceroute on page 391](#).

## Related topics

[ping-option on page 376](#)

[smtpstest on page 389](#)

[telnetstest on page 390](#)

[traceroute on page 391](#)

[system dns on page 286](#)

## ping-option

Use this command to configure behavior of [ping on page 375](#).

## Syntax

```
execute ping-option data-size <bytes_int>
execute ping-option df-bit {yes | no}
execute ping-option pattern <bufferpattern_hex>
execute ping-option repeat-count <repeat_int>
execute ping-option source {auto | <interface_ipv4>}
execute ping-option timeout <seconds_int>
execute ping-option tos {default | lowcost | lowdelay | reliability | throughput}
```

```
execute ping-option ttl <hops_int>
execute ping-option validate-reply {yes | no}
execute ping-option view-settings
```

Variable	Description	Default
data-size <bytes_int>	Enter datagram size in bytes. This allows you to send out packets of different sizes for testing the effect of packet size on the connection. If you want to configure the pattern that will be used to buffer small datagrams to reach this size, also configure <code>pattern &lt;bufferpattern_hex&gt;</code> .	56
df-bit {yes   no}	Enter either yes to set the DF bit in the IP header to prevent the ICMP packet from being fragmented, or enter no to allow the ICMP packet to be fragmented.	no
pattern <bufferpattern_hex>	Enter a hexadecimal pattern, such as 00ffaabb, to fill the optional data buffer at the end of the ICMP packet. The size of the buffer is determined by <code>data-size &lt;bytes_int&gt;</code> .	
repeat-count <repeat_int>	Enter the number of times to repeat the ping.	5
source {auto   <interface_ipv4>}	Select the network interface from which the ping is sent. Enter either auto or a mail network interface's IP address.	auto
timeout <seconds_int>	Enter the ping response timeout in seconds.	2
tos {default   lowcost   lowdelay   reliability   throughput}	Enter the IP type-of-service option value, either: <ul style="list-style-type: none"> <li>default: Do not indicate (that is, set the TOS byte to 0).</li> <li>lowcost: Minimize cost.</li> <li>lowdelay: Minimize delay.</li> <li>reliability: Maximize reliability.</li> <li>throughput: Maximize throughput.</li> </ul>	default
ttl <hops_int>	Enter the time-to-live (TTL) value.	64
validate-reply {yes   no}	Select whether or not to validate ping replies.	no
view-settings	Display the current ping option settings.	

## Example

This example sets the number of pings to three and the source IP address to that of the port2 network interface, 10.10.10.1, then views the ping options to verify their configuration.

```
execute ping-option repeat-count 3
execute ping-option source 10.10.10.1
execute ping-option view-settings
```

The CLI would display the following:

```
Ping Options:
Repeat Count: 3
Data Size: 56
Timeout: 2
```

```
TTL: 64
TOS: 0
DF bit: unset
Source Address: 10.10.10.1
Pattern:
Pattern Size in Bytes: 0
Validate Reply: no
```

## Related topics

[ping on page 375](#)

[traceroute on page 391](#)

## ping6

Use this command to perform a ping6 request to an IPv6 host by specifying its fully qualified domain name (FQDN) or IP address, using the options configured by [ping6-option on page 378](#).

Pings are often used to test connectivity.

## Syntax

```
execute ping6 {<fqdn_str> | <host_ipv4>}
```

Variable	Description	Default
ping6 {<fqdn_str>   <host_ipv4>}	Enter either the IP address or fully qualified domain name (FQDN) of the host.	

## Related topics

[ping on page 375](#)

[ping6-option on page 378](#)

## ping6-option

Use this command to configure behavior of [ping6 on page 378](#).

## Syntax

```
execute ping6-option data-size <bytes_int>
execute ping6-option pattern <bufferpattern_hex>
execute ping6-option repeat-count <repeat_int>
execute ping6-option source {auto | <interface_ipv4>}
execute ping6-option timeout <seconds_int>
execute ping6-option tos {default | lowcost | lowdelay | reliability | throughput}
execute ping6-option ttl <hops_int>
execute ping6-option validate-reply {yes | no}
execute ping6-option view-settings
```

Variable	Description	Default
data-size <bytes_int>	Enter datagram size in bytes. This allows you to send out packets of different sizes for testing the effect of packet size on the connection. If you want to configure the pattern that will be used to buffer small datagrams to reach this size, also configure <code>pattern &lt;bufferpattern_hex&gt;</code> .	56
pattern <bufferpattern_hex>	Enter a hexadecimal pattern, such as 00ffaabb, to fill the optional data buffer at the end of the ICMP packet. The size of the buffer is determined by <code>data-size &lt;bytes_int&gt;</code> .	
repeat-count <repeat_int>	Enter the number of times to repeat the ping.	5
source {auto   <interface_ipv4>}	Select the network interface from which the ping is sent. Enter either auto or a mail network interface's IP address.	auto
timeout <seconds_int>	Enter the ping response timeout in seconds.	2
tos {default   lowcost   lowdelay   reliability   throughput}	Enter the IP type-of-service option value, either: <ul style="list-style-type: none"> <li>default: Do not indicate (that is, set the TOS byte to 0).</li> <li>lowcost: Minimize cost.</li> <li>lowdelay: Minimize delay.</li> <li>reliability: Maximize reliability.</li> <li>throughput: Maximize throughput.</li> </ul>	default
ttl <hops_int>	Enter the time-to-live (TTL) value.	64
validate-reply {yes   no}	Select whether or not to validate ping replies.	no
view-settings	Display the current ping option settings.	

## Related topics

[ping on page 375](#)

[ping6 on page 378](#)

[db on page 359](#)

## raid

Use this command to find and add a hard disk to the array unit after you insert a second hard disk into the drive bay.

---



This command is only available for some FortiMail platforms which support RAID.

---

## Syntax

```
execute raid add-disk
```

## Example

You could notify the RAID controller to add the hard disk to the array unit after inserting a new hard disk.

```
execute raid
```

The CLI displays the following:

```
This operation will scan for new hard drives and add them into the RAID array  
Do you want to continue? (y/n)
```

After you enter *y* (yes), if all hard disks have already been added to an array, the CLI displays the following:

```
existing raid disk at 12 is 120034123776  
existing raid disk at 13 is 120034123776  
no NEW disks in the system
```

## Related topics

[system status on page 397](#)

## reboot

Use this command to restart the FortiMail unit.

## Syntax

```
execute reboot
```

## Example

The following example reboots the FortiMail unit.

```
execute reboot
```

The CLI displays the following:

```
This operation will reboot the system !  
Do you want to continue? (y/n)
```

After you enter `y` (yes), the CLI displays the following:

```
System is rebooting...
```

If you are connected to the CLI through a local console, the CLI displays messages while the reboot is occurring.

If you are connected to the CLI through the network, the CLI will not display any notification while the reboot is occurring, as this occurs after the network interfaces have been shut down. Instead, you may notice that the connection is terminated. Time required by the reboot varies by many factors, such as whether or not hard disk verification is required, but may be several minutes.

## Related topics

[shutdown on page 388](#)

## reload

If you set your console to batch mode, use this command to flush the current configuration from system memory (RAM) and reload the configuration from a previously saved configuration file.

In addition, you can also use this command to reload individual daemons that have crashed. In this case, the command is as following:

```
execute reload [{httpd | ...}]
```

where `[{httpd | ...}]` indicates the name of a specific daemon that you want to restart, if you want to limit the reload to a specific daemon.

For example, if HTTP and HTTPS access are enabled, but you cannot get a connection response on webmail or the GUI, although you can still connect via SSH and ping. Thus you know that the FortiMail unit has not crashed entirely. If you do not want to reboot because this would interrupt SMTP, you can choose to restart the HTTP daemon only.

```
FortiMail-400 # execute reload httpd  
Restart httpd?  
Do you want to continue? (y/n)y
```

```
Reloading httpd....done
```

Note that the command does not check whether your indicated daemon actually exists. It simply indicates whether the command is executed. If the command does not take a few seconds to execute, it is possible that the daemon does not really exist.

## Syntax

```
execute reload [<daemon_name>]
```

## Related topics

[reboot on page 380](#)

[restore config on page 383](#)

[restore image on page 385](#)

## restore as

Use this command to restore an antispam configuration file from a TFTP server.

## Syntax

```
execute restore as tftp <filename_str> <server_ipv4>
```

Variable	Description	Default
<filename_str>	Enter the name of the configuration file stored on a TFTP server.	
<server_ipv4>	Enter the IP address of the TFTP server where the configuration file is stored.	

## Related topics

[restore av on page 382](#)

## restore av

use this command to restore an antivirus configuration file from a TFTP server.

## Syntax

```
execute restore av tftp <filename_str> <server_ipv4>
```

Variable	Description	Default
<filename_str>	Enter the name of the configuration file stored on a TFTP server.	
<server_ipv4>	Enter the IP address of the TFTP server where the configuration file is stored.	

## Related topics

restore as on page 382

## restore config

Use this command to restore a primary configuration file from a TFTP server.



Back up your configuration before entering this command. This procedure can perform large changes to your configuration, including, if you are downgrading the firmware, resetting all changes that you have made to the FortiMail unit's configuration file and reverting the system to the default values for the firmware version, including factory default settings for the IP addresses of network interfaces. For information on creating a backup, see the [FortiMail Administration Guide](#).



Unlike installing firmware via TFTP during a boot interrupt, installing firmware using this command will attempt to preserve settings and files, and not necessarily restore the FortiMail unit to its firmware/factory default configuration. For information on installing firmware via TFTP boot interrupt, see the [FortiMail Administration Guide](#).

## Syntax

```
execute restore config {tftp <filename_str> <server_ipv4> |
  management-station {normal | template} <revision_int>}
```

Variable	Description	Default
<filename_str>	If you want to restore a configuration file stored on a TFTP server, enter the name of the configuration file.	
<server_ipv4>	If you want to restore a configuration file stored on a TFTP server, enter the IP address of the TFTP server.	
management-station {normal   template}	If you want to restore a configuration file or apply a template stored on a FortiManager unit, enter the management-station keyword then enter either: <ul style="list-style-type: none"> <li>normal: Restore a configuration revision number.</li> <li>template: Apply a template revision number.</li> </ul>	

Variable	Description	Default
<revision_int>	If you want to restore a configuration file or apply a template stored on a FortiManager unit, enter the revision number of the configuration file or template.	

## Example

This example restores configuration file revision 2, which is stored on the FortiManager unit.

```
execute restore config management-station normal 2
```

The CLI displays the following:

```
This operation will overwrite the current settings!
Do you want to continue? (y/n)
```

After you enter *y* (yes), the CLI displays the following:

```
Connect to FortiManager ...
Please wait...
```

## Example

This example restores a configuration file from a TFTP server at 172.16.1.5.

```
execute restore config tftp fml.cfg 172.16.1.5
```

The CLI displays the following:

```
This operation will overwrite the current settings!
(The current admin password will be preserved.)
Do you want to continue? (y/n)
```

After you enter *y* (yes), the CLI displays the following, then terminates the SSH connection and reboots with the restored configuration:

```
Connect to tftp server 172.16.1.5 ...
Please wait...
```

```
Get config file from tftp server OK.
File check OK.
```

## Related topics

[backup on page 350](#)

[system central-management](#)

## restore image

Use this command to restore a firmware file from an FTP, SCP, or TFTP server.



Back up your configuration before entering this command. This procedure can perform large changes to your configuration, including, if you are downgrading the firmware, resetting all changes that you have made to the FortiMail unit's configuration file and reverting the system to the default values for the firmware version, including factory default settings for the IP addresses of network interfaces. For information on creating a backup, see the [FortiMail Administration Guide](#).

## Syntax

```
execute restore image {ftp|scp|tftp} <filename_str> <server_ipv4> <user><password>
```

Variable	Description	Default
<filename_str>	Enter the name of the firmware file backup file.	
<server_ipv4>	Enter the IP address of the server.	
<user><password>	You may need to enter the credentials to log on to the server.	

## Example

This example restores firmware file FE\_2000A-v300-build397-FORTINET.out, which is stored on the TFTP server 192.168.1.20.

```
execute restore image tftp FE_2000A-v300-build397-FORTINET.out 192.168.1.20
```

The CLI displays the following:

```
This operation will replace the current firmware version!
Do you want to continue? (y/n)
```

After you enter y (yes), the CLI displays the following:

```
Connect to tftp server 192.168.1.20 ...
Please wait...
#####
Get image from tftp server OK.
Check image OK.
```

## Related topics

[restore config on page 383](#)

[system central-management](#)

## restore mail-queues

Use this command to restore a mail queue file from a TFTP server.



Back up your configuration before entering this command. This procedure can perform large changes to your configuration, including, if you are downgrading the firmware, resetting all changes that you have made to the FortiMail unit's configuration file and reverting the system to the default values for the firmware version, including factory default settings for the IP addresses of network interfaces. For information on creating a backup, see the [FortiMail Administration Guide](#).

## Syntax

```
execute restore mail-queues {tftp <filename_str> <server_ipv4>}
```

Variable	Description	Default
<filename_str>	If you want to restore a firmware file stored on a TFTP server, enter the name of the firmware file backup file.	
<server_ipv4>	If you want to restore a firmware file stored on a TFTP server, enter the IP address of the TFTP server.	

## Related topics

[restore config on page 383](#)

## safelist

Use this command to configure safelist operations.

## Syntax

```
execute safelist add
execute safelist backup
execute safelist purge
execute safelist remove
execute safelist restore
```

Variable	Description	Default
add	Add a domain or user level safelist, or system level safelist, as shown below (respectively): <pre>execute safelist add [domain   user]     &lt;domain-name   user-name&gt; &lt;list-content&gt; execute safelist add [system] &lt;list-content&gt;</pre>	
backup	Backup a domain or user level safelist, or system level safelist to a TFTP server, as shown below (respectively): <pre>execute safelist backup [domain   user]     &lt;domain-name   user-name&gt; &lt;tftp-server-ip&gt; &lt;file-name&gt; execute safelist backup [system] &lt;tftp-server-ip&gt; &lt;file-name&gt;</pre>	
purge	Purge a domain or user level safelist, or system level safelist, as shown below (respectively): <pre>execute safelist purge [domain   user]     &lt;domain-name-list   user-name-list&gt; execute safelist purge [system]</pre>	
remove	Remove a domain or user level safelist, or system level safelist, as shown below (respectively): <pre>execute safelist remove [domain   user]     &lt;domain-name   user-name&gt; &lt;list-content&gt; execute safelist remove [system] &lt;list-content&gt;</pre>	
restore	Restore a domain or user level safelist, or system level safelist from a TFTP server, as shown below (respectively): <pre>execute safelist restore [domain   user]     &lt;domain-name   user-name&gt; &lt;tftp-server-ip&gt; &lt;file-name&gt; execute safelist restore [system] &lt;tftp-server-ip&gt; &lt;file-name&gt;</pre>	

## Related topics

[blocklist](#)

## sched-backup

Use this command to schedule backup to FortiManager.

## Syntax

```
execute sched-backup
```

## shutdown

Use this command to prepare the FortiMail unit to be powered down by halting the software, clearing all buffers, and writing all cached data to disk.



Power off the FortiMail unit only after issuing this command. Unplugging or switching off the FortiMail unit without issuing this command could result in data loss.

---

## Syntax

```
execute shutdown
```

## Example

The following example halts the FortiMail unit.

```
execute shutdown
```

The CLI displays the following:

```
This operation will halt the system  
(power-cycle needed to restart)!Do you want to continue? (y/n)
```

After you enter `y` (yes), the CLI displays the following:

```
System is shutting down...(power-cycle needed to restart)
```

If you are connected to the CLI through a local console, the CLI displays a message when the shutdown is complete.

If you are connected to the CLI through the network, the CLI will not display any notification when the shutdown is complete, as this occurs after the network interfaces have been shut down. Instead, you may notice that the connection times out.

## Related topics

[reboot on page 380](#)

# smtpstest

Use this command to test SMTP connectivity to a specified host.

## Syntax

```
execute smtpstest {<fqdn_str> | <host_ipv4>}[:<port_int>] [domain <domain_str>]
```

Variable	Description	Default
{<fqdn_str>   <host_ipv4>}	Enter the IP address or fully qualified domain name (FQDN) of the SMTP server.	
[:<port_int>]	If the SMTP server listens on a port number other than port 25, enter a colon (:) followed by the port number.	:25
[domain <domain_str>]	If you want to test the connection from an IP address in the protected domain's IP pool, enter the name of the protected domain.	

## Example

This example tests the connection to an SMTP server at 192.168.1.10 on port 2525. For the outgoing connection, the FortiMail unit uses the source IP address 192.168.1.20 from the IP pool selected in the protected domain example.com.

```
execute smtpstest 192.168.1.10:2525 domain example.com
```

The CLI displays the following:

(using 192.168.1.20 to connect)

Remote Output:

```
220 fortimail.example.com ESMTP Smtpd; Mon, 19 Jan 2009
13:27:35 -0500
```

Connection Status:

Connecting to remote host succeeded.

## Related topics

[telnettest on page 390](#)

[traceroute on page 391](#)

[ping on page 375](#)

[system dns on page 286](#)

## ssh

Use this command to connect to another device via SSH.

### Syntax

```
execute ssh <username@host> <password>
```

Variable	Description	Default
<username@host>	Enter the user name and password. The host can be an IP address or the host name of the remote device.	
<password>		

## storage

Use this command to configure remote file storage.

### Syntax

```
execute storage format  
execute storage fscheck  
execute storage start  
execute storage test
```

Variable	Description	Default
format	Remove all data on the remote storage device.	
fscheck	Check the remote file storage system.	
start	Start the remote storage daemon.	
test	Test the remote file storage system.	

## telnettest

Use this command to test Telnet connectivity to a specified host.

## Syntax

```
execute telnettest {<fqdn_str> | <host_ipv4>}[:<port_int>]
```

Variable	Description	Default
{<fqdn_str>   <host_ipv4>}	Enter the IP address or fully qualified domain name (FQDN) of the Telnet server.	
[:<port_int>]	If the Telnet server listens on a port number other than port 23, enter a colon (:) followed by the port number.	:23

## Example

This example tests the connection to an Telnet server at 192.168.1.10 on port 2323.

```
execute telnettest 192.168.1.10:2323
```

The CLI displays the following:

(using 192.168.1.20 to connect)

Remote Output(hex):

```
FF FD 18 FF FD 20 FF FD
```

```
23 FF FD 27
```

Connection Status:

Connecting to remote host succeeded.

## Related topics

[smtpstest on page 389](#)

[traceroute on page 391](#)

[ping on page 375](#)

[system dns on page 286](#)

## traceroute

Use this command to use ICMP to test the connection between the FortiMail unit and another network device, and display information about the time required for network hops between the device and the FortiMail unit.

## Syntax

```
execute traceroute {<fqdn_str> | <host_ipv4>}
```

Variable	Description	Default
traceroute {<fqdn_str>   <host_ipv4>}	Enter the IP address or fully qualified domain name (FQDN) of the host.	

## Example

This example tests connectivity between the FortiMail unit and <http://docs.fortinet.com>. In this example, the trace times out after the first hop, indicating a possible connectivity problem at that point in the network.

```
FortiMail# execute traceroute docs.fortinet.com
traceroute to docs.fortinet.com (65.39.139.196), 30 hops max, 38 byte packets
 1 172.16.1.200 (172.16.1.200) 0.324 ms 0.427 ms 0.360 ms
 2 * * *
```

## Example

This example tests the availability of a network route to the server example.com.

```
execute traceroute example.com
```

The CLI displays the following:

```
traceroute to example.com (192.168.1.10), 32 hops max, 72 byte packets
 1 172.16.1.2 0 ms 0 ms 0 ms
 2 10.10.10.1 <static.isp.example.net> 2 ms 1 ms 2 ms
 3 10.20.20.1 1 ms 5 ms 1 ms
 4 10.10.10.2 <core.isp.example.net> 171 ms 186 ms 14 ms
 5 10.30.30.1 <isp2.example.net> 10 ms 11 ms 10 ms
 6 10.40.40.1 73 ms 74 ms 75 ms
 7 192.168.1.1 79 ms 77 ms 79 ms
 8 192.168.1.2 73 ms 73 ms 79 ms
 9 192.168.1.10 73 ms 73 ms 79 ms
10 192.168.1.10 73 ms 73 ms 79 ms
```

## Example

This example attempts to test connectivity between the FortiMail unit and example.com. However, the FortiMail unit could not trace the route, because the primary or secondary DNS server that the FortiMail unit is configured to query could not resolve the FQDN example.com into an IP address, and it therefore did not know to which IP address it should connect. As a result, an error message is displayed.

```
FortiMail# execute traceroute example.com
traceroute: unknown host example.com
Command fail. Return code 1
```

To resolve the error message in order to perform connectivity testing, the administrator would first configure the FortiMail unit with the IP addresses of DNS servers that are able to resolve the FQDN example.com. For details, see [system dns on page 286](#).

## Related topics

[smtpstest on page 389](#)

[telnettest on page 390](#)

[ping on page 375](#)

[ping-option on page 376](#)

[system dns on page 286](#)

## update

Use this command to manually request updates to the FortiGuard Antivirus and FortiGuard Antispam engine and definitions from the FortiGuard Distribution Network (FDN).

You can alternatively or additionally configure scheduled updates and push updates. For details, see [system fortiguard antivirus on page 293](#) and [system fortiguard antispam on page 295](#).

## Syntax

```
execute update {as | av | now}
```

## Related topics

[system fortiguard antivirus on page 293](#)

[system fortiguard antispam on page 295](#)

## user-config

Use this command to generate a file with the latest user-specific configurations, such as user preferences, personal block/safelists, and secondary addresses, to the user configuration file, so that you will have the latest configuration when you make a configuration backup using [backup on page 350](#).

## Syntax

```
execute user-config generate
execute user-config getinfo
```

Variable	Description	Default
generate	Updates the user configuration file with the latest user-specific configuration.	
getinfo	Displays the time stamp when the last configuration file update was performed.	

## Related topics

[backup on page 350](#)

## vm

Use this command to upload a VM license.

## Syntax

```
execute vm license tftp <license_file_name> <tftp_server_ip>
```

Variable	Description	Default
<license_file_name> <tftp_server_ip>	Specify the license file name and the TFTP server IP address.	

# get

get commands display a part of your FortiMail unit's configuration in the form of a list of settings and their values.

Unlike show, get displays **all** settings, even if they are still in their default state.

For example, you might get the current DNS settings:

```
FortiMail# get system dns
primary : 172.16.95.19
secondary : 0.0.0.0
private-ip-query : enable
cache : enable
```

Notice that the command displays the setting for the secondary DNS server, even though it has not been configured, or has been reverted to its default value.

Also unlike show, unless used from within an object or table, get requires that you specify the object or table whose settings you want to display.

For example, at the root prompt, this command would be valid:

```
FortiMail# get system dns
```

and this command would not:

```
FortiMail# get
```

Depending on whether or not you have specified an object, like show, get may display one of two different outputs: either the configuration that you have just entered but not yet saved, or the configuration as it currently exists on the disk, respectively.

For example, immediately after configuring the secondary DNS server setting but **before** saving it, get displays two different outputs (differences highlighted in bold):

```
FortiMail# config system dns
(dns)# set secondary 192.168.1.10
(dns)# get
primary : 172.16.95.19
secondary : 192.168.1.10
private-ip-query : enable
cache : enable
(dns)# get system dns
primary : 172.16.95.19
secondary : 0.0.0.0
private-ip-query : enable
cache : enable
```

The first output from get indicates the value that you have configured but not yet saved; the second output from get indicates the value that was last saved to disk.

If you were to now enter end, saving your setting to disk, get output for both syntactical forms would again match. However, if you were to enter abort at this point and discard your recently entered secondary DNS setting instead of saving it to disk, the FortiMail unit's configuration would therefore match the second output, not the first.



If you have entered settings but cannot remember how they differ from the existing configuration, the two different forms of `get`, with and without the object name, can be a useful way to remind yourself.

---

Most `get` commands, such as `get system dns`, are used to display configured settings. You can find relevant information about such commands in the corresponding `config` commands in the `config` chapter.

Other `get` commands, such as [system performance on page 396](#), are used to display system information that is **not** configurable. This chapter describes this type of `get` command.

This chapter describes the following commands:

[system performance on page 396](#)

[system status on page 397](#)

---



Although not explicitly shown in this section, for all `config` commands, there are related `get` and `show & show full-configuration` commands which display that part of the configuration. `get` and `show` commands use the same syntax as their related `config` command, unless otherwise mentioned. For syntax examples and descriptions of each configuration object, field, and option, see [config on page 40](#).

---

## system performance

Displays the FortiMail unit's CPU usage, memory usage, system load, and up time.

### Syntax

```
get system performance
```

### Example

```
FortiMail# get system performance
CPU usage: 0% used, 100% idle
Memory usage: 17% used
System Load: 5
Uptime: 0 days, 8 hours, 24 minutes.
```

### Related topics

[system status on page 397](#)

## system status

Use this command to display FortiMail system status information including:

- firmware version, build number and date
- antivirus definition version and release date and time
- FortiMail unit serial number and BIOS version
- log hard disk availability
- mailbox disk availability
- host name
- operation mode
- distribution scope
- branching point (same as firmware build number)
- release version
- certificate bundle
- system time

## Syntax

```
get system status
```

## Example

```
Version: FortiMail-VM-KVM v7.0.1(GA), build159, 2021.08.31
Architecture: 64-bit
Serial-Number: FEVMxxxxxxxxxxxxx
BIOS version: n/a
VM Registration: Valid: License has been authorized
VM License File: License file and resources are valid
VM Resources: 1 CPU/8 allowed, 3952 MB RAM, 4096 MB maximum, 1048576 MB allowed, 249 GB Disk/8192 GB
              allowed
Log disk: Capacity 49 GB, Used 1220 MB (2.41%), Free 48 GB
Mailbox disk: Capacity 198 GB, Used 408 MB (0.21%), Free 197 GB
Filesystem mode: Read-Write
Hostname: FEVM08000216197
Operation mode: Server
HA configured mode: Off
HA effective mode: Off
FIPS-CC status: disabled
Strong-crypto: enabled
Distribution: International
Branch point: 159
Virus DB: 88.00819(2021-09-02 08:39)
Extended DB: Disabled
Extreme DB: Disabled
AntiSpam DB: 7.00453(2021-08-30 20:47)
GeoIP DB: 2.00088(2021-07-20 21:29)
```

get

---

Certificate Bundle: 1.00026(2021-05-25 11:30)  
Uptime: 0 days 22 hours 42 minutes  
Last reboot: Wed Sep 01 12:21:59 PDT 2021  
System time: Thu Sep 02 11:04:31 PDT 2021

## Related topics

[system performance on page 396](#)

# show & show full-configuration

The show commands display a part of your FortiMail unit's configuration in the form of commands that are required to achieve that configuration from the firmware's default state.



Although not explicitly shown in this section, for all `config` commands, there are related `get` and `show` commands which display that part of the configuration. `get` and `show` commands use the same syntax as their related `config` command, unless otherwise mentioned. For syntax examples and descriptions of each configuration object, field, and option, see the `config` chapters.

Unlike `get`, `show` does **not** display settings that are assumed to remain in their default state.

For example, you might show the current DNS settings:

```
FortiMail# show system dns
config system dns
  set primary 172.16.1.10
end
```

Notice that the command does **not** display the setting for the secondary DNS server. This indicates that it has not been configured, or has reverted to its default value.

Exceptions include `show full-configuration` commands. This displays the full configuration, **including** the default settings, similar to `get` commands. However, `show full-configuration` output uses configuration file syntax, while `get` commands do not.

For example, you might show the current DNS settings, **including** settings that remain at their default values (differences highlighted in bold):

```
FortiMail# show full-configuration system dns
config system dns
  set primary 172.16.1.10
  set secondary 172.16.1.11
  set private-ip-query disable
  set cache enable
end
```

Depending on whether or not you have specified an object, like `get`, `show` may display one of two different outputs: either the configuration that you have just entered but not yet saved, or the configuration as it currently exists on the disk, respectively.

For example, immediately after configuring the secondary DNS server setting but **before** saving it, `show` displays two different outputs (differences highlighted in bold):

```
FortiMail# config system dns
FortiMail (dns)# set secondary 192.168.1.10
FortiMail (dns)# show
config system dns
  set primary 172.16.1.10
  set secondary 192.168.1.10
  set private-ip-query enable
  set cache enable
end
```

```
FortiMail (dns)# show system dns
config system dns
  set primary 172.16.1.10
end
```

The first output from show indicates the value that you have configured but not yet saved; the second output from show indicates the value that was last saved to disk.



If you have entered settings but cannot remember how they differ from the existing configuration, the two different forms of show, with and without the object name, can be a useful way to remind yourself.

---

If you were to now enter end, saving your setting to disk, show output for both syntactical forms would again match. However, if you were to enter abort at this point and discard your recently entered secondary DNS setting instead of saving it to disk, the FortiMail unit's configuration would therefore match the second output, not the first.



[www.fortinet.com](http://www.fortinet.com)

Copyright© 2025 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's Chief Legal Officer, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.