

FortiGate® FortiOS V7.6.4 Feature/Platform Matrix



	FG/FWF-40F Series	FG/FWF-50G Series	FG/FWF-60E Series	FG/FWF-60F Series	FG-70F Series	FG/FWF-70G Series	FG-80E Series	FG-80F Series	FG-90E Series	FG-90G Series	FG-140E Series	FG-100F Series	FG-120G Series
Systems													
VDOM Support	•	• (5 max)	•	•	•	•	•	•	•	•	•	•	•
Dedicate CPU for Management Tasks	•	•		•	•	•		•		•		•	•
IPMI Sensors													
FortiDeploy Support	•	•	•	•	•	•	•	•	•	•	•	•	•
FortiCarrier License Upgrade													
Networking													
Virtual VLAN Switch	•	•		•	•	•		•		•	•	•	•
Virtual Hardware Switch	•	•	•	•	•	•	•	•	•	•	•	•	•
ACL Offload to Switch											•	•	•
WAN Optimization, Web Caching	N/A	51F: Disk Option Toggle	N/A	N/A	71F: Disk Option Toggle	71G: Disk Option Toggle	N/A	81F: Disk Option Toggle	N/A	91G: Disk Option Toggle	101E: Disk Option Toggle	101F: Disk Option Toggle	121F: Disk Option Toggle
Max Explicit Proxy User Number	N/A	N/A	N/A	N/A	1,000	1,000	N/A	1,000	N/A	1,000	12,000	12,000	12,000
UTM													
AV Quarantine	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI
AV Extreme DB													
nTurbo Acceleration	•	•	•	•	•	•	•	•		•	•	•	•
DoS Protection	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	•	•
Syn Proxy with NP													
DLP Fingerprinting				61F	71F	71G		81F		91G		101F	121G
Proxy-Based													
Zero Trust Network Access (ZTNA)					•	•		•		•	•	•	•
UTM profile with proxy-based inspection mode					•	•		•		•	•	•	•
Firewall policy with proxy-based inspection mode					•	•		•		•	•	•	•
Explicit and transparent proxies					•	•		•		•	•	•	•
Virtual server load balance					•	•		•		•	•	•	•
Proxy-only UTM profiles- Video Filter, Inline CASB, ICAP, WAF, SSH Filter					•	•		•		•	•	•	•
VPN													
L2TP client	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI
SSL VPN					•			•			•	•	•
Log & Reporting													
Disk Logging		51G	61E	61F	71F	71G	81E	81F	91E	91G	101E	101F	121G
FortiView Historical Data		51G: 1 hour	61E: 1 hour	61F: 1 hour	71F: 1 hour	71G: 1 hour	81E: 1 hour	81F: 1 hour	91E: 1 hour	91G: 1 hour	101E: 24 hours	101F: 24 hours	121G: 24 hours

^ Doesn't support Mesh
Requires local storage

** Default 24 Hours, extension enabled via CLI
*** Dual disks



	FG-200E Series	FG-200F Series	FG-200G Series	FG-300E Series	FG-400E Series	FG-400F Series	FG-500E Series	FG-600E Series	FG-600F Series	FG-800D	FG-900D	FG-900G Series	FG-1000D
Systems													
VDOM Support	•	•	•	•	•	•	•	•	•	•	•	•	•
Dedicate CPU for Management Tasks		•	•			•			•			•	•
IPMI Sensors				•	•	•	•	•	•	•	•	•	•
FortiDeploy Support	•	•	•	•	•	•	•	•	•	•	•		
FortiCarrier License Upgrade													
Networking													
Virtual VLAN Switch		•	•	•	•	•			•			•	
Virtual Hardware Switch		•	•	•	•	•			•			•	
ACL Offload to ISF		•	•	•	•	•	•	•	•			•	
WAN Optimization, Web Caching	201E: Disk Option Toggle	201F: Disk Option Toggle	201G: Disk Option Toggle	• ***	• ***	• ***	• ***	• ***	• ***	Disk Option Toggle	Disk Option Toggle	• ***	Disk Option Toggle
Max Explicit Proxy User Number	12,000	12,000	12,000	12,000	12,000	12,000	12,000	12,000	12,000	12,000	12,000	32,000	32,000
UTM													
AV Quarantine	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI
AV Extreme DB			•	•	•	•	•	•	•	•	•	•	•
nTurbo Acceleration		•	•	•	•	•	•	•	•	•	•	•	•
DoS Protection	•	•	•	•	•	•	•	•	•	•	•	•	•
Syn Proxy with NP				•	•	•	•	•					
DLP Fingerprinting	201E	201F	201G	301E	401E	401F	501E	601E	601F	•	•	901G	•
Proxy-Based													
Zero Trust Network Access (ZTNA)	•	•	•	•	•	•	•	•	•	•	•	•	•
UTM profile with proxy-based inspection mode	•	•	•	•	•	•	•	•	•	•	•	•	•
Firewall policy with proxy-based inspection mode	•	•	•	•	•	•	•	•	•	•	•	•	•
Explicit and transparent proxies	•	•	•	•	•	•	•	•	•	•	•	•	•
Virtual server load balance	•	•	•	•	•	•	•	•	•	•	•	•	•
Proxy-only UTM profiles- Video Filter, Inline CASB, ICAP, WAF, SSH Filter	•	•	•	•	•	•	•	•	•	•	•	•	•
VPN													
L2TP client													
SSL VPN	•	•	•	•	•	•	•	•	•	•	•	•	•
Log & Reporting													
Disk Logging	201E	201F	201G	301E	401E	401F	501E	601E	601F	•	•	•	•
FortiView Historical Data	201E: 24 hours	201F: 24 hours	201G: 24 hours	301E: 24 hours	401E: 24 hours	401F: 24 hours	501E: 24 hours	601E: 24 hours	601F: 24 hours	24 hours	24 hours	24 hours	24 hours

[illegible]



	FG-3500F Series	FG-3600E	FG-3700D	FG-3700F Series	FG-3960E FG-3980E	FG-4200F FG-4400F	FG-4800F	FG-5001E Series	FG-6000F Series	FG-7000E Series	FG-7000F Series	FG-VM00	FG-VM01 to VMUL
Systems													
VDOM Support	•	•	•	•	•	•	•	•	•	•	•		•
Dedicate CPU for Management Tasks	•	•	•	•	•	•	•	•	•	•	•		
IPMI Sensors	•	•	•	•	•	•	•	•	•	•	•		
FortiDeploy Support												•	•
FortiCarrier License Upgrade	•	•	•	•	•	•	•	•	•	•	•	•	•
Networking													
Virtual VLAN Switch	•			•		•	•						
Virtual Hardware Switch	•			•		•	•						
ACL Offload to ISF	•	•	•	•	•	•	•	•	•	•	•		
WAN Optimization, Web Caching	• ***	• ***	• ***	• ***	• ***	• ***	• ***	5001E1:Disk Option Toggle				Disk Option Toggle / •	Disk Option Toggle / •
Max Explicit Proxy User Number	128,000	128,000	128,000	128,000	128,000	128,000	128,000	128,000	64,000	64,000	64,000	128,000	128,000
UTM													
AV Quarantine	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI	CLI
AV Extreme DB	•	•	•	•	•	•	•	•	•	•	•		•
nTurbo Acceleration	•	•	•	•	•	•	•	•	•	•	•		
DoS Protection	•	•	•	•	•	•	•	•	•	•	•	•	•
Syn Proxy with NP		•	•		•			•	•	•			
DLP Fingerprinting	3501F	3601E	•	3701F		4201/4401F	4801F	5001E1	•	•	•	•	•
Proxy-Based													
Zero Trust Network Access (ZTNA)	•	•	•	•	•	•	•	•	•	•	•	•	•
UTM profile with proxy-based inspection mode	•	•	•	•	•	•	•	•	•	•	•	•	•
Firewall policy with proxy-based inspection mode	•	•	•	•	•	•	•	•	•	•	•	•	•
Explicit and transparent proxies	•	•	•	•	•	•	•	•	•	•	•	•	•
Virtual server load balance	•	•	•	•	•	•	•	•	•	•	•	•	•
Proxy-only UTM profiles- Video Filter, Inline CASB, ICAP, WAF, SSH Filter	•	•	•	•	•	•	•	•	•	•	•	•	•
VPN													
L2TP client													
SSL VPN	•	•	•	•	•	•	•	•	•	•	•	•	•
Log & Reporting													
Disk Logging	•	•	•	•		•	•	5001E1	•	•	•	•	•
FortiView Historical Data	7 days **	7 days **	7 days **	7 days **		7 days **	7 days **	5001E1: 7 days **	7 days **	7 days **	7 days **	24 hours	24 hours

Copyright© 2025 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.