



# FortiAnalyzer - Dataset Reference

Version 6.4.1

**FORTINET DOCUMENT LIBRARY**

<https://docs.fortinet.com>

**FORTINET VIDEO GUIDE**

<https://video.fortinet.com>

**FORTINET BLOG**

<https://blog.fortinet.com>

**CUSTOMER SERVICE & SUPPORT**

<https://support.fortinet.com>

**FORTINET TRAINING & CERTIFICATION PROGRAM**

<https://www.fortinet.com/support-and-training/training.html>

**NSE INSTITUTE**

<https://training.fortinet.com>

**FORTIGUARD CENTER**

<https://fortiguard.com/>

**END USER LICENSE AGREEMENT**

<https://www.fortinet.com/doc/legal/EULA.pdf>

**FEEDBACK**

Email: [techdoc@fortinet.com](mailto:techdoc@fortinet.com)



June 15, 2020

FortiAnalyzer 6.4.1 Dataset Reference

05-641-622945-20200615

# TABLE OF CONTENTS

<b>Introduction</b> .....	<b>4</b>
Understanding datasets and macros .....	4
<b>Dataset Reference List</b> .....	<b>5</b>
<b>Macro Reference List</b> .....	<b>266</b>
<b>Change Log</b> .....	<b>269</b>

# Introduction

This document provides information about the various types of FortiAnalyzer datasets.

## Understanding datasets and macros

FortiAnalyzer datasets are collections of log messages from monitored devices.

Charts in FortiAnalyzer are generated based on the datasets. To create a chart, you can use the predefined datasets, or you can create your own custom datasets by querying the log messages in the SQL database on the FortiAnalyzer unit. Both predefined and custom datasets can be cloned, but only custom datasets can be deleted. You can also view the SQL query for a dataset, and test the query against specific devices or log arrays.

You can create custom reports that contain macros that are created based on predefined and custom datasets. Macros are used to dynamically display the device log data as text in a report. They can be embedded within a text field of a paragraph in a report layout in XML format. Macros display a single value, such as a user name, highest session count, or highest bandwidth, and so on.

For more information about how to create datasets, charts, and macros, see the *FortiAnalyzer Administration Guide*.

# Dataset Reference List

The following tables list the datasets included with FortiAnalyzer. The tables contain the name, SQL query syntax, and log category for each dataset.

Dataset Name	Description	Log Category
Traffic-Bandwidth-Summary-Day-Of-Month	Traffic bandwidth timeline	traffic

```
select
  $flex_timescale(timestamp) as horex,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in
from
  ###(select timestamp, sum(bandwidth) as bandwidth, sum(traffic_out) as traffic_out, sum
(traffic_in) as traffic_in from {{FGT_DATASET_BASE_TRAFFIC_BANDWIDTH_SESSION}} base_query
group by timestamp order by bandwidth desc)### t where $filter-drilldown group by horex having
sum(traffic_out+traffic_in)>0 order by horex
```

Dataset Name	Description	Log Category
Session-Summary-Day-Of-Month	Number of session timeline	traffic

```
select
  $flex_timescale(timestamp) as horex,
  sum(sessions) as sessions
from
  ###(select timestamp, sum(sessions) as sessions from {{FGT_DATASET_BASE_TRAFFIC_BANDWIDTH_
SESSION}} base_query group by timestamp order by sessions desc)### t where $filter-drilldown
group by horex order by horex
```

Dataset Name	Description	Log Category
Top-Users-By-Bandwidth	Bandwidth application top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
```

```

count(*) as sessions
from
$log
where
$filter
and (
logflag&1>0
)
group by
user_src
having
sum(
coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
)> 0
order by
bandwidth desc

```

Dataset Name	Description	Log Category
Top-App-By-Bandwidth	Top applications by bandwidth usage	traffic

```

select
app_group_name(app) as app_group,
sum(
coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
) as bandwidth,
sum(
coalesce(rcvdbyte, 0)
) as traffic_in,
sum(
coalesce(sentbyte, 0)
) as traffic_out,
count(*) as sessions
from
$log
where
$filter
and (
logflag&1>0
)
and nullifna(app) is not null
group by
app_group
having
sum(
coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
)> 0
order by
bandwidth desc

```

Dataset Name	Description	Log Category
Top-User-Source-By-Sessions	Top user source by session count	traffic

```

select
coalesce(

```

```

        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
group by
    user_src
order by
    sessions desc

```

Dataset Name	Description	Log Category
Top-App-By-Sessions	Top applications by session count	traffic

```

select
    app_group_name(app) as app_group,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(app) is not null
group by
    app_group
order by
    sessions desc

```

Dataset Name	Description	Log Category
Top-Destination-Addresses-By-Sessions	Top destinations by session count	traffic

```

select
    coalesce(
        nullifna(
            root_domain(hostname)
        ),
        ipstr(dstip)
    ) as domain,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )

```

## Dataset Reference List

```
)  
group by  
  domain  
order by  
  sessions desc
```

Dataset Name	Description	Log Category
Top-Destination-Addresses-By-Bandwidth	Top destinations by bandwidth usage	traffic

```
select  
  coalesce(  
    nullifna(  
      root_domain(hostname)  
    ),  
    ipstr(dstip)  
  ) as domain,  
  sum(  
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)  
  ) as bandwidth,  
  sum(  
    coalesce(rcvdbyte, 0)  
  ) as traffic_in,  
  sum(  
    coalesce(sentbyte, 0)  
  ) as traffic_out  
from  
  $log  
where  
  $filter  
  and (  
    logflag&1>0  
  )  
  and coalesce(  
    nullifna(  
      root_domain(hostname)  
    ),  
    ipstr(`dstip`)  
  ) is not null  
group by  
  domain  
having  
  sum(  
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)  
  ) > 0  
order by  
  bandwidth desc
```

Dataset Name	Description	Log Category
DHCP-Summary-By-Port	Event top dhcp summary	event

```
drop  
  table if exists rpt_tmptbl_1;  
drop
```



```

    table if exists rpt_tmptbl_2;
drop
    table if exists rpt_tmptbl_3; create temporary table rpt_tmptbl_1 as
select
    devintf,
    mac
from
    ###(select concat(interface, '.', devid) as devintf, mac from $log where $last3day_period
$filter and logid_to_int(logid) = 26001 and dhcp_msg = 'Ack' group by devintf, mac)### t group
by devintf, mac; create temporary table rpt_tmptbl_2 as select devintf, mac from ###(select
concat(interface, '.', devid) as devintf, mac from $log where $filter and logid_to_int(logid)
= 26001 and dhcp_msg = 'Ack' group by devintf, mac)### t group by devintf, mac; create tem-
porary table rpt_tmptbl_3 as select distinct on (1) devintf, cast(used*100.0/total as decimal
(18,2)) as percent_of_allocated_ip from ###(select distinct on (devintf) concat(interface,
'.', devid) as devintf, used, total, itime from $log where $filter and logid_to_int(logid)-
)=26003 and total>0 /*SkipSTART*/order by devintf, itime desc/*SkipEND*/)### t order by dev-
intf, itime desc; select t1.devintf as interface, percent_of_allocated_ip, new_cli_count from
rpt_tmptbl_3 t1 inner join (select devintf, count(mac) as new_cli_count from rpt_tmptbl_2
where not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.mac=rpt_tmptbl_1.mac) group by
devintf) t2 on t1.devintf=t2.devintf order by interface, percent_of_allocated_ip desc

```

Dataset Name	Description	Log Category
Top-Wifi-Client-By-Bandwidth	Traffic top WiFi client by bandwidth usage	traffic

```

select
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    srcssid,
    get_devtype(srcswversion, osname, devtype) as devtype_new,
    coalesce(
        nullifna(`srcname`),
        `srcmac`
    ) as hostname_mac,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and (
        srcssid is not null
        or dstssid is not null
    )
group by
    user_src,
    srcssid,
    devtype_new,
    hostname_mac

```

```

having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Traffic-History-By-Active-User	Traffic history by active user	traffic

```

select
  $flex_timescale(timestamp) as hodex,
  count(
    distinct(user_src)
  ) as total_user
from
  ###(select timestamp, user_src, sum(sessions) as sessions from {{FGT_DATASET_BASE_TRAFFIC_
  BANDWIDTH_SESSION}} base_query group by timestamp, user_src order by sessions desc)### t where
  $filter-drilldown group by hodex order by hodex

```

Dataset Name	Description	Log Category
Top-Allowed-Websites-By-Requests	UTM top allowed web sites by request	traffic

```

select
  hostname,
  catdesc,
  count(*) as requests
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and utmevent in (
    'webfilter', 'banned-word', 'web-content',
    'command-block', 'script-filter'
  )
  and hostname is not null
  and (
    utmaction not in ('block', 'blocked')
    or action != 'deny'
  )
group by
  hostname,
  catdesc
order by
  requests desc

```

Dataset Name	Description	Log Category
Top-50-Websites-By-Bandwidth	Webfilter top allowed web sites by bandwidth usage	webfilter

```

select
    domain,
    string_agg(distinct catdesc, ', ') as agg_catdesc,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
    ###(select coalesce(nullifna(hostname), ipstr('dstip`)) as domain, catdesc, sum(coalesce
    (sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in,
    sum(coalesce(sentbyte, 0)) as traffic_out from $log-traffic where $filter and (logflag&1>0)
    and utmaction!='blocked' and (countweb>0 or ((logver is null or logver<502000000) and (host-
    name is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block',
    'script-filter')))) group by domain, catdesc having sum(coalesce(sentbyte, 0)+coalesce(rcvd-
    byte, 0))>0 /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t group by domain, catdesc
    order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Blocked-Websites	UTM top blocked web sites by request	traffic

```

select
    hostname,
    count(*) as requests
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and utmevent in (
        'webfilter', 'banned-word', 'web-content',
        'command-block', 'script-filter'
    )
    and hostname is not null
    and (
        utmaction in ('block', 'blocked')
        or action = 'deny'
    )
group by
    hostname
order by
    requests desc

```

Dataset Name	Description	Log Category
Top-Web-Users-By-Request	UTM top web users by request	traffic

```

select
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    get_devtype(srcswversion, osname, devtype) as devtype_new,
    srcname,

```

```

count(*) as requests
from
$log
where
$filter
and (
logflag&1>0
)
and utmevent in (
'webfilter', 'banned-word', 'web-content',
'command-block', 'script-filter'
)
group by
user_src,
devtype_new,
srcname
order by
requests desc

```

Dataset Name	Description	Log Category
Top-Allowed-WebSites-By-Bandwidth	UTM top allowed websites by bandwidth usage	traffic

```

select
appid,
hostname,
catdesc,
sum(
coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
) as bandwidth,
sum(
coalesce(rcvdbyte, 0)
) as traffic_in,
sum(
coalesce(sentbyte, 0)
) as traffic_out
from
$log
where
$filter
and (
logflag&1>0
)
and utmevent in (
'webfilter', 'banned-word', 'web-content',
'command-block', 'script-filter'
)
and hostname is not null
group by
appid,
hostname,
catdesc
having
sum(
coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
)& gt; 0

```

```
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
Top-Blocked-Web-Users	UTM top blocked web users	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  get_devtype(srcswversion, osname, devtype) as devtype_new,
  srcname,
  count(*) as requests
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and utmevent in (
    'webfilter', 'banned-word', 'web-content',
    'command-block', 'script-filter'
  )
  and (
    utmaction in ('block', 'blocked')
    or action = 'deny'
  )
group by
  user_src,
  devtype_new,
  srcname
order by
  requests desc
```

Dataset Name	Description	Log Category
Top-20-Web-Users-By-Bandwidth	Webfilter top web users by bandwidth usage	webfilter

```
select
  user_src,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as
  traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out from $log-traffic where $filter and (log-
  flag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (hostname is not null
  or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-fil-
  ter')))) group by user_src having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0
/*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t group by user_src order by bandwidth
desc
```

Dataset Name	Description	Log Category
Top-Web-Users-By-Bandwidth	UTM top web users by bandwidth usage	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  get_devtype(srcswversion, osname, devtype) as devtype_new,
  srcname,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and utmevent in (
    'webfilter', 'banned-word', 'web-content',
    'command-block', 'script-filter'
  )
group by
  user_src,
  devtype_new,
  srcname
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) > 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-Video-Streaming-Websites-By-Bandwidth	UTM top video streaming websites by bandwidth usage	traffic

```

select
  appid,
  hostname,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in

```

```

    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and catdesc in ('Streaming Media and Download')
group by
    appid,
    hostname
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
Top-Email-Senders-By-Count	Default top email senders by count	traffic

```

select
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    count(*) as requests
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and service in (
        'smtp', 'SMTP', '25/tcp', '587/tcp',
        'smtps', 'SMTPS', '465/tcp'
    )
group by
    user_src
order by
    requests desc

```

Dataset Name	Description	Log Category
Top-Email-Receivers-By-Count	Default email top receivers by count	traffic

```

select
    coalesce(
        nullifna(`user`),

```

```

        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    count(*) as requests
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and service in (
        'pop3', 'POP3', '110/tcp', 'imap',
        'IMAP', '143/tcp', 'imaps', 'IMAPS',
        '993/tcp', 'pop3s', 'POP3S', '995/tcp'
    )
group by
    user_src
order by
    requests desc

```

Dataset Name	Description	Log Category
Top-Email-Senders-By-Bandwidth	Default email top senders by bandwidth usage	traffic

```

select
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and service in (
        'smtp', 'SMTP', '25/tcp', '587/tcp',
        'smtps', 'SMTPS', '465/tcp'
    )
group by
    user_src
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) > 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
Top-Email-Receivers-By-Bandwidth	Default email top receivers by bandwidth usage	traffic



```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and service in (
    'pop3', 'POP3', '110/tcp', 'imap',
    'IMAP', '143/tcp', 'imaps', 'IMAPS',
    '993/tcp', 'pop3s', 'POP3S', '995/tcp'
  )
group by
  user_src
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-Malware-By-Name	UTM top virus	virus

```

select
  virus,
  max(virusid_s) as virusid,
  (
    case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then 'Adware'
  else 'Virus' end
  ) as malware_type,
  sum(totalnum) as totalnum
from
  ###(select virus, virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from
  $log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not
  null group by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by
  virus, malware_type order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Virus-By-Name	UTM top virus	virus

```

select
  virus,
  max(virusid_s) as virusid,
  (

```

```

        case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then 'Adware'
else 'Virus' end
    ) as malware_type,
    sum(totalnum) as totalnum
from
    ###(select virus, virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from
$log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not
null group by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by
virus, malware_type order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Virus-Victim	UTM top virus user	virus

```

select
    user_src,
    sum(totalnum) as totalnum
from
    ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as totalnum from
$log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not
null group by user_src /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by user_src
order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Attack-Source	UTM top attack source	attack

```

select
    coalesce(
        nullifna(`user`),
        ipstr(`srcip`)
    ) as user_src,
    count(*) as totalnum
from
    $log
where
    $filter
group by
    user_src
order by
    totalnum desc

```

Dataset Name	Description	Log Category
Top-Attack-Victim	UTM top attack dest	attack

```

select
    dstip,
    count(*) as totalnum
from
    $log
where
    $filter
    and dstip is not null
group by
    dstip

```

```
order by
  totalnum desc
```

Dataset Name	Description	Log Category
Top-Static-IPSEC-Tunnels-By-Bandwidth	Top static IPsec tunnels by bandwidth usage	event

```
select
  vpn_name,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      tunnelid,
      vpn_name,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
      ) as traffic_in,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
      ) as traffic_out,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
      ) as bandwidth
    from
      ###({{FGT_DATASET_EVENT_VPN_IPSEC_TUNNEL_BANDWIDTH}})### t where (tunnelip is null or
tunnelip='0.0.0.0') group by devid, vd, remip, vpn_name, tunnelid) tt group by vpn_name having
sum(traffic_in+traffic_out)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-SSL-VPN-Tunnel-Users-By-Bandwidth	Top SSL VPN tunnel users by bandwidth usage	event

```
select
  user_src,
  remip as remote_ip,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
```

```

    vd,
    remip,
    user_src,
    tunnelid,
    min(s_time) as s_time,
    max(e_time) as e_time,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
    ) as bandwidth,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
    ) as traffic_in,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
    ) as traffic_out
from
    ###({{FGT_DATASE_EVENT_SSL_VPN_TUNNEL_USERS}})### t where tunneltype='ssl-tunnel' group
by devid, vd, user_src, remip, tunnelid) tt where bandwidth>0 group by user_src, remote_ip
order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Tunnels-By-Bandwidth	Top dial up IPsec tunnels by bandwidth usage	event

```

select
    vpn_name,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
    (
        select
            devid,
            vd,
            tunnelid,
            remip,
            vpn_name,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
            ) as traffic_in,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
            ) as traffic_out,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
            ) as bandwidth
        from
            ###({{FGT_DATASET_EVENT_VPN_DIAL_UP_IPSEC_TUNNELS}})### t where not (tunnelip is null or

```

```
tunnelid='0.0.0.0') group by devid, vd, remip, vpn_name, tunnelid) tt group by vpn_name having
sum(traffic_out+traffic_in)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Users-By-Bandwidth	Top dial up IPsec users by bandwidth usage	event

```
select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as user_src,
  remip,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
      string_agg(distinct user_agg, ' ') as user_agg,
      remip,
      tunnelid,
      min(s_time) as s_time,
      max(e_time) as e_time,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
      ) as bandwidth,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
      ) as traffic_in,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
      ) as traffic_out
    from
      ###({{FGT_DATASET_EVENT_VPN_DIAL_UP_IPSEC_BANDWIDTH}})### t group by devid, vd, remip,
tunnelid) tt where bandwidth>0 group by user_src, remip order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Dial-Up-IPSEC-Users-By-Duration	Top dial up IPsec users by duration	event

```
select
  coalesce(
    xauthuser_agg,
    user_agg,
```

```

        ipstr(`remip`)
    ) as user_src,
    from_dtime(
        min(s_time)
    ) as start_time,
    sum(duration) as duration,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
(
    select
        devid,
        vd,
        remip,
        string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
        string_agg(distinct user_agg, ' ') as user_agg,
        tunnelid,
        min(s_time) as s_time,
        max(e_time) as e_time,
        (
            case when min(s_time)= max(e_time) then max(max_duration) else max(max_duration)- min
(min_duration) end
        ) as duration,
        (
            case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
        ) as bandwidth,
        (
            case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
        ) as traffic_in,
        (
            case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
        ) as traffic_out
    from
        ###({{FGT_DATASET_EVENT_VPN_DIAL_UP_IPSEC_BANDWIDTH}})### t group by devid, vd, remip,
        tunnelid) tt where bandwidth>0 group by user_src order by duration desc

```

Dataset Name	Description	Log Category
Top-SSL-VPN-Web-Mode-Users-By-Bandwidth	Top SSL VPN web mode users by bandwidth usage	event

```

select
    user_src,
    remip as remote_ip,
    from_dtime(
        min(s_time)
    ) as start_time,
    sum(bandwidth) as bandwidth,
    sum(traffic_in) as traffic_in,
    sum(traffic_out) as traffic_out
from
(

```

```

select
    devid,
    vd,
    user_src,
    remip,
    tunnelid,
    min(s_time) as s_time,
    max(e_time) as e_time,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
    ) as bandwidth,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
    ) as traffic_in,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
    ) as traffic_out
from
    ###({{FGT_DATASE_EVENT_SSL_VPN_TUNNEL_USERS}})### t group by devid, vd, user_src, remip,
tunnelid) tt where bandwidth>0 group by user_src, remote_ip order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-SSL-VPN-Web-Mode-Users-By-Duration	Top SSL VPN web mode users by duration	event

```

select
    user_src,
    remip as remote_ip,
    from_dtime(
        min(s_time)
    ) as start_time,
    (
        max(e_time)- min(s_time)
    ) as duration
from
    (
        select
            devid,
            vd,
            user_src,
            remip,
            tunnelid,
            min(s_time) as s_time,
            max(e_time) as e_time
        from
            ###({{FGT_DATASE_EVENT_SSL_VPN_TUNNEL_USERS}})### t where tunneltype='ssl-web' group by
devid, vd, user_src, remip, tunnelid) tt group by user_src, remote_ip order by duration desc

```

Dataset Name	Description	Log Category
Top-SSL-VPN-Users-By-Duration	Top SSL VPN users by duration	event

```

select
  user_src,
  tunneltype,
  sum(duration) as duration,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      remip,
      user_src,
      tunneltype,
      tunnelid,
      (
        case when min(s_time)= max(e_time) then max(max_duration) else max(max_duration)- min
(min_duration) end
      ) as duration,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
      ) as traffic_in,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
      ) as traffic_out,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
      ) as bandwidth
    from
      ###({{FGT_DATASE_EVENT_SSL_VPN_TUNNEL_USERS}})### t group by devid, vd, remip, user_src,
tunnelid, tunneltype) tt where bandwidth>0 group by user_src, tunneltype order by duration
desc

```

Dataset Name	Description	Log Category
vpn-Top-Dial-Up-VPN-Users-By-Duration	Top dial up VPN users by duration	event

```

select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as user_src,
  t_type as tunneltype,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(duration) as duration,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out

```



```

from
(
  select
    devid,
    vd,
    remip,
    string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
    string_agg(distinct user_agg, ' ') as user_agg,
    t_type,
    tunnelid,
    min(s_time) as s_time,
    max(e_time) as e_time,
    (
      case when min(s_time)= max(e_time) then max(max_duration) else max(max_duration)- min
(min_duration) end
    ) as duration,
    (
      case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
    ) as bandwidth,
    (
      case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
    ) as traffic_in,
    (
      case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
    ) as traffic_out
  from
    ###({{FGT_DATASET_EVENT_VPN_DIAL_UP_IPSEC_USERS}})### t where (t_type like 'ssl%' or (t_
type like 'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0'))) group by devid, vd,
    remip, t_type, tunnelid) tt where bandwidth>0 group by user_src, tunneltype order by duration
    desc

```

Dataset Name	Description	Log Category
vpn-User-Login-history	VPN user login history	event

```

select
  $flex_timescale(timestamp) as hodex,
  sum(total_num) as total_num
from
(
  select
    timestamp,
    devid,
    vd,
    remip,
    tunnelid,
    sum(tunnelup) as total_num,
    max(traffic_in) as traffic_in,
    max(traffic_out) as traffic_out
  from
    ###(select $flex_timestamp as timestamp, devid, vd, remip, tunnelid, (case when action=
'tunnel-up' then 1 else 0 end) as tunnelup, max(coalesce(sentbyte, 0)) as traffic_out, max
(coalesce(rcvbyte, 0)) as traffic_in from $log where $filter and subtype='vpn' and

```

(tunneltype like 'ipsec%' or tunneltype like 'ssl%') and action in ('tunnel-up', 'tunnel-stats', 'tunnel-down') and tunnelid is not null group by timestamp, action, devid, vd, remip, tunnelid /\*SkipSTART\*/order by timestamp desc/\*SkipEND\*/)### t group by timestamp, devid, vd, remip, tunnelid having max(tunnelup) > 0 and max(traffic\_in)+max(traffic\_out)>0) t group by hodec order by total\_num desc

Dataset Name	Description	Log Category
vpn-Failed-Login-Attempts	VPN failed logins	event

```
select
    f_user,
    tunneltype,
    sum(total_num) as total_num
from
    ###(select coalesce(nullifna(`xauthuser`), `user`) as f_user, tunneltype, count(*) as total_
num from $log where $filter and subtype='vpn' and (tunneltype='ipsec' or left(tunneltype,
3)='ssl') and action in ('ssl-login-fail', 'ipsec-login-fail') and coalesce(nullifna(`xau-
thuser`), nullifna(`user`)) is not null group by f_user, tunneltype)### t group by f_user, tun-
neltype order by total_num desc
```

Dataset Name	Description	Log Category
vpn-Authenticated-Logins	VPN authenticated logins	event

```
select
    coalesce(
        xauthuser_agg,
        user_agg,
        ipstr(`remip`)
    ) as f_user,
    t_type as tunneltype,
    from_dtime(
        min(s_time)
    ) as start_time,
    sum(total_num) as total_num,
    sum(duration) as duration
from
    (
        select
            string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
            string_agg(distinct user_agg, ' ') as user_agg,
            t_type,
            devid,
            vd,
            remip,
            tunnelid,
            min(s_time) as s_time,
            max(e_time) as e_time,
            (
                case when min(s_time)= max(e_time) then max(max_duration) else max(max_duration)- min
(min_duration) end
            ) as duration,
            (
                case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
```

```

    ) as bandwidth,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
    ) as traffic_in,
    (
        case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
    ) as traffic_out,
    sum(tunnelup) as total_num
from
    ###({{FGT_DATASET_EVENT_VPN_DIAL_UP_IPSEC_USERS}})### t group by t_type, devid, vd,
remip, tunnelid having max(tunnelup) > 0) tt where bandwidth>0 group by f_user, tunneltype
order by total_num desc

```

Dataset Name	Description	Log Category
vpn-Traffic-Usage-Trend-VPN-Summary	VPN traffic usage trend	event

```

select
    hodex,
    sum(ssl_traffic_bandwidth) as ssl_bandwidth,
    sum(ipsec_traffic_bandwidth) as ipsec_bandwidth
from
    (
        select
            $flex_timescale(timestamp) as hodex,
            devid,
            vd,
            remip,
            tunnelid,
            (
                case when t_type like 'ssl%' then (
                    case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out)
else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
                ) else 0 end
            ) as ssl_traffic_bandwidth,
            (
                case when t_type like 'ipsec%' then (
                    case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out)
else max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
                ) else 0 end
            ) as ipsec_traffic_bandwidth,
            min(s_time) as s_time,
            max(e_time) as e_time
        from
            ###({{FGT_DATASET_EVENT_VPN_TRAFFIC_USAGE}})### t group by hodex, devid, t_type, vd,
remip, tunnelid) tt group by hodex order by hodex

```

Dataset Name	Description	Log Category
Top-S2S-IPSEC-Tunnels-By-Bandwidth-and-Availability	Top S2S IPsec tunnels by bandwidth usage and avail	event

```

select
    vpntunnel,
    tunneltype,
    sum(traffic_out) as traffic_out,
    sum(traffic_in) as traffic_in,
    sum(bandwidth) as bandwidth,
    sum(uptime) as uptime
from
    (
        select
            vpntunnel,
            tunneltype,
            tunnelid,
            devid,
            vd,
            sum(sent_end - sent_beg) as traffic_out,
            sum(rcvd_end - rcvd_beg) as traffic_in,
            sum(
                sent_end - sent_beg + rcvd_end - rcvd_beg
            ) as bandwidth,
            sum(duration_end - duration_beg) as uptime
        from
            ###(select tunnelid, tunneltype, vpntunnel, devid, vd, min(coalesce(sentbyte, 0)) as
sent_beg, max(coalesce(sentbyte, 0)) as sent_end, min(coalesce(rcvdbyte, 0)) as rcvd_beg, max
(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce(duration, 0)) as duration_beg, max(coalesce
(duration, 0)) as duration_end from $log where $filter and subtype='vpn' and action='tunnel-
stats' and tunneltype like 'ipsec%' and (tunnelip is null or tunnelip='0.0.0.0') and nullifna
('user') is null and tunnelid is not null and tunnelid!=0 group by tunnelid, tunneltype, vpn-
tunnel, devid, vd /*SkipSTART*/order by tunnelid/*SkipEND*/)### t group by vpntunnel, tun-
neltype, tunnelid, devid, vd order by bandwidth desc) t where bandwidth>0 group by vpntunnel,
tunneltype order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-Dialup-IPSEC-By-Bandwidth-and-Availability	Top dialup IPsec users by bandwidth usage and avail	event

```

select
    user_src,
    remip,
    sum(traffic_out) as traffic_out,
    sum(traffic_in) as traffic_in,
    sum(bandwidth) as bandwidth,
    sum(uptime) as uptime
from
    (
        select
            user_src,
            remip,
            tunnelid,
            devid,
            vd,
            sum(sent_end - sent_beg) as traffic_out,
            sum(rcvd_end - rcvd_beg) as traffic_in,
            sum(
                sent_end - sent_beg + rcvd_end - rcvd_beg
            ) as bandwidth,
            sum(duration_end - duration_beg) as uptime
        from
            ###(select tunnelid, tunneltype, vpntunnel, devid, vd, min(coalesce(sentbyte, 0)) as
sent_beg, max(coalesce(sentbyte, 0)) as sent_end, min(coalesce(rcvdbyte, 0)) as rcvd_beg, max
(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce(duration, 0)) as duration_beg, max(coalesce
(duration, 0)) as duration_end from $log where $filter and subtype='vpn' and action='tunnel-
stats' and tunneltype like 'ipsec%' and (tunnelip is null or tunnelip='0.0.0.0') and nullifna
('user') is null and tunnelid is not null and tunnelid!=0 group by tunnelid, tunneltype, vpn-
tunnel, devid, vd /*SkipSTART*/order by tunnelid/*SkipEND*/)### t group by vpntunnel, tun-
neltype, tunnelid, devid, vd order by bandwidth desc) t where bandwidth>0 group by vpntunnel,
tunneltype order by bandwidth desc

```

```

    ) as bandwidth,
    sum(duration_end - duration_beg) as uptime
from
    ###(select tunnelid, coalesce(nullifna(`xauthuser`), nullifna(`user`), ipstr(`remip`))
as user_src, remip, devid, vd, min(coalesce(sentbyte, 0)) as sent_beg, max(coalesce(sentbyte,
0)) as sent_end, min(coalesce(rcvdbyte, 0)) as rcvd_beg, max(coalesce(rcvdbyte, 0)) as rcvd_
end, min(coalesce(duration, 0)) as duration_beg, max(coalesce(duration, 0)) as duration_end
from $log where $filter and subtype='vpn' and action='tunnel-stats' and tunneltype like
'ipsec%' and not (tunnelip is null or tunnelip='0.0.0.0') and tunnelid is not null and tun-
nelid!=0 group by tunnelid, user_src, remip, devid, vd /*SkipSTART*/order by tun-
nelid/*SkipEND*/)### t group by user_src, remip, tunnelid, devid, vd order by bandwidth desc)
t where bandwidth>0 group by user_src, remip order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-SSL-Tunnel-Mode-By-Bandwidth-and-Availability	Top SSL tunnel users by bandwidth usage and avail	event

```

select
    user_src,
    remote_ip,
    sum(traffic_out) as traffic_out,
    sum(traffic_in) as traffic_in,
    sum(bandwidth) as bandwidth,
    sum(uptime) as uptime
from
    (
        select
            user_src,
            remip as remote_ip,
            tunnelid,
            devid,
            vd,
            sum(sent_end - sent_beg) as traffic_out,
            sum(rcvd_end - rcvd_beg) as traffic_in,
            sum(
                sent_end - sent_beg + rcvd_end - rcvd_beg
            ) as bandwidth,
            sum(duration_end - duration_beg) as uptime
        from
            ###(select tunnelid, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src, remip,
devid, vd, min(coalesce(sentbyte, 0)) as sent_beg, max(coalesce(sentbyte, 0)) as sent_end, min
(coalesce(rcvdbyte, 0)) as rcvd_beg, max(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce(dur-
ation, 0)) as duration_beg, max(coalesce(duration, 0)) as duration_end from $log where $filter
and subtype='vpn' and action='tunnel-stats' and tunneltype in ('ssl-tunnel', 'ssl') and
coalesce(nullifna(`user`), ipstr(`remip`)) is not null and tunnelid is not null group by tun-
nelid, user_src, remip, devid, vd /*SkipSTART*/order by tunnelid/*SkipEND*/)### t group by
user_src, remote_ip, tunnelid, devid, vd order by bandwidth desc) t where bandwidth>0 group by
user_src, remote_ip order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-SSL-Web-Mode-By-Bandwidth-and-Availability	Top SSL web users by bandwidth usage and avail	event

```

select
  user_src,
  remote_ip,
  sum(traffic_out) as traffic_out,
  sum(traffic_in) as traffic_in,
  sum(bandwidth) as bandwidth,
  sum(uptime) as uptime
from
  (
    select
      user_src,
      remip as remote_ip,
      tunnelid,
      devid,
      vd,
      sum(sent_end - sent_beg) as traffic_out,
      sum(rcvd_end - rcvd_beg) as traffic_in,
      sum(
        sent_end - sent_beg + rcvd_end - rcvd_beg
      ) as bandwidth,
      sum(duration_end - duration_beg) as uptime
    from
      ###(select tunnelid, coalesce(nullifna(`user`), ipstr(`remip`)) as user_src, remip,
      devid, vd, min(coalesce(sentbyte, 0)) as sent_beg, max(coalesce(sentbyte, 0)) as sent_end, min
      (coalesce(rcvdbyte, 0)) as rcvd_beg, max(coalesce(rcvdbyte, 0)) as rcvd_end, min(coalesce(duration, 0)) as duration_beg, max(coalesce(duration, 0)) as duration_end from $log where $filter
      and subtype='vpn' and action='tunnel-stats' and tunneltype='ssl-web' and coalesce(nullifna
      (`user`), ipstr(`remip`)) is not null and tunnelid is not null group by tunnelid, user_src,
      remip, devid, vd /*SkipSTART*/order by tunnelid/*SkipEND*/)### t group by user_src, remote_ip,
      tunnelid, devid, vd having sum(sent_end-sent_beg+rcvd_end-rcvd_beg)>0 order by bandwidth desc)
      t where bandwidth>0 group by user_src, remote_ip order by bandwidth desc

```

Dataset Name	Description	Log Category
Admin-Login-Summary	Event admin login summary	event

```

select
  f_user,
  ui,
  sum(login) as total_num,
  sum(login_duration) as total_duration,
  sum(config_change) as total_change
from
  (
    select
      `user` as f_user,
      ui,
      (
        case when logid_to_int(logid)= 32001 then 1 else 0 end
      ) as login,
      (
        case when logid_to_int(logid)= 32003 then duration else 0 end
      ) as login_duration,
      (
        case when logid_to_int(logid)= 32003
          and state is not null then 1 else 0 end
      )

```

```

        ) as config_change
    from
        $log
    where
        $filter
        and nullifna(`user`) is not null
        and logid_to_int(logid) in (32001, 32003)
    ) t
group by
    f_user,
    ui
having
    sum(login)+ sum(config_change)& gt; 0
order by
    total_num desc

```

Dataset Name	Description	Log Category
Admin-Login-Summary-By-Date	Event admin login summary by date	event

```

select
    $flex_timescale(timestamp) as dom,
    sum(total_num) as total_num,
    sum(total_change) as total_change
from
    ###(select timestamp, sum(login) as total_num, sum(config_change) as total_change from
    (select $flex_timestamp as timestamp, (case when logid_to_int(logid)=32001 then 1 else 0 end)
    as login, (case when logid_to_int(logid)=32003 and state is not null then 1 else 0 end) as con-
    fig_change from $log where $filter and logid_to_int(logid) in (32001, 32003)) t group by
    timestamp having sum(login)+sum(config_change)>0 /*SkipSTART*/order by timestamp
    desc/*SkipEND*/)### t group by dom order by dom

```

Dataset Name	Description	Log Category
Admin-Failed-Login-Summary	Event admin failed login summary	event

```

select
    `user` as f_user,
    ui,
    count(status) as total_failed
from
    $log
where
    $filter
    and nullifna(`user`) is not null
    and logid_to_int(logid) = 32002
group by
    ui,
    f_user
order by
    total_failed desc

```

Dataset Name	Description	Log Category
System-Summary-By-Severity	Event system summary by severity	event

## Dataset Reference List

```
select
    severity_tmp as severity,
    sum(count) as total_num
from
    ###({{FGT_DATASET_EVENT_SYSTEM_EVENTS}})### t group by severity order by total_num desc
```

Dataset Name	Description	Log Category
System-Summary-By-Date	Event system summary by date	event

```
select
    $flex_timescale(timestamp) as dom,
    sum(critical) as critical,
    sum(high) as high,
    sum(medium) as medium
from
    ###(select $flex_timestamp as timestamp, sum(case when level in ('critical', 'alert', 'emergency') then 1 else 0 end) as critical, sum(case when level = 'error' then 1 else 0 end) as high, sum(case when level = 'warning' then 1 else 0 end) as medium from $log where $filter and subtype='system' group by timestamp /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t
group by dom order by dom
```

Dataset Name	Description	Log Category
Important-System-Summary-By-Date	Event system summary by date	event

```
select
    $flex_timescale(timestamp) as dom,
    sum(critical) as critical,
    sum(high) as high,
    sum(medium) as medium
from
    ###(select $flex_timestamp as timestamp, sum(case when level in ('critical', 'alert', 'emergency') then 1 else 0 end) as critical, sum(case when level = 'error' then 1 else 0 end) as high, sum(case when level = 'warning' then 1 else 0 end) as medium from $log where $filter and subtype='system' group by timestamp /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t
group by dom order by dom
```

Dataset Name	Description	Log Category
System-Critical-Severity-Events	Event system critical severity events	event

```
select
    msg_desc as msg,
    severity_tmp as severity,
    sum(count) as counts
from
    ###({{FGT_DATASET_EVENT_SYSTEM_EVENTS}})### t where severity_tmp='Critical' group by msg,
    severity_tmp order by counts desc
```

Dataset Name	Description	Log Category
System-High-Severity-Events	Event system high severity events	event

```
select
    msg_desc as msg,
```



```

    severity_tmp as severity,
    sum(count) as counts
from
    ###({{FGT_DATASET_EVENT_SYSTEM_EVENTS}})### t where severity_tmp='High' group by msg, severity_tmp order by counts desc

```

Dataset Name	Description	Log Category
System-Medium-Severity-Events	Event system medium severity events	event

```

select
    msg_desc as msg,
    severity_tmp as severity,
    sum(count) as counts
from
    ###({{FGT_DATASET_EVENT_SYSTEM_EVENTS}})### t where severity_tmp='Medium' group by msg, severity_tmp order by counts desc

```

Dataset Name	Description	Log Category
utm-drilldown-Top-Traffic-Summary	UTM drilldown traffic summary	traffic

```

select
    srcip,
    srcname
from
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
    srcip, srcname, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where
    $filter and (logflag&1>0) group by user_src, srcip, srcname order by bandwidth desc)### t
where $filter-drilldown group by srcip, srcname

```

Dataset Name	Description	Log Category
utm-drilldown-Top-User-Destination	UTM drilldown top user destination	traffic

```

select
    appid,
    app,
    dstip,
    sum(sessions) as sessions,
    sum(bandwidth) as bandwidth
from
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
    appid, app, dstip, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as
    bandwidth from $log where $filter and (logflag&1>0) and dstip is not null and nullifna(app) is
    not null group by user_src, appid, app, dstip having sum(coalesce(sentbyte, 0)+coalesce(rcvd-
    byte, 0))>0 order by bandwidth desc)### t where $filter-drilldown group by appid, app, dstip
    order by bandwidth desc

```

Dataset Name	Description	Log Category
utm-drilldown-Email-Senders-Summary	UTM drilldown email senders summary	traffic

```

select
    sum(requests) as requests,

```

```

sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_TOP_EMAIL_SENDERS}})### t where $filter-drilldown

```

Dataset Name	Description	Log Category
utm-drilldown-Email-Receiveers-Summary	UTM drilldown email receivers summary	traffic

```

select
  sum(requests) as requests,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_TOP_EMAIL_RECIPIENTS}})### t where $filter-drilldown

```

Dataset Name	Description	Log Category
utm-drilldown-Top-Email-Recipients-By-Bandwidth	UTM drilldown top email recipients	traffic

```

select
  recipient,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_TOP_EMAIL_RECIPIENTS}})### t where $filter-drilldown group by
recipient having sum(bandwidth)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
utm-drilldown-Top-Email-Senders-By-Bandwidth	UTM drilldown top email senders	traffic

```

select
  sender,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_TOP_EMAIL_SENDERS}})### t where $filter-drilldown and sender is
not null group by sender having sum(bandwidth)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
utm-drilldown-Top-Allowed-Websites-By-Bandwidth	UTM drilldown top allowed web sites by bandwidth	traffic

```

select
  appid,
  hostname,
  sum(bandwidth) as bandwidth
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
appid, hostname, (case when utmaction in ('block', 'blocked') then 1 else 0 end) as blocked,
sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter
and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (hostname is
not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-
filter')))) and hostname is not null group by user_src, appid, hostname, blocked order by

```

```
bandwidth desc)### t where $filter-drilldown and blocked=0 group by appid, hostname order by
bandwidth desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Blocked-Websites-By-Request	UTM drilldown top blocked web sites by request	webfilter

```
select
  appid,
  hostname,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, 0 as appid, hostname,
  (case when action='blocked' then 1 else 0 end) as blocked, count(*) as requests from $log
  where $filter and (eventtype is null or logver>=502000000) and hostname is not null group by
  user_src, appid, hostname, blocked order by requests desc)### t where $filter-drilldown and
  blocked=1 group by appid, hostname order by requests desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Virus-By-Name	UTM drilldown top virus	virus

```
select
  virus,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, count(*) as total-
  num from $log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus)
  is not null group by user_src, virus order by totalnum desc)### t where $filter-drilldown
  group by virus order by totalnum desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Attacks	UTM drilldown top attacks by name	attack

```
select
  attack,
  sum(attack_count) as attack_count
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, attack, count(*) as
  attack_count from $log where $filter and nullifna(attack) is not null group by user_src,
  attack order by attack_count desc)### t where $filter-drilldown group by attack order by
  attack_count desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-Vulnerability	UTM drilldown top vulnerability by name	netscan

```
select
  vuln,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, vuln, count(*) as total-
  num from $log where $filter and action='vuln-detection' and vuln is not null group by user_
```

```
src, vuln order by totalnum desc)### t where $filter-drilldown group by vuln order by totalnum desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-App-By-Bandwidth	UTM drilldown top applications by bandwidth usage	traffic

```
select
  appid,
  app,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as sessions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk /*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown group by appid, app having sum(bandwidth)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
utm-drilldown-Top-App-By-Sessions	UTM drilldown top applications by session count	traffic

```
select
  appid,
  app,
  sum(sessions) as sessions
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as sessions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk /*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown group by appid, app order by sessions desc
```

Dataset Name	Description	Log Category
Top5-Users-By-Bandwidth	UTM drilldown top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as dldn_user,
  count(*) as session,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in
from
  $log
where
  $filter
  and (
```

```

        logflag&1>0
    )
group by
    dldn_user
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
bandwidth-app-Top-App-By-Bandwidth-Sessions	Top applications by bandwidth usage	traffic

```

select
    app_group_name(app) as app_group,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(app) is not null
group by
    app_group
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
bandwidth-app-Category-By-Bandwidth	Application risk application usage by category	traffic

```

select
    appcat,
    sum(bandwidth) as bandwidth
from
    ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as sessions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk

```

```
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null group by appcat order by bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Top-Users-By-Bandwidth-Sessions	Bandwidth application top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  user_src
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )& gt; 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Traffic-By-Active-User-Number	Bandwidth application traffic by active user number	traffic

```
select
  $flex_timescale(timestamp) as horex,
  count(
    distinct(user_src)
  ) as total_user
from
  ###(select $flex_timestamp as timestamp, coalesce(nullifna(`user`), nullifna(`unauthuser`),
  ipstr(`srcip`)) as user_src from $log where $filter and (logflag&1>0) group by timestamp,
  user_src order by timestamp desc)### t group by horex order by horex
```

Dataset Name	Description	Log Category
bandwidth-app-Top-Dest-By-Bandwidth-Sessions	Bandwidth application top dest by bandwidth usage sessions	traffic

```
select
  coalesce(
    nullifna(
      root_domain(hostname)
    ),
    ipstr(`dstip`)
  ) as domain,
  sum(
    coalesce(sentbyte, 0) + coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  domain
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Top-Policies-By-Bandwidth-Sessions	Top policies by bandwidth and sessions	traffic

```
select
  coalesce(
    pol.name,
    cast(policyid as text)
  ) as polid,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions
from
  ###(select policyid, poluuid, sum(coalesce(rcvdbyte, 0) + coalesce(sentbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum(coalesce(sentbyte, 0)) as traffic_out, count(*) as sessions from $log where $filter and (logflag&1>0) group by policyid, poluuid order by bandwidth desc)### t1 left join $ADOMTBL_PLHD_POLINFO pol on t1.poluuid=pol.uuid
group by polid order by bandwidth desc
```

Dataset Name	Description	Log Category
bandwidth-app-Traffic-Statistics	Bandwidth application traffic statistics	traffic

drop

```
table if exists rpt_tmptbl_1; create temporary table rpt_tmptbl_1(
  total_sessions varchar(255),
  total_bandwidth varchar(255),
  ave_session varchar(255),
  ave_bandwidth varchar(255),
  active_date varchar(255),
  total_users varchar(255),
  total_app varchar(255),
  total_dest varchar(255)
); insert into rpt_tmptbl_1 (
  total_sessions, total_bandwidth,
  ave_session, ave_bandwidth
)
```

select

```
format_numeric_no_decimal(
  sum(sessions)
) as total_sessions,
bandwidth_unit(
  sum(bandwidth)
) as total_bandwidth,
format_numeric_no_decimal(
  cast(
    sum(sessions)/ $days_num as decimal(18, 0)
  )
) as ave_session,
bandwidth_unit(
  cast(
    sum(bandwidth)/ $days_num as decimal(18, 0)
  )
) as ave_bandwidth
```

from

```
###(select count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and (logflag&1>0))### t; update rpt_tmptbl_1 set active_date=t1.dom from (select dom, sum(sessions) as sessions from ###(select $DAY_OF_MONTH as dom, count(*) as sessions from $log where $filter and (logflag&1>0) group by dom order by sessions desc)### t group by dom order by sessions desc limit 1) as t1; update rpt_tmptbl_1 set total_users=t2.totalnum from (select format_numeric_no_decimal(count(distinct(user_src))) as totalnum from ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, count(*) as count from $log where $filter and (logflag&1>0) group by user_src order by count desc)### t) as t2; update rpt_tmptbl_1 set total_app=t3.totalnum from (select format_numeric_no_decimal(count(distinct(app_grp))) as totalnum from ###(select app_group_name(app) as app_grp, count(*) as count from $log where $filter and (logflag&1>0) and nullifna(app) is not null group by app_grp order by count desc)### t) as t3; update rpt_tmptbl_1 set total_dest=t4.totalnum from (select format_numeric_no_decimal(count(distinct(dstip))) as totalnum from ###(select dstip, count(*) as count from $log where $filter and (logflag&1>0) and dstip is not null group by dstip order by count desc)### t) as t4; select 'Total Sessions' as summary, total_sessions as stats from rpt_tmptbl_1 union all select 'Total Bytes Transferred' as summary, total_bandwidth as stats from rpt_tmptbl_1 union all select 'Most Active Date By Sessions' as summary, active_date as stats from rpt_tmptbl_1 union all select 'Total Users' as summary, total_users as stats from rpt_tmptbl_1 union all select 'Total Applications' as summary, total_app as stats from rpt_tmptbl_1 union all select 'Total Destinations' as summary,
```



```
total_dest as stats from rpt_tmptbl_1 union all select 'Average Sessions Per Day' as summary,
ave_session as stats from rpt_tmptbl_1 union all select 'Average Bytes Per Day' as summary,
ave_bandwidth as stats from rpt_tmptbl_1
```

Dataset Name	Description	Log Category
Score-Summary-For-All-Users-Devices	Reputation score summary for all users devices	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  sum(scores) as scores
from
  ###({{FGT_DATASET_TRAFFIC_CLIENT_REPUTATION_INCIDENTS}})### t group by hodex order by hodex
```

Dataset Name	Description	Log Category
Number-Of-Incidents-For-All-Users-Devices	Reputation number of incidents for all users devices	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  sum(scores) as scores,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATASET_TRAFFIC_CLIENT_REPUTATION_INCIDENTS}})### t group by hodex order by hodex
```

Dataset Name	Description	Log Category
Top-Users-By-Reputation-Scores	Reputation top users by scores	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(crscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crscore is not null
group by
  user_src
having
  sum(crscore % 65536) > 0
order by
  scores desc
```

Dataset Name	Description	Log Category
Top-Devices-By-Reputation-Scores	Reputation top devices by scores	traffic

```

select
  get_devtype(srcswversion, osname, devtype) as devtype_new,
  coalesce(
    nullifna(`srcname`),
    nullifna(`srcmac`),
    ipstr(`srcip`)
  ) as dev_src,
  sum(crscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crscore is not null
group by
  devtype_new,
  dev_src
having
  sum(crscore % 65536) > 0
order by
  scores desc

```

Dataset Name	Description	Log Category
Top-Users-With-Increased-Scores	Reputation top users with increased scores	traffic

```

drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  f_user,
  sum(sum_rp_score) as sum_rp_score
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as f_user, sum
(crscore%65536) as sum_rp_score from $log where $pre_period $filter and (logflag&1>0) and
crscore is not null group by f_user having sum(crscore%65536)>0 order by sum_rp_score desc)###
t group by f_user; create temporary table rpt_tmptbl_2 as select f_user, sum(sum_rp_score) as
sum_rp_score from ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`sr-
cip`)) as f_user, sum(crscore%65536) as sum_rp_score from $log where $filter and (logflag&1>0)
and crscore is not null group by f_user having sum(crscore%65536)>0 order by sum_rp_score
desc)### t group by f_user; select t1.f_user, sum(t1.sum_rp_score) as t1_sum_score, sum
(t2.sum_rp_score) as t2_sum_score, (sum(t2.sum_rp_score)-sum(t1.sum_rp_score)) as delta from
rpt_tmptbl_1 as t1 inner join rpt_tmptbl_2 as t2 on t1.f_user=t2.f_user where t2.sum_rp_score
> t1.sum_rp_score group by t1.f_user order by delta desc

```

Dataset Name	Description	Log Category
Top-Devices-With-Increased-Scores	Reputation top devices with increased scores	traffic

```

drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as

```

```

select
  f_device,
  devtype_new,
  sum(sum_rp_score) as sum_rp_score
from
  ###(select coalesce(nullifna(`srcname`),nullifna(`srcmac`), ipstr(`srcip`)) as f_device,
  get_devtype(srswversion, osname, devtype) as devtype_new, sum(crsscore%65536) as sum_rp_score
  from $log where $pre_period $filter and (logflag&1>0) and crsscore is not null group by f_
  device, devtype_new having sum(crsscore%65536)>0 order by sum_rp_score desc)### t group by f_
  device, devtype_new; create temporary table rpt_tmptbl_2 as select f_device, devtype_new, sum
  (sum_rp_score) as sum_rp_score from ###(select coalesce(nullifna(`srcname`),nullifna(`sr-
  cmac`), ipstr(`srcip`)) as f_device, get_devtype(srswversion, osname, devtype) as devtype_
  new, sum(crsscore%65536) as sum_rp_score from $log where $filter and (logflag&1>0) and crsscore
  is not null group by f_device, devtype_new having sum(crsscore%65536)>0 order by sum_rp_score
  desc)### t group by f_device, devtype_new; select t1.f_device, t1.devtype_new , sum(t1.sum_rp_
  score) as t1_sum_score, sum(t2.sum_rp_score) as t2_sum_score, (sum(t2.sum_rp_score)-sum
  (t1.sum_rp_score)) as delta from rpt_tmptbl_1 as t1 inner join rpt_tmptbl_2 as t2 on t1.f_
  device=t2.f_device and t1.devtype_new=t2.devtype_new where t2.sum_rp_score > t1.sum_rp_score
  group by t1.f_device, t1.devtype_new order by delta desc

```

Dataset Name	Description	Log Category
Attacks-By-Severity	Threat attacks by severity	attack

```

select
  (
    case when severity = 'critical' then 'Critical' when severity = 'high' then 'High' when
    severity = 'medium' then 'Medium' when severity = 'low' then 'Low' when severity = 'info' then
    'Info' end
  ) as severity,
  count(*) as totalnum
from
  $log
where
  $filter
group by
  severity
order by
  totalnum desc

```

Dataset Name	Description	Log Category
Top-Attacks-Detected	Threat top attacks detected	attack

```

select
  attack,
  attackid,
  cve,
  severity,
  sum(attack_count) as attack_count
from
  ###(select attack, attackid, t1.severity, cve, (case when t1.severity = 'critical' then 1
  when t1.severity = 'high' then 2 when t1.severity = 'medium' then 3 when t1.severity = 'low'
  then 4 else 5 end) as severity_level, count(*) as attack_count from $log t1 left join (select
  name, cve, vuln_type from ips_mdata) t2 on t1.attack=t2.name where $filter and nullifna
  (attack) is not null group by attack, attackid, t1.severity, severity_level, cve

```

```
/*SkipSTART*/order by severity_level, attack_count desc/*SkipEND*/)### t group by attack,
attackid, severity, severity_level, cve order by severity_level, attack_count desc
```

Dataset Name	Description	Log Category
Top-Attacks-Blocked	Threat top attacks blocked	attack

```
select
  attack,
  count(*) as attack_count
from
  $log
where
  $filter
  and nullifna(attack) is not null
  and action not in ('detected', 'pass_session')
group by
  attack
order by
  attack_count desc
```

Dataset Name	Description	Log Category
Top-Virus-Source	Threat top virus source	virus

```
select
  srcip,
  hostname,
  sum(totalnum) as totalnum
from
  ###(select srcip , ipstr(`dstip`) as hostname, count(*) as totalnum from $log where $filter
  and (eventtype is null or logver>=502000000) and nullifna(virus) is not null group by srcip,
  hostname /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by srcip, hostname order
  by totalnum desc
```

Dataset Name	Description	Log Category
Intrusion-in-Last-7-Days	Threat intrusion timeline	attack

```
select
  $flex_timescale(timestamp) as hodex,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter group
  by timestamp /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t group by hodex order by
  hodex
```

Dataset Name	Description	Log Category
Virus-Time-Line	Threat virus timeline	virus

```
select
  $flex_datetime(timestamp) as hodex,
  sum(totalnum) as totalnum
from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter and
```

```
(eventtype is null or logver>=502000000) and nullifna(virus) is not null group by timestamp
/*SkipSTART*/order by timestamp desc/*SkipEND*/)### t group by hodex order by hodex
```

Dataset Name	Description	Log Category
Top-Spyware-Victims	Threat top spyware victims	virus

```
select
  user_src,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATASET_VIRUS_TOP_MALWARE_VICTIMS}})### t where virus like 'Riskware%' group by
  user_src order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Spyware-by-Name	Threat top spyware by name	virus

```
select
  virus,
  max(virusid_s) as virusid,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATABASE_VIRUS_TOP_MALWARE_NAME}})### t where virus like 'Riskware%' group by
  virus order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Spyware-Source	Threat top spyware source	traffic

```
select
  srcip,
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and virus like 'Riskware%'
group by
  srcip,
  hostname
order by
  totalnum desc
```

Dataset Name	Description	Log Category
Spyware-Time-Line	Threat spyware timeline	virus

```
select
  $flex_timescale(timestamp) as hodex,
  sum(totalnum) as totalnum
from
```

```
###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter and
virus like 'Riskware%' group by timestamp /*SkipSTART*/order by timestamp desc/*SkipEND*/)###
t group by hodex order by hodex
```

Dataset Name	Description	Log Category
Top-Adware-Victims	Threat top adware victims	virus

```
select
  user_src,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATASET_VIRUS_TOP_MALWARE_VICTIMS}})### t where virus like 'Adware%' group by
  user_src order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Adware-by-Name	Threat top adware by name	virus

```
select
  virus,
  max(virusid_s) as virusid,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATABASE_VIRUS_TOP_MALWARE_NAME}})### t where virus like 'Adware%' group by virus
order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Adware-Source	Threat top adware source	traffic

```
select
  srcip,
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and virus like 'Adware%'
group by
  srcip,
  hostname
order by
  totalnum desc
```

Dataset Name	Description	Log Category
Adware-Time-Line	Threat adware timeline	virus

```
select
  $flex_timescale(timestamp) as hodex,
  sum(totalnum) as totalnum
```

```

from
  ###(select $flex_timestamp as timestamp, count(*) as totalnum from $log where $filter and
virus like 'Adware%' group by timestamp /*SkipSTART*/order by timestamp desc/*SkipEND*/)### t
group by hodex order by hodex

```

Dataset Name	Description	Log Category
Intrusions-Timeline-By-Severity	Threat intrusions timeline by severity	attack

```

select
  $flex_timescale(timestamp) as timescale,
  sum(critical) as critical,
  sum(high) as high,
  sum(medium) as medium,
  sum(low) as low,
  sum(info) as info
from
  ###(select $flex_timestamp as timestamp, sum(case when severity = 'critical' then 1 else 0
end) as critical, sum(case when severity = 'high' then 1 else 0 end) as high, sum(case when
severity = 'medium' then 1 else 0 end) as medium, sum(case when severity = 'notice' then 1
else 0 end) as low, sum(case when severity = 'info' or severity = 'debug' then 1 else 0 end)
as info from $log where $filter group by timestamp /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t group by timescale order by timescale

```

Dataset Name	Description	Log Category
Important-Intrusions-Timeline-By-Severity	Threat intrusions timeline by severity	attack

```

select
  $flex_timescale(timestamp) as timescale,
  sum(critical) as critical,
  sum(high) as high,
  sum(medium) as medium,
  sum(low) as low,
  sum(info) as info
from
  ###(select $flex_timestamp as timestamp, sum(case when severity = 'critical' then 1 else 0
end) as critical, sum(case when severity = 'high' then 1 else 0 end) as high, sum(case when
severity = 'medium' then 1 else 0 end) as medium, sum(case when severity = 'notice' then 1
else 0 end) as low, sum(case when severity = 'info' or severity = 'debug' then 1 else 0 end)
as info from $log where $filter group by timestamp /*SkipSTART*/order by timestamp
desc/*SkipEND*/)### t group by timescale order by timescale

```

Dataset Name	Description	Log Category
Top-Intrusions-By-Types	Threat top intrusions by types	attack

```

select
  vuln_type,
  count(*) as totalnum
from
  $log t1
  left join (
    select
      name,

```

```

        cve,
        vuln_type
    from
        ips_mdata
    ) t2 on t1.attack = t2.name
where
    $filter
    and vuln_type is not null
group by
    vuln_type
order by
    totalnum desc

```

Dataset Name	Description	Log Category
Critical-Severity-Intrusions	Threat critical severity intrusions	attack

```

select
    attack,
    attackid,
    cve,
    vuln_type,
    count(*) as totalnum
from
    $log t1
    left join (
        select
            name,
            cve,
            vuln_type
        from
            ips_mdata
        ) t2 on t1.attack = t2.name
where
    $filter
    and t1.severity = 'critical'
    and nullifna(attack) is not null
group by
    attack,
    attackid,
    cve,
    vuln_type
order by
    totalnum desc

```

Dataset Name	Description	Log Category
High-Severity-Intrusions	Threat high severity intrusions	attack

```

select
    attack,
    attackid,
    vuln_type,
    cve,
    count(*) as totalnum
from

```



```

$log t1
left join (
  select
    name,
    cve,
    vuln_type
  from
    ips_mdata
) t2 on t1.attack = t2.name
where
  $filter
  and t1.severity = 'high'
  and nullifna(attack) is not null
group by
  attack,
  attackid,
  vuln_type,
  cve
order by
  totalnum desc

```

Dataset Name	Description	Log Category
Medium-Severity-Intrusions	Threat medium severity intrusions	attack

```

select
  attack,
  vuln_type,
  cve,
  count(*) as totalnum
from
  $log t1
  left join (
    select
      name,
      cve,
      vuln_type
    from
      ips_mdata
  ) t2 on t1.attack = t2.name
where
  $filter
  and t1.severity = 'medium'
  and nullifna(attack) is not null
group by
  attack,
  vuln_type,
  cve
order by
  totalnum desc

```

Dataset Name	Description	Log Category
Top-Intrusion-Victims	Threat top intrusion victims	attack

```

select
  victim,
  sum(cri_num) as critical,
  sum(high_num) as high,
  sum(med_num) as medium,
  sum(cri_num + high_num + med_num) as totalnum
from
  ###(select dstip as victim, sum((case when severity='critical' then 1 else 0 end)) as cri_
num, sum(case when severity='high' then 1 else 0 end) as high_num, sum(case when sever-
ity='medium' then 1 else 0 end) as med_num from $log where $filter and severity in ('crit-
ical', 'high', 'medium') group by victim)### t group by victim order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Intrusion-Sources	Threat top intrusion sources	attack

```

select
  source,
  sum(cri_num) as critical,
  sum(high_num) as high,
  sum(med_num) as medium,
  sum(cri_num + high_num + med_num) as totalnum
from
  ###(select srcip as source, sum(case when severity='critical' then 1 else 0 end) as cri_num,
sum(case when severity='high' then 1 else 0 end) as high_num, sum(case when severity='medium'
then 1 else 0 end) as med_num from $log where $filter and severity in ('critical', 'high',
'medium') group by source)### t group by source order by totalnum desc

```

Dataset Name	Description	Log Category
Top-Blocked-Intrusions	Threat top blocked intrusions	attack

```

select
  attack,
  attackid,
  (
    case when t1.severity = 'critical' then 'Critical' when t1.severity = 'high' then 'High'
when t1.severity = 'medium' then 'Medium' when t1.severity = 'low' then 'Low' when t1.severity
= 'info' then 'Info' end
  ) as severity_name,
  count(*) as totalnum,
  vuln_type,
  (
    case when t1.severity = 'critical' then 0 when t1.severity = 'high' then 1 when t1.-
severity = 'medium' then 2 when t1.severity = 'low' then 3 when t1.severity = 'info' then 4
else 5 end
  ) as severity_number
from
  $log t1
left join (
  select
    name,
    cve,
    vuln_type
  from
    ips_mdata

```

```

) t2 on t1.attack = t2.name
where
$filter
and nullifna(attack) is not null
and action not in ('detected', 'pass_session')
group by
attack,
attackid,
t1.severity,
vuln_type
order by
severity_number,
totalnum desc

```

Dataset Name	Description	Log Category
Top-Monitored-Intrusions	Threat top monitored intrusions	attack

```

select
attack,
attackid,
(
case when t1.severity = 'critical' then 'Critical' when t1.severity = 'high' then 'High'
when t1.severity = 'medium' then 'Medium' when t1.severity = 'low' then 'Low' when t1.severity
= 'info' then 'Info' end
) as severity_name,
count(*) as totalnum,
vuln_type,
(
case when t1.severity = 'critical' then 0 when t1.severity = 'high' then 1 when t1.-
severity = 'medium' then 2 when t1.severity = 'low' then 3 when t1.severity = 'info' then 4
else 5 end
) as severity_number
from
$log t1
left join (
select
name,
cve,
vuln_type
from
ips_mdata
) t2 on t1.attack = t2.name
where
$filter
and nullifna(attack) is not null
and action in ('detected', 'pass_session')
group by
attack,
attackid,
t1.severity,
vuln_type
order by
severity_number,
totalnum desc

```

Dataset Name	Description	Log Category
Attacks-Over-HTTP-HTTPS	Threat attacks over HTTP HTTPS	attack

```

select
  attack,
  attackid,
  (
    case when severity = 'critical' then 'Critical' when severity = 'high' then 'High' when
severity = 'medium' then 'Medium' when severity = 'low' then 'Low' when severity = 'info' then
'Info' end
  ) as severity,
  count(*) as totalnum,
  (
    case when severity = 'critical' then 0 when severity = 'high' then 1 when severity =
'medium' then 2 when severity = 'low' then 3 when severity = 'info' then 4 else 5 end
  ) as severity_number
from
  $log
where
  $filter
  and severity in ('critical', 'high', 'medium')
  and upper(service) in ('HTTP', 'HTTPS')
group by
  attack,
  attackid,
  severity,
  severity_number
order by
  severity_number,
  totalnum desc

```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OffWire	Default access point detection summary by status off-wire	event

```

select
  (
    case apstatus when 1 then 'rogue' when 2 then 'accepted' when 3 then 'suppressed' else
'others' end
  ) as ap_full_status,
  count(*) as totalnum
from
  (
    select
      apstatus,
      bssid,
      ssid
    from
      ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter and
apstatus is not null and apstatus!=0 and bssid is not null and onwire='no' and logid_to_int
(logid) in (43527, 43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582,
43583, 43584, 43585) group by apstatus, bssid, ssid order by subtotal desc)### t group by
apstatus, bssid, ssid) t group by ap_full_status order by totalnum desc

```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OffWire_table	Default access point detection summary by status off-wire	event

```
select
(
case apstatus when 1 then 'rogue' when 2 then 'accepted' when 3 then 'suppressed' else
'others' end
) as ap_full_status,
count(*) as totalnum
from
(
select
apstatus,
bssid,
ssid
from
###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter and
apstatus is not null and apstatus!=0 and bssid is not null and onwire='no' and logid_to_int
(logid) in (43527, 43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582,
43583, 43584, 43585) group by apstatus, bssid, ssid order by subtotal desc)### t group by
apstatus, bssid, ssid) t group by ap_full_status order by totalnum desc
```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OnWire	Default access point detection summary by status on-wire	event

```
select
(
case apstatus when 1 then 'rogue' when 2 then 'accepted' when 3 then 'suppressed' else
'others' end
) as ap_full_status,
count(*) as totalnum
from
(
select
apstatus,
bssid,
ssid
from
###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter and
apstatus is not null and apstatus!=0 and bssid is not null and onwire='yes' and logid_to_int
(logid) in (43527, 43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582,
43583, 43584, 43585) group by apstatus, bssid, ssid order by subtotal desc)### t group by
apstatus, bssid, ssid) t group by ap_full_status order by totalnum desc
```

Dataset Name	Description	Log Category
default-AP-Detection-Summary-by-Status-OnWire_table	Default access point detection summary by status on-wire	event

```
select
(
```

```

        case apstatus when 1 then 'rogue' when 2 then 'accepted' when 3 then 'suppressed' else
'others' end
    ) as ap_full_status,
    count(*) as totalnum
from
    (
        select
            apstatus,
            bssid,
            ssid
        from
            ###(select apstatus, bssid, ssid, count(*) as subtotal from $log where $filter and
apstatus is not null and apstatus!=0 and bssid is not null and onwire='yes' and logid_to_int
(logid) in (43527, 43521, 43525, 43563, 43564, 43565, 43566, 43569, 43570, 43571, 43582,
43583, 43584, 43585) group by apstatus, bssid, ssid order by subtotal desc)### t group by
apstatus, bssid, ssid) t group by ap_full_status order by totalnum desc

```

Dataset Name	Description	Log Category
default-Managed-AP-Summary	Default managed access point summary	event

```

select
    (
        case when (
            action like '%join%'
            and logid_to_int(logid) in (43522, 43551)
        ) then 'Authorized' else 'Unauthorized' end
    ) as ap_status,
    count(*) as totalnum
from
    $log
where
    $filter
    and logid_to_int(logid) in (43522, 43551)
group by
    ap_status
order by
    totalnum desc

```

Dataset Name	Description	Log Category
default-Managed-AP-Summary_table	Default managed access point summary	event

```

select
    (
        case when (
            action like '%join%'
            and logid_to_int(logid) in (43522, 43551)
        ) then 'Authorized' else 'Unauthorized' end
    ) as ap_status,
    count(*) as totalnum
from
    $log
where
    $filter
    and logid_to_int(logid) in (43522, 43551)

```

```
group by
  ap_status
order by
  totalnum desc
```

Dataset Name	Description	Log Category
default-Unclassified-AP-Summary	Default unclassified access point summary	event

```
select
(
  case onwire when 'no' then 'off-wire' when 'yes' then 'on-wire' else 'others' end
) as ap_status,
count(*) as totalnum
from
###(select onwire, ssid, bssid, count(*) as subtotal from $log where $filter and apstatus=0
and bssid is not null and logid_to_int(logid) in (43521, 43525, 43527, 43563, 43564, 43565,
43566, 43569, 43570, 43571, 43582, 43583, 43584, 43585) group by onwire, ssid, bssid order by
subtotal desc)### t group by ap_status order by totalnum desc
```

Dataset Name	Description	Log Category
default-Unclassified-AP-Summary_ table	Default unclassified access point summary	event

```
select
(
  case onwire when 'no' then 'off-wire' when 'yes' then 'on-wire' else 'others' end
) as ap_status,
count(*) as totalnum
from
###(select onwire, ssid, bssid, count(*) as subtotal from $log where $filter and apstatus=0
and bssid is not null and logid_to_int(logid) in (43521, 43525, 43527, 43563, 43564, 43565,
43566, 43569, 43570, 43571, 43582, 43583, 43584, 43585) group by onwire, ssid, bssid order by
subtotal desc)### t group by ap_status order by totalnum desc
```

Dataset Name	Description	Log Category
default-selected-AP-Details-OffWire	Default selected access point details off-wire	event

```
select
(
  case apstatus when 0 then 'unclassified' when 1 then 'rogue' when 2 then 'accepted' when 3
then 'suppressed' else 'others' end
) as ap_full_status,
devid,
vd,
ssid,
bssid,
manuf,
rssi,
channel,
radioband,
from_dtime(
  min(dtime)
) as first_seen,
```

```

    from_dtime(
        max(dtime)
    ) as last_seen,
    detectionmethod,
    itime,
    onwire as on_wire
from
    $log
where
    $filter
    and apstatus is not null
    and bssid is not null
    and onwire = 'no'
    and logid_to_int(logid) in (
        43521, 43563, 43564, 43565, 43566, 43569,
        43570, 43571
    )
group by
    ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    rssi,
    channel,
    radioband,
    detectionmethod,
    itime,
    onwire,
    apstatus

```

Dataset Name	Description	Log Category
default-selected-AP-Details-OnWire	Default selected access point details on-wire	event

```

select
    (
        case apstatus when 0 then 'unclassified' when 1 then 'rogue' when 2 then 'accepted' when 3
then 'suppressed' else 'others' end
    ) as ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    rssi,
    channel,
    radioband,
    from_dtime(
        min(dtime)
    ) as first_seen,
    from_dtime(
        max(dtime)
    ) as last_seen,
    detectionmethod,

```



```

    itime,
    onwire as on_wire
from
    $log
where
    $filter
    and apstatus is not null
    and bssid is not null
    and onwire = 'yes'
    and logid_to_int(logid) in (
        43521, 43563, 43564, 43565, 43566, 43569,
        43570, 43571
    )
group by
    ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    rssi,
    channel,
    radioband,
    detectionmethod,
    itime,
    onwire,
    apstatus

```

Dataset Name	Description	Log Category
event-Wireless-Client-Details	Event wireless client details	event

```

drop
    table if exists rpt_tmptbl_1; create temporary table rpt_tmptbl_1 as
select
    ip,
    lmac,
    sn,
    ssid,
    channel,
    radioband,
    min(first) as first,
    max(last) as last
from
    ###(select ip, lower(mac) as lmac, sn, ssid, channel, radioband, min(dtime) as first, max
    (dtime) as last from $log-event where $filter and ip is not null and mac is not null and sn is
    not null and ssid is not null group by ip, lmac, sn, ssid, channel, radioband order by ip)###
    t group by ip, lmac, sn, ssid, channel, radioband; select user_src, ip, lmac, sn, ssid, chan-
    nel, radioband, from_dtime(first) as first_seen, from_dtime(last) as last_seen, cast(volume as
    decimal(18,2)) as bandwidth from (select * from rpt_tmptbl_1 inner join (select user_src,
    srcip, sum(volume) as volume from ###(select coalesce(nullifna(`user`), nullifna(`un-
    authuser`), ipstr(`srcip`)) as user_src, srcip, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte,
    0)) as volume from $log-traffic where $filter-time and (logflag&1>0) and srcip is not null
    group by user_src, srcip having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by
    volume desc)### t group by user_src, srcip order by user_src, srcip) t on rpt_tmptbl_1.ip =
    t.srcip) t order by volume desc

```

Dataset Name	Description	Log Category
event-Wireless-Accepted-Offwire	Event wireless accepted off-wire	event

```
select
  'accepted' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'no' as on_wire
from
  ###({{FGT_DATASET_EVENT_WIRELESS_ROGUE_OFFWIRE}})### t where apstatus=2 and onwire='no'
group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order
by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Accepted-Onwire	Event wireless accepted on-wire	event

```
select
  'accepted' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'yes' as on_wire
from
  ###({{FGT_DATASET_EVENT_WIRELESS_ROGUE_ONWIRE}})### t where apstatus=2 and onwire='yes'
group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order
by last_seen desc
```

Dataset Name	Description	Log Category
event-Wireless-Rogue-Offwire	Event wireless rogue off-wire	event

```
select
  'rogue' as ap_full_status,
  devid,
  vd,
```

```

ssid,
bssid,
manuf,
channel,
radioband,
from_dtime(
    max(last_seen)
) as last_seen,
detectionmethod,
snclosest,
'no' as on_wire
from
    ###({{FGT_DATASET_EVENT_WIRELESS_ROGUE_OFFWIRE}})### t where apstatus=1 and onwire='no'
group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order
by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Rogue-Onwire	Event wireless rogue on-wire	event

```

select
    'rogue' as ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    channel,
    radioband,
    from_dtime(
        max(last_seen)
    ) as last_seen,
    detectionmethod,
    snclosest,
    'yes' as on_wire
from
    ###({{FGT_DATASET_EVENT_WIRELESS_ROGUE_ONWIRE}})### t where apstatus=1 and onwire='yes'
group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order
by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Suppressed-Offwire	Event wireless suppressed off-wire	event

```

select
    'suppressed' as ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    channel,
    radioband,
    from_dtime(
        max(last_seen)
    ) as last_seen,

```

```

    detectionmethod,
    snclosest,
    'no' as on_wire
from
    ###({{FGT_DATASET_EVENT_WIRELESS_ROGUE_OFFWIRE}})### t where apstatus=3 and onwire='no'
group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order
by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Suppressed-Onwire	Event wireless suppressed on-wire	event

```

select
    'suppressed' as ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    channel,
    radioband,
    from_dtime(
        max(last_seen)
    ) as last_seen,
    detectionmethod,
    snclosest,
    'yes' as on_wire
from
    ###({{FGT_DATASET_EVENT_WIRELESS_ROGUE_ONWIRE}})### t where apstatus=3 and onwire='yes'
group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order
by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Unclassified-Offwire	Event wireless unclassified off-wire	event

```

select
    'unclassified' as ap_full_status,
    devid,
    vd,
    ssid,
    bssid,
    manuf,
    channel,
    radioband,
    from_dtime(
        max(last_seen)
    ) as last_seen,
    detectionmethod,
    snclosest,
    'no' as on_wire
from
    ###({{FGT_DATASET_EVENT_WIRELESS_ROGUE_OFFWIRE}})### t where apstatus=0 and onwire='no'
group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order
by last_seen desc

```

Dataset Name	Description	Log Category
event-Wireless-Unclassified-Onwire	Event wireless unclassified on-wire	event

```
select
  'unclassified' as ap_full_status,
  devid,
  vd,
  ssid,
  bssid,
  manuf,
  channel,
  radioband,
  from_dtime(
    max(last_seen)
  ) as last_seen,
  detectionmethod,
  snclosest,
  'yes' as on_wire
from
  ###({{FGT_DATASET_EVENT_WIRELESS_ROGUE_ONWIRE}})### t where apstatus=0 and onwire='yes'
group by devid, vd, ssid, bssid, manuf, channel, radioband, detectionmethod, snclosest order
by last_seen desc
```

Dataset Name	Description	Log Category
default-Top-IPSEC-Vpn-Dial-Up-User-By-Bandwidth	Default top IPsec VPN dial up user by bandwidth usage	event

```
select
  coalesce(
    xauthuser_agg,
    user_agg,
    ipstr(`remip`)
  ) as user_src,
  from_dtime(
    min(s_time)
  ) as start_time,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  (
    select
      devid,
      vd,
      string_agg(distinct xauthuser_agg, ' ') as xauthuser_agg,
      string_agg(distinct user_agg, ' ') as user_agg,
      remip,
      tunnelid,
      min(s_time) as s_time,
      max(e_time) as e_time,
      (
        case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
        max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
      ) as bandwidth,
```

```

(
    case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
) as traffic_in,
(
    case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
) as traffic_out
from
###({{FGT_DATASET_EVENT_VPN_DIAL_UP_IPSEC_BANDWIDTH}})### t group by devid, vd, remip,
tunnelid) tt group by user_src having sum(bandwidth)>0 order by bandwidth desc

```

Dataset Name	Description	Log Category
default-Top-Sources-Of-SSL-VPN-Tunnels-By-Bandwidth	Default top sources of SSL VPN tunnels by bandwidth usage	event

```

select
    remip as remote_ip,
    sum(bandwidth) as bandwidth
from
(
    select
        devid,
        vd,
        remip,
        tunnelid,
        (
            case when min(s_time)= max(e_time) then max(max_traffic_in) else max(max_traffic_in)-
min(min_traffic_in) end
        ) as traffic_in,
        (
            case when min(s_time)= max(e_time) then max(max_traffic_out) else max(max_traffic_
out)- min(min_traffic_out) end
        ) as traffic_out,
        (
            case when min(s_time)= max(e_time) then max(max_traffic_in)+ max(max_traffic_out) else
max(max_traffic_in)- min(min_traffic_in)+ max(max_traffic_out)- min(min_traffic_out) end
        ) as bandwidth
    from
        ###({{FGT_DATASET_EVENT_VPN_TRAFFIC_USAGE}})### t where t_type like 'ssl%' group by
devid, vd, remip, tunnelid) tt group by remote_ip having sum(traffic_in+traffic_out)>0 order
by bandwidth desc

```

Dataset Name	Description	Log Category
webfilter-Web-Activity-Summary-By-Requests	Webfilter web activity summary by requests	webfilter

```

select
    $flex_timescale(timestamp) as hodesk,
    sum(allowed_request) as allowed_request,
    sum(blocked_request) as blocked_request
from
    ###(select $flex_timestamp as timestamp, sum(case when action!='blocked' then 1 else 0 end)
as allowed_request, sum(case when action='blocked' then 1 else 0 end) as blocked_request from

```

```
$log where $filter and (eventtype is null or logver>=502000000) group by timestamp
/*SkipSTART*/order by timestamp desc/*SkipEND*/)### t group by hosex order by hosex
```

Dataset Name	Description	Log Category
traffic-Browsing-Time-Summary	Traffic browsing time summary	traffic

```
select
  $flex_timescale(timestamp) as hosex,
  cast(
    ebtr_value(
      ebtr_agg_flat(browsetime),
      null,
      $timespan
    ) / 60.0 as decimal(18, 2)
  ) as browsetime
from
  ###({{FGT_DATABASE_TRAFFIC_BROWSE_TIME}})### t group by hosex order by hosex
```

Dataset Name	Description	Log Category
traffic-Browsing-Time-Summary-Enhanced	Traffic browsing time summary enhanced	traffic

```
select
  $flex_timescale(timestamp) as hosex,
  cast(
    ebtr_value(
      ebtr_agg_flat(browsetime),
      null,
      $timespan
    ) / 60.0 as decimal(18, 2)
  ) as browsetime
from
  ###({{FGT_DATABASE_TRAFFIC_BROWSE_TIME}})### t group by hosex order by hosex
```

Dataset Name	Description	Log Category
webfilter-Top-Web-Users-By-Blocked-Requests	Webfilter top web users by blocked requests	webfilter

```
select
  user_src,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as requests from
$log where $filter and (eventtype is null or logver>=502000000) and coalesce(nullifna(`user`),
ipstr(`srcip`)) is not null and action='blocked' group by user_src /*SkipSTART*/order by
requests desc/*SkipEND*/)### t group by user_src order by requests desc
```

Dataset Name	Description	Log Category
webfilter-Top-Web-Users-By-Allowed-Requests	Webfilter top web users by allowed requests	webfilter

```
select
  user_src,
  sum(requests) as requests
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as requests from
$log where $filter and (eventtype is null or logver>=502000000) and coalesce(nullifna(`user`),
ipstr(`srcip`)) is not null and action!='blocked' group by user_src /*SkipSTART*/order by
requests desc/*SkipEND*/)### t group by user_src order by requests desc
```

Dataset Name	Description	Log Category
traffic-Top-Web-Users-By-Browsing-Time	Traffic top web users by browsing time	traffic

```
select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###(select user_src, ebtr_agg_flat(browsetime) as browsetime, sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in, sum(traffic_out) as traffic_out from (select coalesce(nullifna
(`user`), ipstr(`srcip`)) as user_src, ebtr_agg_flat($browse_time) as browsetime, sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in,
sum(coalesce(sentbyte, 0)) as traffic_out from $log where $filter and $browse_time is not null
group by user_src) t group by user_src /*SkipSTART*/order by ebtr_value(ebtr_agg_flat(brow-
setime), null, null) desc/*SkipEND*/)### t group by user_src order by browsetime desc
```

Dataset Name	Description	Log Category
webfilter-Top-Blocked-Web-Sites-By-Requests	Webfilter top blocked web sites by requests	webfilter

```
select
  domain,
  catdesc,
  sum(requests) as requests
from
  ###(select hostname as domain, catdesc, count(*) as requests from $log where $filter and
(eventtype is null or logver>=502000000) and hostname is not null and catdesc is not null and
action='blocked' group by domain, catdesc /*SkipSTART*/order by requests desc/*SkipEND*/)### t
group by domain, catdesc order by requests desc
```

Dataset Name	Description	Log Category
webfilter-Top-Allowed-Web-Sites-By-Requests	Webfilter top allowed web sites by requests	webfilter

```
select
  domain,
  string_agg(distinct catdesc, ', ') as agg_catdesc,
```



```

sum(requests) as requests
from
###(select hostname as domain, catdesc, count(*) as requests from $log where $filter and
(eventtype is null or logver>=502000000) and hostname is not null and catdesc is not null and
action!='blocked' group by domain, catdesc /*SkipSTART*/order by requests desc/*SkipEND*/)###
t group by domain order by requests desc

```

Dataset Name	Description	Log Category
webfilter-Top-Video-Streaming-Websites-By-Bandwidth	Webfilter top video streaming websites by bandwidth usage	webfilter

```

select
domain,
sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in,
sum(traffic_out) as traffic_out
from
###(select coalesce(nullifna(root_domain(hostname)), 'other') as domain, sum(coalesce(sent-
byte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, sum(coalesce(rcvdbyte, 0)) as traffic_in, sum
(coalesce(sentbyte, 0)) as traffic_out from $log-traffic where $filter and (logflag&1>0) and
(countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent in
('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) and catdesc
in ('Streaming Media and Download') group by domain having sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0))>0 /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t group by domain order
by bandwidth desc

```

Dataset Name	Description	Log Category
webfilter-Top-Blocked-Web-Categories	Webfilter top blocked web categories	webfilter

```

select
catdesc,
sum(requests) as requests
from
###(select catdesc, count(*) as requests from $log-webfilter where $filter and (eventtype is
null or logver>=502000000) and catdesc is not null and action='blocked' group by catdesc
/*SkipSTART*/order by requests desc/*SkipEND*/)### t group by catdesc order by requests desc

```

Dataset Name	Description	Log Category
webfilter-Top-Allowed-Web-Categories	Webfilter top allowed web categories	webfilter

```

select
catdesc,
sum(requests) as requests
from
###(select catdesc, count(*) as requests from $log-webfilter where $filter and (eventtype is
null or logver>=502000000) and catdesc is not null and action!='blocked' group by catdesc
/*SkipSTART*/order by requests desc/*SkipEND*/)### t group by catdesc order by requests desc

```

Dataset Name	Description	Log Category
traffic-Top-50-Sites-By-Browsing-Time	Traffic top sites by browsing time	traffic

```

select
  hostname,
  string_agg(distinct catdesc, ', ') as agg_catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###({{FGT_DATASET_TRAFFIC_TOP_SITES_BY_EB_TIME}})### t group by hostname order by browsetime
desc

```

Dataset Name	Description	Log Category
traffic-Top-50-Sites-By-Browsing-Time-Enhanced	Traffic top sites by browsing time enhanced	traffic

```

select
  hostname,
  string_agg(distinct catdesc, ', ') as agg_catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###({{FGT_DATASET_TRAFFIC_TOP_SITES_BY_EB_TIME}})### t group by hostname order by browsetime
desc

```

Dataset Name	Description	Log Category
traffic-Top-10-Categories-By-Browsing-Time	Traffic top category by browsing time	traffic

```

select
  catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_TOP_CATS_BY_EB_TIME}})### t group by catdesc order by browsetime
desc

```

Dataset Name	Description	Log Category
traffic-Top-10-Categories-By-Browsing-Time-Enhanced	Traffic top category by browsing time enhanced	traffic

```

select
  catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_TOP_CATS_BY_EB_TIME}})### t group by catdesc order by browsetime
desc

```

Dataset Name	Description	Log Category
traffic-Top-Destination-Countries-By-Browsing-Time	Traffic top destination countries by browsing time	traffic

```

select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###({{FGT_DATASET_TRAFFIC_TOP_DST_COUNTRY_BY_EB_TIME}})### t group by dstcountry order by
browsetime desc

```

Dataset Name	Description	Log Category
traffic-Top-Destination-Countries-By-Browsing-Time-Enhanced	Traffic top destination countries by browsing time enhanced	traffic

```

select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###({{FGT_DATASET_TRAFFIC_TOP_DST_COUNTRY_BY_EB_TIME}})### t group by dstcountry order by
browsetime desc

```

Dataset Name	Description	Log Category
webfilter-Top-Search-Phrases	Webfilter top search phrases	webfilter

```

select
  keyword,

```

```

count(*) as requests
from
    $log
where
    $filter
    and keyword is not null
group by
    keyword
order by
    requests desc

```

Dataset Name	Description	Log Category
Top-10-Users-Browsing-Time	Estimated browsing time	traffic

```

select
    user_src,
    ebtr_value(
        ebtr_agg_flat(browsetime),
        null,
        $timespan
    ) as browsetime
from
    ###({{FGT_DATASET_TRAFFIC_EB_TIME}})### t group by user_src order by browsetime desc

```

Dataset Name	Description	Log Category
Top-10-Users-Browsing-Time-Enhanced	Estimated browsing time enhanced	traffic

```

select
    user_src,
    ebtr_value(
        ebtr_agg_flat(browsetime),
        null,
        $timespan
    ) as browsetime
from
    ###({{FGT_DATASET_TRAFFIC_EB_TIME}})### t group by user_src order by browsetime desc

```

Dataset Name	Description	Log Category
Estimated-Browsing-Time	Estimated browsing time	traffic

```

select
    user_src,
    ebtr_value(
        ebtr_agg_flat(browsetime),
        null,
        $timespan
    ) as browsetime
from
    ###({{FGT_DATASET_TRAFFIC_EB_TIME}})### t group by user_src order by browsetime desc

```

Dataset Name	Description	Log Category
Estimated-Browsing-Time-Enhanced	Estimated browsing time enhanced	traffic

```
select
  user_src,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###({{FGT_DATASET_TRAFFIC_EB_TIME}})### t group by user_src order by browsetime desc
```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Bandwidth	Top access point by bandwidth usage	traffic

```
select
  coalesce(ap, srcintf) as ap_srcintf,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and (
    srcssid is not null
    or dstssid is not null
  )
group by
  ap_srcintf
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )& gt; 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Client	Top access point by client	traffic

```
select
  ap_srcintf as srcintf,
  count(distinct srcmac) as totalnum
from
  ###(select coalesce(ap, srcintf) as ap_srcintf, srcssid, osname, srcswversion, get_devtype
  (srcswversion, osname, devtype) as devtype_new, srcmac, count(*) as subtotal from $log where
  $filter and (logflag&1>0) and (srcssid is not null or dstssid is not null) and srcmac is not
  null group by ap_srcintf, srcssid, osname, srcswversion, devtype_new, srcmac order by subtotal
  desc)### t group by srcintf order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Top-SSID-By-Bandwidth	Top SSIDs by bandwidth usage	traffic

```
select
  srcssid,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and srcssid is not null
group by
  srcssid
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) > 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
wifi-Top-SSID-By-Client	Top SSIDs by client	traffic

```
select
  srcssid,
  count(distinct srcmac) as totalnum
from
  ###({{FGT_DATASET_TRAFFIC_TOP_WIFI_CLIENT}})### t where srcssid is not null group by srcssid
order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Top-App-By-Bandwidth	Top WiFi applications by bandwidth usage	traffic

```
select
  appid,
  app,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and (
    srcssid is not null
```

```

        or dstssid is not null
    )
    and nullifna(app) is not null
group by
    appid,
    app
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) > 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-Client-By-Bandwidth	Top WiFi client by bandwidth usage	traffic

```

select
    (
        coalesce(srcname, srcmac, 'unknown') || ' (' || get_devtype(srcswversion, osname, devtype)
|| ', ' || coalesce(osname, '') || (
            case when srcswversion is null then '' else ' ' || srcswversion end
        ) || ')'
    ) as client,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and (
        srcssid is not null
        or dstssid is not null
    )
group by
    client
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) > 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-OS-By-Bandwidth	Top WiFi os by bandwidth usage	traffic

```

select
    (
        coalesce(osname, 'unknown') || ' ' || coalesce(srcswversion, '')
    ) as os,
    sum(

```

```

        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and (
        srcssid is not null
        or dstssid is not null
    )
group by
    os
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-OS-By-WiFi-Client	Top WiFi os by WiFi client	traffic

```

select
    (
        coalesce(osname, 'unknown') || ' ' || coalesce(osversion, '')
    ) as os,
    count(distinct srcmac) as totalnum
from
    ###({{FGT_DATASET_TRAFFIC_TOP_WIFI_CLIENT}})### t group by os order by totalnum desc

```

Dataset Name	Description	Log Category
wifi-Top-Device-By-Bandwidth	Top WiFi device by bandwidth usage	traffic

```

select
    get_devtype(srcswversion, osname, devtype) as devtype_new,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and (
        srcssid is not null
        or dstssid is not null
    )
    and devtype is not null
group by

```



```

    devtype_new
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
wifi-Top-Device-By-Client	Top WiFi device by client	traffic

```

select
    devtype_new,
    count(distinct srcmac) as totalnum
from
    ###(select srcintf, srcssid, osname, srcswversion, get_devtype(srcswversion, osname, dev-
type) as devtype_new, srcmac, count(*) as subtotal from $log where $filter and (logflag&1>0)
and (srcssid is not null or dstssid is not null) and srcmac is not null group by srcintf, src-
ssid, osname, srcswversion, devtype, srcmac order by subtotal desc)### t where devtype_new is
not null group by devtype_new order by totalnum desc

```

Dataset Name	Description	Log Category
wifi-Overall-Traffic	WiFi overall traffic	traffic

```

select
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and (
        srcssid is not null
        or dstssid is not null
    )

```

Dataset Name	Description	Log Category
wifi-Num-Distinct-Client	WiFi num distinct client	traffic

```

select
    count(distinct srcmac) as totalnum
from
    ###(select srcintf, srcssid, osname, srcswversion, get_devtype(srcswversion, osname, dev-
type) as devtype_new, srcmac, count(*) as subtotal from $log where $filter and (logflag&1>0)
and (srcssid is not null or dstssid is not null) and srcmac is not null group by srcintf, src-
ssid, osname, srcswversion, devtype_new, srcmac order by subtotal desc)### t

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Bandwidth-and-Sessions	Top subnets by application bandwidth	traffic

```

select
  ip_subnet(`srcip`) as subnet,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  subnet
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Application-Bandwidth	Top applications by bandwidth	traffic

```

select
  ip_subnet(`srcip`) as subnet,
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  subnet,
  app_group
having

```

```

sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
)& gt; 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Application-Sessions	Top applications by sessions	traffic

```

select
    ip_subnet(`srcip`) as subnet,
    app_group_name(app) as app_group,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(app) is not null
group by
    subnet,
    app_group
order by
    sessions desc

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Website-Bandwidth	Top websites and web category by bandwidth	traffic

```

select
    subnet,
    website,
    sum(bandwidth) as bandwidth
from
    ###(select ip_subnet(`srcip`) as subnet, hostname as website, sum(coalesce(sentbyte, 0)+
    coalesce(rcvbyte, 0)) as bandwidth from $log-traffic where $filter and hostname is not null
    and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (hostname is
    not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-
    filter')))) group by subnet, website order by bandwidth desc)### t group by subnet, website
    order by bandwidth desc

```

Dataset Name	Description	Log Category
Top30-Subnets-by-Website-Hits	Top websites and web category by sessions	webfilter

```

select
    subnet,
    website,
    sum(hits) as hits
from
    ###(select ip_subnet(`srcip`) as subnet, hostname as website, count(*) as hits from $log

```

where \$filter and hostname is not null and (eventtype is null or logver>=502000000) group by subnet, website order by hits desc)### t group by subnet, website order by hits desc

Dataset Name	Description	Log Category
Top30-Subnets-with-Top10-User-by-Bandwidth	Top users by bandwidth	traffic

```
select
  ip_subnet(`srcip`) as subnet,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and srcip is not null
group by
  subnet,
  user_src
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
Top30-Subnets-with-Top10-User-by-Sessions	Top users by sessions	traffic

```
select
  ip_subnet(`srcip`) as subnet,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
```

```
group by
    subnet,
    user_src
order by
    sessions desc
```

Dataset Name	Description	Log Category
app-Top-20-Category-and-Applications-by-Bandwidth	Top category and applications by bandwidth usage	traffic

```
select
    appcat,
    app,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
group by
    appcat,
    app
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc
```

Dataset Name	Description	Log Category
app-Top-20-Category-and-Applications-by-Session	Top category and applications by session	traffic

```
select
    appcat,
    app,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
group by
    appcat,
    app
order by
    sessions desc
```

Dataset Name	Description	Log Category
app-Top-500-Allowed-Applications-by-Bandwidth	Top allowed applications by bandwidth usage	traffic

```

select
  from_itime(itime) as timestamp,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  appcat,
  app,
  coalesce(
    root_domain(hostname),
    ipstr(dstip)
  ) as destination,
  sum(
    coalesce(`sentbyte`, 0)+ coalesce(`rcvdbyte`, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and action in ('accept', 'close', 'timeout')
group by
  timestamp,
  user_src,
  appcat,
  app,
  destination
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
app-Top-500-Blocked-Applications-by-Session	Top blocked applications by session	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  appcat,
  app,
  count(*) as sessions
from
  $log
where
  $filter

```

```

and (
    logflag&1>0
)
and action in (
    'deny', 'blocked', 'reset', 'dropped'
)
group by
    user_src,
    appcat,
    app
order by
    sessions desc

```

Dataset Name	Description	Log Category
web-Detailed-Website-Browsing-Log	Web detailed website browsing log	traffic

```

select
    from_dtime(dtime) as timestamp,
    catdesc,
    hostname as website,
    status,
    sum(bandwidth) as bandwidth
from
    ###(select dtime, catdesc, hostname, cast(utmaction as text) as status, sum(coalesce(sent-
byte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and hostname is
not null and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (host-
name is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block',
'script-filter')))) group by dtime, catdesc, hostname, utmaction order by dtime desc)### t
group by dtime, catdesc, website, status order by dtime desc

```

Dataset Name	Description	Log Category
web-Hourly-Category-and-Website-Hits-Action	Web hourly category and website hits action	webfilter

```

select
    hod,
    website,
    sum(hits) as hits
from
    ###(select $hour_of_day as hod, (hostname || ' (' || coalesce(`catdesc`, 'Unknown') || ')')
as website , count(*) as hits from $log where $filter and hostname is not null and (eventtype
is null or logver>=502000000) group by hod, website order by hod, hits desc)### t group by
hod, website order by hod, hits desc

```

Dataset Name	Description	Log Category
web-Top-20-Category-and-Websites-by-Bandwidth	Web top category and websites by bandwidth usage	traffic

```

select
    website,
    catdesc,
    sum(bandwidth) as bandwidth
from

```

```
###(select hostname as website, catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as
bandwidth from $log-traffic where $filter and hostname is not null and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent in ('web-
filter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by website,
catdesc order by bandwidth desc)### t group by website, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
web-Top-20-Category-and-Websites-by-Session	Web top category and websites by session	webfilter

```
select
    website,
    catdesc,
    sum(sessions) as hits
from
    ###({FGT_DATASET_WEBFILTER_TOP_WEBSITES})### t group by website, catdesc order by hits
desc
```

Dataset Name	Description	Log Category
web-Top-500-Website-Sessions-by-Bandwidth	Web top website sessions by bandwidth usage	traffic

```
select
    from_dtime(dtime) as timestamp,
    user_src,
    website,
    catdesc,
    cast(
        sum(dura)/ 60 as decimal(18, 2)
    ) as dura,
    sum(bandwidth) as bandwidth
from
    ###(select dtime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
user_src, hostname as website, catdesc, sum(coalesce(duration, 0)) as dura, sum(coalesce(sent-
byte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter and hostname is not null
and (logflag&1>0) and action in ('accept','close','timeout') group by dtime, user_src, web-
site, catdesc having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth
desc)### t group by dtime, user_src, website, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
web-Top-500-User-Visted-Websites-by-Bandwidth	Web top user visted websites by bandwidth usage	traffic

```
select
    website,
    catdesc,
    sum(bandwidth) as bandwidth
from
    ###(select hostname as website, catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as
bandwidth from $log-traffic where $filter and hostname is not null and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent in ('web-
filter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by hostname,
```



```
catdesc having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc)###
t group by website, catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
web-Top-500-User-Visted-Websites-by-Session	Web top user visted websites by session	webfilter

```
select
  website,
  catdesc,
  sum(sessions) as sessions
from
  ###({{FGT_DATASET_WEBFILTER_TOP_WEBSITES}})### t group by website, catdesc order by sessions
desc
```

Dataset Name	Description	Log Category
fct-Installed-Feature-Summary	Installed Feature Summary	fct-event

```
select
  clientfeature,
  count(distinct fctuid) as totalnum
from
  ###({{FCT_DATASET_EP_STATUS}})### t where clientfeature is not null group by clientfeature
order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Device-by-Operating-System	Device by OS	fct-event

```
select
  os_short as os,
  count(distinct fctuid) as totalnum
from
  ###({{FCT_DATASET_EP_STATUS}})### t where os_short is not null group by os order by totalnum
desc
```

Dataset Name	Description	Log Category
fct-Installed-FortiClient-Version	FortiClient Version	fct-event

```
select
  fctver as fctver_short,
  count(distinct fctuid) as totalnum
from
  ###({{FCT_DATASET_EP_STATUS}})### t where fctver is not null group by fctver order by total-
num desc
```

Dataset Name	Description	Log Category
fct-Endpoint-Profile-Deployment	Endpoint Profile Deployment	fct-event

```
select
  profile,
  count(distinct fctuid) as totalnum
```

```
from
  ###(select uid as fctuid, coalesce(nullifna(usingpolicy), 'No Profile') as profile from $log
where $filter group by uid, profile)### t group by profile order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Client-Summary	Client Summary	fct-event

```
select
  hostname,
  deviceip,
  os_short as os,
  profile,
  fctver,
  from_etime(
    max(etime)
  ) as last_seen
from
  ###(select hostname, deviceip, regexp_replace(os, '\\(build.*', '') as os_short, nullifna
(usingpolicy) as profile, fctver, max(etime) as etime from $log where $filter and os is not
null group by hostname, deviceip, os_short, profile, fctver order by etime desc)### t group by
hostname, deviceip, os, profile, fctver order by last_seen desc
```

Dataset Name	Description	Log Category
fct-Total-Threats-Found	Total Threats Found	fct-traffic

```
select
  utmevent_s as utmevent,
  count(distinct threat) as totalnum
from
  ###(select coalesce(nullifna(lower(utmevent)), 'unknown') as utmevent_s, threat from $log
where $filter and threat is not null and utmaction='blocked' group by utmevent_s, threat)### t
group by utmevent order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Top10-AV-Threats-Detected	Top AV Threats Detected	fct-traffic

```
select
  threat,
  sum(totalnum) as totalnum
from
  (
    (
      select
        threat,
        sum(totalnum) as totalnum
      from
        ###(select threat, count(*) as totalnum from $log-fct-traffic where $filter and threat
is not null and lower(utmevent)='antivirus' group by threat order by totalnum desc)### t group
by threat) union all (select threat, sum(totalnum) as totalnum from ###(select virus as
threat, count(*) as totalnum from $log-fct-event where $filter and virus is not null group by
threat order by totalnum desc)### t group by threat)) t group by threat order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Top10-Infected-Devices-with-Botnet	Top Infected Devices with Botnet	fct-traffic

```
select
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and hostname is not null
  and lower(utmevent) in ('webfilter', 'appfirewall')
  and lower(threat) like '%botnet%'
group by
  hostname
order by
  totalnum desc
```

Dataset Name	Description	Log Category
fct-Top10-Infected-Devices-with-Virus-Malware	Top Infected Devices with Virus Malware	fct-traffic

```
select
  hostname,
  sum(totalnum) as totalnum
from
  (
    (
      select
        hostname,
        sum(totalnum) as totalnum
      from
        ###(select hostname, count(*) as totalnum from $log-fct-traffic where $filter and host-
name is not null and lower(utmevent) in ('antivirus', 'antimalware') group by hostname order
by totalnum desc)### t group by hostname) union all (select hostname, sum(totalnum) as total-
num from ###(select hostname, count(*) as totalnum from $log-fct-event where $filter and host-
name is not null and virus is not null group by hostname order by totalnum desc)### t group by
hostname)) t group by hostname order by totalnum desc
```

Dataset Name	Description	Log Category
fct-All-Antivirus-Antimalware-Detections	All Antivirus and Antimalware Detections	fct-traffic

```
select
  threat,
  hostname,
  hostuser,
  utmaction,
  from_dtime(
    max(dtime)
  ) as last_seen
```

```

from
(
(
select
threat,
hostname,
hostuser,
utmaction,
max(dtime) as dtime
from
###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, utmac-
tion, max(dtime) as dtime from $log-fct-traffic where $filter and lower(utmevent) in ('anti-
virus', 'antimalware')) group by threat, hostname, hostuser, utmaction order by threat)### t
group by threat, hostname, hostuser, utmaction) union all (select threat, hostname, hostuser,
utmaction, max(dtime) as dtime from ###(select virus as threat, hostname, coalesce(nullifna
(`user`), 'Unknown') as hostuser, action as utmaction, max(dtime) as dtime from $log-fct-event
where $filter and (logflag is null or logflag&8=0) and virus is not null group by threat, host-
name, hostuser, utmaction order by threat)### t group by threat, hostname, hostuser, utmac-
tion)) t group by threat, hostname, hostuser, utmaction order by threat

```

Dataset Name	Description	Log Category
fct-Web-Filter-Violations	Web Filter Violations	fct-traffic

```

select
hostuser,
hostname,
string_agg(distinct remotename, ',') as remotename,
utmaction,
sum(total) as totalnum,
from_dtime(
max(dtime)
) as last_seen
from
###(select remotename, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, utmac-
tion, count(*) as total, max(dtime) as dtime from $log where $filter and lower(utmevent)-
='webfilter' and utmaction='blocked' group by remotename, hostname, hostuser, utmaction order
by total desc)### t group by hostuser, hostname, utmaction order by totalnum desc

```

Dataset Name	Description	Log Category
fct-Application-Firewall	Application Firewall	fct-traffic

```

select
threat,
hostname,
hostuser,
utmaction,
from_dtime(
max(dtime)
) as last_seen
from
###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, utmaction,
max(dtime) as dtime from $log where $filter and lower(utmevent)='appfirewall' and utmac-
tion='blocked' group by threat, hostname, hostuser, utmaction order by dtime desc)### t1 left

```

```
join app_mdata t2 on t1.threat=t2.name group by threat, risk, hostname, hostuser, utmaction
order by risk desc
```

Dataset Name	Description	Log Category
fct-Errors-and-Alerts	Errors and Alerts	fct-event

```
select
  msg,
  hostname,
  hostuser,
  from_dtime(
    max(dtime)
  ) as last_seen
from
  ###(select msg, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, max(dtime) as
  dtime from $log where $filter and level in ('error', 'alert') group by msg, hostname, hostuser
  order by dtime desc)### t group by msg, hostname, hostuser order by last_seen desc
```

Dataset Name	Description	Log Category
fct-Threats-by-Top-Devices	Threats by Top Devices	fct-traffic

```
select
  hostname,
  count(*) as totalnum
from
  $log
where
  $filter
  and hostname is not null
  and utmevent is not null
  and utmaction = 'blocked'
group by
  hostname
order by
  totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Device-Vulnerabilities	Vulnerabilities Detected by User/Device	fct-netscan

```
select
  vulnseverity,
  (
    CASE vulnseverity WHEN 'Critical' THEN 5 WHEN 'High' THEN 4 WHEN 'Medium' THEN 3 WHEN
    'Info' THEN 2 WHEN 'Low' THEN 1 ELSE 0 END
  ) as severity_number,
  count(distinct vulnname) as vuln_num
from
  ###(select vulnseverity, devid, vulnname from $log where $filter and nullifna(vulnseverity)
  is not null and nullifna(vulnname) is not null group by vulnseverity, vulnname, devid)### t
  group by vulnseverity order by severity_number desc
```

Dataset Name	Description	Log Category
fct-vuln-Category-Type-Vulnerabilities	Vulnerabilities Detected by Category Type	fct-netscan

```
select
  vulncat,
  count(distinct vulnname) as totalnum
from
  ###(select vulncat, vulnname from $log where $filter and nullifna(vulncat) is not null and
  nullifna(vulnname) is not null group by vulncat, vulnname)### t group by vulncat order by
  totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerabilities-by-OS	Fortidient Vulnerabilities by OS	fct-netscan

```
select
  os,
  count(distinct vulnname) as totalnum
from
  ###(select os, vulnname from $log where $filter and nullifna(os) is not null and nullifna
  (vulnname) is not null group by os, vulnname)### t group by os order by totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerabilities-by-Risk-Level	Number Vulnerability by Device and Risk Level	fct-netscan

```
select
  vulnseverity,
  (
    case when vulnseverity = 'Critical' then 5 when vulnseverity = 'High' then 4 when
  vulnseverity = 'Medium' then 3 when vulnseverity = 'Low' then 2 when vulnseverity = 'Info'
  then 1 else 0 end
  ) as severity_number,
  count(distinct vulnname) as vuln_num,
  count(distinct devid) as dev_num
from
  ###(select vulnseverity, devid, vulnname from $log where $filter and nullifna(vulnseverity)
  is not null and nullifna(vulnname) is not null and nullifna(devid) is not null group by
  vulnseverity, vulnname, devid)### t group by vulnseverity order by dev_num desc, severity_num-
  ber desc
```

Dataset Name	Description	Log Category
fct-vuln-Device-by-Risk-Level	Number Vulnerability by Device and Risk Level	fct-netscan

```
select
  vulnseverity,
  (
    case when vulnseverity = 'Critical' then 5 when vulnseverity = 'High' then 4 when
  vulnseverity = 'Medium' then 3 when vulnseverity = 'Low' then 2 when vulnseverity = 'Info'
  then 1 else 0 end
  ) as severity_number,
  count(distinct vulnname) as vuln_num,
  count(distinct devid) as dev_num
from
```

```
###(select vulnseverity, devid, vulnname from $log where $filter and nullifna(vulnseverity)
is not null and nullifna(vulnname) is not null and nullifna(devid) is not null group by
vulnseverity, vulnname, devid)### t group by vulnseverity order by dev_num desc, severity_num-
ber desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerability-Trend	Vulnerability Trend	fct-netscan

```
select
  $flex_timescale(timestamp) as hodesk,
  count(distinct vulnname) as total_num
from
  ###(select $flex_timestamp as timestamp, vulnname from $log where $filter and nullifna(vul-
nname) is not null group by timestamp, vulnname order by timestamp desc)### t group by hodesk
order by hodesk
```

Dataset Name	Description	Log Category
fct-vuln-Details-by-Risk-Level-Device	Vulnerability Details for Each Risk Level by Device	fct-netscan

```
select
  hostname,
  os,
  vulnseverity,
  count(distinct vulnname) as vuln_num,
  count(distinct products) as products,
  count(distinct cve_id) as cve_count
from
  ###(select hostname, os, vulnname, vulnseverity, vulnid from $log where $filter and vulnname
is not null and vulnseverity is not null and hostname is not null group by hostname, os, vul-
nname, vulnseverity, vulnid)### t1 left join fct_mdata t2 on t1.vulnid=t2.vid::int group by
hostname, os, vulnseverity order by vuln_num desc, hostname
```

Dataset Name	Description	Log Category
fct-vuln-Details-by-Device-User	Vulnerability Details by Device User	fct-netscan

```
select
  hostname,
  (
    '<div style=word-break:normal>' || vulnname || '</div>'
  ) as vulnname,
  vulnseverity,
  vulncat,
  string_agg(distinct products, ',') as products,
  string_agg(distinct cve_id, ',') as cve_list,
  (
    '<a href=' || String_agg(DISTINCT vendor_link, ',') || '>Remediation Info</a>'
  ) as vendor_link
from
  ###(select hostname, vulnname, vulnseverity, vulncat, vulnid from $log where $filter and vul-
nname is not null and hostname is not null group by hostname, vulnname, vulnseverity, vulncat,
vulnid)### t1 inner join fct_mdata t2 on t1.vulnid=t2.vid::int group by hostname, vulnname,
vulnseverity, vulncat order by hostname
```

Dataset Name	Description	Log Category
fct-vuln-Remediation-by-Device	Remediate The Vulnerability Found on Device	fct-netscan

```
select
  hostname,
  (
    '<div style=word-break:normal>' || vulnname || '</div>'
  ) as vulnname,
  vulnseverity,
  string_agg(distinct vendor_link, ',') as vendor_link
from
  ###(select hostname, vulnname, vulnseverity, vulnid from $log where $filter and vulnname is
not null and hostname is not null group by hostname, vulnname, vulnseverity, vulnid)### t1
inner join fct_mdata t2 on t1.vulnid=t2.vid::int group by hostname, vulnname, vulnseverity
order by vulnseverity, hostname
```

Dataset Name	Description	Log Category
fct-vuln-Remediation-by-Vulnerability	Remediation by Vulnerability	fct-netscan

```
select
  (
    '<b>' || vulnname || '</b><br><br>' || 'Description<br><div style=word-break:normal>'
|| description || '</div><br><br>' || 'Affected Products<br>' || products || '<br><br>'
|| 'Impact<br>' || impact || '<br><br>' || 'Recommended Actions<br>' || vendor_link ||
'<br><br><br>'
  ) as remediation
from
  ###(select devid, vulnname, vulnseverity, (case vulnseverity when 'low' then 1 when 'info'
then 2 when 'medium' then 3 when 'high' then 4 when 'critical' then 5 else 0 end) as severity_
level, vulnid from $log where $filter and vulnname is not null group by devid, vulnname,
vulnseverity, severity_level, vulnid order by severity_level)### t1 inner join fct_mdata t2 on
t1.vulnid=t2.vid::int group by remediation order by remediation
```

Dataset Name	Description	Log Category
fct-vuln-Top-30-Targeted-High-Risk-Vulnerabilities	Top 30 Targeted High Risk Vulnerabilities	fct-netscan

```
select
  t3.cve_id,
  score,
  string_agg(distinct products, ',') as products,
  (
    '<a href=' || String_agg(vendor_link, ',') || '>Mitigation Infomation</a>'
  ) as vendor_link
from
  ###(select vulnid from $log where $filter group by vulnid)### t1 inner join fct_mdata t2 on
t2.vid=t1.vulnid::text inner join fct_cve_score t3 on strpos(t2.cve_id, t3.cve_id) > 0 group
by t3.cve_id, score order by score desc, t3.cve_id
```

Dataset Name	Description	Log Category
fct-Endpoints-by-FortiGate	Endpoints by FortiGate	fct-event



```
select
    fgtserial,
    count(distinct fctuid) as totalnum
from
    ###({FCT_DATASET_EP_STATUS})### t where fgtserial is not null group by fgtserial order by
totalnum desc
```

Dataset Name	Description	Log Category
fct-Top-Malware-Detections	Top Infected Devices with Malware	fct-traffic

```
select
    hostname,
    fctuid,
    sum(totalnum) as totalnum
from
    (
        (
            select
                hostname,
                fctuid,
                sum(totalnum) as totalnum
            from
                ###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, utmac-
tion, max(dtime) as dtime, uid as fctuid, count(*) as totalnum from $log where $filter and
lower(utmaction) in ('antivirus', 'antimalware') group by threat, hostname, hostuser, utmac-
tion, uid order by threat)### t group by hostname, fctuid) union all (select hostname, fctuid,
sum(totalnum) as totalnum from ###(select virus as threat, hostname, coalesce(nullifna
(`user`), 'Unknown') as hostuser, action as utmaction, max(dtime) as dtime, uid as fctuid,
count(*) as totalnum from $log-fct-event where $filter and (logflag is null or logflag&8=0)
and virus is not null group by threat, hostname, hostuser, utmaction, uid order by threat)###
t group by hostname, fctuid)) t group by hostname, fctuid order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Top10-Malware-Detections	Top 10 Infected Devices with Malware	fct-traffic

```
select
    threat,
    hostname,
    hostuser,
    utmaction,
    fctuid,
    sum(totalnum) as totalnum
from
    (
        (
            select
                threat,
                hostname,
                hostuser,
                utmaction,
                fctuid,
                sum(totalnum) as totalnum
            from
                ###(select threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser,
```

```
utmaction, max(dtime) as dtime, uid as fctuid, count(*) as totalnum from $log where $filter
and lower(utmevent) in ('antivirus', 'antimalware') group by threat, hostname, hostuser, utmac-
tion, uid order by threat)### t group by threat, hostname, hostuser, utmaction, fctuid) union
all (select threat, hostname, hostuser, utmaction, fctuid, sum(totalnum) as totalnum from ###
(select virus as threat, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, action
as utmaction, max(dtime) as dtime, uid as fctuid, count(*) as totalnum from $log-fct-event
where $filter and (logflag is null or logflag&8=0) and virus is not null group by threat, host-
name, hostuser, utmaction, uid order by threat)### t group by threat, hostname, hostuser,
utmaction, fctuid)) t where utmaction != 'pass' group by threat, hostname, hostuser, utmac-
tion, fctuid order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Devices-with-Botnet	Infected Devices with Botnet	fct-traffic

```
select
  threat,
  hostname,
  coalesce(
    nullifna(`user`),
    'Unknown'
  ) as hostuser,
  utmaction,
  uid as fctuid,
  count(*) as totalnum
from
  $log
where
  $filter
  and hostname is not null
  and lower(utmevent) in ('webfilter', 'appfirewall')
  and lower(threat) like '%botnet%'
group by
  threat,
  hostname,
  hostuser,
  utmaction,
  fctuid
order by
  totalnum desc
```

Dataset Name	Description	Log Category
fct-vuln-Vulnerability-by-Hostname	Vulnerability Details for Each Risk Level by Device	fct-netscan

```
select
  hostname,
  os,
  vulnseverity,
  count(distinct vulnname) as vuln_num,
  count(distinct products) as products,
  count(distinct cve_id) as cve_count
from
  ###(select hostname, os, vulnname, vulnseverity, vulnid from $log where $filter and vulnname
is not null and vulnseverity is not null and hostname is not null group by hostname, os, vul-
```

```
nname, vulnseverity, vulnid)### t1 left join fct_mdata t2 on t1.vulnid=t2.vid::int group by
hostname, os, vulnseverity order by vuln_num desc, hostname
```

Dataset Name	Description	Log Category
fct-Users-With-Web-Violations	Web Filter Violations	fct-traffic

```
select
  hostuser,
  hostname,
  string_agg(distinct remotename, ',') as remotename,
  utmaction,
  sum(total) as totalnum,
  from_dtime(
    max(dtime)
  ) as last_seen
from
  ###(select remotename, hostname, coalesce(nullifna(`user`), 'Unknown') as hostuser, utmac-
tion, count(*) as total, max(dtime) as dtime from $log where $filter and lower(utmevent)-
='webfilter' and utmaction='blocked' group by remotename, hostname, hostuser, utmaction order
by total desc)### t group by hostuser, hostname, utmaction order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Compliance-by-FortiGate	FortiClinet Compliance by FortiGate Enforcing	fct-event

```
select
  fgtserial,
  count(distinct fctuid) as totalnum
from
  (
    select
      fgtserial,
      fctuid,
      max(compliance_flag) as compliance_flag
    from
      ###({{FCT_DATASET_EP_STATUS}})### tt group by fgtserial, fctuid) t where compliance_flag
= 1 group by fgtserial order by totalnum desc
```

Dataset Name	Description	Log Category
fct-Compliance-Status	Number of FortiClinets by Compliance Status	fct-event

```
select
  (
    case compliance_flag when 1 then 'Compliant' else 'Non-Compliant' end
  ) as compliance,
  count(distinct fctuid) as totalnum
from
  (
    select
      fctuid,
      max(compliance_flag) as compliance_flag
    from
      ###({{FCT_DATASET_EP_STATUS}})### tt group by fctuid) t group by compliance order by
totalnum desc
```

Dataset Name	Description	Log Category
fct-Non-Compliant-Endpoints	Non-compliant Endpoints	fct-event

```
select
  t1.fgtserial,
  t3.srcintf,
  t2.epname as hostname,
  t2.mac,
  'Non-Compliant' as status
from
  (
    select
      fgtserial,
      fctuid,
      max(compliance_flag) as compliance_flag
    from
      ###({FCT_DATASET_EP_STATUS})### tt group by fgtserial, fctuid) t1 left join $ADOM_
  ENDPOINT t2 on t1.fctuid = t2.fctuid left join $ADOM_EPEU_DEVMAP t3 on t2.epid = t3.epid where
  compliance_flag = 0 group by t1.fctuid, t1.fgtserial, t3.srcintf, t2.epname, t2.mac
```

Dataset Name	Description	Log Category
fct-Traffic-Web-Hits	Web Traffic Trend	fct-traffic

```
select
  $flex_timescale(timestamp) as hodesk,
  sum(requests) as requests
from
  ###(select $flex_timestamp as timestamp, count(*) as requests from $log where $filter and
  lower(utmevent)='webfilter' group by timestamp order by timestamp desc)### t group by hodesk
order by hodesk
```

Dataset Name	Description	Log Category
fct-Traffic-Top-Allowed-Web-Cat	Top Visited Web Categories	fct-traffic

```
select
  category,
  sum(requests) as requests
from
  ###(select fct_webcat(threat) as category, remotename as website, count(*) as requests from
  $log where $filter and direction='outbound' and threat is not null and utmaction='passthrough'
  and lower(utmevent)='webfilter' group by category, website order by requests desc)### t group
  by category order by requests desc
```

Dataset Name	Description	Log Category
fct-Traffic-Top-Allowed-Website	Top Visited Websites	fct-traffic

```
select
  website,
  string_agg(distinct category, ', ') as agg_category,
  sum(requests) as requests
from
  ###(select fct_webcat(threat) as category, remotename as website, count(*) as requests from
```

```
$log where $filter and direction='outbound' and threat is not null and utmaction='passthrough'
and lower(utmevent)='webfilter' group by category, website order by requests desc)### t where
website is not null group by website order by requests desc
```

Dataset Name	Description	Log Category
fct-Traffic-Top-Category-By-Website-Session	Top Web Categories by Website Session	fct-traffic

```
select
  fct_webcat(threat) as category,
  remotename as website,
  count(*) as requests
from
  $log
where
  $filter
  and nullifna(threat) is not null
  and lower(utmevent)= 'webfilter'
group by
  category,
  website
order by
  requests desc
```

Dataset Name	Description	Log Category
fct-Traffic-Top-Web-Users-By-Website	Top Web Users by Website	fct-traffic

```
select
  coalesce(
    nullifna(`user`),
    ipstr(`srcip`)
  ) as user_src,
  remotename as website,
  count(*) as requests
from
  $log
where
  $filter
  and direction = 'outbound'
  and remotename is not null
  and utmaction = 'passthrough'
  and lower(utmevent)= 'webfilter'
group by
  user_src,
  website
order by
  requests desc
```

Dataset Name	Description	Log Category
os-Detect-OS-Count	Detected operation system count	traffic

```
select
  (
```

```

        coalesce(osname, 'Unknown')
    ) as os,
    count(*) as totalnum
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
group by
    os
order by
    totalnum desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Sessions-Table	Drilldown top applications by session count	traffic

```

select
    appid,
    app,
    sum(sessions) as sessions
from
    ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
    user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+-
    coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
    group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
where $filter-drilldown and nullifna(app) is not null group by appid, app order by sessions
desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Sessions-Bar	Drilldown top applications by session count	traffic

```

select
    appid,
    app,
    sum(sessions) as sessions
from
    ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
    user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+-
    coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
    group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
where $filter-drilldown and nullifna(app) is not null group by appid, app order by sessions
desc

```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Bandwidth-Table	Drilldown top applications by bandwidth usage	traffic

```

select
    appid,
    app,
    sum(bandwidth) as bandwidth

```

```
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+
  coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
  group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
  where $filter-drilldown and nullifna(app) is not null group by appid, app having sum(band-
  width)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-App-By-Bandwidth-Bar	Drilldown top applications by bandwidth usage	traffic

```
select
  appid,
  app,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+
  coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
  group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
  where $filter-drilldown and nullifna(app) is not null group by appid, app having sum(band-
  width)>0 order by bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-Destination-By-Sessions-Table	Drilldown top destination by session count	traffic

```
select
  dstip,
  sum(sessions) as sessions
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+
  coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
  group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
  where $filter-drilldown and dstip is not null group by dstip order by sessions desc
```

Dataset Name	Description	Log Category
drilldown-Top-Destination-By-Bandwidth-Table	Drilldown top destination by bandwidth usage	traffic

```
select
  dstip,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+
  coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
  group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
  where $filter-drilldown and dstip is not null group by dstip having sum(bandwidth)>0 order by
  bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Sessions-Table	Drilldown top user by session count	traffic

```
select
  user_src,
  sum(sessions) as sessions
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+
  coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
  group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
  where $filter-drilldown and user_src is not null group by user_src order by sessions desc
```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Sessions-Bar	Drilldown top user by session count	traffic

```
select
  user_src,
  sum(sessions) as sessions
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+
  coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
  group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
  where $filter-drilldown and user_src is not null group by user_src order by sessions desc
```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Bandwidth-Table	Drilldown top user by bandwidth usage	traffic

```
select
  user_src,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+
  coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
  group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
  where $filter-drilldown and user_src is not null group by user_src having sum(bandwidth)>0
  order by bandwidth desc
```

Dataset Name	Description	Log Category
drilldown-Top-User-By-Bandwidth-Bar	Drilldown top user by bandwidth usage	traffic

```
select
  user_src,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as
  user_src, dstip, srcintf, dstintf, policyid, count(*) as sessions, sum(coalesce(sentbyte, 0)+
  coalesce(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0)
  group by appid, app, user_src, dstip, srcintf, dstintf, policyid order by sessions desc)### t
```



where \$filter-drilldown and user\_src is not null group by user\_src having sum(bandwidth)>0  
order by bandwidth desc

Dataset Name	Description	Log Category
drilldown-Top-Web-User-By-Visit-Table	Drilldown top web user by visit	traffic

```
select
  user_src,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
    hostname, count(*) as requests from $log-traffic where $filter-exclude-var and (logflag&1>0)
    and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
    and hostname is not null group by user_src, hostname order by requests desc)### union all ###
    (select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests
    from $log-webfilter where $filter-exclude-var and (eventtype is null or logver>=502000000) and
    hostname is not null group by user_src, hostname order by requests desc)###) t where $filter-
    drilldown and user_src is not null group by user_src order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Web-User-By-Visit-Bar	Drilldown top web user by visit	traffic

```
select
  user_src,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
    hostname, count(*) as requests from $log-traffic where $filter-exclude-var and (logflag&1>0)
    and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
    and hostname is not null group by user_src, hostname order by requests desc)### union all ###
    (select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests
    from $log-webfilter where $filter-exclude-var and (eventtype is null or logver>=502000000) and
    hostname is not null group by user_src, hostname order by requests desc)###) t where $filter-
    drilldown and user_src is not null group by user_src order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Website-By-Request-Table	Drilldown top website by request	traffic

```
select
  hostname,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
    hostname, count(*) as requests from $log-traffic where $filter-exclude-var and (logflag&1>0)
    and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
    and hostname is not null group by user_src, hostname order by requests desc)### union all ###
    (select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests
    from $log-webfilter where $filter-exclude-var and (eventtype is null or logver>=502000000) and
    hostname is not null group by user_src, hostname order by requests desc)###) t where $filter-
    drilldown and user_src is not null group by user_src order by visits desc
```

hostname is not null group by user\_src, hostname order by requests desc)###) t where \$filter-drilldown and hostname is not null group by hostname order by visits desc

Dataset Name	Description	Log Category
drilldown-Top-Website-By-Request-Bar	Drilldown top website by request	traffic

```
select
  hostname,
  sum(requests) as visits
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
hostname, count(*) as requests from $log-traffic where $filter-exclude-var and (logflag&1>0)
and utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')
and hostname is not null group by user_src, hostname order by requests desc)### union all ###
(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, hostname, count(*) as requests
from $log-webfilter where $filter-exclude-var and (eventtype is null or logver>=502000000) and
hostname is not null group by user_src, hostname order by requests desc)###) t where $filter-
drilldown and hostname is not null group by hostname order by visits desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Sender-By-Volume	Drilldown top email sender by volume	traffic

```
select
  sender,
  sum(bandwidth) as volume
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and (logflag&1>0) and
service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in
('general-email-log', 'spamfilter') group by sender, recipient order by requests desc)###
union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-
var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and
eventtype is null group by `from`, `to` order by requests desc)###) t where $filter-drilldown
and sender is not null group by sender having sum(bandwidth)>0 order by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Send-Recipient-By-Volume	Drilldown top email send recipient by volume	traffic

```
select
  recipient,
  sum(bandwidth) as volume
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and (logflag&1>0) and
service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in
('general-email-log', 'spamfilter') group by sender, recipient order by requests desc)###
union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum(coalesce
```

```
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-
var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and
eventtype is null group by `from`, `to` order by requests desc)###) t where $filter-drilldown
and recipient is not null group by recipient having sum(bandwidth)>0 order by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Sender-By-Count	Drilldown top email sender by count	traffic

```
select
  sender,
  sum(requests) as requests
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and (logflag&1>0) and
service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in
('general-email-log', 'spamfilter') group by sender, recipient order by requests desc)###
union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-
var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and
eventtype is null group by `from`, `to` order by requests desc)###) t where $filter-drilldown
and sender is not null group by sender order by requests desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Send-Recipient-By-Count	Drilldown top email send recipient by count	traffic

```
select
  recipient,
  sum(requests) as requests
from
  (
    ###(select sender, recipient, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter-exclude-var and (logflag&1>0) and
service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and utmevent in
('general-email-log', 'spamfilter') group by sender, recipient order by requests desc)###
union all ###(select `from` as sender, `to` as recipient, count(*) as requests, sum(coalesce
(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-emailfilter where $filter-exclude-
var and service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') and
eventtype is null group by `from`, `to` order by requests desc)###) t where $filter-drilldown
and recipient is not null group by recipient order by requests desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Recipient-By-Volume	Drilldown top email receiver by volume	traffic

```
select
  recipient,
  sum(bandwidth) as volume
from
  (
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0) and service
```

```
in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp',
'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by
recipient, sender order by requests desc)### union all ###(select `to` as recipient, `from` as
sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth
from $log-emailfilter where $filter-exclude-var and service in ('pop3', 'POP3', '110/tcp',
'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and event-
type is null group by `to`, `from` order by requests desc)###) t where $filter-drilldown and
recipient is not null group by recipient having sum(bandwidth)>0 order by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Receive-Sender-By-Volume	Drilldown top email receive sender by volume	traffic

```
select
  sender,
  sum(bandwidth) as volume
from
  (
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0) and service
in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp',
'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by
recipient, sender order by requests desc)### union all ###(select `to` as recipient, `from` as
sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth
from $log-emailfilter where $filter-exclude-var and service in ('pop3', 'POP3', '110/tcp',
'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and event-
type is null group by `to`, `from` order by requests desc)###) t where $filter-drilldown and
sender is not null group by sender having sum(bandwidth)>0 order by volume desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Recipient-By-Count	Drilldown top email receiver by count	traffic

```
select
  recipient,
  sum(requests) as requests
from
  (
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
(rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0) and service
in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp',
'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by
recipient, sender order by requests desc)### union all ###(select `to` as recipient, `from` as
sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth
from $log-emailfilter where $filter-exclude-var and service in ('pop3', 'POP3', '110/tcp',
'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and event-
type is null group by `to`, `from` order by requests desc)###) t where $filter-drilldown and
recipient is not null group by recipient order by requests desc
```

Dataset Name	Description	Log Category
drilldown-Top-Email-Receive-Sender-By-Count	Drilldown top email receive sender by count	traffic

```

select
  sender,
  sum(requests) as requests
from
  (
    ###(select recipient, sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce
    (rcvdbyte, 0)) as bandwidth from $log where $filter-exclude-var and (logflag&1>0) and service
    in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp',
    'pop3s', 'POP3S', '995/tcp') and utmevent in ('general-email-log', 'spamfilter') group by
    recipient, sender order by requests desc)### union all ###(select `to` as recipient, `from` as
    sender, count(*) as requests, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth
    from $log-emailfilter where $filter-exclude-var and service in ('pop3', 'POP3', '110/tcp',
    'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp') and event-
    type is null group by `to`, `from` order by requests desc)###) t where $filter-drilldown and
    sender is not null group by sender order by requests desc

```

Dataset Name	Description	Log Category
drilldown-Top-Attack-Destination	Drilldown top attack dest	attack

```

select
  dstip,
  sum(totalnum) as totalnum
from
  ###(select srcip, dstip, count(*) as totalnum from $log where $filter-exclude-var group by
  srcip, dstip order by totalnum desc)### t where $filter-drilldown and dstip is not null group
  by dstip order by totalnum desc

```

Dataset Name	Description	Log Category
drilldown-Top-Attack-Source	Drilldown top attack source	attack

```

select
  srcip,
  sum(totalnum) as totalnum
from
  ###(select srcip, dstip, count(*) as totalnum from $log where $filter-exclude-var group by
  srcip, dstip order by totalnum desc)### t where $filter-drilldown and srcip is not null group
  by srcip order by totalnum desc

```

Dataset Name	Description	Log Category
drilldown-Top-Attack-List	Drilldown top attack list	attack

```

select
  from_itime(itime) as timestamp,
  attack,
  srcip,
  dstip
from
  ###(select itime, attack, srcip, dstip from $log where $filter-exclude-var order by itime
  desc)### t where $filter-drilldown order by timestamp desc

```

Dataset Name	Description	Log Category
drilldown-Top-Virus	UTM top virus	virus

```

select
  virus,
  max(virusid_s) as virusid,
  (
    case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then 'Adware'
    else 'Virus' end
  ) as malware_type,
  sum(totalnum) as totalnum
from
  ###(select virus, virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from
$log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not
null group by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by
virus, malware_type order by totalnum desc

```

Dataset Name	Description	Log Category
drilldown-Virus-Detail	Drilldown virus detail	virus

```

select
  from_itime(itime) as timestamp,
  virus,
  user_src,
  dstip,
  hostname,
  recipient
from
  ###(select itime, virus, coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, dstip,
cast(' ' as char) as hostname, cast(' ' as char) as recipient from $log where $filter and
(eventtype is null or logver>=502000000) and nullifna(virus) is not null order by itime
desc)### t where $filter-drilldown order by timestamp desc

```

Dataset Name	Description	Log Category
user-drilldown-Top-Blocked-Web-Sites-By-Requests	User drilldown top blocked web sites by requests	webfilter

```

select
  hostname,
  sum(requests) as requests
from
  ###({{FGT_DATASET_WEBFILTER_TOP_WEB_BY_REQUEST}})### t where $filter-drilldown and action-
='blocked' group by hostname order by requests desc

```

Dataset Name	Description	Log Category
user-drilldown-Top-Allowed-Web-Sites-By-Requests	User drilldown top allowed web sites by requests	webfilter

```

select
  hostname,
  sum(requests) as requests
from
  ###({{FGT_DATASET_WEBFILTER_TOP_WEB_BY_REQUEST}})### t where $filter-drilldown and action!-
='blocked' group by hostname order by requests desc

```

Dataset Name	Description	Log Category
user-drilldown-Top-Blocked-Web-Categories	User drilldown top blocked web categories	webfilter

```
select
  catdesc,
  sum(requests) as requests
from
  ###({{FGT_DATASET_WEBFILTER_TOP_WEB_CATS}})### t where $filter-drilldown and action-
  ='blocked' group by catdesc order by requests desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Allowed-Web-Categories	User drilldown top allowed web categories	webfilter

```
select
  catdesc,
  sum(requests) as requests
from
  ###({{FGT_DATASET_WEBFILTER_TOP_WEB_CATS}})### t where $filter-drilldown and action!-
  ='blocked' group by catdesc order by requests desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Attacks	User drilldown top attacks by name	attack

```
select
  attack,
  sum(attack_count) as attack_count
from
  ###({{FGT_DATASET_ATTACK_TOP_ATTACKS}})### t where $filter-drilldown group by attack order
  by attack_count desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Attacks-High-Severity	User drilldown top attacks high severity	attack

```
select
  attack,
  sum(attack_count) as attack_count
from
  ###({{FGT_DATASET_ATTACK_TOP_ATTACKS}})### t where $filter-drilldown and high_severity=1
  group by attack order by attack_count desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Virus-By-Name	User drilldown top virus	virus

```
select
  virus,
  max(virusid_s) as virusid,
  sum(totalnum) as totalnum
```

```
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, virus, virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from $log where $filter and nullifna(virus) is not null group by user_src, virus, virusid_s order by totalnum desc)### t where $filter-drilldown group by virus order by totalnum desc
```

Dataset Name	Description	Log Category
user-drilldown-Top-Virus-Receivers-Over-Email	User drilldown top virus receivers over email	virus

```
select
  receiver,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, `to` as receiver, count(*) as totalnum from $log where $filter and subtype='infected' and (service in ('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') or service in ('pop3', 'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S', '995/tcp')) and nullifna(virus) is not null group by user_src, receiver order by totalnum desc)### t where $filter-drilldown group by receiver order by totalnum desc
```

Dataset Name	Description	Log Category
user-drilldown-Count-Spam-Activity-by-Hour-of-Day	User drilldown count spam activity by hour of day	emailfilter

```
select
  $hour_of_day(timestamp) as hourstamp,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATASET_EMAILFILTER_USER_SENDER}})### t where $filter-drilldown and mf_receiver is not null and action in ('detected', 'blocked') group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
user-drilldown-Top-Spam-Sources	User drilldown top spam sources	emailfilter

```
select
  mf_sender,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATASET_EMAILFILTER_USER_SENDER}})### t where $filter-drilldown and mf_sender is not null and action in ('detected', 'blocked') group by mf_sender order by totalnum desc
```

Dataset Name	Description	Log Category
event-Usage-CPU	Event usage CPU	event

```
select
  hourstamp,
  cast(
    sum(cpu_usage) / sum(num) as decimal(6, 2)
  ) as cpu_avg_usage
from
  ###(select $hour_of_day as hourstamp, sum(cpu) as cpu_usage, count(*) as num from $log where
```



```
$filter and subtype='system' and action='perf-stats' group by hourstamp)### t group by
hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
event-Usage-Memory	Event usage memory	event

```
select
  hourstamp,
  cast(
    sum(mem_usage)/ sum(num) as decimal(6, 2)
  ) as mem_avg_usage
from
  ###(select $hour_of_day as hourstamp, sum(mem) as mem_usage, count(*) as num from $log where
  $filter and subtype='system' and action='perf-stats' group by hourstamp)### t group by
  hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
event-Usage-Sessions	Event usage sessions	event

```
select
  hourstamp,
  cast(
    sum(sess_usage)/ sum(num) as decimal(10, 2)
  ) as sess_avg_usage
from
  ###(select $hour_of_day as hourstamp, sum(totalsession) as sess_usage, count(*) as num from
  $log where $filter and subtype='system' and action='perf-stats' group by hourstamp)### t group
  by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
event-Usage-CPU-Sessions	Event usage CPU sessions	event

```
select
  hourstamp,
  cast(
    sum(sess_usage)/ sum(num) as decimal(10, 2)
  ) as sess_avg_usage,
  cast(
    sum(cpu_usage)/ sum(num) as decimal(6, 2)
  ) as cpu_avg_usage
from
  ###(select $hour_of_day as hourstamp, sum(cpu) as cpu_usage, sum(totalsession) as sess_
  usage, count(*) as num from $log where $filter and subtype='system' and action='perf-stats'
  group by hourstamp)### t group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
App-Risk-Top-Users-By-Bandwidth	Top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
```

```

        ipstr(`srcip`)
    ) as user_src,
    srcip,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    sum(
        coalesce(rcvdbyte, 0)
    ) as traffic_in,
    sum(
        coalesce(sentbyte, 0)
    ) as traffic_out
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and srcip is not null
group by
    user_src,
    srcip
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
App-Risk-Top-User-Source-By-Sessions	Application risk top user source by session count	traffic

```

select
    srcip,
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as user_src,
    count(*) as sessions
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and srcip is not null
group by
    srcip,
    user_src
order by
    sessions desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Users-By-Reputation-Scores-Bar	Application risk reputation top users by scores	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(crscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crscore is not null
group by
  user_src
having
  sum(crscore % 65536) > 0
order by
  scores desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Devices-By-Reputation-Scores	Application risk reputation top devices by scores	traffic

```

select
  get_devtype(srcswversion, osname, devtype) as devtype_new,
  coalesce(
    nullifna(`srcname`),
    nullifna(`srcmac`),
    ipstr(`srcip`)
  ) as dev_src,
  sum(crscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crscore is not null
group by
  devtype_new,
  dev_src
having
  sum(crscore % 65536) > 0
order by
  scores desc

```

Dataset Name	Description	Log Category
App-Risk-Application-Usage-By-Category-With-Pie	Application risk application usage by category	traffic

```
select
  appcat,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as sessions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk /*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown and nullifna(appcat) is not null group by appcat order by bandwidth desc
```

Dataset Name	Description	Log Category
App-Risk-App-Usage-by-Category	Application risk application usage by category	traffic

```
select
  appcat,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as sessions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk /*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown and nullifna(appcat) is not null group by appcat order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-20-Categories-By-Bandwidth	Webfilter categories by bandwidth usage	webfilter

```
select
  catdesc,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and (logflag&1>0) and (countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) and catdesc is not null group by catdesc /*SkipSTART*/order by bandwidth desc/*SkipEND*/)### t group by catdesc order by bandwidth desc
```

Dataset Name	Description	Log Category
App-Risk-Key-Applications-Crossing-The-Network	Application risk application activity	traffic

```
select
  app_group_name(app) as app_group,
  appcat,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  count(*) as num_session
from
  $log
```

```

where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(app) is not null
group by
    app_group,
    appcat
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
App-Risk-Applications-Running-Over-HTTP	Application risk applications running over HTTP	traffic

```

select
    app_group_name(app) as app_group,
    service,
    count(*) as sessions,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(app) is not null
    and service in (
        '80/tcp', '443/tcp', 'HTTP', 'HTTPS',
        'http', 'https'
    )
group by
    app_group,
    service
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
App-Risk-Top-Web-Sites-Visited-By-Network-Users-Pie-Cha	Application risk web browsing summary category	traffic

```

select
    catdesc,
    sum(num_sess) as num_sess,
    sum(bandwidth) as bandwidth
from

```

```
###(select catdesc, count(*) as num_sess, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))
as bandwidth from $log-traffic where $filter and (logflag&1>0) and (countweb>0 or ((logver is
null or logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-
word', 'web-content', 'command-block', 'script-filter')))) and catdesc is not null group by
catdesc order by num_sess desc)### t group by catdesc order by num_sess desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Web-Sites-Visited-By-Network-Users	Application risk web browsing summary category	traffic

```
select
  catdesc,
  sum(num_sess) as num_sess,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, count(*) as num_sess, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))
as bandwidth from $log-traffic where $filter and (logflag&1>0) and (countweb>0 or ((logver is
null or logver<502000000) and (hostname is not null or utmevent in ('webfilter', 'banned-
word', 'web-content', 'command-block', 'script-filter')))) and catdesc is not null group by
catdesc order by num_sess desc)### t group by catdesc order by num_sess desc
```

Dataset Name	Description	Log Category
App-Risk-Web-Browsing-Hostname-Category	Application risk web browsing activity hostname category	webfilter

```
select
  domain,
  catdesc,
  sum(visits) as visits
from
  ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, catdesc, count(*) as vis-
its from $log where $filter and (eventtype is null or logver>=502000000) and catdesc is not
null group by domain, catdesc order by visits desc)### t group by domain, catdesc order by vis-
its desc
```

Dataset Name	Description	Log Category
Top-Destination-Countries-By-Browsing-Time	Traffic top destination countries by browsing time	traffic

```
select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###({{FGT_DATASET_TRAFFIC_TOP_DST_COUNTRY_BY_EB_TIME}})### t group by dstcountry order by
browsetime desc
```

Dataset Name	Description	Log Category
Top-Destination-Countries-By-Browsing-Time-Enhanced	Traffic top destination countries by browsing time enhanced	traffic

```
select
  dstcountry,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###({{FGT_DATASET_TRAFFIC_TOP_DST_COUNTRY_BY_EB_TIME}})### t group by dstcountry order by
  browsetime desc
```

Dataset Name	Description	Log Category
App-Risk-Traffic-Top-Hostnames-By-Browsing-Time	Traffic top domains by browsing time	traffic

```
select
  hostname,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
  ###({{FGT_DATASET_TRAFFIC_TOP_DOMAINS_BY_EB_TIME}})### t group by hostname order by brow-
  setime desc
```

Dataset Name	Description	Log Category
App-Risk-Traffic-Top-Hostnames-By-Browsing-Time-Enhanced	Traffic top domains by browsing time enhanced	traffic

```
select
  hostname,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from
```

```
###({{FGT_DATASET_TRAFFIC_TOP_DOMAINS_BY_EB_TIME}})### t group by hostname order by brow-  
setime desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Threat-Vectors-Crossing-The-Network	Application risk top threat vectors	attack

```
select  
    severity,  
    count(*) as totalnum  
from  
    $log  
where  
    $filter  
group by  
    severity  
order by  
    totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Critical-Threat-Vectors-Crossing-The-Network	Application risk top critical threat vectors	attack

```
select  
    attack,  
    severity,  
    ref,  
    count(*) as totalnum  
from  
    $log  
where  
    $filter  
    and severity = 'critical'  
    and nullifna(attack) is not null  
group by  
    attack,  
    severity,  
    ref  
order by  
    totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-High-Threat-Vectors-Crossing-The-Network	Application risk top high threat vectors	attack

```
select  
    attack,  
    severity,  
    ref,  
    count(*) as totalnum  
from  
    $log  
where
```



```
$filter
and severity = 'high'
and nullifna(attack) is not null
group by
  attack,
  severity,
  ref
order by
  totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Medium-Threat-Vectors-Crossing-The-Network	Application risk top medium threat vectors	attack

```
select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity = 'medium'
  and nullifna(attack) is not null
group by
  attack,
  severity,
  ref
order by
  totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Low-Threat-Vectors-Crossing-The-Network	Application risk top low threat vectors	attack

```
select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity = 'low'
  and nullifna(attack) is not null
group by
  attack,
  severity,
  ref
order by
  totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Info-Threat-Vectors-Crossing-The-Network	Application risk top info threat vectors	attack

```
select
  attack,
  severity,
  ref,
  count(*) as totalnum
from
  $log
where
  $filter
  and severity = 'info'
  and nullifna(attack) is not null
group by
  attack,
  severity,
  ref
order by
  totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Virus-By-Name	UTM top virus	virus

```
select
  virus,
  max(virusid_s) as virusid,
  (
    case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then 'Adware'
  else 'Virus' end
  ) as malware_type,
  sum(totalnum) as totalnum
from
  ###(select virus, virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from
$log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not
null group by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by
virus, malware_type order by totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Top-Virus-Victim	UTM top virus user	virus

```
select
  user_src,
  sum(totalnum) as totalnum
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as user_src, count(*) as totalnum from
$log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not
null group by user_src /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by user_src
order by totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Data-Loss-Prevention-Type-Events	Application risk DLP UTM event	dlp

```
select
  subtype : :text as utmsubtype,
  count(*) as number
from
  ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and subtype is not
  null group by subtype order by number desc
```

Dataset Name	Description	Log Category
App-Risk-Vulnerability-Discovered	Application risk vulnerability discovered	netscan

```
select
  vuln,
  vulnref as ref,
  vulncat,
  severity,
  count(*) as totalnum
from
  $log
where
  $filter
  and vuln is not null
group by
  vuln,
  vulnref,
  vulncat,
  severity
order by
  totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Malware-Discovered	Application risk virus discovered	virus

```
select
  dom,
  sum(totalnum) as totalnum
from
  ###(select $DAY_OF_MONTH as dom, count(*) as totalnum from $log where $filter and nullifna
  (virus) is not null and (eventtype is null or logver>=502000000) group by dom order by total-
  num desc)### t group by dom order by totalnum desc
```

Dataset Name	Description	Log Category
App-Risk-Breakdown-Of-Risk-Applications	Application risk breakdown of risk applications	traffic

```
select
  unnest(
    string_to_array(behavior, ',')
```

```

    ) as d_behavior,
    count(*) as number
from
    $log t1
    inner join app_mdata t2 on t1.appid = t2.id
where
    $filter
    and (
        logflag&1>0
    )
group by
    d_behavior
order by
    number desc

```

Dataset Name	Description	Log Category
App-Risk-Number-Of-Applications-By-Risk-Behavior	Application risk number of applications by risk behavior	traffic

```

select
    risk as d_risk,
    unnest(
        string_to_array(behavior, ',')
    ) as f_behavior,
    count(*) as number
from
    $log t1
    inner join app_mdata t2 on t1.appid = t2.id
where
    $filter
    and (
        logflag&1>0
    )
group by
    risk,
    f_behavior
order by
    risk desc,
    number desc

```

Dataset Name	Description	Log Category
App-Risk-High-Risk-Application	Application risk high risk application	traffic

```

select
    risk as d_risk,
    behavior as d_behavior,
    t2.id,
    t2.name,
    t2.app_cat,
    t2.technology,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth,
    count(*) as sessions

```

```

from
    $log t1
    inner join app_mdata t2 on t1.appid = t2.id
where
    $filter
    and (
        logflag&1>0
    )
    and behavior is not null
group by
    t2.id
order by
    risk desc,
    sessions desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Severe-High-Risk-Application	Severe and high risk applications	traffic

```

select
    appcat,
    count(distinct app) as total_num
from
    ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as sessions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk /*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown and nullifna(appcat) is not null and apprisk in ('critical', 'high') group by appcat order by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Threats-Prevention	Threat Prevention	app-ctrl

```

select
    threat_name,
    count(distinct threats) as total_num
from
    (
        ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name, app as threats from $log-app-ctrl where $filter and lower(appcat)='botnet' group by app)### union all ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name, virus as threats from $log-virus where $filter and nullifna(virus) is not null group by virus)### union all ###(select cast('Malicious & Phishing Sites' as char(32)) as threat_name, hostname as threats from $log-web-filter where $filter and cat in (26, 61) group by hostname)### union all ###(select cast('Critical & High Intrusion Attacks' as char(32)) as threat_name, attack as threats from $log-attack where $filter and severity in ('critical', 'high') group by attack)###) t group by threat_name order by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Application-Vulnerability	Application vulnerabilities discovered	attack

```

select
    attack,
    attackid,

```

```

vuln_type,
cve,
severity_number,
count(distinct dstip) as victims,
count(distinct srcip) as sources,
sum(totalnum) as totalnum
from
###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then 5
when t1.severity='high' then 4 when t1.severity='medium' then 3 when t1.severity='low' then 2
when t1.severity='info' then 1 else 0 end) as severity_number, dstip, srcip, count(*) as total-
num from $log t1 left join (select name, cve, vuln_type from ips_mdata) t2 on t1.at-
tack=t2.name where $filter and nullifna(attack) is not null and t1.severity is not null group
by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip )### t group by attack,
attackid, vuln_type, severity_number, cve order by severity_number desc, totalnum desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Breakdown-Of-High-Risk-Application	Severe and high risk applications	traffic

```

select
  appcat,
  count(distinct app) as total_num
from
###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as ses-
sions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null and apprisk in ('critical', 'high') group by appcat order by
total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-20-High-Risk-Application	Application risk high risk application	traffic

```

select
  risk as d_risk,
  count(distinct user_src) as users,
  id,
  name,
  app_cat,
  technology,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
###(select lower(app) as lowapp, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count
(*) as sessions from $log where $filter and (logflag&1>0) group by lowapp, user_src order by
bandwidth desc)### t1 inner join app_mdata t2 on t1.lowapp=lower(t2.name) where risk>='4'
group by id, name, app_cat, technology, risk order by d_risk desc, sessions desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-High-Risk-Application-Behavioral	Application Behavioral Characteristics	traffic

```

select
  behavior,
  round(
    sum(total_num)* 100 / sum(
      sum(total_num)
    ) over (),
    2
  ) as percentage
from
  (
    ###(select (case when lower(appcat)='botnet' then 'malicious' when lower(appcat)-
    ='remote.access' then 'tunneling' when lower(appcat) in ('storage.backup', 'video/audio') then
    'bandwidth-consuming' when lower(appcat)='p2p' then 'peer-to-peer' when lower(appcat)='proxy'
    then 'proxy' end) as behavior, sum(sessions) as total_num from {{FGT_DATASET_BASE_TRAFFIC_TOP_
    APPS}} t where lower(appcat) in ('botnet', 'remote.access', 'storage.backup', 'video/audio',
    'p2p', 'proxy') and apprisk in ('critical', 'high') group by appcat order by total_num
    desc)### union all ###(select 'malicious' as behavior, count(*) as total_num from $log-attack
    where $filter and (logflag&16>0) and severity in ('critical', 'high') group by behavior)###) t
    where $filter-drilldown group by behavior order by percentage desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Key-Application-Crossing-The-Network	Key Application Crossing The Network	traffic

```

select
  risk as d_risk,
  count(distinct user_src) as users,
  id,
  name,
  app_cat,
  technology,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###(select app, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_
  src, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as sessions from
  $log where $filter and (logflag&1>0) group by app, user_src order by bandwidth desc)### t1
  inner join app_mdata t2 on t1.app=t2.name group by id, app, app_cat, technology, risk order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Risk-Application-Usage-By-Category-With-Pie	Application risk application usage by category	traffic

```

select
  appcat,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as ses-
  sions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk
  /*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
  and nullifna(appcat) is not null group by appcat order by bandwidth desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Category-Breakdown-By-Bandwidth	Category breakdown of all applications, sorted by bandwidth	traffic

```
select
  appcat,
  count(distinct app) as app_num,
  count(distinct user_src) as user_num,
  sum(bandwidth) as bandwidth,
  sum(sessions) as num_session
from
  ###(select app, appcat, user_src, sum(bandwidth) as bandwidth, sum(sessions) as sessions
  from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t where nullifna(appcat) is not null group by app,
  appcat, user_src order by bandwidth desc)### t where $filter-drilldown group by appcat order
  by bandwidth desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-Web-Applications-by-Bandwidth	Top 25 Web Categories by Bandwidth	traffic

```
select
  d_risk,
  id,
  name,
  technology,
  count(distinct f_user) as user_num,
  sum(bandwidth) as bandwidth,
  sum(num_session) as num_session
from
  ###(select risk as d_risk, t2.id, t2.name, t2.technology, coalesce(nullifna(t1.`user`), null-
  lifna(t1.`unauthuser`), ipstr(t1.`srcip`)) as f_user, sum(coalesce(sentbyte, 0)+coalesce(rcvd-
  byte, 0)) as bandwidth, count(*) as num_session from $log t1 inner join app_mdata t2 on
  t1.appid=t2.id where $filter and (logflag&1>0) and nullifna(app) is not null and service in
  ('80/tcp', '443/tcp', 'HTTP', 'HTTPS', 'http', 'https') group by risk, t2.id, t2.name, t2.-
  technology, f_user)### t group by d_risk, id, name, technology order by bandwidth desc
```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Top-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```
select
  catdesc,
  count(distinct f_user) as user_num,
  sum(sessions) as sessions,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as f_
  user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from
  $log-traffic where $filter and catdesc is not null and (logflag&1>0) and (countweb>0 or
  ((logver is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter',
  'banned-word', 'web-content', 'command-block', 'script-filter')))) group by f_user, catdesc
  order by sessions desc)### t group by catdesc order by sessions desc
```



Dataset Name	Description	Log Category
Apprisk-Ctrl-Common-Virus-Botnet-Spyware	Common virus disvocered, the botnet communictions and the spyware/adware	traffic

```

select
  virus_s as virus,
  (
    case when lower(appcat)= 'botnet' then 'Botnet C&C' else (
      case when virus_s like 'Riskware%' then 'Spyware' when virus_s like 'Adware%' then
'Adware' else 'Virus' end
    ) end
  ) as malware_type,
  appid,
  app,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  (
    ###(select app as virus_s, appcat, appid, app, dstip, srcip, count(*) as total_num from
$log-traffic where $filter and (logflag&1>0) and lower(appcat)='botnet' group by virus_s,
appcat, appid, dstip, srcip, app order by total_num desc)### union all ###(select unnest
(string_to_array(virus, ',')) as virus_s, appcat, appid, app, dstip, srcip, count(*) as total_
num from $log-traffic where $filter and (logflag&1>0) and virus is not null group by virus_s,
appcat, appid, dstip, srcip, app order by total_num desc)### union all ###(select attack as
virus_s, 'botnet' as appcat, 0 as appid, attack as app, dstip, srcip, count(*) as total_num
from $log-attack where $filter and (logflag&16>0) group by virus_s, appcat, appid, dstip,
srcip, app order by total_num desc)###) t group by virus, appid, app, malware_type order by
total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Zero-Day-Detected-On-Network	Zero-day malware detected on the network	traffic

```

select
  virus_s,
  appid,
  app,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  ###(select unnest(string_to_array(virus, ',')) as virus_s, appid, app, dstip, srcip, count
(*) as total_num from $log where $filter and (logflag&1>0) and virus like '%Poss-
ibleThreat.SB%' group by virus_s, dstip, srcip, appid, app )### t where virus_s like '%Poss-
ibleThreat.SB%' group by virus_s, appid, app order by total_num desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Files-Analyzed-By-FortiCloud-Sandbox	Files analyzed by FortiCloud Sandbox	virus

```

select
    $DAY_OF_MONTH as dom,
    count(*) as total_num
from
    $log
where
    $filter
    and nullifna(filename) is not null
    and logid_to_int(logid)= 9233
group by
    dom
order by
    dom

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-Malicious-Files-Detected-By-FortiCloud-Sandbox	Files detected by FortiCloud Sandbox	virus

```

select
    filename,
    analyticscksum,
    count(distinct dstip) as victims,
    count(distinct srcip) as source
from
    ###(select filename, analyticscksum, dstip, srcip from $log where $filter and filename is
not null and logid_to_int(logid)=9233 and analyticscksum is not null group by filename, ana-
lyticscksum, srcip, dstip)### t group by filename, analyticscksum order by victims desc,
source desc

```

Dataset Name	Description	Log Category
Apprisk-Ctrl-File-Transferred-By-Application	File transferred by applications on the network	app-ctrl

```

select
    appid,
    app,
    filename,
    cloudaction,
    max(filesize) as filesize
from
    $log
where
    $filter
    and filesize is not null
    and clouduser is not null
    and filename is not null
group by
    cloudaction,
    appid,
    app,
    filename
order by
    filesize desc

```

Dataset Name	Description	Log Category
appctrl-Top-Blocked-SCCP-Callers	Appctrl top blocked SCCP callers	app-ctrl

```
select
  srcname as caller,
  count(*) as totalnum
from
  $log
where
  $filter
  and lower(appcat)= 'voip'
  and app = 'sccp'
  and action = 'block'
  and srcname is not null
group by
  caller
order by
  totalnum desc
```

Dataset Name	Description	Log Category
appctrl-Top-Blocked-SIP-Callers	Appctrl top blocked SIP callers	app-ctrl

```
select
  srcname as caller,
  count(*) as totalnum
from
  $log
where
  $filter
  and srcname is not null
  and lower(appcat)= 'voip'
  and app = 'sip'
  and action = 'block'
group by
  caller
order by
  totalnum desc
```

Dataset Name	Description	Log Category
security-Top20-High-Risk-Application-In-Use	High risk application in use	traffic

```
select
  d_risk,
  count(distinct f_user) as users,
  name,
  app_cat,
  technology,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###(select risk as d_risk, coalesce(nullifna(t1.`user`), nullifna(t1.`unauthuser`), ipstr
  (t1.`srcip`)) as f_user, t2.name, t2.app_cat, t2.technology, sum(coalesce(sentbyte,
```

```
0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as sessions from $log t1 inner join app_
mdata t2 on t1.appid=t2.id where $filter and risk>='4' and (logflag&1>0) group by f_user, t2.-
name, t2.app_cat, t2.technology, risk)### t group by d_risk, name, app_cat, technology order
by d_risk desc, sessions desc
```

Dataset Name	Description	Log Category
security-High-Risk-Application-By-Category	High risk application by category	traffic

```
select
  app_cat,
  count(distinct app) as total_num
from
  ###(select app_cat, app from $log t1 inner join app_mdata t2 on t1.appid=t2.id where $filter
and risk>='4' and (logflag&1>0) group by app_cat, app)### t group by app_cat order by total_
num desc
```

Dataset Name	Description	Log Category
security-Top10-Application-Categories-By-Bandwidth	Application risk application usage by category	traffic

```
select
  appcat,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as ses-
sions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
and nullifna(appcat) is not null group by appcat order by bandwidth desc
```

Dataset Name	Description	Log Category
Security-Category-Breakdown-By-Bandwidth	Category breakdown of all applications, sorted by bandwidth	traffic

```
select
  appcat,
  count(distinct app) as app_num,
  count(distinct user_src) as user_num,
  sum(bandwidth) as bandwidth,
  sum(sessions) as num_session
from
  ###(select app, appcat, user_src, sum(bandwidth) as bandwidth, sum(sessions) as sessions
from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t where nullifna(appcat) is not null group by app,
appcat, user_src order by bandwidth desc)### t where $filter-drilldown group by appcat order
by bandwidth desc
```

Dataset Name	Description	Log Category
security-Top25-Web-Applications-By-Bandwidth	Top Web Applications by Bandwidth	traffic

```

select
  d_risk,
  name,
  app_cat,
  technology,
  count(distinct f_user) as users,
  sum(bandwidth) as bandwidth,
  sum(num_session) as sessions
from
  ###(select risk as d_risk, t2.app_cat, t2.name, t2.technology, coalesce(nullifna(t1.`user`),
  nullifna(t1.`unauthuser`), ipstr(t1.`srcip`)) as f_user, sum(coalesce(sentbyte, 0)+coalesce
  (rcvdbyte, 0)) as bandwidth, count(*) as num_session from $log t1 inner join app_mdata t2 on
  t1.appid=t2.id where $filter and (logflag&1>0) and nullifna(app) is not null and service in
  ('80/tcp', '443/tcp', 'HTTP', 'HTTPS', 'http', 'https') group by risk, t2.app_cat, t2.name,
  t2.technology, f_user)### t group by d_risk, name, app_cat, technology order by bandwidth desc

```

Dataset Name	Description	Log Category
Security-Top25-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```

select
  catdesc,
  count(distinct f_user) as user_num,
  sum(sessions) as sessions,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as f_
  user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from
  $log-traffic where $filter and catdesc is not null and (logflag&1>0) and (countweb>0 or
  ((logver is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter',
  'banned-word', 'web-content', 'command-block', 'script-filter')))) group by f_user, catdesc
  order by sessions desc)### t group by catdesc order by sessions desc

```

Dataset Name	Description	Log Category
security-Top25-Malware-Virus-Botnet-Spyware	Malware: viruses, Bots, Spyware/Adware	traffic

```

select
  virus_s as virus,
  (
    case when lower(appcat)= 'botnet' then 'Botnet C&C' else (
      case when virus_s like 'Riskware%' then 'Spyware' when virus_s like 'Adware%' then
      'Adware' else 'Virus' end
    ) end
  ) as malware_type,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  (
    ###(select app as virus_s, appcat, dstip, srcip, count(*) as total_num from $log-traffic
    where $filter and (logflag&1>0) and lower(appcat)='botnet' group by virus_s, appcat, dstip,
    srcip order by total_num desc)### union all ###(select unnest(string_to_array(virus, ',')) as
    virus_s, appcat, dstip, srcip, count(*) as total_num from $log-traffic where $filter and

```

```
(logflag&1>0) and virus is not null group by virus_s, appcat, dstip, srcip order by total_num desc)### union all ###(select attack as virus_s, 'null' as appcat, dstip, srcip, count(*) as total_num from $log-attack where $filter and (logflag&16>0) group by virus_s, appcat, dstip, srcip order by total_num desc)###) t group by virus, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Malware-Virus-Spyware	Malware: viruses, Spyware/Adware	virus

```
select
  virus,
  max(virusid_s) as virusid,
  malware_type,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  ###(select virus, virusid_to_str(virusid, eventtype) as virusid_s, srcip, dstip, (case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then 'Adware' else 'Virus' end) as malware_type, count(*) as total_num from $log where $filter and nullifna(virus) is not null group by virus, virusid_s, srcip, dstip order by total_num desc)### t group by virus, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Malware-Botnet	Malware: Botnet	appctrl

```
select
  app,
  appid,
  malware_type,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  (
    ###(select app, appid, cast('Botnet C&C' as char(32)) as malware_type, srcip, dstip, count(*) as total_num from $log-app-ctrl where $filter and lower(appcat)='botnet' and nullifna(app) is not null group by app, appid, malware_type, srcip, dstip order by total_num desc)### union all ###(select attack as app, 0 as appid, cast('Botnet C&C' as char(32)) as malware_type, srcip, dstip, count(*) as total_num from $log-attack where $filter and (logflag&16>0) group by app, appid, malware_type, srcip, dstip order by total_num desc)###) t group by app, appid, malware_type order by total_num desc
```

Dataset Name	Description	Log Category
security-Top10-Victims-of-Malware	Victims of Malware	virus

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  virus as malware,
```

```

count(*) as total_num
from
$log
where
$filter
and virus is not null
group by
user_src,
malware
order by
total_num desc

```

Dataset Name	Description	Log Category
security-Top10-Victims-of-Phishing-Site	Victims of Phishing Site	webfilter

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  (
    lower(service) || '://' || hostname || url
  ) as phishing_site,
  count(*) as total_num
from
$log
where
$filter
and lower(service) in ('http', 'https')
and hostname is not null
and cat in (26, 61)
group by
user_src,
phishing_site
order by
total_num desc

```

Dataset Name	Description	Log Category
security-Top25-Malicious-Phishing-Sites	Malicious Phishing Site	webfilter

```

select
  phishing_site,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total) as total_num
from
  ###(select (lower(service) || '://' || hostname || url) as phishing_site, dstip, srcip,
count(*) as total from $log where $filter and lower(service) in ('http', 'https') and hostname
is not null and cat in (26, 61) group by phishing_site, dstip, srcip order by total desc)### t
group by phishing_site order by total_num desc

```

Dataset Name	Description	Log Category
security-Application-Vulnerability	Application vulnerabilities discovered	attack

```

select
  attack,
  attackid,
  vuln_type,
  cve,
  severity_number,
  count(distinct dstip) as victims,
  count(distinct srcip) as sources,
  sum(totalnum) as totalnum
from
  ###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then 5
  when t1.severity='high' then 4 when t1.severity='medium' then 3 when t1.severity='low' then 2
  when t1.severity='info' then 1 else 0 end) as severity_number, dstip, srcip, count(*) as total-
  num from $log t1 left join (select name, cve, vuln_type from ips_mdata) t2 on t1.at-
  tack=t2.name where $filter and nullifna(attack) is not null and t1.severity is not null group
  by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip )### t group by attack,
  attackid, vuln_type, severity_number, cve order by severity_number desc, totalnum desc

```

Dataset Name	Description	Log Category
security-Files-Analyzed-By-FortiCloud-Sandbox	Files analyzed by FortiCloud Sandbox	virus

```

select
  $day_of_week as dow,
  count(*) as total_num
from
  $log
where
  $filter
  and nullifna(filename) is not null
  and logid_to_int(logid)= 9233
group by
  dow
order by
  dow

```

Dataset Name	Description	Log Category
Security-Zero-Day-Detected-On-Network	Zero-day malware detected on the network	traffic

```

select
  virus_s,
  app,
  count(distinct dstip) as victims,
  count(distinct srcip) as source,
  sum(total_num) as total_num
from
  ###(select unnest(string_to_array(virus, ',')) as virus_s, app, dstip, srcip, count(*) as
  total_num from $log where $filter and (logflag&1>0) and virus like '%PossibleThreat.SB%' group
  by virus_s, dstip, srcip, app)### t group by virus_s, app order by total_num desc

```



Dataset Name	Description	Log Category
security-Data-Loss-Incidents-By-Severity	Data loss incidents summary by severity	dlp

```
select
  initcap(severity : :text) as s_severity,
  count(*) as total_num
from
  ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and severity is not
  null group by s_severity order by total_num desc
```

Dataset Name	Description	Log Category
security-Data-Loss-Files-By-Service	Data Lass Files By Service	dlp

```
select
  filename,
  (
    case direction when 'incoming' then 'Download' when 'outgoing' then 'Upload' end
  ) as action,
  max(filesize) as filesize,
  service
from
  ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and filesize is not
  null group by filename, direction, service order by filesize desc
```

Dataset Name	Description	Log Category
security-Endpoint-Security-Events-Summary	Endpoint Security Events summary	fct-traffic

```
select
  (
    case utmevent when 'antivirus' then 'Malware incidents' when 'webfilter' then 'Mali-
    cious/phishing websites' when 'appfirewall' then 'Risk applications' when 'dlp' then 'Data
    loss incidents' when 'netscan' then 'Vulnerability detected' else 'Others' end
  ) as events,
  count(*) as total_num
from
  $log
where
  $filter
  and utmevent is not null
group by
  events
order by
  total_num desc
```

Dataset Name	Description	Log Category
security-Top-Endpoing-Running-High-Risk-Application	Endpoints Running High Risk Application	fct-traffic

```

select
  coalesce(
    nullifna(`user`),
    ipstr(`srcip`),
    'Unknown'
  ) as f_user,
  coalesce(
    nullifna(hostname),
    'Unknown'
  ) as host_name,
  threat as app,
  t2.app_cat as appcat,
  risk as d_risk
from
  $log t1
  inner join app_mdata t2 on t1.threat = t2.name
where
  $filter
  and utmevent = 'appfirewall'
  and risk & gt;= '4'
group by
  f_user,
  host_name,
  t1.threat,
  t2.app_cat,
  t2.risk
order by
  risk desc

```

Dataset Name	Description	Log Category
security-Top-Endpoints-Infected-With-Malware	Endpoints Infected With Malware	fct-event

```

select
  coalesce(
    nullifna(`user`),
    ipstr(`deviceip`),
    'Unknown'
  ) as f_user,
  coalesce(
    nullifna(hostname),
    'Unknown'
  ) as host_name,
  virus,
  file
from
  $log
where
  $filter
  and clientfeature = 'av'
  and virus is not null
group by
  f_user,
  host_name,

```

```
virus,
file
```

Dataset Name	Description	Log Category
security-Top-Endpoints-With-Web-Violateions	Endpoints With Web Violations	fct-traffic

```
select
  f_user,
  host_name,
  remotename,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as f_user, coalesce(nullifna(host-
name), 'Unknown') as host_name, remotename, count(*) as total_num from $log where $filter and
utmevent='webfilter' and remotename is not null and utmaction='blocked' group by f_user, host_
name, remotename order by total_num desc)### t group by f_user, host_name, remotename order by
total_num desc
```

Dataset Name	Description	Log Category
security-Top-Endpoints-With-Data-Loss-Incidents	Endpoints With Data Loss Incidents	fct-event

```
select
  f_user,
  host_name,
  msg,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`user`), ipstr(`deviceip`), 'Unknown') as f_user, coalesce(nul-
lifna(hostname), 'Unknown') as host_name, msg, count(*) as total_num from $log where $filter
and clientfeature='dlp' group by f_user, host_name, msg order by total_num desc)### t group by
f_user, host_name, msg order by total_num desc
```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Call-Registrations-by-Hour-of-Day	Content count total SCCP call registrations by hour of day	content

```
select
  $hour_of_day as hourstamp,
  count(*) as totalnum
from
  $log
where
  $filter
  and proto = 'sccp'
  and kind = 'register'
group by
  hourstamp
order by
  hourstamp
```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Calls-Duration-by-Hour-of-Day	Content count total SCCP calls duration by hour of day	content

```
select
    $hour_of_day as hourstamp,
    sum(duration) as sccp_usage
from
    $log
where
    $filter
    and proto = 'sccp'
    and kind = 'call-info'
    and status = 'end'
group by
    hourstamp
order by
    hourstamp
```

Dataset Name	Description	Log Category
content-Count-Total-SCCP-Calls-per-Status	Content count total SCCP calls per status	content

```
select
    status,
    count(*) as totalnum
from
    $log
where
    $filter
    and proto = 'sccp'
    and kind = 'call-info'
group by
    status
order by
    totalnum desc
```

Dataset Name	Description	Log Category
content-Count-Total-SIP-Call-Registrations-by-Hour-of-Day	Content count total SIP call registrations by hour of day	content

```
select
    $hour_of_day as hourstamp,
    count(*) as totalnum
from
    $log
where
    $filter
    and proto = 'sip'
    and kind = 'register'
group by
    hourstamp
```

```
order by
  hourstamp
```

Dataset Name	Description	Log Category
content-Count-Total-SIP-Calls-per-Status	Content count total SIP calls per status	content

```
select
  status,
  count(*) as totalnum
from
  $log
where
  $filter
  and proto = 'sip'
  and kind = 'call'
group by
  status
order by
  totalnum desc
```

Dataset Name	Description	Log Category
content-Dist-Total-SIP-Calls-by-Duration	Content dist total SIP calls by duration	content

```
select
  (
    case when duration<60 then 'LESS_ONE_MIN' when duration<600 then 'LESS_TEN_MIN' when duration<3600 then 'LESS_ONE_HOUR' when duration & gt;= 3600 then 'MORE_ONE_HOUR' else 'unknown'
  ) as f_duration,
  count(*) as totalnum
from
  $log
where
  $filter
  and proto = 'sip'
  and kind = 'call'
  and status = 'end'
group by
  f_duration
order by
  totalnum desc
```

Dataset Name	Description	Log Category
Botnet-Activity-By-Sources	Botnet activity by sources	traffic

```
select
  app,
  user_src,
  sum(events) as events
from
  (
```

```
(
  select
    app,
    user_src,
    sum(totalnum) as events
  from
    ###({{FGT_DATASET_TRAFFIC_APP_BOTNET}})### t group by app, user_src order by events
  desc) union all (select attack as app, user_src, sum(totalnum) as events from ###({{FGT_
DATASET_ATTACK_APP_BOTNET}})### t group by app, user_src order by events desc)) t group by
app, user_src order by events desc
```

Dataset Name	Description	Log Category
Botnet-Infected-Hosts	Botnet infected hosts	traffic

```
select
  user_src,
  devtype_new,
  host_mac,
  sum(events) as events
from
  (
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
get_devtype(srcswversion, osname, devtype) as devtype_new, coalesce(srcname, srcmac) as host_
mac, count(*) as events from $log-traffic where $filter and (logflag&1>0) and appcat='Botnet'
group by user_src, devtype_new, host_mac order by events desc)### union all ###(select
coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, 'Unknown' as
devtype_new, hostname as host_mac, count(*) as events from $log-attack where $filter and (log-
flag&16>0) group by user_src, devtype_new, host_mac order by events desc)###) t group by user_
src, devtype_new, host_mac order by events desc
```

Dataset Name	Description	Log Category
Detected-Botnet	Detected botnet	traffic

```
select
  app,
  sum(events) as events
from
  (
    (
      select
        app,
        sum(totalnum) as events
      from
        ###({{FGT_DATASET_TRAFFIC_APP_BOTNET}})### t group by app order by events desc) union
all (select attack as app, sum(totalnum) as events from ###({{FGT_DATASET_ATTACK_APP_
BOTNET}})### t group by app order by events desc)) t group by app order by events desc
```

Dataset Name	Description	Log Category
Botnet-Sources	Botnet sources	traffic

```
select
  dstip,
  domain,
```

```

sum(events) as events
from
(
(
select
dstip,
domain,
events
from
###(select dstip, root_domain(hostname) as domain, count(*) as events from $log-
traffic where $filter and (logflag&1>0) and appcat='Botnet' and dstip is not null group by
dstip, domain order by events desc)### t) union all (select dstip, root_domain(hostname) as
domain, sum(totalnum) as events from ###({{FGT_DATASET_ATTACK_APP_BOTNET}})### t group by
dstip, domain order by events desc)) t group by dstip, domain order by events desc

```

Dataset Name	Description	Log Category
Botnet-Victims	Botnet victims	traffic

```

select
user_src,
sum(events) as events
from
(
(
select
user_src,
sum(totalnum) as events
from
###({{FGT_DATASET_TRAFFIC_APP_BOTNET}})### t group by user_src) union all (select
user_src, sum(totalnum) as events from ###({{FGT_DATASET_ATTACK_APP_BOTNET}})### t group by
user_src)) t group by user_src order by events desc

```

Dataset Name	Description	Log Category
Botnet-Timeline	Botnet timeline	traffic

```

select
$flex_datetime(timestamp) as hodex,
sum(events) as events
from
(
###(select $flex_timestamp as timestamp, count(*) as events from $log-traffic where $fil-
ter and (logflag&1>0) and appcat='Botnet' group by timestamp order by timestamp desc)### union
all ###(select $flex_timestamp as timestamp, count(*) as events from $log-dns where $filter
and (botnetdomain is not null or botnetip is not null) group by timestamp order by
timestamp)### union all ###(select $flex_timestamp as timestamp, count(*) as events from $log-
attack where $filter and (logflag&16>0) group by timestamp order by timestamp)###) t group by
hodex order by hodex

```

Dataset Name	Description	Log Category
Application-Session-History	Application session history	traffic

```

select
$flex_timescale(timestamp) as hodex,

```

```

sum(counter) as counter
from
  ###(select $flex_timestamp as timestamp, count(*) as counter from $log where $filter and
(logflag&1>0) group by timestamp order by timestamp desc)### t group by hodex order by hodex

```

Dataset Name	Description	Log Category
Application-Usage-List	Detailed application usage	traffic

```

select
  appid,
  app,
  appcat,
  (
    case when (
      utmaction in ('block', 'blocked')
      or action = 'deny'
    ) then 'Blocked' else 'Allowed' end
  ) as custaction,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth,
  count(*) as num_session
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
  and policyid != 0
group by
  appid,
  app,
  appcat,
  custaction
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
PCI-DSS-Compliance-Summary	PCI DSS Compliance Summary	event

```

select
  status,
  num_reason as requirements,
  cast(
    num_reason * 100.0 / (
      sum(num_reason) over()
    ) as decimal(18, 2)
  ) as percent
from
  (
    select
      (

```



```

        case when fail_count>0 then 'Non-Compliant' else 'Compliant' end
    ) as status,
    count(distinct reason) as num_reason
from
    (
        select
            ftnt_pci_id,
            (
                sum(fail_count) over (partition by ftnt_pci_id)
            ) as fail_count,
            reason
        from
            ###(select ftnt_pci_id, (case when result='fail' then 1 else 0 end) as fail_count,
reason from $log t1 inner join pci_dss_mdata t2 on t1.reason=t2.ftnt_id where $filter and sub-
type='compliance-check' group by ftnt_pci_id, result, reason)### t) t group by status) t order
by status

```

Dataset Name	Description	Log Category
PCI-DSS-Non-Compliant-Requirements-By-Severity	PCI DSS Non-Compliant Requirements by Severity	event

```

with query as (
    select
        *
    from
        (
            select
                ftnt_pci_id,
                severity,
                (
                    sum(fail_count) over (partition by ftnt_pci_id)
                ) as fail_count,
                reason
            from
                ###({{FGT_DATASET_EVENT_COMPLIANCE_CHECK}})### t) t where fail_count>0) select t.sever-
ity, count(distinct t.reason) as requirements from (select distinct on (1) reason, severity
from query order by reason, (case lower(severity) when 'high' then 4 when 'critical' then 3
when 'medium' then 2 when 'low' then 1 else 0 end) desc) t group by t.severity order by
requirements desc

```

Dataset Name	Description	Log Category
PCI-DSS-Compliant-Requirements-By-Severity	PCI DSS Compliant Requirements by Severity	event

```

with query as (
    select
        *
    from
        (
            select
                ftnt_pci_id,
                severity,
                (
                    sum(fail_count) over (partition by ftnt_pci_id)

```

```

        ) as fail_count,
        reason
    from
        ###({{FGT_DATASET_EVENT_COMPLIANCE_CHECK}})### t) t where fail_count=0) select t.sever-
ity, count(distinct t.reason) as requirements from (select distinct on (1) reason, severity
from query order by reason, (case lower(severity) when 'high' then 4 when 'critical' then 3
when 'medium' then 2 when 'low' then 1 else 0 end) desc) t group by t.severity order by
requirements desc

```

Dataset Name	Description	Log Category
PCI-DSS-Fortinet-Security-Best-Practice-Summary	PCI DSS Fortinet Security Best Practice Summary	event

```

select
    status,
    num_reason as practices,
    cast(
        num_reason * 100.0 /(
            sum(num_reason) over()
        ) as decimal(18, 2)
    ) as percent
from
    (
        select
            (
                case when result = 'fail' then 'Failed' else 'Passed' end
            ) as status,
            count(distinct reason) as num_reason
        from
            ###(select result, reason from $log where $filter and subtype='compliance-check' and res-
ult in ('fail','pass') group by result, reason)### t group by status) t order by status desc

```

Dataset Name	Description	Log Category
PCI-DSS-Failed-Fortinet-Security-Best-Practices-By-Severity	PCI DSS Failed Fortinet Security Best Practices by Severity	event

```

select
    status,
    num_reason as practices,
    cast(
        num_reason * 100.0 /(
            sum(num_reason) over()
        ) as decimal(18, 2)
    ) as percent
from
    (
        select
            initcap(status) as status,
            count(distinct reason) as num_reason
        from
            ###(select status, reason from $log where $filter and subtype='compliance-check' and res-
ult='fail' group by status, reason)### t group by status) t order by status

```

Dataset Name	Description	Log Category
PCI-DSS-Passed-Fortinet-Security-Best-Practices-By-Severity	PCI DSS Passed Fortinet Security Best Practices by Severity	event

```
select
  status,
  num_reason as practices,
  cast(
    num_reason * 100.0 / (
      sum(num_reason) over()
    ) as decimal(18, 2)
  ) as percent
from
  (
    select
      initcap(status) as status,
      count(distinct reason) as num_reason
    from
      ###(select status, reason from $log where $filter and subtype='compliance-check' and result='pass' group by status, reason)### t group by status) t order by status
```

Dataset Name	Description	Log Category
PCI-DSS-Requirements-Compliance-Details	PCI DSS Requirements Compliance Details	event

```
select
  ftnt_pci_id,
  left(
    string_agg(distinct ftnt_id, ','),
    120
  ) as practice,
  (
    case when sum(fail_count) > 0 then 'Non-Compliant' else 'Compliant' end
  ) as compliance,
  pci_requirement
from
  ###(select ftnt_pci_id, ftnt_id, (case when result='fail' then 1 else 0 end) as fail_count,
  pci_requirement from $log t1 inner join pci_dss_mdata t2 on t1.reason=t2.ftnt_id where $filter
  and subtype='compliance-check' group by ftnt_pci_id, ftnt_id, result, pci_requirement)### t
  group by ftnt_pci_id, pci_requirement order by ftnt_pci_id
```

Dataset Name	Description	Log Category
PCI-DSS-Fortinet-Security-Best-Practice-Details	PCI DSS Fortinet Security Best Practice Details	event

```
select
  reason as ftnt_id,
  msg,
  initcap(status) as status,
  module
from
  $log
```

```

where
    $filter
    and subtype = 'compliance-check'
group by
    reason,
    status,
    module,
    msg
order by
    ftnt_id

```

Dataset Name	Description	Log Category
DLP-Email-Activity-Details	Email DLP Violations Summary	dlp

```

select
    from_itime(itime) as timestamp,
    sender,
    receiver,
    regexp_replace(filename, '.*/', '') as filename,
    filesize,
    profile,
    action,
    direction
from
    ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and (service in
('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') or service in ('pop3',
'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S',
'995/tcp')) order by timestamp desc

```

Dataset Name	Description	Log Category
Email-DLP-Chart	Email DLP Activity Summary	dlp

```

select
    profile,
    count(*) as total_num
from
    ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and (service in
('smtp', 'SMTP', '25/tcp', '587/tcp', 'smtps', 'SMTPS', '465/tcp') or service in ('pop3',
'POP3', '110/tcp', 'imap', 'IMAP', '143/tcp', 'imaps', 'IMAPS', '993/tcp', 'pop3s', 'POP3S',
'995/tcp')) group by profile order by total_num desc

```

Dataset Name	Description	Log Category
DLP-Web-Activity-Details	Web DLP Violations Summary	dlp

```

select
    from_itime(itime) as timestamp,
    srcip,
    dstip,
    hostname,
    profile,
    filename,
    filesize,
    action,

```

```

direction
from
  ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and lower(service)
in ('http', 'https') order by timestamp desc

```

Dataset Name	Description	Log Category
Web-DLP-Chart	Web DLP Activity Summary	dlp

```

select
  profile,
  count(*) as total_num
from
  ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and lower(service)
in ('http', 'https') group by profile order by total_num desc

```

Dataset Name	Description	Log Category
DLP-FTP-Activity-Details	Web DLP Violations Summary	dlp

```

select
  from_itime(itime) as timestamp,
  srcip,
  dstip,
  filename,
  profile,
  filesize,
  action,
  direction
from
  ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and lower(service)
in ('ftp', 'ftps') order by timestamp desc

```

Dataset Name	Description	Log Category
FTP-DLP-Chart	FTP DLP Activity Summary	dlp

```

select
  profile,
  count(*) as total_num
from
  ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and lower(service)
in ('ftp', 'ftps') group by profile order by total_num desc

```

Dataset Name	Description	Log Category
top-users-by-browsetime	Top Users by website browsetime	traffic

```

select
  user_src,
  domain,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime

```

```

from
  ###(select user_src, domain, ebtr_agg_flat(browsetime) as browsetime from (select coalesce
  (nullifna(`user`), ipstr(`srcip`)) as user_src, coalesce(nullifna(hostname), ipstr(`dstip`))
  as domain, ebtr_agg_flat($browse_time) as browsetime from $log where $filter and $browse_time
  is not null group by user_src, domain) t group by user_src, domain order by ebtr_value(ebtr_
  agg_flat(browsetime), null, null) desc)### t group by user_src, domain order by browsetime
  desc

```

Dataset Name	Description	Log Category
wifi-usage-by-hour-authenticated	Wifi Usage by Hour - Authenticated	event

```

select
  hod,
  count(distinct stamac) as totalnum
from
  ###(select $HOURL_OF_DAY as hod, stamac from $log where $filter and subtype='wireless' and
  action='client-authentication' group by hod, stamac)### t group by hod order by hod

```

Dataset Name	Description	Log Category
wifi-usage-authenticated-timeline	Wifi Usage Timeline - Authenticated	event

```

select
  $flex_timescale(timestamp) as hodex,
  count(distinct stamac) as totalnum
from
  ###(select $flex_timestamp as timestamp, stamac from $log where $filter and sub-
  type='wireless' and action='client-authentication' group by timestamp, stamac order by
  timestamp desc)### t group by hodex order by hodex

```

Dataset Name	Description	Log Category
app-top-user-by-bandwidth	Top 10 Applications Bandwidth by User Drilldown	traffic

```

select
  app,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  sum(
    coalesce(`sentbyte`, 0)+ coalesce(`rcvdbyte`, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app,
  user_src

```

```
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
app-top-user-by-session	Top 10 Application Sessions by User Drilldown	traffic

```
select
  app,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app,
  user_src
order by
  sessions desc
```

Dataset Name	Description	Log Category
traffic-Interface-Bandwidth-Usage	Interface Bandwidth Usage	traffic

```
with qry as (
  select
    dom as dom_s,
    devid as devid_s,
    vd as vd_s,
    srcintf,
    dstintf,
    total_sent,
    total_rcvd
  from
    ###(select $DAY_OF_MONTH as dom, devid, vd, srcintf, dstintf, sum(coalesce(sentbyte, 0))
    as total_sent, sum(coalesce(rcvdbyte, 0)) as total_rcvd, sum(coalesce(sentbyte, 0)+coalesce
    (rcvdbyte, 0)) as total from $log where $filter and (logflag&1>0) and nullifna(srcintf) is not
    null and nullifna(dstintf) is not null group by dom, devid, vd, srcintf, dstintf having sum
    (coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by total desc)### t) select dom, unnest
    (array['download', 'upload']) as type, unnest(array[sum(download), sum(upload)]) as bandwidth
  from (select coalesce(t1.dom_s, t2.dom_s) as dom, coalesce(t1.devid_s, t2.devid_s) as devid,
    coalesce(t1.vd_s, t2.vd_s) as vd, coalesce(t1.srcintf, t2.dstintf) as intf, sum(coalesce
    (t1.total_sent, 0)+coalesce(t2.total_rcvd, 0)) as download, sum(coalesce(t2.total_sent, 0)+
    coalesce(t1.total_rcvd, 0)) as upload from qry t1 full join qry t2 on t1.dom_s=t2.dom_s and
    t1.srcintf=t2.dstintf group by dom, devid, vd, intf) t where $filter-drilldown group by dom
  order by dom
```

Dataset Name	Description	Log Category
ctap-SB-Files-Needing-Inspection-vs-Others	Files Needing Inspection vs Others	virus

```
select
(
case when suffix in (
'bat', 'cmd', 'exe', 'jar', 'msi', 'vbs',
'7z', 'zip', 'gzip', 'lzw', 'tar',
'rar', 'cab', 'doc', 'docx', 'xls',
'xlsx', 'ppt', 'pptx', 'pdf', 'swf',
'lnk', 'js'
) then 'Higher Risk File Types' else 'Excluded Files' end
) as files,
sum(total_num) as total_num
from
###({{FGT_DATASET_VIRUS_FSA_DETECTED_FILE_TYPES}})### t group by files order by total_num
desc
```

Dataset Name	Description	Log Category
ctap-SB-Breakdown-of-File-Types	Breakdown of File Types	virus

```
select
(
case when suffix in (
'exe', 'msi', 'upx', 'vbs', 'bat', 'cmd',
'dll', 'ps1', 'jar'
) then 'Executable Files' when suffix in ('pdf') then 'Adobe PDF' when suffix in ('swf')
then 'Adobe Flash' when suffix in (
'doc', 'docx', 'rtf', 'dotx', 'docm',
'dotm', 'dot'
) then 'Microsoft Word' when suffix in (
'xls', 'xlsx', 'xltx', 'xlsm', 'xlsb',
'xlam', 'xlt'
) then 'Microsoft Excel' when suffix in (
'ppsx', 'ppt', 'pptx', 'potx', 'sldx',
'pptm', 'ppsm', 'potm', 'ppam', 'sldm',
'pps', 'pot'
) then 'Microsoft PowerPoint' when suffix in ('msg') then 'Microsoft Outlook' when suffix
in ('htm', 'js', 'url', 'lnk') then 'Web Files' when suffix in (
'cab', 'tgz', 'z', '7z', 'tar', 'lzh',
'kgb', 'rar', 'zip', 'gz', 'xz', 'bz2'
) then 'Archive Files' when suffix in ('apk') then 'Android Files' else 'Others' end
) as filetype,
sum(total_num) as total_num
from
###({{FGT_DATASET_VIRUS_FSA_DETECTED_FILE_TYPES}})### t group by filetype order by total_num
desc
```

Dataset Name	Description	Log Category
ctap-SB-Top-Sandbox-Malicious-Exes		virus



```

select
  (
    case fsaverdict when 'malicious' then 5 when 'high risk' then 4 when 'medium risk' then 3
when 'low risk' then 2 else 1 end
  ) as risk,
  filename,
  service,
  count(*) as total_num
from
  $log
where
  $filter
  and dtype = 'fortisandbox'
  and file_name_ext(filename)= 'exe'
  and fsaverdict not in ('clean', 'submission failed')
group by
  filename,
  risk,
  service
order by
  risk desc,
  total_num desc,
  filename

```

Dataset Name	Description	Log Category
ctap-SB-Sources-of-Sandbox-Discovered-Malware	Sources of Sandbox Discovered Malware	virus

```

select
  srcip,
  count(*) as total_num
from
  $log
where
  $filter
  and dtype = 'fortisandbox'
  and nullifna(filename) is not null
  and fsaverdict not in ('clean', 'submission failed')
group by
  srcip
order by
  total_num desc

```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-High-Risk-Application	Application risk high risk application	traffic

```

select
  risk as d_risk,
  count(distinct user_src) as users,
  id,
  name,
  app_cat,
  technology,
  sum(bandwidth) as bandwidth,

```

```

sum(sessions) as sessions
from
    ###(select lower(app) as lowapp, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count
(*) as sessions from $log where $filter and (logflag&1>0) group by lowapp, user_src order by
bandwidth desc)### t1 inner join app_mdata t2 on t1.lowapp=lower(t2.name) where risk>='4'
group by id, name, app_cat, technology, risk order by d_risk desc, sessions desc

```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Application-Vulnerability	Application vulnerabilities discovered	attack

```

select
    attack,
    attackid,
    vuln_type,
    cve,
    severity_number,
    count(distinct dstip) as victims,
    count(distinct srcip) as sources,
    sum(totalnum) as totalnum
from
    ###(select attack, attackid, vuln_type, t2.cve, (case when t1.severity='critical' then 5
when t1.severity='high' then 4 when t1.severity='medium' then 3 when t1.severity='low' then 2
when t1.severity='info' then 1 else 0 end) as severity_number, dstip, srcip, count(*) as total-
num from $log t1 left join (select name, cve, vuln_type from ips_mdata) t2 on t1.at-
tack=t2.name where $filter and nullifna(attack) is not null and t1.severity is not null group
by attack, attackid, vuln_type, t2.cve, t1.severity, dstip, srcip )### t group by attack,
attackid, vuln_type, severity_number, cve order by severity_number desc, totalnum desc

```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Common-Virus-Botnet-Spyware	Common Virus Botnet Spyware	app-ctrl

```

select
    malware as virus,
    (
        case when lower(appcat)= 'botnet' then 'Botnet C&C' else (
            case when malware like 'Riskware%' then 'Spyware' when malware like 'Adware%' then
'Adware' else 'Virus' end
        ) end
    ) as malware_type,
    appid,
    app,
    count(distinct dstip) as victims,
    count(distinct srcip) as source,
    sum(total_num) as total_num
from
    (
        ###(select app as malware, appcat, appid, app, dstip, srcip, count(*) as total_num from
$log-app-ctrl where $filter and lower(appcat)='botnet' group by malware, appcat, appid, app,
dstip, srcip, app order by total_num desc)### union all ###(select virus as malware, 'null' as
appcat, 0 as appid, service as app, dstip, srcip, count(*) as total_num from $log-virus where
$filter and virus is not null group by malware, appcat, app, appid, dstip, srcip order by

```

```
total_num desc)### union all ###(select attack as malware, 'null' as appcat, 0 as appid, service as app, dstip, srcip, count(*) as total_num from $log-attack where $filter and (logflag&16>0) group by malware, appcat, app, appid, dstip, srcip order by total_num desc)###) t group by malware, malware_type, app, appid order by total_num desc
```

Dataset Name	Description	Log Category
ctap-App-Risk-Reputation-Top-Devices-By-Scores	Reputation Top Devices By-Scores	traffic

```
select
  coalesce(
    nullifna(`srcname`),
    ipstr(`srcip`),
    nullifna(`srcmac`)
  ) as dev_src,
  sum(crsscore % 65536) as scores
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and crsscore is not null
group by
  dev_src
having
  sum(crsscore % 65536) > 0
order by
  scores desc
```

Dataset Name	Description	Log Category
ctap-HTTP-SSL-Traffic-Ratio	HTTP SSL Traffic Ratio	traffic

```
select
  (
    case when service in ('80/tcp', 'HTTP', 'http') then 'HTTP' else 'HTTPS' end
  ) as service,
  sum(
    coalesce(sentbyte, 0) + coalesce(rcvbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
  and service in (
    '80/tcp', '443/tcp', 'HTTP', 'HTTPS',
    'http', 'https'
  )
group by
```

```

service
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
ctap-Top-Source-Countries	Top Source Countries	traffic

```

select
    srccountry,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and nullifna(srccountry) is not null
    and srccountry <> 'Reserved'
group by
    srccountry
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc,
    srccountry

```

Dataset Name	Description	Log Category
ctap-SaaS-Apps	CTAP SaaS Apps	traffic

```

select
    app_group,
    sum(bandwidth) as bandwidth
from
    ###({{FGT_DATASET_TRAFFIC_APP_BANDWIDTH}})### t1 inner join app_mdata t2 on lower(t1.app_group)=lower(t2.name) where behavior like '%Cloud%' group by app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
ctap-IaaS-Apps	CTAP IaaS Apps	traffic

```

select
    app_group,
    sum(bandwidth) as bandwidth
from

```

```
###({{FGT_DATASET_TRAFFIC_APP_BANDWIDTH}})### t1 inner join app_mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Cloud.IT' group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
ctap-RAS-Apps	CTAP RAS Apps	traffic

```
select
  name as app_group,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_APP_BANDWIDTH}})### t1 inner join app_mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Remote.Access' group by name order by bandwidth desc
```

Dataset Name	Description	Log Category
ctap-Proxy-Apps	CTAP Proxy Apps	traffic

```
select
  name as app_group,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_APP_BANDWIDTH}})### t1 inner join app_mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Proxy' group by name order by bandwidth desc
```

Dataset Name	Description	Log Category
ctap-Top-SocialMedia-App-By-Bandwidth	Top SocialMedia Applications by Bandwidth Usage	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions
from
  ###({{FGT_DATASET_TRAFFIC_APP_BANDWIDTH}})### t1 inner join app_mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Social.Media' group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
ctap-Top-Streaming-App-By-Bandwidth	Top Streaming applications by bandwidth usage	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions
from
  ###({{FGT_DATASET_TRAFFIC_APP_BANDWIDTH}})### t1 inner join app_mdata t2 on lower(t1.app_group)=lower(t2.name) where app_cat='Video/Audio' group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
ctap-Top-Game-App-By-Bandwidth	Top Game applications by bandwidth usage	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions
from
  ###({{FGT_DATASET_TRAFFIC_APP_BANDWIDTH}})### t1 inner join app_mdata t2 on lower(t1.app_
group)=lower(t2.name) where app_cat='Game' group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
ctap-Top-P2P-App-By-Bandwidth	Top P2P applications by bandwidth usage	traffic

```
select
  app_group,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions
from
  ###({{FGT_DATASET_TRAFFIC_APP_BANDWIDTH}})### t1 inner join app_mdata t2 on lower(t1.app_
group)=lower(t2.name) where app_cat='P2P' group by app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
ctap-apprisk-ctrl-Top-Web-Categories-Visited	Top 25 Web Categories Visited	traffic

```
select
  catdesc,
  count(distinct f_user) as user_num,
  sum(sessions) as sessions,
  sum(bandwidth) as bandwidth
from
  ###(select catdesc, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as f_
user, count(*) as sessions, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from
$log-traffic where $filter and catdesc is not null and (logflag&1>0) and (countweb>0 or
((logver is null or logver<502000000) and (hostname is not null or utmevent in ('webfilter',
'banned-word', 'web-content', 'command-block', 'script-filter')))) group by f_user, catdesc
order by sessions desc)### t group by catdesc order by sessions desc
```

Dataset Name	Description	Log Category
ctap-App-Risk-Applications-Running-Over-HTTP	Application risk applications running over HTTP	traffic

```
select
  app_group_name(app) as app_group,
  service,
  count(*) as sessions,
```

```

sum(
  coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
  and service in (
    '80/tcp', '443/tcp', 'HTTP', 'HTTPS',
    'http', 'https'
  )
group by
  app_group,
  service
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
ctap-App-Risk-Web-Browsing-Activity-Hostname-Category	Application risk web browsing activity hostname category	webfilter

```

select
  domain,
  catdesc,
  sum(visits) as visits
from
  ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, catdesc, count(*) as visits from $log where $filter and (eventtype is null or logver>=502000000) and catdesc is not null group by domain, catdesc order by visits desc)### t group by domain, catdesc order by visits desc

```

Dataset Name	Description	Log Category
ctap-Top-Sites-By-Browsing-Time	Traffic top sites by browsing time	traffic

```

select
  hostname,
  string_agg(distinct catdesc, ', ') as agg_catdesc,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out
from

```

```
###({{FGT_DATASET_TRAFFIC_TOP_SITES_BY_EB_TIME}})### t group by hostname order by browsetime desc
```

Dataset Name	Description	Log Category
ctap-Average-Bandwidth-Hour	Average Bandwidth Hour	traffic

```
select
    hourstamp,
    sum(bandwidth)/ count(distinct daystamp) as bandwidth
from
    ###(select to_char(from_dtime(dtime), 'HH24:00') as hourstamp, to_char(from_dtime(dtime),
    'DD Mon') as daystamp, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth from $log
    where $filter and (logflag&1>0) group by hourstamp, daystamp having sum(coalesce(sentbyte, 0)+
    coalesce(rcvdbyte, 0))>0 order by hourstamp)### t group by hourstamp order by hourstamp
```

Dataset Name	Description	Log Category
ctap-Top-Bandwidth-Hosts	Top Bandwidth Hosts	traffic

```
select
    hostname,
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    ) as bandwidth
from
    $log - traffic
where
    $filter
    and hostname is not null
    and (
        logflag&1>0
    )
group by
    hostname
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )>0
order by
    bandwidth desc
```

Dataset Name	Description	Log Category
saas-Application-Discovered	All Applications Discovered on the Network	traffic

```
select
    (
        case is_saas when 1 then 'SaaS Apps' else 'Other Apps' end
    ) as app_type,
    count(distinct app_s) as total_num
from
    ###({{FGT_DATASET_TRAFFIC_SAAS_APPS}})### t group by is_saas order by is_saas
```



Dataset Name	Description	Log Category
saas-SaaS-Application-by-Category	Number of SaaS Applications by Category	traffic

```
select
(
case saas_cat when 0 then 'Sanctioned' else 'Unsanctioned' end
) as saas_cat_str,
count(distinct app_s) as num_saas_app
from
###({{FGT_DATASET_TRAFFIC_SAAS_APP_BY_CAT}})### t where saas_cat in (0, 1) group by saas_cat
order by saas_cat
```

Dataset Name	Description	Log Category
saas-SaaS-Application-by-Bandwidth	Number of SaaS Applications by Bandwidth	traffic

```
select
(
case saas_cat when 0 then 'Sanctioned' else 'Tolerated' end
) as saas_cat_str,
sum(bandwidth) as bandwidth
from
###({{FGT_DATASET_TRAFFIC_SAAS_APP_BY_CAT}})### t where saas_cat in (0, 2) group by saas_cat
order by saas_cat
```

Dataset Name	Description	Log Category
saas-SaaS-Application-by-Session	Number of SaaS Applications by Session	traffic

```
select
(
case saas_cat when 0 then 'Sanctioned' else 'Tolerated' end
) as saas_cat_str,
sum(total_app) as total_app
from
###({{FGT_DATASET_TRAFFIC_SAAS_APP_BY_CAT}})### t where saas_cat in (0, 2) group by saas_cat
order by saas_cat
```

Dataset Name	Description	Log Category
saas-SaaS-App-Users-vs-Others	Number of Users of SaaS Apps vs Others	traffic

```
select
(
case is_saas when 0 then 'Other Apps' else 'SaaS Apps' end
) as app_type,
count(distinct saasuser) as total_user
from
###(select saasuser, saas_s/10 as is_saas from (select coalesce(nullifna('user'), nullifna('clouduser'), nullifna('unauthuser'), srcname, ipstr('srcip')) as saasuser, unnest(saasinfo) as saas_s from $log where $filter and apps is not null) t group by saasuser, is_saas)### t
group by app_type
```

Dataset Name	Description	Log Category
saas-SaaS-App-Users	Number of Users of SaaS Apps	traffic

```
select
(
case saas_cat when 0 then 'Sanctioned' when 1 then 'Unsanctioned' else 'Others' end
) as app_type,
count(distinct saasuser) as total_user
from
###(select saasuser, saas_s%10 as saas_cat from (select coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser, unnest(saasinfo) as saas_s from $log where $filter and apps is not null) t where saas_s>=10 group by saasuser, saas_cat)### t group by saas_cat order by saas_cat
```

Dataset Name	Description	Log Category
saas-Top-SaaS-User-by-Bandwidth-Session	Top SaaS Users by Bandwidth and Session	traffic

```
select
saasuser,
sum(bandwidth) as bandwidth,
sum(traffic_in) as traffic_in,
sum(traffic_out) as traffic_out,
sum(sessions) as sessions,
sum(session_block) as session_block,
(
sum(sessions)- sum(session_block)
) as session_pass,
count(distinct app_s) as total_app
from
###(select saasuser, app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as traffic_in, sum(sentbyte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_block from (select coalesce(nullifna(`user`), nullifna(`clouduser`), nullifna(`unauthuser`), srcname, ipstr(`srcip`)) as saasuser, unnest(apps) as app_s, unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce(rcvdbyte, 0) as rcvdbyte, (CASE WHEN (logflag&2>0) THEN 1 ELSE 0 END) as is_blocked from $log where $filter and apps is not null) t where saas_s>=10 group by saasuser, app_s order by bandwidth desc)### t group by saasuser order by bandwidth desc
```

Dataset Name	Description	Log Category
saas-Top-Category-by-SaaS-Application-Usage	Top Categories by SaaS Application Usage	traffic

```
select
app_cat,
(
case saas_cat when 0 then 'Sanctioned' else 'Unsanctioned' end
) as saas_cat_str,
count(distinct app_s) as total_app
from
###(select app_s, saas_s%10 as saas_cat from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s from $log where $filter and apps is not null) t where saas_s>=10 group by app_s, saas_cat)### t1 inner join app_mdata t2 on t1.app_s=t2.name where saas_cat in (0, 1) group by app_cat, saas_cat order by total_app desc
```

Dataset Name	Description	Log Category
saas-Top-SaaS-Category-by-Number-of-User	Top SaaS Categories by Number of Users	traffic

```
select
  app_cat,
  (
    case saas_cat when 0 then 'Sanctioned' else 'Unsanctioned' end
  ) as saas_cat_str,
  count(distinct saasuser) as total_user
from
  ###({{FGT_DATASET_TRAFFIC_SAAS_TOP_USER}})### t1 inner join app_mdata t2 on t1.app_s=t2.name
where saas_cat in (0, 1) group by app_cat, saas_cat order by total_user desc
```

Dataset Name	Description	Log Category
saas-Top-User-by-Number-of-SaaS-Application	Top Users by Number of SaaS Applications	traffic

```
select
  saasuser,
  (
    case saas_cat when 0 then 'Sanctioned' else 'Unsanctioned' end
  ) as saas_cat_str,
  count(distinct app_s) as total_app
from
  ###({{FGT_DATASET_TRAFFIC_SAAS_TOP_USER}})### t where saas_cat in (0, 1) group by saasuser,
saas_cat order by total_app desc
```

Dataset Name	Description	Log Category
saas-Top-SaaS-Application-by-Bandwidth-Session	Top SaaS Applications by Sessions and Bandwidth	traffic

```
select
  t2.id as app_id,
  app_s,
  app_cat,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
    sum(sessions)- sum(session_block)
  ) as session_pass
from
  ###(select app_s, sum(sentbyte+rcvdbyte) as bandwidth, sum(rcvdbyte) as traffic_in, sum(sent-
byte) as traffic_out, count(*) as sessions, sum(is_blocked) as session_block from (select
unnest(apps) as app_s, unnest(saasinfo) as saas_s, coalesce(sentbyte, 0) as sentbyte, coalesce
(rcvdbyte, 0) as rcvdbyte, (CASE WHEN (logflag&2>0) THEN 1 ELSE 0 END) as is_blocked from $log
where $filter and apps is not null) t where saas_s>=10 group by app_s)### t1 inner join app_
mdata t2 on t1.app_s=t2.name group by app_id, app_s, app_cat order by bandwidth desc
```

Dataset Name	Description	Log Category
saas-Top-Tolerated-SaaS-Application-by-Bandwidth	Top Tolerated SaaS Applications by Bandwidth	traffic

```
select
  app_s,
  sum(sentbyte + rcvdbyte) as bandwidth
from
  (
    select
      unnest(apps) as app_s,
      unnest(saasinfo) as saas_s,
      coalesce(sentbyte, 0) as sentbyte,
      coalesce(rcvdbyte, 0) as rcvdbyte
    from
      $log
    where
      $filter
      and apps is not null
  ) t
where
  saas_s = 12
group by
  app_s
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
saas-drilldown-Top-Tolerated-SaaS-Application	Top Tolerated SaaS Applications	traffic

```
select
  app_s,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
    sum(sessions) - sum(session_block)
  ) as session_pass
from
  ###({{FGT_DATASET_TRAFFIC_TOLERATED_SAAS_APP}})### t where $filter-drilldown group by app_s
order by bandwidth desc
```

Dataset Name	Description	Log Category
saas-Top-User-by-Tolerated-SaaS-Application-Drilldown	Top Users by Tolerated SaaS Applications	traffic

```
select
  saasuser,
  count(distinct app_s) as total_app
```

```

from
  ###({{FGT_DATASET_TRAFFIC_TOLERATED_SAAS_APP}})### t group by saasuser order by total_app
desc

```

Dataset Name	Description	Log Category
saas-drilldown-Top-File-Sharing-SaaS-Application-Detail	Top File Sharing SaaS Applications Detail	traffic

```

select
  saasuser,
  sum(bandwidth) as bandwidth,
  sum(traffic_in) as traffic_in,
  sum(traffic_out) as traffic_out,
  sum(sessions) as sessions,
  sum(session_block) as session_block,
  (
    sum(sessions)- sum(session_block)
  ) as session_pass
from
  ###({{FGT_DATASET_TRAFFIC_SAAS_APP_GROUP}})### t where $filter-drilldown group by saasuser
order by sessions desc

```

Dataset Name	Description	Log Category
saas-Top-File-Sharing-SaaS-Application	Top File Sharing Applications	traffic

```

select
  t2.id as appid,
  (
    case t2.risk when '5' then 'Critical' when '4' then 'High' when '3' then 'Medium' when '2'
then 'Info' else 'Low' end
  ) as risk,
  app_group,
  bandwidth,
  traffic_in,
  traffic_out,
  sessions,
  session_block,
  session_pass,
  total_user
from
  (
    select
      app_group,
      count(distinct saasuser) as total_user,
      sum(bandwidth) as bandwidth,
      sum(traffic_in) as traffic_in,
      sum(traffic_out) as traffic_out,
      sum(sessions) as sessions,
      sum(session_block) as session_block,
      (
        sum(sessions)- sum(session_block)
      ) as session_pass
    from

```

```

    ###({{FGT_DATASET_TRAFFIC_SAAS_APP_GROUP}})### t group by app_group) t1 inner join app_
mdata t2 on lower(t1.app_group)=lower(t2.name) where t2.app_cat='Storage.Backup' order by
total_user desc, bandwidth desc

```

Dataset Name	Description	Log Category
saas-Top-File-Sharing-SaaS-Application-Drilldown	Top File Sharing Applications	traffic

```

select
    t2.id as appid,
    (
        case t2.risk when '5' then 'Critical' when '4' then 'High' when '3' then 'Medium' when '2'
then 'Info' else 'Low' end
    ) as risk,
    app_group,
    bandwidth,
    traffic_in,
    traffic_out,
    sessions,
    session_block,
    session_pass,
    total_user
from
    (
        select
            app_group,
            count(distinct saasuser) as total_user,
            sum(bandwidth) as bandwidth,
            sum(traffic_in) as traffic_in,
            sum(traffic_out) as traffic_out,
            sum(sessions) as sessions,
            sum(session_block) as session_block,
            (
                sum(sessions)- sum(session_block)
            ) as session_pass
        from
            ###({{FGT_DATASET_TRAFFIC_SAAS_APP_GROUP}})### t group by app_group) t1 inner join app_
mdata t2 on lower(t1.app_group)=lower(t2.name) where t2.app_cat='Storage.Backup' order by
total_user desc, bandwidth desc

```

Dataset Name	Description	Log Category
aware-Device-By-Location	Device by Location	traffic

```

select
    'All' : :text as country,
    count(distinct devid) as device_count
from
    ###(select devid from $log where $filter group by devid)### t

```

Dataset Name	Description	Log Category
aware-Network-Endpoint-Devices	Endpoint Devices on Network	

```
select
  category,
  total_num
from
  (
    select
      'Seen Devices' as category,
      1 as idx,
      count(distinct epname) as total_num
    from
      (
        select
          epname,
          max(lastseen) as itime
        from
          $ADOM_ENDPOINT
        where
          epname is not null
        group by
          epname
      ) t
    where
      $filter
    union all
    select
      'New Devices' as category,
      2 as idx,
      count(distinct epname) as total_num
    from
      (
        select
          epname,
          min(firstseen) as itime
        from
          $ADOM_ENDPOINT
        where
          epname is not null
        group by
          epname
      ) t
    where
      $filter
    union all
    select
      'Unseen Devices' as category,
      3 as idx,
      count(distinct t1.epname) as total_num
    from
      $ADOM_ENDPOINT t1
    where
      not exists (
        select
          1
        from
          (
            select
```

```

        epname,
        max(lastseen) as itime
    from
        $ADOM_ENDPOINT
    where
        epname is not null
    group by
        epname
    ) t2
    where
        $filter
        and t1.epname = t2.epname
    )
) t
order by
    idx

```

Dataset Name	Description	Log Category
aware-New-Endpoint-Devices	New Endpoint Devices	

```

drop
    table if exists devmap_tmp; create temporary table devmap_tmp as (
        select
            epid,
            max(euid) as max_euid
        from
            $ADOM_EPEU_DEVMAP
        where
            euid & gt;= 1024
        group by
            epid
    );
select
    timestamp,
    epname as hostname,
    max(osname) as osname,
    max(devtype) as devtype,
    max(srcip) as srcip,
    string_agg(distinct epname, ',') as user_agg
from
    (
        select
            from_itime(itime) as timestamp,
            osname,
            epname,
            epdevtype as devtype,
            epip as srcip,
            epid
        from
            (
                select
                    max(osname) as osname,
                    max(epname) as epname,
                    max(epdevtype) as epdevtype,
                    max(epip) as epip,

```



## Dataset Reference List

```
        epid,
        min(firstseen) as itime
    from
        $ADOM_ENDPOINT
    where
        epname is not null
    group by
        epname,
        epid
    ) t
    where
        $filter
    ) t1
    inner join devmap_tmp on devmap_tmp.epid = t1.epid
    inner join $ADOM_ENDUSER as teu on devmap_tmp.max_euid = teu.euid
group by
    timestamp,
    hostname
order by
    timestamp desc
```

Dataset Name	Description	Log Category
aware-New-Endpoint-Devices-Trend	New Endpoint Devices Trend	

```
select
    $flex_timescale(itime) as hodex,
    count(distinct epname) as total_num
from
    (
        select
            epname,
            min(firstseen) as itime
        from
            $ADOM_ENDPOINT
        where
            epname is not null
        group by
            epname
    ) t
where
    $filter
group by
    hodex
order by
    hodex
```

Dataset Name	Description	Log Category
aware-Top-Endpoint-Operating-Systems	Top Endpoint Operating Systems	fct-traffic

```
select
    os1 as os,
    count(distinct hostname) as total_num
from
```

```
###(select split_part(os, ',', 1) as os1, hostname from $log where $filter and nullifna(os)
is not null group by os1, hostname)### t group by os order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Endpoint-Applications-Windows	Top Endpoint Applications Windows	fct-traffic

```
select
  srcname1 as srcname,
  count(distinct hostname) as total_num
from
  ###(select split_part(srcname, '.', 1) as srcname1, hostname from $log where $filter and nullifna(srcname) is not null and lower(os) like '%windows%' group by srcname, hostname)### t
group by srcname order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Endpoint-Applications-Mac	Top Endpoint Applications Mac	fct-traffic

```
select
  srcname1 as srcname,
  count(distinct hostname) as total_num
from
  ###(select split_part(srcname, '.', 1) as srcname1, hostname from $log where $filter and nullifna(srcname) is not null and lower(os) like '%mac os%' group by srcname, hostname)### t
group by srcname order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-SaaS-Application-by-Number-of-Users	Top SaaS Applications by Number of Users	traffic

```
select
  app_group,
  count(distinct saasuser) as total_user
from
  ###(select app_group_name(app_s) as app_group, saasuser from (select unnest(apps) as app_s, unnest(saasinfo) as saas_s, coalesce(nullifna('user'), nullifna('clouduser'), nullifna('unauthuser'), srcname, ipstr('srcip')) as saasuser from $log where $filter and (logflag&1>0) and apps is not null) t where saas_s>=10 group by app_group, saasuser)### t group by app_group
order by total_user desc
```

Dataset Name	Description	Log Category
aware-Summary-Of-Changes	Summary of Changes	event

```
select
  regexp_replace(msg, '[^ ]*$', '') as msg_trim,
  count(*) as total_num
from
  $log
where
  $filter
  and logid_to_int(logid)= 44547
group by
```

```

    msg_trim
order by
    total_num desc

```

Dataset Name	Description	Log Category
aware-Change-Details	Change Details	event

```

select
    $calendar_time as timestamp,
    `user`,
    ui,
    msg
from
    $log
where
    $filter
    and logid_to_int(logid)= 44547
order by
    timestamp desc

```

Dataset Name	Description	Log Category
aware-Vulnerabilities-By-Severity	Vulnerabilities by Security	fct-netscan

```

select
    vulnseverity,
    count(distinct vulnname) as vuln_num
from
    ###(select vulnseverity, vulnname from $log where $filter and nullifna(vulnname) is not null
    and nullifna(vulnseverity) is not null group by vulnseverity, vulnname)### t group by
    vulnseverity order by vuln_num desc

```

Dataset Name	Description	Log Category
aware-Vulnerabilities-Trend	Vulnerabilities Trend	fct-netscan

```

select
    $flex_timescale(timestamp) as timescale,
    sum(critical) as critical,
    sum(high) as high,
    sum(medium) as medium,
    sum(low) as low
from
    ###(select $flex_timestamp as timestamp, sum(case when lower(vulnseverity) = 'critical' then
    1 else 0 end) as critical, sum(case when lower(vulnseverity) = 'high' then 1 else 0 end) as
    high, sum(case when lower(vulnseverity) = 'medium' then 1 else 0 end) as medium, sum(case when
    lower(vulnseverity) = 'notice' then 1 else 0 end) as Low from $log where $filter group by
    timestamp order by timestamp desc)### t group by timescale order by timescale

```

Dataset Name	Description	Log Category
aware-Top-Critical-Vulnerabilities	Top Critical Vulnerabilities	fct-netscan

```

select
    vulnname,

```

```

vulnseverity,
vulncat,
count(distinct hostname) as total_num
from
###(select hostname, vulnname, vulnseverity, vulncat, count(*) as total_num from $log where
$filter and nullifna(vulnname) is not null and vulnseverity='Critical' group by hostname, vul-
nname, vulnseverity, vulncat order by total_num desc)### t group by vulnname, vulnseverity,
vulncat order by total_num desc

```

Dataset Name	Description	Log Category
aware-Top-Vulnerabilities-Last-Period	Top Vulnerabilities Last Period	fct-netscan

```

select
vulnname,
vulnseverity,
sev_num,
vulncat,
count(distinct hostname) as total_num
from
###(select hostname, vulnname, vulnseverity, (CASE vulnseverity WHEN 'Critical' THEN 5 WHEN
'High' THEN 4 WHEN 'Medium' THEN 3 WHEN 'Info' THEN 2 WHEN 'Low' THEN 1 ELSE 0 END) as sev_
num, vulncat, count(*) as total_num from $log where $pre_period $filter and nullifna(vulnname)
is not null group by hostname, vulnname, vulnseverity, vulncat order by sev_num desc, total_
num desc)### t group by vulnname, vulnseverity, sev_num, vulncat order by sev_num desc, total_
num desc

```

Dataset Name	Description	Log Category
aware-Top-New-Vulnerabilities	Top New Vulnerabilities	fct-netscan

```

drop
table if exists rpt_tmptbl_1;
drop
table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
vulnid,
vulnname,
vulnseverity,
vulncat,
hostname
from
###(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $pre_period
$filter and nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; create temporary
table rpt_tmptbl_2 as select vulnid, vulnname, vulnseverity, vulncat, hostname from ###(select
vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $filter and nullifna(vul-
nname) is not null group by vulnid, vulnname, vulnseverity, vulncat, hostname)### t group by
vulnid, vulnname, vulnseverity, vulncat, hostname; select vulnname, (case when vulnsever-
ity='Critical' then 5 when vulnseverity='High' then 4 when vulnseverity='Medium' then 3 when
vulnseverity='Low' then 2 when vulnseverity='Info' then 1 else 0 end) as sev, vulnseverity,
vulncat, count(distinct hostname) as host_num, cve_id from rpt_tmptbl_2 t1 left join fct_mdata
t2 on t1.vulnid=t2.vid::int where not exists (select 1 from rpt_tmptbl_1 where t1.vulnid=rpt_
tmptbl_1.vulnid) group by vulnname, sev, vulnseverity, vulncat, cve_id order by sev desc,
host_num desc

```

Dataset Name	Description	Log Category
aware-Top-User-With-Critical-Vulnerabilities	Top Users with Critical Vulnerabilities	fct-netscan

```
select
  hostname,
  `user` as user_src,
  vulnname,
  vulncat,
  count(*) as total_num
from
  $log
where
  $filter
  and nullifna(`user`) is not null
  and vulnseverity = 'Critical'
group by
  hostname,
  user_src,
  vulnname,
  vulncat
order by
  total_num desc
```

Dataset Name	Description	Log Category
aware-Ingress-Data-Flow-By-Zone	Ingress Data Flow By Zone	traffic

```
select
  app,
  tag,
  sum(rcvdbyte) as rcvdbyte
from
  ###(select dvid, app, dstintf, sum(coalesce(rcvdbyte, 0)) as rcvdbyte from $log where $filter
  group by dvid, app, dstintf having sum(coalesce(rcvdbyte, 0)) > 0 order by rcvdbyte
  desc)### tt1 inner join (select dvid, intfname, unnest(tags) as tag from intfinfo) tt2 on
  tt1.dvid=tt2.dvid and tt1.dstintf=tt2.intfname group by app, tag order by rcvdbyte desc
```

Dataset Name	Description	Log Category
aware-Egress-Data-Flow-By-Zone	Egress Data Flow By Zone	traffic

```
select
  app,
  tag,
  sum(sentbyte) as sentbyte
from
  ###(select dvid, app, srcintf, sum(coalesce(sentbyte, 0)) as sentbyte from $log where $filter
  group by dvid, app, srcintf having sum(coalesce(sentbyte, 0)) > 0 order by sentbyte
  desc)### tt1 inner join (select dvid, intfname, unnest(tags) as tag from intfinfo) tt2 on
  tt1.dvid=tt2.dvid and tt1.srcintf=tt2.intfname group by app, tag order by sentbyte desc
```

Dataset Name	Description	Log Category
aware-Top-Device-Attack-Targets	Top Device Attack Targets	fct-netscan

```

select
    hostname,
    count(*) as total_num
from
    $log
where
    $filter
    and nullifna(hostname) is not null
    and nullifna(vulnname) is not null
group by
    hostname
order by
    total_num desc

```

Dataset Name	Description	Log Category
aware-Top-Attack-Targets	Top Attack Targets	fct-netscan

```

select
    hostname,
    srcip,
    os,
    vuln_num,
    (
        CASE sevid WHEN 5 THEN 'Critical' WHEN 4 THEN 'High' WHEN 3 THEN 'Medium' WHEN '2' THEN
'Info' ELSE 'Low' END
    ) as vulnseverity,
    sevid as severity_num,
    left(cve_agg, 512) as cve_agg
from
    (
        select
            hostname,
            max(srcip) as srcip,
            string_agg(distinct os1, '/') as os,
            count(distinct vulnname) as vuln_num,
            max(
                (
                    CASE vulnseverity WHEN 'Critical' THEN 5 WHEN 'High' THEN 4 WHEN 'Medium' THEN 3
WHEN 'Info' THEN 2 WHEN 'Low' THEN 1 ELSE 0 END
                )
            ) as sevid,
            string_agg(distinct cve_id, ',') as cve_agg
        from
            ###(select hostname, max(deviceip) as srcip, split_part(os, ',', 1) as os1, vulnname,
vulnseverity, vulnid from $log where $filter and nullifna(vulnname) is not null and nullifna
(vulnseverity) is not null group by hostname, os1, vulnname, vulnseverity, vulnid)### t1 left
join fct_mdata t2 on t1.vulnid=t2.vid::int group by hostname) t order by severity_num desc,
vuln_num desc

```

Dataset Name	Description	Log Category
aware-Threats-By-Severity	Threats by Severity	attack

```

select
    initcap(sev) as severity,

```

```

sum(total_num) as total_num
from
(
    ###(select crlevel::text as sev, count(*) as total_num from $log-virus where $filter and
    nullifna(virus) is not null and crlevel is not null group by sev order by total_num desc)###
    union all ###(select severity::text as sev, count(*) as total_num from $log-attack where $filter and
    nullifna(attack) is not null and severity is not null group by sev order by total_num
    desc)### union all ###(select apprisk::text as sev, count(*) as total_num from $log-app-ctrl
    where $filter and lower(appcat)='botnet' and apprisk is not null group by sev order by total_
    num desc)###) t group by severity order by total_num desc

```

Dataset Name	Description	Log Category
aware-Threats-Type-By-Severity	Threats Type by Severity	virus

```

select
    threat_type,
    sum(critical) as critical,
    sum(high) as high,
    sum(medium) as medium,
    sum(low) as low
from
(
    ###(select (case when eventtype='botnet' then 'Botnets' else 'Malware' end) as threat_
    type, sum(case when crlevel = 'critical' then 1 else 0 end) as critical, sum(case when crlevel
    = 'high' then 1 else 0 end) as high, sum(case when crlevel = 'medium' then 1 else 0 end) as
    medium, sum(case when crlevel = 'low' then 1 else 0 end) as low from $log-virus where $filter
    and nullifna(virus) is not null group by threat_type)### union all ###(select 'Intrusions' as
    threat_type, sum(case when severity = 'critical' then 1 else 0 end) as critical, sum(case when
    severity = 'high' then 1 else 0 end) as high, sum(case when severity = 'medium' then 1 else 0
    end) as medium, sum(case when severity = 'low' then 1 else 0 end) as low from $log-attack
    where $filter and nullifna(attack) is not null group by threat_type)### union all ###(select
    'Botnets' as threat_type, sum(case when apprisk = 'critical' then 1 else 0 end) as critical,
    sum(case when apprisk = 'high' then 1 else 0 end) as high, sum(case when apprisk = 'medium'
    then 1 else 0 end) as medium, sum(case when apprisk = 'low' then 1 else 0 end) as low from
    $log-app-ctrl where $filter and lower(appcat)='botnet' group by threat_type)###) t group by
    threat_type

```

Dataset Name	Description	Log Category
aware-Threats-By-Day	Threats by Day	virus

```

select
    daystamp,
    sum(total_num) as total_num
from
(
    ###(select $day_of_week as daystamp, count(*) as total_num from $log-virus where $filter
    and nullifna(virus) is not null group by daystamp)### union all ###(select $day_of_week as day-
    stamp, count(*) as total_num from $log-attack where $filter and nullifna(attack) is not null
    group by daystamp)### union all ###(select $day_of_week as daystamp, count(*) as total_num
    from $log-app-ctrl where $filter and lower(appcat)='botnet' group by daystamp)###) t group by
    daystamp order by daystamp

```

Dataset Name	Description	Log Category
aware-Threats-By-Day-Radar	Threats by Day	virus

```
select
    daystamp,
    sum(total_num) as total_num
from
    (
        ###(select $day_of_week as daystamp, count(*) as total_num from $log-virus where $filter
        and nullifna(virus) is not null group by daystamp)### union all ###(select $day_of_week as day-
        stamp, count(*) as total_num from $log-attack where $filter and nullifna(attack) is not null
        group by daystamp)### union all ###(select $day_of_week as daystamp, count(*) as total_num
        from $log-app-ctrl where $filter and lower(appcat)='botnet' group by daystamp)###) t group by
        daystamp order by daystamp
```

Dataset Name	Description	Log Category
aware-Count-Of-Malware-Events	Count of Malware Events	virus

```
select
    virus,
    count(*) as total_num
from
    $log
where
    $filter
    and nullifna(virus) is not null
group by
    virus
order by
    total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Malware-By-Count	Top Malware by Count	app-ctrl

```
select
    virus,
    malware_type,
    risk_level,
    count(distinct dstip) as victim,
    count(distinct srcip) as source,
    sum(total_num) as total_num
from
    (
        ###(select app as virus, 'Botnet C&C' as malware_type, apprisk::text as risk_level, dstip,
        srcip, count(*) as total_num from $log-app-ctrl where $filter and lower(appcat)='botnet' and
        apprisk is not null group by app, malware_type, apprisk, dstip, srcip order by total_num
        desc)### union all ###(select virus, (case when eventtype='botnet' then 'Botnet C&C' else
        'Virus' end) as malware_type, crlevel::text as risk_level, dstip, srcip, count(*) as total_num
        from $log-virus where $filter and nullifna(virus) is not null and crlevel is not null group by
        virus, malware_type, crlevel, dstip, srcip order by total_num desc)### union all ###(select
        attack as virus, (case when eventtype='botnet' then 'Botnet C&C' else 'Virus' end) as malware_
        type, crlevel::text as risk_level, dstip, srcip, count(*) as total_num from $log-attack where
        $filter and (logflag&16>0) and crlevel is not null group by virus, malware_type, crlevel,
        dstip, srcip order by total_num desc)###) t group by virus, malware_type, risk_level order by
        total_num desc
```



Dataset Name	Description	Log Category
aware-Top-Failed-Login-Attempts	Top Failed Login Attempts	event

```
select
  `user` as f_user,
  ui,
  dstip,
  count(status) as total_failed
from
  $log
where
  $filter
  and nullifna(`user`) is not null
  and logid_to_int(logid) = 32002
group by
  ui,
  f_user,
  dstip
order by
  total_failed desc
```

Dataset Name	Description	Log Category
aware-Top-Failed-Authentication-Attempts	VPN failed logins	event

```
select
  f_user,
  tunneltype,
  sum(total_num) as total_num
from
  ###(select coalesce(nullifna(`xauthuser`), `user`) as f_user, tunneltype, count(*) as total_
num from $log where $filter and subtype='vpn' and (tunneltype='ipsec' or left(tunneltype,
3)='ssl') and action in ('ssl-login-fail', 'ipsec-login-fail') and coalesce(nullifna(`xau-
thuser`), nullifna(`user`)) is not null group by f_user, tunneltype)### t group by f_user, tun-
neltype order by total_num desc
```

Dataset Name	Description	Log Category
aware-Top-Denied-Connections	Top Denied Connections	traffic

```
select
  coalesce(
    nullifna(`user`),
    ipstr(`srcip`)
  ) as user_src,
  service || '(' || ipstr(srcip) || ')' as interface,
  dstip,
  count(*) as total_num
from
  $log
where
  $filter
  and (
    logflag&1>0
```

```

)
and action = 'deny'
group by
  user_src,
  interface,
  dstip
order by
  total_num desc

```

Dataset Name	Description	Log Category
aware-Failed-Compliance-Checked-By-Device	Failed Compliance Checked by Device	event

```

select
  devid,
  'Failed' as results,
  count(distinct reason) as total_num
from
  ###(select devid, reason from $log where $filter and subtype='compliance-check' and res-
ult='fail' group by devid, reason)### t group by devid, results order by total_num desc

```

Dataset Name	Description	Log Category
aware-loc-Blacklist-Summary	IOC Blacklist Summary	app-ctrl

```

drop
  table if exists tmp_ep_eu_map; create temporary table tmp_ep_eu_map as (
    select
      epid,
      euid
    from
      $ADOM_EPEU_DEVMAP
    where
      euid & gt;= 1024
  );
select
  coalesce(
    nullifna(ename),
    nullifna(
      ipstr(`srcip`)
    ),
    'Unknown'
  ) as ename,
  user_agg,
  sevid,
  (
    CASE sevid WHEN 5 THEN 'Critical' WHEN 4 THEN 'High' WHEN 3 THEN 'Medium' WHEN '2' THEN
'Info' ELSE 'Low' END
  ) as severity,
  threats,
  bl_count as total_bl
from
  (
    select
      th1.epid,

```

```
    srcip,
    sevid,
    bl_count,
    threats
from
(
    select
        epid,
        srcip,
        max(verdict)+ 1 as sevid,
        sum(bl_count) as bl_count
    from
        (
            (
                select
                    epid,
                    srcip,
                    day_st as itime,
                    bl_count,
                    verdict,
                    unnest(dvid) as dvid_s
                from
                    $ADOMTBL_PLHD_IOC_VERDICT
                where
                    bl_count>0
            )
            union all
            (
                select
                    epid,
                    srcip,
                    day_st as itime,
                    bl_count,
                    verdict,
                    unnest(dvid) as dvid_s
                from
                    $ADOMTBL_PLHD_INTERIM_IOC_VERDICT
                where
                    bl_count>0
            )
        ) tvdt
    left join devtable td on td.dvid = tvdt.dvid_s
where
    $filter
    and $filter - drilldown
group by
    epid,
    srcip
) th1
inner join (
    select
        epid,
        string_agg(name, ',') as threats
    from
        (
            (
```

```
select
  epid,
  thid
from
  (
    (
      select
        epid,
        thid,
        itime,
        unnest(dvid) as dvid_s
      from
        (
          select
            epid,
            unnest(threatid) as thid,
            day_st as itime,
            dvid
          from
            $ADOMTBL_PLHD_IOC_VERDICT
          where
            bl_count>0
        ) ta1
    )
    union all
    (
      select
        epid,
        thid,
        itime,
        unnest(dvid) as dvid_s
      from
        (
          select
            epid,
            unnest(threatid) as thid,
            day_st as itime,
            dvid
          from
            $ADOMTBL_PLHD_INTERIM_IOC_VERDICT
          where
            bl_count>0
        ) ta2
    )
  ) t
left join devtable td on td.dvid = t.dvid_s
where
  $filter
  and $filter - drilldown
group by
  epid,
  thid
) thr
inner join td_threat_name_mdata tm on tm.id = thr.thid
) t
group by
```

```

        epid
    ) th2 on th1.epid = th2.epid
) t1
left join (
    select
        epid,
        string_agg(distinct euname, ',') as user_agg
    from
        tmp_ep_eu_map tpu
        inner join $ADOM_ENDUSER as teu on tpu.euid = teu.euid
    group by
        epid
) t2 on t2.epid = t1.epid
inner join $ADOM_ENDPOINT as tep on tep.epid = t1.epid
order by
    total_bl desc,
    sevid desc

```

Dataset Name	Description	Log Category
aware-loc-Potential-Breach-By-Day	IOC Potential Breach by Day	app-ctrl

```

select
    number,
    day_st as itime
from
    (
        select
            count(epid) as number,
            to_char(
                from_otime(itime),
                'Day'
            ) as day_st
        from
            (
                select
                    epid,
                    day_st as itime,
                    unnest(dvid) as dvid_s
                from
                    $ADOMTBL_PLHD_INTERIM_IOC_VERDICT
                where
                    cs_count>0
            )
        union all
            (
                select
                    epid,
                    day_st as itime,
                    unnest(dvid) as dvid_s
                from
                    $ADOMTBL_PLHD_IOC_VERDICT
                where
                    cs_count>0
            )
    ) t
left join devtable td on td.dvid = t.dvid_s

```

```

        where
            $filter
            and $filter - drilldown
        group by
            day_st
    ) tt
order by
    itime

```

Dataset Name	Description	Log Category
aware-loc-Potential-Breach-By-Day-Bar	IOC Potential Breach by Day	app-ctrl

```

select
    number,
    day_st as itime
from
    (
        select
            count(epid) as number,
            to_char(
                from_otime(itime),
                'Day'
            ) as day_st
        from
            (
                select
                    epid,
                    day_st as itime,
                    unnest(dvid) as dvid_s
                from
                    $ADOMTBL_PLHD_INTERIM_IOC_VERDICT
                where
                    cs_count>0
                union all
                (
                    select
                        epid,
                        day_st as itime,
                        unnest(dvid) as dvid_s
                    from
                        $ADOMTBL_PLHD_IOC_VERDICT
                    where
                        cs_count>0
                )
            ) t
        left join devtable td on td.dvid = t.dvid_s
    ) tt
order by
    itime

```

Dataset Name	Description	Log Category
aware-loc-suspicion-summary	IOC Suspicion Summary	app-ctrl

```

select
  coalesce(
    nullifna(epname),
    nullifna(
      ipstr(`srcip`)
    ),
    'Unknown'
  ) as epname,
  cs_count as total_cs,
  cs_score as max_cs,
  verdict as max_verdict,
  threats
from
  (
    select
      th1.epid,
      srcip,
      itime,
      cs_count,
      verdict,
      cs_score,
      threats
    from
      (
        select
          epid,
          srcip,
          min(itime) as itime,
          sum(cs_count) as cs_count,
          max(verdict) as verdict,
          max(cs_score) as cs_score
        from
          (
            (
              select
                epid,
                srcip,
                day_st as itime,
                cs_count,
                verdict,
                cs_score,
                unnest(dvid) as dvid_s
              from
                $ADOMTBL_PLHD_IOC_VERDICT
              where
                bl_count = 0
                and cs_count>0
            )
            union all
            (
              select
                epid,

```

```
        srcip,
        day_st as itime,
        cs_count,
        verdict,
        cs_score,
        unnest(dvid) as dvid_s
    from
        $ADOMTBL_PLHD_INTERIM_IOC_VERDICT
    where
        bl_count = 0
        and cs_count>0
    )
    ) tvdt
    left join devtable td on td.dvid = tvdt.dvid_s
where
    $filter
    and $filter - drilldown
group by
    epid,
    srcip
) th1
inner join (
    select
        epid,
        string_agg(name, ',') as threats
    from
        (
            (
                select
                    epid,
                    thid
                from
                    (
                        (
                            select
                                epid,
                                thid,
                                itime,
                                unnest(dvid) as dvid_s
                            from
                                (
                                    select
                                        epid,
                                        unnest(threatid) as thid,
                                        day_st as itime,
                                        dvid
                                    from
                                        $ADOMTBL_PLHD_IOC_VERDICT
                                    where
                                        bl_count = 0
                                        and cs_count>0
                                ) ta1
                            )
                        )
                    ) union all
                    (
                        select
```



```

        epid,
        thid,
        itime,
        unnest(dvid) as dvid_s
    from
    (
        select
            epid,
            unnest(threatid) as thid,
            day_st as itime,
            dvid
        from
            $ADOMTBL_PLHD_INTERIM_IOC_VERDICT
        where
            bl_count = 0
            and cs_count>0
    ) ta2
    )
    ) tt1
    left join devtable td on td.dvid = tt1.dvid_s
where
    $filter
    and $filter - drilldown
group by
    epid,
    thid
    ) thr
    inner join td_threat_name_mdata tm on tm.id = thr.thid
    ) tt2
group by
    epid
    ) th2 on th1.epid = th2.epid
    ) t
    inner join $ADOM_ENDPOINT as tep on tep.epid = t.epid
order by
    max_verdict desc,
    max_cs desc,
    total_cs desc

```

Dataset Name	Description	Log Category
aware-Botnet-IP	Top Source IP Affected by Botnet	virus

```

select
    f_user,
    srcip,
    string_agg(distinct `virus`, ',') as virus_agg,
    count(
        distinct ipstr(`dstip`)
    ) as dstip_cnt,
    max(action) as action,
    sum(total_num) as total_num,
    min(
        from_itime(first_seen)
    ) as first_seen,
    max(

```

```

        from_itime(last_seen)
    ) as last_seen
from
    ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`)) as f_user, srcip, virus,
dstip, max(action) as action, count(*) as total_num, min(itime) as first_seen, max(itime) as
last_seen from $log where $filter and logid in ('0202009248', '0202009249') and virus is not
null group by srcip, f_user, virus, dstip order by total_num desc)### t group by srcip, f_user
order by total_num desc

```

Dataset Name	Description	Log Category
aware-Botnet-Domain	New Botnet Domains	dns

```

select
    botnet,
    count(distinct `qname`) as qname_cnt,
    count(
        distinct ipstr(`dstip`)
    ) as dnssvr_cnt,
    sum(total_num) as total_num,
    min(
        from_itime(first_seen)
    ) as first_seen,
    max(
        from_itime(last_seen)
    ) as last_seen
from
    ###(select coalesce(`botnetdomain`, ipstr(`botnetip`)) as botnet, qname, dstip, count(*) as
total_num, min(nanosec_to_sec(eventtime)) as first_seen, max(nanosec_to_sec(eventtime)) as
last_seen from $log where $filter and logid in ('1501054601', '1501054600') group by botnet,
qname, dstip order by total_num desc)### t group by botnet order by first_seen desc

```

Dataset Name	Description	Log Category
aware-High-Risk-URL-Category	Category of High Risk URLs	webfilter

```

select
    catdesc,
    string_agg(distinct hostname, ',') as hostname_agg,
    max(action) as action,
    sum(total_num) as total_num,
    min(
        from_itime(first_seen)
    ) as first_seen,
    max(
        from_itime(last_seen)
    ) as last_seen
from
    ###(select catdesc, hostname, max(action) as action, count(*) as total_num, min(itime) as
first_seen, max(itime) as last_seen from $log where $filter and cat in (26, 61, 86, 88, 90,
91, 93) group by catdesc, hostname order by total_num desc)### t group by catdesc order by
total_num desc

```

Dataset Name	Description	Log Category
aware-Malicious-Files	Type of Malicious Files from AV and Sandbox	virus

```

select
  virus,
  left(url_agg, 1000) as url_agg,
  left(filename_agg, 1000) as filename_agg,
  quarskip,
  action,
  from_sandbox,
  total_num,
  first_seen,
  last_seen
from
  (
    select
      virus,
      string_agg(distinct url, '<br/>') as url_agg,
      string_agg(distinct filename, '<br/>') as filename_agg,
      max(quarskip) as quarskip,
      max(action) as action,
      max(from_sandbox) as from_sandbox,
      sum(total_num) as total_num,
      min(
        from_etime(first_seen)
      ) as first_seen,
      max(
        from_etime(last_seen)
      ) as last_seen
    from
      ###(select virus, url, filename, max(quarskip) as quarskip, max(action) as action, (case
when logid in ('0211009234', '0211009235') then 1 else 0 end) as from_sandbox, count(*) as
total_num, min(etime) as first_seen, max(etime) as last_seen from $log where $filter and virus
is not null and logid in ('0211009234', '0201009235', '0211008192', '0211008193',
'0211008194', '0211008195') group by virus, url, filename, from_sandbox order by total_num
desc)### t group by virus) t order by total_num desc

```

Dataset Name	Description	Log Category
newthing-New-Users	New users	fct-traffic

```

drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  f_user,
  min(start_time) as start_time
from
  ###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as f_user, min(dtime) as start_time
from $log where $pre_period $filter group by f_user order by start_time desc)### t group by f_
user; create temporary table rpt_tmptbl_2 as select f_user, min(start_time) as start_time from
###(select coalesce(nullifna(`user`), ipstr(`srcip`)) as f_user, min(dtime) as start_time from
$log where $filter group by f_user order by start_time desc)### t group by f_user; select f_
user, from_dtime(min(start_time)) as start_time from rpt_tmptbl_2 where f_user is not null and
not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.f_user=rpt_tmptbl_1.f_user) group by
f_user order by start_time desc

```

Dataset Name	Description	Log Category
newthing-New-Devices	New devices	fct-traffic

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  hostname,
  os,
  srcip,
  fctver
from
  ###(select hostname, os, srcip, fctver from $log where $pre_period $filter and hostname is
not null group by hostname, os, srcip, fctver order by hostname)### t group by hostname, os,
srcip, fctver; create temporary table rpt_tmptbl_2 as select hostname, os, srcip, fctver from
###(select hostname, os, srcip, fctver from $log where $filter and hostname is not null group
by hostname, os, srcip, fctver order by hostname)### t group by hostname, os, srcip, fctver;
select hostname, max(fctos_to_devtype(os)) as devtype, string_agg(distinct os, '/') as os_agg,
string_agg(distinct ipstr(srcip), '/') as srcip_agg, string_agg(distinct fctver, '/') as
fctver_agg from rpt_tmptbl_2 where not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_
2.hostname=rpt_tmptbl_1.hostname) group by hostname order by hostname
```

Dataset Name	Description	Log Category
newthing-New-Software-Installed	New software installed	fct-traffic

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  srcproduct,
  hostname
from
  ###(select srcproduct, hostname from $log where $pre_period $filter and nullifna(srcproduct)
is not null group by srcproduct, hostname order by srcproduct)### t group by srcproduct, host-
name; create temporary table rpt_tmptbl_2 as select srcproduct, hostname from ###(select
srcproduct, hostname from $log where $filter and nullifna(srcproduct) is not null group by
srcproduct, hostname order by srcproduct)### t group by srcproduct, hostname; select
srcproduct, string_agg(distinct hostname, ',') as host_agg from rpt_tmptbl_2 where not exists
(select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.srcproduct=rpt_tmptbl_1.srcproduct) group by
srcproduct order by srcproduct
```

Dataset Name	Description	Log Category
newthing-New-Security-Threats	New security threats	virus

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  threat_name,
  cat_id,
```

```

    srcip
from
(
    ###(select app as threat_name, 1 as cat_id, srcip from $log-app-ctrl where $pre_period
$filter and nullifna(app) is not null and lower(appcat)='botnet' group by threat_name, cat_id,
srcip)### union all ###(select virus as threat_name, 2 as cat_id, srcip from $log-virus where
$pre_period $filter and nullifna(virus) is not null group by threat_name, cat_id, srcip)###
union all ###(select attack as threat_name, 3 as cat_id, srcip from $log-attack where $pre_
period $filter and nullifna(attack) is not null group by threat_name, cat_id, srcip)###) t;
create temporary table rpt_tmptbl_2 as select daystamp, threat_name, cat_id, srcip from (###
(select $DAY_OF_MONTH as daystamp, app as threat_name, 1 as cat_id, srcip from $log-app-ctrl
where $filter and nullifna(app) is not null and lower(appcat)='botnet' group by daystamp,
threat_name, cat_id, srcip order by daystamp)### union all ###(select $DAY_OF_MONTH as day-
stamp, virus as threat_name, 2 as cat_id, srcip from $log-virus where $filter and nullifna
(virus) is not null group by daystamp, threat_name, cat_id, srcip order by daystamp)### union
all ###(select $DAY_OF_MONTH as daystamp, attack as threat_name, 3 as cat_id, srcip from $log-
attack where $filter and nullifna(attack) is not null group by daystamp, threat_name, cat_id,
srcip order by daystamp)###) t; select threat_name, (case cat_id when 1 then 'Botnet' when 2
then 'Malware' when 3 then 'Attack' end) as threat_cat, count(distinct srcip) as host_num,
string_agg(distinct cve, ',') as cve_agg from rpt_tmptbl_2 left join ips_mdata t2 on rpt_
tmptbl_2.threat_name=t2.name where not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_
2.threat_name=rpt_tmptbl_1.threat_name) group by threat_name, threat_cat order by host_num
desc

```

Dataset Name	Description	Log Category
newthing-dns-Botnet-Domain-IP	New Queried Botnet C&C Domains and IPs	dns

```

drop
    table if exists rpt_tmptbl_1;
drop
    table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
    domain,
    malware_type,
    action_s as action,
    srcip,
    sevid
from
    ###(select coalesce(botnetdomain, ipstr(botnetip)) as domain, cast('Botnet C&C' as char(32))
as malware_type, (case when action='block' then 'Blocked' when action='redirect' then 'Redir-
ected' else 'Passed' end) as action_s, srcip, (CASE WHEN level IN ('critical', 'alert', 'emer-
gency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN level='notice' THEN
2 ELSE 1 END) as sevid, coalesce(botnetdomain, ipstr(botnetip)) as sources_s, count(*) as
total_num from $log where $pre_period $filter and (botnetdomain is not null or botnetip is not
null) group by domain, action_s, srcip, sevid order by sevid desc)### t group by domain, mal-
ware_type, action, srcip, sevid; create temporary table rpt_tmptbl_2 as select domain, mal-
ware_type, action_s as action, srcip, sevid from ###(select coalesce(botnetdomain, ipstr
(botnetip)) as domain, cast('Botnet C&C' as char(32)) as malware_type, (case when action-
='block' then 'Blocked' when action='redirect' then 'Redirected' else 'Passed' end) as action_
s, srcip, (CASE WHEN level IN ('critical', 'alert', 'emergency') THEN 5 WHEN level='error'
THEN 4 WHEN level='warning' THEN 3 WHEN level='notice' THEN 2 ELSE 1 END) as sevid, coalesce
(botnetdomain, ipstr(botnetip)) as sources_s, count(*) as total_num from $log where $filter
and (botnetdomain is not null or botnetip is not null) group by domain, action_s, srcip, sevid
order by sevid desc)### group by domain, malware_type, action, srcip, sevid; select domain,
srcip, sevid, (CASE sevid WHEN 5 THEN 'Critical' WHEN 4 THEN 'High' WHEN 3 THEN 'Medium' WHEN

```

```
'2' THEN 'Info' ELSE 'Low' END) as severity from rpt_tmptbl_2 where (domain is not null and
not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.domain=rpt_tmptbl_1.domain)) or
(srcip is not null and not exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.srcip=rpt_
tmptbl_1.srcip)) group by domain, srcip, sevid order by sevid desc, domain
```

Dataset Name	Description	Log Category
newthing-New-Security-Threats-Timeline	New security threats timeline	virus

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  threat_name,
  cat_id,
  srcip
from
  (
    ###(select app as threat_name, 1 as cat_id, srcip from $log-app-ctrl where $pre_period
$filter and nullifna(app) is not null and lower(appcat)='botnet' group by threat_name, cat_id,
srcip)### union all ###(select virus as threat_name, 2 as cat_id, srcip from $log-virus where
$pre_period $filter and nullifna(virus) is not null group by threat_name, cat_id, srcip)###
union all ###(select attack as threat_name, 3 as cat_id, srcip from $log-attack where $pre_
period $filter and nullifna(attack) is not null group by threat_name, cat_id, srcip)###) t;
create temporary table rpt_tmptbl_2 as select timestamp, threat_name, cat_id, srcip from (###
(select $flex_timestamp as timestamp, app as threat_name, 1 as cat_id, srcip from $log-app-
ctrl where $filter and nullifna(app) is not null and lower(appcat)='botnet' group by
timestamp, threat_name, cat_id, srcip order by timestamp)### union all ###(select $flex_
timestamp as timestamp, virus as threat_name, 2 as cat_id, srcip from $log-virus where $filter
and nullifna(virus) is not null group by timestamp, threat_name, cat_id, srcip order by
timestamp)### union all ###(select $flex_timestamp as timestamp, attack as threat_name, 3 as
cat_id, srcip from $log-attack where $filter and nullifna(attack) is not null group by
timestamp, threat_name, cat_id, srcip order by timestamp)###) t; select $flex_datetime
(timestamp) as timescale, count(distinct srcip) as host_num, (case cat_id when 1 then 'Botnet'
when 2 then 'Malware' when 3 then 'Attack' end) as threat_cat from rpt_tmptbl_2 where not
exists (select 1 from rpt_tmptbl_1 where rpt_tmptbl_2.threat_name=rpt_tmptbl_1.threat_name)
group by timescale, cat_id order by timescale, cat_id
```

Dataset Name	Description	Log Category
newthing-New-Vulnerability	New vulnerabilities	fct-netscan

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  vulnid,
  vulnname,
  vulnseverity,
  vulncat,
  hostname
from
  ###(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $pre_period
```

```
$filter and nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; create temporary
table rpt_tmptbl_2 as select vulnid, vulnname, vulnseverity, vulncat, hostname from ###(select
vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $filter and nullifna(vul-
nname) is not null group by vulnid, vulnname, vulnseverity, vulncat, hostname)### t group by
vulnid, vulnname, vulnseverity, vulncat, hostname; select vulnname, (case when vulnsever-
ity='Critical' then 5 when vulnseverity='High' then 4 when vulnseverity='Medium' then 3 when
vulnseverity='Low' then 2 when vulnseverity='Info' then 1 else 0 end) as sev, vulnseverity,
vulncat, count(distinct hostname) as host_num, cve_id from rpt_tmptbl_2 t1 left join fct_mdata
t2 on t1.vulnid=t2.vid::int where not exists (select 1 from rpt_tmptbl_1 where t1.vulnid=rpt_
tmptbl_1.vulnid) group by vulnname, sev, vulnseverity, vulncat, cve_id order by sev desc,
host_num desc
```

Dataset Name	Description	Log Category
newthing-New-Vulnerability-Graph	New vulnerabilities (Graph)	fct-netscan

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  vulnid,
  vulnname,
  vulnseverity,
  vulncat,
  hostname
from
  ###(select vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $pre_period
$filter and nullifna(vulnname) is not null group by vulnid, vulnname, vulnseverity, vulncat,
hostname)### t group by vulnid, vulnname, vulnseverity, vulncat, hostname; create temporary
table rpt_tmptbl_2 as select vulnid, vulnname, vulnseverity, vulncat, hostname from ###(select
vulnid, vulnname, vulnseverity, vulncat, hostname from $log where $filter and nullifna(vul-
nname) is not null group by vulnid, vulnname, vulnseverity, vulncat, hostname)### t group by
vulnid, vulnname, vulnseverity, vulncat, hostname; select vulnseverity, count (distinct vul-
nid) as vuln_num from rpt_tmptbl_2 where not exists (select 1 from rpt_tmptbl_1 where rpt_
tmptbl_2.vulnid=rpt_tmptbl_1.vulnid) group by vulnseverity order by (case when vulnsever-
ity='Critical' then 5 when vulnseverity='High' then 4 when vulnseverity='Medium' then 3 when
vulnseverity='Low' then 2 when vulnseverity='Info' then 1 else 0 end) desc
```

Dataset Name	Description	Log Category
newthing-System-Alerts	System Alerts	local-event

```
select
  from_itime(itime) as timestamp,
  msg
from
  $log
where
  $filter
  and msg is not null
  and level = 'critical'
order by
  timestamp desc
```

Dataset Name	Description	Log Category
newthing-Configuration-Changes	Configuration Changes	event

```
select
  `user` as f_user,
  devid,
  from_dtime(dtime) as time_s,
  ui,
  msg
from
  $log
where
  $filter
  and cfgtid>0
order by
  time_s desc
```

Dataset Name	Description	Log Category
newthing-FortiGate-Upgrades	FortiGate Upgrades	event

```
select
  devid,
  from_dtime(dtime) as time_s,
  info[1] as intf,
  info[2] as prev_ver,
  info[3] as new_ver
from
  (
    select
      devid,
      dtime,
      regexp_matches(
        msg, 'from ([^ ]+) \\((([^ ]+) -> ([^ ]+)\\)'
      ) as info
    from
      $log
    where
      $filter
      and action = 'restore-image'
  ) t
order by
  time_s desc
```

Dataset Name	Description	Log Category
newthing-User-Upgrades	User Upgrades	fct-event

```
drop
  table if exists rpt_tmptbl_1;
drop
  table if exists rpt_tmptbl_2; create temporary table rpt_tmptbl_1 as
select
  fgtserial,
  hostname,
```



```

deviceip,
os,
dttime
from
###(select distinct on (fgtserial, hostname) fgtserial, hostname, deviceip, os, dttime from
$log where $pre_period $filter and hostname is not null order by fgtserial, hostname, dttime
desc)### t; create temporary table rpt_tmptbl_2 as select fgtserial, hostname, deviceip, os,
dttime from $log where $filter and hostname is not null order by fgtserial, hostname, dttime
desc)### t; select distinct on (1, 2) t2.fgtserial as devid, t2.hostname, t2.deviceip, t1.os
as prev_os, t2.os as cur_os, from_dtime(t1.dtime) as time_s from rpt_tmptbl_2 t2 inner join
rpt_tmptbl_1 t1 on t2.fgtserial=t1.fgtserial and t2.hostname=t1.hostname and t2.os!=t1.os
order by devid, t2.hostname, t1.dtime desc

```

Dataset Name	Description	Log Category
GTP-List-of-APN-Used	List of APNs Used	gtp

```

select
  apn,
  from_dtime(
    min(first_seen)
  ) as first_seen,
  from_dtime(
    max(last_seen)
  ) as last_seen
from
###(select apn, min(dtime) as first_seen, max(dtime) as last_seen from $log where $filter
and nullifna(apn) is not null group by apn order by last_seen desc)### t group by apn order by
last_seen desc, first_seen

```

Dataset Name	Description	Log Category
GTP-Top-APN-by-Bytes	Top APNs by Bytes	gtp

```

select
  apn,
  sum(
    coalesce(`u-bytes`, 0)
  ) as total_bytes
from
$log
where
$filter
and nullifna(apn) is not null
and status = 'traffic-count'
group by
  apn
having
  sum(
    coalesce(`u-bytes`, 0)
  ) > 0
order by
  total_bytes desc

```

Dataset Name	Description	Log Category
GTP-Top-APN-by-Duration	Top APNs by Duration	gtp

```
select
  apn,
  sum(
    coalesce(duration, 0)
  ) as total_dura
from
  $log
where
  $filter
  and nullifna(apn) is not null
  and status = 'traffic-count'
group by
  apn
having
  sum(
    coalesce(duration, 0)
  )>0
order by
  total_dura desc
```

Dataset Name	Description	Log Category
GTP-Top-APN-by-Packets	Top APNs by Number of Packets	gtp

```
select
  apn,
  sum(
    coalesce(`u-pkts`, 0)
  ) as total_num
from
  $log
where
  $filter
  and nullifna(apn) is not null
  and status = 'traffic-count'
group by
  apn
having
  sum(
    coalesce(`u-pkts`, 0)
  )> 0
order by
  total_num desc
```

Dataset Name	Description	Log Category
Top10-dns-Botnet-Domain-IP	Top Queried Botnet C&C Domains and IPs	dns

```
select
  domain,
  malware_type,
  action,
```

```

count(distinct srcip) as victims,
count(distinct sources_s) as sources,
sum(total_num) as total_num
from
###({{FGT_DATASET_DNS_BOTNET_DOMAINS}})### t group by domain, malware_type, action order by
total_num desc

```

Dataset Name	Description	Log Category
dns-Botnet-Usage	Top Queried Botnet C&C Domains and IPs	dns

```

select
domain,
malware_type,
action,
count(distinct srcip) as victims,
count(distinct sources_s) as sources,
sum(total_num) as total_num
from
###({{FGT_DATASET_DNS_BOTNET_DOMAINS}})### t group by domain, malware_type, action order by
total_num desc

```

Dataset Name	Description	Log Category
Dns-Detected-Botnet	Top Queried Botnet C&C Domains and IPs	dns

```

select
domain,
malware_type,
action,
count(distinct srcip) as victims,
count(distinct sources_s) as sources,
sum(total_num) as total_num
from
###({{FGT_DATASET_DNS_BOTNET_DOMAINS}})### t group by domain, malware_type, action order by
total_num desc

```

Dataset Name	Description	Log Category
dns-Botnet-Domain-IP	Queried Botnet C&C Domains and IPs	dns

```

select
domain,
srcip,
sevid,
(
CASE sevid WHEN 5 THEN 'Critical' WHEN 4 THEN 'High' WHEN 3 THEN 'Medium' WHEN '2' THEN
'Info' ELSE 'Low' END
) as severity
from
###({{FGT_DATASET_DNS_BOTNET_DOMAINS}})### t group by domain, srcip, sevid order by sevid
desc, domain

```

Dataset Name	Description	Log Category
dns-High-Risk-Source	High Risk Sources	dns

```

select
  srcip,
  sum(total_num) as total_num,
  sum(
    case when sevid = 5 then total_num else 0 end
  ) as num_cri,
  sum(
    case when sevid = 4 then total_num else 0 end
  ) as num_hig,
  sum(
    case when sevid = 3 then total_num else 0 end
  ) as num_med
from
  ###(select srcip, (CASE WHEN level IN ('critical', 'alert', 'emergency') THEN 5 WHEN level=
='error' THEN 4 WHEN level='warning' THEN 3 WHEN level='notice' THEN 2 ELSE 1 END) as sevid,
count(*) as total_num from $log where $filter and srcip is not null group by srcip, sevid
order by total_num desc)### t where sevid>=3 group by srcip having sum(total_num)>0 order by
total_num desc

```

Dataset Name	Description	Log Category
dns-DNS-Request-Over-Time	DNS Request Over Time	dns

```

select
  $flex_timescale(timestamp) as timescale,
  sum(
    case when sevid = 5 then total_num else 0 end
  ) as num_cri,
  sum(
    case when sevid = 4 then total_num else 0 end
  ) as num_hig,
  sum(
    case when sevid = 3 then total_num else 0 end
  ) as num_med,
  sum(
    case when sevid = 2 then total_num else 0 end
  ) as num_inf,
  sum(
    case when sevid = 1 then total_num else 0 end
  ) as num_low
from
  ###(select $flex_timestamp as timestamp, (CASE WHEN level IN ('critical', 'alert', 'emer-
gency') THEN 5 WHEN level='error' THEN 4 WHEN level='warning' THEN 3 WHEN level='notice' THEN
2 ELSE 1 END) as sevid, count(*) as total_num from $log where $filter group by timestamp,
sevid order by total_num desc)### t group by timescale order by timescale

```

Dataset Name	Description	Log Category
dns-Top-Queried-Domain	Top Queried Domain	dns

```

select
  qname,
  count(*) as total_num
from
  $log
where

```

## Dataset Reference List

```
$filter
and qname is not null
group by
qname
order by
total_num desc
```

Dataset Name	Description	Log Category
dns-Top-Domain-Lookup-Failure-Bar	Top Domain Lookup Failures	dns

```
select
qname,
srcip,
count(*) as total_num
from
$log
where
$filter
and qname is not null
and (
action = 'block'
or logid_to_int(logid)= 54200
)
group by
qname,
srcip
order by
total_num desc
```

Dataset Name	Description	Log Category
dns-Top-Domain-Lookup-Failure-Table	Top Domain Lookup Failures	dns

```
select
qname,
srcip,
count(*) as total_num
from
$log
where
$filter
and qname is not null
and (
action = 'block'
or logid_to_int(logid)= 54200
)
group by
qname,
srcip
order by
total_num desc
```

Dataset Name	Description	Log Category
dns-Query-Timeout	Query Timeout	dns

```

select
  srcip,
  qname,
  count(*) as total_num
from
  $log
where
  $filter
  and srcip is not null
  and logid_to_int(logid)= 54200
group by
  qname,
  srcip
order by
  total_num desc

```

Dataset Name	Description	Log Category
dns-Blocked-Query	Blocked Queries	dns

```

select
  srcip,
  msg,
  count(*) as total_num
from
  $log
where
  $filter
  and srcip is not null
  and action = 'block'
group by
  srcip,
  msg
order by
  total_num desc

```

Dataset Name	Description	Log Category
perf-stat-cpu-usage-drilldown	Fortigate resource detail timeline	event

```

select
  hodex,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions

```

```
) as sessions,
cast(
  sum(sent_kbps)/ count(*) as decimal(10, 0)
) as sent_kbps,
cast(
  sum(recv_kbps)/ count(*) as decimal(10, 0)
) as recv_kbps,
cast(
  sum(transmit_kbps)/ count(*) as decimal(10, 0)
) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
max(lograte_peak) as lograte_peak,
max(session_peak) as session_peak,
max(transmit_kbps_peak) as transmit_kbps_peak,
cast(
  sum(cps_ave)/ count(*) as decimal(10, 0)
) as cps_ave,
max(cps_peak) as cps_peak
from
(
  select
    hodex,
    devid,
    get_fgt_role(devid, slot) as role,
    cast(
      sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
      sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
      sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
      sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
      sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
      sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
      sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
      sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
      sum(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
```

```

sum(session_peak) as session_peak,
sum(transmit_kbps_peak) as transmit_kbps_peak,
cast(
    sum(cps_ave) as decimal(10, 0)
) as cps_ave,
sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hodex,
        devid,
        slot,
        sum(total_cpu) / sum(count) as cpu_ave,
        sum(total_mem) / sum(count) as mem_ave,
        sum(total_disk) / sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        ) / 100.00 / sum(count) as log_rate,
        sum(totalsession) / sum(count) as sessions,
        sum(sent) / sum(count) as sent_kbps,
        sum(recv) / sum(count) as recv_kbps,
        sum(sent + recv) / sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak) / 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps) / sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum
        (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as
        total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
        (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
        0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
        (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
        sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
        '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
        integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
        (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
        (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
        action='perf-stats' group by timestamp, devid, slot)### t where $filter-drilldown group by
        hodex, devid, slot) t group by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-mem-usage-drilldown	Fortigate resource detail timeline	event

```

select
    hodex,
    cast(
        sum(cpu_ave) / count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave) / count(*) as decimal(6, 0)

```



```
) as mem_ave,
cast(
  sum(disk_ave)/ count(*) as decimal(6, 0)
) as disk_ave,
cast(
  sum(log_rate)/ count(*) as decimal(10, 2)
) as log_rate,
cast(
  sum(sessions)/ count(*) as decimal(10, 0)
) as sessions,
cast(
  sum(sent_kbps)/ count(*) as decimal(10, 0)
) as sent_kbps,
cast(
  sum(recv_kbps)/ count(*) as decimal(10, 0)
) as recv_kbps,
cast(
  sum(transmit_kbps)/ count(*) as decimal(10, 0)
) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
max(lograte_peak) as lograte_peak,
max(session_peak) as session_peak,
max(transmit_kbps_peak) as transmit_kbps_peak,
cast(
  sum(cps_ave)/ count(*) as decimal(10, 0)
) as cps_ave,
max(cps_peak) as cps_peak
from
(
  select
    hodex,
    devid,
    get_fgt_role(devid, slot) as role,
    cast(
      sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
      sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
      sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
      sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
      sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
      sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
      sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
```

```

cast(
    sum(transmit_kbps) as decimal(10, 0)
) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
cast(
    sum(lograte_peak) as decimal(10, 2)
) as lograte_peak,
sum(session_peak) as session_peak,
sum(transmit_kbps_peak) as transmit_kbps_peak,
cast(
    sum(cps_ave) as decimal(10, 0)
) as cps_ave,
sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hodex,
        devid,
        slot,
        sum(total_cpu)/ sum(count) cpu_ave,
        sum(total_mem)/ sum(count) as mem_ave,
        sum(total_disk)/ sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        )/ 100.00 / sum(count) as log_rate,
        sum(totalsession)/ sum(count) as sessions,
        sum(sent)/ sum(count) as sent_kbps,
        sum(recv)/ sum(count) as recv_kbps,
        sum(sent + recv)/ sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak)/ 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps)/ sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum
        (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
        total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
        (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
        0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
        (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
        sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
        '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
        integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
        (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
        (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
        action='perf-stats' group by timestamp, devid, slot)### t where $filter-drilldown group by
        hodex, devid, slot) t group by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-disk-usage-drilldown	Fortigate resource detail timeline	event

```
select
  hodex,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps)/ count(*) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps)/ count(*) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  max(lograte_peak) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak,
  cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
  ) as cps_ave,
  max(cps_peak) as cps_peak
from
  (
    select
      hodex,
      devid,
      get_fgt_role(devid, slot) as role,
      cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
      ) as cpu_ave,
      cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
      ) as mem_ave,
      cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
      ) as disk_ave,
      cast(
        sum(log_rate) as decimal(10, 2)
      ) as log_rate,
      cast(
        sum(sessions) as decimal(10, 0)
      ) as sessions,
```

```

    ) as sessions,
    cast(
        sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
        sum(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
    sum(session_peak) as session_peak,
    sum(transmit_kbps_peak) as transmit_kbps_peak,
    cast(
        sum(cps_ave) as decimal(10, 0)
    ) as cps_ave,
    sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hindex,
        devid,
        slot,
        sum(total_cpu) / sum(count) as cpu_ave,
        sum(total_mem) / sum(count) as mem_ave,
        sum(total_disk) / sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        ) / 100.00 / sum(count) as log_rate,
        sum(totalsession) / sum(count) as sessions,
        sum(sent) / sum(count) as sent_kbps,
        sum(recv) / sum(count) as recv_kbps,
        sum(sent + recv) / sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak) / 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps) / sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum
        (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
        total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
        (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
        0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
        (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
        sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
        '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
        integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast

```

```
(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
action='perf-stats' group by timestamp, devid, slot)### t where $filter-drilldown group by
hodex, devid, slot) t group by hodex, devid, role) t group by hodex order by hodex
```

Dataset Name	Description	Log Category
perf-stat-sessions-drilldown	Fortigate resource detail timeline	event

```
select
  hodex,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps)/ count(*) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps)/ count(*) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  max(lograte_peak) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak,
  cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
  ) as cps_ave,
  max(cps_peak) as cps_peak
from
  (
    select
      hodex,
      devid,
      get_fgt_role(devid, slot) as role,
      cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
      ) as cpu_ave,
      cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
```

```

    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,
    cast(
        sum(lograte_peak) as decimal(10, 2)
    ) as lograte_peak,
    sum(session_peak) as session_peak,
    sum(transmit_kbps_peak) as transmit_kbps_peak,
    cast(
        sum(cps_ave) as decimal(10, 0)
    ) as cps_ave,
    sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hindex,
        devid,
        slot,
        sum(total_cpu)/ sum(count) cpu_ave,
        sum(total_mem)/ sum(count) as mem_ave,
        sum(total_disk)/ sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        )/ 100.00 / sum(count) as log_rate,
        sum(totalsession)/ sum(count) as sessions,
        sum(sent)/ sum(count) as sent_kbps,
        sum(recv)/ sum(count) as recv_kbps,
        sum(sent + recv)/ sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak)/ 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps)/ sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from

```

```

###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum
(coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
(coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
action='perf-stats' group by timestamp, devid, slot)### t where $filter-drilldown group by
hodex, devid, slot) t group by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-lograte-drilldown	Fortigate resource detail timeline	event

```

select
  hodex,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate)/ count(*) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions)/ count(*) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps)/ count(*) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps)/ count(*) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  max(lograte_peak) as lograte_peak,
  max(session_peak) as session_peak,
  max(transmit_kbps_peak) as transmit_kbps_peak,
  cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
  ) as cps_ave,
  max(cps_peak) as cps_peak
from
  (

```

```
select
  hodex,
  devid,
  get_fgt_role(devid, slot) as role,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  cast(
    sum(lograte_peak) as decimal(10, 2)
  ) as lograte_peak,
  sum(session_peak) as session_peak,
  sum(transmit_kbps_peak) as transmit_kbps_peak,
  cast(
    sum(cps_ave) as decimal(10, 0)
  ) as cps_ave,
  sum(cps_peak) as cps_peak
from
  (
    select
      $flex_timescale(timestamp) as hodex,
      devid,
      slot,
      sum(total_cpu)/ sum(count) cpu_ave,
      sum(total_mem)/ sum(count) as mem_ave,
      sum(total_disk)/ sum(count) as disk_ave,
      sum(
        total_trate + total_erate + total_orate
      )/ 100.00 / sum(count) as log_rate,
      sum(totalsession)/ sum(count) as sessions,
      sum(sent)/ sum(count) as sent_kbps,
      sum(recv)/ sum(count) as recv_kbps,
      sum(sent + recv)/ sum(count) as transmit_kbps,
```



```

        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak)/ 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps)/ sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from
    ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum
    (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
    total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
    (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
    0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
    (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
    sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
    '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
    integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
    (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
    (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
    action='perf-stats' group by timestamp, devid, slot)### t where $filter-drilldown group by
    hodex, devid, slot) t group by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-connections-drilldown	Fortigate resource detail timeline	event

```

select
    hodex,
    cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate)/ count(*) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions)/ count(*) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps)/ count(*) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps)/ count(*) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps)/ count(*) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,
    max(disk_peak) as disk_peak,
    max(cpu_peak) as cpu_peak,

```

```
max(lograte_peak) as lograte_peak,
max(session_peak) as session_peak,
max(transmit_kbps_peak) as transmit_kbps_peak,
cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
) as cps_ave,
max(cps_peak) as cps_peak
from
(
    select
        hodex,
        devid,
        get_fgt_role(devid, slot) as role,
        cast(
            sum(cpu_ave)/ count(*) as decimal(6, 0)
        ) as cpu_ave,
        cast(
            sum(mem_ave)/ count(*) as decimal(6, 0)
        ) as mem_ave,
        cast(
            sum(disk_ave)/ count(*) as decimal(6, 0)
        ) as disk_ave,
        cast(
            sum(log_rate) as decimal(10, 2)
        ) as log_rate,
        cast(
            sum(sessions) as decimal(10, 0)
        ) as sessions,
        cast(
            sum(sent_kbps) as decimal(10, 0)
        ) as sent_kbps,
        cast(
            sum(recv_kbps) as decimal(10, 0)
        ) as recv_kbps,
        cast(
            sum(transmit_kbps) as decimal(10, 0)
        ) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        cast(
            sum(lograte_peak) as decimal(10, 2)
        ) as lograte_peak,
        sum(session_peak) as session_peak,
        sum(transmit_kbps_peak) as transmit_kbps_peak,
        cast(
            sum(cps_ave) as decimal(10, 0)
        ) as cps_ave,
        sum(cps_peak) as cps_peak
    from
    (
        select
            $flex_timescale(timestamp) as hodex,
            devid,
            slot,
            sum(total_cpu)/ sum(count) cpu_ave,
```

```

sum(total_mem)/ sum(count) as mem_ave,
sum(total_disk)/ sum(count) as disk_ave,
sum(
    total_trate + total_erate + total_orate
)/ 100.00 / sum(count) as log_rate,
sum(totalsession)/ sum(count) as sessions,
sum(sent)/ sum(count) as sent_kbps,
sum(rcv)/ sum(count) as rcv_kbps,
sum(sent + rcv)/ sum(count) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
max(lograte_peak)/ 100.00 as lograte_peak,
max(session_peak) as session_peak,
max(transmit_peak) as transmit_kbps_peak,
sum(cps)/ sum(count) as cps_ave,
max(cps_peak) as cps_peak
from
    ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum
(coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
(coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
integer)) as rcv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
action='perf-stats' group by timestamp, devid, slot)### t where $filter-drilldown group by
hodex, devid, slot) t group by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-bandwidth-drilldown	Fortigate resource detail timeline	event

```

select
    hodex,
    cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate)/ count(*) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions)/ count(*) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps)/ count(*) as decimal(10, 0)
    ) as sent_kbps,

```

```
cast(
    sum(recv_kbps)/ count(*) as decimal(10, 0)
) as recv_kbps,
cast(
    sum(transmit_kbps)/ count(*) as decimal(10, 0)
) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
max(lograte_peak) as lograte_peak,
max(session_peak) as session_peak,
max(transmit_kbps_peak) as transmit_kbps_peak,
cast(
    sum(cps_ave)/ count(*) as decimal(10, 0)
) as cps_ave,
max(cps_peak) as cps_peak
from
(
    select
        hodex,
        devid,
        get_fgt_role(devid, slot) as role,
        cast(
            sum(cpu_ave)/ count(*) as decimal(6, 0)
        ) as cpu_ave,
        cast(
            sum(mem_ave)/ count(*) as decimal(6, 0)
        ) as mem_ave,
        cast(
            sum(disk_ave)/ count(*) as decimal(6, 0)
        ) as disk_ave,
        cast(
            sum(log_rate) as decimal(10, 2)
        ) as log_rate,
        cast(
            sum(sessions) as decimal(10, 0)
        ) as sessions,
        cast(
            sum(sent_kbps) as decimal(10, 0)
        ) as sent_kbps,
        cast(
            sum(recv_kbps) as decimal(10, 0)
        ) as recv_kbps,
        cast(
            sum(transmit_kbps) as decimal(10, 0)
        ) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        cast(
            sum(lograte_peak) as decimal(10, 2)
        ) as lograte_peak,
        sum(session_peak) as session_peak,
        sum(transmit_kbps_peak) as transmit_kbps_peak,
        cast(
            sum(cps_ave) as decimal(10, 0)
        ) as cps_ave,
```

```

    ) as cps_ave,
    sum(cps_peak) as cps_peak
from
(
    select
        $flex_timescale(timestamp) as hodex,
        devid,
        slot,
        sum(total_cpu) / sum(count) as cpu_ave,
        sum(total_mem) / sum(count) as mem_ave,
        sum(total_disk) / sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        ) / 100.00 / sum(count) as log_rate,
        sum(totalsession) / sum(count) as sessions,
        sum(sent) / sum(count) as sent_kbps,
        sum(recv) / sum(count) as recv_kbps,
        sum(sent + recv) / sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak) / 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak,
        sum(cps) / sum(count) as cps_ave,
        max(cps_peak) as cps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum
        (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
        total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
        (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
        0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
        (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
        sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
        '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
        integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
        (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
        (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
        action='perf-stats' group by timestamp, devid, slot)### t where $filter-drilldown group by
        hodex, devid, slot) t group by hodex, devid, role) t group by hodex order by hodex

```

Dataset Name	Description	Log Category
perf-stat-usage-summary-average	Fortigate resource summary view	event

```

select
    devid,
    get_fgt_role(devid, slot) as role,
    cast(
        sum(cpu_ave) / count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave) / count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave) / count(*) as decimal(6, 0)

```

```

) as disk_ave,
cast(
    sum(log_rate) as decimal(10, 2)
) as log_rate,
cast(
    sum(sessions) as decimal(10, 0)
) as sessions,
cast(
    sum(sent_kbps) as decimal(10, 0)
) as sent_kbps,
cast(
    sum(recv_kbps) as decimal(10, 0)
) as recv_kbps,
cast(
    sum(transmit_kbps) as decimal(10, 0)
) as transmit_kbps,
max(mem_peak) as mem_peak,
max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
cast(
    sum(lograte_peak) as decimal(10, 2)
) as lograte_peak,
sum(session_peak) as session_peak,
sum(transmit_kbps_peak) as transmit_kbps_peak
from
(
    select
        devid,
        slot,
        sum(total_cpu) / sum(count) as cpu_ave,
        sum(total_mem) / sum(count) as mem_ave,
        sum(total_disk) / sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        ) / 100.00 / sum(count) as log_rate,
        sum(totalsession) / sum(count) as sessions,
        sum(sent) / sum(count) as sent_kbps,
        sum(recv) / sum(count) as recv_kbps,
        sum(sent + recv) / sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak) / 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum(coalesce
        (mem, 0)) as total_mem, max(coalesce(mem, 0)) as mem_peak, sum(coalesce(disk, 0)) as total_disk,
        max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0))
        as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate, 0)) as total_erate,
        sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(erate, 0)+coalesce
        (orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalsession, max(coalesce
        (totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth, '/', 1), '0') as
        integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as recv,
        max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast(coalesce(split_part
        (bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce(setuprate, 0)) as cps,

```

```
max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and action='perf-stats' group
by timestamp, devid, slot)### t group by devid, slot) t group by devid, role order by devid,
role
```

Dataset Name	Description	Log Category
perf-stat-usage-summary-peak	Fortigate resource summary view	event

```
select
  devid,
  get_fgt_role(devid, slot) as role,
  cast(
    sum(cpu_ave)/ count(*) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(mem_ave)/ count(*) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(disk_ave)/ count(*) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(log_rate) as decimal(10, 2)
  ) as log_rate,
  cast(
    sum(sessions) as decimal(10, 0)
  ) as sessions,
  cast(
    sum(sent_kbps) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv_kbps) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(transmit_kbps) as decimal(10, 0)
  ) as transmit_kbps,
  max(mem_peak) as mem_peak,
  max(disk_peak) as disk_peak,
  max(cpu_peak) as cpu_peak,
  cast(
    sum(lograte_peak) as decimal(10, 2)
  ) as lograte_peak,
  sum(session_peak) as session_peak,
  sum(transmit_kbps_peak) as transmit_kbps_peak
from
  (
    select
      devid,
      slot,
      sum(total_cpu)/ sum(count) as cpu_ave,
      sum(total_mem)/ sum(count) as mem_ave,
      sum(total_disk)/ sum(count) as disk_ave,
      sum(
        total_trate + total_erate + total_orate
      ) / 100.00 / sum(count) as log_rate,
      sum(totalsession)/ sum(count) as sessions,
      sum(sent)/ sum(count) as sent_kbps,
```

```

        sum(recv)/ sum(count) as recv_kbps,
        sum(sent + recv)/ sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak)/ 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak
    from
    ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum(coalesce
    (mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as total_disk,
    max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0))
    as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate, 0)) as total_erate,
    sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(erate, 0)+coalesce
    (orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalsession, max(coalesce
    (totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth, '/', 1), '0') as
    integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as recv,
    max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast(coalesce(split_part
    (bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce(setuprate, 0)) as cps,
    max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and action='perf-stats' group
    by timestamp, devid, slot)### t group by devid, slot) t group by devid, role order by devid,
    role

```

Dataset Name	Description	Log Category
perf-stat-usage-details-drilldown-master	Fortigate resource summary view	event

```

select
    devid,
    get_fgt_role(devid, slot) as role,
    cast(
        sum(cpu_ave)/ count(*) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(mem_ave)/ count(*) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(disk_ave)/ count(*) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(log_rate) as decimal(10, 2)
    ) as log_rate,
    cast(
        sum(sessions) as decimal(10, 0)
    ) as sessions,
    cast(
        sum(sent_kbps) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv_kbps) as decimal(10, 0)
    ) as recv_kbps,
    cast(
        sum(transmit_kbps) as decimal(10, 0)
    ) as transmit_kbps,
    max(mem_peak) as mem_peak,

```



```

max(disk_peak) as disk_peak,
max(cpu_peak) as cpu_peak,
cast(
    sum(lograte_peak) as decimal(10, 2)
) as lograte_peak,
sum(session_peak) as session_peak,
sum(transmit_kbps_peak) as transmit_kbps_peak
from
(
    select
        devid,
        slot,
        sum(total_cpu)/ sum(count) as cpu_ave,
        sum(total_mem)/ sum(count) as mem_ave,
        sum(total_disk)/ sum(count) as disk_ave,
        sum(
            total_trate + total_erate + total_orate
        )/ 100.00 / sum(count) as log_rate,
        sum(totalsession)/ sum(count) as sessions,
        sum(sent)/ sum(count) as sent_kbps,
        sum(recv)/ sum(count) as recv_kbps,
        sum(sent + recv)/ sum(count) as transmit_kbps,
        max(mem_peak) as mem_peak,
        max(disk_peak) as disk_peak,
        max(cpu_peak) as cpu_peak,
        max(lograte_peak)/ 100.00 as lograte_peak,
        max(session_peak) as session_peak,
        max(transmit_peak) as transmit_kbps_peak
    from
        ###(select $flex_timestamp as timestamp, devid, slot, count(*) as count, sum(coalesce
        (mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as total_disk,
        max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0))
        as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate, 0)) as total_erate,
        sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(erate, 0)+coalesce
        (orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalsession, max(coalesce
        (totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth, '/', 1), '0') as
        integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as recv,
        max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast(coalesce(split_part
        (bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce(setuprate, 0)) as cps,
        max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and action='perf-stats' group
        by timestamp, devid, slot)### t group by devid, slot) t group by devid, role order by devid,
        role

```

Dataset Name	Description	Log Category
incident-Incident-Count-by-Status	Incident status distribution	

```

select
    status,
    count(*) as cnt
from
    $incident
group by
    status
order by
    status

```

Dataset Name	Description	Log Category
incident-Incident-Count-by-Status-Donut	Incident status distribution	

```
select
  status,
  count(*) as cnt
from
  $incident
group by
  status
order by
  status
```

Dataset Name	Description	Log Category
incident-Open-Incident-Count-Timeline	Incident count by status over time	

```
select
  $flex_timescale(agg_time) as hodex,
  max(num_sta_draft) as num_sta_draft,
  max(num_sta_analysis) as num_sta_analysis,
  max(num_sta_response) as num_sta_response,
  max(num_sta_closed) as num_sta_closed,
  max(num_sta_cancelled) as num_sta_cancelled
from
  $incident_history
where
  $cust_time_filter(agg_time)
group by
  hodex
order by
  hodex
```

Dataset Name	Description	Log Category
incident-Closed-Incident-Count-Timeline	Incident count by status over time	

```
select
  $flex_timescale(agg_time) as hodex,
  max(num_sta_draft) as num_sta_draft,
  max(num_sta_analysis) as num_sta_analysis,
  max(num_sta_response) as num_sta_response,
  max(num_sta_closed) as num_sta_closed,
  max(num_sta_cancelled) as num_sta_cancelled
from
  $incident_history
where
  $cust_time_filter(agg_time)
group by
  hodex
```

```
order by
  hindex
```

Dataset Name	Description	Log Category
Top-10-Apps-by-Bandwidth	Top applications by bandwidth usage	traffic

```
select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
Top-10-User-by-Bandwidth	Top users by bandwidth usage	traffic

```
select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  srcip,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out
```

```

from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and srcip is not null
group by
  user_src,
  srcip
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Top-10-Applications-by-Number-of-Users	Top Applications by number of users	traffic

```

select
  app_group_name(app) as app_group,
  count(distinct user_src) as number
from
  ###(select coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src,
  app, appcat from $log where $filter and (logflag&1>0) and nullifna(app) is not null group by
  user_src, app, appcat)### t group by app_group order by number desc

```

Dataset Name	Description	Log Category
Top-10-User-by-Session	Top user by session count	traffic

```

select
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as user_src,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
group by
  user_src
order by
  sessions desc

```

Dataset Name	Description	Log Category
Top-10-Apps-by-Session	Top applications by bandwidth usage	traffic

```

select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvdbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc

```

Dataset Name	Description	Log Category
Applications-by-Risk-Level	Applications by Risk Level	traffic

```

select
  app_group_name(app) as app_group,
  min(id) as id,
  appcat,
  max(risk) as d_risk,
  (
    case when max(risk)= '5' then 'Critical' when max(risk)= '4' then 'High' when max(risk)=
'3' then 'Medium' when max(risk)= '2' then 'Low' else 'Info' end
  ) as risk_level,
  sum(sessions) as sessions,
  sum(sent) as sent,
  sum(received) as received,
  sum(bandwidth) as bandwidth
from
  ###(select appid, app, appcat, sum(coalesce(sentbyte, 0)) as sent, sum(coalesce(rcvdbyte,
0)) as received, sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0)) as bandwidth, count(*) as
sessions from $log where $filter and (logflag&1>0) group by appid, app, appcat order by band-
width desc)### t1 inner join app_mdata t2 on lower(t1.app)=lower(t2.name) group by app_group,
appcat order by d_risk desc, bandwidth desc

```

Dataset Name	Description	Log Category
soc-Event-vs-Incident-Today-Trend	Events vs Incidents Today Trend	

```

select
  item,
  num_cur,
  num_pre,
  num_diff
from
  (
    select
      'Events' as item,
      num_cur,
      num_pre,
      (num_cur - num_pre) as num_diff
    from
      (
        select
          (
            select
              count(*)
            from
              $event
            where
              $cust_time_filter(alerttime, TODAY)
          ) as num_cur,
          (
            select
              count(*)
            from
              $event
            where
              $cust_time_filter(alerttime, YESTERDAY)
          ) as num_pre
        ) t
    union all
    select
      'Incidents' as item,
      num_cur,
      num_pre,
      (num_cur - num_pre) as num_diff
    from
      (
        select
          (
            select
              count(*)
            from
              $incident
            where
              $cust_time_filter(createtime, TODAY)
          ) as num_cur,
          (
            select
              count(*)

```

```

        from
        $incident
        where
        $cust_time_filter(createtime, YESTERDAY)
    ) as num_pre
) t
) t
order by
item

```

Dataset Name	Description	Log Category
soc-Event-vs-Incident-History-Trend	Events vs Incidents History Trend	

```

select
item,
num_cur,
num_pre,
num_diff
from
(
    select
        'Events' as item,
        num_cur,
        num_pre,
        (num_cur - num_pre) as num_diff
    from
        (
            select
                (
                    select
                        count(*)
                    from
                        $event
                    where
                        $cust_time_filter(alerttime)
                ) as num_cur,
                (
                    select
                        count(*)
                    from
                        $event
                    where
                        $cust_time_filter(alerttime, LAST_N_PERIOD, 1)
                ) as num_pre
            ) t
        union all
        select
            'Incidents' as item,
            num_cur,
            num_pre,
            (num_cur - num_pre) as num_diff
        from
            (
                select
                    (

```

```

        select
            count(*)
        from
            $incident
        where
            $cust_time_filter(createtime)
    ) as num_cur,
    (
        select
            count(*)
        from
            $incident
        where
            $cust_time_filter(createtime, LAST_N_PERIOD, 1)
    ) as num_pre
    ) t
) t
order by
    item

```

Dataset Name	Description	Log Category
soc-Event-vs-Incident-Trend	Events vs Incidents Trend	

```

select
    t1.item,
    t1.num_cur as num_today,
    t1.num_pre as num_yesterday,
    t1.num_diff as num_diff1,
    t2.num_cur as num_this_period,
    t2.num_pre as num_last_period,
    t2.num_diff as num_diff2
from
    (
        select
            'Events' as item,
            num_cur,
            num_pre,
            (num_cur - num_pre) as num_diff
        from
            (
                select
                    (
                        select
                            count(*)
                        from
                            $event
                        where
                            $cust_time_filter(alerttime, TODAY)
                    ) as num_cur,
                    (
                        select
                            count(*)
                        from
                            $event
                        where

```



```
        $cust_time_filter(alerttime, YESTERDAY)
    ) as num_pre
) t
union all
select
    'Incidents' as item,
    num_cur,
    num_pre,
    (num_cur - num_pre) as num_diff
from
    (
        select
            (
                select
                    count(*)
                from
                    $incident
                where
                    $cust_time_filter(createtime, TODAY)
            ) as num_cur,
            (
                select
                    count(*)
                from
                    $incident
                where
                    $cust_time_filter(createtime, YESTERDAY)
            ) as num_pre
        ) t
) t1 full
join (
    select
        'Events' as item,
        num_cur,
        num_pre,
        (num_cur - num_pre) as num_diff
    from
        (
            select
                (
                    select
                        count(*)
                    from
                        $event
                    where
                        $cust_time_filter(alerttime)
                ) as num_cur,
                (
                    select
                        count(*)
                    from
                        $event
                    where
                        $cust_time_filter(alerttime, LAST_N_PERIOD, 1)
                ) as num_pre
            ) t
        ) t
```

```

union all
select
    'Incidents' as item,
    num_cur,
    num_pre,
    (num_cur - num_pre) as num_diff
from
    (
        select
            (
                select
                    count(*)
                from
                    $incident
                where
                    $cust_time_filter(createtime)
            ) as num_cur,
            (
                select
                    count(*)
                from
                    $incident
                where
                    $cust_time_filter(createtime, LAST_N_PERIOD, 1)
            ) as num_pre
        ) t
    ) t2 on t1.item = t2.item
order by
    t1.item

```

Dataset Name	Description	Log Category
soc-Total-Event-by-Severity	Total Events by Severity	

```

select
    (
        CASE severity WHEN 0 THEN 'Critical' WHEN 1 THEN 'High' WHEN 2 THEN 'Medium' WHEN 3 THEN
'Low' ELSE NULL END
    ) as sev,
    count(*) as num_events
from
    $event
group by
    severity
order by
    severity

```

Dataset Name	Description	Log Category
soc-Total-Event-by-Severity-History	Total Events by Severity History	

```

select
    dom,
    (
        CASE severity WHEN 0 THEN 'Critical' WHEN 1 THEN 'High' WHEN 2 THEN 'Medium' WHEN 3 THEN
'Low' ELSE NULL END
    )

```

```

    ) as sev,
    sum(num_events) as num_events
from
(
    select
        dom,
        unnest(agg_sev) as severity,
        unnest(agg_num) as num_events
    from
        (
            select
                $DAY_OF_MONTH(agg_time) as dom,
                array[0,
                    1,
                    2,
                    3] as agg_sev,
                array[max(num_sev_critical),
                    max(num_sev_high),
                    max(num_sev_medium),
                    max(num_sev_low) ] as agg_num
            from
                $event_history
            where
                $cust_time_filter(agg_time)
            group by
                dom
            order by
                dom
        ) t
    ) t
group by
    dom,
    severity
order by
    dom,
    severity

```

Dataset Name	Description	Log Category
soc-Total-Event-by-Severity-Category	Total Events Count by Severity and Category	

```

select
(
    CASE severity WHEN 0 THEN 'Critical' WHEN 1 THEN 'High' WHEN 2 THEN 'Medium' WHEN 3 THEN
'Low' ELSE NULL END
) as sev,
triggername,
count(*) as num_events
from
    $event
group by
    severity,
    triggername
order by
    severity,
    triggername

```

Dataset Name	Description	Log Category
soc-Total-Incident-by-Severity	Total Incidents by Severity	

```
select
  severity,
  count(*) as num_inc
from
  $incident
group by
  severity
order by
  severity
```

Dataset Name	Description	Log Category
soc-Total-Event-vs-Incident-History	Total Events vs Incidents History	

```
select
  coalesce(t1.hodex, t2.hodex) as hodex,
  coalesce(num_event_total, 0) as num_event_total,
  coalesce(num_inc_total, 0) as num_inc_total,
  coalesce(num_event_high, 0) as num_event_high
from
  (
    select
      $flex_timescale(agg_time) as hodex,
      max(num_total) as num_event_total,
      max(num_sev_critical + num_sev_high) as num_event_high
    from
      $event_history
    where
      $cust_time_filter(agg_time)
    group by
      hodex
    order by
      hodex
  ) t1 full
join (
  select
    $flex_timescale(agg_time) as hodex,
    max(
      num_sev_high + num_sev_medium + num_sev_low
    ) as num_inc_total
  from
    $incident_history
  where
    $cust_time_filter(agg_time)
  group by
    hodex
  order by
    hodex
) t2 on t1.hodex = t2.hodex
order by
  hodex
```

Dataset Name	Description	Log Category
soc-Incident-List	List of Incidents	

```
select
  incid_to_str(incid) as incnum,
  from_otime(createtime) as timestamp,
  category,
  severity,
  status,
  endpoint
from
  $incident
where
  $cust_time_filter(createtime)
order by
  createtime desc
```

Dataset Name	Description	Log Category
fex-RSRQ-timeline	FortiExtender RSRQ timeline	event

```
select
  $flex_timescale(timestamp) as hodex,
  cast(
    sum(rsrq_sum) / sum(count) as decimal(18, 2)
  ) || 'dB' as rsrq
from
  ###(select $flex_timestamp(dtime) as timestamp, sum(to_number(rsrq, '999999.99')) as rsrq_
sum, sum(to_number(sinr, '999999.99')) as sinr_sum, count(*) as count from $log where $filter
and logid='0111046409' group by timestamp order by timestamp desc)### t group by hodex order
by hodex desc
```

Dataset Name	Description	Log Category
fex-SINR-timeline	FortiExtender SINR timeline	event

```
select
  $flex_timescale(timestamp) as hodex,
  cast(
    sum(sinr_sum) / sum(count) as decimal(18, 0)
  ) || 'dB' as sinr
from
  ###(select $flex_timestamp(dtime) as timestamp, sum(to_number(rsrq, '999999.99')) as rsrq_
sum, sum(to_number(sinr, '999999.99')) as sinr_sum, count(*) as count from $log where $filter
and logid='0111046409' group by timestamp order by timestamp desc)### t group by hodex order
by hodex desc
```

Dataset Name	Description	Log Category
fgt-device-monitoring-inventory	FortiGate Device Monitoring Inventory	event

```
select
  devname,
  (' ' || devid) as id_devid,
  ip,
```

```

platform,
os,
'1' as total_num
from
$func - fgt - inventory as t1
where
exists (
select
1
from
devtable t2
where
$dev_filter
and t2.devid = t1.devid
)
order by
devname

```

Dataset Name	Description	Log Category
fgt-inventory-hardware	FortiGate Monitoring Inventory Hardware	event

```

select
platform,
count(*) as total_num
from
$func - fgt - inventory as t1
where
exists (
select
1
from
devtable t2
where
$dev_filter
and t2.devid = t1.devid
)
group by
platform
order by
total_num desc

```

Dataset Name	Description	Log Category
fgt-inventory-software	FortiGate Monitoring Inventory Software	event

```

select
'FortiOS' as sf_name,
(platform || ' ' || os) as firmware,
count(*) as total_num
from
$func - fgt - inventory as t1
where
exists (
select
1

```

```

    from
      devtable t2
    where
      $dev_filter
      and t2.devid = t1.devid
  )
group by
  platform,
  os
order by
  total_num desc

```

Dataset Name	Description	Log Category
cup-utilization-timeline-for-each-device	FortiGate cpu utilization timeline	event

```

select
  $flex_timescale(timestamp) as hodex,
  devid,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(total_mem)/ sum(count) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps
from
  ###(select $flex_timestamp as timestamp, devid, count(*) as count, sum(coalesce(mem, 0)) as
total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce
(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_
peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate, 0)) as total_erate, sum
(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate,
0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalsession, max(coalesce(totalses-
sion, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer))
as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth,
 '/', 2), '0') as integer)) as transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce
(setuprate, 0)) as cps_peak from $log where $filter and action='perf-stats' group by
timestamp, devid)### t where $filter-drilldown group by hodex, devid order by hodex

```

Dataset Name	Description	Log Category
status-timeline-by-device-cpu-utilization	FortiGate cpu summary view	event

```

select
  devid,
  cast(

```

```

        sum(total_cpu)/ sum(count) as decimal(6, 0)
    ) as cpu_ave,
    max(cpu_peak) as cpu_peak
from
    ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
    (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
    total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
    (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
    0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
    (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
    sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
    '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
    integer)) as rcv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
    (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
    (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
    action='perf-stats' group by devid)### t group by devid order by cpu_peak desc

```

Dataset Name	Description	Log Category
event-cpu-utilization-dev	FortiGate cpu summary view	event

```

select
    devid,
    cast(
        sum(total_cpu)/ sum(count) as decimal(6, 0)
    ) as cpu_ave,
    max(cpu_peak) as cpu_peak
from
    ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
    (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
    total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
    (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
    0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
    (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
    sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
    '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
    integer)) as rcv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
    (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
    (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
    action='perf-stats' group by devid)### t group by devid order by cpu_peak desc

```

Dataset Name	Description	Log Category
memory-utilization-timeline-for-each-device	FortiGate cpu utilization timeline	event

```

select
    $flex_timescale(timestamp) as hodox,
    devid,
    cast(
        sum(total_cpu)/ sum(count) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(total_mem)/ sum(count) as decimal(6, 0)
    ) as mem_ave,
    cast(

```



```

        sum(total_disk)/ sum(count) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(sent)/ sum(count) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv)/ sum(count) as decimal(10, 0)
    ) as recv_kbps
from
    ###(select $flex_timestamp as timestamp, devid, count(*) as count, sum(coalesce(mem, 0)) as
total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce
(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_
peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate, 0)) as total_erate, sum
(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate,
0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalsession, max(coalesce(totalses-
sion, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer))
as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth,
 '/', 2), '0') as integer)) as transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce
(setuprate, 0)) as cps_peak from $log where $filter and action='perf-stats' group by
timestamp, devid)### t where $filter-drilldown group by hodex, devid order by hodex

```

Dataset Name	Description	Log Category
status-timeline-by-device-mem-utilization	FortiGate memory summary view	event

```

select
    devid,
    cast(
        sum(total_mem)/ sum(count) as decimal(6, 0)
    ) as mem_ave,
    max(mem_peak) as mem_peak
from
    ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
(coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
(coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
 '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
action='perf-stats' group by devid)### t group by devid order by mem_peak desc

```

Dataset Name	Description	Log Category
event-mem-utilization-dev	FortiGate memory summary view	event

```

select
    devid,
    cast(
        sum(total_mem)/ sum(count) as decimal(6, 0)
    ) as mem_ave,

```

```

    max(mem_peak) as mem_peak
from
    ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
    (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
    total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
    (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
    0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
    (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
    sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
    '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
    integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
    (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
    (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
    action='perf-stats' group by devid)### t group by devid order by mem_peak desc

```

Dataset Name	Description	Log Category
disk-utilization-timeline-for-each-device	FortiGate cpu utilization timeline	event

```

select
    $flex_timescale(timestamp) as hodex,
    devid,
    cast(
        sum(total_cpu)/ sum(count) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(total_mem)/ sum(count) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(total_disk)/ sum(count) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(sent)/ sum(count) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv)/ sum(count) as decimal(10, 0)
    ) as recv_kbps
from
    ###(select $flex_timestamp as timestamp, devid, count(*) as count, sum(coalesce(mem, 0)) as
    total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce
    (disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_
    peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate, 0)) as total_erate, sum
    (coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate,
    0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalsession, max(coalesce(totalses-
    sion, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer))
    as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast
    (coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth,
    '/', 2), '0') as integer)) as transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce
    (setuprate, 0)) as cps_peak from $log where $filter and action='perf-stats' group by
    timestamp, devid)### t where $filter-drilldown group by hodex, devid order by hodex

```

Dataset Name	Description	Log Category
status-timeline-by-device-disk-utilization	FortiGate disk summary view	event

```

select
  devid,
  cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
  ) as disk_ave,
  max(disk_peak) as disk_peak
from
  ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
  (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
  total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
  (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
  0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
  (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
  sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
  '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
  integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
  (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
  (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
  action='perf-stats' group by devid)### t group by devid order by disk_peak desc

```

Dataset Name	Description	Log Category
event-disk-utilization-dev	FortiGate disk summary view	event

```

select
  devid,
  cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
  ) as disk_ave,
  max(disk_peak) as disk_peak
from
  ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
  (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
  total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
  (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
  0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
  (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
  sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
  '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
  integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
  (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
  (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
  action='perf-stats' group by devid)### t group by devid order by disk_peak desc

```

Dataset Name	Description	Log Category
event-total-session-summary	FortiGate Total Sessions	event

```

select
  devid,
  max(session_peak) as max_session,
  cast(
    sum(totalsession)/ sum(count) as decimal(10, 0)
  ) as sessions,
  max(cps_peak) as cps_peak,
  cast(

```

```

        sum(cps)/ sum(count) as decimal(10, 0)
    ) as cps_ave
from
    ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
    (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
    total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
    (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
    0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
    (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
    sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
    '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
    integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
    (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
    (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
    action='perf-stats' group by devid)### t group by devid order by max_session desc

```

Dataset Name	Description	Log Category
event-session-rate-summary	FortiGate Session Rate	event

```

select
    devid,
    max(cps_peak) as max_rate
from
    ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
    (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
    total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
    (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
    0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
    (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
    sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
    '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
    integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
    (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
    (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
    action='perf-stats' group by devid)### t group by devid order by max_rate desc

```

Dataset Name	Description	Log Category
event-session-summary-dev	FortiGate Total Sessions	event

```

select
    devid,
    max(session_peak) as max_session,
    cast(
        sum(totalsession)/ sum(count) as decimal(10, 0)
    ) as sessions,
    max(cps_peak) as cps_peak,
    cast(
        sum(cps)/ sum(count) as decimal(10, 0)
    ) as cps_ave
from
    ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
    (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
    total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
    (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,

```

```
0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(
erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
'/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
action='perf-stats' group by devid)### t group by devid order by max_session desc
```

Dataset Name	Description	Log Category
fgt-intf-down-timeline-for-each-device	FortiGate Interface Down Timeline	event

```
select
  $flex_timescale(timestamp) as hodex,
  devid,
  sum(total_num) as total_num
from
  ###(select $flex_timestamp as timestamp, devid, status, count(*) as total_num from $log
where $filter and logid_to_int(logid)=20099 and status='DOWN' group by timestamp, devid,
status)### t where $filter-drilldown group by hodex, devid order by hodex
```

Dataset Name	Description	Log Category
fgt-intf-down-timeline-by-device	FortiGate Interface Down by Device	event

```
select
  devid,
  status,
  sum(total_num) as total_num
from
  ###(select $flex_timestamp as timestamp, devid, status, count(*) as total_num from $log
where $filter and logid_to_int(logid)=20099 and status='DOWN' group by timestamp, devid,
status)### t group by devid, status order by total_num desc
```

Dataset Name	Description	Log Category
fgt-intf-down-dev-donut	FortiGate Interface Down by Device	event

```
select
  devid,
  status,
  sum(total_num) as total_num
from
  ###(select $flex_timestamp as timestamp, devid, status, count(*) as total_num from $log
where $filter and logid_to_int(logid)=20099 and status='DOWN' group by timestamp, devid,
status)### t group by devid, status order by total_num desc
```

Dataset Name	Description	Log Category
fgt-intf-down-dev-tbl	FortiGate Interface Down by Device	event

```
select
  devid,
  status,
  sum(total_num) as total_num
```

```
from
  ###(select $flex_timestamp as timestamp, devid, status, count(*) as total_num from $log
where $filter and logid_to_int(logid)=20099 and status='DOWN' group by timestamp, devid,
status)### t group by devid, status order by total_num desc
```

Dataset Name	Description	Log Category
intf-sent-timeline-for-each-device	FortiGate cpu utilization timeline	event

```
select
  $flex_timescale(timestamp) as hodex,
  devid,
  cast(
    sum(total_cpu)/ sum(count) as decimal(6, 0)
  ) as cpu_ave,
  cast(
    sum(total_mem)/ sum(count) as decimal(6, 0)
  ) as mem_ave,
  cast(
    sum(total_disk)/ sum(count) as decimal(6, 0)
  ) as disk_ave,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps
from
  ###(select $flex_timestamp as timestamp, devid, count(*) as count, sum(coalesce(mem, 0)) as
total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce
(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_
peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate, 0)) as total_erate, sum
(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate,
0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalsession, max(coalesce(totalses-
sion, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer))
as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast
(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth,
 '/', 2), '0') as integer)) as transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce
(setuprate, 0)) as cps_peak from $log where $filter and action='perf-stats' group by
timestamp, devid)### t where $filter-drilldown group by hodex, devid order by hodex
```

Dataset Name	Description	Log Category
status-timeline-by-device-intf-sent	FortiGate interface summary view	event

```
select
  devid,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(sent + recv)/ sum(count) as decimal(10, 0)
  ) as transmit_kbps,
```

```

    max(transmit_peak) as transmit_kbps_peak
from
    ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
    (coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
    total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
    (coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
    0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
    (erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
    sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
    '/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
    integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
    (coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
    (setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
    action='perf-stats' group by devid)### t group by devid order by transmit_kbps_peak desc

```

Dataset Name	Description	Log Category
intf-recv-timeline-for-each-device	FortiGate cpu utilization timeline	event

```

select
    $flex_timescale(timestamp) as hodex,
    devid,
    cast(
        sum(total_cpu)/ sum(count) as decimal(6, 0)
    ) as cpu_ave,
    cast(
        sum(total_mem)/ sum(count) as decimal(6, 0)
    ) as mem_ave,
    cast(
        sum(total_disk)/ sum(count) as decimal(6, 0)
    ) as disk_ave,
    cast(
        sum(sent)/ sum(count) as decimal(10, 0)
    ) as sent_kbps,
    cast(
        sum(recv)/ sum(count) as decimal(10, 0)
    ) as recv_kbps
from
    ###(select $flex_timestamp as timestamp, devid, count(*) as count, sum(coalesce(mem, 0)) as
    total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as total_disk, max(coalesce
    (disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max(coalesce(cpu, 0)) as cpu_
    peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate, 0)) as total_erate, sum
    (coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce(erate, 0)+coalesce(orate,
    0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalsession, max(coalesce(totalses-
    sion, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer))
    as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as recv, max(cast
    (coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast(coalesce(split_part(bandwidth,
    '/', 2), '0') as integer)) as transmit_peak, sum(coalesce(setuprate, 0)) as cps, max(coalesce
    (setuprate, 0)) as cps_peak from $log where $filter and action='perf-stats' group by
    timestamp, devid)### t where $filter-drilldown group by hodex, devid order by hodex

```

Dataset Name	Description	Log Category
status-timeline-by-device-intf-recv	FortiGate interface summary view	event

```

select
  devid,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(sent + recv)/ sum(count) as decimal(10, 0)
  ) as transmit_kbps,
  max(transmit_peak) as transmit_kbps_peak
from
  ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
(coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
(coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
'/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
action='perf-stats' group by devid)### t group by devid order by transmit_kbps_peak desc

```

Dataset Name	Description	Log Category
event-intf-summary-dev	FortiGate interface summary view	event

```

select
  devid,
  cast(
    sum(sent)/ sum(count) as decimal(10, 0)
  ) as sent_kbps,
  cast(
    sum(recv)/ sum(count) as decimal(10, 0)
  ) as recv_kbps,
  cast(
    sum(sent + recv)/ sum(count) as decimal(10, 0)
  ) as transmit_kbps,
  max(transmit_peak) as transmit_kbps_peak
from
  ###(select min(itime) as first_seen, max(itime) as last_seen, devid, count(*) as count, sum
(coalesce(mem, 0)) as total_mem, max(coalesce(mem, 0)) mem_peak, sum(coalesce(disk, 0)) as
total_disk, max(coalesce(disk, 0)) as disk_peak, sum(coalesce(cpu, 0)) as total_cpu, max
(coalesce(cpu, 0)) as cpu_peak, sum(coalesce(trate, 0)) as total_trate, sum(coalesce(erate,
0)) as total_erate, sum(coalesce(orate, 0)) as total_orate, max(coalesce(trate, 0)+coalesce
(erate, 0)+coalesce(orate, 0)) as lograte_peak, sum(coalesce(totalsession, 0)) as totalses-
sion, max(coalesce(totalsession, 0)) as session_peak, sum(cast(coalesce(split_part(bandwidth,
'/', 1), '0') as integer)) as sent, sum(cast(coalesce(split_part(bandwidth, '/', 2), '0') as
integer)) as recv, max(cast(coalesce(split_part(bandwidth, '/', 1), '0') as integer)+cast
(coalesce(split_part(bandwidth, '/', 2), '0') as integer)) as transmit_peak, sum(coalesce
(setuprate, 0)) as cps, max(coalesce(setuprate, 0)) as cps_peak from $log where $filter and
action='perf-stats' group by devid)### t group by devid order by transmit_kbps_peak desc

```



Dataset Name	Description	Log Category
fgt-intf-stats-timeline-util-in-each	FortiGate Interface Statistics Timeline	event

```

select
  hosex,
  dev_intf,
  kbps_out_avg,
  kbps_in_avg,
  util_out_avg,
  util_in_avg
from
  (
    select
      $flex_timescale(timestamp) as hosex,
      (devname || ':' || intfname) as dev_intf,
      cast(
        sum(bps_out) / sum(interval) / 1000 as decimal(10, 0)
      ) as kbps_out_avg,
      cast(
        sum(bps_in) / sum(interval) / 1000 as decimal(10, 0)
      ) as kbps_in_avg,
      cast(
        sum(util_out) / sum(interval) / 100 as decimal(10, 2)
      ) as util_out_avg,
      cast(
        sum(util_in) / sum(interval) / 100 as decimal(10, 2)
      ) as util_in_avg
    from
      (
        select
          $flex_timestamp(timestamp) as timestamp,
          tbl_intf.dvid,
          intfname,
          sum(interval) as interval,
          sum(sentbps * interval) as bps_out,
          sum(rcvdbps * interval) as bps_in,
          sum(sentutil * interval) as util_out,
          sum(rcvdutil * interval) as util_in
        from
          (
            select
              distinct dvid
            from
              ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
time_filter(timestamp) group by timestamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on
t1.dvid = t2.dvid group by hosex, dev_intf) t where $filter-drilldown order by hosex

```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-util-in	FortiGate Interface Received Utilization	event

```

select
  (devname || ':' || intfname) as dev_intf,
  cast(

```

```

        sum(bps_out)/ sum(interval)/ 1000 as decimal(10, 0)
    ) as kbps_out_avg,
    cast(
        sum(bps_in)/ sum(interval)/ 1000 as decimal(10, 0)
    ) as kbps_in_avg,
    cast(
        sum(util_out)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_out_avg,
    cast(
        sum(util_in)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_in_avg
from
    (
        select
            $flex_timestamp(timestamp) as tmstamp,
            tbl_intf.dvid,
            intfname,
            sum(interval) as interval,
            sum(sentbps * interval) as bps_out,
            sum(rcvdbps * interval) as bps_in,
            sum(sentutil * interval) as util_out,
            sum(rcvdutil * interval) as util_in
        from
            (
                select
                    distinct dvid
                from
                    ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
time_filter(timestamp) group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on
t1.dvid = t2.dvid group by dev_intf order by util_in_avg desc, kbps_in_avg desc, kbps_out_avg
desc

```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-util-out-each	FortiGate Interface Statistics Timeline	event

```

select
    horex,
    dev_intf,
    kbps_out_avg,
    kbps_in_avg,
    util_out_avg,
    util_in_avg
from
    (
        select
            $flex_timescale(tmstamp) as horex,
            (devname || ':' || intfname) as dev_intf,
            cast(
                sum(bps_out)/ sum(interval)/ 1000 as decimal(10, 0)
            ) as kbps_out_avg,
            cast(
                sum(bps_in)/ sum(interval)/ 1000 as decimal(10, 0)
            ) as kbps_in_avg,
            cast(

```

```

        sum(util_out)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_out_avg,
    cast(
        sum(util_in)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_in_avg
from
    (
        select
            $flex_timestamp(timestamp) as tmstamp,
            tbl_intf.dvid,
            intfname,
            sum(interval) as interval,
            sum(sentbps * interval) as bps_out,
            sum(rcvdbps * interval) as bps_in,
            sum(sentutil * interval) as util_out,
            sum(rcvdutil * interval) as util_in
        from
            (
                select
                    distinct dvid
                from
                    ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
time_filter(timestamp) group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on
t1.dvid = t2.dvid group by hodex, dev_intf) t where $filter-drilldown order by hodex

```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-util-out	FortiGate Interface Sent Utilization	event

```

select
    (devname || ':' || intfname) as dev_intf,
    cast(
        sum(bps_out)/ sum(interval)/ 1000 as decimal(10, 0)
    ) as kbps_out_avg,
    cast(
        sum(bps_in)/ sum(interval)/ 1000 as decimal(10, 0)
    ) as kbps_in_avg,
    cast(
        sum(util_out)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_out_avg,
    cast(
        sum(util_in)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_in_avg
from
    (
        select
            $flex_timestamp(timestamp) as tmstamp,
            tbl_intf.dvid,
            intfname,
            sum(interval) as interval,
            sum(sentbps * interval) as bps_out,
            sum(rcvdbps * interval) as bps_in,
            sum(sentutil * interval) as util_out,
            sum(rcvdutil * interval) as util_in
        from

```

```
(
  select
    distinct dvid
  from
    ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
time_filter(timestamp) group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on
t1.dvid = t2.dvid group by dev_intf order by util_out_avg desc, kbps_out_avg desc, kbps_in_avg
desc
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-bit-rate-in-each	FortiGate Interface Statistics Timeline	event

```
select
  hosex,
  dev_intf,
  kbps_out_avg,
  kbps_in_avg,
  util_out_avg,
  util_in_avg
from
  (
    select
      $flex_timescale(tmstamp) as hosex,
      (devname || ':' || intfname) as dev_intf,
      cast(
        sum(bps_out) / sum(interval) / 1000 as decimal(10, 0)
      ) as kbps_out_avg,
      cast(
        sum(bps_in) / sum(interval) / 1000 as decimal(10, 0)
      ) as kbps_in_avg,
      cast(
        sum(util_out) / sum(interval) / 100 as decimal(10, 2)
      ) as util_out_avg,
      cast(
        sum(util_in) / sum(interval) / 100 as decimal(10, 2)
      ) as util_in_avg
    from
      (
        select
          $flex_timestamp(timestamp) as tmstamp,
          tbl_intf.dvid,
          intfname,
          sum(interval) as interval,
          sum(sentbps * interval) as bps_out,
          sum(rcvdbps * interval) as bps_in,
          sum(sentutil * interval) as util_out,
          sum(rcvdutil * interval) as util_in
        from
          (
            select
              distinct dvid
            from
              ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
```

```
time_filter(timestamp) group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on
t1.dvid = t2.dvid group by hodex, dev_intf) t where $filter-drilldown order by hodex
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-bit-rate-in	FortiGate Interface Received Bit Rate	event

```
select
  (devname || ':' || intfname) as dev_intf,
  cast(
    sum(bps_out)/ sum(interval)/ 1000 as decimal(10, 0)
  ) as kbps_out_avg,
  cast(
    sum(bps_in)/ sum(interval)/ 1000 as decimal(10, 0)
  ) as kbps_in_avg,
  cast(
    sum(util_out)/ sum(interval)/ 100 as decimal(10, 2)
  ) as util_out_avg,
  cast(
    sum(util_in)/ sum(interval)/ 100 as decimal(10, 2)
  ) as util_in_avg
from
  (
    select
      $flex_timestamp(timestamp) as tmstamp,
      tbl_intf.dvid,
      intfname,
      sum(interval) as interval,
      sum(sentbps * interval) as bps_out,
      sum(rcvdbps * interval) as bps_in,
      sum(sentutil * interval) as util_out,
      sum(rcvdutil * interval) as util_in
    from
      (
        select
          distinct dvid
        from
          ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
time_filter(timestamp) group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on
t1.dvid = t2.dvid group by dev_intf order by kbps_in_avg desc
```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-bit-rate-out-each	FortiGate Interface Statistics Timeline	event

```
select
  hodex,
  dev_intf,
  kbps_out_avg,
  kbps_in_avg,
  util_out_avg,
  util_in_avg
from
  (
    select
```

```

$flex_timescale(tmstamp) as hodex,
(devname || ':' || intfname) as dev_intf,
cast(
    sum(bps_out)/ sum(interval)/ 1000 as decimal(10, 0)
) as kbps_out_avg,
cast(
    sum(bps_in)/ sum(interval)/ 1000 as decimal(10, 0)
) as kbps_in_avg,
cast(
    sum(util_out)/ sum(interval)/ 100 as decimal(10, 2)
) as util_out_avg,
cast(
    sum(util_in)/ sum(interval)/ 100 as decimal(10, 2)
) as util_in_avg
from
(
    select
        $flex_timestamp(timestamp) as tmstamp,
        tbl_intf.dvid,
        intfname,
        sum(interval) as interval,
        sum(sentbps * interval) as bps_out,
        sum(rcvdbps * interval) as bps_in,
        sum(sentutil * interval) as util_out,
        sum(rcvdutil * interval) as util_in
    from
        (
            select
                distinct dvid
            from
                ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
time_filter(timestamp) group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on
t1.dvid = t2.dvid group by hodex, dev_intf) t where $filter-drilldown order by hodex

```

Dataset Name	Description	Log Category
fgt-intf-stats-timeline-bit-rate-out	FortiGate Interface Sent Bit Rate	event

```

select
    (devname || ':' || intfname) as dev_intf,
    cast(
        sum(bps_out)/ sum(interval)/ 1000 as decimal(10, 0)
    ) as kbps_out_avg,
    cast(
        sum(bps_in)/ sum(interval)/ 1000 as decimal(10, 0)
    ) as kbps_in_avg,
    cast(
        sum(util_out)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_out_avg,
    cast(
        sum(util_in)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_in_avg
from
(
    select

```

```

    $flex_timestamp(timestamp) as tmstamp,
    tbl_intf.dvid,
    intfname,
    sum(interval) as interval,
    sum(sentbps * interval) as bps_out,
    sum(rcvdbps * interval) as bps_in,
    sum(sentutil * interval) as util_out,
    sum(rcvdutil * interval) as util_in
from
(
    select
        distinct dvid
    from
        ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
time_filter(timestamp) group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on
t1.dvid = t2.dvid group by dev_intf order by kbps_out_avg desc

```

Dataset Name	Description	Log Category
fgt-intf-stats-summary-view	FortiGate Interface Received Utilization	event

```

select
    (devname || ':' || intfname) as dev_intf,
    cast(
        sum(bps_out)/ sum(interval)/ 1000 as decimal(10, 0)
    ) as kbps_out_avg,
    cast(
        sum(bps_in)/ sum(interval)/ 1000 as decimal(10, 0)
    ) as kbps_in_avg,
    cast(
        sum(util_out)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_out_avg,
    cast(
        sum(util_in)/ sum(interval)/ 100 as decimal(10, 2)
    ) as util_in_avg
from
(
    select
        $flex_timestamp(timestamp) as tmstamp,
        tbl_intf.dvid,
        intfname,
        sum(interval) as interval,
        sum(sentbps * interval) as bps_out,
        sum(rcvdbps * interval) as bps_in,
        sum(sentutil * interval) as util_out,
        sum(rcvdutil * interval) as util_in
    from
        (
            select
                distinct dvid
            from
                ###(select dvid from $log-event where $filter and action='perf-stats' group by
dvid)### t) tbl_log inner join intfstats tbl_intf on tbl_log.dvid = tbl_intf.dvid where $cust_
time_filter(timestamp) group by tmstamp, tbl_intf.dvid, intfname) t1 left join devtable t2 on

```

## Dataset Reference List

```
t1.dvid = t2.dvid group by dev_intf order by util_in_avg desc, kbps_in_avg desc, kbps_out_avg desc
```

Dataset Name	Description	Log Category
fgt-ha-failure-timeline	FortiGate HA Failure Timeline	event

```
select
  $flex_timescale(timestamp) as hodex,
  count(*) as total_num
from
  ###(select $flex_timestamp as timestamp, dttime, devid, coalesce(nullifna(logdesc), msg) as
msg_desc from $log where $filter and subtype='ha' and logid_to_int(logid) in (35011, 35012,
35013, 37892, 37893, 37897, 37898, 37901, 37902, 37907, 37908) order by dttime desc)### t group
by hodex order by hodex
```

Dataset Name	Description	Log Category
fgt-ha-failure-summary	FortiGate HA Failure Summary	event

```
select
  from_dtime(dttime) as time_s,
  devid,
  msg_desc
from
  ###(select $flex_timestamp as timestamp, dttime, devid, coalesce(nullifna(logdesc), msg) as
msg_desc from $log where $filter and subtype='ha' and logid_to_int(logid) in (35011, 35012,
35013, 37892, 37893, 37897, 37898, 37901, 37902, 37907, 37908) order by dttime desc)### t order
by time_s desc
```

Dataset Name	Description	Log Category
fgt-env-faults-power	FortiGate Power Supply Faults	event

```
select
  from_dtime(dttime) as time_s,
  devid,
  coalesce(
    nullifna(logdesc),
    msg
  ) as msg_desc
from
  $log
where
  $filter
  and logid_to_int(logid) in (22105, 22107)
order by
  time_s desc
```

Dataset Name	Description	Log Category
fgt-env-faults-fan	FortiGate Fan Faults	event

```
select
  from_dtime(dttime) as time_s,
  devid,
```



```

    coalesce(
        nullifna(logdesc),
        msg
    ) as msg_desc
from
    $log
where
    $filter
    and logid_to_int(logid)= 22108
order by
    time_s desc

```

Dataset Name	Description	Log Category
fgt-env-faults-temperature	FortiGate Temperatre Too High	event

```

select
    from_dtime(dtime) as time_s,
    devid,
    coalesce(
        nullifna(logdesc),
        msg
    ) as msg_desc
from
    $log
where
    $filter
    and logid_to_int(logid)= 22109
order by
    time_s desc

```

Dataset Name	Description	Log Category
Behaviour-Banned-Application	Bullying Chat Search and Message Logging	app-ctrl

```

select
    filename,
    string_agg(distinct app, ' ') as app_agg,
    string_agg(
        distinct from_itime(itime): :text,
        ' '
    ) as itime_agg,
    string_agg(distinct user_src, ' ') as user_agg,
    string_agg(distinct `group`, ' ') as group_agg,
    string_agg(
        distinct ipstr(`srcip`),
        ' '
    ) as srcip_agg,
    count(*) as requests
from
    ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(
    `srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
    book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
    send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
    'bing.search_search.phrase')) and ($bully_keywords) order by itime desc)### t group by file-
    name order by requests desc

```

Dataset Name	Description	Log Category
Behaviour-Banned-User	Bullying Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(distinct app, ' ') as app_agg,
  string_agg(
    distinct from_itime(itime): :text,
    ' '
  ) as itime_agg,
  string_agg(distinct user_src, ' ') as user_agg,
  string_agg(distinct `group`, ' ') as group_agg,
  string_agg(
    distinct ipstr(`srcip`),
    ' '
  ) as srcip_agg,
  count(*) as requests
from
  ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(
  `srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
  book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
  send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
  'bing.search_search.phrase')) and ($bully_keywords) order by itime desc)### t group by file-
  name order by requests desc
```

Dataset Name	Description	Log Category
Behaviour-Banned-User-Drilldown	Bullying Chat Search and Message Logging	app-ctrl

```
select
  filename,
  string_agg(distinct app, ' ') as app_agg,
  string_agg(
    distinct from_itime(itime): :text,
    ' '
  ) as itime_agg,
  string_agg(distinct user_src, ' ') as user_agg,
  string_agg(distinct `group`, ' ') as group_agg,
  string_agg(
    distinct ipstr(`srcip`),
    ' '
  ) as srcip_agg,
  count(*) as requests
from
  ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(
  `srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
  book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
  send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
  'bing.search_search.phrase')) and ($bully_keywords) order by itime desc)### t group by file-
  name order by requests desc
```

Dataset Name	Description	Log Category
behaviour-banned	Bullying Chat Search and Message Logging	app-ctrl

```

select
  filename,
  string_agg(distinct app, ' ') as app_agg,
  string_agg(
    distinct from_itime(itime)::text,
    ' '
  ) as itime_agg,
  string_agg(distinct user_src, ' ') as user_agg,
  string_agg(distinct `group`, ' ') as group_agg,
  string_agg(
    distinct ipstr(`srcip`),
    ' '
  ) as srcip_agg,
  count(*) as requests
from
  ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(
  `srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
  book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
  send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
  'bing.search_search.phrase')) and ($bully_keywords) order by itime desc)### t group by file-
  name order by requests desc

```

Dataset Name	Description	Log Category
Self-Harm-Behaviour-Banned-User-Pie	Self-Harm Chat Search and Message Logging	app-ctrl

```

select
  filename,
  string_agg(distinct app, ' ') as app_agg,
  string_agg(
    distinct from_itime(itime)::text,
    ' '
  ) as itime_agg,
  string_agg(distinct user_src, ' ') as user_agg,
  string_agg(distinct `group`, ' ') as group_agg,
  string_agg(
    distinct ipstr(`srcip`),
    ' '
  ) as srcip_agg,
  count(*) as requests
from
  ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(
  `srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
  book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
  send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
  'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by file-
  name order by requests desc

```

Dataset Name	Description	Log Category
Self-Harm-Behaviour-Banned-Application-Pie	Self-Harm Chat Search and Message Logging	app-ctrl

```

select
  filename,
  string_agg(distinct app, ' ') as app_agg,

```

```

string_agg(
    distinct from_itime(itime): :text,
    ' '
) as itime_agg,
string_agg(distinct user_src, ' ') as user_agg,
string_agg(distinct `group`, ' ') as group_agg,
string_agg(
    distinct ipstr(`srcip`),
    ' '
) as srcip_agg,
count(*) as requests
from
    ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by file-
name order by requests desc

```

Dataset Name	Description	Log Category
Self-Harm-Behaviour-Banned-User-Bar	Self-Harm Chat Search and Message Logging	app-ctrl

```

select
    filename,
    string_agg(distinct app, ' ') as app_agg,
    string_agg(
        distinct from_itime(itime): :text,
        ' '
    ) as itime_agg,
    string_agg(distinct user_src, ' ') as user_agg,
    string_agg(distinct `group`, ' ') as group_agg,
    string_agg(
        distinct ipstr(`srcip`),
        ' '
    ) as srcip_agg,
    count(*) as requests
from
    ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by file-
name order by requests desc

```

Dataset Name	Description	Log Category
Self-Harm-Behaviour-Banned-User-Drilldown	Self-Harm Chat Search and Message Logging	app-ctrl

```

select
    filename,
    string_agg(distinct app, ' ') as app_agg,
    string_agg(
        distinct from_itime(itime): :text,
        ' '
    ) as itime_agg,
    string_agg(distinct user_src, ' ') as user_agg,
    string_agg(distinct `group`, ' ') as group_agg,
    string_agg(
        distinct ipstr(`srcip`),
        ' '
    ) as srcip_agg,
    count(*) as requests
from
    ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
(`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by file-
name order by requests desc

```

```

) as itime_agg,
string_agg(distinct user_src, ' ') as user_agg,
string_agg(distinct `group`, ' ') as group_agg,
string_agg(
    distinct ipstr(`srcip`),
    ' '
) as srcip_agg,
count(*) as requests
from
    ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
    (`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
    book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
    send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
    'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by file-
    name order by requests desc

```

Dataset Name	Description	Log Category
Self-Harm-behaviour-banned	Self-Harm Chat Search and Message Logging	app-ctrl

```

select
    filename,
    string_agg(distinct app, ' ') as app_agg,
    string_agg(
        distinct from_itime(itime): :text,
        ' '
    ) as itime_agg,
    string_agg(distinct user_src, ' ') as user_agg,
    string_agg(distinct `group`, ' ') as group_agg,
    string_agg(
        distinct ipstr(`srcip`),
        ' '
    ) as srcip_agg,
    count(*) as requests
from
    ###(select filename, app, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr
    (`srcip`)) as user_src, `group`, `srcip` from $log where $filter and (lower(app) in ('face-
    book_post', 'facebook_chat', 'twitter_post', 'youtube_video.access', 'gmail_chat', 'gmail_
    send.message', 'linkedin_post', 'vimeo_video.access', 'google.search_search.phrase',
    'bing.search_search.phrase')) and ($banned_keywords) order by itime desc)### t group by file-
    name order by requests desc

```

Dataset Name	Description	Log Category
Browsing-Time-per-Social-Media	Browsing Time vs. Domain	traffic

```

select
    domain,
    ebtr_value(
        ebtr_agg_flat(browsetime),
        null,
        $timespan
    ) as browsetime
from
    ###({{FGT_DATASET_TRAFFIC_TOP_DOMAIN_USER_BY_EB_TIME}})### t where browsetime is not null
group by domain order by browsetime desc

```

Dataset Name	Description	Log Category
Social-Networking-Bar-Graph	Social Networking Browsing Time	traffic

```
select
  f_user,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_TOP_DOMAIN_USER_BY_EB_TIME}})### t where bandwidth>0 group by f_
user order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Social-Networking-Durations-Sources-Drilldown	Top Social Networking Durations from Sources Drilldown	traffic

```
select
  f_user,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###({{FGT_DATASET_TRAFFIC_TOP_DOMAIN_USER_BY_EB_TIME}})### t where $filter-drilldown and
browsetime is not null group by f_user order by browsetime desc
```

Dataset Name	Description	Log Category
Top-Social-Networking-Durations-Domains-Drilldown	Browsing Time vs. Domain	traffic

```
select
  domain,
  ebtr_value(
    ebtr_agg_flat(browsetime),
    null,
    $timespan
  ) as browsetime
from
  ###({{FGT_DATASET_TRAFFIC_TOP_DOMAIN_USER_BY_EB_TIME}})### t where browsetime is not null
group by domain order by browsetime desc
```

Dataset Name	Description	Log Category
Facebook-Posts	Facebook Posts	app-ctrl

```
select
  from_itime(itime) as i_time,
  coalesce(
    nullifna(`user`),
    nullifna(`unauthuser`),
    ipstr(`srcip`)
  ) as f_user,
  srcip,
```

```

    filename
from
    $log
where
    $filter
    and lower(app)= lower('Facebook_Post')
    and filename is not null
order by
    i_time desc

```

Dataset Name	Description	Log Category
Facebook-Chats	Facebook Chats	app-ctrl

```

select
    filename,
    string_agg(
        distinct from_itime(itime): :text,
        ' '
    ) as itime_agg,
    string_agg(distinct user_src, ' ') as user_agg,
    string_agg(distinct `group`, ' ') as group_agg,
    string_agg(
        distinct ipstr(srcip),
        ' '
    ) as srcip_agg,
    count(*) as requests
from
    ###(select filename, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`src-
    cip`)) as user_src, `group`, srcip from $log where $filter and lower(app)=lower('Facebook_
    Chat') and filename is not null)### t group by filename order by requests desc

```

Dataset Name	Description	Log Category
Twitter-Posts	Twitter Posts	app-ctrl

```

select
    from_itime(itime) as i_time,
    coalesce(
        nullifna(`user`),
        nullifna(`unauthuser`),
        ipstr(`srcip`)
    ) as f_user,
    srcip,
    filename
from
    $log
where
    $filter
    and lower(app)= lower('Twitter_Post')
    and filename is not null
order by
    i_time desc

```

Dataset Name	Description	Log Category
LinkedIn-Posts-and-Comments	LinkedIn Posts and Comments	app-ctrl

```

select
  filename,
  string_agg(
    distinct from_itime(itime): :text,
    ' '
  ) as itime_agg,
  string_agg(distinct user_src, ' ') as user_agg,
  string_agg(distinct `group`, ' ') as group_agg,
  string_agg(
    distinct ipstr(srcip),
    ' '
  ) as srcip_agg,
  count(*) as requests
from
  ###(select filename, itime, coalesce(nullifna(`user`), nullifna(`unauthuser`), ipstr(`srcip`)) as user_src, `group`, srcip from $log where $filter and lower(app)=lower('LinkedIn_Post') and filename is not null)### t group by filename order by requests desc

```

Dataset Name	Description	Log Category
sdwan-fw-Device-Interface-Quality-Bibandwidth-drilldown	SD-WAN Device-Interface Statistic	event

```

select
  devid,
  sum(bibandwidth)/ sum(count_linkup) as bibandwidth
from
  ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and bibandwidth is not null group by devid having sum(count_linkup)>0 order by bibandwidth desc

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Latency-Line	SD-WAN Device-Interface Latency Timeline	event

```

select
  $flex_timescale(timestamp) as hodex,
  t1.interface,
  min(latency) as latency
from
  (
    select
      timestamp,
      devid,
      interface,
      sum(latency)/ sum(count_linkup) as latency
    from
      ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t group by timestamp, devid, interface having sum(count_linkup)>0) t1 inner join (select interface, count(*) as num_intf from ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and interface is not null group by interface order by num_intf desc limit 10)t2 on t1.interface=t2.interface group by hodex, t1.interface order by hodex

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Jitter-Line	SD-WAN Device-Interface Jitter Timeline	event



```

select
    $flex_timescale(timestamp) as hosex,
    t1.interface,
    min(jitter) as jitter
from
    (
        select
            timestamp,
            devid,
            interface,
            sum(jitter)/ sum(count_linkup) as jitter
        from
            ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t group by timestamp, devid, interface hav-
ing sum(count_linkup)>0) t1 inner join (select interface, count(*) as num_intf from ###({{FGT_
DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and interface is not null group
by interface order by num_intf desc limit 10)t2 on t1.interface=t2.interface group by hosex,
t1.interface order by hosex

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Packetloss-Line	SD-WAN Device-Interface Packetloss Timeline	event

```

select
    $flex_timescale(timestamp) as hosex,
    t1.interface,
    min(packetloss) as packetloss
from
    (
        select
            timestamp,
            devid,
            interface,
            sum(packetloss)/ sum(count_linkup) as packetloss
        from
            ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t group by timestamp, devid, interface hav-
ing sum(count_linkup)>0) t1 inner join (select interface, count(*) as num_intf from ###({{FGT_
DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and interface is not null group
by interface order by num_intf desc limit 10)t2 on t1.interface=t2.interface group by hosex,
t1.interface order by hosex

```

Dataset Name	Description	Log Category
sdwan-Device-Latency-Line	SD-WAN Device Latency Timeline	event

```

select
    $flex_timescale(timestamp) as hosex,
    devid,
    min(latency) as latency
from
    (
        select
            timestamp,
            devid,
            interface,
            sum(latency)/ sum(count_linkup) as latency

```

```

from
    ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and latency is
not null group by timestamp, devid, interface having sum(count_linkup)>0) t1 group by hodex,
devid order by hodex

```

Dataset Name	Description	Log Category
sdwan-Device-Jitter-Line	SD-WAN Device Jitter Timeline	event

```

select
    $flex_timescale(timestamp) as hodex,
    devid,
    min(jitter) as jitter
from
    (
        select
            timestamp,
            devid,
            interface,
            sum(jitter)/ sum(count_linkup) as jitter
        from
            ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and jitter is
not null group by timestamp, devid, interface having sum(count_linkup)>0) t1 group by hodex,
devid order by hodex

```

Dataset Name	Description	Log Category
sdwan-Device-Packetloss-Line	SD-WAN Device Packet Loss Timeline	event

```

select
    $flex_timescale(timestamp) as hodex,
    devid,
    min(packetloss) as packetloss
from
    (
        select
            timestamp,
            devid,
            interface,
            sum(packetloss)/ sum(count_linkup) as packetloss
        from
            ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and packetloss
is not null group by timestamp, devid, interface having sum(count_linkup)>0) t1 group by
hodex, devid order by hodex

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Summary-by-Bibandwidth	SD-WAN Device Interface Summary by Bibandwidth	event

```

select
    devid,
    interface,
    sum(bibandwidth)/ sum(count_linkup) as bibandwidth,
    cast(
        min(latency_min) as decimal(18, 2)

```

```

) as latency_min,
cast(
  sum(latency)/ sum(count_linkup) as decimal(18, 2)
) as latency_avg,
cast(
  max(latency_max) as decimal(18, 2)
) as latency_max,
cast(
  min(jitter_min) as decimal(18, 2)
) as jitter_min,
cast(
  sum(jitter)/ sum(count_linkup) as decimal(18, 2)
) as jitter_avg,
cast(
  max(jitter_max) as decimal(18, 2)
) as jitter_max,
cast(
  min(packetloss_min) as decimal(18, 2)
) as packetloss_min,
cast(
  sum(packetloss)/ sum(count_linkup) as decimal(18, 2)
) as packetloss_avg,
cast(
  max(packetloss_max) as decimal(18, 2)
) as packetloss_max
from
  ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and interface is not
  null group by devid, interface having sum(count_linkup)>0 order by devid, interface

```

Dataset Name	Description	Log Category
sdwan-Top-App-By-Bandwidth	Top SD-WAN application by bandwidth	traffic

```

select
  appid,
  app_group,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-drilldown group by
  appid, app_group order by bandwidth desc

```

Dataset Name	Description	Log Category
sdwan-Top-App-By-Bandwidth-Sankey	Top SD-WAN application by bandwidth usage	traffic

```

select
  'SD-WAN Utilization' as summary,
  app_group,
  devid,
  dstintf as interface,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-drilldown group by
  app_group, devid, interface order by bandwidth desc

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-bandwidth-Drilldown	SD-WAN Device Statistic by Bibandwidth	event

```
select
  devid,
  sum(bibandwidth)/ sum(count_linkup) as bibandwidth
from
  ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and bibandwidth is
not null group by devid having sum(count_linkup)>0 order by bibandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-Rules-Donut-Bandwidth	Top SD-WAN Links bandwidth	traffic

```
select
  vwlservice,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-drilldown group by
vwlservice order by bandwidth desc limit 10
```

Dataset Name	Description	Log Category
sdwan-device-interface-bandwidth	Top SD-WAN Links bandwidth	traffic

```
select
  interface,
  sum(bandwidth) as bandwidth
from
  (
    (
      select
        srcintf as interface,
        sum(bandwidth) as bandwidth
      from
        ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where srcintfrole='wan' and
$filter-drilldown group by interface) union all (select dstintf as interface, sum(bandwidth)
as bandwidth from ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where dstint-
frole='wan' and $filter-drilldown group by interface)) t group by interface order by bandwidth
desc limit 10
```

Dataset Name	Description	Log Category
sdwan-Top-Application-Session-Bandwidth	Top SD-WAN application by bandwidth	traffic

```
select
  appid,
  app_group,
  sum(bandwidth) as bandwidth,
  sum(sessions) as sessions
from
```

```
###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-drilldown group by
appid, app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Top-Users-By-Bandwidth-Bar	SD-WAN Top users by bandwidth usage	traffic

```
select
  user_src,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-drilldown group by
  user_src order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-top-user-app-Drilldown	SD-WAN Top users and Application by bandwidth	traffic

```
select
  user_src,
  app_group,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-drilldown group by
  user_src, app_group order by bandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-Intfe-traffic-out-bandwidth-Line	SD-WAN Device-Interface traffic sent bandwidth Timeline	traffic

```
select
  $flex_timescale(timestamp) as hosex,
  t1.dstintf as interface,
  sum(traffic_out) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t1 inner join (select dstintf, count
  (*) as num_intf from ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-
  drilldown and dstintf is not null and dstintfrole ='wan' group by dstintf order by num_intf
  desc limit 10)t2 on t1.dstintf=t2.dstintf group by hosex, t1.dstintf order by hosex
```

Dataset Name	Description	Log Category
sdwan-Device-Intfe-traffic-in-bandwidth-Line	SD-WAN Device-Interface traffic received bandwidth Timeline	traffic

```
select
  $flex_timescale(timestamp) as hosex,
  t1.srcintf as interface,
  sum(traffic_in) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t1 inner join (select srcintf, count
  (*) as num_intf from ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-
  drilldown and srcintf is not null and srcintfrole ='wan' group by srcintf order by num_intf
  desc limit 10)t2 on t1.srcintf=t2.srcintf group by hosex, t1.srcintf order by hosex
```

Dataset Name	Description	Log Category
sdwan-Device-Intfe-traffic-bandwidth-Line	SD-WAN Device-Interface traffic sent bandwidth Timeline	traffic

```
select
  $flex_timescale(timestamp) as hodex,
  t1.dstintf as interface,
  sum(traffic_out) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t1 inner join (select dstintf, count
  (*) as num_intf from ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-
  drilldown and dstintf is not null and dstintfrole ='wan' group by dstintf order by num_intf
  desc limit 10)t2 on t1.dstintf=t2.dstintf group by hodex, t1.dstintf order by hodex
```

Dataset Name	Description	Log Category
sdwan-Device-SLA-Interface-bandwidth-Drilldown	SD-WAN Device Statistic by Bibandwidth	event

```
select
  devid,
  sum(bibandwidth)/ sum(count_linkup) as bibandwidth
from
  ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and bibandwidth is
  not null group by devid having sum(count_linkup)>0 order by bibandwidth desc
```

Dataset Name	Description	Log Category
sdwan-Device-SLA-Rule-Latency-Line	SD-WAN Device-SLA-Rule Latency Line	event

```
select
  $flex_timescale(timestamp) as hodex,
  t1.sla_rule,
  min(latency) as latency
from
  (
    select
      timestamp,
      devid,
      sla_rule,
      sum(latency)/ sum(count_linkup) as latency
    from
      ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t group by timestamp, devid, sla_rule hav-
      ing sum(count_linkup)>0) t1 inner join (select sla_rule, count(*) as num_intf from ###({{FGT_
      DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and sla_rule is not null group
      by sla_rule order by num_intf desc limit 10)t2 on t1.sla_rule=t2.sla_rule group by hodex,
      t1.sla_rule order by hodex
```

Dataset Name	Description	Log Category
sdwan-Device-SLA-Rule-Jitter-Line	SD-WAN Device-SLA-Rule Jitter Line	event

```
select
  $flex_timescale(timestamp) as hodex,
```

```

t1.sla_rule,
min(jitter) as jitter
from
(
select
timestamp,
devid,
sla_rule,
sum(jitter)/ sum(count_linkup) as jitter
from
###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t group by timestamp, devid, sla_rule hav-
ing sum(count_linkup)>0) t1 inner join (select sla_rule, count(*) as num_intf from ###({{FGT_
DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and sla_rule is not null group
by sla_rule order by num_intf desc limit 10)t2 on t1.sla_rule=t2.sla_rule group by horex,
t1.sla_rule order by horex

```

Dataset Name	Description	Log Category
sdwan-Device-SLA-Rule-Packetloss-Line	SD-WAN Device-SLA-Rule Packetloss Line	event

```

select
$flex_timescale(timestamp) as horex,
t1.sla_rule,
min(packetloss) as packetloss
from
(
select
timestamp,
devid,
sla_rule,
sum(packetloss)/ sum(count_linkup) as packetloss
from
###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t group by timestamp, devid, sla_rule hav-
ing sum(count_linkup)>0) t1 inner join (select sla_rule, count(*) as num_intf from ###({{FGT_
DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and sla_rule is not null group
by sla_rule order by num_intf desc limit 10)t2 on t1.sla_rule=t2.sla_rule group by horex,
t1.sla_rule order by horex

```

Dataset Name	Description	Log Category
sdwan-device-sla-intf-latency-pass-percent	SD-WAN Device Latency Pass Percentage by SLA rules and Interface	event

```

select
sla_rule,
interface,
cast(
100 *(
1 - sum(failed_latency)/ sum(count_linkup)
) as decimal(18, 2)
) as latency
from
###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown group by sla_rule,
interface having sum(count_linkup)>0 order by latency desc

```

Dataset Name	Description	Log Category
sdwan-device-sla-intf-jitter-pass-percent	SD-WAN Device Jitter Pass Percentage by SLA rules and Interface	event

```
select
  sla_rule,
  interface,
  cast(
    100 * (
      1 - sum(failed_jitter) / sum(count_linkup)
    ) as decimal(18, 2)
  ) as jitter
from
  ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown group by sla_rule,
  interface having sum(count_linkup)>0 order by jitter desc
```

Dataset Name	Description	Log Category
sdwan-device-sla-intf-packetloss-pass-percent	SD-WAN Device Packet Loss Pass Percentage by SLA rules and Interface	event

```
select
  sla_rule,
  interface,
  cast(
    100 * (
      1 - sum(failed_packetloss) / sum(count_linkup)
    ) as decimal(18, 2)
  ) as packetloss
from
  ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown group by sla_rule,
  interface having sum(count_linkup)>0 order by packetloss desc
```

Dataset Name	Description	Log Category
sdwan-Device-Availability-status	SD-WAN Device Statistic by Bibandwidth	event

```
select
  devid,
  sum(bibandwidth) / sum(count_linkup) as bibandwidth
from
  ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and bibandwidth is
  not null group by devid having sum(count_linkup)>0 order by bibandwidth desc
```

Dataset Name	Description	Log Category
sdwan-device-intf-availability-percentage-bar	SD-WAN Device Interface Availability Percentage	event

```
(
  select
    'SD-WAN' as interface,
    cast(
      sum(availcnt) * 100.0 / sum(count) as decimal(18, 2)
    ) as availability
  from
    ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown
```



```

    ) as available
from
(
    select
        timestamp,
        devid,
        first_value(count) OVER (
            PARTITION BY timestamp,
            devid
            ORDER BY
                link_status / count desc,
                count desc
        ) as count,
        first_value(link_status) OVER (
            PARTITION BY timestamp,
            devid
            ORDER BY
                link_status / count desc,
                count desc
        ) as availcnt
from
(
    select
        timestamp,
        devid,
        interface,
        sum(link_status) as link_status,
        sum(count) as count
from
    ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and
count>0 group by timestamp, devid, interface)t) t group by interface) union all (select inter-
face, cast(sum(link_status)*100.0/sum(count) as decimal(18,2)) as available from ###({{FGT_
DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown group by interface order by
interface)

```

Dataset Name	Description	Log Category
sdwan-device-intf-availability- percentage-donut	SD-WAN Device Interface Availability Percentage Donut	event

```

select
    interface,
    unnest(avail) as avail,
    unnest(val) as val
from
(
    select
        interface,
        array[ 'Available',
        'Unavailable' ] as avail,
        array[available,
        100 - available] as val
from
    (
        (
            select

```

```

        'SD-WAN' as interface,
        cast(
            sum(available)* 100.0 / sum(count) as decimal(18, 2)
        ) as available
    from
    (
        select
            timestamp,
            devid,
            first_value(count) OVER (
                PARTITION BY timestamp,
                devid
                ORDER BY
                    link_status / count desc,
                    count desc
            ) as count,
            first_value(link_status) OVER (
                PARTITION BY timestamp,
                devid
                ORDER BY
                    link_status / count desc,
                    count desc
            ) as availcnt
        from
        (
            select
                timestamp,
                devid,
                interface,
                sum(link_status) as link_status,
                sum(count) as count
            from
                ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown
and count>0 group by timestamp, devid, interface)t) t group by interface) union all (select
interface, cast(sum(link_status)*100.0/sum(count) as decimal(18,2)) as available from ###
({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown group by interface order
by interface)) t) t

```

Dataset Name	Description	Log Category
sdwan-Device-Application-sdwan-Rules-and-Ports-drilldown	SD-WAN Device Statistic by Bibandwidth	event

```

select
    devid,
    sum(bibandwidth) / sum(count_linkup) as bibandwidth
from
    ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and bibandwidth is
not null group by devid having sum(count_linkup)>0 order by bibandwidth desc

```

Dataset Name	Description	Log Category
sdwan-Device-Interface-Application-Traffic-Sankey	Top SD-WAN application by bandwidth sankey	traffic

```

select
  'SD-WAN Rules' as summary,
  'Rule:' || vwlservice as vwlservice,
  app_group,
  devid,
  dstintf as interface,
  sum(bandwidth) as bandwidth
from
  ###({{FGT_DATASET_TRAFFIC_SD_WAN_RULES_INTF_USR}})### t where $filter-drilldown group by
  vwlservice, app_group, devid, interface order by bandwidth desc

```

Dataset Name	Description	Log Category
sdwan-fw-Device-Interface-test2	SD-WAN Device-Interface Statistic	event

```

select
  devid,
  sum(bibandwidth) / sum(count_linkup) as bibandwidth
from
  ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and bibandwidth is
  not null group by devid having sum(count_linkup)>0 order by bibandwidth desc

```

Dataset Name	Description	Log Category
sdwan-Device-Intf-Avail-Percentage-Timeline	SD-WAN Device Interface Availability Percentage Timeline	event

```

select
  hodex,
  interface,
  available
from
  (
    (
      select
        $flex_datetime(timestamp) as hodex,
        'SD-WAN' as interface,
        cast(
          sum(availcnt) * 100.0 / sum(count) as decimal(18, 2)
        ) as available
      from
        (
          select
            timestamp,
            devid,
            first_value(count) OVER (
              PARTITION BY timestamp,
              devid
              ORDER BY
                link_status / count desc,
                count desc
            ) as count,
            first_value(link_status) OVER (
              PARTITION BY timestamp,
              devid
              ORDER BY

```

```

        link_status / count desc,
        count desc
    ) as availcnt
from
(
    select
        timestamp,
        devid,
        interface,
        sum(link_status) as link_status,
        sum(count) as count
    from
        ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $filter-drilldown and
count>0 group by timestamp, devid, interface)t) t group by hodex order by hodex) union all
(select $flex_datetime(timestamp) as hodex, interface, cast(sum(link_status)*100.0/sum(count)
as decimal(18,2)) as available from ###({{FGT_DATASET_EVENT_SD_WAN_DEV_STAT}})### t where $fil-
ter-drilldown group by hodex, interface order by hodex)) t order by hodex

```

Dataset Name	Description	Log Category
Top-Web-Sites-by-Bandwidth	Top web sites by bandwidth usage	webfilter

```

select
    domain,
    sum(bandwidth) as bandwidth
from
    ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, sum(coalesce(sentbyte,
0)+coalesce(rcvdbyte, 0)) as bandwidth from $log-traffic where $filter and (logflag&1>0) and
(countweb>0 or ((logver is null or logver<502000000) and (hostname is not null or utmevent in
('webfilter', 'banned-word', 'web-content', 'command-block', 'script-filter')))) group by
domain having sum(coalesce(sentbyte, 0)+coalesce(rcvdbyte, 0))>0 order by bandwidth desc)### t
group by domain order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-App-Category-by-Session	Application risk application usage by category	traffic

```

select
    appcat,
    sum(sessions) as total_num
from
    ###(select appid, app, appcat, apprisk, sum(bandwidth) as bandwidth, sum(sessions) as ses-
sions from {{FGT_DATASET_BASE_TRAFFIC_TOP_APPS}} t group by appid, app, appcat, apprisk
/*SkipSTART*/order by sessions desc, bandwidth desc/*SkipEND*/)### t where $filter-drilldown
group by appcat order by total_num desc

```

Dataset Name	Description	Log Category
Top-Region-Name-by-Traffic	Traffic top destination countries by browsing time	traffic

```

select
    dstcountry,
    sum(bandwidth) as bandwidth
from
    ###({{FGT_DATASET_TRAFFIC_TOP_DST_COUNTRY_BY_EB_TIME}})### t where $filter-drilldown group
by dstcountry order by bandwidth desc

```

Dataset Name	Description	Log Category
Top-App-By-Bandwidth-Chart	Top applications by bandwidth usage	traffic

```
select
  app_group_name(app) as app_group,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  ) as bandwidth,
  sum(
    coalesce(rcvbyte, 0)
  ) as traffic_in,
  sum(
    coalesce(sentbyte, 0)
  ) as traffic_out,
  count(*) as sessions
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and nullifna(app) is not null
group by
  app_group
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
Top-Protocols-By-Traffic	Top applications by bandwidth usage	traffic

```
select
  service,
  sum(bandwidth) as bandwidth
from
  ###(select service, sum(bandwidth) as bandwidth from {{FGT_DATASET_BASE_TRAFFIC_BANDWIDTH_SESSION}} base_query group by service order by bandwidth desc)### t where $filter-drilldown
group by service order by bandwidth desc
```

Dataset Name	Description	Log Category
Top-Web-Sites-by-Sessions	Top web sites by session count	webfilter

```
select
  domain,
  sum(sessions) as sessions
from
  ###(select coalesce(nullifna(hostname), ipstr(`dstip`)) as domain, count(*) as sessions
from $log where $filter and (eventtype is null or logver>=502000000) group by domain order by sessions desc)### t group by domain order by sessions desc
```

Dataset Name	Description	Log Category
Top-Attacks-by-Count	Threat attacks by severity	attack

```
select
  attack,
  sum(attack_count) as totalnum
from
  ###({{FGT_DATASET_ATTACK_TOP_ATTACKS}})### t where $filter-drilldown and attack is not null
group by attack order by totalnum desc
```

Dataset Name	Description	Log Category
Top-Spams-by-Count	User drilldown top spam sources	emailfilter

```
select
  user_src,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATASET_EMAILFILTER_USER_SENDER}})### t where $filter-drilldown and mf_sender is
not null group by user_src order by totalnum desc
```

Dataset Name	Description	Log Category
utm-Top-Virus-Count	UTM top virus	virus

```
select
  virus,
  max(virusid_s) as virusid,
  (
    case when virus like 'Riskware%' then 'Spyware' when virus like 'Adware%' then 'Adware'
  else 'Virus' end
  ) as malware_type,
  sum(totalnum) as totalnum
from
  ###(select virus, virusid_to_str(virusid, eventtype) as virusid_s, count(*) as totalnum from
$log where $filter and (eventtype is null or logver>=502000000) and nullifna(virus) is not
null group by virus, virusid_s /*SkipSTART*/order by totalnum desc/*SkipEND*/)### t group by
virus, malware_type order by totalnum desc
```

Dataset Name	Description	Log Category
security-Antivirus-Inspections	Antivirus Inspections	virus

```
select
  action,
  sum(totalnum) as totalnum
from
  ###({{FGT_DATASET_EMAILFILTER_USER_SENDER}})### t where $filter-drilldown and action is not
null group by action order by totalnum desc
```

Dataset Name	Description	Log Category
Top-DLP-by-Count	Email DLP Activity Summary	dlp

```
select
  profile,
  count(*) as total_num
from
  ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and profile is not
  null group by profile order by total_num desc
```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Client	Top access point by client	traffic

```
select
  ap_srcintf as srcintf,
  count(distinct srcmac) as totalnum
from
  ###(select coalesce(ap, srcintf) as ap_srcintf, srcssid, osname, srcswversion, get_devtype
  (srcswversion, osname, devtype) as devtype_new, srcmac, count(*) as subtotal from $log where
  $filter and (logflag&1>0) and (srcssid is not null or dstssid is not null) and srcmac is not
  null group by ap_srcintf, srcssid, osname, srcswversion, devtype_new, srcmac order by subtotal
  desc)### t group by srcintf order by totalnum desc
```

Dataset Name	Description	Log Category
wifi-Top-AP-By-Bandwidth	Top access point by bandwidth usage	traffic

```
select
  coalesce(ap, srcintf) as ap_srcintf,
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  ) as bandwidth
from
  $log
where
  $filter
  and (
    logflag&1>0
  )
  and (
    srcssid is not null
    or dstssid is not null
  )
group by
  ap_srcintf
having
  sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
  )> 0
order by
  bandwidth desc
```

Dataset Name	Description	Log Category
wifi-Top-SSID-By-Bandwidth	Top SSIDs by bandwidth usage	traffic

```
select
  srcssid,
```

```

sum(
    coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
) as bandwidth
from
    $log
where
    $filter
    and (
        logflag&1>0
    )
    and srcssid is not null
group by
    srcssid
having
    sum(
        coalesce(sentbyte, 0)+ coalesce(rcvdbyte, 0)
    )> 0
order by
    bandwidth desc

```

Dataset Name	Description	Log Category
360-degree-security-Application-Visibility-and-Control-Summary	Application Visibility and Control Summary	app-ctrl

```

select
    appcat,
    count(distinct app) as total_num
from
    ###(select appcat, app from $log where $filter and app is not null and appcat is not null
group by appcat, app)### t group by appcat order by total_num desc

```

Dataset Name	Description	Log Category
360-degree-security-Threats-Detection-and-Prevention-Summary	Threat Prevention	app-ctrl

```

select
    threat_name,
    count(distinct threats) as total_num
from
    (
        ###(select cast('Malware & Botnet C&C' as char(32)) as threat_name, app as threats from
$log-app-ctrl where $filter and lower(appcat)='botnet' group by app)### union all ###(select
cast('Malware & Botnet C&C' as char(32)) as threat_name, virus as threats from $log-virus
where $filter and nullifna(virus) is not null group by virus)### union all ###(select cast
('Malicious & Phishing Sites' as char(32)) as threat_name, hostname as threats from $log-web-
filter where $filter and cat in (26, 61) group by hostname)### union all ###(select cast('Crit-
ical & High Intrusion Attacks' as char(32)) as threat_name, attack as threats from $log-attack
where $filter and severity in ('critical', 'high') group by attack)###) t group by threat_name
order by total_num desc

```

Dataset Name	Description	Log Category
360-degree-security-Data-Exfiltration-Detection-and-Prevention-Summary	Data Exfiltration Summary	dlp



```

select
    data_loss,
    count(*) as total_num
from
    ###({{FGT_DATASET_DLP_VIOLATION_SUMMARY}})### t where $filter-drilldown and data_loss is not
    null group by data_loss order by total_num desc

```

Dataset Name	Description	Log Category
360-degree-security-Endpoint-Protection-Summary	Endpoint Protection	fct-traffic

```

select
    blocked_event,
    count(*) as total_num
from
    (
        select
            (
                case utmevent when 'antivirus' then 'Malware Deteced and Blocked' when 'appfirewall'
then 'Risk Application Blocked' when 'webfilter' then (
                    case when coalesce(
                        nullifna(`user`),
                        ipstr(`srcip`)
                    ) is not null then 'Web Sites Violation Blocked' else 'Non User Initiated Web Vis-
its' end
                ) else NULL end
            ) as blocked_event
        from
            $log
        where
            $filter
            and utmaction in ('blocked', 'quarantined')
    ) t
where
    blocked_event is not null
group by
    blocked_event
order by
    total_num desc

```

# Macro Reference List

The following table lists the available predefined macros that can be used in a report layout to display the log data as text (XML format) dynamically.

Macro Name	Description	Dataset Used	Log Category
Application Category with Highest Session Count	Application category with the highest session count	App-Sessions-By-Category	Traffic
Application with Highest Bandwidth	Application with the highest bandwidth usage	Top-App-By-Bandwidth	Traffic
Application with Highest Session Count	Applications with the highest session count	Top-App-By-Sessions	Traffic
Attack with Highest Session Count	Attack with highest session count	Utm-Top-Attack-Source	Attack
Botnet with Highest Session Count	Botnet with the highest session count	Detected-Botnet	Traffic
Destination with Highest Bandwidth	Destination with the highest bandwidth usage	Top-Destinations-By-Bandwidth	Traffic
Destination with Highest Session Count	Destination with the highest session count	Top-Destinations-By-Sessions	Traffic
Highest Bandwidth Consumed (Application) Category	Highest bandwidth consumed by application category	App-Risk-App-Usage-By-Category	Traffic
Highest Bandwidth Consumed (Application)	Highest bandwidth consumed by application	Top-App-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Destination)	Highest bandwidth consumed by destination	Top-Destinations-By-Bandwidth	Traffic
Highest Bandwidth Consumed (P2P Application)	Highest bandwidth consumed by P2P application	Top-P2P-App-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Source)	Highest bandwidth consumed by source	Top-Users-By-Bandwidth	Traffic
Highest Bandwidth Consumed (Web Category)	Highest bandwidth consumed by website category	Top-Web-Category-by-Bandwidth	Web Filter
Highest Bandwidth Consumed (Website)	Highest bandwidth consumed by website	Top-Web-Sites-by-Bandwidth	Web Filter
Highest Risk Application with Highest Bandwidth	Highest risk application with the highest bandwidth usage	High-Risk-Application-By-Bandwidth	Traffic
Highest Risk Application with Highest Session Count	Highest risk application with the highest session count	High-Risk-Application-By-Sessions	Traffic

Macro Name	Description	Dataset Used	Log Category
Highest Session Count by Application Category	Highest session count by application category	App-Sessions-By-Category	Traffic
Highest Session Count by Application	Highest session count by application	Top-App-By-Sessions	Traffic
Highest Session Count by Attack	Highest session count by attack	Utm-Top-Attack-Source	Attack
Highest Session Count by Botnet	Highest session count by botnet	Detected-Botnet	Traffic
Highest Session Count by Destination	Highest session count by destination	Top-Destinations-By-Sessions	Traffic
Highest Session Count by Highest Severity Attack	Highest session count by highest severity attack	Threat-Attacks-By-Severity	Attack
Highest Session Count by P2P Application	Highest session count by P2P application	Top-P2P-App-By-Sessions	Traffic
Highest Session Count by Source	Highest session count by source	Top-User-Source-By-Sessions	Traffic
Highest Session Count by Virus	Highest session count by virus	Utm-Top-Virus	Traffic
Highest Session Count by Web Category	Highest session count by website category	Top-Web-Category-by-Sessions	Web Filter
Highest Session Count by Website	Highest session count by website	Top-Web-Sites-by-Sessions	Web Filter
Highest Severity Attack with Highest Session Count	Highest severity attack with the highest session count	Threat-Attacks-By-Severity	Attack
P2P Application with Highest Bandwidth	P2P applications with the highest bandwidth usage	Top-P2P-App-By-Bandwidth	Traffic
P2P Application with Highest Session Count	P2P applications with the highest session count	Top-P2P-App-By-Sessions	Traffic
Source with Highest Bandwidth	Source with the highest bandwidth usage	Top-Users-By-Bandwidth	Traffic
Source with Highest Session Count	Source with the highest session count	Top-User-Source-By-Sessions	Traffic
Total Number of Attacks	Total number of attacks detected	Total-Attack-Source	Attack
Total Number of Botnet Events	Total number of botnet events	Total-Number-of-Botnet-Events	Traffic
Total Number of Viruses	Total number of viruses detected	Total-Number-of-Viruses	Traffic
User Details	User details of traffic	Traffic-User-Detail	Traffic
Virus with Highest Session Count	Virus with the highest session count	Utm-Top-Virus	Traffic

Macro Name	Description	Dataset Used	Log Category
Web Category with Highest Bandwidth	Web filtering category with the highest bandwidth usage	Top-Web-Category-by-Bandwidth	Web Filter
Web Category with Highest Session Count	Web filtering category with the highest session count	Top-Web-Category-by-Sessions	Web Filter
Website with Highest Bandwidth	Website with the highest bandwidth usage	Top-Web-Sites-by-Bandwidth	Web Filter
Website with Highest Session Count	Website with the highest session count	Top-Web-Sites-by-Sessions	Web Filter

## Change Log

Date	Change Description
2020-06-15	Initial release.



**FORTINET®**



Copyright© 2020 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. In no event does Fortinet make any commitment related to future deliverables, features or development, and circumstances may change such that any forward-looking statements herein are not accurate. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.