



# FortiOS - Log Reference

Version 6.2.3

**FORTINET DOCUMENT LIBRARY**

<https://docs.fortinet.com>

**FORTINET VIDEO GUIDE**

<https://video.fortinet.com>

**FORTINET BLOG**

<https://blog.fortinet.com>

**CUSTOMER SERVICE & SUPPORT**

<https://support.fortinet.com>

**FORTINET TRAINING & CERTIFICATION PROGRAM**

<https://www.fortinet.com/support-and-training/training.html>

**NSE INSTITUTE**

<https://training.fortinet.com>

**FORTIGUARD CENTER**

<https://fortiguard.com/>

**END USER LICENSE AGREEMENT**

<https://www.fortinet.com/doc/legal/EULA.pdf>

**FEEDBACK**

Email: [techdoc@fortinet.com](mailto:techdoc@fortinet.com)



# TABLE OF CONTENTS

<b>Change Log</b> .....	<b>28</b>
<b>Introduction</b> .....	<b>29</b>
Before you begin .....	29
What's new .....	30
FortiOS 6.2.3 .....	30
FortiOS 6.2.2 .....	30
FortiOS 6.2.1 .....	30
FortiOS 6.2.0 .....	30
<b>Log Types and Subtypes</b> .....	<b>32</b>
Type .....	32
Subtype .....	32
List of log types and subtypes .....	32
UTM log subtypes .....	33
FortiOS priority levels .....	34
Log field format .....	35
<b>Log Schema Structure</b> .....	<b>36</b>
Log message fields .....	36
Log ID numbers .....	39
Log ID definitions .....	40
<b>FortiGuard Web Filter Categories</b> .....	<b>43</b>
<b>CEF Support</b> .....	<b>46</b>
FortiOS to CEF log field mapping guidelines .....	46
CEF priority levels .....	46
Examples of CEF support .....	47
Traffic log support for CEF .....	47
Event log support for CEF .....	49
Antivirus log support for CEF .....	50
Webfilter log support for CEF .....	51
IPS log support for CEF .....	52
Email Spamfilter log support for CEF .....	52
Anomaly log support for CEF .....	53
VoIP log support for CEF .....	53
DLP log support for CEF .....	54
Application log support for CEF .....	54
WAF log support for CEF .....	55
DNS log support for CEF .....	55
SSH log support for CEF .....	56
<b>UTM Extended Logging</b> .....	<b>57</b>
Enabling extended logging .....	57
Extended logging option in UTM profiles .....	57
Syslog server mode .....	58
Example of an extended log .....	58

<b>Log Messages</b> .....	<b>59</b>
Anomaly .....	59
18432 - LOGID_ATTCK_ANOMALY_TCP_UDP .....	59
18433 - LOGID_ATTCK_ANOMALY_ICMP .....	60
18434 - LOGID_ATTCK_ANOMALY_OTHERS .....	62
App .....	64
28672 - LOGID_APP_CTRL_IM_BASIC .....	64
28673 - LOGID_APP_CTRL_IM_BASIC_WITH_STATUS .....	65
28674 - LOGID_APP_CTRL_IM_BASIC_WITH_COUNT .....	67
28675 - LOGID_APP_CTRL_IM_FILE .....	68
28676 - LOGID_APP_CTRL_IM_CHAT .....	70
28677 - LOGID_APP_CTRL_IM_CHAT_BLOCK .....	71
28678 - LOGID_APP_CTRL_IM_BLOCK .....	73
28704 - LOGID_APP_CTRL_IPS_PASS .....	74
28705 - LOGID_APP_CTRL_IPS_BLOCK .....	76
28706 - LOGID_APP_CTRL_IPS_RESET .....	79
28720 - LOGID_APP_CTRL_SSH_PASS .....	81
28721 - LOGID_APP_CTRL_SSH_BLOCK .....	82
28736 - LOGID_APP_CTRL_PORT_ENF .....	84
28737 - LOGID_APP_CTRL_PROTO_ENF .....	86
AV .....	88
8192 - MSGID_INFECT_WARNING .....	88
8193 - MSGID_INFECT_NOTIF .....	91
8194 - MSGID_INFECT_MIME_WARNING .....	93
8195 - MSGID_INFECT_MIME_NOTIF .....	95
8200 - MSGID_MIME_FILETYPE_EXE_WARNING .....	98
8201 - MSGID_MIME_FILETYPE_EXE_NOTIF .....	100
8202 - MSGID_AVQUERY_WARNING .....	102
8203 - MSGID_AVQUERY_NOTIF .....	104
8204 - MSGID_MIME_AVQUERY_WARNING .....	106
8205 - MSGID_MIME_AVQUERY_NOTIF .....	109
8212 - MSGID_MALWARE_LIST_WARNING .....	111
8213 - MSGID_MALWARE_LIST_NOTIF .....	113
8214 - MSGID_MIME_MALWARE_LIST_WARNING .....	116
8215 - MSGID_MIME_MALWARE_LIST_NOTIF .....	118
8448 - MSGID_BLOCK_WARNING .....	120
8450 - MSGID_BLOCK_MIME_WARNING .....	122
8451 - MSGID_BLOCK_MIME_NOTIF .....	124
8452 - MSGID_BLOCK_COMMAND .....	126
8457 - MSGID_MMS_CHECKSUM .....	128
8458 - MSGID_MMS_CHECKSUM_NOTIF .....	130
8704 - MSGID_OVERSIZE_WARNING .....	132
8705 - MSGID_OVERSIZE_NOTIF .....	134
8706 - MSGID_OVERSIZE_MIME_WARNING .....	135
8707 - MSGID_OVERSIZE_MIME_NOTIF .....	137
8708 - MSGID_OVERSIZE_STREAM_UNCOMP_WARNING .....	139
8709 - MSGID_OVERSIZE_STREAM_UNCOMP_NOTIF .....	141
8720 - MSGID_SWITCH_PROTO_WARNING .....	142
8721 - MSGID_SWITCH_PROTO_NOTIF .....	144

8960 - MESSAGES_SCAN_UNCOMPRESSED_WARNING	146
8961 - MESSAGES_SCAN_UNCOMPRESSED_NOTIFICATION	148
8962 - MESSAGES_SCAN_ARCHIVE_ENCRYPTED_WARNING	151
8963 - MESSAGES_SCAN_ARCHIVE_ENCRYPTED_NOTIFICATION	153
8964 - MESSAGES_SCAN_ARCHIVE_CORRUPTED_WARNING	155
8965 - MESSAGES_SCAN_ARCHIVE_CORRUPTED_NOTIFICATION	158
8966 - MESSAGES_SCAN_ARCHIVE_MULTIPART_WARNING	160
8967 - MESSAGES_SCAN_ARCHIVE_MULTIPART_NOTIFICATION	162
8968 - MESSAGES_SCAN_ARCHIVE_NESTED_WARNING	165
8969 - MESSAGES_SCAN_ARCHIVE_NESTED_NOTIFICATION	167
8970 - MESSAGES_SCAN_ARCHIVE_OVERSIZE_WARNING	169
8971 - MESSAGES_SCAN_ARCHIVE_OVERSIZE_NOTIFICATION	172
8972 - MESSAGES_SCAN_ARCHIVE_UNHANDLED_WARNING	174
8973 - MESSAGES_SCAN_ARCHIVE_UNHANDLED_NOTIFICATION	176
8974 - MESSAGES_SCAN_AV_ENGINE_LOAD_FAILED_ERROR	179
8975 - MESSAGES_SCAN_ARCHIVE_PARTIALLYCORRUPTED_WARNING	181
8976 - MESSAGES_SCAN_ARCHIVE_PARTIALLYCORRUPTED_NOTIFICATION	183
8977 - MESSAGES_SCAN_ARCHIVE_FILESLIMIT_WARNING	186
8978 - MESSAGES_SCAN_ARCHIVE_FILESLIMIT_NOTIFICATION	188
8979 - MESSAGES_SCAN_ARCHIVE_TIMEOUT_WARNING	190
8980 - MESSAGES_SCAN_ARCHIVE_TIMEOUT_NOTIFICATION	193
9233 - MESSAGES_ANALYTICS_SUBMITTED	195
9234 - MESSAGES_ANALYTICS_INFECT_WARNING	197
9235 - MESSAGES_ANALYTICS_INFECT_NOTIFICATION	200
9236 - MESSAGES_ANALYTICS_INFECT_MIME_WARNING	202
9237 - MESSAGES_ANALYTICS_INFECT_MIME_NOTIFICATION	204
9238 - MESSAGES_ANALYTICS_FSA_RESULT	207
9239 - MESSAGES_CONTENT_DISARM_NOTIFICATION	208
9240 - MESSAGES_CONTENT_DISARM_WARNING	210
CIFS	212
63000 - LOG_ID_CIFS_FILE_BLOCK	212
63001 - LOG_ID_CIFS_FILE_PASS	213
DLP	215
24576 - LOG_ID_DLP_WARN	215
24577 - LOG_ID_DLP_NOTIFICATION	217
24578 - LOG_ID_DLP_DOC_SOURCE	219
24579 - LOG_ID_DLP_DOC_SOURCE_ERROR	220
DNS	221
54000 - LOG_ID_DNS_QUERY	221
54200 - LOG_ID_DNS_RESOLV_ERROR	222
54400 - LOG_ID_DNS_URL_FILTER_BLOCK	224
54401 - LOG_ID_DNS_URL_FILTER_ALLOW	226
54600 - LOG_ID_DNS_BOTNET_IP	228
54601 - LOG_ID_DNS_BOTNET_DOMAIN	230
54800 - LOG_ID_DNS_FTGD_WARNING	232
54801 - LOG_ID_DNS_FTGD_ERROR	234
54802 - LOG_ID_DNS_FTGD_CAT_ALLOW	236
54803 - LOG_ID_DNS_FTGD_CAT_BLOCK	238
54804 - LOG_ID_DNS_SAFE_SEARCH	239

Email .....	241
20480 - LOGID_ANTISPAM_EMAIL_SMTP_NOTIF .....	241
20481 - LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF .....	243
20482 - LOGID_ANTISPAM_EMAIL_POP3_NOTIF .....	245
20483 - LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF .....	247
20484 - LOGID_ANTISPAM_EMAIL_IMAP_NOTIF .....	249
20485 - LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING .....	251
20486 - LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF .....	252
20487 - LOGID_ANTISPAM_ENDPOINT_MM7_WARNING .....	254
20488 - LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF .....	256
20489 - LOGID_ANTISPAM_ENDPOINT_MM1_WARNING .....	258
20490 - LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF .....	260
20491 - LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF .....	262
20492 - LOGID_ANTISPAM_MM1_FLOOD_WARNING .....	264
20493 - LOGID_ANTISPAM_MM1_FLOOD_NOTIF .....	265
20494 - LOGID_ANTISPAM_MM4_FLOOD_WARNING .....	267
20495 - LOGID_ANTISPAM_MM4_FLOOD_NOTIF .....	269
20496 - LOGID_ANTISPAM_MM1_DUPE_WARNING .....	271
20497 - LOGID_ANTISPAM_MM1_DUPE_NOTIF .....	273
20498 - LOGID_ANTISPAM_MM4_DUPE_WARNING .....	275
20499 - LOGID_ANTISPAM_MM4_DUPE_NOTIF .....	277
20500 - LOGID_ANTISPAM_EMAIL_MSN_NOTIF .....	278
20501 - LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF .....	280
20502 - LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF .....	282
20503 - LOGID_EMAIL_SMTP_GENERAL_NOTIF .....	284
20504 - LOGID_EMAIL_POP3_GENERAL_NOTIF .....	286
20505 - LOGID_EMAIL_IMAP_GENERAL_NOTIF .....	288
20506 - LOGID_EMAIL_MAPI_GENERAL_NOTIF .....	290
20507 - LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF .....	291
20508 - LOGID_ANTISPAM_EMAIL_MAPI_NOTIF .....	293
20509 - LOGID_ANTISPAM_FTGD_ERR .....	295
Event .....	297
20002 - LOG_ID_DOMAIN_UNRESOLVABLE .....	297
20003 - LOG_ID_MAIL_SENT_FAIL .....	298
20004 - LOG_ID_POLICY_TOO_BIG .....	299
20005 - LOG_ID_PPP_LINK_UP .....	299
20006 - LOG_ID_PPP_LINK_DOWN .....	300
20007 - LOG_ID_SOCKET_EXHAUSTED .....	301
20008 - LOG_ID_POLICY6_TOO_BIG .....	302
20010 - LOG_ID_KERNEL_ERROR .....	303
20016 - LOG_ID_MODEM_EXCEED_REDIAL_COUNT .....	303
20017 - LOG_ID_MODEM_FAIL_TO_OPEN .....	304
20020 - LOG_ID_MODEM_USB_DETECTED .....	305
20021 - LOG_ID_MAIL_RESENT .....	305
20022 - LOG_ID_MODEM_USB_REMOVED .....	306
20023 - LOG_ID_MODEM_USBLTE_DETECTED .....	307
20024 - LOG_ID_MODEM_USBLTE_REMOVED .....	307
20025 - LOG_ID_REPORTD_REPORT_SUCCESS .....	308
20026 - LOG_ID_REPORTD_REPORT_FAILURE .....	309

20027 - LOG_ID_REPORT_DEL_OLD_REC .....	310
20028 - LOG_ID_REPORT_RECREATE_DB .....	310
20031 - LOG_ID_RAD_OUT_OF_MEM .....	311
20032 - LOG_ID_RAD_NOT_FOUND .....	312
20033 - LOG_ID_RAD_MOBILE_IPV6 .....	312
20034 - LOG_ID_RAD_IPV6_OUT_OF_RANGE .....	313
20035 - LOG_ID_RAD_MIN_OUT_OF_RANGE .....	314
20036 - LOG_ID_RAD_MAX_OUT_OF_RANGE .....	314
20037 - LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE .....	315
20039 - LOG_ID_RAD_MTU_TOO_SMALL .....	316
20040 - LOG_ID_RAD_TIME_TOO_SMALL .....	316
20041 - LOG_ID_RAD_HOP_OUT_OF_RANGE .....	317
20042 - LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE .....	318
20043 - LOG_ID_RAD_AGENT_OUT_OF_RANGE .....	318
20044 - LOG_ID_RAD_AGENT_FLAG_NOT_SET .....	319
20045 - LOG_ID_RAD_PREFIX_TOO_LONG .....	320
20046 - LOG_ID_RAD_PREF_TIME_TOO_SMALL .....	320
20047 - LOG_ID_RAD_FAIL_IPV6_SOCKET .....	321
20048 - LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO .....	322
20049 - LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM .....	322
20050 - LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS .....	323
20051 - LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS .....	324
20052 - LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT .....	324
20053 - LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6 .....	325
20054 - LOG_ID_RAD_EXIT_BY_SIGNAL .....	326
20055 - LOG_ID_RAD_FAIL_CMDB_QUERY .....	326
20056 - LOG_ID_RAD_FAIL_CMDB_FOR_EACH .....	327
20057 - LOG_ID_RAD_FAIL_FIND_VIRT_INTF .....	328
20058 - LOG_ID_RAD_UNLOAD_INTF .....	328
20061 - LOG_ID_RAD_INV_ICMPV6_TYPE .....	329
20062 - LOG_ID_RAD_INV_ICMPV6_RA_LEN .....	330
20063 - LOG_ID_RAD_ICMPV6_NO_SRC_ADDR .....	330
20064 - LOG_ID_RAD_INV_ICMPV6_RS_LEN .....	331
20065 - LOG_ID_RAD_INV_ICMPV6_CODE .....	332
20066 - LOG_ID_RAD_INV_ICMPV6_HOP .....	332
20067 - LOG_ID_RAD_MISMATCH_HOP .....	333
20068 - LOG_ID_RAD_MISMATCH_MGR_FLAG .....	334
20069 - LOG_ID_RAD_MISMATCH_OTH_FLAG .....	334
20070 - LOG_ID_RAD_MISMATCH_TIME .....	335
20071 - LOG_ID_RAD_MISMATCH_TIMER .....	336
20072 - LOG_ID_RAD_EXTRA_DATA .....	336
20073 - LOG_ID_RAD_NO_OPT_DATA .....	337
20074 - LOG_ID_RAD_INV_OPT_LEN .....	338
20075 - LOG_ID_RAD_MISMATCH_MTU .....	338
20077 - LOG_ID_RAD_MISMATCH_PREF_TIME .....	339
20078 - LOG_ID_RAD_INV_OPT .....	340
20079 - LOG_ID_RAD_READY .....	340
20080 - LOG_ID_RAD_FAIL_TO_RCV .....	341
20081 - LOG_ID_RAD_INV_HOP .....	342

20082 - LOG_ID_RAD_INV_PKTINFO .....	342
20083 - LOG_ID_RAD_FAIL_TO_CHECK .....	343
20084 - LOG_ID_RAD_FAIL_TO_SEND .....	344
20085 - LOG_ID_SESSION_CLASH .....	344
20090 - LOG_ID_INTF_LINK_STA_CHG .....	345
20099 - LOG_ID_INTF_STA_CHG .....	346
20100 - LOG_ID_WEB_CAT_UPDATED .....	347
20101 - LOG_ID_WEB_LIC_EXPIRE .....	347
20102 - LOG_ID_SPAM_LIC_EXPIRE .....	348
20103 - LOG_ID_AV_LIC_EXPIRE .....	349
20104 - LOG_ID_IPS_LIC_EXPIRE .....	349
20107 - LOG_ID_LOG_UPLOAD_ERR .....	350
20108 - LOG_ID_LOG_UPLOAD_DONE .....	351
20109 - LOG_ID_WEB_LIC_EXPIRED .....	352
20113 - LOG_ID_IPSA_DOWNLOAD_FAIL .....	352
20115 - LOG_ID_IPSA_STATUSUPD_FAIL .....	353
20116 - LOG_ID_SPAM_LIC_EXPIRED .....	354
20117 - LOG_ID_AV_LIC_EXPIRED .....	354
20118 - LOG_ID_WEBF_STATUS_REACH .....	355
20119 - LOG_ID_WEBF_STATUS_UNREACH .....	356
20200 - LOG_ID_FIPS_SELF_TEST .....	356
20201 - LOG_ID_FIPS_SELF_ALL_TEST .....	357
20202 - LOG_ID_DISK_FORMAT_ERROR .....	358
20203 - LOG_ID_DAEMON_SHUTDOWN .....	359
20204 - LOG_ID_DAEMON_START .....	360
20205 - LOG_ID_DISK_FORMAT_REQ .....	360
20206 - LOG_ID_DISK_SCAN_REQ .....	361
20207 - LOG_ID_RAD_MISMATCH_VALID_TIME .....	362
20208 - LOG_ID_ZOMBIE_DAEMON_CLEANUP .....	363
20209 - LOG_ID_DISK_UNAVAIL .....	363
20210 - LOG_ID_DISK_TRIM_START .....	364
20211 - LOG_ID_DISK_TRIM_END .....	365
20212 - LOG_ID_DISK_SCAN_NEEDED .....	366
20213 - LOG_ID_DISK_LOG_CORRUPTED .....	366
20220 - LOGID_EVENT_SHAPER_OUTBOUND_MAXED_OUT .....	367
20221 - LOGID_EVENT_SHAPER_INBOUND_MAXED_OUT .....	368
20300 - LOG_ID_BGP_NB_STAT_CHG .....	368
20301 - LOG_ID_VZ_LOG .....	369
20302 - LOG_ID_OSPF_NB_STAT_CHG .....	370
20303 - LOG_ID_OSPF6_NB_STAT_CHG .....	370
20401 - LOG_ID_ROUTER_CLEAR .....	371
22000 - LOG_ID_INV_PKT_LEN .....	372
22001 - LOG_ID_UNSUPPORTED_PROT_VER .....	373
22002 - LOG_ID_INV_REQ_TYPE .....	373
22003 - LOG_ID_FAIL_SET_SIG_HANDLER .....	374
22004 - LOG_ID_FAIL_CREATE_SOCKET .....	375
22005 - LOG_ID_FAIL_CREATE_SOCKET_RETRY .....	375
22006 - LOG_ID_FAIL_REG_CMDB_EVENT .....	376
22009 - LOG_ID_FAIL_FIND_AV_PROFILE .....	377



22010 - LOG_ID_SENDTO_FAIL .....	377
22011 - LOG_ID_ENTER_MEM_CONSERVE_MODE .....	378
22012 - LOG_ID_LEAVE_MEM_CONSERVE_MODE .....	379
22013 - LOG_ID_IPPOOLPBA_BLOCK_EXHAUSTED .....	380
22014 - LOG_ID_IPPOOLPBA_NATIP_EXHAUSTED .....	381
22015 - LOG_ID_IPPOOLPBA_CREATE .....	381
22016 - LOG_ID_IPPOOLPBA_DEALLOCATE .....	382
22017 - LOG_ID_EXCEED_GLOB_RES_LIMIT .....	383
22018 - LOG_ID_EXCEED_VD_RES_LIMIT .....	384
22019 - LOG_ID_LOGRATE_OVER_LIMIT .....	385
22020 - LOG_ID_FAIL_CREATE_HA_SOCKET .....	385
22021 - LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY .....	386
22031 - LOG_ID_SUCCESS_CSF_LOG_SYNC_CONFIG_CHANGED .....	387
22032 - LOG_ID_CSF_LOOP_FOUND .....	387
22033 - LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FSA .....	388
22035 - LOG_ID_CSF_UPSTREAM_SN_CHANGED .....	389
22036 - LOG_ID_CSF_FGT_CONNECTED .....	390
22037 - LOG_ID_CSF_FGT_DISCONNECTED .....	391
22100 - LOG_ID_QUAR_DROP_TRAN_JOB .....	392
22101 - LOG_ID_QUAR_DROP_TLL_JOB .....	392
22102 - LOG_ID_LOG_DISK_FAILURE .....	393
22103 - LOG_ID_QUAR_LIMIT_REACHED .....	394
22104 - LOG_ID_POWER_RESTORE .....	395
22105 - LOG_ID_POWER_FAILURE .....	396
22106 - LOG_ID_POWER_OPTIONAL_NOT_DETECTED .....	396
22107 - LOG_ID_VOLT_ANOM .....	397
22108 - LOG_ID_FAN_ANOM .....	398
22109 - LOG_ID_TEMP_TOO_HIGH .....	399
22110 - LOG_ID_SPARE_BLOCK_LOW .....	399
22113 - LOG_ID_FNBAM_FAILURE .....	400
22150 - LOG_ID_VOLT_NOM .....	401
22151 - LOG_ID_FAN_NOM .....	401
22152 - LOG_ID_TEMP_TOO_LOW .....	402
22153 - LOG_ID_TEMP_NORM .....	403
22200 - LOG_ID_AUTO_UPT_CERT .....	404
22201 - LOG_ID_AUTO_GEN_CERT .....	405
22203 - LOG_ID_AUTO_GEN_CERT_FAIL .....	405
22204 - LOG_ID_AUTO_GEN_CERT_PENDING .....	406
22205 - LOG_ID_AUTO_GEN_CERT_SUCC .....	407
22206 - LOG_ID_CRL_EXPIRED .....	408
22700 - LOG_ID_IPS_FAIL_OPEN .....	409
22701 - LOG_ID_IPS_FAIL_OPEN_END .....	409
22800 - LOG_ID_SCAN_SERV_FAIL .....	410
22802 - LOG_ID_ENTER_FD_CONSERVE_MODE .....	411
22803 - LOG_ID_LEAVE_FD_CONSERVE_MODE .....	412
22804 - LOG_ID_LIC_STATUS_CHG .....	412
22805 - LOG_ID_FAIL_TO_VALIDATE_LIC .....	413
22806 - LOG_ID_DUP_LIC .....	414
22808 - LOG_ID_LIC_EXPIRE .....	415

22809 - LOG_ID_LIC_WILL_EXPIRE .....	415
22810 - LOG_ID_SCANUNIT_ERROR_BLOCK .....	416
22811 - LOG_ID_SCANUNIT_ERROR_PASS .....	417
22812 - LOG_ID_SCANUNIT_AVENG_RELOAD .....	418
22813 - LOG_ID_SCANUNIT_AVDB_RELOAD .....	419
22814 - LOG_ID_SCANUNIT_AVDB_RELOAD_ERROR .....	420
22815 - LOG_ID_SCANUNIT_AVDB_LOAD .....	420
22816 - LOG_ID_SCANUNIT_AVDB_LOAD_ERROR .....	421
22850 - LOG_ID_USER_QUARANTINE_MAC_ADD .....	422
22851 - LOG_ID_USER_QUARANTINE_MAC_DELETE .....	423
22852 - LOG_ID_USER_QUARANTINE_MAC_BOUNCE_PORT_HIT .....	423
22853 - LOG_ID_USER_QUARANTINE_MAC_BOUNCE_PORT_MISS .....	424
22890 - LOG_ID_FORTILINKD .....	425
22891 - LOG_ID_FLCFGD_SYNC_ERROR .....	426
22892 - LOG_ID_FLCFGD_SYNC_COMPLETE .....	426
22893 - LOG_ID_FLCFGD_SYNC_STATE .....	427
22894 - LOG_ID_FLCFGD_UPGRADE_ERROR .....	428
22895 - LOG_ID_FLCFGD_UPGRADE_STATUS .....	429
22896 - LOG_ID_FORTILINKD_CRITICAL .....	429
22900 - LOG_ID_CAPUTP_SESSION .....	430
22901 - LOG_ID_FAZ_CON .....	431
22902 - LOG_ID_FAZ_DISCON .....	431
22903 - LOG_ID_FAZ_CON_ERR .....	432
22904 - LOG_ID_CAPUTP_SESSION_NOTIF .....	433
22912 - LOG_ID_FDS_SRV_ERRCON .....	434
22913 - LOG_ID_FDS_SRV_DISCON .....	435
22914 - LOG_ID_FDS_SRV_CHG .....	435
22915 - LOG_ID_FDS_SRV_CON .....	436
22916 - LOG_ID_FDS_STATUS .....	437
22917 - LOG_ID_FDS_SMS_QUOTA .....	438
22918 - LOG_ID_FDS_CTRL_STATUS .....	438
22921 - LOG_ID_EVENT_ROUTE_INFO_CHANGED .....	439
22922 - LOG_ID_EVENT_LINK_MONITOR_STATUS .....	440
22923 - LOG_ID_EVENT_VWL_LQTY_STATUS .....	441
22924 - LOG_ID_EVENT_VWL_VOLUME_STATUS .....	441
22925 - LOG_ID_EVENT_LINK_MONITOR_SLA_INFO .....	442
22926 - LOG_ID_EVENT_VWL_NEIGHBOR_STATUS .....	443
22927 - LOG_ID_EVENT_VWL_NEIGHBOR_STANDALONE .....	444
22928 - LOG_ID_EVENT_VWL_NEIGHBOR_PRIMARY .....	444
22929 - LOG_ID_EVENT_VWL_NEIGHBOR_SECONDARY .....	445
22949 - LOG_ID_FDS_JOIN .....	446
22950 - LOG_ID_FDS_LOGIN_SUCC .....	446
22951 - LOG_ID_FDS_LOGOUT .....	447
22952 - LOG_ID_FDS_LOGIN_FAIL .....	448
22953 - LOG_ID_IOC_DETECTED .....	449
23101 - LOG_ID_IPSEC_TUNNEL_UP .....	449
23102 - LOG_ID_IPSEC_TUNNEL_DOWN .....	450
23103 - LOG_ID_IPSEC_TUNNEL_STAT .....	451
26001 - LOG_ID_DHCP_ACK .....	452

26002 - LOG_ID_DHCP_RELEASE .....	453
26003 - LOG_ID_DHCP_STAT .....	454
26004 - LOG_ID_DHCP_CLIENT_LEASE .....	455
26005 - LOG_ID_DHCP_LEASE_USAGE_HIGH .....	455
26006 - LOG_ID_DHCP_LEASE_USAGE_FULL .....	456
26007 - LOG_ID_DHCP_BLOCKED_MAC .....	457
26008 - LOG_ID_DHCP_DDNS_ADD .....	457
26009 - LOG_ID_DHCP_DDNS_DELETE .....	458
26010 - LOG_ID_DHCP_DDNS_COMPLETED .....	459
26011 - LOG_ID_DHCPV6_REPLY .....	460
26012 - LOG_ID_DHCPV6_RELEASE .....	461
27001 - LOG_ID_VRRP_STATE_CHG .....	462
29001 - LOG_ID_PPPD_MSG .....	462
29002 - LOG_ID_PPPD_AUTH_SUC .....	463
29003 - LOG_ID_PPPD_AUTH_FAIL .....	464
29010 - LOG_ID_PPPOE_STATUS_REPORT_NOTIF .....	465
29011 - LOG_ID_PPPD_FAIL_TO_EXEC .....	466
29012 - LOG_ID_PPP_OPT_ERR .....	466
29013 - LOG_ID_PPPD_START .....	467
29014 - LOG_ID_PPPD_EXIT .....	468
29015 - LOG_ID_PPP_RCV_BAD_PEER_IP .....	468
29016 - LOG_ID_PPP_RCV_BAD_LOCAL_IP .....	469
29017 - LOG_ID_PPP_OPT_NOTIF .....	470
29021 - LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED .....	470
29022 - LOG_ID_DDNS_UPDATE_FAIL .....	471
32001 - LOG_ID_ADMIN_LOGIN_SUCC .....	472
32002 - LOG_ID_ADMIN_LOGIN_FAIL .....	473
32003 - LOG_ID_ADMIN_LOGOUT .....	474
32005 - LOG_ID_ADMIN_OVERRIDE_VDOM .....	475
32006 - LOG_ID_ADMIN_ENTER_VDOM .....	476
32007 - LOG_ID_ADMIN_LEFT_VDOM .....	477
32008 - LOG_ID_VIEW_DISK_LOG_FAIL .....	478
32009 - LOG_ID_SYSTEM_START .....	478
32010 - LOG_ID_DISK_LOG_FULL .....	479
32011 - LOG_ID_LOG_ROLL .....	480
32014 - LOG_ID_CS_LIC_EXPIRE .....	480
32015 - LOG_ID_DISK_LOG_USAGE .....	481
32017 - LOG_ID_FDS_DAILY_QUOTA_FULL .....	482
32018 - LOG_ID_FIPS_ENTER_ERR_MOD .....	482
32019 - LOG_ID_CC_ENTER_ERR_MOD .....	483
32020 - LOG_ID_SSH_CORRPUT_MAC .....	484
32021 - LOG_ID_ADMIN_LOGIN_DISABLE .....	485
32022 - LOG_ID_VDOM_ENABLED .....	486
32023 - LOG_ID_MEM_LOG_FIRST_FULL .....	486
32024 - LOG_ID_ADMIN_PASSWD_EXPIRE .....	487
32025 - LOG_ID_SSH_REKEY .....	488
32026 - LOG_ID_SSH_BAD_PACKET_LENGTH .....	488
32027 - LOG_ID_VIEW_DISK_LOG_SUCC .....	489
32028 - LOG_ID_LOG_DEL_DIR .....	490

32029 - LOG_ID_LOG_DEL_FILE .....	491
32030 - LOG_ID_SEND_FDS_STAT .....	491
32031 - LOG_ID_VIEW_MEM_LOG_FAIL .....	492
32032 - LOG_ID_DISK_DLP_ARCH_FULL .....	493
32033 - LOG_ID_DISK_QUAR_FULL .....	494
32034 - LOG_ID_DISK_REPORT_FULL .....	494
32035 - LOG_ID_VDOM_DISABLED .....	495
32036 - LOG_ID_DISK_IPS_ARCH_FULL .....	496
32037 - LOG_ID_DISK_LOG_FIRST_FULL .....	496
32038 - LOG_ID_LOG_ROLL_FORTICRON .....	497
32039 - LOG_ID_VIEW_MEM_LOG_SUCC .....	498
32040 - LOG_ID_REPORT_DELETED .....	499
32041 - LOG_ID_REPORT_DELETED_GUI .....	499
32042 - LOG_ID_MEM_LOG_SECOND_FULL .....	500
32043 - LOG_ID_MEM_LOG_FINAL_FULL .....	501
32044 - LOG_ID_LOG_DELETE .....	501
32045 - LOG_ID_MGR_LIC_EXPIRE .....	502
32048 - LOG_ID_SCHEDULE_EXPIRE .....	503
32049 - LOG_ID_FC_EXPIRE .....	504
32050 - LOG_ID_POL_PKT_CAPTURE_FULL .....	504
32051 - LOG_ID_LOG_UPLOAD .....	505
32052 - LOG_ID_UPLOAD_RUN_SCRIPT .....	506
32053 - LOG_ID_ADMIN_MTNER_LOGIN_SUCC .....	506
32054 - LOG_ID_ADMIN_MTNER_LOGOUT .....	507
32057 - LOG_ID_VIEW_FAZ_LOG_FAIL .....	508
32058 - LOG_ID_VIEW_FAZ_LOG_SUCC .....	509
32095 - LOG_ID_GUI_CHG_SUB_MODULE .....	510
32097 - LOG_ID_DELETE_CAPTURE_PKT .....	511
32100 - LOG_ID_FORTI_TOKEN_SYNC .....	511
32102 - LOG_ID_CHG_CONFIG .....	512
32103 - LOG_ID_NEW_FIRMWARE .....	513
32104 - LOG_ID_CHG_CONFIG_GUI .....	514
32105 - LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE .....	515
32106 - LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE .....	515
32107 - LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE .....	516
32108 - LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE .....	517
32109 - LOG_ID_UPD_SIGN_AV_DB .....	518
32110 - LOG_ID_UPD_SIGN_IPS_DB .....	519
32111 - LOG_ID_UPD_SIGN_AVIPS_DB .....	519
32113 - LOG_ID_UPD_SIGN_SRCVIS_DB .....	520
32114 - LOG_ID_UPD_SIGN_GEOIP_DB .....	521
32116 - LOG_ID_UPD_SIGN_AVPKG_FAILURE .....	522
32117 - LOG_ID_UPD_SIGN_AVPKG_SUCCESS .....	522
32118 - LOG_ID_UPD_ADMIN_AV_DB .....	523
32119 - LOG_ID_UPD_SCANUNIT_AV_DB .....	524
32120 - LOG_ID_RPT_ADD_DATASET .....	525
32122 - LOG_ID_RPT_DEL_DATASET .....	526
32125 - LOG_ID_RPT_ADD_CHART .....	526
32126 - LOG_ID_RPT_DEL_CHART .....	527

32129 - LOG_ID_ADD_GUEST .....	528
32130 - LOG_ID_CHG_USER .....	529
32131 - LOG_ID_DEL_GUEST .....	530
32132 - LOG_ID_ADD_USER .....	530
32138 - LOG_ID_REBOOT .....	531
32139 - LOG_ID_WAKE_ON_LAN .....	532
32140 - LOG_ID_TIME_USER_SETTING_CHG .....	533
32141 - LOG_ID_TIME_NTP_SETTING_CHG .....	534
32142 - LOG_ID_BACKUP_CONF .....	534
32143 - LOG_ID_BACKUP_CONF_BY_SCP .....	535
32144 - LOG_ID_BACKUP_CONF_ERROR .....	536
32145 - LOG_ID_BACKUP_CONF_ALERT .....	537
32146 - LOG_ID_TIME_PTP_SETTING_CHG .....	537
32148 - LOG_ID_GET_CRL .....	538
32149 - LOG_ID_COMMAND_FAIL .....	539
32151 - LOG_ID_ADD_IP6_LOCAL_POL .....	540
32152 - LOG_ID_CHG_IP6_LOCAL_POL .....	541
32153 - LOG_ID_DEL_IP6_LOCAL_POL .....	541
32155 - LOG_ID_ACT_FTOKEN_REQ .....	542
32156 - LOG_ID_ACT_FTOKEN_SUCC .....	543
32157 - LOG_ID_SYNC_FTOKEN_SUCC .....	544
32158 - LOG_ID_SYNC_FTOKEN_FAIL .....	545
32159 - LOG_ID_ACT_FTOKEN_FAIL .....	545
32160 - LOG_ID_FTM_PUSH_SUCC .....	546
32161 - LOG_ID_FTM_PUSH_FAIL .....	547
32168 - LOG_ID_REACH_VDOM_LIMIT .....	547
32169 - LOG_ID_ALARM_DLP_DB .....	548
32170 - LOG_ID_ALARM_MSG .....	549
32171 - LOG_ID_ALARM_ACK .....	550
32172 - LOG_ID_ADD_IP4_LOCAL_POL .....	551
32173 - LOG_ID_CHG_IP4_LOCAL_POL .....	551
32174 - LOG_ID_DEL_IP4_LOCAL_POL .....	552
32190 - LOG_ID_UPT_INVALID_IMG .....	553
32191 - LOG_ID_UPT_INVALID_IMG_CC .....	554
32192 - LOG_ID_UPT_INVALID_IMG_RSA .....	554
32193 - LOG_ID_UPT_IMG_RSA .....	555
32194 - LOG_ID_UPT_IMG_FAIL .....	556
32199 - LOG_ID_RESTORE_IMG_USB .....	557
32200 - LOG_ID_SHUTDOWN .....	558
32201 - LOG_ID_LOAD_IMG_SUCC .....	558
32202 - LOG_ID_RESTORE_IMG .....	559
32203 - LOG_ID_RESTORE_CONF .....	560
32204 - LOG_ID_RESTORE_FGD_SVR .....	561
32205 - LOG_ID_RESTORE_VDOM_LIC .....	562
32206 - LOG_ID_RESTORE_SCRIPT .....	562
32207 - LOG_ID_RETRIEVE_CONF_LIST .....	563
32208 - LOG_ID_IMP_PKCS12_CERT .....	564
32209 - LOG_ID_RESTORE_USR_DEF_IPS .....	565
32210 - LOG_ID_BACKUP_IMG_SUCC .....	565

32211 - LOG_ID_UPLOAD_REVISION .....	566
32212 - LOG_ID_DEL_REVISION .....	567
32213 - LOG_ID_RESTORE_TEMPLATE .....	568
32214 - LOG_ID_RESTORE_FILE .....	569
32215 - LOG_ID_UPT_IMG .....	569
32217 - LOG_ID_UPD_IPS .....	570
32218 - LOG_ID_UPD_DLP .....	571
32219 - LOG_ID_BACKUP_OUTPUT .....	572
32220 - LOG_ID_BACKUP_COMMAND .....	573
32221 - LOG_ID_UPD_VDOM_LIC .....	573
32222 - LOG_ID_GLB_SETTING_CHG .....	574
32223 - LOG_ID_BACKUP_USER_DEF_IPS .....	575
32224 - LOG_ID_BACKUP_DISK_LOG .....	576
32225 - LOG_ID_DEL_ALL_REVISION .....	577
32226 - LOG_ID_LOAD_IMG_FAIL .....	577
32227 - LOG_ID_UPD_DLP_FAIL .....	578
32228 - LOG_ID_LOAD_IMG_FAIL_WRONG_IMG .....	579
32229 - LOG_ID_LOAD_IMG_FAIL_NO_RSA .....	580
32230 - LOG_ID_LOAD_IMG_FAIL_INVALID_RSA .....	581
32231 - LOG_ID_RESTORE_FGD_SVR_FAIL .....	581
32232 - LOG_ID_RESTORE_VDOM_LIC_FAIL .....	582
32233 - LOG_ID_BACKUP_IMG_FAIL .....	583
32234 - LOG_ID_RESTORE_IMG_INVALID_CC .....	584
32235 - LOG_ID_RESTORE_IMG_FORTIGUARD .....	584
32236 - LOG_ID_BACKUP_MEM_LOG .....	585
32237 - LOG_ID_BACKUP_MEM_LOG_FAIL .....	586
32238 - LOG_ID_BACKUP_DISK_LOG_FAIL .....	587
32239 - LOG_ID_BACKUP_DISK_LOG_USB .....	588
32240 - LOG_ID_SYS_USB_MODE .....	588
32241 - LOG_ID_BACKUP_DISK_LOG_USB_FAIL .....	589
32242 - LOG_ID_UPD_VDOM_LIC_FAIL .....	590
32243 - LOG_ID_UPD_IPS_SCP .....	591
32244 - LOG_ID_UPD_IPS_SCP_FAIL .....	591
32245 - LOG_ID_BACKUP_USER_DEF_IPS_FAIL .....	592
32246 - LOG_ID_RESTORE_USR_DEF_IPS_CRITICAL .....	593
32247 - LOG_ID_SSH_NEGOTIATION_FAILURE .....	594
32252 - LOG_ID_FACTORY_RESET .....	595
32253 - LOG_ID_FORMAT_RAID .....	595
32254 - LOG_ID_ENABLE_RAID .....	596
32255 - LOG_ID_DISABLE_RAID .....	597
32300 - LOG_ID_UPLOAD_RPT_IMG .....	598
32301 - LOG_ID_ADD_VDOM .....	599
32302 - LOG_ID_DEL_VDOM .....	599
32545 - LOG_ID_SYS_RESTART .....	600
32546 - LOG_ID_APPLICATION_CRASH .....	601
32547 - LOG_ID_AUTOSCRIPT_START .....	602
32548 - LOG_ID_AUTOSCRIPT_STOP .....	602
32549 - LOG_ID_AUTOSCRIPT_STOP_AUTO .....	603
32550 - LOG_ID_AUTOSCRIPT_DELETE_RSLT .....	604

32551 - LOG_ID_AUTOSCRIPRT_BACKUP_RSLT .....	605
32552 - LOG_ID_AUTOSCRIPRT_CHECK_STATUS .....	605
32553 - LOG_ID_AUTOSCRIPRT_STOP_REACH_LIMIT .....	606
32561 - LOG_ID_ADMIN_LOGOUT_DISCONNECT .....	607
32562 - LOG_ID_STORE_CONF_FAIL_SPACE .....	608
32564 - LOG_ID_RESTORE_CONF_FAIL .....	609
32565 - LOG_ID_RESTORE_CONF_BY_MGMT .....	609
32566 - LOG_ID_RESTORE_CONF_BY_SCP .....	610
32567 - LOG_ID_RESTORE_CONF_BY_USB .....	611
32568 - LOG_ID_DEL_REVISION_DB .....	612
32569 - LOG_ID_FSW_SWITCH_LOG_EVENT .....	612
32570 - LOG_ID_ADMIN_MTNER_LOGOUT_DISCONNECT .....	613
32601 - LOG_ID_FGT_SWITCH_LOG_DISCOVER .....	614
32602 - LOG_ID_FGT_SWITCH_LOG_AUTH .....	615
32603 - LOG_ID_FGT_SWITCH_LOG_DEAUTH .....	616
32604 - LOG_ID_FGT_SWITCH_LOG_DELETE .....	617
32605 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_UP .....	617
32606 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_DOWN .....	618
32607 - LOG_ID_FGT_SWITCH_PUSH_IMAGE .....	619
32608 - LOG_ID_FGT_SWITCH_STAGE_IMAGE .....	620
32609 - LOG_ID_FGT_SWITCH_DISABLE_DISCOVERY .....	620
32610 - LOG_ID_FGT_SWITCH_LOG_WARNING .....	621
32611 - LOG_ID_FGT_SWITCH_EXPORT_POOL .....	622
32612 - LOG_ID_FGT_SWITCH_EXPORT_VDOM .....	623
32613 - LOG_ID_FGT_SWITCH_REQUEST_PORT .....	623
32614 - LOG_ID_FGT_SWITCH_RETURN_PORT .....	624
32615 - LOG_ID_FGT_SWITCH_MAC_ADD .....	625
32616 - LOG_ID_FGT_SWITCH_MAC_DEL .....	626
32617 - LOG_ID_FGT_SWITCH_MAC_MOVE .....	626
32693 - LOG_ID_FGT_SWITCH_GROUP_SWC .....	627
32694 - LOG_ID_FGT_SWITCH_GROUP_POE .....	628
32695 - LOG_ID_FGT_SWITCH_GROUP_LINK .....	629
32696 - LOG_ID_FGT_SWITCH_GROUP_STP .....	630
32697 - LOG_ID_FGT_SWITCH_GROUP_SWITCH .....	631
32698 - LOG_ID_FGT_SWITCH_GROUP_ROUTER .....	632
32699 - LOG_ID_FGT_SWITCH_GROUP_SYSTEM .....	632
32700 - LOG_ID_DPDK_EARLY_INIT_FAIL .....	633
34415 - LOG_ID_NP6_IPSEC_ENGINE_BUSY .....	634
34416 - LOG_ID_NP6_IPSEC_ENGINE_POSSIBLY_LOCKUP .....	635
34417 - LOG_ID_NP6_IPSEC_ENGINE_LOCKUP .....	635
35001 - LOG_ID_HA_SYNC_VIRDB .....	636
35002 - LOG_ID_HA_SYNC_ETDB .....	637
35003 - LOG_ID_HA_SYNC_EXDB .....	637
35004 - LOG_ID_HA_SYNC_FLDB .....	638
35005 - LOG_ID_HA_SYNC_IPS .....	639
35007 - LOG_ID_HA_SYNC_AV .....	639
35009 - LOG_ID_HA_SYNC_CID .....	640
35011 - LOG_ID_HA_SYNC_FAIL .....	641
35012 - LOG_ID_CONF_SYNC_FAIL .....	641

35013 - LOG_ID_HA_FAILOVER_FAIL .....	642
35014 - LOG_ID_HA_RESET_UPTIME .....	643
35015 - LOG_ID_HA_CLEAR_HISTORY .....	643
36881 - LOG_ID_EVENT_SYSTEM_CFG_REVERT .....	644
36882 - LOG_ID_EVENT_SYSTEM_CFG_MANUALLY_SAVED .....	645
37120 - MESSAGESID_NEG_GENERIC_P1_NOTIF .....	645
37121 - MESSAGESID_NEG_GENERIC_P1_ERROR .....	647
37122 - MESSAGESID_NEG_GENERIC_P2_NOTIF .....	648
37123 - MESSAGESID_NEG_GENERIC_P2_ERROR .....	649
37124 - MESSAGESID_NEG_I_P1_ERROR .....	650
37125 - MESSAGESID_NEG_I_P2_ERROR .....	652
37126 - MESSAGESID_NEG_NO_STATE_ERROR .....	653
37127 - MESSAGESID_NEG_PROGRESS_P1_NOTIF .....	654
37128 - MESSAGESID_NEG_PROGRESS_P1_ERROR .....	655
37129 - MESSAGESID_NEG_PROGRESS_P2_NOTIF .....	657
37130 - MESSAGESID_NEG_PROGRESS_P2_ERROR .....	658
37131 - MESSAGESID_ESP_ERROR .....	660
37132 - MESSAGESID_ESP_CRITICAL .....	661
37133 - MESSAGESID_INSTALL_SA .....	662
37134 - MESSAGESID_DELETE_P1_SA .....	663
37135 - MESSAGESID_DELETE_P2_SA .....	664
37136 - MESSAGESID_DPD_FAILURE .....	665
37137 - MESSAGESID_CONN_FAILURE .....	667
37138 - MESSAGESID_CONN_UPDOWN .....	668
37139 - MESSAGESID_P2_UPDOWN .....	669
37141 - MESSAGESID_CONN_STATS .....	670
37889 - MESSAGESID_VC_DELETE .....	672
37890 - MESSAGESID_VC_MOVE_VDOM .....	672
37891 - MESSAGESID_VC_ADD_VDOM .....	673
37892 - MESSAGESID_VC_MOVE_MEMB_STATE .....	674
37893 - MESSAGESID_VC_DETECT_MEMB_DEAD .....	675
37894 - MESSAGESID_VC_DETECT_MEMB_JOIN .....	675
37895 - MESSAGESID_VC_ADD_HADEV .....	676
37896 - MESSAGESID_VC_DEL_HADEV .....	677
37897 - MESSAGESID_HADEV_READY .....	678
37898 - MESSAGESID_HADEV_FAIL .....	678
37899 - MESSAGESID_HADEV_PEERINFO .....	679
37900 - MESSAGESID_HBDEV_DELETE .....	680
37901 - MESSAGESID_HBDEV_DOWN .....	681
37902 - MESSAGESID_HBDEV_UP .....	681
37903 - MESSAGESID_SYNC_STATUS .....	682
37904 - MESSAGESID_HA_ACTIVITY .....	683
37907 - MESSAGESID_VLAN_HB_UP .....	684
37908 - MESSAGESID_VLAN_HB_DOWN .....	684
37909 - MESSAGESID_VLAN_HB_DOWN_SUM .....	685
38010 - LOG_ID_FIPS_ENCRY_FAIL .....	686
38011 - LOG_ID_FIPS_DECRY_FAIL .....	686
38012 - LOG_ID_ENTROPY_TOKEN .....	687
38031 - LOG_ID_FSSO_LOGON .....	688



38032 - LOG_ID_FSSO_LOGOFF .....	689
38033 - LOG_ID_FSSO_SVR_STATUS .....	690
38400 - LOGID_EVENT_NOTIF_SEND_SUCC .....	690
38401 - LOGID_EVENT_NOTIF_SEND_FAIL .....	692
38402 - LOGID_EVENT_NOTIF_DNS_FAIL .....	693
38403 - LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE .....	694
38404 - LOGID_EVENT_NOTIF_HOSTNAME_ERROR .....	694
38405 - LOGID_NOTIF_CODE_SENDTO_SMS_PHONE .....	695
38406 - LOGID_NOTIF_CODE_SENDTO_SMS_TO .....	696
38407 - LOGID_NOTIF_CODE_SENDTO_EMAIL .....	696
38408 - LOGID_EVENT_OFTP_SSL_CONNECTED .....	697
38409 - LOGID_EVENT_OFTP_SSL_DISCONNECTED .....	698
38410 - LOGID_EVENT_OFTP_SSL_FAILED .....	699
38411 - LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO .....	700
38412 - LOGID_EVENT_TOKEN_CODE_SENDTO .....	700
38656 - LOGID_EVENT_RAD_RPT_PROTO_ERROR .....	701
38657 - LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND .....	702
38658 - LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND .....	703
38659 - LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED .....	703
38660 - LOGID_EVENT_RAD_RPT_ACCT_EVENT .....	704
38661 - LOGID_EVENT_RAD_RPT_OTHER .....	705
38662 - LOGID_EVENT_RAD_STAT_PROTO_ERROR .....	706
38663 - LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND .....	707
38665 - LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED .....	707
38666 - LOGID_EVENT_RAD_STAT_ACCT_EVENT .....	708
38667 - LOGID_EVENT_RAD_STAT_OTHER .....	709
38668 - LOGID_EVENT_RAD_STAT_EP_BLK .....	710
39424 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP .....	711
39425 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN .....	712
39426 - LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL .....	713
39936 - LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS .....	714
39937 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY .....	715
39938 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS .....	716
39939 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT .....	717
39940 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE .....	718
39941 - LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY .....	719
39942 - LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK .....	720
39943 - LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON .....	721
39944 - LOG_ID_EVENT_SSL_VPN_SESSION_ALERT .....	722
39945 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL .....	722
39946 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR .....	723
39947 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP .....	724
39948 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN .....	725
39949 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS .....	726
39950 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG .....	727
39951 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR .....	728
39952 - LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE .....	729
39953 - LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE .....	730
40001 - LOG_ID_PPTP_TUNNEL_UP .....	731

40002 - LOG_ID_PPTP_TUNNEL_DOWN .....	732
40003 - LOG_ID_PPTP_TUNNEL_STAT .....	733
40014 - LOG_ID_PPTP_REACH_MAX_CON .....	734
40017 - LOG_ID_L2TPD_CLIENT_CON_FAIL .....	735
40019 - LOG_ID_L2TPD_CLIENT_DISCON .....	735
40021 - LOG_ID_PPTP_NOT_CONIG .....	736
40022 - LOG_ID_PPTP_NO_IP_AVAIL .....	737
40024 - LOG_ID_PPTP_OUT_MEM .....	738
40034 - LOG_ID_PPTP_START .....	738
40035 - LOG_ID_PPTP_START_FAIL .....	739
40036 - LOG_ID_PPTP_EXIT .....	740
40037 - LOG_ID_PPTPD_SVR_DISCON .....	741
40038 - LOG_ID_PPTPD_CLIENT_CON .....	742
40039 - LOG_ID_PPTPD_CLIENT_DISCON .....	742
40101 - LOG_ID_L2TP_TUNNEL_UP .....	743
40102 - LOG_ID_L2TP_TUNNEL_DOWN .....	744
40103 - LOG_ID_L2TP_TUNNEL_STAT .....	745
40114 - LOG_ID_L2TPD_START .....	746
40115 - LOG_ID_L2TPD_EXIT .....	747
40118 - LOG_ID_L2TPD_CLIENT_CON .....	747
40704 - LOG_ID_EVENT_SYS_PERF .....	748
40705 - LOG_ID_EVENT_SYS_CPU_USAGE .....	749
40960 - LOG_ID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR .....	750
41000 - LOG_ID_UPD_FGT_SUCC .....	751
41001 - LOG_ID_UPD_FGT_FAIL .....	751
41002 - LOG_ID_UPD_SRC_VIS .....	752
41006 - LOG_ID_UPD_FSA_VIRDB .....	753
41984 - LOG_ID_EVENT_VPN_CERT_LOAD .....	754
41985 - LOG_ID_EVENT_VPN_CERT_REMOVAL .....	755
41986 - LOG_ID_EVENT_VPN_CERT_REGEN .....	755
41987 - LOG_ID_EVENT_VPN_CERT_UPDATE .....	756
41988 - LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE .....	757
41989 - LOG_ID_EVENT_VPN_CERT_ERR .....	758
41990 - LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED .....	759
41991 - LOG_ID_EVENT_VPN_CERT_EXPORT .....	760
42201 - LOG_ID_NETX_VMX_ATTACH .....	761
42202 - LOG_ID_NETX_VMX_DETACH .....	761
42203 - LOG_ID_NETX_VMX_DENIED .....	762
43008 - LOG_ID_EVENT_AUTH_SUCCESS .....	763
43009 - LOG_ID_EVENT_AUTH_FAILED .....	764
43010 - LOG_ID_EVENT_AUTH_LOCKOUT .....	765
43011 - LOG_ID_EVENT_AUTH_TIME_OUT .....	766
43014 - LOG_ID_EVENT_AUTH_FSAE_LOGON .....	767
43015 - LOG_ID_EVENT_AUTH_FSAE_LOGOFF .....	767
43016 - LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS .....	768
43017 - LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL .....	769
43018 - LOG_ID_EVENT_AUTH_FGOVRD_FAIL .....	770
43020 - LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS .....	771
43025 - LOG_ID_EVENT_AUTH_PROXY_SUCCESS .....	772

43026 - LOG_ID_EVENT_AUTH_PROXY_FAILED .....	773
43027 - LOG_ID_EVENT_AUTH_PROXY_TIME_OUT .....	774
43028 - LOG_ID_EVENT_AUTH_PROXY_GROUP_INFO_FAILED .....	775
43029 - LOG_ID_EVENT_AUTH_WARNING_SUCCESS .....	776
43030 - LOG_ID_EVENT_AUTH_WARNING_TBL_FULL .....	777
43032 - LOG_ID_EVENT_AUTH_PROXY_USER_LIMIT_REACHED .....	778
43033 - LOG_ID_EVENT_AUTH_PROXY_MULTIPLE_LOGIN .....	779
43034 - LOG_ID_EVENT_AUTH_PROXY_NO_RESP .....	780
43037 - LOG_ID_EVENT_AUTH_IPV4_FLUSH .....	781
43038 - LOG_ID_EVENT_AUTH_IPV6_FLUSH .....	782
43039 - LOG_ID_EVENT_AUTH_LOGON .....	782
43040 - LOG_ID_EVENT_AUTH_LOGOUT .....	783
43041 - LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT .....	784
43042 - LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE .....	785
43043 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS .....	786
43044 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL .....	787
43045 - LOG_ID_EVENT_AUTH_8021X_SUCCESS .....	788
43046 - LOG_ID_EVENT_AUTH_8021X_FAIL .....	789
43050 - LOG_ID_EVENT_AUTH_FSAE_CONNECT .....	790
43051 - LOG_ID_EVENT_AUTH_FSAE_DISCONNECT .....	791
43264 - LOGID_MMS_STATS .....	791
43520 - LOG_ID_EVENT_WIRELESS_SYS .....	792
43521 - LOG_ID_EVENT_WIRELESS_ROGUE .....	793
43522 - LOG_ID_EVENT_WIRELESS_WTP .....	794
43524 - LOG_ID_EVENT_WIRELESS_STA .....	795
43525 - LOG_ID_EVENT_WIRELESS_ONWIRE .....	797
43526 - LOG_ID_EVENT_WIRELESS_WTPR .....	798
43527 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG .....	799
43528 - LOG_ID_EVENT_WIRELESS_WTPR_ERROR .....	800
43529 - LOG_ID_EVENT_WIRELESS_CLB .....	801
43530 - LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE .....	802
43531 - LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH .....	803
43532 - LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP .....	804
43533 - LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI .....	805
43534 - LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR .....	807
43535 - LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV .....	808
43542 - LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD .....	809
43544 - LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD .....	810
43546 - LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH .....	811
43548 - LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP .....	812
43550 - LOG_ID_EVENT_WIRELESS_STA_LOCATE .....	813
43551 - LOG_ID_EVENT_WIRELESS_WTP_JOIN .....	814
43552 - LOG_ID_EVENT_WIRELESS_WTP_LEAVE .....	815
43553 - LOG_ID_EVENT_WIRELESS_WTP_FAIL .....	816
43554 - LOG_ID_EVENT_WIRELESS_WTP_UPDATE .....	817
43555 - LOG_ID_EVENT_WIRELESS_WTP_RESET .....	818
43556 - LOG_ID_EVENT_WIRELESS_WTP_KICK .....	819
43557 - LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE .....	820
43558 - LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR .....	821

43559 - LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH .....	822
43560 - LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED .....	823
43561 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP .....	824
43562 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN .....	824
43563 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT .....	825
43564 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR .....	827
43565 - LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR .....	828
43566 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE .....	829
43567 - LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT .....	831
43568 - LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR .....	832
43569 - LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED .....	834
43570 - LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED .....	835
43571 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG .....	837
43572 - LOG_ID_EVENT_WIRELESS_STA ASSO .....	838
43573 - LOG_ID_EVENT_WIRELESS_STA_AUTH .....	839
43574 - LOG_ID_EVENT_WIRELESS_STA_DASS .....	841
43575 - LOG_ID_EVENT_WIRELESS_STA_DAUT .....	842
43576 - LOG_ID_EVENT_WIRELESS_STA_IDLE .....	843
43577 - LOG_ID_EVENT_WIRELESS_STA_DENY .....	844
43578 - LOG_ID_EVENT_WIRELESS_STA_KICK .....	846
43579 - LOG_ID_EVENT_WIRELESS_STA_IP .....	847
43580 - LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP .....	848
43581 - LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN .....	849
43582 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED .....	850
43583 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED .....	851
43584 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE .....	852
43585 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED .....	853
43586 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN .....	854
43587 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START .....	855
43588 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN .....	856
43589 - LOG_ID_EVENT_WIRELESS_WTPR_RADAR .....	857
43590 - LOG_ID_EVENT_WIRELESS_WTPR_NOL .....	858
43591 - LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS .....	859
43592 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY .....	860
43593 - LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER .....	861
43594 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER .....	862
43595 - LOG_ID_EVENT_WIRELESS_CLB_DENY .....	863
43596 - LOG_ID_EVENT_WIRELESS_CLB_RETRY .....	864
43597 - LOG_ID_EVENT_WIRELESS_WTP_ADD .....	865
43598 - LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS .....	866
43599 - LOG_ID_EVENT_WIRELESS_WTP_DEL .....	867
43600 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP .....	868
43601 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON .....	869
43602 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS .....	870
43603 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE .....	872
43604 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST .....	873
43605 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS .....	874
43606 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE .....	875
43607 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK .....	876

43608 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE .....	878
43609 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_OPTIMIZATION_START ..	879
43610 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_OPTIMIZATION_STOP ...	880
43611 - LOG_ID_EVENT_WIRELESS_SYS_AC_UP .....	881
43612 - LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED .....	882
43613 - LOG_ID_EVENT_WIRELESS_WTP_ERR .....	882
43614 - LOG_ID_EVENT_WIRELESS_DHCP_STAVATION .....	883
43615 - LOG_ID_EVENT_WIRELESS_SYS_AC_IPSEC_FAIL .....	884
43616 - LOG_ID_EVENT_WIRELESS_WTPR_NOL_ADD .....	885
43618 - LOG_ID_EVENT_WIRELESS_WTP_IMAGE_RC_SUCCESS .....	886
43619 - LOG_ID_EVENT_WIRELESS_OFFENDINGAP_DETECT .....	887
43620 - LOG_ID_EVENT_WIRELESS_OFFENDINGAP_ONAIR .....	888
43621 - LOG_ID_EVENT_WIRELESS_WTP_DATA_CHAN_CHG .....	890
43622 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_PROBE .....	891
43623 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_MISSING .....	892
43624 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_DETECTED .....	893
43625 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_SUCCESS .....	894
43626 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_FAILURE .....	895
43627 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_TIMEOUT .....	896
43628 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_MAC_AUTH_	
SUCCESS .....	897
43629 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_FAILURE .....	899
43630 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_SUCCESS .....	900
43631 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_NO_RESP .....	901
43632 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_FAILURE .....	902
43633 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_SUCCESS ...	903
43634 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_NO_RESP ...	904
43635 - LOG_ID_EVENT_WIRELESS_STA_OKC_NO_MATCH .....	905
43636 - LOG_ID_EVENT_WIRELESS_STA_OKC_LOCAL_MATCH .....	906
43637 - LOG_ID_EVENT_WIRELESS_STA_OKC_INTER_AC_MATCH .....	907
43638 - LOG_ID_EVENT_WIRELESS_STA_OKC_INTER_AP_MATCH .....	908
43639 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_ACTION_REQ .....	910
43640 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_AUTH_REQ .....	911
43641 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_REASSOC_REQ .....	912
43642 - LOG_ID_EVENT_WIRELESS_STA_FT_ACTION_REQ .....	913
43643 - LOG_ID_EVENT_WIRELESS_STA_FT_ACTION_RESP .....	914
43644 - LOG_ID_EVENT_WIRELESS_STA_FT_AUTH_REQ .....	915
43645 - LOG_ID_EVENT_WIRELESS_STA_FT_AUTH_RESP .....	916
43646 - LOG_ID_EVENT_WIRELESS_STA_FT_REASSOC_REQ .....	917
43647 - LOG_ID_EVENT_WIRELESS_STA_FT_REASSOC_RESP .....	918
43648 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_SECOND_	
MSG .....	919
43649 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_FOURTH_	
MSG .....	921
43650 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FIRST_MSG .....	922
43651 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_SECOND_MSG .....	923
43652 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_THIRD_MSG .....	924
43653 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FOURTH_MSG .....	925
43654 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FIRST_GROUP_MSG ...	926

43655 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_SECOND_GROUP_MSG	927
43656 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_MAX_STA_CNT	928
43657 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_FAIL	929
43658 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NO_RESP	930
43659 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DIFF_OFFER	931
43660 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NO_ACK	932
43661 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NAK	933
43662 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DUP_IP	934
43663 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DISCOVER	935
43664 - LOG_ID_EVENT_WIRELESS_STA_DHCP_OFFER	936
43665 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DECLINE	937
43666 - LOG_ID_EVENT_WIRELESS_STA_DHCP_REQUEST	938
43667 - LOG_ID_EVENT_WIRELESS_STA_DHCP_ACK	939
43668 - LOG_ID_EVENT_WIRELESS_STA_DHCP_RELEASE	940
43669 - LOG_ID_EVENT_WIRELESS_STA_DHCP_INFORM	941
43670 - LOG_ID_EVENT_WIRELESS_STA_DHCP_SELF_ASSIGNED	942
43671 - LOG_ID_EVENT_WIRELESS_STA_DNS_NO_RESP	943
43672 - LOG_ID_EVENT_WIRELESS_STA_DNS_SERVER_FAILURE	944
43673 - LOG_ID_EVENT_WIRELESS_STA_DNS_NO_DOMAIN	945
43674 - LOG_ID_EVENT_WIRELESS_STA_WPA_KRACK_FT_REASSOC	946
43675 - LOG_ID_EVENT_WIRELESS_STA_AUTH_REQ	947
43676 - LOG_ID_EVENT_WIRELESS_STA_AUTH_RESP	948
43677 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_REQ	949
43678 - LOG_ID_EVENT_WIRELESS_STA_REASSOC_REQ	951
43679 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_RESP	952
43680 - LOG_ID_EVENT_WIRELESS_STA_REASSOC_RESP	953
43681 - LOG_ID_EVENT_WIRELESS_STA_PROBE_REQ	954
43682 - LOG_ID_EVENT_WIRELESS_STA_PROBE_RESP	955
43683 - LOG_ID_EVENT_WIRELESS_BLE_DEV_LOCATE	956
43684 - LOG_ID_EVENT_WIRELESS_ADDRGRP_DUPLICATE_MAC	957
43685 - LOG_ID_EVENT_WIRELESS_ADDRGRP_ADDR_APPLY	958
43686 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_SCHEDULE	959
43687 - LOG_ID_EVENT_WIRELESS_STA_WL_BRIDGE_TRAFFIC_STATS	960
43776 - LOG_ID_EVENT_NAC_QUARANTINE	961
43777 - LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE	962
43800 - LOG_ID_EVENT_ELBC_BLADE_JOIN	963
43801 - LOG_ID_EVENT_ELBC_BLADE_LEAVE	964
43802 - LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND	965
43803 - LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST	966
43804 - LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE	967
43805 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND	967
43806 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST	968
43807 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE	969
43808 - LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE	970
43809 - LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE	971
44544 - LOGID_EVENT_CONFIG_PATH	972
44545 - LOGID_EVENT_CONFIG_OBJ	972
44546 - LOGID_EVENT_CONFIG_ATTR	973
44547 - LOGID_EVENT_CONFIG_OBJATTR	974

44548 - LOGID_EVENT_CONFIG_EXEC .....	975
44549 - LOGID_EVENT_CONFIG_OBJATTR_MTNER .....	976
44550 - LOGID_EVENT_CONFIG_OBJ_MTNER .....	977
44551 - LOGID_EVENT_CONFIG_ATTR_MTNER .....	978
44552 - LOGID_EVENT_CONFIG_PATH_MTNER .....	979
44553 - LOGID_EVENT_CONFIG_FIXEDPORT_DIS .....	979
44554 - LOGID_EVENT_CONFIG_POL_CHANGED .....	980
44555 - LOGID_EVENT_CMDB_DEADLOCK_DETECTED .....	981
45057 - LOG_ID_FCC_ADD .....	982
45058 - LOG_ID_FCC_CLOSE .....	983
45061 - LOG_ID_FCC_CLOSE_BY_TYPE .....	983
45071 - LOG_ID_FCC_VULN_SCAN .....	984
45109 - LOG_ID_EC_FTCL_LOGOFF .....	985
45114 - LOG_ID_EC_REG_QUARANTINE .....	986
45115 - LOG_ID_EC_REG_UNQUARANTINE .....	987
45119 - LOG_ID_EC_FTCL_DISCONN .....	988
46000 - LOG_ID_VIP_REAL_SVR_ENA .....	989
46001 - LOG_ID_VIP_REAL_SVR_DISA .....	990
46002 - LOG_ID_VIP_REAL_SVR_UP .....	990
46003 - LOG_ID_VIP_REAL_SVR_DOWN .....	991
46004 - LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN .....	992
46005 - LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN .....	993
46006 - LOG_ID_VIP_REAL_SVR_FAIL .....	994
46400 - LOG_ID_EVENT_EXT_SYS .....	995
46401 - LOG_ID_EVENT_EXT_LOCAL .....	995
46402 - LOG_ID_EVENT_EXT_LOCAL_ERROR .....	996
46403 - LOG_ID_EVENT_EXT_REMOTE_EMERG .....	997
46404 - LOG_ID_EVENT_EXT_REMOTE_ALERT .....	997
46405 - LOG_ID_EVENT_EXT_REMOTE_CRITICAL .....	998
46406 - LOG_ID_EVENT_EXT_REMOTE_ERROR .....	999
46407 - LOG_ID_EVENT_EXT_REMOTE_WARNING .....	1000
46408 - LOG_ID_EVENT_EXT_REMOTE_NOTIF .....	1000
46409 - LOG_ID_EVENT_EXT_REMOTE_INFO .....	1001
46410 - LOG_ID_EVENT_EXT_REMOTE_DEBUG .....	1002
46501 - LOG_ID_INTERNAL_LTE_MODEM_DETECTION .....	1003
46502 - LOG_ID_INTERNAL_LTE_MODEM_GPSD .....	1003
46503 - LOG_ID_INTERNAL_LTE_MODEM_GPS_LOC_ACQUISITION .....	1004
46504 - LOG_ID_INTERNAL_LTE_MODEM_BILLD .....	1005
46505 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_PURGED .....	1005
46506 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_DAILY_LOG .....	1006
46507 - LOG_ID_INTERNAL_LTE_MODEM_FW_UPGRADE .....	1007
46508 - LOG_ID_INTERNAL_LTE_MODEM_QDL_DETECTION .....	1007
46509 - LOG_ID_INTERNAL_LTE_MODEM_REBOOT .....	1008
46510 - LOG_ID_INTERNAL_LTE_MODEM_OP_MODE .....	1009
46511 - LOG_ID_INTERNAL_LTE_MODEM_POWER_ON_OFF .....	1009
46512 - LOG_ID_INTERNAL_LTE_MODEM_SIM_STATE .....	1010
46513 - LOG_ID_INTERNAL_LTE_MODEM_LINK_CONNECTION .....	1011
46514 - LOG_ID_INTERNAL_LTE_MODEM_MANUAL_HANDOVER .....	1011
46515 - LOG_ID_INTERNAL_LTE_MODEM_IP_ADDR .....	1012

46600 - LOG_ID_EVENT_AUTOMATION_TRIGGERED .....	1013
46900 - LOG_ID_POE_STATUS_REPORT .....	1013
47000 - LOG_ID_MALWARE_LIST_TRUNCATED_ENTER .....	1014
47001 - LOG_ID_MALWARE_LIST_TRUNCATED_EXIT .....	1015
47203 - LOG_ID_ENTER_BYPASS .....	1015
47204 - LOG_ID_EXIT_BYPASS .....	1016
48000 - LOG_ID_WAD_SSL_RCV_HS .....	1017
48001 - LOG_ID_WAD_SSL_RCV_WRG_HS .....	1018
48002 - LOG_ID_WAD_SSL_SENT_HS .....	1019
48003 - LOG_ID_WAD_SSL_WRG_HS_LEN .....	1019
48004 - LOG_ID_WAD_SSL_RCV_CCS .....	1020
48005 - LOG_ID_WAD_SSL_RSA_DH_FAIL .....	1021
48006 - LOG_ID_WAD_SSL_SENT_CCS .....	1022
48007 - LOG_ID_WAD_SSL_BAD_HASH .....	1023
48009 - LOG_ID_WAD_SSL_DECRY_FAIL .....	1024
48011 - LOG_ID_WAD_SSL_LESS_MINOR .....	1025
48013 - LOG_ID_WAD_SSL_NOT_SUPPORT_CS .....	1026
48016 - LOG_ID_WAD_SSL_HS_FIN .....	1027
48017 - LOG_ID_WAD_SSL_HS_TOO_LONG .....	1028
48019 - LOG_ID_WAD_SSL_SENT_ALERT .....	1029
48023 - LOG_ID_WAD_SSL_RCV_ALERT .....	1030
48027 - LOG_ID_WAD_SSL_INVALID_CONT_TYPE .....	1031
48029 - LOG_ID_WAD_SSL_BAD_CCS_LEN .....	1032
48031 - LOG_ID_WAD_SSL_BAD_DH .....	1033
48032 - LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG .....	1034
48034 - LOG_ID_WAD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH ..	1034
48035 - LOG_ID_WAD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_	
MISMATCH .....	1035
48038 - LOG_ID_WAD_SSL_RCV_FATAL_ALERT .....	1036
48039 - LOG_ID_WAD_SSL_SENT_FATAL_ALERT .....	1037
48101 - LOG_ID_WAD_AUTH_FAIL_PSK .....	1038
48102 - LOG_ID_WAD_AUTH_FAIL_OTH .....	1039
48300 - LOG_ID_WRG_SVR_FGT_CONF .....	1040
48301 - LOG_ID_UNEXP_APP_TYPE .....	1041
51000 - LOG_ID_NB_TBL_CHG .....	1042
52000 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_SUMMARY .....	1043
52001 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_CHANGE .....	1044
53000 - LOG_ID_SDNC_CONNECTED .....	1045
53001 - LOG_ID_SDNC_DISCONNECTED .....	1046
53002 - LOG_ID_SDNC_SUBSCRIBE .....	1046
53003 - LOG_ID_SDNC_UNSUBSCRIBE .....	1047
53100 - LOG_ID_VPN_OCVPN_REGISTERED .....	1048
53101 - LOG_ID_VPN_OCVPN_UNREGISTERED .....	1048
53102 - LOG_ID_VPN_OCVPN_COMM_ESTABLISHED .....	1049
53103 - LOG_ID_VPN_OCVPN_COMM_ERROR .....	1050
53104 - LOG_ID_VPN_OCVPN_DNS_ERROR .....	1050
53105 - LOG_ID_VPN_OCVPN_ROUTE_ERROR .....	1051
53200 - LOG_ID_CONNECTOR_OBJECT_ADD .....	1052
53201 - LOG_ID_CONNECTOR_OBJECT_REMOVE .....	1053



FILE-FILTER .....	1054
64000 - LOG_ID_FILE_FILTER_BLOCK .....	1054
64001 - LOG_ID_FILE_FILTER_LOG .....	1056
GTP .....	1058
41216 - LOGID_GTP_FORWARD .....	1058
41217 - LOGID_GTP_DENY .....	1060
41218 - LOGID_GTP_RATE_LIMIT .....	1061
41219 - LOGID_GTP_STATE_INVALID .....	1063
41220 - LOGID_GTP_TUNNEL_LIMIT .....	1064
41221 - LOGID_GTP_TRAFFIC_COUNT .....	1066
41222 - LOGID_GTP_USER_DATA .....	1068
41223 - LOGID_GTPV2_FORWARD .....	1069
41224 - LOGID_GTPV2_DENY .....	1070
41225 - LOGID_GTPV2_RATE_LIMIT .....	1072
41226 - LOGID_GTPV2_STATE_INVALID .....	1073
41227 - LOGID_GTPV2_TUNNEL_LIMIT .....	1075
41228 - LOGID_GTPV2_TRAFFIC_COUNT .....	1076
41229 - LOGID_GTPU_FORWARD .....	1078
41230 - LOGID_GTPU_DENY .....	1079
IPS .....	1080
16384 - LOGID_ATTCK_SIGNATURE_TCP_UDP .....	1080
16385 - LOGID_ATTCK_SIGNATURE_ICMP .....	1082
16386 - LOGID_ATTCK_SIGNATURE_OTHERS .....	1084
16399 - LOGID_ATTACK_MALICIOUS_URL .....	1086
16400 - LOGID_ATTACK_BOTNET_WARNING .....	1088
16401 - LOGID_ATTACK_BOTNET_NOTIF .....	1090
SSH .....	1092
61000 - LOG_ID_SSH_COMMAND_BLOCK .....	1092
61001 - LOG_ID_SSH_COMMAND_BLOCK_ALERT .....	1093
61002 - LOG_ID_SSH_COMMAND_PASS .....	1095
61003 - LOG_ID_SSH_COMMAND_PASS_ALERT .....	1096
61010 - LOG_ID_SSH_CHANNEL_BLOCK .....	1098
61011 - LOG_ID_SSH_CHANNEL_PASS .....	1099
SSL .....	1101
62000 - LOG_ID_SSL_CERT_BLACKLISTED .....	1101
62001 - LOG_ID_SSL_CERT_PASS .....	1102
62002 - LOG_ID_SSL_CERT_BLOCK .....	1104
62003 - LOG_ID_SSL_EXEMPT .....	1105
62050 - LOG_ID_SSL_HS_CERT_REQ_EXEMPT .....	1107
62051 - LOG_ID_SSL_HS_CERT_REQ_BLOCK .....	1108
62052 - LOG_ID_SSL_HS_UNSUPPROTED_EXEMPT .....	1110
62053 - LOG_ID_SSL_HS_UNSUPPORTED_BLOCK .....	1111
62200 - LOG_ID_SSL_EXEMPT_ADDR .....	1113
62202 - LOG_ID_SSL_EXEMPT_FTGD_CAT .....	1114
Traffic .....	1116
2 - LOG_ID_TRAFFIC_ALLOW .....	1116
3 - LOG_ID_TRAFFIC_DENY .....	1120
4 - LOG_ID_TRAFFIC_OTHER_START .....	1124
5 - LOG_ID_TRAFFIC_OTHER_ICMP_ALLOW .....	1128

6-LOG_ID_TRAFFIC_OTHER_ICMP_DENY .....	1133
7-LOG_ID_TRAFFIC_OTHER_INVALID .....	1137
8-LOG_ID_TRAFFIC_WANOPT .....	1141
9-LOG_ID_TRAFFIC_WEBCACHE .....	1145
10-LOG_ID_TRAFFIC_EXPLICIT_PROXY .....	1150
11-LOG_ID_TRAFFIC_FAIL_CONN .....	1155
12-LOG_ID_TRAFFIC_MULTICAST .....	1159
13-LOG_ID_TRAFFIC_END_FORWARD .....	1163
14-LOG_ID_TRAFFIC_END_LOCAL .....	1168
15-LOG_ID_TRAFFIC_START_FORWARD .....	1172
16-LOG_ID_TRAFFIC_START_LOCAL .....	1176
17-LOG_ID_TRAFFIC_SNIFFER .....	1180
19-LOG_ID_TRAFFIC_BROADCAST .....	1185
20-LOG_ID_TRAFFIC_STAT .....	1189
21-LOG_ID_TRAFFIC_SNIFFER_STAT .....	1193
22-LOG_ID_TRAFFIC_UTM_CORRELATION .....	1197
VoIP .....	1202
44032-LOGID_EVENT_VOIP_SIP .....	1202
44033-LOGID_EVENT_VOIP_SIP_BLOCK .....	1203
44034-LOGID_EVENT_VOIP_SIP_FUZZING .....	1205
44035-LOGID_EVENT_VOIP_SCCP_REGISTER .....	1206
44036-LOGID_EVENT_VOIP_SCCP_UNREGISTER .....	1207
44037-LOGID_EVENT_VOIP_SCCP_CALL_BLOCK .....	1208
44038-LOGID_EVENT_VOIP_SCCP_CALL_INFO .....	1210
WAF .....	1211
30248-LOGID_WAF_SIGNATURE_BLOCK .....	1211
30249-LOGID_WAF_SIGNATURE_PASS .....	1213
30250-LOGID_WAF_SIGNATURE_ERASE .....	1215
30251-LOGID_WAF_CUSTOM_SIGNATURE_BLOCK .....	1216
30252-LOGID_WAF_CUSTOM_SIGNATURE_PASS .....	1218
30253-LOGID_WAF_METHOD_BLOCK .....	1220
30255-LOGID_WAF_ADDRESS_LIST_BLOCK .....	1222
30257-LOGID_WAF_CONSTRAINTS_BLOCK .....	1223
30258-LOGID_WAF_CONSTRAINTS_PASS .....	1225
30259-LOGID_WAF_URL_ACCESS_PERMIT .....	1227
30260-LOGID_WAF_URL_ACCESS_BYPASS .....	1229
30261-LOGID_WAF_URL_ACCESS_BLOCK .....	1230
Web .....	1232
12288-LOG_ID_WEB_CONTENT_BANWORD .....	1232
12289-LOG_ID_WEB_CONTENT_MMS_BANWORD .....	1234
12290-LOG_ID_WEB_CONTENT_EXEMPTWORD .....	1236
12291-LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD .....	1238
12292-LOG_ID_WEB_CONTENT_KEYWORD .....	1240
12293-LOG_ID_WEB_CONTENT_SEARCH .....	1242
12305-LOG_ID_WEB_CONTENT_MMS_BANWORD_NOTIF .....	1244
12544-LOG_ID_URL_FILTER_BLOCK .....	1246
12545-LOG_ID_URL_FILTER_EXEMPT .....	1248
12546-LOG_ID_URL_FILTER_ALLOW .....	1250
12547-LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK .....	1252

12548 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK .....	1254
12549 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS .....	1256
12550 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS .....	1258
12551 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK .....	1260
12552 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS .....	1261
12553 - LOG_ID_URL_FILTER_INVALID_CERT .....	1263
12554 - LOG_ID_URL_FILTER_INVALID_SESSION .....	1265
12555 - LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK .....	1267
12556 - LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS .....	1269
12557 - LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE .....	1270
12558 - LOG_ID_URL_FILTER_RATING_ERR .....	1271
12559 - LOG_ID_URL_FILTER_PASS .....	1272
12560 - LOG_ID_URL_WISP_BLOCK .....	1274
12561 - LOG_ID_URL_WISP_REDIR .....	1276
12562 - LOG_ID_URL_WISP_ALLOW .....	1278
12688 - LOG_ID_WEB_SSL_EXEMPT .....	1280
12800 - LOG_ID_WEB_FTGD_ERR .....	1282
12801 - LOG_ID_WEB_FTGD_WARNING .....	1284
12802 - LOG_ID_WEB_FTGD_QUOTA .....	1286
13056 - LOG_ID_WEB_FTGD_CAT_BLK .....	1287
13057 - LOG_ID_WEB_FTGD_CAT_WARN .....	1289
13312 - LOG_ID_WEB_FTGD_CAT_ALLOW .....	1291
13315 - LOG_ID_WEB_FTGD_QUOTA_COUNTING .....	1293
13316 - LOG_ID_WEB_FTGD_QUOTA_EXPIRED .....	1295
13317 - LOG_ID_WEB_URL .....	1297
13568 - LOG_ID_WEB_SCRIPTFILTER_ACTIVEX .....	1299
13573 - LOG_ID_WEB_SCRIPTFILTER_COOKIE .....	1301
13584 - LOG_ID_WEB_SCRIPTFILTER_APPLET .....	1303
13600 - LOG_ID_WEB_SCRIPTFILTER_OTHER .....	1305
13601 - LOG_ID_WEB_WF_COOKIE .....	1307
13602 - LOG_ID_WEB_WF_REFERERER .....	1309
13603 - LOG_ID_WEB_WF_COMMAND_BLOCK .....	1311
13616 - LOG_ID_CONTENT_TYPE_BLOCK .....	1313
13632 - LOGID_HTTP_HDR_CHG_REQ .....	1315
13633 - LOGID_HTTP_HDR_CHG_RESP .....	1316

# Change Log

Date	Change Description
2019-12-19	Initial release.

# Introduction

This document provides information about all the log messages applicable to the FortiGate devices running FortiOS version 6.2.3 or higher. The logs are intended for administrators to use as reference for more information about a specific log entry and message generated by FortiOS.

This document also provides information about log fields when FortiOS sends log messages to remote syslog servers in Common Event Format (CEF). See [CEF Support on page 46](#). It also describes how to enable extended logging. See [UTM Extended Logging on page 57](#).



Performance statistics are not logged to disk. Performance statistics can be received by a syslog server or by FortiAnalyzer.

---

## Before you begin

Before you begin using this reference, read the following notes:

- Information in this document applies to all FortiGate units that are currently running FortiOS 6.2.3 or higher.
- Ensure that you have enabled logging for the FortiOS unit.
- Each log message is displayed in the *Log & Report* pane of the GUI. You can also download the RAW format from the *Log & Report* pane.
- Each log message is documented similar to how it appears in the RAW format.



This reference contains detailed information for each log type and subtype; however, this reference contains only information gathered at publication and, as a result, not every log message field contains detailed information.

---

## What's new

This section identifies major changes in the Log Reference from version 6.2.0 and later.

### FortiOS 6.2.3

For more information about new features, please see the [6.2.3 New Features Guide](#).

There are no major log changes between FortiOS 6.2.2 and 6.2.3.

### FortiOS 6.2.2

For more information about new features, please see the [6.2.2 New Features Guide](#).

There are no major log changes between FortiOS 6.2.1 and 6.2.2.

### FortiOS 6.2.1

For more information about new features, please see the [6.2.1 New Features Guide](#).

#### New log types

- File Filter was added as a new log type with a log category ID of 19.

#### Subtype changes

- In the App log type, the `app-ctrl-all` subtype was split into the following event types: `signature`, `port-violation`, `protocol-violation`.

### FortiOS 6.2.0

For more information about new features, please see the [FortiOS 6.2.0 New Features Guide](#).

#### New log types

- Secure Socket Layer (SSL) was added as a new log type with a log category ID of 17.
- Common Internet File System (CIFS) was added as a new log type with a log category ID of 18.

#### Subtype changes

- In the Event log type, the following changes were made:
  - A *FortiExtender* subtype was added. In the FortiOS GUI, you can view logs sent from FortiExtender units on the *Log & Report* pane.

- A *connector* subtype was added to log dynamic address changes for SDN connectors.
- In the Antivirus log type, the following changes were made:
  - A *malware-list* subtype was added.
  - The *botnet* subtype was deleted.
- In the IPS log type, the *botnet* subtype was added.
- In the Email log type, a *file\_filter* subtype was added to log filtering based on metadata (file type).
- In the Webfilter log type, a *file\_filter* subtype was added added to log filtering based on metadata (file type).

# Log Types and Subtypes

This section describes the log types, subtypes, and priority levels. It also describes the log field format.

## Type

Each log entry contains a Type (type) or category field that indicates its log type and which log file stores the log entry.

## Subtype

Each log entry contains a Sub Type (subtype) or subcategory field within a log type, based on the feature associated with the cause of the log entry.

For example:

- In event logs, some of the subtypes are compliance check, system, and user.
- In traffic logs, the subtypes are forward, local, multicast, and sniffer.

## List of log types and subtypes

FortiGate devices can record the following types and subtypes of log entry information:

Type	Description	Subtype
<b>Traffic</b>	Records traffic flow information, such as an HTTP/HTTPS request and its response, if any.	<ul style="list-style-type: none"><li>• Forward</li><li>• Local</li><li>• Multicast</li><li>• Sniffer</li></ul>
<b>Event</b>	Records system and administrative events, such as downloading a backup copy of the configuration, or daemon activities.	<ul style="list-style-type: none"><li>• Compliance-check</li><li>• Connector</li><li>• Endpoint control</li><li>• FortiExtender</li><li>• High Availability</li><li>• Router</li><li>• Security-audit</li><li>• System</li><li>• User</li><li>• Virtual Private Network (VPN)</li></ul>



Type	Description	Subtype
		<ul style="list-style-type: none"> <li>• WAD</li> <li>• Wireless</li> </ul>
<b>UTM</b>	Records UTM events.	See list of UTM log subtypes below

## UTM log subtypes

UTM Log Subtypes	Description	Event Type
Virus	Records virus attacks.	<ul style="list-style-type: none"> <li>• Analytics</li> <li>• Filename</li> <li>• Filetype Executable</li> <li>• Infected</li> <li>• Malware list</li> <li>• Mime Fragmented</li> <li>• Outbreak-prevention</li> <li>• Oversized</li> <li>• Scan Error</li> <li>• Suspicious</li> <li>• Switch Proto</li> </ul>
Web Filter	Records web filter events.	<ul style="list-style-type: none"> <li>• ActiveX Filter</li> <li>• Applet Filter</li> <li>• webfilter_command_block</li> <li>• Content</li> <li>• Cookie Filter</li> <li>• FortiGuard Allow</li> <li>• FortiGuard Block</li> <li>• FortiGuard Quota Counting</li> <li>• FortiGuard Quota Expired</li> <li>• Script Filter</li> <li>• URL Filter</li> </ul>
IPS	Records intrusion prevention events.	<ul style="list-style-type: none"> <li>• Botnet</li> <li>• Malicious URL</li> <li>• Signature</li> </ul>
Email Filter	Records email filter events.	<ul style="list-style-type: none"> <li>• Carrier Endpoint Filter</li> <li>• File Filter</li> <li>• FTGD Error</li> <li>• Google Gmail</li> <li>• IMAP</li> <li>• MAPI</li> <li>• MMS</li> <li>• MSN Hotmail</li> </ul>

UTM Log Subtypes	Description	Event Type
		<ul style="list-style-type: none"> <li>• POP3</li> <li>• SMTP</li> <li>• Yahoo Mail</li> </ul>
Anomaly	Records intrusion attempts.	<ul style="list-style-type: none"> <li>• Anomaly</li> </ul>
VoIP	Records voice over IP events.	<ul style="list-style-type: none"> <li>• VoIP</li> </ul>
DLP	Records data leak prevention events.	<ul style="list-style-type: none"> <li>• DLP</li> <li>• Document Source</li> </ul>
App-CTRL	Records intrusion attempts. Application Control log is output when a signature matches an application pattern.	<ul style="list-style-type: none"> <li>• Signature</li> <li>• Port-violation</li> <li>• Protocol-violation</li> </ul>
WAF	Records web application firewall information for FortiWeb appliances and virtual appliances.	<ul style="list-style-type: none"> <li>• Address List</li> <li>• Custom Signature</li> <li>• HTTP Constraint</li> <li>• HTTP Method</li> <li>• Signature</li> <li>• URL access</li> </ul>
DNS	Records domain name server events.	<ul style="list-style-type: none"> <li>• DNS-query</li> <li>• DNS-response</li> </ul>
SSH	Records Secure Socket Shell events.	<ul style="list-style-type: none"> <li>• SSH Channel</li> <li>• SSH Command</li> </ul>
SSL	Records detected/blocked malicious SSL connections.	<ul style="list-style-type: none"> <li>• SSL anomalies</li> <li>• SSL exempt</li> </ul>
CIFS	Records CIFS file filter events.	<ul style="list-style-type: none"> <li>• CIFS-auth-all</li> </ul>
File Filter	Records file filter events.	<ul style="list-style-type: none"> <li>• File-filter</li> </ul>

## FortiOS priority levels

Each log entry contains a Level (level) field that indicates the estimated severity of the event that caused the log entry, such as `level=warning`, and therefore how high a priority it is likely to be. Level (level) associations with the descriptions below are not always uniform. They also may not correspond with your own definitions of how severe each event is. If you require notification when a specific event occurs, either configure SNMP traps or alert email by administrator-defined Severity Level (`severity_level`) or ID (`logid`), not by Level (level).

Level (0 is highest)	Name	Description
0	Emergency	The system is unusable or not responding.
1	Alert	Immediate action required. Used in security logs.

Level (0 is highest)	Name	Description
2	Critical	Functionality is affected.
3	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
5	Notification	Information about normal events.
6	Information	General information about system operations. Used in event logs to record configuration changes.

For each location where the FortiGate device can store log files (disk, memory, Syslog or FortiAnalyzer), you can define a severity threshold. FortiOS stores all log messages equal to or exceeding the log severity level selected. For example, if you select Error, FortiOS will store log messages whose log severity level is Error, Critical, Alert, and Emergency.

## Log field format

The following table describes the standard format in which each log type is described in this document. For documentation purposes, all log types and subtypes follow this generic table format to present the log entry information.

Log Field Name	Description	Data Type	Length
appact	The security action from app control	string	16

# Log Schema Structure

This section describes the schema of the FortiOS log messages.

## Log message fields

Each log message consists of several sections of fields. In the FortiOS GUI, you can view the logs in the *Log & Report* pane, which displays the formatted view. If you want to view logs in raw format, you must download the log and view it in a text editor.

Following is an example of a traffic log message in raw format:

```
date=2017-11-15 time=11:44:16 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1510775056 srcip=10.1.100.155 srcname="pc1"
srcport=40772 srcintf="port12" srcintfrole="undefined" dstip=35.197.51.42
dstname="fortiguard.com" dstport=443 dstintf="port11" dstintfrole="undefined"
poluid="707a0d88-c972-51e7-bbc7-4d421660557b" sessionid=8058 proto=6 action="close"
policyid=1 policytype="policy" policymode="learn" service="HTTPS" dstcountry="United
States" srccountry="Reserved" trandisp="snat" transip=172.16.200.2 transport=40772
appid=40568 app="HTTPS.BROWSER" appcat="Web.Client" apprisk="medium" duration=2
sentbyte=1850 rcvbyte=39898 sentpkt=25 rcvdpkt=37 utmaction="allow" countapp=1
devtype="Linux PC" osname="Linux" mastersrcmac="a2:e9:00:ec:40:01"
srcmac="a2:e9:00:ec:40:01" srcserver=0 utmref=0-220586
```

The following table provides an example of the log field information in the FortiOS GUI in the detailed view of the *Log & Report* pane and in the downloaded, raw log file.

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
<b>General</b>		
Date (date)	Day, month, and year when the log message was recorded.	date=2017-11-15
Direction (direction)	Indicates message/packets direction.	direction=incoming
Time (time)	Hour clock when the log message was recorded.	time=11:44:16
Duration (duration)	Duration of the session.	duration=2
Session ID (sessionid)	ID for the session.	sessionid=8058
Virtual Domain (vd)	Name of the virtual domain in which the log message was recorded.	vd="vdom1"
NAT Translation (transport)	NAT source port.	transport=40772
<b>Source</b>		

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
IP (srcip)	IP address of the traffic's origin. The source varies by the direction: <ul style="list-style-type: none"> <li>In HTTP requests, this is the web browser or other client.</li> <li>In HTTP responses, this is the physical server.</li> </ul>	srcip=10.1.100.155
NAT IP (transip)	NAT source IP.	transip=172.16.200.2
Source Port (srcport)	Port number of the traffic's origin.	srcport=40772
Country (srccountry)	Name of the source country.	srccountry="Reserved"
Source Interface(srcintf)	Interface name of the traffic's origin.	srcintf="port12"
Source Name (srcname)	Name of the source.	srcname="pc1"
Source Interface Name (srcintfrole)	Name of the source interface.	srcintfrole="undefined"
Device Type (devtype)	Device type of the source.	devtype="Linux PC"
OS Name (osname)	OS of the source.	osname="Linux"
Master Source MAC (mastersrcmac)	The master MAC address for a host that has multiple network interfaces.	mastersrcmac="a2:e9:00:ec:40:01"
Source MAC (srcmac)	MAC address associated with the source IP address.	srcmac="a2:e9:00:ec:40:01"
Source Server (srcserver)	Server of the source.	srcserver=0
Device ID (devid)	Serial number of the device for the traffic's origin.	devid="FGVM02Q105060010"
<b>Destination</b>		
IP (dstip)	Destination IP address for the web.	dstip=35.197.51.42
Port (dstport)	Port number of the traffic's destination.	dstport=443
Country (dstcountry)	Name of the destination country.	dstcountry="United States"
Destination Interface (dstintf)	Interface of the traffic's destination.	dstintf="port11"
Destination Name (dstname)	Name of the destination.	dstname="fortiguard.com"
Destination Interface Name (dstintfrole)	Name of the destination interface.	dstintfrole="undefined"
<b>Application</b>		

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
Application Name (app)	Name of the application.	app="HTTPS.BROWSER"
Category (appcat)	Category of the application.	appcat="Web.Client"
Service (service)	Name of the service.	service="HTTPS"
Application ID (appid)	ID of the application.	appid=40568
Application Risk (apprisk)	Risk level of the application.	apprisk="medium"
countapp	Number of App Ctrl logs associated with the session.	countapp=1
<b>Data</b>		
Received bytes (rcvbyte)	Number of bytes received.	rcvbyte=39898
Received packets (rcvpkt)	Number of packets received.	rcvpkt=37
Sent bytes (sentbyte)	Number of bytes sent.	sentbyte=1850
Sent packets (sentpkt)	Number of packets sent.	sentpkt=25
<b>Action</b>		
Action (action)	Status of the session. Uses following definitions: <ul style="list-style-type: none"> <li>Deny: blocked by firewall policy</li> <li>Start: session start log (special option to enable logging at start of a session). This means firewall allowed.</li> <li>All Others: allowed by Firewall Policy and the status indicates how it was closed.</li> </ul>	action=close
Policy (policyid)	Name of the firewall policy governing the traffic which caused the log message.	policyid=1
Policy UUID (poluid)	UUID for the firewall policy.	poluid="707a0d88-c972-51e7-bbc7-4d421660557b"
Policy Type (policytype)		policytype="policy"
Policy Mode (policymode)	Firewall policy mode.	policymode="learn"
<b>Security</b>		
Level (level)	Security level rating.	level="notice"

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
<b>Other</b>		
Event Time (eventtime)	Epoch time the log was triggered by FortiGate. If you convert the epoch time to human readable time, it might not match the Date and Time in the header owing to a small delay between the time the log was triggered and recorded. The Log Time field is the same for the same log among all log devices, but the Date and Time might differ.	eventtime=1510775056
Protocol Number (proto)	tcp: The protocol used by web traffic (tcp by default)	proto=6
Type (type)	Log type. See <a href="#">Type on page 32</a>	type="traffic"
Log ID (logid)	Log ID. See <a href="#">Log ID definitions on page 40</a>	logid="0000000013"
Sub Type(subtype)	Subtype of the traffic. See <a href="#">Subtype on page 32</a> .	subtype="forward"
trandisp	NAT translation type.	trandisp="snat"
UTM Action (utmaction)	Security action performed by UTM.	utmaction="allow"
UTM Reference (utmref)	UTM reference number.	utmref=0-220586
UTM Reference (utmref)	UTM reference number.	utmref=0-220586

## Log ID numbers

The ID (logid) is a 10-digit field. It is a unique identifier for that specific log and includes the following information about the log entry.

Log ID number components	Description	Examples
Log Type	Represented by the first two digits of the log ID.	<ul style="list-style-type: none"> <li>Traffic log IDs begin with "00".</li> <li>Event log IDs begin with "01".</li> </ul>
Sub Type or Event Type	Represented by the second two digits of the log ID.	<ul style="list-style-type: none"> <li>VPN log subtype is represented with "01" which belongs to the Event log type that is represented with "01". Therefore, all VPN related Event log IDs will begin with the 0101 log ID series.</li> </ul>

Log ID number components	Description	Examples
Message ID	The last six digits of the log ID represent the message ID.	<ul style="list-style-type: none"> <li>An administrator account always has the log ID 0000003401.</li> </ul>

The logid field is a number assigned to all permutations of the same message. It classifies a log entry by the nature of the cause of the log message, such as administrator authentication failures or traffic. Other log messages that share the same cause will share the same logid.

## Log ID definitions

Following are the definitions for the log type IDs and subtype IDs applicable to FortiOS version 5.2.1 and later.

Log Category IDs	Subtype IDs
traffic: 0	<ul style="list-style-type: none"> <li>forward: 0</li> <li>local: 1</li> <li>multicast: 2</li> <li>sniffer: 4</li> </ul>
event: 1	<ul style="list-style-type: none"> <li>system: 0</li> <li>vpn: 1</li> <li>user: 2</li> <li>router: 3</li> <li>wireless: 4</li> <li>wad: 5</li> <li>endpoint: 7</li> <li>ha: 8</li> <li>compliance-check: 9</li> <li>security_audit: 10</li> <li>connector: 12</li> <li>fortiextender:</li> </ul>
virus: 2	<ul style="list-style-type: none"> <li>malware-list: 7</li> <li>infected: 11</li> <li>blocked: 12</li> <li>oversized: 13</li> <li>scanerror: 62</li> <li>suspicious: 0</li> <li>analytics: 1</li> <li>switchproto: 63</li> <li>mimefragmented: 61</li> <li>virus_filetype_exe: 3</li> <li>botnet: 2</li> </ul>
webfilter: 3	<ul style="list-style-type: none"> <li>content: 14</li> </ul>



Log Category IDs	Subtype IDs
	<ul style="list-style-type: none"> <li>• urlfilter: 15</li> <li>• ftgd_blk: 16</li> <li>• ftgd_allow: 17</li> <li>• ftgd_err: 18</li> <li>• url_monitor: 19</li> <li>• scriptfilter_activex: 35</li> <li>• scriptfilter_cookie: 36</li> <li>• scriptfilter_applet: 37</li> <li>• ftgd_quota_counting: 38</li> <li>• ftgd_quota_expired: 39</li> <li>• ftgd_quota: 40</li> <li>• scriptfilter_other: 41</li> <li>• webfilter_command_block: 43</li> <li>• file_filter</li> </ul>
ips: 4	<ul style="list-style-type: none"> <li>• signature: 19</li> <li>• malicious_url: 21</li> <li>• botnet</li> </ul>
email: 5	<ul style="list-style-type: none"> <li>• smtp: 8</li> <li>• pop3: 9</li> <li>• imap: 10</li> <li>• mapi: 11</li> <li>• carrier-endpoint-filter: 47</li> <li>• mass-mms: 52</li> <li>• msn-hotmail: 5</li> <li>• yahoo-mail: 6</li> <li>• gmail: 7</li> <li>• ftgd_err: 53</li> <li>• file_filter: 54</li> </ul>
anomaly: 7	<ul style="list-style-type: none"> <li>• anomaly: 20</li> </ul>
voip: 8	<ul style="list-style-type: none"> <li>• viop: 14</li> </ul>
dlp: 9	<ul style="list-style-type: none"> <li>• dlp: 54</li> <li>• dlp-docsource: 55</li> </ul>
app_ctrl: 10	<ul style="list-style-type: none"> <li>• app-ctrl-all: 59</li> </ul>
WAF: 12	<ul style="list-style-type: none"> <li>• signature: 0</li> <li>• custom_signature: 1</li> <li>• method: 2</li> <li>• constraints: 3</li> <li>• address_list: 4</li> <li>• url_access: 5</li> </ul>
GTP: 14	<ul style="list-style-type: none"> <li>• all: 0</li> </ul>

Log Category IDs	Subtype IDs
DNS: 15	<ul style="list-style-type: none"><li>• dns-query: 0</li><li>• dns-response: 1</li></ul>
SSH: 16	<ul style="list-style-type: none"><li>• ssh-command: 0</li><li>• ssh-channel: 1</li></ul>
SSL: 17	<ul style="list-style-type: none"><li>• ssl-anomalies: 0</li><li>• ssl-exempt: 1</li></ul>
CIFS: 18	<ul style="list-style-type: none"><li>• cifs-filefilter: 0</li></ul>
File Filter: 19	<ul style="list-style-type: none"><li>• file-filter: 0</li></ul>

# FortiGuard Web Filter Categories

The below details the mapping between FortiGuard Web Filter category names and numbers.

Number	Category
0	Unrated
1	Drug abuse
2	Alternative beliefs
3	Hacking
4	Illegal or unethical
5	Discrimination
6	Explicit violence
7	Abortion
8	Other adult materials
9	Advocacy organizations
11	Gambling
12	Extremist groups
13	Nudity and risque
14	Pornography
15	Dating
16	Weapons (sales)
17	Advertising
18	Brokerage and trading
19	Freeware and software downloads
20	Games
23	Web-based email
24	File sharing and storage
25	Streaming media and download
26	Malicious websites
28	Entertainment
29	Arts and culture
30	Education

Number	Category
31	Finance and banking
33	Health and wellness
34	Job search
35	Medicine
36	News and media
37	Social networking
38	Political organizations
39	Reference
40	Global religion
41	Search engines and portals
42	Shopping
43	General organizations
44	Society and lifestyles
46	Sports
47	Travel
48	Personal vehicles
49	Business
50	Information and computer security
51	Government and legal organizations
52	Information technology
53	Armed forces
54	Dynamic content
55	Meaningless content
56	Web hosting
57	Marijuana
58	Folklore
59	Proxy avoidance
61	Phishing
62	Plagiarism
63	Sex education

Number	Category
64	Alcohol
65	Tobacco
66	Lingerie and swimsuit
67	Sports hunting and war games
68	Web chat
69	Instant messaging
70	Newsgroups and message boards
71	Digital postcards
72	Peer-to-peer file sharing
75	Internet radio and TV
76	Internet telephony
77	Child education
78	Real estate
79	Restaurant and dining
80	Personal websites and blogs
81	Secure websites
82	Content servers
83	Child abuse
84	Web-based applications
85	Domain parking
86	Spam URLs
87	Personal privacy
88	Dynamic DNS
89	Auction
90	Newly observed domain
91	Newly registered domain
92	Charitable organizations
93	Remote access
94	Web analytics
95	Online meeting

# CEF Support

You can configure FortiOS 6.2.3 to send logs to remote syslog servers in Common Event Format (CEF) by using the `config log syslogd setting` command.

When CEF is enabled, FortiOS sends logs to syslog servers in CEF. This section describes how FortiOS logs support CEF.



You can view logs in CEF on remote syslog servers or FortiAnalyzer, but not in the FortiOS GUI.

---

## FortiOS to CEF log field mapping guidelines

The following CEF format:

```
Date/Time host CEF:Version|Device Vendor|Device Product|Device Version|Signature
ID|Name|Severity| [Extension]
```

Displays as following in FortiOS logs with CEF enabled:

```
"MMM dd HH:mm:ss" "hostname of the fortigate"
CEF:0|Fortinet|Fortigate|version|logid|type:subtype +[eventtype] +[action] +
[status]|reversed level|...
```

The `SignatureId` field in FortiOS logs maps to the `logid` field in CEF and should be last 5 digits of `logid`.

The `Name` field in CEF uses the following formula:

```
type:subtype + [eventtype] + [action] + [status]
```

Following is an example of the header and one key-value pair for extension from the Event VPN log in CEF:

```
#Feb 12 10:31:04 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|37127|event:vpn negotiate
success|3|FTNTFGTlogid=0101037127
```

The `type:subtype` field in FortiOS logs maps to the `cat` field in CEF.

Any fields in FortiOS logs that are unmatched to fields in CEF include the `FTNTFGT` prefix.

Quotes (") are removed from FortiOS logs to support CEF.

Forward slashes (/) in string values as well as the equal sign (=) and backward slashes (\) are escaped in FortiOS logs to support CEF.

## CEF priority levels

Following are the CEF priority levels. They are opposite of FortiOS priority levels. See also [FortiOS priority levels on page 34](#).

Level (8 is highest)	Name	Description
8	Emergency	The system is unusable or not responding.
7	Alert	Immediate action required. Used in security logs.
6	Critical	Functionality is affected.
5	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
3	Notification	Information about normal events.
2	Information	General information about system operations. Used in event logs to record configuration changes.
1	Debug	Debug information.

## Examples of CEF support

This section includes examples of how the different types of log message support CEF.

### Traffic log support for CEF

The following is an example of a traffic log on the FortiGate disk:

```
date=2018-12-27 time=11:07:55 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1545937675 srcip=10.1.100.11 srcport=54190
srcintf="port12" srcintfrole="undefined" dstip=52.53.140.235 dstport=443
dstintf="port11" dstintfrole="undefined" poluid="c2d460aa-fe6f-51e8-9505-
41b5117dfdd4" sessionid=402 proto=6 action="close" policyid=1 policytype="policy"
service="HTTPS" dstcountry="United States" srccountry="Reserved" trandisp="snat"
transip=172.16.200.1 transport=54190 appid=40568 app="HTTPS.BROWSER"
appcat="Web.Client" apprisk="medium" applist="g-default" duration=2 sentbyte=3652
rcvbyte=146668 sentpkt=58 rcvpkt=105 utmaction="allow" countapp=2 utmref=65532-56
```

The following is an example of a traffic log sent in CEF format to a syslog server:

```
Dec 27 11:07:55 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|00013|traffic:forward
close|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0000000013 cat=traffic:forward
FTNTFGTsubtype=forward FTNTFGTlevel=notice FTNTFGTvd=vdom1 FTNTFGTeventtime=1545937675
src=10.1.100.11 spt=54190 deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined
dst=52.53.140.235 dpt=443 deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined
FTNTFGTpoluid=c2d460aa-fe6f-51e8-9505-41b5117dfdd4 externalId=402 proto=6 act=close
FTNTFGTpolicyid=1 FTNTFGTpolicytype=policy app=HTTPS FTNTFGTdstcountry=United States
FTNTFGTsrccountry=Reserved FTNTFGTtrandisp=snat sourceTranslatedAddress=172.16.200.1
sourceTranslatedPort=54190 FTNTFGTappid=40568 FTNTFGTapp=HTTPS.BROWSER
FTNTFGTappcat=Web.Client FTNTFGTapprisk=medium FTNTFGTapplist=g-default
FTNTFGTduration=2 out=3652 in=146668 FTNTFGTsentpkt=58 FTNTFGTrcvdpkt=105
FTNTFGTutmaction=allow FTNTFGTcountapp=2
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
type: subtype	cat
srcip	src
srcport	spt
srcintf	deviceInboundInterface
dstip	dst
dstport	dpt
dstintf	deviceOutboundInterface
sessionid	externalID
proto	proto
action	act
transip	sourceTranslatedAddress
transport	sourceTranslatedPort
service	app
sentbyte	out
rcvdbyte	in

## Custom fields

To configure the traffic log with custom fields, enter the following CLI commands:

```

config log custom-field
  edit 1
    set name "custom_name1"
    set value "HN123456"
  next
  edit 2
    set name "custom_name2"
    set value "accounting_dpt"
  next
end
config firewall policy
  edit 1
    set name "A-v4-out"
    set uuid c2d460aa-fe6f-51e8-9505-41b5117dfdd4
    set srcintf "port12"
    set dstintf "port11"
    set srcaddr "all"
    set dstaddr "all"
    set action accept
    set schedule "always"
    set service "ALL"
    set utm-status enable
    set logtraffic all

```



```

set custom-log-fields "1" "2"
set application-list "g-default"
set ssl-ssh-profile "certificate-inspection"
set nat enable
next
end

```

The following is an example of a traffic log with custom fields on the FortiGate disk:

```

date=2018-12-27 time=11:12:30 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1545937950 srcip=10.1.100.11 srcport=58843
srcintf="port12" srcintfrole="undefined" dstip=172.16.200.55 dstport=53
dstintf="port11" dstintfrole="undefined" poluid="c2d460aa-fe6f-51e8-9505-
41b5117dfdd4" sessionid=440 proto=17 action="accept" policyid=1 policytype="policy"
service="DNS" dstcountry="Reserved" srccountry="Reserved" trandisp="snat"
transip=172.16.200.1 transport=58843 appid=16195 app="DNS" appcat="Network.Service"
apprisk="elevated" applist="g-default" duration=180 sentbyte=70 rcvdbyte=528 sentpkt=1
rcvdpkt=1 custom_name1="HN123456" custom_name2="accounting_dpt"

```

The following is an example of a traffic log with custom fields sent in CEF format to a syslog server:

```

Dec 27 11:12:30 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|00013|traffic:forward
accept|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0000000013 cat=traffic:forward
FTNTFGTsubtype=forward FTNTFGTlevel=notice FTNTFGTvd=vdom1 FTNTFGTeventtime=1545937950
src=10.1.100.11 spt=58843 deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined
dst=172.16.200.55 dpt=53 deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined
FTNTFGTpoluid=c2d460aa-fe6f-51e8-9505-41b5117dfdd4 externalId=440 proto=17 act=accept
FTNTFGTpolicyid=1 FTNTFGTpolicytype=policy app=DNS FTNTFGTdstcountry=Reserved
FTNTFGTsrccountry=Reserved FTNTFGTtrandisp=snat sourceTranslatedAddress=172.16.200.1
sourceTranslatedPort=58843 FTNTFGTappid=16195 FTNTFGTapp=DNS
FTNTFGTappcat=Network.Service FTNTFGTapprisk=elevated FTNTFGTapplist=g-default
FTNTFGTduration=180 out=70 in=528 FTNTFGTsentpkt=1 FTNTFGTrcvdpkt=1 FTNTFGTcustom_
name1=HN123456 FTNTFGTcustom_name2=accounting_dpt

```

The following table maps FortiOS custom log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
custom_name1	FTNTFGTcustom_name1
custom_name2	FTNTFGTcustom_name2

## Event log support for CEF

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
msg	msg
cookies	requestCookies
user	duser
status	outcome
role	sourceServiceName

FortiOS Log Field Name	CEF Field Name
ui	sproc
reason	reason
action	act

## system subtype

The following is an example of a system subtype event log on the FortiGate disk:

```
date=2018-12-27 time=11:15:40 logid="0100032002" type="event" subtype="system" level="alert"
vd="vdom1" eventtime=1545938140 logdesc="Admin login failed" sn="0" user="admin1"
ui="https (172.16.200.254)" method="https" srcip=172.16.200.254 dstip=172.16.200.1
action="login" status="failed" reason="name_invalid" msg="Administrator admin1 login
failed from https (172.16.200.254) because of invalid user name"
```

The following is an example of a system subtype event log sent in CEF format to a syslog server:

```
Dec 27 11:15:40 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|32002|event:system login
failed|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0100032002 cat=event:system
FTNTFGTsubtype=system FTNTFGTlevel=alert FTNTFGTvd=vdom1 FTNTFGTeventtime=1545938140
FTNTFGTlogdesc=Admin login failed FTNTFGTsn=0 duser=admin1 sproc=https (172.16.200.254)
FTNTFGTmethod=https src=172.16.200.254 dst=172.16.200.1 act=login outcome=failed
reason=name_invalid msg=Administrator admin1 login failed from https (172.16.200.254)
because of invalid user name
```

## user subtype

The following is an example of a user subtype log on the FortiGate disk:

```
date=2018-12-27 time=11:17:35 logid="0102043008" type="event" subtype="user" level="notice"
vd="vdom1" eventtime=1545938255 logdesc="Authentication success" srcip=10.1.100.11
dstip=172.16.200.55 policyid=1 interface="port12" user="bob" group="N/A"
authproto="TELNET (10.1.100.11)" action="authentication" status="success" reason="N/A"
msg="User bob succeeded in authentication"
```

The following is an example of a user subtype log sent in CEF format to a syslog server:

```
Dec 27 11:17:35 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|43008|event:user authentication
success|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0102043008 cat=event:user
FTNTFGTsubtype=user FTNTFGTlevel=notice FTNTFGTvd=vdom1 FTNTFGTeventtime=1545938255
FTNTFGTlogdesc=Authentication success src=10.1.100.11 dst=172.16.200.55
FTNTFGTpolicyid=1 deviceInboundInterface=port12 duser=bob FTNTFGTgroup=N/A
FTNTFGTauthproto=TELNET (10.1.100.11) act=authentication outcome=success reason=N/A
msg=User bob succeeded in authentication
```

## Antivirus log support for CEF

The following is an example of an antivirus log on the FortiGate disk:

```
date=2018-12-27 time=11:20:49 logid="0211008192" type="utm" subtype="virus"
eventtype="infected" level="warning" vd="vdom1" eventtime=1545938448 msg="File is
infected." action="blocked" service="HTTP" sessionid=695 srcip=10.1.100.11
dstip=172.16.200.55 srcport=44356 dstport=80 srcintf="port12" srcintfrole="undefined"
dstintf="port11" dstintfrole="undefined" policyid=1 proto=6 direction="incoming"
filename="eicar.com" quarskip="File-was-not-quarantined." virus="EICAR_TEST_FILE"
```

```
dtype="Virus" ref="http://www.fortinet.com/ve?vn=EICAR_TEST_FILE" virusid=2172
url="http://172.16.200.55/virus/eicar.com" profile="g-default" user="bob"
agent="curl/7.47.0"
analyticscksum="275a021bbfb6489e54d471899f7db9d1663fc695ec2fe2a2c4538aabf651fd0f"
analyticssubmit="false" crscore=50 crlevel="critical"
```

The following is an example of an antivirus log sent in CEF format to a syslog server:

```
Dec 27 11:20:48 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|08192|utm:virus infected
blocked|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0211008192 cat=utm:virus
FTNTFGTsubtype=virus FTNTFGTeventtype=infected FTNTFGTlevel=warning FTNTFGTvd=vdom1
FTNTFGTeventtime=1545938448 msg=File is infected. act=blocked app=HTTP externalId=695
src=10.1.100.11 dst=172.16.200.55 spt=44356 dpt=80 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined deviceOutboundInterface=port11
FTNTFGTdstintfrole=undefined FTNTFGTpolicyid=1 proto=6 deviceDirection=0
fname=eicar.com FTNTFGTquarskip=File-was-not-quarantined. FTNTFGTvirus=EICAR_TEST_FILE
FTNTFGTdtype=Virus FTNTFGTref=http://www.fortinet.com/ve?vn=EICAR_TEST_FILE
FTNTFGTvirusid=2172 request=http://172.16.200.55/virus/eicar.com FTNTFGTprofile=g-
default duser=bob requestClientApplication=curl/7.47.0
FTNTFGTanalyticscksum=275a021bbfb6489e54d471899f7db9d1663fc695ec2fe2a2c4538aabf651fd0f
FTNTFGTanalyticssubmit=false FTNTFGTcrscore=50 FTNTFGTcrlevel=critical
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
direction	deviceDirection (inbound/outbound mapping to 0/1)
filename	fname
ref	FTNTFGTref (There is \ added to escape = )
url	request
agent	requestClientApplication

## Webfilter log support for CEF

The following is an example of a webfilter log on the FortiGate disk:

```
date=2018-12-27 time=11:23:50 logid="0316013056" type="utm" subtype="webfilter"
eventtype="ftgd_blk" level="warning" vd="vdom1" eventtime=1545938629 policyid=1
sessionid=764 user="bob" srcip=10.1.100.11 srcport=59194 srcintf="port12"
srcintfrole="undefined" dstip=185.230.61.185 dstport=80 dstintf="port11"
dstintfrole="undefined" proto=6 service="HTTP" hostname="ambrishsriv.wixsite.com"
profile="g-default" action="blocked" reqtype="direct" url="/bizsquads" sentbyte=96
rcvdbyte=0 direction="outgoing" msg="URL belongs to a denied category in policy"
method="domain" cat=26 catdesc="Malicious Websites" crscore=60 crlevel="high"
```

The following is an example of a webfilter log sent in CEF format to a syslog server:

```
Dec 27 11:23:49 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|13056|utm:webfilter ftgd_blk
blocked|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0316013056 cat=utm:webfilter
FTNTFGTsubtype=webfilter FTNTFGTeventtype=ftgd_blk FTNTFGTlevel=warning
FTNTFGTvd=vdom1 FTNTFGTeventtime=1545938629 FTNTFGTpolicyid=1 externalId=764 duser=bob
src=10.1.100.11 spt=59194 deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined
dst=185.230.61.185 dpt=80 deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined
proto=6 app=HTTP dhost=ambrishsriv.wixsite.com FTNTFGTprofile=g-default act=blocked
FTNTFGTreqtype=direct request=/bizsquads out=96 in=0 deviceDirection=1 msg=URL belongs
to a denied category in policy FTNTFGTmethod=domain FTNTFGTcat=26
requestContext=Malicious Websites FTNTFGTcrscore=60 FTNTFGTcrlevel=high
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
hostname	dhost
catdesc	requestContext

## IPS log support for CEF

The following is an example of an IPS log on the FortiGate disk:

```
date=2018-12-27 time=11:28:07 logid="0419016384" type="utm" subtype="ips"
eventtype="signature" level="alert" vd="vdom1" eventtime=1545938887 severity="info"
srcip=172.16.200.55 srccountry="Reserved" dstip=10.1.100.11 srcintf="port11"
srcintfrole="undefined" dstintf="port12" dstintfrole="undefined" sessionid=901
action="reset" proto=6 service="HTTP" policyid=1 attack="Eicar.Virus.Test.File"
srcport=80 dstport=44362 hostname="172.16.200.55" url="/virus/eicar.com"
direction="incoming" attackid=29844 profile="test-ips"
ref="http://www.fortinet.com/ids/VID29844" user="bob" incidentserialno=877326946
msg="file_transfer: Eicar.Virus.Test.File,"
```

The following is an example of an IPS sent in CEF format to a syslog server:

```
Dec 27 11:28:07 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|16384|utm:ips signature
reset|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0419016384 cat=utm:ips
FTNTFGTsubtype=ips FTNTFGTeventtype=signature FTNTFGTlevel=alert FTNTFGTvd=vdom1
FTNTFGTeventtime=1545938887 FTNTFGTseverity=info src=172.16.200.55
FTNTFGTsrccountry=Reserved dst=10.1.100.11 deviceInboundInterface=port11
FTNTFGTsrcintfrole=undefined deviceOutboundInterface=port12
FTNTFGTdstintfrole=undefined externalId=901 act=reset proto=6 app=HTTP
FTNTFGTpolicyid=1 FTNTFGTattack=Eicar.Virus.Test.File spt=80 dpt=44362
dhost=172.16.200.55 request=/virus/eicar.com deviceDirection=0 FTNTFGTattackid=29844
FTNTFGTprofile=test-ips FTNTFGTref=http://www.fortinet.com/ids/VID29844 duser=bob
FTNTFGTincidentserialno=877326946 msg=file_transfer: Eicar.Virus.Test.File,
```

## Email Spamfilter log support for CEF

The following is an example of an email spamfilter log on the FortiGate disk:

```
date=2018-12-27 time=11:36:58 logid="0508020503" type="utm" subtype="emailfilter"
eventtype="smtp" level="information" vd="vdom1" eventtime=1545939418 policyid=1
sessionid=1135 user="bob" srcip=10.1.100.11 srcport=35969 srcintf="port12"
srcintfrole="undefined" dstip=172.18.62.158 dstport=25 dstintf="port11"
dstintfrole="undefined" proto=6 service="SMTP" profile="test-spam" action="log-only"
from="testpcl@qa.fortinet.com" to="test1@server88.qa.fortinet.com"
sender="testpcl@qa.fortinet.com" recipient="test1@server88.qa.fortinet.com"
direction="outgoing" msg="general email log" subject="hello_world2" size="216"
attachment="no"
```

The following is an example of an email spamfilter log sent in CEF format to a syslog server:

```
Dec 27 11:36:58 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|20503|utm:emailfilter smtp log-
only|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0508020503 cat=utm:emailfilter
FTNTFGTsubtype=emailfilter FTNTFGTeventtype=smtp FTNTFGTlevel=information
FTNTFGTvd=vdom1 FTNTFGTeventtime=1545939418 FTNTFGTpolicyid=1 externalId=1135
duser=bob src=10.1.100.11 spt=35969 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined dst=172.18.62.158 dpt=25 deviceOutboundInterface=port11
```

```
FTNTFGTdstintfrole=undefined proto=6 app=SMTP FTNTFGTprofile=test-spam act=log-only
suser=testpcl@qa.fortinet.com duser=test1@server88.qa.fortinet.com
FTNTFGTsender=testpcl@qa.fortinet.com FTNTFGTrecipient=test1@server88.qa.fortinet.com
deviceDirection=1 msg=general email log FTNTFGTsubject=hello_world2 FTNTFGTsize=216
FTNTFGTattachment=no
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
from	suser
to	duser

## Anomaly log support for CEF

The following is an example of an anomaly log on the FortiGate disk:

```
date=2018-12-27 time=11:40:04 logid="0720018433" type="utm" subtype="anomaly"
eventtype="anomaly" level="alert" vd="vdom1" eventtime=1545939604 severity="critical"
srcip=10.1.100.11 srccountry="Reserved" dstip=172.16.200.55 srcintf="port12"
srcintfrole="undefined" sessionid=0 action="clear_session" proto=1 service="PING"
count=1 attack="icmp_flood" icmpid="0x3053" icmptype="0x08" icmpcode="0x00"
attackid=16777316 policyid=1 policytype="DoS-policy"
ref="http://www.fortinet.com/ids/VID16777316" msg="anomaly: icmp_flood, 51 > threshold
50" crscore=50 crlevel="critical"
```

The following is an example of an anomaly log sent in CEF format to a syslog server:

```
Dec 27 11:40:04 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|18433|utm:anomaly anomaly clear_
session|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0720018433 cat=utm:anomaly
FTNTFGTsubtype=anomaly FTNTFGTeventtype=anomaly FTNTFGTlevel=alert FTNTFGTvd=vdom1
FTNTFGTeventtime=1545939604 FTNTFGTseverity=critical src=10.1.100.11
FTNTFGTsrccountry=Reserved dst=172.16.200.55 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined externalId=0 act=clear_session proto=1 app=PING cnt=1
FTNTFGTattack=icmp_flood FTNTFGTicmpid=0x3053 FTNTFGTicmptype=0x08
FTNTFGTicmpcode=0x00 FTNTFGTattackid=16777316 FTNTFGTpolicyid=1 FTNTFGTpolicytype=DoS-
policy FTNTFGTref=http://www.fortinet.com/ids/VID16777316 msg=anomaly: icmp_flood, 51
> threshold 50 FTNTFGTcrscore=50 FTNTFGTcrlevel=critical
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
count	cnt

## VoIP log support for CEF

The following is an example of an VoIP log on the FortiGate disk:

```
date=2018-12-27 time=16:47:09 logid="0814044032" type="utm" subtype="voip" eventtype="voip"
level="information" vd="vdom1" eventtime=1545958028 session_id=18975 epoch=0 event_
id=6857 srcip=10.1.100.11 src_port=5060 dstip=172.16.200.55 dst_port=5060 proto=17
src_int="port12" dst_int="port11" policy_id=1 profile="default" voip_proto="sip"
kind="call" action="permit" status="start" duration=0 dir="session_origin" call_
id="3444-13134@127.0.0.1" from="sip:sipp@127.0.0.1:5060"
to="sip:service@172.16.200.55:5060"
```

The following is an example of an VoIP sent in CEF format to a syslog server:

```
Dec 27 16:47:08 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|44032|utm:voip voip permit
start|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0814044032 cat=utm:voip
FTNTFGTsubtype=voip FTNTFGTeventtype=voip FTNTFGTlevel=information FTNTFGTvd=vdom1
FTNTFGTeventtime=1545958028 externalId=18975 FTNTFGTepoch=0 FTNTFGTevent_id=6857
src=10.1.100.11 spt=5060 dst=172.16.200.55 dpt=5060 proto=17
deviceInboundInterface=port12 deviceOutboundInterface=port11 FTNTFGTpolicy_id=1
FTNTFGTprofile=default FTNTFGTvoip_proto=sip FTNTFGTkind=call act=permit outcome=start
FTNTFGTduration=0 FTNTFGTdir=session_origin FTNTFGTcall_id=3444-13134@127.0.0.1
suser=sip:sipp@127.0.0.1:5060 duser=sip:service@172.16.200.55:5060
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
status	outcome
from	suser
to	duser

## DLP log support for CEF

The following is an example of a DLP log on the FortiGate disk:

```
date=2018-12-27 time=14:29:36 logid="0954024576" type="utm" subtype="dlp" eventtype="dlp"
level="warning" vd="vdom1" eventtime=1545949776 filteridx=1 dlpeextra="test-dlp3"
filtertype="file-type" filtercat="file" severity="medium" policyid=1 sessionid=12680
epoch=418303178 eventid=0 user="bob" srcip=10.1.100.11 srcport=33638 srcintf="port12"
srcintfrole="undefined" dstip=172.18.62.158 dstport=80 dstintf="port11"
dstintfrole="undefined" proto=6 service="HTTP" filetype="gif" direction="incoming"
action="block" hostname="172.18.62.158" url="/dlp/flower.gif" agent="curl/7.47.0"
filename="flower.gif" filesize=1209 profile="test-dlp"
```

The following is an example of a DLP log sent in CEF format to a syslog server:

```
Dec 27 14:29:36 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|24576|utm:dlp dlp
block|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0954024576 cat=utm:dlp
FTNTFGTsubtype=dlp FTNTFGTeventtype=dlp FTNTFGTlevel=warning FTNTFGTvd=vdom1
FTNTFGTeventtime=1545949776 FTNTFGTfilteridx=1 FTNTFGTdlpeextra=test-dlp3
FTNTFGTfiltertype=file-type FTNTFGTfiltercat=file FTNTFGTseverity=medium
FTNTFGTpolicyid=1 externalId=12680 FTNTFGTepoch=418303178 FTNTFGTeventid=0 duser=bob
src=10.1.100.11 spt=33638 deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined
dst=172.18.62.158 dpt=80 deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined
proto=6 app=HTTP FTNTFGTfiletype=gif deviceDirection=0 act=block dhost=172.18.62.158
request=/dlp/flower.gif requestClientApplication=curl/7.47.0 fname=flower.gif
fsize=1209 FTNTFGTprofile=test-dlp
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
filename	fname

## Application log support for CEF

The following is an example of an application log on the FortiGate disk:

```

date=2018-12-27 time=14:28:08 logid="1059028704" type="utm" subtype="app-ctrl"
eventtype="app-ctrl-all" level="information" vd="vdom1" eventtime=1545949688
appid=34050 srcip=10.1.100.11 dstip=104.80.89.24 srcport=56826 dstport=80
srcintf="port12" srcintfrole="undefined" dstintf="port11" dstintfrole="undefined"
proto=6 service="HTTP" direction="outgoing" policyid=1 sessionid=12567 applist="g-
default" appcat="Web.Client" app="HTTP.BROWSER_Firefox" action="pass"
hostname="detectportal.firefox.com" incidentserialno=1702350499 url="/success.txt"
msg="Web.Client: HTTP.BROWSER_Firefox," apprisk="elevated"

```

The following is an example of an application sent in CEF format to a syslog server:

```

Dec 27 14:28:08 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|28704|utm:app-ctrl app-ctrl-all
pass|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1059028704 cat=utm:app-ctrl
FTNTFGTsubtype=app-ctrl FTNTFGTeventtype=app-ctrl-all FTNTFGTlevel=information
FTNTFGTvd=vdom1 FTNTFGTeventtime=1545949688 FTNTFGTappid=34050 src=10.1.100.11
dst=104.80.89.24 spt=56826 dpt=80 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined deviceOutboundInterface=port11
FTNTFGTdstintfrole=undefined proto=6 app=HTTP deviceDirection=1 FTNTFGTpolicyid=1
externalId=12567 FTNTFGTapplist=g-default FTNTFGTappcat=Web.Client
FTNTFGTapp=HTTP.BROWSER_Firefox act=pass dhost=detectportal.firefox.com
FTNTFGTincidentserialno=1702350499 request=/success.txt msg=Web.Client: HTTP.BROWSER_
Firefox, FTNTFGTapprisk=elevated

```

## WAF log support for CEF

The following is an example of an WAF log on the FortiGate disk:

```

date=2018-12-27 time=14:55:20 logid="1203030258" type="utm" subtype="waf" eventtype="waf-
http-constraint" level="warning" vd="vdom1" eventtime=1545951320 policyid=1
sessionid=13614 user="bob" profile="waf_test" srcip=10.1.100.11 srcport=57304
dstip=172.16.200.55 dstport=80 srcintf="port12" srcintfrole="lan" dstintf="port11"
dstintfrole="wan" proto=6 service="HTTP"
url="http://172.16.200.55/index.html?a=0123456789&b=0123456789&c=0123456789"
severity="medium" action="passthrough" direction="request" agent="curl/7.47.0"
constraint="url-param-num" rawdata="Method=GET|User-Agent=curl/7.47.0"

```

The following is an example of an WAF sent in CEF format to a syslog server:

```

Dec 27 14:55:20 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|30258|utm:waf waf-http-constraint
passthrough|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1203030258 cat=utm:waf
FTNTFGTsubtype=waf FTNTFGTeventtype=waf-http-constraint FTNTFGTlevel=warning
FTNTFGTvd=vdom1 FTNTFGTeventtime=1545951320 FTNTFGTpolicyid=1 externalId=13614
duser=bob FTNTFGTprofile=waf_test src=10.1.100.11 spt=57304 dst=172.16.200.55 dpt=80
deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan deviceOutboundInterface=port11
FTNTFGTdstintfrole=wan proto=6 app=HTTP
request=http://172.16.200.55/index.html?a\=0123456789&b\=0123456789&c\=0123456789
FTNTFGTseverity=medium act=passthrough deviceDirection=0
requestClientApplication=curl/7.47.0 FTNTFGTconstraint=url-param-num
FTNTFGTrawdata=Method\=GET|User-Agent\=curl/7.47.0

```

## DNS log support for CEF

The following is an example of an DNS log on the FortiGate disk:

```

date=2018-12-27 time=14:45:26 logid="1501054802" type="dns" subtype="dns-response"
level="notice" vd="vdom1" eventtime=1545950726 policyid=1 sessionid=13355 user="bob"
srcip=10.1.100.11 srcport=54621 srcintf="port12" srcintfrole="lan" dstip=172.16.200.55
dstport=53 dstintf="port11" dstintfrole="wan" proto=17 profile="default"
srcmac="a2:e9:00:ec:40:01" xid=5137 qname="detectportal.firefox.com" qtype="A"

```

```
qtypeval=1 qclass="IN" ipaddr="104.80.89.26, 104.80.89.24" msg="Domain is monitored"
action="pass" cat=52 catdesc="Information Technology"
```

The following is an example of an DNS sent in CEF format to a syslog server:

```
Dec 27 14:45:26 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|54802|dns:dns-response
pass|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1501054802 cat=dns:dns-response
FTNTFGTsubtype=dns-response FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545950726 FTNTFGTpolicyid=1 externalId=13355 duser=bob
src=10.1.100.11 spt=54621 deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan
dst=172.16.200.55 dpt=53 deviceOutboundInterface=port11 FTNTFGTdstintfrole=wan
proto=17 FTNTFGTprofile=default FTNTFGTsrcmac=a2:e9:00:ec:40:01 FTNTFGTxid=5137
FTNTFGTqname=detectportal.firefox.com FTNTFGTqtype=A FTNTFGTqtypeval=1
FTNTFGTqclass=IN FTNTFGTipaddr=104.80.89.26, 104.80.89.24 msg=Domain is monitored
act=pass FTNTFGTcat=52 FTNTFGTcatdesc=Information Technology
```

## SSH log support for CEF

The following is an example of an SSH log on the FortiGate disk:

```
date=2018-12-27 time=14:36:15 logid="1600061002" type="utm" subtype="ssh" eventtype="ssh-
command" level="notice" vd="vdom1" eventtime=1545950175 policyid=1 sessionid=12921
user="bob" profile="test-ssh" srcip=10.1.100.11 srcport=56698 dstip=172.16.200.55
dstport=22 srcintf="port12" srcintfrole="lan" dstintf="port11" dstintfrole="wan"
proto=6 action="passthrough" direction="outgoing" login="root" command="ls"
severity="low"
```

The following is an example of an SSH sent in CEF format to a syslog server:

```
Dec 27 14:36:15 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|61002|utm:ssh ssh-command
passthrough|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1600061002 cat=utm:ssh
FTNTFGTsubtype=ssh FTNTFGTeventtype=ssh-command FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545950175 FTNTFGTpolicyid=1 externalId=12921 duser=bob
FTNTFGTprofile=test-ssh src=10.1.100.11 spt=56698 dst=172.16.200.55 dpt=22
deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan deviceOutboundInterface=port11
FTNTFGTdstintfrole=wan proto=6 act=passthrough FTNTFGTlogin=root FTNTFGTcommand=ls
FTNTFGTseverity=low
```



# UTM Extended Logging

FortiOS 6.0.0 and later supports extended logging for UTM log types to reliable Syslog servers over TCP. Extended logging adds HTTP header information to the `rawdata` field in UTM log types. You must enable extended logging before you can use the feature.

When extended logging is enabled, the following HTTP header information can be added to the `rawdata` field in UTM logs:

- Method
- X-Forwarded-For
- Request-Content-Type | Response-Content-Type
- Referer
- User-Agent

The full `rawdata` field of 20KB is only sent to reliable Syslog servers. Other logging devices, such as disk, FortiAnalyzer, and UDP Syslog servers, receive the information, but only keep a maximum of 2KB total log length, including the `rawdata` field, and discard the rest of the extended log information.

## Enabling extended logging

You can enable extended logging for the following UTM profiles:

- antivirus
- application
- dlp
- ips
- waf
- webfilter

When you enable the `extended-log` option for UTM profiles, all HTTP header information for HTTP-deny traffic is logged.

When you enable the `web-extended-all-action-log-enable` option for webfilter profile, all HTTP header information for HTTP-allow traffic is logged.

## Extended logging option in UTM profiles

The `extended-log` option has been added to all UTM profiles, for example:

```
# webfilter profile
config webfilter profile
  edit "test-webfilter"
    set extended-log enable
    set web-extended-all-action-log enable
  next
end
# av profile
```

```
config antivirus profile
  edit "av-proxy-test"
    set extended-log enable
  next
end
# waf profile
config waf profile
  edit "test-waf"
    set extended-log enable
  next
end
```

## Syslog server mode

The Syslog server mode changed to `udp`, `reliable`, and `legacy-reliable`. You must set the mode to `reliable` to support extended logging, for example:

```
config log syslogd setting
  set status enable
  set server "<ip address>"
  set mode reliable
  set facility local6
end
```

## Example of an extended log

Following is an example extended log for a `utm` log type with a `webfilter` subtype for a reliable Syslog server. The `rawdata` field contains the extended log data.

```
Dec 18 15:40:15 10.6.30.254 date=2017-12-18 time=15:40:14 devname="600D-9"
devid="FGT6HD3915800120" logid="0316013056" type="utm" subtype="webfilter"
eventtype="ftgd_blk" level="warning" vd="vdom1" eventtime=1513640414 policyid=2
sessionid=440522 srcip=10.1.100.128 srcport=60995 srcintf="port2" srcintfrole="lan"
dstip=209.121.139.177 dstport=80 dstintf="port1" dstintfrole="wan" proto=6
service="HTTP" hostname="detectportal.firefox.com" profile="test-webfilter"
action="blocked" reqtype="direct" url="/success.txt" sentbyte=285 rcvdbyte=0
direction="outgoing" msg="URL belongs to a denied category in policy" method="domain"
cat=52 catdesc="Information Technology" crscore=30 crlevel="high"
rawdata="Method=GET|User-Agent=Mozilla/5.0 (Windows NT 6.1; rv:57.0) Gecko/20100101
Firefox/57.0"
```

# Log Messages

The following sections list the FortiOS 6.2.3 log messages by log ID number.

## Anomaly

### 18432 - LOGID\_ATTCK\_ANOMALY\_TCP\_UDP

**Message ID:** 18432

**Message Description:** LOGID\_ATTCK\_ANOMALY\_TCP\_UDP

**Message Meaning:** Attack detected by UCP/TCP anomaly

**Type:** Anomaly

**Category:** ANOMALY

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	4096
service	Name of Service	string	80
sessionid	Session ID	uint32	10
severity	Severity	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3

## 18433 - LOGID\_ATTCK\_ANOMALY\_ICMP

**Message ID:** 18433

**Message Description:** LOGID\_ATTCK\_ANOMALY\_ICMP

**Message Meaning:** Attack detected by ICMP anomaly

**Type:** Anomaly**Category:** ANOMALY**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
icmpcode	ICMP code	string	6
icmpid	ICMP ID	string	8
icmptype	ICMP Type	string	6
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	4096
service	Name of Service	string	80
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
severity	Severity	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3

## 18434 - LOGID\_ATTCK\_ANOMALY\_OTHERS

**Message ID:** 18434

**Message Description:** LOGID\_ATTCK\_ANOMALY\_OTHERS

**Message Meaning:** Attack detected by other anomaly

**Type:** Anomaly

**Category:** ANOMALY

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	4096
service	Name of Service	string	80
sessionid	Session ID	uint32	10
severity	Severity	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3

## App

### 28672 - LOGID\_APP\_CTRL\_IM\_BASIC

**Message ID:** 28672

**Message Description:** LOGID\_APP\_CTRL\_IM\_BASIC

**Message Meaning:** Application control IM-basic

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20



Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28673 - LOGID\_APP\_CTRL\_IM\_BASIC\_WITH\_STATUS

**Message ID:** 28673

**Message Description:** LOGID\_APP\_CTRL\_IM\_BASIC\_WITH\_STATUS

**Message Meaning:** Application control IM

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28674 - LOGID\_APP\_CTRL\_IM\_BASIC\_WITH\_COUNT

**Message ID:** 28674

**Message Description:** LOGID\_APP\_CTRL\_IM\_BASIC\_WITH\_COUNT

**Message Meaning:** Application control IM (chat message count)

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28675 - LOGID\_APP\_CTRL\_IM\_FILE

**Message ID:** 28675

**Message Description:** LOGID\_APP\_CTRL\_IM\_FILE

**Message Meaning:** Application control IM (file)

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28676 - LOGID\_APP\_CTRL\_IM\_CHAT

**Message ID:** 28676

**Message Description:** LOGID\_APP\_CTRL\_IM\_CHAT

**Message Meaning:** Application control IM (chat)

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28677 - LOGID\_APP\_CTRL\_IM\_CHAT\_BLOCK

**Message ID:** 28677

**Message Description:** LOGID\_APP\_CTRL\_IM\_CHAT\_BLOCK

**Message Meaning:** Application control IM (chat blocked)

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20



Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28678 - LOGID\_APP\_CTRL\_IM\_BLOCK

**Message ID:** 28678

**Message Description:** LOGID\_APP\_CTRL\_IM\_BLOCK

**Message Meaning:** Application control IM (blocked)

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28704 - LOGID\_APP\_CTRL\_IPS\_PASS

**Message ID:** 28704

**Message Description:** LOGID\_APP\_CTRL\_IPS\_PASS

**Message Meaning:** Application control (IPS) (pass)

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
authserver		string	32
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11

Log Field Name	Description	Data Type	Length
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 28705 - LOGID\_APP\_CTRL\_IPS\_BLOCK

**Message ID:** 28705

**Message Description:** LOGID\_APP\_CTRL\_IPS\_BLOCK

**Message Meaning:** Application control (IPS) (block)

**Type:** App

**Category:** SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
authserver		string	32
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128

Log Field Name	Description	Data Type	Length
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256

Log Field Name	Description	Data Type	Length
vd		string	32
vrf		uint8	3

## 28706 - LOGID\_APP\_CTRL\_IPS\_RESET

**Message ID:** 28706

**Message Description:** LOGID\_APP\_CTRL\_IPS\_RESET

**Message Meaning:** Application control (IPS) (reset)

**Type:** App

**Category:** SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
authserver		string	32
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8



Log Field Name	Description	Data Type	Length
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 28720 - LOGID\_APP\_CTRL\_SSH\_PASS

**Message ID:** 28720

**Message Description:** LOGID\_APP\_CTRL\_SSH\_PASS

**Message Meaning:** Application control IM (SSH) (pass)

**Type:** App

**Category:** SIGNATURE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28721 - LOGID\_APP\_CTRL\_SSH\_BLOCK

**Message ID:** 28721

**Message Description:** LOGID\_APP\_CTRL\_SSH\_BLOCK

**Message Meaning:** Application control IM (SSH) (block)

**Type:** App**Category:** SIGNATURE**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39

Log Field Name	Description	Data Type	Length
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28736 - LOGID\_APP\_CTRL\_PORT\_ENF

**Message ID:** 28736

**Message Description:** LOGID\_APP\_CTRL\_PORT\_ENF

**Message Meaning:** Application control port enforcement

**Type:** App

**Category:** PORT-VIOLATION

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
authserver		string	32
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10

Log Field Name	Description	Data Type	Length
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
service		string	80

Log Field Name	Description	Data Type	Length
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 28737 - LOGID\_APP\_CTRL\_PROTO\_ENF

**Message ID:** 28737

**Message Description:** LOGID\_APP\_CTRL\_PROTO\_ENF

**Message Meaning:** Application control protocol enforcement

**Type:** App

**Category:** PROTOCOL-VIOLATION

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10

Log Field Name	Description	Data Type	Length
applist		string	64
apprisk		string	16
authserver		string	32
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	36

Log Field Name	Description	Data Type	Length
profiletype		string	36
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## AV

### 8192 - MESGID\_INFECT\_WARNING

**Message ID:** 8192

**Message Description:** MESGID\_INFECT\_WARNING

**Message Meaning:** Infected file detected by the FortiGate unit and blocked



**Type:** AV**Category:** INFECTED**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256

Log Field Name	Description	Data Type	Length
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8193 - MESGID\_INFECT\_NOTIF

**Message ID:** 8193

**Message Description:** MESGID\_INFECT\_NOTIF

**Message Meaning:** Infected file detected by the FortiGate unit and it passed

**Type:** AV

**Category:** INFECTED

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8194 - MESGID\_INFECT\_MIME\_WARNING

**Message ID:** 8194

**Message Description:** MESGID\_INFECT\_MIME\_WARNING

**Message Meaning:** MIME header detected to have a virus and blocked

**Type:** AV

**Category:** INFECTED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256

Log Field Name	Description	Data Type	Length
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46

Log Field Name	Description	Data Type	Length
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8195 - MESGID\_INFECT\_MIME\_NOTIF

**Message ID:** 8195

**Message Description:** MESGID\_INFECT\_MIME\_NOTIF

**Message Meaning:** MIME header infected and passed

**Type:** AV**Category:** INFECTED**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128



Log Field Name	Description	Data Type	Length
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256

Log Field Name	Description	Data Type	Length
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8200 - MESGID\_MIME\_FILETYPE\_EXE\_WARNING

**Message ID:** 8200

**Message Description:** MESGID\_MIME\_FILETYPE\_EXE\_WARNING

**Message Meaning:** File is an executable (warning)

**Type:** AV

**Category:** FILETYPE-EXECUTABLE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
checksum		string	16
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 8201 - MESGID\_MIME\_FILETYPE\_EXE\_NOTIF

**Message ID:** 8201

**Message Description:** MESGID\_MIME\_FILETYPE\_EXE\_NOTIF

**Message Meaning:** File is an executable (notice)

**Type:** AV

**Category:** FILETYPE-EXECUTABLE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
checksum		string	16
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 8202 - MESGID\_AVQUERY\_WARNING

**Message ID:** 8202

**Message Description:** MESGID\_AVQUERY\_WARNING

**Message Meaning:** File reported infected by Outbreak Prevention (warning)

**Type:** AV

**Category:** OUTBREAK-PREVENTION

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5

Log Field Name	Description	Data Type	Length
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8203 - MESGID\_AVQUERY\_NOTIF

**Message ID:** 8203

**Message Description:** MESGID\_AVQUERY\_NOTIF

**Message Meaning:** File reported infected by Outbreak Prevention (notice)

**Type:** AV

**Category:** OUTBREAK-PREVENTION

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256



Log Field Name	Description	Data Type	Length
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46

Log Field Name	Description	Data Type	Length
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8204 - MESGID\_MIME\_AVQUERY\_WARNING

**Message ID:** 8204

**Message Description:** MESGID\_MIME\_AVQUERY\_WARNING

**Message Meaning:** MIME data reported infected by Outbreak Prevention (warning)

**Type:** AV**Category:** OUTBREAK-PREVENTION**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128

Log Field Name	Description	Data Type	Length
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256

Log Field Name	Description	Data Type	Length
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8205 - MESGID\_MIME\_AVQUERY\_NOTIF

**Message ID:** 8205

**Message Description:** MESGID\_MIME\_AVQUERY\_NOTIF

**Message Meaning:** MIME data reported infected by Outbreak Prevention (notice)

**Type:** AV

**Category:** OUTBREAK-PREVENTION

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5

Log Field Name	Description	Data Type	Length
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8212 - MESSAGESID\_MALWARE\_LIST\_WARNING

**Message ID:** 8212

**Message Description:** MESSAGESID\_MALWARE\_LIST\_WARNING

**Message Meaning:** File reported infected by external malware list (warning)

**Type:** AV

**Category:** MALWARE-LIST

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256

Log Field Name	Description	Data Type	Length
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46



Log Field Name	Description	Data Type	Length
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8213 - MESSAGESID\_MALWARE\_LIST\_NOTIF

**Message ID:** 8213

**Message Description:** MESSAGESID\_MALWARE\_LIST\_NOTIF

**Message Meaning:** File reported infected by external malware list (notice)

**Type:** AV**Category:** MALWARE-LIST**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128

Log Field Name	Description	Data Type	Length
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256

Log Field Name	Description	Data Type	Length
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8214 - MESGID\_MIME\_MALWARE\_LIST\_WARNING

**Message ID:** 8214

**Message Description:** MESGID\_MIME\_MALWARE\_LIST\_WARNING

**Message Meaning:** MIME data reported infected by external malware list (warning)

**Type:** AV

**Category:** MALWARE-LIST

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5

Log Field Name	Description	Data Type	Length
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8215 - MESSGID\_MIME\_MALWARE\_LIST\_NOTIF

**Message ID:** 8215

**Message Description:** MESSGID\_MIME\_MALWARE\_LIST\_NOTIF

**Message Meaning:** MIME data reported infected by external malware list (notice)

**Type:** AV

**Category:** MALWARE-LIST

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256

Log Field Name	Description	Data Type	Length
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46

Log Field Name	Description	Data Type	Length
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8448 - MESGID\_BLOCK\_WARNING

**Message ID:** 8448

**Message Description:** MESGID\_BLOCK\_WARNING

**Message Meaning:** FortiGate unit blocked a file because it contains a virus



**Type:** AV**Category:** FILENAME**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8450 - MESGID\_BLOCK\_MIME\_WARNING

**Message ID:** 8450

**Message Description:** MESGID\_BLOCK\_MIME\_WARNING

**Message Meaning:** FortiGate unit blocked a file because it contains a virus (MIME)

**Type:** AV

**Category:** MIMEFRAGMENTED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8451 - MESSAGES\_BLOCK\_MIME\_NOTIF

**Message ID:** 8451

**Message Description:** MESSAGES\_BLOCK\_MIME\_NOTIF

**Message Meaning:** FortiGate unit blocked a file because it contains a virus (MIME)

**Type:** AV

**Category:** MIMEFRACTURED

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8452 - MESGID\_BLOCK\_COMMAND

**Message ID:** 8452

**Message Description:** MESGID\_BLOCK\_COMMAND

**Message Meaning:** FortiGate unit blocked a virus command

**Type:** AV

**Category:** COMMAND-BLOCKED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64

Log Field Name	Description	Data Type	Length
authserver		string	32
command		string	16
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 8457 - MESSGID\_MMS\_CHECKSUM

**Message ID:** 8457

**Message Description:** MESSGID\_MMS\_CHECKSUM

**Message Meaning:** MMS content checksum blocked an infected file

**Type:** AV

**Category:** FILENAME

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32



Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8458 - MESGID\_MMS\_CHECKSUM\_NOTIF

**Message ID:** 8458

**Message Description:** MESGID\_MMS\_CHECKSUM\_NOTIF

**Message Meaning:** MMS content checksum was matched

**Type:** AV

**Category:** FILENAME

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256

Log Field Name	Description	Data Type	Length
vd	VDOM name	string	32
vrf		uint8	3

## 8704 - MESSAGESID\_OVERSIZE\_WARNING

**Message ID:** 8704

**Message Description:** MESSAGESID\_OVERSIZE\_WARNING

**Message Meaning:** Defined file size limit was exceeded

**Type:** AV

**Category:** OVERSIZE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8705 - MESSAGESID\_OVERSIZE\_NOTIF

**Message ID:** 8705

**Message Description:** MESSAGESID\_OVERSIZE\_NOTIF

**Message Meaning:** File size limit was exceeded

**Type:** AV

**Category:** OVERSIZE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8706 - MESGID\_OVERSIZE\_MIME\_WARNING

**Message ID:** 8706

**Message Description:** MESGID\_OVERSIZE\_MIME\_WARNING

**Message Meaning:** File (MIME) size exceed the defined size limit

**Type:** AV

**Category:** OVERSIZE**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5



Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8707 - MESGID\_OVERSIZE\_MIME\_NOTIF

**Message ID:** 8707

**Message Description:** MESGID\_OVERSIZE\_MIME\_NOTIF

**Message Meaning:** File (MIME) size exceed the defined size limit

**Type:** AV

**Category:** OVERSIZE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8708 - MESGID\_OVERSIZE\_STREAM\_UNCOMP\_WARNING

**Message ID:** 8708

**Message Description:** MESGID\_OVERSIZE\_STREAM\_UNCOMP\_WARNING

**Message Meaning:** stream-based uncompression reached size limit

**Type:** AV

**Category:** OVERSIZE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8709 - MESGID\_OVERSIZE\_STREAM\_UNCOMP\_NOTIF

**Message ID:** 8709

**Message Description:** MESGID\_OVERSIZE\_STREAM\_UNCOMP\_NOTIF

**Message Meaning:** stream-based uncompression reached size limit

**Type:** AV

**Category:** OVERSIZE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256

Log Field Name	Description	Data Type	Length
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8720 - MESGID\_SWITCH\_PROTO\_WARNING

**Message ID:** 8720

**Message Description:** MESGID\_SWITCH\_PROTO\_WARNING

**Message Meaning:** Switching protocols request (warning)

**Type:** AV

**Category:** SWITCHPROTO

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8721 - MESGID\_SWITCH\_PROTO\_NOTIF

**Message ID:** 8721

**Message Description:** MESGID\_SWITCH\_PROTO\_NOTIF

**Message Meaning:** Switching protocols request (notice)

**Type:** AV

**Category:** SWITCHPROTO

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32



Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8960 - MESGID\_SCAN\_UNCOMPSizeLIMIT\_WARNING

**Message ID:** 8960

**Message Description:** MESGID\_SCAN\_UNCOMPSizeLIMIT\_WARNING

**Message Meaning:** File reached the uncompressed nested limit

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8961 - MESGID\_SCAN\_UNCOMPSizeLIMIT\_NOTIF

**Message ID:** 8961

**Message Description:** MESGID\_SCAN\_UNCOMPSizeLIMIT\_NOTIF

**Message Meaning:** File reached the uncompressed size limit

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128

Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8962 - MESGID\_SCAN\_ARCHIVE\_ENCRYPTED\_WARNING

**Message ID:** 8962

**Message Description:** MESGID\_SCAN\_ARCHIVE\_ENCRYPTED\_WARNING

**Message Meaning:** Archived file is corrupted

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8963 - MESGID\_SCAN\_ARCHIVE\_ENCRYPTED\_NOTIF

**Message ID:** 8963

**Message Description:** MESGID\_SCAN\_ARCHIVE\_ENCRYPTED\_NOTIF

**Message Meaning:** Archived file is encrypted

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8964 - MESGID\_SCAN\_ARCHIVE\_CORRUPTED\_WARNING

**Message ID:** 8964

**Message Description:** MESGID\_SCAN\_ARCHIVE\_CORRUPTED\_WARNING

**Message Meaning:** Corrupted archive (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128

Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8965 - MESGID\_SCAN\_ARCHIVE\_CORRUPTED\_NOTIF

**Message ID:** 8965

**Message Description:** MESGID\_SCAN\_ARCHIVE\_CORRUPTED\_NOTIF

**Message Meaning:** Corrupted archive (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8966 - MESGID\_SCAN\_ARCHIVE\_MULTIPART\_WARNING

**Message ID:** 8966

**Message Description:** MESGID\_SCAN\_ARCHIVE\_MULTIPART\_WARNING

**Message Meaning:** File is a multipart archive or contains multiple files within the archive

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13



Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8967 - MESGID\_SCAN\_ARCHIVE\_MULTIPART\_NOTIF

**Message ID:** 8967

**Message Description:** MESGID\_SCAN\_ARCHIVE\_MULTIPART\_NOTIF

**Message Meaning:** File is a multipart archive or contains multiple files within the archive

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128

Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8968 - MESGID\_SCAN\_ARCHIVE\_NESTED\_WARNING

**Message ID:** 8968

**Message Description:** MESGID\_SCAN\_ARCHIVE\_NESTED\_WARNING

**Message Meaning:** File is a nested archived file

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8969 - MESGID\_SCAN\_ARCHIVE\_NESTED\_NOTIF

**Message ID:** 8969

**Message Description:** MESGID\_SCAN\_ARCHIVE\_NESTED\_NOTIF

**Message Meaning:** File is an archived type unhandled

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512



Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8970 - MESGID\_SCAN\_ARCHIVE\_OVERSIZE\_WARNING

**Message ID:** 8970

**Message Description:** MESGID\_SCAN\_ARCHIVE\_OVERSIZE\_WARNING

**Message Meaning:** Archived file is oversized

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128

Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8971 - MESGID\_SCAN\_ARCHIVE\_OVERSIZE\_NOTIF

**Message ID:** 8971

**Message Description:** MESGID\_SCAN\_ARCHIVE\_OVERSIZE\_NOTIF

**Message Meaning:** Archived file is oversized

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8972 - MESGID\_SCAN\_ARCHIVE\_UNHANDLED\_WARNING

**Message ID:** 8972

**Message Description:** MESGID\_SCAN\_ARCHIVE\_UNHANDLED\_WARNING

**Message Meaning:** Unhandled archive (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8973 - MESGID\_SCAN\_ARCHIVE\_UNHANDLED\_NOTIF

**Message ID:** 8973

**Message Description:** MESGID\_SCAN\_ARCHIVE\_UNHANDLED\_NOTIF

**Message Meaning:** Unhandled archive (notice)

**Type:** AV

**Category:** SCANERROR



**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128

Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8974 - MESGID\_SCAN\_AV\_ENGINE\_LOAD\_FAILED\_ERROR

**Message ID:** 8974

**Message Description:** MESGID\_SCAN\_AV\_ENGINE\_LOAD\_FAILED\_ERROR

**Message Meaning:** AV Engine load failed

**Type:** AV

**Category:** SCANERROR

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8975 - MESGID\_SCAN\_ARCHIVE\_PARTIALLYCORRUPTED\_WARNING

**Message ID:** 8975

**Message Description:** MESGID\_SCAN\_ARCHIVE\_PARTIALLYCORRUPTED\_WARNING

**Message Meaning:** Partially corrupted archive (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8976 - MESGID\_SCAN\_ARCHIVE\_PARTIALLYCORRUPTED\_NOTIF

**Message ID:** 8976

**Message Description:** MESGID\_SCAN\_ARCHIVE\_PARTIALLYCORRUPTED\_NOTIF

**Message Meaning:** Partially corrupted archive (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128

Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8977 - MESGID\_SCAN\_ARCHIVE\_FILESLIMIT\_WARNING

**Message ID:** 8977

**Message Description:** MESGID\_SCAN\_ARCHIVE\_FILESLIMIT\_WARNING

**Message Meaning:** Exceeded archive files limit (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8978 - MESGID\_SCAN\_ARCHIVE\_FILESLIMIT\_NOTIF

**Message ID:** 8978

**Message Description:** MESGID\_SCAN\_ARCHIVE\_FILESLIMIT\_NOTIF

**Message Meaning:** Exceeded archive files limit (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8979 - MESGID\_SCAN\_ARCHIVE\_TIMEOUT\_WARNING

**Message ID:** 8979

**Message Description:** MESGID\_SCAN\_ARCHIVE\_TIMEOUT\_WARNING

**Message Meaning:** Archive scan timeout (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128



Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8980 - MESGID\_SCAN\_ARCHIVE\_TIMEOUT\_NOTIF

**Message ID:** 8980

**Message Description:** MESGID\_SCAN\_ARCHIVE\_TIMEOUT\_NOTIF

**Message Meaning:** Archive scan timeout (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9233 - MESSAGES\_ANALYTICS\_SUBMITTED

**Message ID:** 9233

**Message Description:** MESSAGES\_ANALYTICS\_SUBMITTED

**Message Meaning:** File submitted to Sandbox

**Type:** AV

**Category:** ANALYTICS

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9234 - MESGID\_ANALYTICS\_INFECT\_WARNING

**Message ID:** 9234

**Message Description:** MESGID\_ANALYTICS\_INFECT\_WARNING

**Message Meaning:** File reported infected by FortiSandbox (warning)

**Type:** AV

**Category:** INFECTED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128

Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9235 - MESGID\_ANALYTICS\_INFECT\_NOTIF

**Message ID:** 9235

**Message Description:** MESGID\_ANALYTICS\_INFECT\_NOTIF

**Message Meaning:** File reported infected by FortiSandbox (notice)

**Type:** AV

**Category:** INFECTED

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9236 - MESGID\_ANALYTICS\_INFECT\_MIME\_WARNING

**Message ID:** 9236

**Message Description:** MESGID\_ANALYTICS\_INFECT\_MIME\_WARNING

**Message Meaning:** File reported infected by FortiSandbox (warning)

**Type:** AV

**Category:** INFECTED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9237 - MESGID\_ANALYTICS\_INFECT\_MIME\_NOTIF

**Message ID:** 9237

**Message Description:** MESGID\_ANALYTICS\_INFECT\_MIME\_NOTIF

**Message Meaning:** File reported infected by FortiSandbox (notice)

**Type:** AV

**Category:** INFECTED

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128

Log Field Name	Description	Data Type	Length
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9238 - MESGID\_ANALYTICS\_FSA\_RESULT

**Message ID:** 9238

**Message Description:** MESGID\_ANALYTICS\_FSA\_RESULT

**Message Meaning:** File verdict returned from FortiSandbox

**Type:** AV

**Category:** ANALYTICS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
analyticscksum	The checksum of the file submitted for analytics	string	64
date	Date	string	10
devid		string	16
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
fsaverdict		string	32
level	Log level	string	11
logid	Log ID	string	10
service	Proxy service which scanned this traffic	string	5
srcdomain		string	255
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
vd	VDOM name	string	32

## 9239 - MESGID\_CONTENT\_DISARM\_NOTIF

**Message ID:** 9239

**Message Description:** MESGID\_CONTENT\_DISARM\_NOTIF

**Message Meaning:** Active content detected by Content Disarm engine

**Type:** AV

**Category:** CONTENT-DISARM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
analyticscksum		string	64
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39



Log Field Name	Description	Data Type	Length
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 9240 - MESSID\_CONTENT\_DISARM\_WARNING

**Message ID:** 9240

**Message Description:** MESSID\_CONTENT\_DISARM\_WARNING

**Message Meaning:** File was disarmed by Content Disarm engine

**Type:** AV

**Category:** CONTENT-DISARM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
analyticscksum		string	64
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39

Log Field Name	Description	Data Type	Length
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## CIFS

### 63000 - LOG\_ID\_CIFS\_FILE\_BLOCK

**Message ID:** 63000

**Message Description:** LOG\_ID\_CIFS\_FILE\_BLOCK

**Message Meaning:** File was blocked by file filter

**Type:** CIFS

**Category:** CIFS-FILEFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
domainctrlauthstate		uint32	5
domainctrlauthtype		uint32	5
domainctrldomain		string	80
domainctrlip		ip	39
domainctrlname		string	64
domainctrlprotocoltype		uint32	5
domainctrlusername		string	65
dstintf		string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip		ip	39
dstport		uint16	5
errorcode		string	20
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
service		string	5
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
vd		string	32

## 63001 - LOG\_ID\_CIFS\_FILE\_PASS

**Message ID:** 63001

**Message Description:** LOG\_ID\_CIFS\_FILE\_PASS

**Message Meaning:** File detected by file-type filter

**Type:** CIFS

**Category:** CIFS-FILEFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
domainctrlauthstate		uint32	5
domainctrlauthtype		uint32	5
domainctrldomain		string	80
domainctrlip		ip	39
domainctrlname		string	64
domainctrlprotocoltype		uint32	5
domainctrlusername		string	65
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
errorcode		string	20
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
service		string	5
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8

Log Field Name	Description	Data Type	Length
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
vd		string	32

## DLP

### 24576 - LOG\_ID\_DLP\_WARN

**Message ID:** 24576

**Message Description:** LOG\_ID\_DLP\_WARN

**Message Meaning:** Data leak detected by specified DLP sensor rule

**Type:** DLP

**Category:** DLP

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	DLP event type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
infectedfilelevel		uint32	10
infectedfilename		string	256
infectedfilesize		uint64	10
infectedfiletype		string	23
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcdomain		string	255
srcintf	Source Interface	string	32



Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subservice		string	16
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 24577 - LOG\_ID\_DLP\_NOTIF

**Message ID:** 24577

**Message Description:** LOG\_ID\_DLP\_NOTIF

**Message Meaning:** Data leak detected by specified DLP sensor rule

**Type:** DLP

**Category:** DLP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
infectedfilelevel		uint32	10
infectedfilename		string	256
infectedfilesize		uint64	10
infectedfiletype		string	23
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subservice		string	16
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 24578 - LOG\_ID\_DLP\_DOC\_SOURCE

**Message ID:** 24578

**Message Description:** LOG\_ID\_DLP\_DOC\_SOURCE

**Message Meaning:** DLP fingerprint document source notice

**Type:** DLP

**Category:** DLP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
dlpextra	DLP extra information	string	256
docsource	DLP fingerprint document source	string	515
eventtime		uint64	20
eventtype	DLP event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
sensitivity	Sensitivity for document fingerprint	string	36
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
tz		string	5
vd	Virtual domain name	string	32

## 24579 - LOG\_ID\_DLP\_DOC\_SOURCE\_ERROR

**Message ID:** 24579

**Message Description:** LOG\_ID\_DLP\_DOC\_SOURCE\_ERROR

**Message Meaning:** DLP fingerprint document source error

**Type:** DLP

**Category:** DLP

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
dlpextra	DLP extra information	string	256

Log Field Name	Description	Data Type	Length
docsource	DLP fingerprint document source	string	515
eventtime		uint64	20
eventtype	DLP event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
sensitivity	Sensitivity for document fingerprint	string	36
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
tz		string	5
vd	Virtual domain name	string	32

## DNS

### 54000 - LOG\_ID\_DNS\_QUERY

**Message ID:** 54000

**Message Description:** LOG\_ID\_DNS\_QUERY

**Message Meaning:** DNS query message

**Type:** DNS

**Category:** DNS-QUERY

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype		string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54200 - LOG\_ID\_DNS\_RESOLV\_ERROR

**Message ID:** 54200

**Message Description:** LOG\_ID\_DNS\_RESOLV\_ERROR

**Message Meaning:** DNS resolution error message

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32

Log Field Name	Description	Data Type	Length
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54400 - LOG\_ID\_DNS\_URL\_FILTER\_BLOCK

**Message ID:** 54400

**Message Description:** LOG\_ID\_DNS\_URL\_FILTER\_BLOCK

**Message Meaning:** Domain blocked because it is in the domain-filter list

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning



Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54401 - LOG\_ID\_DNS\_URL\_FILTER\_ALLOW

**Message ID:** 54401

**Message Description:** LOG\_ID\_DNS\_URL\_FILTER\_ALLOW

**Message Meaning:** Domain allowed because it is in the domain-filter list

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39

Log Field Name	Description	Data Type	Length
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54600 - LOG\_ID\_DNS\_BOTNET\_IP

**Message ID:** 54600

**Message Description:** LOG\_ID\_DNS\_BOTNET\_IP

**Message Meaning:** Domain blocked by DNS botnet C&C (IP)

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54601 - LOG\_ID\_DNS\_BOTNET\_DOMAIN

**Message ID:** 54601

**Message Description:** LOG\_ID\_DNS\_BOTNET\_DOMAIN

**Message Meaning:** Domain blocked by DNS botnet C&C (Domain)

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54800 - LOG\_ID\_DNS\_FTGD\_WARNING

**Message ID:** 54800

**Message Description:** LOG\_ID\_DNS\_FTGD\_WARNING

**Message Meaning:** FortiGuard rating error warning

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39



Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54801 - LOG\_ID\_DNS\_FTGD\_ERROR

**Message ID:** 54801

**Message Description:** LOG\_ID\_DNS\_FTGD\_ERROR

**Message Meaning:** FortiGuard rating error occurred

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54802 - LOG\_ID\_DNS\_FTGD\_CAT\_ALLOW

**Message ID:** 54802

**Message Description:** LOG\_ID\_DNS\_FTGD\_CAT\_ALLOW

**Message Meaning:** Domain is monitored

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32

Log Field Name	Description	Data Type	Length
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54803 - LOG\_ID\_DNS\_FTGD\_CAT\_BLOCK

**Message ID:** 54803

**Message Description:** LOG\_ID\_DNS\_FTGD\_CAT\_BLOCK

**Message Meaning:** Domain belongs to a denied category in policy

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54804 - LOG\_ID\_DNS\_SAFE\_SEARCH

**Message ID:** 54804

**Message Description:** LOG\_ID\_DNS\_SAFE\_SEARCH

**Message Meaning:** DNS Safe Search enforced

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5



Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## Email

### 20480 - LOGID\_ANTISPAM\_EMAIL\_SMTP\_NOTIF

**Message ID:** 20480

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_SMTP\_NOTIF

**Message Meaning:** SMTP warning

**Type:** Email

**Category:** SMTP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguareesp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20481 - LOGID\_ANTISPAM\_EMAIL\_SMTP\_BWORD\_NOTIF

**Message ID:** 20481

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_SMTP\_BWORD\_NOTIF

**Message Meaning:** SMTP warning

**Type:** Email

**Category:** SMTP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128

Log Field Name	Description	Data Type	Length
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20482 - LOGID\_ANTISPAM\_EMAIL\_POP3\_NOTIF

**Message ID:** 20482

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_POP3\_NOTIF

**Message Meaning:** POP3 warning

**Type:** Email

**Category:** POP3

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16

Log Field Name	Description	Data Type	Length
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20483 - LOGID\_ANTISPAM\_EMAIL\_POP3\_BWORD\_NOTIF

**Message ID:** 20483

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_POP3\_BWORD\_NOTIF

**Message Meaning:** POP3 notice

**Type:** Email

**Category:** POP3

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5



Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20484 - LOGID\_ANTISPAM\_EMAIL\_IMAP\_NOTIF

**Message ID:** 20484

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_IMAP\_NOTIF

**Message Meaning:** IMAP notice

**Type:** Email

**Category:** IMAP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20485 - LOGID\_ANTISPAM\_ENDPOINT\_FILTER\_WARNING

**Message ID:** 20485

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_FILTER\_WARNING

**Message Meaning:** Endpoint filter warning

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20486 - LOGID\_ANTISPAM\_ENDPOINT\_FILTER\_NOTIF

**Message ID:** 20486

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_FILTER\_NOTIF

**Message Meaning:** Endpoint filter notice

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20487 - LOGID\_ANTISPAM\_ENDPOINT\_MM7\_WARNING

**Message ID:** 20487

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_MM7\_WARNING

**Message Meaning:** MM7 warning

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3

Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20488 - LOGID\_ANTISPAM\_ENDPOINT\_MM7\_NOTIF

**Message ID:** 20488

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_MM7\_NOTIF

**Message Meaning:** MM7 notice

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20489 - LOGID\_ANTISPAM\_ENDPOINT\_MM1\_WARNING

**Message ID:** 20489

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_MM1\_WARNING

**Message Meaning:** MM1 warning

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20490 - LOGID\_ANTISPAM\_ENDPOINT\_MM1\_NOTIF

**Message ID:** 20490

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_MM1\_NOTIF

**Message Meaning:** MM1 notice

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20491 - LOGID\_ANTISPAM\_EMAIL\_IMAP\_BWORD\_NOTIF

**Message ID:** 20491

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_IMAP\_BWORD\_NOTIF

**Message Meaning:** IMAP banned word notice

**Type:** Email

**Category:** IMAP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512

Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

**20492 - LOGID\_ANTISPAM\_MM1\_FLOOD\_WARNING****Message ID:** 20492**Message Description:** LOGID\_ANTISPAM\_MM1\_FLOOD\_WARNING**Message Meaning:** MM1 flood detection warning**Type:** Email**Category:** MASS-MMS**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512



Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20493 - LOGID\_ANTISPAM\_MM1\_FLOOD\_NOTIF

**Message ID:** 20493

**Message Description:** LOGID\_ANTISPAM\_MM1\_FLOOD\_NOTIF

**Message Meaning:** MM1 flood detection notice

**Type:** Email

**Category:** MASS-MMS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20494 - LOGID\_ANTISPAM\_MM4\_FLOOD\_WARNING

**Message ID:** 20494

**Message Description:** LOGID\_ANTISPAM\_MM4\_FLOOD\_WARNING

**Message Meaning:** MM4 flood detection warning

**Type:** Email

**Category:** MASS-MMS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3

Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20495 - LOGID\_ANTISPAM\_MM4\_FLOOD\_NOTIF

**Message ID:** 20495

**Message Description:** LOGID\_ANTISPAM\_MM4\_FLOOD\_NOTIF

**Message Meaning:** MM4 flood detection notice

**Type:** Email

**Category:** MASS-MMS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20496 - LOGID\_ANTISPAM\_MM1\_DUPE\_WARNING

**Message ID:** 20496

**Message Description:** LOGID\_ANTISPAM\_MM1\_DUPE\_WARNING

**Message Meaning:** MM1 duplicate detection warning

**Type:** Email

**Category:** MASS-MMS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512



Log Field Name	Description	Data Type	Length
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20497 - LOGID\_ANTISPAM\_MM1\_DUPE\_NOTIF

**Message ID:** 20497

**Message Description:** LOGID\_ANTISPAM\_MM1\_DUPE\_NOTIF

**Message Meaning:** MM1 duplicate detection notice

**Type:** Email

**Category:** MASS-MMS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20498 - LOGID\_ANTISPAM\_MM4\_DUPE\_WARNING

**Message ID:** 20498

**Message Description:** LOGID\_ANTISPAM\_MM4\_DUPE\_WARNING

**Message Meaning:** MM4 duplicate detection warning

**Type:** Email

**Category:** MASS-MMS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512

Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

**20499 - LOGID\_ANTISPAM\_MM4\_DUPE\_NOTIF****Message ID:** 20499**Message Description:** LOGID\_ANTISPAM\_MM4\_DUPE\_NOTIF**Message Meaning:** MM4 duplicate detection notice**Type:** Email**Category:** MASS-MMS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20500 - LOGID\_ANTISPAM\_EMAIL\_MSN\_NOTIF

**Message ID:** 20500

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_MSN\_NOTIF

**Message Meaning:** MSN Hotmail email message

**Type:** Email

**Category:** MSN-HOTMAIL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20501 - LOGID\_ANTISPAM\_EMAIL\_YAHOO\_NOTIF

**Message ID:** 20501

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_YAHOO\_NOTIF

**Message Meaning:** Yahoo! email message

**Type:** Email

**Category:** YAHOO-MAIL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3



Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20502 - LOGID\_ANTISPAM\_EMAIL\_GOOGLE\_NOTIF

**Message ID:** 20502

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_GOOGLE\_NOTIF

**Message Meaning:** Gmail email message

**Type:** Email

**Category:** GMAIL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20503 - LOGID\_EMAIL\_SMTP\_GENERAL\_NOTIF

**Message ID:** 20503

**Message Description:** LOGID\_EMAIL\_SMTP\_GENERAL\_NOTIF

**Message Meaning:** SMTP warning

**Type:** Email

**Category:** SMTP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20504 - LOGID\_EMAIL\_POP3\_GENERAL\_NOTIF

**Message ID:** 20504

**Message Description:** LOGID\_EMAIL\_POP3\_GENERAL\_NOTIF

**Message Meaning:** POP3 warning

**Type:** Email

**Category:** POP3

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20505 - LOGID\_EMAIL\_IMAP\_GENERAL\_NOTIF

**Message ID:** 20505

**Message Description:** LOGID\_EMAIL\_IMAP\_GENERAL\_NOTIF

**Message Meaning:** IMAP notice

**Type:** Email

**Category:** IMAP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512



Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

**20506 - LOGID\_EMAIL\_MAPI\_GENERAL\_NOTIF****Message ID:** 20506**Message Description:** LOGID\_EMAIL\_MAPI\_GENERAL\_NOTIF**Message Meaning:** MAPI notice**Type:** Email**Category:** MAPI**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20507 - LOGID\_ANTISPAM\_EMAIL\_MAPI\_BWORD\_NOTIF

**Message ID:** 20507

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_MAPI\_BWORD\_NOTIF

**Message Meaning:** MAPI banned word notice

**Type:** Email

**Category:** MAPI

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20508 - LOGID\_ANTISPAM\_EMAIL\_MAPI\_NOTIF

**Message ID:** 20508

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_MAPI\_NOTIF

**Message Meaning:** MAPI email message

**Type:** Email

**Category:** MAPI

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3

Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20509 - LOGID\_ANTISPAM\_FTGD\_ERR

**Message ID:** 20509

**Message Description:** LOGID\_ANTISPAM\_FTGD\_ERR

**Message Meaning:** FortiGuard error message

**Type:** Email

**Category:** FTGD\_ERR

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	8
agent		string	64
attachment		string	3
authserver		string	32
banword		string	128
cc		string	4096
date		string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
fortiguardresp		string	512
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	64
proto		uint8	3
recipient		string	512
sender		string	128
service		string	36
sessionid		uint32	10
size		string	16
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subject		string	256
subtype		string	20



Log Field Name	Description	Data Type	Length
time		string	8
to		string	512
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## Event

### 20002 - LOG\_ID\_DOMAIN\_UNRESOLVABLE

**Message ID:** 20002

**Message Description:** LOG\_ID\_DOMAIN\_UNRESOLVABLE

**Message Meaning:** Domain name of alert email sender unresolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20003 - LOG\_ID\_MAIL\_SENT\_FAIL

**Message ID:** 20003

**Message Description:** LOG\_ID\_MAIL\_SENT\_FAIL

**Message Meaning:** Alert email send status failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20004 - LOG\_ID\_POLICY\_TOO\_BIG

**Message ID:** 20004

**Message Description:** LOG\_ID\_POLICY\_TOO\_BIG

**Message Meaning:** Policy too big for installation

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20005 - LOG\_ID\_PPP\_LINK\_UP

**Message ID:** 20005

**Message Description:** LOG\_ID\_PPP\_LINK\_UP

**Message Meaning:** Modem PPP link up

**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20006 - LOG\_ID\_PPP\_LINK\_DOWN

**Message ID:** 20006**Message Description:** LOG\_ID\_PPP\_LINK\_DOWN**Message Meaning:** Modem PPP link down**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20007 - LOG\_ID\_SOCKET\_EXHAUSTED

**Message ID:** 20007

**Message Description:** LOG\_ID\_SOCKET\_EXHAUSTED

**Message Meaning:** NAT port exhausted

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
nat	NAT IP Address	ip	39
proto	Protocol Number	uint8	3
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vrf		uint8	3

## 20008 - LOG\_ID\_POLICY6\_TOO\_BIG

**Message ID:** 20008

**Message Description:** LOG\_ID\_POLICY6\_TOO\_BIG

**Message Meaning:** IPv6 policy too big for installation

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20010 - LOG\_ID\_KERNEL\_ERROR

**Message ID:** 20010

**Message Description:** LOG\_ID\_KERNEL\_ERROR

**Message Meaning:** Kernel error

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20016 - LOG\_ID\_MODEM\_EXCEED\_REDIAL\_COUNT

**Message ID:** 20016

**Message Description:** LOG\_ID\_MODEM\_EXCEED\_REDIAL\_COUNT

**Message Meaning:** Modem exceeded redial limit

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20017 - LOG\_ID\_MODEM\_FAIL\_TO\_OPEN

**Message ID:** 20017

**Message Description:** LOG\_ID\_MODEM\_FAIL\_TO\_OPEN

**Message Meaning:** Modem failed to open

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32



## 20020 - LOG\_ID\_MODEM\_USB\_DETECTED

**Message ID:** 20020

**Message Description:** LOG\_ID\_MODEM\_USB\_DETECTED

**Message Meaning:** USB modem detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20021 - LOG\_ID\_MAIL\_RESENT

**Message ID:** 20021

**Message Description:** LOG\_ID\_MAIL\_RESENT

**Message Meaning:** Alert email resent

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
count	Count	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20022 - LOG\_ID\_MODEM\_USB\_REMOVED

**Message ID:** 20022

**Message Description:** LOG\_ID\_MODEM\_USB\_REMOVED

**Message Meaning:** USB modem removed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20023 - LOG\_ID\_MODEM\_USBLTE\_DETECTED

**Message ID:** 20023

**Message Description:** LOG\_ID\_MODEM\_USBLTE\_DETECTED

**Message Meaning:** USB LTE modem detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20024 - LOG\_ID\_MODEM\_USBLTE\_REMOVED

**Message ID:** 20024

**Message Description:** LOG\_ID\_MODEM\_USBLTE\_REMOVED

**Message Meaning:** USB LTE modem removed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20025 - LOG\_ID\_REPORTD\_REPORT\_SUCCESS

**Message ID:** 20025

**Message Description:** LOG\_ID\_REPORTD\_REPORT\_SUCCESS

**Message Meaning:** Report generated successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
datarange	data range for reports	string	50
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
file	File Name for Generated Report?	string	256

Log Field Name	Description	Data Type	Length
filesize	Report File Size in Bytes	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
processtime	process time for reports	uint32	10
reporttype	Report Type	string	20
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20026 - LOG\_ID\_REPORTD\_REPORT\_FAILURE

**Message ID:** 20026

**Message Description:** LOG\_ID\_REPORTD\_REPORT\_FAILURE

**Message Meaning:** Report generation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20027 - LOG\_ID\_REPORT\_DEL\_OLD\_REC

**Message ID:** 20027

**Message Description:** LOG\_ID\_REPORT\_DEL\_OLD\_REC

**Message Meaning:** Outdated report files deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20028 - LOG\_ID\_REPORT\_RECREATE\_DB

**Message ID:** 20028

**Message Description:** LOG\_ID\_REPORT\_RECREATE\_DB

**Message Meaning:** Report database recreated

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20031 - LOG\_ID\_RAD\_OUT\_OF\_MEM

**Message ID:** 20031**Message Description:** LOG\_ID\_RAD\_OUT\_OF\_MEM**Message Meaning:** RADVD out of memory**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20032 - LOG\_ID\_RAD\_NOT\_FOUND

**Message ID:** 20032

**Message Description:** LOG\_ID\_RAD\_NOT\_FOUND

**Message Meaning:** RADVD interface not found

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20033 - LOG\_ID\_RAD\_MOBILE\_IPV6

**Message ID:** 20033

**Message Description:** LOG\_ID\_RAD\_MOBILE\_IPV6

**Message Meaning:** RADVD mobile IPv6 extensions used

**Type:** Event



**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20034 - LOG\_ID\_RAD\_IPV6\_OUT\_OF\_RANGE

**Message ID:** 20034**Message Description:** LOG\_ID\_RAD\_IPV6\_OUT\_OF\_RANGE**Message Meaning:** RADVD mobile IPv6 MinRtrAdvInterval out of range**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20035 - LOG\_ID\_RAD\_MIN\_OUT\_OF\_RANGE

**Message ID:** 20035

**Message Description:** LOG\_ID\_RAD\_MIN\_OUT\_OF\_RANGE

**Message Meaning:** RADVD MinRtrAdvInterval out of range

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20036 - LOG\_ID\_RAD\_MAX\_OUT\_OF\_RANGE

**Message ID:** 20036

**Message Description:** LOG\_ID\_RAD\_MAX\_OUT\_OF\_RANGE

**Message Meaning:** RADVD mobile IPv6 MaxRtrAdvInterval out of range

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20037 - LOG\_ID\_RAD\_MAX\_ADV\_OUT\_OF\_RANGE

**Message ID:** 20037**Message Description:** LOG\_ID\_RAD\_MAX\_ADV\_OUT\_OF\_RANGE**Message Meaning:** RADVD MaxRtrAdvInterval out of range**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20039 - LOG\_ID\_RAD\_MTU\_TOO\_SMALL

**Message ID:** 20039

**Message Description:** LOG\_ID\_RAD\_MTU\_TOO\_SMALL

**Message Meaning:** RADVD AdvLinkMTU too small

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20040 - LOG\_ID\_RAD\_TIME\_TOO\_SMALL

**Message ID:** 20040

**Message Description:** LOG\_ID\_RAD\_TIME\_TOO\_SMALL

**Message Meaning:** RADVD AdvReachableTime too small

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20041 - LOG\_ID\_RAD\_HOP\_OUT\_OF\_RANGE

**Message ID:** 20041**Message Description:** LOG\_ID\_RAD\_HOP\_OUT\_OF\_RANGE**Message Meaning:** RADVD AdvCurHopLimit too big**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20042 - LOG\_ID\_RAD\_DFT\_HOP\_OUT\_OF\_RANGE

**Message ID:** 20042

**Message Description:** LOG\_ID\_RAD\_DFT\_HOP\_OUT\_OF\_RANGE

**Message Meaning:** RADVD AdvCurHopLimit out of range

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20043 - LOG\_ID\_RAD\_AGENT\_OUT\_OF\_RANGE

**Message ID:** 20043

**Message Description:** LOG\_ID\_RAD\_AGENT\_OUT\_OF\_RANGE

**Message Meaning:** RADVD HomeAgentLifetime out of range

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20044 - LOG\_ID\_RAD\_AGENT\_FLAG\_NOT\_SET

**Message ID:** 20044**Message Description:** LOG\_ID\_RAD\_AGENT\_FLAG\_NOT\_SET**Message Meaning:** RADVD AdvHomeAgentFlag not set**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20045 - LOG\_ID\_RAD\_PREFIX\_TOO\_LONG

**Message ID:** 20045

**Message Description:** LOG\_ID\_RAD\_PREFIX\_TOO\_LONG

**Message Meaning:** RADVD invalid prefix length

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20046 - LOG\_ID\_RAD\_PREF\_TIME\_TOO\_SMALL

**Message ID:** 20046

**Message Description:** LOG\_ID\_RAD\_PREF\_TIME\_TOO\_SMALL

**Message Meaning:** RADVD AdvValidLifetime less than AdvPreferredLifetime

**Type:** Event



**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20047 - LOG\_ID\_RAD\_FAIL\_IPV6\_SOCKET

**Message ID:** 20047**Message Description:** LOG\_ID\_RAD\_FAIL\_IPV6\_SOCKET**Message Meaning:** RADVD failed to create an IPv6 socket**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20048 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_PKTINFO

**Message ID:** 20048

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_PKTINFO

**Message Meaning:** RADVD failed to set IPv6 packet info

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20049 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_CHECKSUM

**Message ID:** 20049

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_CHECKSUM

**Message Meaning:** RADVD failed to set IPv6 checksum

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20050 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_UNICAST\_HOPS

**Message ID:** 20050**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_UNICAST\_HOPS**Message Meaning:** RADVD failed to set IPv6 unicast hops**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20051 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_MULTICAST\_HOPS

**Message ID:** 20051

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_MULTICAST\_HOPS

**Message Meaning:** RADVD failed to set IPv6 multicast hops

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20052 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_HOPLIMIT

**Message ID:** 20052

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_HOPLIMIT

**Message Meaning:** RADVD failed to set IPv6 hop limit

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20053 - LOG\_ID\_RAD\_FAIL\_OPT\_IPPROTO\_ICMPV6

**Message ID:** 20053**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPPROTO\_ICMPV6**Message Meaning:** RADVD failed to set ICMPv6 filter**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20054 - LOG\_ID\_RAD\_EXIT\_BY\_SIGNAL

**Message ID:** 20054

**Message Description:** LOG\_ID\_RAD\_EXIT\_BY\_SIGNAL

**Message Meaning:** RADVD exited due to received signal

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20055 - LOG\_ID\_RAD\_FAIL\_CMDB\_QUERY

**Message ID:** 20055

**Message Description:** LOG\_ID\_RAD\_FAIL\_CMDB\_QUERY

**Message Meaning:** RADVD interface query creation failed

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20056 - LOG\_ID\_RAD\_FAIL\_CMDB\_FOR\_EACH

**Message ID:** 20056**Message Description:** LOG\_ID\_RAD\_FAIL\_CMDB\_FOR\_EACH**Message Meaning:** RADVD query error**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20057 - LOG\_ID\_RAD\_FAIL\_FIND\_VIRT\_INTF

**Message ID:** 20057

**Message Description:** LOG\_ID\_RAD\_FAIL\_FIND\_VIRT\_INTF

**Message Meaning:** RADVD virtual interface not found

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20058 - LOG\_ID\_RAD\_UNLOAD\_INTF

**Message ID:** 20058

**Message Description:** LOG\_ID\_RAD\_UNLOAD\_INTF

**Message Meaning:** RADVD unloaded interface

**Type:** Event



**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20061 - LOG\_ID\_RAD\_INV\_ICMPV6\_TYPE

**Message ID:** 20061**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_TYPE**Message Meaning:** RADVD received unwanted ICMPv6 packet**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20062 - LOG\_ID\_RAD\_INV\_ICMPV6\_RA\_LEN

**Message ID:** 20062

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_RA\_LEN

**Message Meaning:** RADVD received ICMPv6 RA packet with invalid length

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20063 - LOG\_ID\_RAD\_ICMPV6\_NO\_SRC\_ADDR

**Message ID:** 20063

**Message Description:** LOG\_ID\_RAD\_ICMPV6\_NO\_SRC\_ADDR

**Message Meaning:** RADVD received ICMPv6 RA packet with non-link local source address

**Type:** Event

**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20064 - LOG\_ID\_RAD\_INV\_ICMPV6\_RS\_LEN

**Message ID:** 20064**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_RS\_LEN**Message Meaning:** RADVD received ICMPv6 RS packet with invalid length**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20065 - LOG\_ID\_RAD\_INV\_ICMPV6\_CODE

**Message ID:** 20065

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_CODE

**Message Meaning:** RADVD received ICMPv6 RS/RA packet with invalid code

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20066 - LOG\_ID\_RAD\_INV\_ICMPV6\_HOP

**Message ID:** 20066

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_HOP

**Message Meaning:** RADVD received ICMPv6 RS/RA packet with invalid hop limit

**Type:** Event

**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20067 - LOG\_ID\_RAD\_MISMATCH\_HOP

**Message ID:** 20067**Message Description:** LOG\_ID\_RAD\_MISMATCH\_HOP**Message Meaning:** RADVD local AdvCurHopLimit disagrees with remote site**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20068 - LOG\_ID\_RAD\_MISMATCH\_MGR\_FLAG

**Message ID:** 20068

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_MGR\_FLAG

**Message Meaning:** RADVD local AdvManagedFlag disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20069 - LOG\_ID\_RAD\_MISMATCH\_OTH\_FLAG

**Message ID:** 20069

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_OTH\_FLAG

**Message Meaning:** RADVD local AdvOtherConfigFlag disagrees with remote site

**Type:** Event

**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20070 - LOG\_ID\_RAD\_MISMATCH\_TIME

**Message ID:** 20070**Message Description:** LOG\_ID\_RAD\_MISMATCH\_TIME**Message Meaning:** RADVD local AdvReachableTime disagrees with remote site**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20071 - LOG\_ID\_RAD\_MISMATCH\_TIMER

**Message ID:** 20071

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_TIMER

**Message Meaning:** RADVD local AdvRetransTimer disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20072 - LOG\_ID\_RAD\_EXTRA\_DATA

**Message ID:** 20072

**Message Description:** LOG\_ID\_RAD\_EXTRA\_DATA

**Message Meaning:** RADVD extra data in RA packet found

**Type:** Event



**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20073 - LOG\_ID\_RAD\_NO\_OPT\_DATA

**Message ID:** 20073**Message Description:** LOG\_ID\_RAD\_NO\_OPT\_DATA**Message Meaning:** RADVD RA packet option length zero**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20074 - LOG\_ID\_RAD\_INV\_OPT\_LEN

**Message ID:** 20074

**Message Description:** LOG\_ID\_RAD\_INV\_OPT\_LEN

**Message Meaning:** RADVD RA packet option length greater than total length

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20075 - LOG\_ID\_RAD\_MISMATCH\_MTU

**Message ID:** 20075

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_MTU

**Message Meaning:** RADVD local AdvLinkMTU disagrees with remote site

**Type:** Event

**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20077 - LOG\_ID\_RAD\_MISMATCH\_PREF\_TIME

**Message ID:** 20077**Message Description:** LOG\_ID\_RAD\_MISMATCH\_PREF\_TIME**Message Meaning:** Interface AdvPreferredLifetime on our interface does not agree with a remote site**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20078 - LOG\_ID\_RAD\_INV\_OPT

**Message ID:** 20078

**Message Description:** LOG\_ID\_RAD\_INV\_OPT

**Message Meaning:** RADVD found invalid option in RA packet from remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20079 - LOG\_ID\_RAD\_READY

**Message ID:** 20079

**Message Description:** LOG\_ID\_RAD\_READY

**Message Meaning:** RADVD daemon started

**Type:** Event

**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20080 - LOG\_ID\_RAD\_FAIL\_TO\_RCV

**Message ID:** 20080**Message Description:** LOG\_ID\_RAD\_FAIL\_TO\_RCV**Message Meaning:** RADVD receive message failed**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20081 - LOG\_ID\_RAD\_INV\_HOP

**Message ID:** 20081

**Message Description:** LOG\_ID\_RAD\_INV\_HOP

**Message Meaning:** RADVD received invalid IPv6 hop limit

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20082 - LOG\_ID\_RAD\_INV\_PKTINFO

**Message ID:** 20082

**Message Description:** LOG\_ID\_RAD\_INV\_PKTINFO

**Message Meaning:** RADVD received invalid IPv6 packet info

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20083 - LOG\_ID\_RAD\_FAIL\_TO\_CHECK

**Message ID:** 20083**Message Description:** LOG\_ID\_RAD\_FAIL\_TO\_CHECK**Message Meaning:** RADVD all-routers membership check failed**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20084 - LOG\_ID\_RAD\_FAIL\_TO\_SEND

**Message ID:** 20084

**Message Description:** LOG\_ID\_RAD\_FAIL\_TO\_SEND

**Message Meaning:** RADVD send message failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20085 - LOG\_ID\_SESSION\_CLASH

**Message ID:** 20085

**Message Description:** LOG\_ID\_SESSION\_CLASH

**Message Meaning:** Session clashed

**Type:** Event



**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
proto	Protocol Number	uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
trace_id		string	32
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20090 - LOG\_ID\_INTF\_LINK\_STA\_CHG

**Message ID:** 20090**Message Description:** LOG\_ID\_INTF\_LINK\_STA\_CHG**Message Meaning:** Interface link status changed**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
intf	Interface	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20099 - LOG\_ID\_INTF\_STA\_CHG

**Message ID:** 20099

**Message Description:** LOG\_ID\_INTF\_STA\_CHG

**Message Meaning:** Interface status changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
vd	Virtual Domain Name	string	32

## 20100 - LOG\_ID\_WEB\_CAT\_UPDATED

**Message ID:** 20100

**Message Description:** LOG\_ID\_WEB\_CAT\_UPDATED

**Message Meaning:** FortiGuard web filter category list updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20101 - LOG\_ID\_WEB\_LIC\_EXPIRE

**Message ID:** 20101

**Message Description:** LOG\_ID\_WEB\_LIC\_EXPIRE

**Message Meaning:** FortiGuard web filter license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20102 - LOG\_ID\_SPAM\_LIC\_EXPIRE

**Message ID:** 20102

**Message Description:** LOG\_ID\_SPAM\_LIC\_EXPIRE

**Message Meaning:** FortiGuard antispam license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20103 - LOG\_ID\_AV\_LIC\_EXPIRE

**Message ID:** 20103

**Message Description:** LOG\_ID\_AV\_LIC\_EXPIRE

**Message Meaning:** FortiGuard antivirus license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20104 - LOG\_ID\_IPS\_LIC\_EXPIRE

**Message ID:** 20104

**Message Description:** LOG\_ID\_IPS\_LIC\_EXPIRE

**Message Meaning:** FortiGuard IPS license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20107 - LOG\_ID\_LOG\_UPLOAD\_ERR

**Message ID:** 20107**Message Description:** LOG\_ID\_LOG\_UPLOAD\_ERR**Message Meaning:** Log upload error**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
error	Error Reason for Log Upload to Forticloud	string	256
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20108 - LOG\_ID\_LOG\_UPLOAD\_DONE

**Message ID:** 20108

**Message Description:** LOG\_ID\_LOG\_UPLOAD\_DONE

**Message Meaning:** Log upload completed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20109 - LOG\_ID\_WEB\_LIC\_EXPIRED

**Message ID:** 20109

**Message Description:** LOG\_ID\_WEB\_LIC\_EXPIRED

**Message Meaning:** FortiGuard web filter license expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20113 - LOG\_ID\_IPSA\_DOWNLOAD\_FAIL

**Message ID:** 20113

**Message Description:** LOG\_ID\_IPSA\_DOWNLOAD\_FAIL

**Message Meaning:** IPSA database download failed



**Type:** Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20115 - LOG\_ID\_IPSA\_STATUSUPD\_FAIL

**Message ID:** 20115**Message Description:** LOG\_ID\_IPSA\_STATUSUPD\_FAIL**Message Meaning:** IPSA driver update failed**Type:** Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20116 - LOG\_ID\_SPAM\_LIC\_EXPIRED

**Message ID:** 20116

**Message Description:** LOG\_ID\_SPAM\_LIC\_EXPIRED

**Message Meaning:** FortiGuard antispam license expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20117 - LOG\_ID\_AV\_LIC\_EXPIRED

**Message ID:** 20117

**Message Description:** LOG\_ID\_AV\_LIC\_EXPIRED

**Message Meaning:** FortiGuard antivirus license expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20118 - LOG\_ID\_WEBF\_STATUS\_REACH

**Message ID:** 20118

**Message Description:** LOG\_ID\_WEBF\_STATUS\_REACH

**Message Meaning:** FortiGuard webfilter reachable

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20119 - LOG\_ID\_WEBF\_STATUS\_UNREACH

**Message ID:** 20119

**Message Description:** LOG\_ID\_WEBF\_STATUS\_UNREACH

**Message Meaning:** FortiGuard webfilter unreachable

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20200 - LOG\_ID\_FIPS\_SELF\_TEST

**Message ID:** 20200

**Message Description:** LOG\_ID\_FIPS\_SELF\_TEST

**Message Meaning:** FIPS CC self-test initiated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20201 - LOG\_ID\_FIPS\_SELF\_ALL\_TEST

**Message ID:** 20201

**Message Description:** LOG\_ID\_FIPS\_SELF\_ALL\_TEST

**Message Meaning:** FIPS ALL CC self-tests initiated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20202 - LOG\_ID\_DISK\_FORMAT\_ERROR

**Message ID:** 20202

**Message Description:** LOG\_ID\_DISK\_FORMAT\_ERROR

**Message Meaning:** Disk partitioning or formatting Error

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20203 - LOG\_ID\_DAEMON\_SHUTDOWN

**Message ID:** 20203

**Message Description:** LOG\_ID\_DAEMON\_SHUTDOWN

**Message Meaning:** Daemon shutdown

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20204 - LOG\_ID\_DAEMON\_START

**Message ID:** 20204

**Message Description:** LOG\_ID\_DAEMON\_START

**Message Meaning:** Daemon started

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20205 - LOG\_ID\_DISK\_FORMAT\_REQ

**Message ID:** 20205

**Message Description:** LOG\_ID\_DISK\_FORMAT\_REQ

**Message Meaning:** Format disk requested

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical



Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20206 - LOG\_ID\_DISK\_SCAN\_REQ

**Message ID:** 20206

**Message Description:** LOG\_ID\_DISK\_SCAN\_REQ

**Message Meaning:** Scan disk requested

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20207 - LOG\_ID\_RAD\_MISMATCH\_VALID\_TIME

**Message ID:** 20207

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_VALID\_TIME

**Message Meaning:** RADVD local AdvValidLifetime disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20208 - LOG\_ID\_ZOMBIE\_DAEMON\_CLEANUP

**Message ID:** 20208

**Message Description:** LOG\_ID\_ZOMBIE\_DAEMON\_CLEANUP

**Message Meaning:** Zombie daemon cleanup

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20209 - LOG\_ID\_DISK\_UNAVAIL

**Message ID:** 20209

**Message Description:** LOG\_ID\_DISK\_UNAVAIL

**Message Meaning:** Disk unavailable

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20210 - LOG\_ID\_DISK\_TRIM\_START

**Message ID:** 20210

**Message Description:** LOG\_ID\_DISK\_TRIM\_START

**Message Meaning:** SSD TRIM started

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20211 - LOG\_ID\_DISK\_TRIM\_END

**Message ID:** 20211

**Message Description:** LOG\_ID\_DISK\_TRIM\_END

**Message Meaning:** SSD TRIM finished

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20212 - LOG\_ID\_DISK\_SCAN\_NEEDED

**Message ID:** 20212

**Message Description:** LOG\_ID\_DISK\_SCAN\_NEEDED

**Message Meaning:** Disk scan is needed

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20213 - LOG\_ID\_DISK\_LOG\_CORRUPTED

**Message ID:** 20213

**Message Description:** LOG\_ID\_DISK\_LOG\_CORRUPTED

**Message Meaning:** Log file on disk is corrupted

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20220 - LOGID\_EVENT\_SHAPER\_OUTBOUND\_MAXED\_OUT

**Message ID:** 20220

**Message Description:** LOGID\_EVENT\_SHAPER\_OUTBOUND\_MAXED\_OUT

**Message Meaning:** Outbound bandwidth rate exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
intf	Interface	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20221 - LOGID\_EVENT\_SHAPER\_INBOUND\_MAXED\_OUT

**Message ID:** 20221

**Message Description:** LOGID\_EVENT\_SHAPER\_INBOUND\_MAXED\_OUT

**Message Meaning:** Inbound bandwidth rate exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
intf	Interface	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20300 - LOG\_ID\_BGP\_NB\_STAT\_CHG

**Message ID:** 20300

**Message Description:** LOG\_ID\_BGP\_NB\_STAT\_CHG

**Message Meaning:** BGP neighbor status changed



**Type:** Event**Category:** ROUTER**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20301 - LOG\_ID\_VZ\_LOG

**Message ID:** 20301**Message Description:** LOG\_ID\_VZ\_LOG**Message Meaning:** Routing log**Type:** Event**Category:** ROUTER**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20302 - LOG\_ID\_OSPF\_NB\_STAT\_CHG

**Message ID:** 20302

**Message Description:** LOG\_ID\_OSPF\_NB\_STAT\_CHG

**Message Meaning:** OSPF neighbor status changed

**Type:** Event

**Category:** ROUTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20303 - LOG\_ID\_OSPF6\_NB\_STAT\_CHG

**Message ID:** 20303

**Message Description:** LOG\_ID\_OSPF6\_NB\_STAT\_CHG

**Message Meaning:** OSPF6 neighbor status changed

**Type:** Event

**Category:** ROUTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 20401 - LOG\_ID\_ROUTER\_CLEAR

**Message ID:** 20401

**Message Description:** LOG\_ID\_ROUTER\_CLEAR

**Message Meaning:** Router cleared

**Type:** Event

**Category:** ROUTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui		string	64
user		string	256
vd	Virtual Domain Name	string	32

## 22000 - LOG\_ID\_INV\_PKT\_LEN

**Message ID:** 22000

**Message Description:** LOG\_ID\_INV\_PKT\_LEN

**Message Meaning:** Packet length mismatch

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22001 - LOG\_ID\_UNSUPPORTED\_PROT\_VER

**Message ID:** 22001

**Message Description:** LOG\_ID\_UNSUPPORTED\_PROT\_VER

**Message Meaning:** Protocol version unsupported

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22002 - LOG\_ID\_INV\_REQ\_TYPE

**Message ID:** 22002

**Message Description:** LOG\_ID\_INV\_REQ\_TYPE

**Message Meaning:** Request type not supported

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22003 - LOG\_ID\_FAIL\_SET\_SIG\_HANDLER

**Message ID:** 22003

**Message Description:** LOG\_ID\_FAIL\_SET\_SIG\_HANDLER

**Message Meaning:** Signal handler setup failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22004 - LOG\_ID\_FAIL\_CREATE\_SOCKET

**Message ID:** 22004

**Message Description:** LOG\_ID\_FAIL\_CREATE\_SOCKET

**Message Meaning:** Socket creation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22005 - LOG\_ID\_FAIL\_CREATE\_SOCKET\_RETRY

**Message ID:** 22005

**Message Description:** LOG\_ID\_FAIL\_CREATE\_SOCKET\_RETRY

**Message Meaning:** Socket creation retry failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22006 - LOG\_ID\_FAIL\_REG\_CMDB\_EVENT

**Message ID:** 22006

**Message Description:** LOG\_ID\_FAIL\_REG\_CMDB\_EVENT

**Message Meaning:** Registration for CMDB events failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32



## 22009 - LOG\_ID\_FAIL\_FIND\_AV\_PROFILE

**Message ID:** 22009

**Message Description:** LOG\_ID\_FAIL\_FIND\_AV\_PROFILE

**Message Meaning:** AntiVirus profile not found

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22010 - LOG\_ID\_SENDTO\_FAIL

**Message ID:** 22010

**Message Description:** LOG\_ID\_SENDTO\_FAIL

**Message Meaning:** URL filter packet send failure

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
process	Process	string	4096
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22011 - LOG\_ID\_ENTER\_MEM\_CONSERVE\_MODE

**Message ID:** 22011

**Message Description:** LOG\_ID\_ENTER\_MEM\_CONSERVE\_MODE

**Message Meaning:** Memory conserve mode entered

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
red		string	32
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
tz		string	5
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22012 - LOG\_ID\_LEAVE\_MEM\_CONSERVE\_MODE

**Message ID:** 22012

**Message Description:** LOG\_ID\_LEAVE\_MEM\_CONSERVE\_MODE

**Message Meaning:** Memory conserve mode exited

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
red		string	32

Log Field Name	Description	Data Type	Length
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
tz		string	5
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22013 - LOG\_ID\_IPPOOLPBA\_BLOCK\_EXHAUSTED

**Message ID:** 22013

**Message Description:** LOG\_ID\_IPPOOLPBA\_BLOCK\_EXHAUSTED

**Message Meaning:** IP pool PBA block exhausted

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
poolname	IP Pool Name	string	36
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
vd	Virtual Domain Name	string	32

## 22014 - LOG\_ID\_IPPOOLPBA\_NATIP\_EXHAUSTED

**Message ID:** 22014

**Message Description:** LOG\_ID\_IPPOOLPBA\_NATIP\_EXHAUSTED

**Message Meaning:** IP pool PBA NAT IP exhausted

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
poolname	IP Pool Name	string	36
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22015 - LOG\_ID\_IPPOOLPBA\_CREATE

**Message ID:** 22015

**Message Description:** LOG\_ID\_IPPOOLPBA\_CREATE

**Message Meaning:** IP pool PBA created

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
nat	NAT IP Address	ip	39
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22016 - LOG\_ID\_IPPOOLPBA\_DEALLOCATE

**Message ID:** 22016

**Message Description:** LOG\_ID\_IPPOOLPBA\_DEALLOCATE

**Message Meaning:** Deallocate IP pool PBA

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
nat	NAT IP Address	ip	39
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22017 - LOG\_ID\_EXCEED\_GLOB\_RES\_LIMIT

**Message ID:** 22017

**Message Description:** LOG\_ID\_EXCEED\_GLOB\_RES\_LIMIT

**Message Meaning:** Global resource limit exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22018 - LOG\_ID\_EXCEED\_VD\_RES\_LIMIT

**Message ID:** 22018

**Message Description:** LOG\_ID\_EXCEED\_VD\_RES\_LIMIT

**Message Meaning:** VDOM resource limit exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22019 - LOG\_ID\_LOGRATE\_OVER\_LIMIT

**Message ID:** 22019

**Message Description:** LOG\_ID\_LOGRATE\_OVER\_LIMIT

**Message Meaning:** Log rate limit exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22020 - LOG\_ID\_FAIL\_CREATE\_HA\_SOCKET

**Message ID:** 22020

**Message Description:** LOG\_ID\_FAIL\_CREATE\_HA\_SOCKET

**Message Meaning:** HA socket creation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22021 - LOG\_ID\_FAIL\_CREATE\_HA\_SOCKET\_RETRY

**Message ID:** 22021**Message Description:** LOG\_ID\_FAIL\_CREATE\_HA\_SOCKET\_RETRY**Message Meaning:** UDP socket creation to relay URL request failed**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22031 - LOG\_ID\_SUCCESS\_CSF\_LOG\_SYNC\_CONFIG\_CHANGED

**Message ID:** 22031

**Message Description:** LOG\_ID\_SUCCESS\_CSF\_LOG\_SYNC\_CONFIG\_CHANGED

**Message Meaning:** Settings modified by Security Fabric service

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22032 - LOG\_ID\_CSF\_LOOP\_FOUND

**Message ID:** 22032

**Message Description:** LOG\_ID\_CSF\_LOOP\_FOUND

**Message Meaning:** Looped configuration in Security Fabric service

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
path		string	512
reason	Reason	string	256
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22033 - LOG\_ID\_FAIL\_CSF\_LOG\_SYNC\_NO\_VALID\_FSA

**Message ID:** 22033

**Message Description:** LOG\_ID\_FAIL\_CSF\_LOG\_SYNC\_NO\_VALID\_FSA

**Message Meaning:** CSF root FSA configuration is not properly set

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
server	Server IP Address	string	64
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22035 - LOG\_ID\_CSF\_UPSTREAM\_SN\_CHANGED

**Message ID:** 22035

**Message Description:** LOG\_ID\_CSF\_UPSTREAM\_SN\_CHANGED

**Message Meaning:** Serial number of upstream is changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
oldsn		string	64
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22036 - LOG\_ID\_CSF\_FGT\_CONNECTED

**Message ID:** 22036

**Message Description:** LOG\_ID\_CSF\_FGT\_CONNECTED

**Message Meaning:** Connection with CSF member established and authorized

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
direction		string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
sn	Serial Number	string	64
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22037 - LOG\_ID\_CSF\_FGT\_DISCONNECTED

**Message ID:** 22037

**Message Description:** LOG\_ID\_CSF\_FGT\_DISCONNECTED

**Message Meaning:** Connection with authorized CSF member terminated

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
direction		string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22100 - LOG\_ID\_QUAR\_DROP\_TRAN\_JOB

**Message ID:** 22100

**Message Description:** LOG\_ID\_QUAR\_DROP\_TRAN\_JOB

**Message Meaning:** Files dropped by quarantine daemon

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
fams_pause	Fortinet Analysis and Management Service Pause	uint32	10
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22101 - LOG\_ID\_QUAR\_DROP\_TLL\_JOB

**Message ID:** 22101

**Message Description:** LOG\_ID\_QUAR\_DROP\_TLL\_JOB



**Message Meaning:** Files dropped due to poor network connection

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22102 - LOG\_ID\_LOG\_DISK\_FAILURE

**Message ID:** 22102

**Message Description:** LOG\_ID\_LOG\_DISK\_FAILURE

**Message Meaning:** Log disk failure imminent

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22103 - LOG\_ID\_QUAR\_LIMIT\_REACHED

**Message ID:** 22103

**Message Description:** LOG\_ID\_QUAR\_LIMIT\_REACHED

**Message Meaning:** Sandbox limit reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22104 - LOG\_ID\_POWER\_RESTORE

**Message ID:** 22104

**Message Description:** LOG\_ID\_POWER\_RESTORE

**Message Meaning:** Power supply restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unit	Unit	uint32	10
vd	Virtual Domain Name	string	32

## 22105 - LOG\_ID\_POWER\_FAILURE

**Message ID:** 22105

**Message Description:** LOG\_ID\_POWER\_FAILURE

**Message Meaning:** Power supply failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unit	Unit	uint32	10
vd	Virtual Domain Name	string	32

## 22106 - LOG\_ID\_POWER\_OPTIONAL\_NOT\_DETECTED

**Message ID:** 22106

**Message Description:** LOG\_ID\_POWER\_OPTIONAL\_NOT\_DETECTED

**Message Meaning:** Optional power supply not detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22107 - LOG\_ID\_VOLT\_ANOM

**Message ID:** 22107

**Message Description:** LOG\_ID\_VOLT\_ANOM

**Message Meaning:** Voltage anomaly

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22108 - LOG\_ID\_FAN\_ANOM

**Message ID:** 22108

**Message Description:** LOG\_ID\_FAN\_ANOM

**Message Meaning:** Fan anomaly

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22109 - LOG\_ID\_TEMP\_TOO\_HIGH

**Message ID:** 22109

**Message Description:** LOG\_ID\_TEMP\_TOO\_HIGH

**Message Meaning:** Temperature too high

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22110 - LOG\_ID\_SPARE\_BLOCK\_LOW

**Message ID:** 22110

**Message Description:** LOG\_ID\_SPARE\_BLOCK\_LOW

**Message Meaning:** Spare blocks availability low

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22113 - LOG\_ID\_FNBAM\_FAILURE

**Message ID:** 22113

**Message Description:** LOG\_ID\_FNBAM\_FAILURE

**Message Meaning:** Authentication error

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
service	Name of Service	string	64
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22150 - LOG\_ID\_VOLT\_NOM

**Message ID:** 22150

**Message Description:** LOG\_ID\_VOLT\_NOM

**Message Meaning:** Voltage normal

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22151 - LOG\_ID\_FAN\_NOM

**Message ID:** 22151

**Message Description:** LOG\_ID\_FAN\_NOM

**Message Meaning:** Fan normal**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22152 - LOG\_ID\_TEMP\_TOO\_LOW

**Message ID:** 22152**Message Description:** LOG\_ID\_TEMP\_TOO\_LOW**Message Meaning:** Temperature too low**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22153 - LOG\_ID\_TEMP\_NORM

**Message ID:** 22153

**Message Description:** LOG\_ID\_TEMP\_NORM

**Message Meaning:** Temperature normal

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22200 - LOG\_ID\_AUTO\_UPT\_CERT

**Message ID:** 22200

**Message Description:** LOG\_ID\_AUTO\_UPT\_CERT

**Message Meaning:** Certificate will be auto-updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert	Certificate	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22201 - LOG\_ID\_AUTO\_GEN\_CERT

**Message ID:** 22201

**Message Description:** LOG\_ID\_AUTO\_GEN\_CERT

**Message Meaning:** Certificate will be auto-regenerated

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert	Certificate	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22203 - LOG\_ID\_AUTO\_GEN\_CERT\_FAIL

**Message ID:** 22203

**Message Description:** LOG\_ID\_AUTO\_GEN\_CERT\_FAIL

**Message Meaning:** Certificate failed to auto-generate

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22204 - LOG\_ID\_AUTO\_GEN\_CERT\_PENDING

**Message ID:** 22204

**Message Description:** LOG\_ID\_AUTO\_GEN\_CERT\_PENDING

**Message Meaning:** Certificate pending to auto-generate

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22205 - LOG\_ID\_AUTO\_GEN\_CERT\_SUCC

**Message ID:** 22205

**Message Description:** LOG\_ID\_AUTO\_GEN\_CERT\_SUCC

**Message Meaning:** Certificate succeed to auto-generate

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22206 - LOG\_ID\_CRL\_EXPIRED

**Message ID:** 22206

**Message Description:** LOG\_ID\_CRL\_EXPIRED

**Message Meaning:** CRL is expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32



## 22700 - LOG\_ID\_IPS\_FAIL\_OPEN

**Message ID:** 22700

**Message Description:** LOG\_ID\_IPS\_FAIL\_OPEN

**Message Meaning:** IPS session scan paused

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22701 - LOG\_ID\_IPS\_FAIL\_OPEN\_END

**Message ID:** 22701

**Message Description:** LOG\_ID\_IPS\_FAIL\_OPEN\_END

**Message Meaning:** IPS session scan resumed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22800 - LOG\_ID\_SCAN\_SERV\_FAIL

**Message ID:** 22800

**Message Description:** LOG\_ID\_SCAN\_SERV\_FAIL

**Message Meaning:** Scan services session failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mode	Mode	string	12
msg	Message Text	string	4096
service	Name of Service	string	64
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22802 - LOG\_ID\_ENTER\_FD\_CONSERVE\_MODE

**Message ID:** 22802

**Message Description:** LOG\_ID\_ENTER\_FD\_CONSERVE\_MODE

**Message Meaning:** File descriptor conserve mode entered

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
red		string	32
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
tz		string	5
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22803 - LOG\_ID\_LEAVE\_FD\_CONSERVE\_MODE

**Message ID:** 22803

**Message Description:** LOG\_ID\_LEAVE\_FD\_CONSERVE\_MODE

**Message Meaning:** File descriptor conserve mode exited

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
red		string	32
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
tz		string	5
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22804 - LOG\_ID\_LIC\_STATUS\_CHG

**Message ID:** 22804

**Message Description:** LOG\_ID\_LIC\_STATUS\_CHG

**Message Meaning:** License status changed

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22805 - LOG\_ID\_FAIL\_TO\_VALIDATE\_LIC

**Message ID:** 22805**Message Description:** LOG\_ID\_FAIL\_TO\_VALIDATE\_LIC**Message Meaning:** License validation failure**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22806 - LOG\_ID\_DUP\_LIC

**Message ID:** 22806

**Message Description:** LOG\_ID\_DUP\_LIC

**Message Meaning:** Duplicate license detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22808 - LOG\_ID\_LIC\_EXPIRE

**Message ID:** 22808

**Message Description:** LOG\_ID\_LIC\_EXPIRE

**Message Meaning:** VM license expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22809 - LOG\_ID\_LIC\_WILL\_EXPIRE

**Message ID:** 22809

**Message Description:** LOG\_ID\_LIC\_WILL\_EXPIRE

**Message Meaning:** VM license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22810 - LOG\_ID\_SCANUNIT\_ERROR\_BLOCK

**Message ID:** 22810

**Message Description:** LOG\_ID\_SCANUNIT\_ERROR\_BLOCK

**Message Meaning:** Scan error - traffic blocked

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dir		string	8
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64
eventtime		uint64	20



Log Field Name	Description	Data Type	Length
file	File Name for Generated Report?	string	256
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
proto	Protocol Number	uint8	3
service	Name of Service	string	64
session_id		uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22811 - LOG\_ID\_SCANUNIT\_ERROR\_PASS

**Message ID:** 22811

**Message Description:** LOG\_ID\_SCANUNIT\_ERROR\_PASS

**Message Meaning:** Scan error - traffic passed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dir		string	8
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dst_int	Destination Interface	string	64
eventtime		uint64	20
file	File Name for Generated Report?	string	256
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
proto	Protocol Number	uint8	3
service	Name of Service	string	64
session_id		uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22812 - LOG\_ID\_SCANUNIT\_AVENG\_RELOAD

**Message ID:** 22812

**Message Description:** LOG\_ID\_SCANUNIT\_AVENG\_RELOAD

**Message Meaning:** Scanunit is reloading AV engine

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22813 - LOG\_ID\_SCANUNIT\_AVDB\_RELOAD

**Message ID:** 22813

**Message Description:** LOG\_ID\_SCANUNIT\_AVDB\_RELOAD

**Message Meaning:** Scanunit reloaded AV Database

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
vd	Virtual Domain Name	string	32

## 22814 - LOG\_ID\_SCANUNIT\_AVDB\_RELOAD\_ERROR

**Message ID:** 22814

**Message Description:** LOG\_ID\_SCANUNIT\_AVDB\_RELOAD\_ERROR

**Message Meaning:** Scanunit AV Database reload error

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22815 - LOG\_ID\_SCANUNIT\_AVDB\_LOAD

**Message ID:** 22815

**Message Description:** LOG\_ID\_SCANUNIT\_AVDB\_LOAD

**Message Meaning:** Scanunit loaded AV Database

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22816 - LOG\_ID\_SCANUNIT\_AVDB\_LOAD\_ERROR

**Message ID:** 22816**Message Description:** LOG\_ID\_SCANUNIT\_AVDB\_LOAD\_ERROR**Message Meaning:** Scanunit AV Database load error**Type:** Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22850 - LOG\_ID\_USER\_QUARANTINE\_MAC\_ADD

**Message ID:** 22850

**Message Description:** LOG\_ID\_USER\_QUARANTINE\_MAC\_ADD

**Message Meaning:** User quarantine MAC added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22851 - LOG\_ID\_USER\_QUARANTINE\_MAC\_DELETE

**Message ID:** 22851

**Message Description:** LOG\_ID\_USER\_QUARANTINE\_MAC\_DELETE

**Message Meaning:** User quarantine MAC deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22852 - LOG\_ID\_USER\_QUARANTINE\_MAC\_BOUNCE\_PORT\_HIT

**Message ID:** 22852

**Message Description:** LOG\_ID\_USER\_QUARANTINE\_MAC\_BOUNCE\_PORT\_HIT

**Message Meaning:** User quarantine MAC bounce port hit

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22853 - LOG\_ID\_USER\_QUARANTINE\_MAC\_BOUNCE\_PORT\_MISS

**Message ID:** 22853

**Message Description:** LOG\_ID\_USER\_QUARANTINE\_MAC\_BOUNCE\_PORT\_MISS

**Message Meaning:** User quarantine MAC bounce port miss

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22890 - LOG\_ID\_FORTILINKD

**Message ID:** 22890

**Message Description:** LOG\_ID\_FORTILINKD

**Message Meaning:** Switch-Controller Daemon Log (Notification)

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22891 - LOG\_ID\_FLCFGD\_SYNC\_ERROR

**Message ID:** 22891

**Message Description:** LOG\_ID\_FLCFGD\_SYNC\_ERROR

**Message Meaning:** Switch-Controller Switch Sync Error

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22892 - LOG\_ID\_FLCFGD\_SYNC\_COMPLETE

**Message ID:** 22892

**Message Description:** LOG\_ID\_FLCFGD\_SYNC\_COMPLETE

**Message Meaning:** Switch-Controller Switch Sync Complete

**Type:** Event

**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22893 - LOG\_ID\_FLCFGD\_SYNC\_STATE

**Message ID:** 22893**Message Description:** LOG\_ID\_FLCFGD\_SYNC\_STATE**Message Meaning:** Switch-Controller Switch Sync State**Type:** Event**Category:** SYSTEM**Severity:** Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22894 - LOG\_ID\_FLCFGD\_UPGRADE\_ERROR

**Message ID:** 22894

**Message Description:** LOG\_ID\_FLCFGD\_UPGRADE\_ERROR

**Message Meaning:** Switch-Controller Switch Upgrade Error

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22895 - LOG\_ID\_FLCFGD\_UPGRADE\_STATUS

**Message ID:** 22895

**Message Description:** LOG\_ID\_FLCFGD\_UPGRADE\_STATUS

**Message Meaning:** Switch-Controller Switch Upgrade Status

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22896 - LOG\_ID\_FORTILINKD\_CRITICAL

**Message ID:** 22896

**Message Description:** LOG\_ID\_FORTILINKD\_CRITICAL

**Message Meaning:** Switch-Controller Daemon Log (Critical)

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22900 - LOG\_ID\_CAPUTP\_SESSION

**Message ID:** 22900

**Message Description:** LOG\_ID\_CAPUTP\_SESSION

**Message Meaning:** CAPUTP session status

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22901 - LOG\_ID\_FAZ\_CON

**Message ID:** 22901

**Message Description:** LOG\_ID\_FAZ\_CON

**Message Meaning:** FortiAnalyzer connection up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22902 - LOG\_ID\_FAZ\_DISCON

**Message ID:** 22902

**Message Description:** LOG\_ID\_FAZ\_DISCON

**Message Meaning:** FortiAnalyzer connection down

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22903 - LOG\_ID\_FAZ\_CON\_ERR

**Message ID:** 22903

**Message Description:** LOG\_ID\_FAZ\_CON\_ERR

**Message Meaning:** FortiAnalyzer connection failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22904 - LOG\_ID\_CAPUTP\_SESSION\_NOTIF

**Message ID:** 22904

**Message Description:** LOG\_ID\_CAPUTP\_SESSION\_NOTIF

**Message Meaning:** CAPUTP session status notification

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22912 - LOG\_ID\_FDS\_SRV\_ERRCON

**Message ID:** 22912

**Message Description:** LOG\_ID\_FDS\_SRV\_ERRCON

**Message Meaning:** FortiCloud server connection failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22913 - LOG\_ID\_FDS\_SRV\_DISCON

**Message ID:** 22913

**Message Description:** LOG\_ID\_FDS\_SRV\_DISCON

**Message Meaning:** FortiCloud server disconnected

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22914 - LOG\_ID\_FDS\_SRV\_CHG

**Message ID:** 22914

**Message Description:** LOG\_ID\_FDS\_SRV\_CHG

**Message Meaning:** FortiCloud server changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22915 - LOG\_ID\_FDS\_SRV\_CON

**Message ID:** 22915

**Message Description:** LOG\_ID\_FDS\_SRV\_CON

**Message Meaning:** FortiCloud server connected

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22916 - LOG\_ID\_FDS\_STATUS

**Message ID:** 22916

**Message Description:** LOG\_ID\_FDS\_STATUS

**Message Meaning:** FortiGuard Message Service status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22917 - LOG\_ID\_FDS\_SMS\_QUOTA

**Message ID:** 22917

**Message Description:** LOG\_ID\_FDS\_SMS\_QUOTA

**Message Meaning:** SMS quota reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22918 - LOG\_ID\_FDS\_CTRL\_STATUS

**Message ID:** 22918

**Message Description:** LOG\_ID\_FDS\_CTRL\_STATUS

**Message Meaning:** FortiGuard Message Service controller status

**Type:** Event

**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22921 - LOG\_ID\_EVENT\_ROUTE\_INFO\_CHANGED

**Message ID:** 22921**Message Description:** LOG\_ID\_EVENT\_ROUTE\_INFO\_CHANGED**Message Meaning:** Routing information changed**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22922 - LOG\_ID\_EVENT\_LINK\_MONITOR\_STATUS

**Message ID:** 22922

**Message Description:** LOG\_ID\_EVENT\_LINK\_MONITOR\_STATUS

**Message Meaning:** Link monitor status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
probeprotocol	Link Monitor Probe Protocol	string	16
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16



Log Field Name	Description	Data Type	Length
tz		string	5
vd	Virtual Domain Name	string	32

## 22923 - LOG\_ID\_EVENT\_VWL\_LQTY\_STATUS

**Message ID:** 22923

**Message Description:** LOG\_ID\_EVENT\_VWL\_LQTY\_STATUS

**Message Meaning:** Virtual WAN Link status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22924 - LOG\_ID\_EVENT\_VWL\_VOLUME\_STATUS

**Message ID:** 22924

**Message Description:** LOG\_ID\_EVENT\_VWL\_VOLUME\_STATUS

**Message Meaning:** Virtual WAN Link volume status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22925 - LOG\_ID\_EVENT\_LINK\_MONITOR\_SLA\_INFO

**Message ID:** 22925**Message Description:** LOG\_ID\_EVENT\_LINK\_MONITOR\_SLA\_INFO**Message Meaning:** Link monitor SLA information**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22926 - LOG\_ID\_EVENT\_VWL\_NEIGHBOR\_STATUS

**Message ID:** 22926

**Message Description:** LOG\_ID\_EVENT\_VWL\_NEIGHBOR\_STATUS

**Message Meaning:** Virtual WAN Link Neighbor status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22927 - LOG\_ID\_EVENT\_VWL\_NEIGHBOR\_STANDALONE

**Message ID:** 22927

**Message Description:** LOG\_ID\_EVENT\_VWL\_NEIGHBOR\_STANDALONE

**Message Meaning:** Virtual WAN Link Neighbor standalone

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22928 - LOG\_ID\_EVENT\_VWL\_NEIGHBOR\_PRIMARY

**Message ID:** 22928

**Message Description:** LOG\_ID\_EVENT\_VWL\_NEIGHBOR\_PRIMARY

**Message Meaning:** Virtual WAN Link Neighbor primary

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22929 - LOG\_ID\_EVENT\_VWL\_NEIGHBOR\_SECONDARY

**Message ID:** 22929

**Message Description:** LOG\_ID\_EVENT\_VWL\_NEIGHBOR\_SECONDARY

**Message Meaning:** Virtual WAN Link Neighbor secondary

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 22949 - LOG\_ID\_FDS\_JOIN

**Message ID:** 22949

**Message Description:** LOG\_ID\_FDS\_JOIN

**Message Meaning:** FortiCloud auto-join attempted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22950 - LOG\_ID\_FDS\_LOGIN\_SUCC

**Message ID:** 22950

**Message Description:** LOG\_ID\_FDS\_LOGIN\_SUCC

**Message Meaning:** FortiCloud activation successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22951 - LOG\_ID\_FDS\_LOGOUT

**Message ID:** 22951

**Message Description:** LOG\_ID\_FDS\_LOGOUT

**Message Meaning:** FortiCloud logout

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22952 - LOG\_ID\_FDS\_LOGIN\_FAIL

**Message ID:** 22952

**Message Description:** LOG\_ID\_FDS\_LOGIN\_FAIL

**Message Meaning:** FortiCloud activation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32



## 22953 - LOG\_ID\_IOC\_DETECTED

**Message ID:** 22953

**Message Description:** LOG\_ID\_IOC\_DETECTED

**Message Meaning:** Compromised host detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 23101 - LOG\_ID\_IPSEC\_TUNNEL\_UP

**Message ID:** 23101

**Message Description:** LOG\_ID\_IPSEC\_TUNNEL\_UP

**Message Meaning:** IPsec VPN tunnel up

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 23102 - LOG\_ID\_IPSEC\_TUNNEL\_DOWN

**Message ID:** 23102

**Message Description:** LOG\_ID\_IPSEC\_TUNNEL\_DOWN

**Message Meaning:** IPsec VPN tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 23103 - LOG\_ID\_IPSEC\_TUNNEL\_STAT

**Message ID:** 23103

**Message Description:** LOG\_ID\_IPSEC\_TUNNEL\_STAT

**Message Meaning:** IPsec VPN tunnel statistics

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	4096
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 26001 - LOG\_ID\_DHCP\_ACK

**Message ID:** 26001

**Message Description:** LOG\_ID\_DHCP\_ACK

**Message Meaning:** DHCP Ack log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	4096
eventtime		uint64	20
hostname	Hostname	string	128
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26002 - LOG\_ID\_DHCP\_RELEASE

**Message ID:** 26002

**Message Description:** LOG\_ID\_DHCP\_RELEASE

**Message Meaning:** DHCP Release log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	4096
eventtime		uint64	20
hostname	Hostname	string	128
interface	Interface	string	32
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26003 - LOG\_ID\_DHCP\_STAT

**Message ID:** 26003

**Message Description:** LOG\_ID\_DHCP\_STAT

**Message Meaning:** DHCP statistics

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
tz		string	5
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 26004 - LOG\_ID\_DHCP\_CLIENT\_LEASE

**Message ID:** 26004

**Message Description:** LOG\_ID\_DHCP\_CLIENT\_LEASE

**Message Meaning:** DHCP client lease granted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26005 - LOG\_ID\_DHCP\_LEASE\_USAGE\_HIGH

**Message ID:** 26005

**Message Description:** LOG\_ID\_DHCP\_LEASE\_USAGE\_HIGH

**Message Meaning:** DHCP lease usage high

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26006 - LOG\_ID\_DHCP\_LEASE\_USAGE\_FULL

**Message ID:** 26006

**Message Description:** LOG\_ID\_DHCP\_LEASE\_USAGE\_FULL

**Message Meaning:** DHCP lease usage full

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26007 - LOG\_ID\_DHCP\_BLOCKED\_MAC

**Message ID:** 26007

**Message Description:** LOG\_ID\_DHCP\_BLOCKED\_MAC

**Message Meaning:** DHCP client blocked log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26008 - LOG\_ID\_DHCP\_DDNS\_ADD

**Message ID:** 26008

**Message Description:** LOG\_ID\_DHCP\_DDNS\_ADD

**Message Meaning:** DHCP DDNS add query

**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	4096
eventtime		uint64	20
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26009 - LOG\_ID\_DHCP\_DDNS\_DELETE

**Message ID:** 26009**Message Description:** LOG\_ID\_DHCP\_DDNS\_DELETE**Message Meaning:** DHCP DDNS delete query**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	4096
eventtime		uint64	20
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26010 - LOG\_ID\_DHCP\_DDNS\_COMPLETED

**Message ID:** 26010

**Message Description:** LOG\_ID\_DHCP\_DDNS\_COMPLETED

**Message Meaning:** DHCP DDNS query completed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	4096
eventtime		uint64	20
fqdn		string	256
ip		ip	39

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26011 - LOG\_ID\_DHCPV6\_REPLY

**Message ID:** 26011

**Message Description:** LOG\_ID\_DHCPV6\_REPLY

**Message Meaning:** DHCPv6 Ack log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	4096
duid		string	128
eventtime		uint64	20
iaid		uint32	10
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 26012 - LOG\_ID\_DHCPV6\_RELEASE

**Message ID:** 26012

**Message Description:** LOG\_ID\_DHCPV6\_RELEASE

**Message Meaning:** DHCPv6 Release log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	4096
duid		string	128
eventtime		uint64	20
iaid		uint32	10
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 27001 - LOG\_ID\_VRRP\_STATE\_CHG

**Message ID:** 27001

**Message Description:** LOG\_ID\_VRRP\_STATE\_CHG

**Message Meaning:** VRRP state changed

**Type:** Event

**Category:** ROUTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29001 - LOG\_ID\_PPPD\_MSG

**Message ID:** 29001

**Message Description:** LOG\_ID\_PPPD\_MSG

**Message Meaning:** PPP status

**Type:** Event

**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
remote	Remote IP Address	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 29002 - LOG\_ID\_PPPD\_AUTH\_SUC

**Message ID:** 29002**Message Description:** LOG\_ID\_PPPD\_AUTH\_SUC**Message Meaning:** PPP authentication successful**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assigned	Assigned IP Address	ip	39
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
remote	Remote IP Address	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 29003 - LOG\_ID\_PPPD\_AUTH\_FAIL

**Message ID:** 29003

**Message Description:** LOG\_ID\_PPPD\_AUTH\_FAIL

**Message Meaning:** PPP authentication failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39



Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
remote	Remote IP Address	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29010 - LOG\_ID\_PPPOE\_STATUS\_REPORT\_NOTIF

**Message ID:** 29010

**Message Description:** LOG\_ID\_PPPOE\_STATUS\_REPORT\_NOTIF

**Message Meaning:** PPPoE status report

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
gateway	gateway ip address for PPPoE status report	ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
mtu	Max Transmission Unit Value	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29011 - LOG\_ID\_PPPD\_FAIL\_TO\_EXEC

**Message ID:** 29011

**Message Description:** LOG\_ID\_PPPD\_FAIL\_TO\_EXEC

**Message Meaning:** PPP execution failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29012 - LOG\_ID\_PPP\_OPT\_ERR

**Message ID:** 29012

**Message Description:** LOG\_ID\_PPP\_OPT\_ERR

**Message Meaning:** PPP received incorrect options

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29013 - LOG\_ID\_PPPD\_START

**Message ID:** 29013**Message Description:** LOG\_ID\_PPPD\_START**Message Meaning:** PPP daemon started**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29014 - LOG\_ID\_PPPD\_EXIT

**Message ID:** 29014

**Message Description:** LOG\_ID\_PPPD\_EXIT

**Message Meaning:** PPP daemon exited

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29015 - LOG\_ID\_PPP\_RCV\_BAD\_PEER\_IP

**Message ID:** 29015

**Message Description:** LOG\_ID\_PPP\_RCV\_BAD\_PEER\_IP

**Message Meaning:** PPP received invalid peer IP

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29016 - LOG\_ID\_PPP\_RCV\_BAD\_LOCAL\_IP

**Message ID:** 29016**Message Description:** LOG\_ID\_PPP\_RCV\_BAD\_LOCAL\_IP**Message Meaning:** PPP received invalid local IP**Type:** Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29017 - LOG\_ID\_PPP\_OPT\_NOTIF

**Message ID:** 29017

**Message Description:** LOG\_ID\_PPP\_OPT\_NOTIF

**Message Meaning:** PPP received incorrect notifications

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 29021 - LOG\_ID\_EVENT\_AUTH\_SNMP\_QUERY\_FAILED

**Message ID:** 29021

**Message Description:** LOG\_ID\_EVENT\_AUTH\_SNMP\_QUERY\_FAILED

**Message Meaning:** SNMP query failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
community	Community	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
version	Version	string	64

## 29022 - LOG\_ID\_DDNS\_UPDATE\_FAIL

**Message ID:** 29022**Message Description:** LOG\_ID\_DDNS\_UPDATE\_FAIL**Message Meaning:** DDNS update failed**Type:** Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32001 - LOG\_ID\_ADMIN\_LOGIN\_SUCC

**Message ID:** 32001

**Message Description:** LOG\_ID\_ADMIN\_LOGIN\_SUCC

**Message Meaning:** Admin login successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method		string	64
msg	Message Text	string	4096



Log Field Name	Description	Data Type	Length
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32002 - LOG\_ID\_ADMIN\_LOGIN\_FAIL

**Message ID:** 32002

**Message Description:** LOG\_ID\_ADMIN\_LOGIN\_FAIL

**Message Meaning:** Admin login failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method		string	64

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32003 - LOG\_ID\_ADMIN\_LOGOUT

**Message ID:** 32003

**Message Description:** LOG\_ID\_ADMIN\_LOGOUT

**Message Meaning:** Admin logout successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
method		string	64
msg	Message Text	string	4096
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32005 - LOG\_ID\_ADMIN\_OVERRIDE\_VDOM

**Message ID:** 32005

**Message Description:** LOG\_ID\_ADMIN\_OVERRIDE\_VDOM

**Message Meaning:** Admin overrode VDOM

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32006 - LOG\_ID\_ADMIN\_ENTER\_VDOM

**Message ID:** 32006

**Message Description:** LOG\_ID\_ADMIN\_ENTER\_VDOM

**Message Meaning:** Super admin entered VDOM

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32007 - LOG\_ID\_ADMIN\_LEFT\_VDOM

**Message ID:** 32007

**Message Description:** LOG\_ID\_ADMIN\_LEFT\_VDOM

**Message Meaning:** Super admin left VDOM

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32008 - LOG\_ID\_VIEW\_DISK\_LOG\_FAIL

**Message ID:** 32008

**Message Description:** LOG\_ID\_VIEW\_DISK\_LOG\_FAIL

**Message Meaning:** Disk log access failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32009 - LOG\_ID\_SYSTEM\_START

**Message ID:** 32009

**Message Description:** LOG\_ID\_SYSTEM\_START

**Message Meaning:** FortiGate started

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32010 - LOG\_ID\_DISK\_LOG\_FULL

**Message ID:** 32010

**Message Description:** LOG\_ID\_DISK\_LOG\_FULL

**Message Meaning:** Disk full

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32011 - LOG\_ID\_LOG\_ROLL

**Message ID:** 32011

**Message Description:** LOG\_ID\_LOG\_ROLL

**Message Meaning:** Disk log rolled

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32014 - LOG\_ID\_CS\_LIC\_EXPIRE

**Message ID:** 32014

**Message Description:** LOG\_ID\_CS\_LIC\_EXPIRE



**Message Meaning:** Support license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32015 - LOG\_ID\_DISK\_LOG\_USAGE

**Message ID:** 32015

**Message Description:** LOG\_ID\_DISK\_LOG\_USAGE

**Message Meaning:** Log disk full

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 32017 - LOG\_ID\_FDS\_DAILY\_QUOTA\_FULL

**Message ID:** 32017

**Message Description:** LOG\_ID\_FDS\_DAILY\_QUOTA\_FULL

**Message Meaning:** FortiCloud daily quota full

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 32018 - LOG\_ID\_FIPS\_ENTER\_ERR\_MOD

**Message ID:** 32018

**Message Description:** LOG\_ID\_FIPS\_ENTER\_ERR\_MOD

**Message Meaning:** FIPS CC entered error mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32019 - LOG\_ID\_CC\_ENTER\_ERR\_MOD

**Message ID:** 32019

**Message Description:** LOG\_ID\_CC\_ENTER\_ERR\_MOD

**Message Meaning:** CC entered error mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32020 - LOG\_ID\_SSH\_CORRPUT\_MAC

**Message ID:** 32020

**Message Description:** LOG\_ID\_SSH\_CORRPUT\_MAC

**Message Meaning:** Message Authentication Code corrupted

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 32021 - LOG\_ID\_ADMIN\_LOGIN\_DISABLE

**Message ID:** 32021

**Message Description:** LOG\_ID\_ADMIN\_LOGIN\_DISABLE

**Message Meaning:** Admin login disabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32022 - LOG\_ID\_VDOM\_ENABLED

**Message ID:** 32022

**Message Description:** LOG\_ID\_VDOM\_ENABLED

**Message Meaning:** VDOM enabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32023 - LOG\_ID\_MEM\_LOG\_FIRST\_FULL

**Message ID:** 32023

**Message Description:** LOG\_ID\_MEM\_LOG\_FIRST\_FULL

**Message Meaning:** Memory log full over first warning level

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32024 - LOG\_ID\_ADMIN\_PASSWD\_EXPIRE

**Message ID:** 32024

**Message Description:** LOG\_ID\_ADMIN\_PASSWD\_EXPIRE

**Message Meaning:** Admin password expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32025 - LOG\_ID\_SSH\_REKEY

**Message ID:** 32025

**Message Description:** LOG\_ID\_SSH\_REKEY

**Message Meaning:** SSH server re-key

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

### 32026 - LOG\_ID\_SSH\_BAD\_PACKET\_LENGTH

**Message ID:** 32026



**Message Description:** LOG\_ID\_SSH\_BAD\_PACKET\_LENGTH

**Message Meaning:** SSH server received bad length packet

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 32027 - LOG\_ID\_VIEW\_DISK\_LOG\_SUCC

**Message ID:** 32027

**Message Description:** LOG\_ID\_VIEW\_DISK\_LOG\_SUCC

**Message Meaning:** Disk logs viewed successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32028 - LOG\_ID\_LOG\_DEL\_DIR

**Message ID:** 32028

**Message Description:** LOG\_ID\_LOG\_DEL\_DIR

**Message Meaning:** Disk log directory deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
vd	Virtual Domain Name	string	32

## 32029 - LOG\_ID\_LOG\_DEL\_FILE

**Message ID:** 32029

**Message Description:** LOG\_ID\_LOG\_DEL\_FILE

**Message Meaning:** Disk log file deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
filesize	Report File Size in Bytes	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32030 - LOG\_ID\_SEND\_FDS\_STAT

**Message ID:** 32030

**Message Description:** LOG\_ID\_SEND\_FDS\_STAT

**Message Meaning:** FDS statistics sent

**Type:** Event

**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32031 - LOG\_ID\_VIEW\_MEM\_LOG\_FAIL

**Message ID:** 32031**Message Description:** LOG\_ID\_VIEW\_MEM\_LOG\_FAIL**Message Meaning:** Memory log access failed**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32032 - LOG\_ID\_DISK\_DLP\_ARCH\_FULL

**Message ID:** 32032

**Message Description:** LOG\_ID\_DISK\_DLP\_ARCH\_FULL

**Message Meaning:** DLP archive full

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32033 - LOG\_ID\_DISK\_QUAR\_FULL

**Message ID:** 32033

**Message Description:** LOG\_ID\_DISK\_QUAR\_FULL

**Message Meaning:** Quarantine full

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32034 - LOG\_ID\_DISK\_REPORT\_FULL

**Message ID:** 32034

**Message Description:** LOG\_ID\_DISK\_REPORT\_FULL

**Message Meaning:** Report full

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32035 - LOG\_ID\_VDOM\_DISABLED

**Message ID:** 32035

**Message Description:** LOG\_ID\_VDOM\_DISABLED

**Message Meaning:** VDOM disabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32036 - LOG\_ID\_DISK\_IPS\_ARCH\_FULL

**Message ID:** 32036

**Message Description:** LOG\_ID\_DISK\_IPS\_ARCH\_FULL

**Message Meaning:** IPS archive full

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32037 - LOG\_ID\_DISK\_LOG\_FIRST\_FULL

**Message ID:** 32037

**Message Description:** LOG\_ID\_DISK\_LOG\_FIRST\_FULL

**Message Meaning:** Disk log full over first warning

**Type:** Event

**Category:** SYSTEM



**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

**32038 - LOG\_ID\_LOG\_ROLL\_FORTICRON****Message ID:** 32038**Message Description:** LOG\_ID\_LOG\_ROLL\_FORTICRON**Message Meaning:** Log rotation requested by FortiCron**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 32039 - LOG\_ID\_VIEW\_MEM\_LOG\_SUCC

**Message ID:** 32039

**Message Description:** LOG\_ID\_VIEW\_MEM\_LOG\_SUCC

**Message Meaning:** Memory logs viewed successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32040 - LOG\_ID\_REPORT\_DELETED

**Message ID:** 32040

**Message Description:** LOG\_ID\_REPORT\_DELETED

**Message Meaning:** Report deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32041 - LOG\_ID\_REPORT\_DELETED\_GUI

**Message ID:** 32041

**Message Description:** LOG\_ID\_REPORT\_DELETED\_GUI

**Message Meaning:** Report deleted from GUI

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32042 - LOG\_ID\_MEM\_LOG\_SECOND\_FULL

**Message ID:** 32042

**Message Description:** LOG\_ID\_MEM\_LOG\_SECOND\_FULL

**Message Meaning:** Memory log full over second warning level

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 32043 - LOG\_ID\_MEM\_LOG\_FINAL\_FULL

**Message ID:** 32043

**Message Description:** LOG\_ID\_MEM\_LOG\_FINAL\_FULL

**Message Meaning:** Memory log full over final warning level

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 32044 - LOG\_ID\_LOG\_DELETE

**Message ID:** 32044

**Message Description:** LOG\_ID\_LOG\_DELETE

**Message Meaning:** Log deleted by user

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32045 - LOG\_ID\_MGR\_LIC\_EXPIRE

**Message ID:** 32045**Message Description:** LOG\_ID\_MGR\_LIC\_EXPIRE**Message Meaning:** FortiGuard management service license expiring**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32048 - LOG\_ID\_SCHEDULE\_EXPIRE

**Message ID:** 32048

**Message Description:** LOG\_ID\_SCHEDULE\_EXPIRE

**Message Meaning:** One time schedule expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32049 - LOG\_ID\_FC\_EXPIRE

**Message ID:** 32049

**Message Description:** LOG\_ID\_FC\_EXPIRE

**Message Meaning:** FortiCloud license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32050 - LOG\_ID\_POL\_PKT\_CAPTURE\_FULL

**Message ID:** 32050

**Message Description:** LOG\_ID\_POL\_PKT\_CAPTURE\_FULL

**Message Meaning:** Policy packet capture full

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32051 - LOG\_ID\_LOG\_UPLOAD

**Message ID:** 32051

**Message Description:** LOG\_ID\_LOG\_UPLOAD

**Message Meaning:** Disk logs upload started

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 32052 - LOG\_ID\_UPLOAD\_RUN\_SCRIPT

**Message ID:** 32052

**Message Description:** LOG\_ID\_UPLOAD\_RUN\_SCRIPT

**Message Meaning:** Upload and run a script

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32053 - LOG\_ID\_ADMIN\_MTNER\_LOGIN\_SUCC

**Message ID:** 32053

**Message Description:** LOG\_ID\_ADMIN\_MTNER\_LOGIN\_SUCC

**Message Meaning:** Admin monitor login successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method		string	64
msg	Message Text	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32054 - LOG\_ID\_ADMIN\_MTNER\_LOGOUT

**Message ID:** 32054

**Message Description:** LOG\_ID\_ADMIN\_MTNER\_LOGOUT

**Message Meaning:** Admin monitor logout successful

**Type:** Event

**Category:** SYSTEM**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method		string	64
msg	Message Text	string	4096
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32057 - LOG\_ID\_VIEW\_FAZ\_LOG\_FAIL

**Message ID:** 32057**Message Description:** LOG\_ID\_VIEW\_FAZ\_LOG\_FAIL**Message Meaning:** FortiAnalyzer log access failed**Type:** Event

**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32058 - LOG\_ID\_VIEW\_FAZ\_LOG\_SUCC

**Message ID:** 32058**Message Description:** LOG\_ID\_VIEW\_FAZ\_LOG\_SUCC**Message Meaning:** FortiAnalyzer logs viewed successfully**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32095 - LOG\_ID\_GUI\_CHG\_SUB\_MODULE

**Message ID:** 32095

**Message Description:** LOG\_ID\_GUI\_CHG\_SUB\_MODULE

**Message Meaning:** Admin performed an action from GUI

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32097 - LOG\_ID\_DELETE\_CAPTURE\_PKT

**Message ID:** 32097

**Message Description:** LOG\_ID\_DELETE\_CAPTURE\_PKT

**Message Meaning:** Policy packet capture file deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32100 - LOG\_ID\_FORTI\_TOKEN\_SYNC

**Message ID:** 32100

**Message Description:** LOG\_ID\_FORTI\_TOKEN\_SYNC

**Message Meaning:** FortiToken synchronized

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32102 - LOG\_ID\_CHG\_CONFIG

**Message ID:** 32102

**Message Description:** LOG\_ID\_CHG\_CONFIG

**Message Meaning:** Configuration changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
module	Configuration Module Name	string	32
msg	Message Text	string	4096
submodule	Configuration Sub-Module Name	string	32
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32103 - LOG\_ID\_NEW\_FIRMWARE

**Message ID:** 32103

**Message Description:** LOG\_ID\_NEW\_FIRMWARE

**Message Meaning:** New firmware available on FortiGuard

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32104 - LOG\_ID\_CHG\_CONFIG\_GUI

**Message ID:** 32104

**Message Description:** LOG\_ID\_CHG\_CONFIG\_GUI

**Message Meaning:** Configuration changed via GUI

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
module	Configuration Module Name	string	32
msg	Message Text	string	4096
submodule	Configuration Sub-Module Name	string	32
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32105 - LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_REACHABLE

**Message ID:** 32105

**Message Description:** LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_REACHABLE

**Message Meaning:** NTP server status changes to reachable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32106 - LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_RESOLVABLE

**Message ID:** 32106

**Message Description:** LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_RESOLVABLE

**Message Meaning:** NTP server status changes to resolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32107 - LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_UNRESOLVABLE

**Message ID:** 32107

**Message Description:** LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_UNRESOLVABLE

**Message Meaning:** NTP server status changes to unresolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32108 - LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_UNREACHABLE

**Message ID:** 32108

**Message Description:** LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_UNREACHABLE

**Message Meaning:** NTP server status changes to unreachable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32109 - LOG\_ID\_UPD\_SIGN\_AV\_DB

**Message ID:** 32109

**Message Description:** LOG\_ID\_UPD\_SIGN\_AV\_DB

**Message Meaning:** Updating virus database

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32110 - LOG\_ID\_UPD\_SIGN\_IPS\_DB

**Message ID:** 32110

**Message Description:** LOG\_ID\_UPD\_SIGN\_IPS\_DB

**Message Meaning:** IPS database updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32111 - LOG\_ID\_UPD\_SIGN\_AVIPS\_DB

**Message ID:** 32111

**Message Description:** LOG\_ID\_UPD\_SIGN\_AVIPS\_DB

**Message Meaning:** AV, IPS, GeolP, SRC-VIS, FortiFlow, URL White-list, Certificate databases updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32113 - LOG\_ID\_UPD\_SIGN\_SRCVIS\_DB

**Message ID:** 32113

**Message Description:** LOG\_ID\_UPD\_SIGN\_SRCVIS\_DB

**Message Meaning:** SRC-VIS object updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32114 - LOG\_ID\_UPD\_SIGN\_GEOIP\_DB

**Message ID:** 32114

**Message Description:** LOG\_ID\_UPD\_SIGN\_GEOIP\_DB

**Message Meaning:** GeoIP object updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32116 - LOG\_ID\_UPD\_SIGN\_AVPKG\_FAILURE

**Message ID:** 32116

**Message Description:** LOG\_ID\_UPD\_SIGN\_AVPKG\_FAILURE

**Message Meaning:** AV package update by SCP failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32117 - LOG\_ID\_UPD\_SIGN\_AVPKG\_SUCCESS

**Message ID:** 32117

**Message Description:** LOG\_ID\_UPD\_SIGN\_AVPKG\_SUCCESS

**Message Meaning:** AV package update by SCP successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32118 - LOG\_ID\_UPD\_ADMIN\_AV\_DB

**Message ID:** 32118

**Message Description:** LOG\_ID\_UPD\_ADMIN\_AV\_DB

**Message Meaning:** AV updated by admin

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32119 - LOG\_ID\_UPD\_SCANUNIT\_AV\_DB

**Message ID:** 32119

**Message Description:** LOG\_ID\_UPD\_SCANUNIT\_AV\_DB

**Message Meaning:** AV database updated by scanunit

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32120 - LOG\_ID\_RPT\_ADD\_DATASET

**Message ID:** 32120

**Message Description:** LOG\_ID\_RPT\_ADD\_DATASET

**Message Meaning:** Report data set added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32122 - LOG\_ID\_RPT\_DEL\_DATASET

**Message ID:** 32122

**Message Description:** LOG\_ID\_RPT\_DEL\_DATASET

**Message Meaning:** Report data set deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32125 - LOG\_ID\_RPT\_ADD\_CHART

**Message ID:** 32125

**Message Description:** LOG\_ID\_RPT\_ADD\_CHART

**Message Meaning:** Report chart widget added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32126 - LOG\_ID\_RPT\_DEL\_CHART

**Message ID:** 32126

**Message Description:** LOG\_ID\_RPT\_DEL\_CHART

**Message Meaning:** Report chart widget deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32129 - LOG\_ID\_ADD\_GUEST

**Message ID:** 32129

**Message Description:** LOG\_ID\_ADD\_GUEST

**Message Meaning:** Guest user added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16



Log Field Name	Description	Data Type	Length
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32130 - LOG\_ID\_CHG\_USER

**Message ID:** 32130

**Message Description:** LOG\_ID\_CHG\_USER

**Message Meaning:** User changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
new_status	New Status	string	512
old_status	Original Status	string	512
passwd	Password	string	20
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32131 - LOG\_ID\_DEL\_GUEST

**Message ID:** 32131

**Message Description:** LOG\_ID\_DEL\_GUEST

**Message Meaning:** Guest user deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32132 - LOG\_ID\_ADD\_USER

**Message ID:** 32132

**Message Description:** LOG\_ID\_ADD\_USER

**Message Meaning:** Local user added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32138 - LOG\_ID\_REBOOT

**Message ID:** 32138

**Message Description:** LOG\_ID\_REBOOT

**Message Meaning:** Device rebooted

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32139 - LOG\_ID\_WAKE\_ON\_LAN

**Message ID:** 32139

**Message Description:** LOG\_ID\_WAKE\_ON\_LAN

**Message Meaning:** Wake on LAN device

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32140 - LOG\_ID\_TIME\_USER\_SETTING\_CHG

**Message ID:** 32140

**Message Description:** LOG\_ID\_TIME\_USER\_SETTING\_CHG

**Message Meaning:** Global time setting changed by user

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32141 - LOG\_ID\_TIME\_NTP\_SETTING\_CHG

**Message ID:** 32141

**Message Description:** LOG\_ID\_TIME\_NTP\_SETTING\_CHG

**Message Meaning:** Global time setting changed by NTP

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32142 - LOG\_ID\_BACKUP\_CONF

**Message ID:** 32142

**Message Description:** LOG\_ID\_BACKUP\_CONF

**Message Meaning:** System configuration backed up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32143 - LOG\_ID\_BACKUP\_CONF\_BY\_SCP

**Message ID:** 32143

**Message Description:** LOG\_ID\_BACKUP\_CONF\_BY\_SCP

**Message Meaning:** System configuration backed up by SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32144 - LOG\_ID\_BACKUP\_CONF\_ERROR

**Message ID:** 32144

**Message Description:** LOG\_ID\_BACKUP\_CONF\_ERROR

**Message Meaning:** System configuration backed up error

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32145 - LOG\_ID\_BACKUP\_CONF\_ALERT

**Message ID:** 32145

**Message Description:** LOG\_ID\_BACKUP\_CONF\_ALERT

**Message Meaning:** System configuration backed up alert

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32146 - LOG\_ID\_TIME\_PTP\_SETTING\_CHG

**Message ID:** 32146

**Message Description:** LOG\_ID\_TIME\_PTP\_SETTING\_CHG

**Message Meaning:** Global time setting changed by PTP

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32148 - LOG\_ID\_GET\_CRL

**Message ID:** 32148

**Message Description:** LOG\_ID\_GET\_CRL

**Message Meaning:** CRL update requested

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
crl		string	4096
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32149 - LOG\_ID\_COMMAND\_FAIL

**Message ID:** 32149

**Message Description:** LOG\_ID\_COMMAND\_FAIL

**Message Meaning:** Command failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32151 - LOG\_ID\_ADD\_IP6\_LOCAL\_POL

**Message ID:** 32151

**Message Description:** LOG\_ID\_ADD\_IP6\_LOCAL\_POL

**Message Meaning:** IPv6 firewall local in policy added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32152 - LOG\_ID\_CHG\_IP6\_LOCAL\_POL

**Message ID:** 32152

**Message Description:** LOG\_ID\_CHG\_IP6\_LOCAL\_POL

**Message Meaning:** IPv6 firewall local in policy setting changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32153 - LOG\_ID\_DEL\_IP6\_LOCAL\_POL

**Message ID:** 32153

**Message Description:** LOG\_ID\_DEL\_IP6\_LOCAL\_POL

**Message Meaning:** IPv6 firewall local in policy deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32155 - LOG\_ID\_ACT\_FTOKEN\_REQ

**Message ID:** 32155

**Message Description:** LOG\_ID\_ACT\_FTOKEN\_REQ

**Message Meaning:** FortiToken activation requested

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
serialno	Serial Number	string	16
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32156 - LOG\_ID\_ACT\_FTOKEN\_SUCC

**Message ID:** 32156

**Message Description:** LOG\_ID\_ACT\_FTOKEN\_SUCC

**Message Meaning:** FortiToken activation successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32157 - LOG\_ID\_SYNC\_FTOKEN\_SUCC

**Message ID:** 32157

**Message Description:** LOG\_ID\_SYNC\_FTOKEN\_SUCC

**Message Meaning:** FortiToken re-synchronized

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32



## 32158 - LOG\_ID\_SYNC\_FTOKEN\_FAIL

**Message ID:** 32158

**Message Description:** LOG\_ID\_SYNC\_FTOKEN\_FAIL

**Message Meaning:** FortiToken re-synchronization failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32159 - LOG\_ID\_ACT\_FTOKEN\_FAIL

**Message ID:** 32159

**Message Description:** LOG\_ID\_ACT\_FTOKEN\_FAIL

**Message Meaning:** FortiToken activation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32160 - LOG\_ID\_FTM\_PUSH\_SUCC

**Message ID:** 32160**Message Description:** LOG\_ID\_FTM\_PUSH\_SUCC**Message Meaning:** FortiToken mobile push message succeeded**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 32161 - LOG\_ID\_FTM\_PUSH\_FAIL

**Message ID:** 32161

**Message Description:** LOG\_ID\_FTM\_PUSH\_FAIL

**Message Meaning:** FortiToken mobile push message failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 32168 - LOG\_ID\_REACH\_VDOM\_LIMIT

**Message ID:** 32168

**Message Description:** LOG\_ID\_REACH\_VDOM\_LIMIT

**Message Meaning:** VDOM limit reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32169 - LOG\_ID\_ALARM\_DLP\_DB

**Message ID:** 32169

**Message Description:** LOG\_ID\_ALARM\_DLP\_DB

**Message Meaning:** DLP database space alarm

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32170 - LOG\_ID\_ALARM\_MSG

**Message ID:** 32170

**Message Description:** LOG\_ID\_ALARM\_MSG

**Message Meaning:** Alarm created

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
alarmid	Alarm ID	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
groupid	User Group ID	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32171 - LOG\_ID\_ALARM\_ACK

**Message ID:** 32171

**Message Description:** LOG\_ID\_ALARM\_ACK

**Message Meaning:** Alarm acknowledged

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
acktime	Alarm Acknowledge Time	string	24
action	Action	string	65
alarmid	Alarm ID	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32172 - LOG\_ID\_ADD\_IP4\_LOCAL\_POL

**Message ID:** 32172

**Message Description:** LOG\_ID\_ADD\_IP4\_LOCAL\_POL

**Message Meaning:** IPv4 firewall local in policy added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32173 - LOG\_ID\_CHG\_IP4\_LOCAL\_POL

**Message ID:** 32173

**Message Description:** LOG\_ID\_CHG\_IP4\_LOCAL\_POL

**Message Meaning:** IPv4 firewall local in policy's setting changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32174 - LOG\_ID\_DEL\_IP4\_LOCAL\_POL

**Message ID:** 32174

**Message Description:** LOG\_ID\_DEL\_IP4\_LOCAL\_POL

**Message Meaning:** IPv4 firewall local in policy deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20



Log Field Name	Description	Data Type	Length
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32190 - LOG\_ID\_UPT\_INVALID\_IMG

**Message ID:** 32190

**Message Description:** LOG\_ID\_UPT\_INVALID\_IMG

**Message Meaning:** Invalid image loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32191 - LOG\_ID\_UPT\_INVALID\_IMG\_CC

**Message ID:** 32191

**Message Description:** LOG\_ID\_UPT\_INVALID\_IMG\_CC

**Message Meaning:** Image with invalid CC signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32192 - LOG\_ID\_UPT\_INVALID\_IMG\_RSA

**Message ID:** 32192

**Message Description:** LOG\_ID\_UPT\_INVALID\_IMG\_RSA

**Message Meaning:** Image with invalid RSA signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32193 - LOG\_ID\_UPT\_IMG\_RSA

**Message ID:** 32193

**Message Description:** LOG\_ID\_UPT\_IMG\_RSA

**Message Meaning:** Image with valid RSA signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32194 - LOG\_ID\_UPT\_IMG\_FAIL

**Message ID:** 32194

**Message Description:** LOG\_ID\_UPT\_IMG\_FAIL

**Message Meaning:** System upgrade failed due to file operation failure

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32199 - LOG\_ID\_RESTORE\_IMG\_USB

**Message ID:** 32199

**Message Description:** LOG\_ID\_RESTORE\_IMG\_USB

**Message Meaning:** Image restored from USB

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32200 - LOG\_ID\_SHUTDOWN

**Message ID:** 32200

**Message Description:** LOG\_ID\_SHUTDOWN

**Message Meaning:** Device shutdown

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32201 - LOG\_ID\_LOAD\_IMG\_SUCC

**Message ID:** 32201

**Message Description:** LOG\_ID\_LOAD\_IMG\_SUCC

**Message Meaning:** Image loaded successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32202 - LOG\_ID\_RESTORE\_IMG

**Message ID:** 32202

**Message Description:** LOG\_ID\_RESTORE\_IMG

**Message Meaning:** Image restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32203 - LOG\_ID\_RESTORE\_CONF

**Message ID:** 32203

**Message Description:** LOG\_ID\_RESTORE\_CONF

**Message Meaning:** Configuration restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32204 - LOG\_ID\_RESTORE\_FGD\_SVR

**Message ID:** 32204

**Message Description:** LOG\_ID\_RESTORE\_FGD\_SVR

**Message Meaning:** FortiGuard service restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32205 - LOG\_ID\_RESTORE\_VDOM\_LIC

**Message ID:** 32205

**Message Description:** LOG\_ID\_RESTORE\_VDOM\_LIC

**Message Meaning:** VM license restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32206 - LOG\_ID\_RESTORE\_SCRIPT

**Message ID:** 32206

**Message Description:** LOG\_ID\_RESTORE\_SCRIPT

**Message Meaning:** Script restored from management station

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32207 - LOG\_ID\_RETRIEVE\_CONF\_LIST

**Message ID:** 32207

**Message Description:** LOG\_ID\_RETRIEVE\_CONF\_LIST

**Message Meaning:** Configuration list retrieval failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32208 - LOG\_ID\_IMP\_PKCS12\_CERT

**Message ID:** 32208

**Message Description:** LOG\_ID\_IMP\_PKCS12\_CERT

**Message Meaning:** PKCS12 certificate imported

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32209 - LOG\_ID\_RESTORE\_USR\_DEF\_IPS

**Message ID:** 32209

**Message Description:** LOG\_ID\_RESTORE\_USR\_DEF\_IPS

**Message Meaning:** IPS custom signatures restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32210 - LOG\_ID\_BACKUP\_IMG\_SUCC

**Message ID:** 32210

**Message Description:** LOG\_ID\_BACKUP\_IMG\_SUCC

**Message Meaning:** Firmware image backed up successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32211 - LOG\_ID\_UPLOAD\_REVISION

**Message ID:** 32211

**Message Description:** LOG\_ID\_UPLOAD\_REVISION

**Message Meaning:** Revision uploaded to flash disk

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32212 - LOG\_ID\_DEL\_REVISION

**Message ID:** 32212

**Message Description:** LOG\_ID\_DEL\_REVISION

**Message Meaning:** Revision deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32213 - LOG\_ID\_RESTORE\_TEMPLATE

**Message ID:** 32213

**Message Description:** LOG\_ID\_RESTORE\_TEMPLATE

**Message Meaning:** Template restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32214 - LOG\_ID\_RESTORE\_FILE

**Message ID:** 32214

**Message Description:** LOG\_ID\_RESTORE\_FILE

**Message Meaning:** File restore failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32215 - LOG\_ID\_UPT\_IMG

**Message ID:** 32215

**Message Description:** LOG\_ID\_UPT\_IMG

**Message Meaning:** Image updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32217 - LOG\_ID\_UPD\_IPS

**Message ID:** 32217

**Message Description:** LOG\_ID\_UPD\_IPS

**Message Meaning:** IPS package - Admin update successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32218 - LOG\_ID\_UPD\_DLP

**Message ID:** 32218

**Message Description:** LOG\_ID\_UPD\_DLP

**Message Meaning:** DLP fingerprint database update via SCP failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32219 - LOG\_ID\_BACKUP\_OUTPUT

**Message ID:** 32219

**Message Description:** LOG\_ID\_BACKUP\_OUTPUT

**Message Meaning:** Error output backup via SCP successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32220 - LOG\_ID\_BACKUP\_COMMAND

**Message ID:** 32220

**Message Description:** LOG\_ID\_BACKUP\_COMMAND

**Message Meaning:** Batch mode command output backup via SCP successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32221 - LOG\_ID\_UPD\_VDOM\_LIC

**Message ID:** 32221

**Message Description:** LOG\_ID\_UPD\_VDOM\_LIC

**Message Meaning:** VM license installed via SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32222 - LOG\_ID\_GLB\_SETTING\_CHG

**Message ID:** 32222

**Message Description:** LOG\_ID\_GLB\_SETTING\_CHG

**Message Meaning:** Global setting changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
new_value	New Virtual Domain Name	string	128
old_value	Original Virtual Domain name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32223 - LOG\_ID\_BACKUP\_USER\_DEF\_IPS

**Message ID:** 32223

**Message Description:** LOG\_ID\_BACKUP\_USER\_DEF\_IPS

**Message Meaning:** IPS custom signatures backup success

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32224 - LOG\_ID\_BACKUP\_DISK\_LOG

**Message ID:** 32224

**Message Description:** LOG\_ID\_BACKUP\_DISK\_LOG

**Message Meaning:** Disk logs backed up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
file	File Name for Generated Report?	string	256
hash	Hash Value of Downloaded File	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5



Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32225 - LOG\_ID\_DEL\_ALL\_REVISION

**Message ID:** 32225

**Message Description:** LOG\_ID\_DEL\_ALL\_REVISION

**Message Meaning:** Revision database reset due to data corruption

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32226 - LOG\_ID\_LOAD\_IMG\_FAIL

**Message ID:** 32226

**Message Description:** LOG\_ID\_LOAD\_IMG\_FAIL

**Message Meaning:** Image failed to load

**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32227 - LOG\_ID\_UPD\_DLP\_FAIL

**Message ID:** 32227**Message Description:** LOG\_ID\_UPD\_DLP\_FAIL**Message Meaning:** DLP fingerprint database failed to update by SCP**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32228 - LOG\_ID\_LOAD\_IMG\_FAIL\_WRONG\_IMG

**Message ID:** 32228

**Message Description:** LOG\_ID\_LOAD\_IMG\_FAIL\_WRONG\_IMG

**Message Meaning:** Firmware image loaded incorrect

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32229 - LOG\_ID\_LOAD\_IMG\_FAIL\_NO\_RSA

**Message ID:** 32229

**Message Description:** LOG\_ID\_LOAD\_IMG\_FAIL\_NO\_RSA

**Message Meaning:** Firmware image without valid RSA signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32230 - LOG\_ID\_LOAD\_IMG\_FAIL\_INVALID\_RSA

**Message ID:** 32230

**Message Description:** LOG\_ID\_LOAD\_IMG\_FAIL\_INVALID\_RSA

**Message Meaning:** Firmware image with invalid RSA signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32231 - LOG\_ID\_RESTORE\_FGD\_SVR\_FAIL

**Message ID:** 32231

**Message Description:** LOG\_ID\_RESTORE\_FGD\_SVR\_FAIL

**Message Meaning:** FortiGuard service failed to restore

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32232 - LOG\_ID\_RESTORE\_VDOM\_LIC\_FAIL

**Message ID:** 32232

**Message Description:** LOG\_ID\_RESTORE\_VDOM\_LIC\_FAIL

**Message Meaning:** VM license failed to restore

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32233 - LOG\_ID\_BACKUP\_IMG\_FAIL

**Message ID:** 32233

**Message Description:** LOG\_ID\_BACKUP\_IMG\_FAIL

**Message Meaning:** Firmware image backup failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32234 - LOG\_ID\_RESTORE\_IMG\_INVALID\_CC

**Message ID:** 32234

**Message Description:** LOG\_ID\_RESTORE\_IMG\_INVALID\_CC

**Message Meaning:** Image with invalid CC signature restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32235 - LOG\_ID\_RESTORE\_IMG\_FORTIGUARD

**Message ID:** 32235

**Message Description:** LOG\_ID\_RESTORE\_IMG\_FORTIGUARD



**Message Meaning:** Image restored from FortiGuard Management

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32236 - LOG\_ID\_BACKUP\_MEM\_LOG

**Message ID:** 32236

**Message Description:** LOG\_ID\_BACKUP\_MEM\_LOG

**Message Meaning:** Memory logs backed up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32237 - LOG\_ID\_BACKUP\_MEM\_LOG\_FAIL

**Message ID:** 32237

**Message Description:** LOG\_ID\_BACKUP\_MEM\_LOG\_FAIL

**Message Meaning:** Memory logs failed to back up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32238 - LOG\_ID\_BACKUP\_DISK\_LOG\_FAIL

**Message ID:** 32238

**Message Description:** LOG\_ID\_BACKUP\_DISK\_LOG\_FAIL

**Message Meaning:** Disk logs failed to back up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32239 - LOG\_ID\_BACKUP\_DISK\_LOG\_USB

**Message ID:** 32239

**Message Description:** LOG\_ID\_BACKUP\_DISK\_LOG\_USB

**Message Meaning:** Disk logs backed up to USB

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32240 - LOG\_ID\_SYS\_USB\_MODE

**Message ID:** 32240

**Message Description:** LOG\_ID\_SYS\_USB\_MODE

**Message Meaning:** System operating in USB mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32241 - LOG\_ID\_BACKUP\_DISK\_LOG\_USB\_FAIL

**Message ID:** 32241

**Message Description:** LOG\_ID\_BACKUP\_DISK\_LOG\_USB\_FAIL

**Message Meaning:** Disk logs failed to back up to USB

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32242 - LOG\_ID\_UPD\_VDOM\_LIC\_FAIL

**Message ID:** 32242

**Message Description:** LOG\_ID\_UPD\_VDOM\_LIC\_FAIL

**Message Meaning:** VM license failed to install via SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32243 - LOG\_ID\_UPD\_IPS\_SCP

**Message ID:** 32243

**Message Description:** LOG\_ID\_UPD\_IPS\_SCP

**Message Meaning:** IPS package updated via SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32244 - LOG\_ID\_UPD\_IPS\_SCP\_FAIL

**Message ID:** 32244

**Message Description:** LOG\_ID\_UPD\_IPS\_SCP\_FAIL

**Message Meaning:** IPS package failed to update via SCP

**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32245 - LOG\_ID\_BACKUP\_USER\_DEF\_IPS\_FAIL

**Message ID:** 32245**Message Description:** LOG\_ID\_BACKUP\_USER\_DEF\_IPS\_FAIL**Message Meaning:** IPS custom signatures backup failed**Type:** Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32246 - LOG\_ID\_RESTORE\_USR\_DEF\_IPS\_CRITICAL

**Message ID:** 32246

**Message Description:** LOG\_ID\_RESTORE\_USR\_DEF\_IPS\_CRITICAL

**Message Meaning:** IPS custom signatures restored critical

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32247 - LOG\_ID\_SSH\_NEGOTIATION\_FAILURE

**Message ID:** 32247

**Message Description:** LOG\_ID\_SSH\_NEGOTIATION\_FAILURE

**Message Meaning:** SSH protocol cannot be negotiated

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
addr	IP Address	string	80
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
port	Port Number	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32252 - LOG\_ID\_FACTORY\_RESET

**Message ID:** 32252

**Message Description:** LOG\_ID\_FACTORY\_RESET

**Message Meaning:** Factory settings reset

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32253 - LOG\_ID\_FORMAT\_RAID

**Message ID:** 32253

**Message Description:** LOG\_ID\_FORMAT\_RAID

**Message Meaning:** RAID disk formatted

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32254 - LOG\_ID\_ENABLE\_RAID

**Message ID:** 32254

**Message Description:** LOG\_ID\_ENABLE\_RAID

**Message Meaning:** RAID enabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32255 - LOG\_ID\_DISABLE\_RAID

**Message ID:** 32255

**Message Description:** LOG\_ID\_DISABLE\_RAID

**Message Meaning:** RAID disabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32300 - LOG\_ID\_UPLOAD\_RPT\_IMG

**Message ID:** 32300

**Message Description:** LOG\_ID\_UPLOAD\_RPT\_IMG

**Message Meaning:** Report image file uploaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32301 - LOG\_ID\_ADD\_VDOM

**Message ID:** 32301

**Message Description:** LOG\_ID\_ADD\_VDOM

**Message Meaning:** VDOM added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32302 - LOG\_ID\_DEL\_VDOM

**Message ID:** 32302

**Message Description:** LOG\_ID\_DEL\_VDOM

**Message Meaning:** VDOM deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32545 - LOG\_ID\_SYS\_RESTART

**Message ID:** 32545

**Message Description:** LOG\_ID\_SYS\_RESTART

**Message Meaning:** Scheduled daily reboot started

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32546 - LOG\_ID\_APPLICATION\_CRASH

**Message ID:** 32546

**Message Description:** LOG\_ID\_APPLICATION\_CRASH

**Message Meaning:** Application crashed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32547 - LOG\_ID\_AUTOSCRIPT\_START

**Message ID:** 32547

**Message Description:** LOG\_ID\_AUTOSCRIPT\_START

**Message Meaning:** Autoscript start

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32548 - LOG\_ID\_AUTOSCRIPT\_STOP

**Message ID:** 32548

**Message Description:** LOG\_ID\_AUTOSCRIPT\_STOP

**Message Meaning:** Autoscript stop

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32549 - LOG\_ID\_AUTOSCRIPT\_STOP\_AUTO

**Message ID:** 32549

**Message Description:** LOG\_ID\_AUTOSCRIPT\_STOP\_AUTO

**Message Meaning:** Autoscript stop automatically

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32550 - LOG\_ID\_AUTOSCRIPT\_DELETE\_RSLT

**Message ID:** 32550

**Message Description:** LOG\_ID\_AUTOSCRIPT\_DELETE\_RSLT

**Message Meaning:** Autoscript delete result

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32551 - LOG\_ID\_AUTOSCRIPT\_BACKUP\_RSLT

**Message ID:** 32551

**Message Description:** LOG\_ID\_AUTOSCRIPT\_BACKUP\_RSLT

**Message Meaning:** Autoscript backup result

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32552 - LOG\_ID\_AUTOSCRIPT\_CHECK\_STATUS

**Message ID:** 32552

**Message Description:** LOG\_ID\_AUTOSCRIPT\_CHECK\_STATUS

**Message Meaning:** Autoscript check status

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32553 - LOG\_ID\_AUTOSCRIPT\_STOP\_REACH\_LIMIT

**Message ID:** 32553

**Message Description:** LOG\_ID\_AUTOSCRIPT\_STOP\_REACH\_LIMIT

**Message Meaning:** Autoscript stop due to limit reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32561 - LOG\_ID\_ADMIN\_LOGOUT\_DISCONNECT

**Message ID:** 32561

**Message Description:** LOG\_ID\_ADMIN\_LOGOUT\_DISCONNECT

**Message Meaning:** Admin disconnected

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method		string	64
msg	Message Text	string	4096
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32562 - LOG\_ID\_STORE\_CONF\_FAIL\_SPACE

**Message ID:** 32562

**Message Description:** LOG\_ID\_STORE\_CONF\_FAIL\_SPACE

**Message Meaning:** Store config failed - not enough flash space

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32



## 32564 - LOG\_ID\_RESTORE\_CONF\_FAIL

**Message ID:** 32564

**Message Description:** LOG\_ID\_RESTORE\_CONF\_FAIL

**Message Meaning:** Configuration failed to restore

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32565 - LOG\_ID\_RESTORE\_CONF\_BY\_MGMT

**Message ID:** 32565

**Message Description:** LOG\_ID\_RESTORE\_CONF\_BY\_MGMT

**Message Meaning:** Configuration restored from management station

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32566 - LOG\_ID\_RESTORE\_CONF\_BY\_SCP

**Message ID:** 32566

**Message Description:** LOG\_ID\_RESTORE\_CONF\_BY\_SCP

**Message Meaning:** Configuration restored by SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32567 - LOG\_ID\_RESTORE\_CONF\_BY\_USB

**Message ID:** 32567

**Message Description:** LOG\_ID\_RESTORE\_CONF\_BY\_USB

**Message Meaning:** Configuration restored by USB

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32568 - LOG\_ID\_DEL\_REVISION\_DB

**Message ID:** 32568

**Message Description:** LOG\_ID\_DEL\_REVISION\_DB

**Message Meaning:** Revision Database deletion

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 32569 - LOG\_ID\_FSW\_SWITCH\_LOG\_EVENT

**Message ID:** 32569

**Message Description:** LOG\_ID\_FSW\_SWITCH\_LOG\_EVENT

**Message Meaning:** Switch-Controller

**Type:** Event

**Category:** SYSTEM

**Severity:** Unknown

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32570 - LOG\_ID\_ADMIN\_MTNER\_LOGOUT\_DISCONNECT

**Message ID:** 32570

**Message Description:** LOG\_ID\_ADMIN\_MTNER\_LOGOUT\_DISCONNECT

**Message Meaning:** Admin monitor disconnected

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method		string	64
msg	Message Text	string	4096
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32601 - LOG\_ID\_FGT\_SWITCH\_LOG\_DISCOVER

**Message ID:** 32601

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_DISCOVER

**Message Meaning:** Switch-Controller discovered

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32602 - LOG\_ID\_FGT\_SWITCH\_LOG\_AUTH

**Message ID:** 32602

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_AUTH

**Message Meaning:** Switch-Controller authorized

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32603 - LOG\_ID\_FGT\_SWITCH\_LOG\_DEAUTH

**Message ID:** 32603

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_DEAUTH

**Message Meaning:** Switch-Controller deauthorized

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32



## 32604 - LOG\_ID\_FGT\_SWITCH\_LOG\_DELETE

**Message ID:** 32604

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_DELETE

**Message Meaning:** Switch-Controller deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32605 - LOG\_ID\_FGT\_SWITCH\_LOG\_TUNNEL\_UP

**Message ID:** 32605

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_TUNNEL\_UP

**Message Meaning:** Switch-Controller Tunnel Up

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32606 - LOG\_ID\_FGT\_SWITCH\_LOG\_TUNNEL\_DOWN

**Message ID:** 32606

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_TUNNEL\_DOWN

**Message Meaning:** Switch-Controller Tunnel Down

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32607 - LOG\_ID\_FGT\_SWITCH\_PUSH\_IMAGE

**Message ID:** 32607

**Message Description:** LOG\_ID\_FGT\_SWITCH\_PUSH\_IMAGE

**Message Meaning:** Image push to FortiSwitch

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32608 - LOG\_ID\_FGT\_SWITCH\_STAGE\_IMAGE

**Message ID:** 32608

**Message Description:** LOG\_ID\_FGT\_SWITCH\_STAGE\_IMAGE

**Message Meaning:** Image stage to FortiSwitch

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32609 - LOG\_ID\_FGT\_SWITCH\_DISABLE\_DISCOVERY

**Message ID:** 32609

**Message Description:** LOG\_ID\_FGT\_SWITCH\_DISABLE\_DISCOVERY

**Message Meaning:** Disable FortiSwitch Discovery

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32610 - LOG\_ID\_FGT\_SWITCH\_LOG\_WARNING

**Message ID:** 32610

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_WARNING

**Message Meaning:** Switch-Controller warning

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32611 - LOG\_ID\_FGT\_SWITCH\_EXPORT\_POOL

**Message ID:** 32611

**Message Description:** LOG\_ID\_FGT\_SWITCH\_EXPORT\_POOL

**Message Meaning:** Export port to pool

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32612 - LOG\_ID\_FGT\_SWITCH\_EXPORT\_VDOM

**Message ID:** 32612

**Message Description:** LOG\_ID\_FGT\_SWITCH\_EXPORT\_VDOM

**Message Meaning:** Export port to vdom

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32613 - LOG\_ID\_FGT\_SWITCH\_REQUEST\_PORT

**Message ID:** 32613

**Message Description:** LOG\_ID\_FGT\_SWITCH\_REQUEST\_PORT

**Message Meaning:** Request port from pool

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32614 - LOG\_ID\_FGT\_SWITCH\_RETURN\_PORT

**Message ID:** 32614

**Message Description:** LOG\_ID\_FGT\_SWITCH\_RETURN\_PORT

**Message Meaning:** Return port to pool

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096



Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 32615 - LOG\_ID\_FGT\_SWITCH\_MAC\_ADD

**Message ID:** 32615

**Message Description:** LOG\_ID\_FGT\_SWITCH\_MAC\_ADD

**Message Meaning:** FortiSwitch MAC add

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32616 - LOG\_ID\_FGT\_SWITCH\_MAC\_DEL

**Message ID:** 32616

**Message Description:** LOG\_ID\_FGT\_SWITCH\_MAC\_DEL

**Message Meaning:** FortiSwitch MAC delete

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32617 - LOG\_ID\_FGT\_SWITCH\_MAC\_MOVE

**Message ID:** 32617

**Message Description:** LOG\_ID\_FGT\_SWITCH\_MAC\_MOVE

**Message Meaning:** FortiSwitch MAC move

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32693 - LOG\_ID\_FGT\_SWITCH\_GROUP\_SWC

**Message ID:** 32693

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_SWC

**Message Meaning:** FortiSwitch switch controller

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32694 - LOG\_ID\_FGT\_SWITCH\_GROUP\_POE

**Message ID:** 32694

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_POE

**Message Meaning:** FortiSwitch PoE

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32695 - LOG\_ID\_FGT\_SWITCH\_GROUP\_LINK

**Message ID:** 32695

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_LINK

**Message Meaning:** FortiSwitch link

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32696 - LOG\_ID\_FGT\_SWITCH\_GROUP\_STP

**Message ID:** 32696

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_STP

**Message Meaning:** FortiSwitch spanning Tree

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32697 - LOG\_ID\_FGT\_SWITCH\_GROUP\_SWITCH

**Message ID:** 32697

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_SWITCH

**Message Meaning:** FortiSwitch switch

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32698 - LOG\_ID\_FGT\_SWITCH\_GROUP\_ROUTER

**Message ID:** 32698

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_ROUTER

**Message Meaning:** FortiSwitch router

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32699 - LOG\_ID\_FGT\_SWITCH\_GROUP\_SYSTEM

**Message ID:** 32699

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_SYSTEM

**Message Meaning:** FortiSwitch system

**Type:** Event



**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32700 - LOG\_ID\_DPDK\_EARLY\_INIT\_FAIL

**Message ID:** 32700**Message Description:** LOG\_ID\_DPDK\_EARLY\_INIT\_FAIL**Message Meaning:** Log description is not available**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 34415 - LOG\_ID\_NP6\_IPSEC\_ENGINE\_BUSY

**Message ID:** 34415

**Message Description:** LOG\_ID\_NP6\_IPSEC\_ENGINE\_BUSY

**Message Meaning:** NP6 IPsec engine is busy

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 34416 - LOG\_ID\_NP6\_IPSEC\_ENGINE\_POSSIBLY\_LOCKUP

**Message ID:** 34416

**Message Description:** LOG\_ID\_NP6\_IPSEC\_ENGINE\_POSSIBLY\_LOCKUP

**Message Meaning:** NP6 IPsec engine is possibly locked up

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 34417 - LOG\_ID\_NP6\_IPSEC\_ENGINE\_LOCKUP

**Message ID:** 34417

**Message Description:** LOG\_ID\_NP6\_IPSEC\_ENGINE\_LOCKUP

**Message Meaning:** NP6 IPsec engine is locked up

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 35001 - LOG\_ID\_HA\_SYNC\_VIRDB

**Message ID:** 35001

**Message Description:** LOG\_ID\_HA\_SYNC\_VIRDB

**Message Meaning:** HA slave synchronized Virus database

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 35002 - LOG\_ID\_HA\_SYNC\_ETDB

**Message ID:** 35002

**Message Description:** LOG\_ID\_HA\_SYNC\_ETDB

**Message Meaning:** HA slave synchronized Extended database

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 35003 - LOG\_ID\_HA\_SYNC\_EXDB

**Message ID:** 35003

**Message Description:** LOG\_ID\_HA\_SYNC\_EXDB

**Message Meaning:** HA slave synchronized Extreme database

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 35004 - LOG\_ID\_HA\_SYNC\_FLDB

**Message ID:** 35004

**Message Description:** LOG\_ID\_HA\_SYNC\_FLDB

**Message Meaning:** HA slave synchronized FLDB

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 35005 - LOG\_ID\_HA\_SYNC\_IPS

**Message ID:** 35005

**Message Description:** LOG\_ID\_HA\_SYNC\_IPS

**Message Meaning:** HA slave synchronized IDS package

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 35007 - LOG\_ID\_HA\_SYNC\_AV

**Message ID:** 35007

**Message Description:** LOG\_ID\_HA\_SYNC\_AV

**Message Meaning:** HA slave synchronized AntiVirus package

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 35009 - LOG\_ID\_HA\_SYNC\_CID

**Message ID:** 35009

**Message Description:** LOG\_ID\_HA\_SYNC\_CID

**Message Meaning:** HA slave synchronized CID package

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32



## 35011 - LOG\_ID\_HA\_SYNC\_FAIL

**Message ID:** 35011

**Message Description:** LOG\_ID\_HA\_SYNC\_FAIL

**Message Meaning:** HA slave synchronization failed

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 35012 - LOG\_ID\_CONF\_SYNC\_FAIL

**Message ID:** 35012

**Message Description:** LOG\_ID\_CONF\_SYNC\_FAIL

**Message Meaning:** Slave sync failed

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 35013 - LOG\_ID\_HA\_FAILOVER\_FAIL

**Message ID:** 35013

**Message Description:** LOG\_ID\_HA\_FAILOVER\_FAIL

**Message Meaning:** HA failover failed

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 35014 - LOG\_ID\_HA\_RESET\_UPTIME

**Message ID:** 35014

**Message Description:** LOG\_ID\_HA\_RESET\_UPTIME

**Message Meaning:** HA reset uptime

**Type:** Event

**Category:** HA

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui		string	64
user		string	256
vd	Virtual Domain Name	string	32

## 35015 - LOG\_ID\_HA\_CLEAR\_HISTORY

**Message ID:** 35015

**Message Description:** LOG\_ID\_HA\_CLEAR\_HISTORY

**Message Meaning:** HA clear history

**Type:** Event

**Category:** HA

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui		string	64
user		string	256
vd	Virtual Domain Name	string	32

## 36881 - LOG\_ID\_EVENT\_SYSTEM\_CFG\_REVERT

**Message ID:** 36881

**Message Description:** LOG\_ID\_EVENT\_SYSTEM\_CFG\_REVERT

**Message Meaning:** Configuration reverted due to timeout

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 36882 - LOG\_ID\_EVENT\_SYSTEM\_CFG\_MANUALLY\_SAVED

**Message ID:** 36882

**Message Description:** LOG\_ID\_EVENT\_SYSTEM\_CFG\_MANUALLY\_SAVED

**Message Meaning:** Configuration manually saved

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 37120 - MESGID\_NEG\_GENERIC\_P1\_NOTIF

**Message ID:** 37120

**Message Description:** MESGID\_NEG\_GENERIC\_P1\_NOTIF

**Message Meaning:** Negotiate IPsec phase 1

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128

Log Field Name	Description	Data Type	Length
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37121 - MESGID\_NEG\_GENERIC\_P1\_ERROR

**Message ID:** 37121

**Message Description:** MESGID\_NEG\_GENERIC\_P1\_ERROR

**Message Meaning:** Negotiate IPsec phase 1

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37122 - MESGID\_NEG\_GENERIC\_P2\_NOTIF

**Message ID:** 37122

**Message Description:** MESGID\_NEG\_GENERIC\_P2\_NOTIF

**Message Meaning:** Negotiate IPsec phase 2

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	21
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5



Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37123 - MESGID\_NEG\_GENERIC\_P2\_ERROR

**Message ID:** 37123

**Message Description:** MESGID\_NEG\_GENERIC\_P2\_ERROR

**Message Meaning:** Negotiate IPsec phase 2

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	21
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37124 - MESGID\_NEG\_I\_P1\_ERROR

**Message ID:** 37124

**Message Description:** MESGID\_NEG\_I\_P1\_ERROR

**Message Meaning:** IPsec phase 1 error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37125 - MESGID\_NEG\_I\_P2\_ERROR

**Message ID:** 37125

**Message Description:** MESGID\_NEG\_I\_P2\_ERROR

**Message Meaning:** IPsec phase 2 error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37126 - MESGID\_NEG\_NO\_STATE\_ERROR

**Message ID:** 37126

**Message Description:** MESGID\_NEG\_NO\_STATE\_ERROR

**Message Meaning:** IPsec no state error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37127 - MESGID\_NEG\_PROGRESS\_P1\_NOTIF

**Message ID:** 37127

**Message Description:** MESGID\_NEG\_PROGRESS\_P1\_NOTIF

**Message Meaning:** Progress IPsec phase 1

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch		string	14
group	User Group Name	string	64
init		string	6
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37128 - MESGID\_NEG\_PROGRESS\_P1\_ERROR

**Message ID:** 37128

**Message Description:** MESGID\_NEG\_PROGRESS\_P1\_ERROR

**Message Meaning:** Progress IPsec phase 1

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch		string	14
group	User Group Name	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32



Log Field Name	Description	Data Type	Length
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37129 - MESGID\_NEG\_PROGRESS\_P2\_NOTIF

**Message ID:** 37129

**Message Description:** MESGID\_NEG\_PROGRESS\_P2\_NOTIF

**Message Meaning:** Progress IPsec phase 2

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch		string	14
group	User Group Name	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	4096

Log Field Name	Description	Data Type	Length
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37130 - MESGID\_NEG\_PROGRESS\_P2\_ERROR

**Message ID:** 37130

**Message Description:** MESGID\_NEG\_PROGRESS\_P2\_ERROR

**Message Meaning:** Progress IPsec phase 2

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch		string	14
group	User Group Name	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37131 - MESGID\_ESP\_ERROR

**Message ID:** 37131

**Message Description:** MESGID\_ESP\_ERROR

**Message Meaning:** IPsec ESP

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37132 - MESGID\_ESP\_CRITICAL

**Message ID:** 37132

**Message Description:** MESGID\_ESP\_CRITICAL

**Message Meaning:** IPsec ESP

**Type:** Event

**Category:** VPN

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37133 - MESSAGES\_INSTALL\_SA

**Message ID:** 37133

**Message Description:** MESSAGES\_INSTALL\_SA

**Message Meaning:** IPsec SA installed

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37134 - MESGID\_DELETE\_P1\_SA

**Message ID:** 37134

**Message Description:** MESGID\_DELETE\_P1\_SA

**Message Meaning:** IPsec phase 1 SA deleted

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37135 - MESGID\_DELETE\_P2\_SA

**Message ID:** 37135

**Message Description:** MESGID\_DELETE\_P2\_SA

**Message Meaning:** IPsec phase 2 SA deleted

**Type:** Event

**Category:** VPN



**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

**37136 - MMSGID\_DPD\_FAILURE****Message ID:** 37136

**Message Description:** MESGID\_DPD\_FAILURE**Message Meaning:** IPsec DPD failed**Type:** Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37137 - MESGID\_CONN\_FAILURE

**Message ID:** 37137

**Message Description:** MESGID\_CONN\_FAILURE

**Message Meaning:** IPsec connection failed

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37138 - MESGID\_CONN\_UPDOWN

**Message ID:** 37138

**Message Description:** MESGID\_CONN\_UPDOWN

**Message Meaning:** IPsec connection status changed

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37139 - MESGID\_P2\_UPDOWN

**Message ID:** 37139

**Message Description:** MESGID\_P2\_UPDOWN

**Message Meaning:** IPsec phase 2 status changed

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
outintf	Out interface	string	32
phase2_name	Phase 2 Name	string	128
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37141 - MESGID\_CONN\_STATS

**Message ID:** 37141

**Message Description:** MESGID\_CONN\_STATS

**Message Meaning:** IPsec tunnel statistics

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
assignip	Assigned IP Address	ip	39

Log Field Name	Description	Data Type	Length
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37889 - MESSAGES\_VC\_DELETE

**Message ID:** 37889

**Message Description:** MESSAGES\_VC\_DELETE

**Message Meaning:** Virtual cluster deleted

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37890 - MESSAGES\_VC\_MOVE\_VDOM

**Message ID:** 37890

**Message Description:** MESSAGES\_VC\_MOVE\_VDOM

**Message Meaning:** Virtual cluster VDOM moved

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10



Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
from_vcluster	source virtual cluster number	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
to_vcluster	destination virtual cluster number	uint32	10
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vdname	vdom name	string	32

## 37891 - MESGID\_VC\_ADD\_VDOM

**Message ID:** 37891

**Message Description:** MESGID\_VC\_ADD\_VDOM

**Message Meaning:** Virtual cluster VDOM added

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
to_vcluster	destination virtual cluster number	uint32	10
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vdname	vdom name	string	32

### 37892 - MESGID\_VC\_MOVE\_MEMB\_STATE

**Message ID:** 37892

**Message Description:** MESGID\_VC\_MOVE\_MEMB\_STATE

**Message Meaning:** Virtual cluster member state moved

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vcluster_member		uint32	10
vcluster_state		string	7
vd	Virtual Domain Name	string	32

## 37893 - MESSAGES\_VC\_DETECT\_MEMBERS\_DEAD

**Message ID:** 37893

**Message Description:** MESSAGES\_VC\_DETECT\_MEMBERS\_DEAD

**Message Meaning:** Virtual cluster member dead

**Type:** Event

**Category:** HA

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37894 - MESSAGES\_VC\_DETECT\_MEMBERS\_JOIN

**Message ID:** 37894

**Message Description:** MESSAGES\_VC\_DETECT\_MEMBERS\_JOIN

**Message Meaning:** Virtual cluster member joined

**Type:** Event

**Category:** HA

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37895 - MESSAGES\_VC\_ADD\_HADEV

**Message ID:** 37895

**Message Description:** MESSAGES\_VC\_ADD\_HADEV

**Message Meaning:** Virtual cluster added HA device interface

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

### 37896 - MESGID\_VC\_DEL\_HADEV

**Message ID:** 37896

**Message Description:** MESGID\_VC\_DEL\_HADEV

**Message Meaning:** Virtual cluster deleted HA device interface

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37897 - MESSAGESID\_HADEV\_READY

**Message ID:** 37897

**Message Description:** MESSAGESID\_HADEV\_READY

**Message Meaning:** HA device interface ready

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 37898 - MESSAGESID\_HADEV\_FAIL

**Message ID:** 37898

**Message Description:** MESSAGESID\_HADEV\_FAIL

**Message Meaning:** HA device interface failed

**Type:** Event

**Category:** HA

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 37899 - MESGID\_HADEV\_PEERINFO

**Message ID:** 37899

**Message Description:** MESGID\_HADEV\_PEERINFO

**Message Meaning:** HA device interface peer information

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 37900 - MESSAGESID\_HBDEV\_DELETE

**Message ID:** 37900

**Message Description:** MESSAGESID\_HBDEV\_DELETE

**Message Meaning:** Heartbeat device interface deleted

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32



## 37901 - MESSAGESID\_HBDEV\_DOWN

**Message ID:** 37901

**Message Description:** MESSAGESID\_HBDEV\_DOWN

**Message Meaning:** Heartbeat device interface down

**Type:** Event

**Category:** HA

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
hbdn_reason	heartbeat down reason	string	18
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 37902 - MESSAGESID\_HBDEV\_UP

**Message ID:** 37902

**Message Description:** MESSAGESID\_HBDEV\_UP

**Message Meaning:** Heartbeat device interface up

**Type:** Event

**Category:** HA

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 37903 - MESGID\_SYNC\_STATUS

**Message ID:** 37903

**Message Description:** MESGID\_SYNC\_STATUS

**Message Meaning:** Synchronization status with master

**Type:** Event

**Category:** HA

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
sync_status	The sync status with the master	string	11
sync_type	The sync type with the master	string	14
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 37904 - MESSAGESID\_HA\_ACTIVITY

**Message ID:** 37904

**Message Description:** MESSAGESID\_HA\_ACTIVITY

**Message Meaning:** Device set as HA master

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha-prio	HA Priority	uint8	3
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 37907 - MESSAGES\_VLAN\_HB\_UP

**Message ID:** 37907

**Message Description:** MESSAGES\_VLAN\_HB\_UP

**Message Meaning:** VLAN heartbeat started

**Type:** Event

**Category:** HA

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 37908 - MESSAGES\_VLAN\_HB\_DOWN

**Message ID:** 37908

**Message Description:** MESSAGES\_VLAN\_HB\_DOWN

**Message Meaning:** VLAN heartbeat lost

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

### 37909 - MESGID\_VLAN\_HB\_DOWN\_SUM

**Message ID:** 37909

**Message Description:** MESGID\_VLAN\_HB\_DOWN\_SUM

**Message Meaning:** VLAN heartbeat lost summary

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38010 - LOG\_ID\_FIPS\_ENCRY\_FAIL

**Message ID:** 38010

**Message Description:** LOG\_ID\_FIPS\_ENCRY\_FAIL

**Message Meaning:** FIPS CC encryption failed

**Type:** Event

**Category:** USER

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38011 - LOG\_ID\_FIPS\_DECRY\_FAIL

**Message ID:** 38011

**Message Description:** LOG\_ID\_FIPS\_DECRY\_FAIL

**Message Meaning:** FIPS CC decryption failed

**Type:** Event

**Category:** USER

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38012 - LOG\_ID\_ENTROPY\_TOKEN

**Message ID:** 38012

**Message Description:** LOG\_ID\_ENTROPY\_TOKEN

**Message Meaning:** Seeding from entropy source

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 38031 - LOG\_ID\_FSSO\_LOGON

**Message ID:** 38031

**Message Description:** LOG\_ID\_FSSO\_LOGON

**Message Meaning:** FSSO logon successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
status	Status	string	23



Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 38032 - LOG\_ID\_FSSO\_LOGOFF

**Message ID:** 38032

**Message Description:** LOG\_ID\_FSSO\_LOGOFF

**Message Meaning:** FSSO logout successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 38033 - LOG\_ID\_FSSO\_SVR\_STATUS

**Message ID:** 38033

**Message Description:** LOG\_ID\_FSSO\_SVR\_STATUS

**Message Meaning:** FSSO Active Directory server authentication status

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 38400 - LOGID\_EVENT\_NOTIF\_SEND\_SUCC

**Message ID:** 38400

**Message Description:** LOGID\_EVENT\_NOTIF\_SEND\_SUCC

**Message Meaning:** Notification message sent

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
eventtime		uint64	20
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
profile	Profile Name	string	64
profilegroup	Profile Group Name	string	4
profiletype	Profile Type	string	64
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
to	Recipient Email Addresses for Notification	string	512
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
virus	Virus Name	string	128

## 38401 - LOGID\_EVENT\_NOTIF\_SEND\_FAIL

**Message ID:** 38401

**Message Description:** LOGID\_EVENT\_NOTIF\_SEND\_FAIL

**Message Meaning:** Notification message send failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
eventtime		uint64	20
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
profile	Profile Name	string	64
profilegroup	Profile Group Name	string	4
profiletype	Profile Type	string	64
service	Name of Service	string	64
sess_duration	Session Duration	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
to	Recipient Email Addresses for Notification	string	512
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
virus	Virus Name	string	128

## 38402 - LOGID\_EVENT\_NOTIF\_DNS\_FAIL

**Message ID:** 38402

**Message Description:** LOGID\_EVENT\_NOTIF\_DNS\_FAIL

**Message Meaning:** MMSC hostname unresolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
hostname	Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
profile	Profile Name	string	64
profiletype	Profile Type	string	64
profile_vd	Virtual Domain Name	string	64
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38403 - LOGID\_EVENT\_NOTIF\_INSUFFICIENT\_RESOURCE

**Message ID:** 38403

**Message Description:** LOGID\_EVENT\_NOTIF\_INSUFFICIENT\_RESOURCE

**Message Meaning:** Insufficient system resource notification

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38404 - LOGID\_EVENT\_NOTIF\_HOSTNAME\_ERROR

**Message ID:** 38404

**Message Description:** LOGID\_EVENT\_NOTIF\_HOSTNAME\_ERROR

**Message Meaning:** FortiGuard hostname unresolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
hostname	Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38405 - LOGID\_NOTIF\_CODE\_SENDTO\_SMS\_PHONE

**Message ID:** 38405

**Message Description:** LOGID\_NOTIF\_CODE\_SENDTO\_SMS\_PHONE

**Message Meaning:** Guest user account login information sent to phone

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38406 - LOGID\_NOTIF\_CODE\_SENDTO\_SMS\_TO

**Message ID:** 38406

**Message Description:** LOGID\_NOTIF\_CODE\_SENDTO\_SMS\_TO

**Message Meaning:** Guest user account login information sent as SMS

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38407 - LOGID\_NOTIF\_CODE\_SENDTO\_EMAIL

**Message ID:** 38407

**Message Description:** LOGID\_NOTIF\_CODE\_SENDTO\_EMAIL



**Message Meaning:** Guest user account login information sent to email

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38408 - LOGID\_EVENT\_OFTP\_SSL\_CONNECTED

**Message ID:** 38408

**Message Description:** LOGID\_EVENT\_OFTP\_SSL\_CONNECTED

**Message Meaning:** SSL connection established

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38409 - LOGID\_EVENT\_OFTP\_SSL\_DISCONNECTED

**Message ID:** 38409

**Message Description:** LOGID\_EVENT\_OFTP\_SSL\_DISCONNECTED

**Message Meaning:** SSL connection closed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38410 - LOGID\_EVENT\_OFTP\_SSL\_FAILED

**Message ID:** 38410

**Message Description:** LOGID\_EVENT\_OFTP\_SSL\_FAILED

**Message Meaning:** SSL connection failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38411 - LOGID\_EVENT\_TWO\_F\_AUTH\_CODE\_SENDTO

**Message ID:** 38411

**Message Description:** LOGID\_EVENT\_TWO\_F\_AUTH\_CODE\_SENDTO

**Message Meaning:** Two-factor authentication code sent

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38412 - LOGID\_EVENT\_TOKEN\_CODE\_SENDTO

**Message ID:** 38412

**Message Description:** LOGID\_EVENT\_TOKEN\_CODE\_SENDTO

**Message Meaning:** Token activation code sent

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38656 - LOGID\_EVENT\_RAD\_RPT\_PROTO\_ERROR

**Message ID:** 38656

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_PROTO\_ERROR

**Message Meaning:** RADIUS protocol error summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38657 - LOGID\_EVENT\_RAD\_RPT\_PROF\_NOT\_FOUND

**Message ID:** 38657

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_PROF\_NOT\_FOUND

**Message Meaning:** RADIUS profile not found summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38658 - LOGID\_EVENT\_RAD\_RPT\_CTX\_NOT\_FOUND

**Message ID:** 38658

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_CTX\_NOT\_FOUND

**Message Meaning:** RADIUS profile CTX not found summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38659 - LOGID\_EVENT\_RAD\_RPT\_ACCT\_STOP\_MISSED

**Message ID:** 38659

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_ACCT\_STOP\_MISSED

**Message Meaning:** RADIUS accounting stop message missing summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38660 - LOGID\_EVENT\_RAD\_RPT\_ACCT\_EVENT

**Message ID:** 38660

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_ACCT\_EVENT

**Message Meaning:** RADIUS accounting event summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38661 - LOGID\_EVENT\_RAD\_RPT\_OTHER

**Message ID:** 38661

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_OTHER

**Message Meaning:** RADIUS endpoint block event or other event summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38662 - LOGID\_EVENT\_RAD\_STAT\_PROTO\_ERROR

**Message ID:** 38662

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_PROTO\_ERROR

**Message Meaning:** RADIUS accounting protocol error

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38663 - LOGID\_EVENT\_RAD\_STAT\_PROF\_NOT\_FOUND

**Message ID:** 38663

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_PROF\_NOT\_FOUND

**Message Meaning:** RADIUS accounting profile not found

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38665 - LOGID\_EVENT\_RAD\_STAT\_ACCT\_STOP\_MISSED

**Message ID:** 38665

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_ACCT\_STOP\_MISSED

**Message Meaning:** RADIUS accounting stop message missing

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

**38666 - LOGID\_EVENT\_RAD\_STAT\_ACCT\_EVENT****Message ID:** 38666**Message Description:** LOGID\_EVENT\_RAD\_STAT\_ACCT\_EVENT**Message Meaning:** RADIUS accounting event**Type:** Event**Category:** USER**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38667 - LOGID\_EVENT\_RAD\_STAT\_OTHER

**Message ID:** 38667

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_OTHER

**Message Meaning:** RADIUS other accounting event

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 38668 - LOGID\_EVENT\_RAD\_STAT\_EP\_BLK

**Message ID:** 38668

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_EP\_BLK

**Message Meaning:** RADIUS endpoint block event

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 39424 - LOG\_ID\_EVENT\_SSL\_VPN\_USER\_TUNNEL\_UP

**Message ID:** 39424

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_USER\_TUNNEL\_UP

**Message Meaning:** SSL VPN tunnel up

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10

Log Field Name	Description	Data Type	Length
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39425 - LOG\_ID\_EVENT\_SSL\_VPN\_USER\_TUNNEL\_DOWN

**Message ID:** 39425

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_USER\_TUNNEL\_DOWN

**Message Meaning:** SSL VPN tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
rcvdbyte	Received Bytes	uint64	20
reason	Reason	string	256
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39426 - LOG\_ID\_EVENT\_SSL\_VPN\_USER\_SSL\_LOGIN\_FAIL

**Message ID:** 39426

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_USER\_SSL\_LOGIN\_FAIL

**Message Meaning:** SSL VPN login fail

**Type:** Event

**Category:** VPN

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 39936 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEB\_TUNNEL\_STATS

**Message ID:** 39936

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEB\_TUNNEL\_STATS

**Message Meaning:** SSL VPN statistics

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
nextstat	Time interval in seconds for the next statistics	uint32	10
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 39937 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_DENY

**Message ID:** 39937

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_DENY

**Message Meaning:** SSL VPN deny

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 39938 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_PASS

**Message ID:** 39938

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_PASS

**Message Meaning:** SSL VPN pass

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 39939 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_TIMEOUT

**Message ID:** 39939

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_TIMEOUT

**Message Meaning:** SSL VPN timeout

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10

Log Field Name	Description	Data Type	Length
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39940 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_CLOSE

**Message ID:** 39940

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_CLOSE

**Message Meaning:** SSL VPN close

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39941 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_SYS\_BUSY

**Message ID:** 39941

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_SYS\_BUSY

**Message Meaning:** SSL VPN system busy

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39942 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_CERT\_OK

**Message ID:** 39942

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_CERT\_OK

**Message Meaning:** SSL VPN certificate OK

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5



Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39943 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_NEW\_CON

**Message ID:** 39943

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_NEW\_CON

**Message Meaning:** SSL VPN new connection

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39944 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_ALERT

**Message ID:** 39944

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_ALERT

**Message Meaning:** SSL VPN alert

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
desc		string	128
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39945 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_EXIT\_FAIL

**Message ID:** 39945

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_EXIT\_FAIL

**Message Meaning:** SSL VPN exit fail

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39946 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_EXIT\_ERR

**Message ID:** 39946

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_EXIT\_ERR

**Message Meaning:** SSL VPN exit error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

**39947 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_UP****Message ID:** 39947**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_UP**Message Meaning:** SSL VPN tunnel up**Type:** Event**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 39948 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_DOWN

**Message ID:** 39948

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_DOWN

**Message Meaning:** SSL VPN tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
rcvdbyte	Received Bytes	uint64	20
reason	Reason	string	256
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39949 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_STATS

**Message ID:** 39949

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_STATS

**Message Meaning:** SSL VPN statistics

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
nextstat	Time interval in seconds for the next statistics	uint32	10
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39950 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_UNKNOWNTAG

**Message ID:** 39950

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_UNKNOWNTAG

**Message Meaning:** SSL VPN unknown tag

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 39951 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_ERROR

**Message ID:** 39951

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_ERROR

**Message Meaning:** SSL VPN tunnel error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39952 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_ENTER\_CONSERVE\_MODE

**Message ID:** 39952

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_ENTER\_CONSERVE\_MODE

**Message Meaning:** SSL VPN enter conserve mode

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 39953 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_LEAVE\_CONSERVE\_MODE

**Message ID:** 39953

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_LEAVE\_CONSERVE\_MODE

**Message Meaning:** SSL VPN leave conserve mode

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40001 - LOG\_ID\_PPTP\_TUNNEL\_UP

**Message ID:** 40001

**Message Description:** LOG\_ID\_PPTP\_TUNNEL\_UP

**Message Meaning:** PPTP tunnel up

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40002 - LOG\_ID\_PPTP\_TUNNEL\_DOWN

**Message ID:** 40002

**Message Description:** LOG\_ID\_PPTP\_TUNNEL\_DOWN

**Message Meaning:** PPTP tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40003 - LOG\_ID\_PPTP\_TUNNEL\_STAT

**Message ID:** 40003

**Message Description:** LOG\_ID\_PPTP\_TUNNEL\_STAT

**Message Meaning:** PPTP tunnel status

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	4096
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40014 - LOG\_ID\_PPTP\_REACH\_MAX\_CON

**Message ID:** 40014

**Message Description:** LOG\_ID\_PPTP\_REACH\_MAX\_CON

**Message Meaning:** PPTP client connection limit reached

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40017 - LOG\_ID\_L2TPD\_CLIENT\_CON\_FAIL

**Message ID:** 40017

**Message Description:** LOG\_ID\_L2TPD\_CLIENT\_CON\_FAIL

**Message Meaning:** L2TP client connection failed

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40019 - LOG\_ID\_L2TPD\_CLIENT\_DISCON

**Message ID:** 40019

**Message Description:** LOG\_ID\_L2TPD\_CLIENT\_DISCON

**Message Meaning:** L2TP client disconnected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40021 - LOG\_ID\_PPTP\_NOT\_CONIG

**Message ID:** 40021

**Message Description:** LOG\_ID\_PPTP\_NOT\_CONIG

**Message Meaning:** PPTP not configured in VDOM

**Type:** Event

**Category:** VPN

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10



Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40022 - LOG\_ID\_PPTP\_NO\_IP\_AVAIL

**Message ID:** 40022

**Message Description:** LOG\_ID\_PPTP\_NO\_IP\_AVAIL

**Message Meaning:** PPTP IP addresses unavailable

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40024 - LOG\_ID\_PPTP\_OUT\_MEM

**Message ID:** 40024

**Message Description:** LOG\_ID\_PPTP\_OUT\_MEM

**Message Meaning:** PPTP config list insufficient memory

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40034 - LOG\_ID\_PPTP\_START

**Message ID:** 40034

**Message Description:** LOG\_ID\_PPTP\_START**Message Meaning:** PPTP daemon started**Type:** Event**Category:** VPN**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40035 - LOG\_ID\_PPTP\_START\_FAIL

**Message ID:** 40035**Message Description:** LOG\_ID\_PPTP\_START\_FAIL**Message Meaning:** PPTP daemon failed to start**Type:** Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40036 - LOG\_ID\_PPTP\_EXIT

**Message ID:** 40036

**Message Description:** LOG\_ID\_PPTP\_EXIT

**Message Meaning:** PPTP daemon exited

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40037 - LOG\_ID\_PPTPD\_SVR\_DISCON

**Message ID:** 40037

**Message Description:** LOG\_ID\_PPTPD\_SVR\_DISCON

**Message Meaning:** PPTP daemon disconnected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40038 - LOG\_ID\_PPTPD\_CLIENT\_CON

**Message ID:** 40038

**Message Description:** LOG\_ID\_PPTPD\_CLIENT\_CON

**Message Meaning:** PPTP client connected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40039 - LOG\_ID\_PPTPD\_CLIENT\_DISCON

**Message ID:** 40039

**Message Description:** LOG\_ID\_PPTPD\_CLIENT\_DISCON

**Message Meaning:** PPTP client disconnected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40101 - LOG\_ID\_L2TP\_TUNNEL\_UP

**Message ID:** 40101

**Message Description:** LOG\_ID\_L2TP\_TUNNEL\_UP

**Message Meaning:** L2TP tunnel up

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	4096
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40102 - LOG\_ID\_L2TP\_TUNNEL\_DOWN

**Message ID:** 40102

**Message Description:** LOG\_ID\_L2TP\_TUNNEL\_DOWN

**Message Meaning:** L2TP tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096



Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40103 - LOG\_ID\_L2TP\_TUNNEL\_STAT

**Message ID:** 40103

**Message Description:** LOG\_ID\_L2TP\_TUNNEL\_STAT

**Message Meaning:** L2TP tunnel status

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
remip	Remote IP	ip	39
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40114 - LOG\_ID\_L2TPD\_START

**Message ID:** 40114

**Message Description:** LOG\_ID\_L2TPD\_START

**Message Meaning:** L2TP daemon started

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40115 - LOG\_ID\_L2TPD\_EXIT

**Message ID:** 40115

**Message Description:** LOG\_ID\_L2TPD\_EXIT

**Message Meaning:** L2TP daemon exited

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40118 - LOG\_ID\_L2TPD\_CLIENT\_CON

**Message ID:** 40118

**Message Description:** LOG\_ID\_L2TPD\_CLIENT\_CON

**Message Meaning:** L2TP client connected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40704 - LOG\_ID\_EVENT\_SYS\_PERF

**Message ID:** 40704

**Message Description:** LOG\_ID\_EVENT\_SYS\_PERF

**Message Meaning:** System performance statistics

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
bandwidth	Bandwidth	string	42
cpu	CPU Usage	uint8	3
date	Date	string	10
devid	Device ID	string	16
disk	Disk Usage	uint8	3
disklograte	Disk Log Rate	uint64	20

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
fazlograte	FortiAnalyzer Logging Rate	uint64	20
freediskstorage		uint32	10
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mem	Memory Usage	uint8	3
msg	Message Text	string	4096
setuprate	Session Setup Rate	uint64	20
subtype	Log Subtype	string	20
sysuptime		uint32	10
time	Time	string	8
totalsession	Total Number of Sessions	uint32	10
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40705 - LOG\_ID\_EVENT\_SYS\_CPU\_USAGE

**Message ID:** 40705

**Message Description:** LOG\_ID\_EVENT\_SYS\_CPU\_USAGE

**Message Meaning:** CPU usage statistics

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
cpu	CPU Usage	uint8	3
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 40960 - LOGID\_EVENT\_WAD\_WEBPROXY\_FWD\_SRV\_ERROR

**Message ID:** 40960

**Message Description:** LOGID\_EVENT\_WAD\_WEBPROXY\_FWD\_SRV\_ERROR

**Message Meaning:** Web proxy forward server error

**Type:** Event

**Category:** WAD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
addr_type	Address Type	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fqdn	Fully Qualified Domain Name	string	256
fwserver_name		string	32
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
port	Port Number	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 41000 - LOG\_ID\_UPD\_FGT\_SUCC

**Message ID:** 41000

**Message Description:** LOG\_ID\_UPD\_FGT\_SUCC

**Message Meaning:** FortiGate update succeeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 41001 - LOG\_ID\_UPD\_FGT\_FAIL

**Message ID:** 41001

**Message Description:** LOG\_ID\_UPD\_FGT\_FAIL

**Message Meaning:** FortiGate update failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 41002 - LOG\_ID\_UPD\_SRC\_VIS

**Message ID:** 41002

**Message Description:** LOG\_ID\_UPD\_SRC\_VIS

**Message Meaning:** Source visibility signature package updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20



Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 41006 - LOG\_ID\_UPD\_FSA\_VIRDB

**Message ID:** 41006

**Message Description:** LOG\_ID\_UPD\_FSA\_VIRDB

**Message Meaning:** FortiSandbox AV database updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
version	Version	string	64

## 41984 - LOG\_ID\_EVENT\_VPN\_CERT\_LOAD

**Message ID:** 41984

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_LOAD

**Message Meaning:** Certificate loaded

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 41985 - LOG\_ID\_EVENT\_VPN\_CERT\_REMOVAL

**Message ID:** 41985

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_REMOVAL

**Message Meaning:** Certificate removed

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 41986 - LOG\_ID\_EVENT\_VPN\_CERT\_REGEN

**Message ID:** 41986

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_REGEN

**Message Meaning:** Certificate regenerated

**Type:** Event

**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 41987 - LOG\_ID\_EVENT\_VPN\_CERT\_UPDATE

**Message ID:** 41987**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_UPDATE**Message Meaning:** Certificate updated**Type:** Event**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert-type	Certification type	string	6

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	4096
name	Name	string	128
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 41988 - LOG\_ID\_EVENT\_SSL\_VPN\_SETTING\_UPDATE

**Message ID:** 41988

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SETTING\_UPDATE

**Message Meaning:** SSL setting changed

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 41989 - LOG\_ID\_EVENT\_VPN\_CERT\_ERR

**Message ID:** 41989

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_ERR

**Message Meaning:** Certificate error

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	4096
name	Name	string	128

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 41990 - LOG\_ID\_EVENT\_VPN\_CERT\_UPDATE\_FAILED

**Message ID:** 41990

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_UPDATE\_FAILED

**Message Meaning:** Certificate update failed

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	4096
name	Name	string	128
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 41991 - LOG\_ID\_EVENT\_VPN\_CERT\_EXPORT

**Message ID:** 41991

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_EXPORT

**Message Meaning:** Certificate exported

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32



## 42201 - LOG\_ID\_NETX\_VMX\_ATTACH

**Message ID:** 42201

**Message Description:** LOG\_ID\_NETX\_VMX\_ATTACH

**Message Meaning:** VMX instance successfully attached

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 42202 - LOG\_ID\_NETX\_VMX\_DETACH

**Message ID:** 42202

**Message Description:** LOG\_ID\_NETX\_VMX\_DETACH

**Message Meaning:** VMX instance successfully detached

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 42203 - LOG\_ID\_NETX\_VMX\_DENIED

**Message ID:** 42203

**Message Description:** LOG\_ID\_NETX\_VMX\_DENIED

**Message Meaning:** VMX instance successfully denied

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43008 - LOG\_ID\_EVENT\_AUTH\_SUCCESS

**Message ID:** 43008

**Message Description:** LOG\_ID\_EVENT\_AUTH\_SUCCESS

**Message Meaning:** Authentication success

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43009 - LOG\_ID\_EVENT\_AUTH\_FAILED

**Message ID:** 43009

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FAILED

**Message Meaning:** Authentication failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43010 - LOG\_ID\_EVENT\_AUTH\_LOCKOUT

**Message ID:** 43010

**Message Description:** LOG\_ID\_EVENT\_AUTH\_LOCKOUT

**Message Meaning:** Authentication lockout

**Type:** Event

**Category:** USER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43011 - LOG\_ID\_EVENT\_AUTH\_TIME\_OUT

**Message ID:** 43011

**Message Description:** LOG\_ID\_EVENT\_AUTH\_TIME\_OUT

**Message Meaning:** Authentication timed out

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
authserver		string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43014 - LOG\_ID\_EVENT\_AUTH\_FSAE\_LOGON

**Message ID:** 43014

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FSAE\_LOGON

**Message Meaning:** FSSO logon authentication status

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43015 - LOG\_ID\_EVENT\_AUTH\_FSAE\_LOGOFF

**Message ID:** 43015

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FSAE\_LOGOFF

**Message Meaning:** FSSO log off authentication status

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43016 - LOG\_ID\_EVENT\_AUTH\_NTLM\_AUTH\_SUCCESS

**Message ID:** 43016

**Message Description:** LOG\_ID\_EVENT\_AUTH\_NTLM\_AUTH\_SUCCESS

**Message Meaning:** NTLM authentication successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43017 - LOG\_ID\_EVENT\_AUTH\_NTLM\_AUTH\_FAIL

**Message ID:** 43017

**Message Description:** LOG\_ID\_EVENT\_AUTH\_NTLM\_AUTH\_FAIL

**Message Meaning:** NTLM authentication failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43018 - LOG\_ID\_EVENT\_AUTH\_FGOVRD\_FAIL

**Message ID:** 43018

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FGOVRD\_FAIL

**Message Meaning:** FortiGuard override failed

**Type:** Event

**Category:** USER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43020 - LOG\_ID\_EVENT\_AUTH\_FGOVRD\_SUCCESS

**Message ID:** 43020

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FGOVRD\_SUCCESS

**Message Meaning:** FortiGuard override successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
expiry	FortiGuard override expiry timestamp	string	64
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
oldwprof	Old Web Filter Profile	string	64
reason	Reason	string	256
scope	FortiGuard Override Scope	string	16
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43025 - LOG\_ID\_EVENT\_AUTH\_PROXY\_SUCCESS

**Message ID:** 43025

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_SUCCESS

**Message Meaning:** Explicit proxy authentication successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authid		string	36
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43026 - LOG\_ID\_EVENT\_AUTH\_PROXY\_FAILED

**Message ID:** 43026

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_FAILED

**Message Meaning:** Explicit proxy authentication failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authid		string	36
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43027 - LOG\_ID\_EVENT\_AUTH\_PROXY\_TIME\_OUT

**Message ID:** 43027

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_TIME\_OUT

**Message Meaning:** Explicit proxy authentication timed out

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43028 - LOG\_ID\_EVENT\_AUTH\_PROXY\_GROUP\_INFO\_FAILED

**Message ID:** 43028

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_GROUP\_INFO\_FAILED

**Message Meaning:** Explicit proxy user group query failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authid		string	36
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43029 - LOG\_ID\_EVENT\_AUTH\_WARNING\_SUCCESS

**Message ID:** 43029

**Message Description:** LOG\_ID\_EVENT\_AUTH\_WARNING\_SUCCESS

**Message Meaning:** FortiGuard authentication override successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
category		uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
expiry	FortiGuard override expiry timestamp	string	64
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	4096
oldwprof	Old Web Filter Profile	string	64
reason	Reason	string	256
scope	FortiGuard Override Scope	string	16
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43030 - LOG\_ID\_EVENT\_AUTH\_WARNING\_TBL\_FULL

**Message ID:** 43030

**Message Description:** LOG\_ID\_EVENT\_AUTH\_WARNING\_TBL\_FULL

**Message Meaning:** FortiGuard authentication override failed

**Type:** Event

**Category:** USER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43032 - LOG\_ID\_EVENT\_AUTH\_PROXY\_USER\_LIMIT\_REACHED

**Message ID:** 43032

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_USER\_LIMIT\_REACHED

**Message Meaning:** Explicit proxy authentication user limit reached

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authid		string	36
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43033 - LOG\_ID\_EVENT\_AUTH\_PROXY\_MULTIPLE\_LOGIN

**Message ID:** 43033

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_MULTIPLE\_LOGIN

**Message Meaning:** Explicit proxy authentication user concurrent check failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authid		string	36
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43034 - LOG\_ID\_EVENT\_AUTH\_PROXY\_NO\_RESP

**Message ID:** 43034

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_NO\_RESP

**Message Meaning:** Explicit proxy authentication no response

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
agent		string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
url		string	512
vd	Virtual Domain Name	string	32

## 43037 - LOG\_ID\_EVENT\_AUTH\_IPV4\_FLUSH

**Message ID:** 43037

**Message Description:** LOG\_ID\_EVENT\_AUTH\_IPV4\_FLUSH

**Message Meaning:** Authentication IPv4 logon flush

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43038 - LOG\_ID\_EVENT\_AUTH\_IPV6\_FLUSH

**Message ID:** 43038

**Message Description:** LOG\_ID\_EVENT\_AUTH\_IPV6\_FLUSH

**Message Meaning:** Authentication IPv6 logon flush

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43039 - LOG\_ID\_EVENT\_AUTH\_LOGON

**Message ID:** 43039

**Message Description:** LOG\_ID\_EVENT\_AUTH\_LOGON

**Message Meaning:** Authentication logon

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authserver		string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43040 - LOG\_ID\_EVENT\_AUTH\_LOGOUT

**Message ID:** 43040

**Message Description:** LOG\_ID\_EVENT\_AUTH\_LOGOUT

**Message Meaning:** Authentication logout

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authserver		string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43041 - LOG\_ID\_EVENT\_AUTH\_DISCLAIMER\_ACCEPT

**Message ID:** 43041

**Message Description:** LOG\_ID\_EVENT\_AUTH\_DISCLAIMER\_ACCEPT

**Message Meaning:** Disclaimer accepted

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32



Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43042 - LOG\_ID\_EVENT\_AUTH\_DISCLAIMER\_DECLINE

**Message ID:** 43042

**Message Description:** LOG\_ID\_EVENT\_AUTH\_DISCLAIMER\_DECLINE

**Message Meaning:** Disclaimer declined

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43043 - LOG\_ID\_EVENT\_AUTH\_EMAIL\_COLLECTING\_SUCCESS

**Message ID:** 43043

**Message Description:** LOG\_ID\_EVENT\_AUTH\_EMAIL\_COLLECTING\_SUCCESS

**Message Meaning:** Email collecting succeeded

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43044 - LOG\_ID\_EVENT\_AUTH\_EMAIL\_COLLECTING\_FAIL

**Message ID:** 43044

**Message Description:** LOG\_ID\_EVENT\_AUTH\_EMAIL\_COLLECTING\_FAIL

**Message Meaning:** Email collecting failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43045 - LOG\_ID\_EVENT\_AUTH\_8021X\_SUCCESS

**Message ID:** 43045

**Message Description:** LOG\_ID\_EVENT\_AUTH\_8021X\_SUCCESS

**Message Meaning:** 802.1x authentication succeeded

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
stamac		string	17
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43046 - LOG\_ID\_EVENT\_AUTH\_8021X\_FAIL

**Message ID:** 43046

**Message Description:** LOG\_ID\_EVENT\_AUTH\_8021X\_FAIL

**Message Meaning:** 802.1x authentication failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	4096
reason	Reason	string	256
stamac		string	17
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43050 - LOG\_ID\_EVENT\_AUTH\_FSAE\_CONNECT

**Message ID:** 43050

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FSAE\_CONNECT

**Message Meaning:** FSSO server connected

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43051 - LOG\_ID\_EVENT\_AUTH\_FSAE\_DISCONNECT

**Message ID:** 43051

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FSAE\_DISCONNECT

**Message Meaning:** FSSO server disconnected

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43264 - LOGID\_MMS\_STATS

**Message ID:** 43264

**Message Description:** LOGID\_MMS\_STATS

**Message Meaning:** MMS statistics

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
checksum	for MMS Statistics	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
infected	Infected MMS	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msgproto	Message Protocol Number	string	16
scanned	Number of Scanned MMSs	uint32	10
subtype	Log Subtype	string	20
suspicious	Number of Suspicious MMSs	uint32	10
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43520 - LOG\_ID\_EVENT\_WIRELESS\_SYS

**Message ID:** 43520

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS

**Message Meaning:** Wireless system activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice



Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43521 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE

**Message ID:** 43521

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE

**Message Meaning:** Rogue AP activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10

Log Field Name	Description	Data Type	Length
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43522 - LOG\_ID\_EVENT\_WIRELESS\_WTP

**Message ID:** 43522

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP

**Message Meaning:** Physical AP activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43524 - LOG\_ID\_EVENT\_WIRELESS\_STA

**Message ID:** 43524

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA

**Message Meaning:** Wireless client activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43525 - LOG\_ID\_EVENT\_WIRELESS\_ONWIRE****Message ID:** 43525**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ONWIRE**Message Meaning:** Rogue AP on wire**Type:** Event**Category:** WIRELESS**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3

Log Field Name	Description	Data Type	Length
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43526 - LOG\_ID\_EVENT\_WIRELESS\_WTPR

**Message ID:** 43526

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR

**Message Meaning:** Physical AP radio activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43527 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG

**Message ID:** 43527

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG

**Message Meaning:** Rogue AP status configured

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43528 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_ERROR

**Message ID:** 43528

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_ERROR

**Message Meaning:** Physical AP radio error activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43529 - LOG\_ID\_EVENT\_WIRELESS\_CLB

**Message ID:** 43529

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_CLB

**Message Meaning:** Wireless client load balancing

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43530 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_WL\_BRIDGE

**Message ID:** 43530

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_WL\_BRIDGE

**Message Meaning:** Wireless bridge intrusion detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threatype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43531 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_BR\_DEAUTH

**Message ID:** 43531

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_BR\_DEAUTH

**Message Meaning:** Wireless broadcasting deauthentication detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17

Log Field Name	Description	Data Type	Length
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43532 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_NL\_PBRESP

**Message ID:** 43532

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_NL\_PBRESP

**Message Meaning:** Wireless null SSID probe response detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43533 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_MAC\_OUI

**Message ID:** 43533

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_MAC\_OUI

**Message Meaning:** Wireless invalid MAC OUI detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
invalidmac	the MAC address with invalid OUI	string	17
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

**43534 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_LONG\_DUR****Message ID:** 43534**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_LONG\_DUR**Message Meaning:** Wireless long duration attack detected**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
duration	Duration of the last threatening packet captured from TA	uint32	10
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17

Log Field Name	Description	Data Type	Length
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43535 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_WEP\_IV

**Message ID:** 43535

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_WEP\_IV

**Message Meaning:** Wireless Weak WEP IV detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096



Log Field Name	Description	Data Type	Length
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
weakwepiv	Weak Wep Initiation Vector	string	8

## 43542 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_EAPOL\_FLOOD

**Message ID:** 43542

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_EAPOL\_FLOOD

**Message Meaning:** Wireless EAPOL packet flooding detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eapolcnt	EAPOL packet count	uint32	10
eapoltype	EAPOL packet type	string	16
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43544 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_MGMT\_FLOOD

**Message ID:** 43544

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_MGMT\_FLOOD

**Message Meaning:** Wireless management flooding detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
eventtime		uint64	20
frametype	Frame Type	string	32

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
mgmtcnt	The number of unauthorized client flooding management frames	uint32	10
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43546 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_SPOOF\_DEAUTH

**Message ID:** 43546

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_SPOOF\_DEAUTH

**Message Meaning:** Wireless spoofed deauthentication detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43548 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_ASLEAP

**Message ID:** 43548

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_ASLEAP

**Message Meaning:** Wireless Asleep attack detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43550 - LOG\_ID\_EVENT\_WIRELESS\_STA\_LOCATE

**Message ID:** 43550

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_LOCATE

**Message Meaning:** Wireless station presence detection

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
noise		int8	4
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
signal	Signal	int8	4
sn	Serial Number	string	64
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43551 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_JOIN

**Message ID:** 43551

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_JOIN

**Message Meaning:** Physical AP join

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43552 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_LEAVE

**Message ID:** 43552

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_LEAVE

**Message Meaning:** Physical AP leave

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43553 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_FAIL

**Message ID:** 43553

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_FAIL

**Message Meaning:** Physical AP fail

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43554 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_UPDATE

**Message ID:** 43554

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_UPDATE

**Message Meaning:** Physical AP update

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43555 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_RESET

**Message ID:** 43555

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_RESET

**Message Meaning:** Physical AP reset

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43556 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_KICK

**Message ID:** 43556

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_KICK

**Message Meaning:** Physical AP kick

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43557 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD\_FAILURE

**Message ID:** 43557

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD\_FAILURE

**Message Meaning:** Physical AP add failure

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43558 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_CFG\_ERR

**Message ID:** 43558

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_CFG\_ERR

**Message Meaning:** Physical AP config error

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43559 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_SN\_MISMATCH

**Message ID:** 43559

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_SN\_MISMATCH

**Message Meaning:** Physical AP SN mismatch

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43560 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_RESTARTED

**Message ID:** 43560

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_RESTARTED

**Message Meaning:** Wireless system restarted

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43561 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_HOSTAPD\_UP

**Message ID:** 43561

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_HOSTAPD\_UP

**Message Meaning:** Wireless system hostapd up

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43562 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_HOSTAPD\_DOWN

**Message ID:** 43562

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_HOSTAPD\_DOWN

**Message Meaning:** Wireless system hostapd down



**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43563 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_DETECT

**Message ID:** 43563**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_DETECT**Message Meaning:** Rogue AP detected**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3

Log Field Name	Description	Data Type	Length
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

**43564 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_OFFAIR****Message ID:** 43564**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_OFFAIR**Message Meaning:** Rogue AP off air**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3

Log Field Name	Description	Data Type	Length
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43565 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_ONAIR

**Message ID:** 43565

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_ONAIR

**Message Meaning:** Rogue AP on air

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10

Log Field Name	Description	Data Type	Length
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43566 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_OFFWIRE

**Message ID:** 43566

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_OFFWIRE

**Message Meaning:** Rogue AP off wire

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4

Log Field Name	Description	Data Type	Length
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43567 - LOG\_ID\_EVENT\_WIRELESS\_FAKEAP\_DETECT

**Message ID:** 43567

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_FAKEAP\_DETECT

**Message Meaning:** Fake AP detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43568 - LOG\_ID\_EVENT\_WIRELESS\_FAKEAP\_ONAIR

**Message ID:** 43568

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_FAKEAP\_ONAIR

**Message Meaning:** Fake AP on air

**Type:** Event

**Category:** WIRELESS



**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10

Log Field Name	Description	Data Type	Length
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43569 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_SUPPRESSED

**Message ID:** 43569

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_SUPPRESSED

**Message Meaning:** Rogue AP suppressed

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43570 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_UNSUPPRESSED

**Message ID:** 43570

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_UNSUPPRESSED

**Message Meaning:** Rogue AP unsuppressed

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10

Log Field Name	Description	Data Type	Length
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43571 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_DETECT\_CHG

**Message ID:** 43571

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_DETECT\_CHG

**Message Meaning:** Rogue AP change detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43572 - LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSO

**Message ID:** 43572

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSO

**Message Meaning:** Wireless client associated

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43573 - LOG\_ID\_EVENT\_WIRELESS\_STA\_AUTH

**Message ID:** 43573

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_AUTH

**Message Meaning:** Wireless client authenticated

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256



Log Field Name	Description	Data Type	Length
vap		string	36
vd	Virtual Domain Name	string	32

## 43574 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DASS

**Message ID:** 43574

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DASS

**Message Meaning:** Wireless client disassociated

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43575 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DAUT

**Message ID:** 43575

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DAUT

**Message Meaning:** Wireless client deauthenticated

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33

Log Field Name	Description	Data Type	Length
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43576 - LOG\_ID\_EVENT\_WIRELESS\_STA\_IDLE

**Message ID:** 43576

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_IDLE

**Message Meaning:** Wireless client idle

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43577 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DENY

**Message ID:** 43577

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DENY

**Message Meaning:** Wireless client denied

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43578 - LOG\_ID\_EVENT\_WIRELESS\_STA\_KICK

**Message ID:** 43578

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_KICK

**Message Meaning:** Wireless client kicked

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43579 - LOG\_ID\_EVENT\_WIRELESS\_STA\_IP

**Message ID:** 43579

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_IP

**Message Meaning:** Wireless client IP assigned

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43580 - LOG\_ID\_EVENT\_WIRELESS\_STA\_LEAVE\_WTP

**Message ID:** 43580

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_LEAVE\_WTP

**Message Meaning:** Wireless client left WTP

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11



Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43581 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WTP\_DISCONN

**Message ID:** 43581

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WTP\_DISCONN

**Message Meaning:** Wireless client WTP disconnected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43582 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_UNCLASSIFIED

**Message ID:** 43582

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_UNCLASSIFIED

**Message Meaning:** Rogue AP status configured as unclassified

**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43583 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_ACCEPTED

**Message ID:** 43583**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_ACCEPTED**Message Meaning:** Rogue AP status configured as accepted**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
apstatus	Access Point Status	uint8	3

Log Field Name	Description	Data Type	Length
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43584 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_ROGUE

**Message ID:** 43584

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_ROGUE

**Message Meaning:** Rogue AP status configured as rogue

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43585 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_SUPPRESSED

**Message ID:** 43585

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_SUPPRESSED

**Message Meaning:** Rogue AP status configured as suppressed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43586 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_CHAN

**Message ID:** 43586

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_CHAN

**Message Meaning:** Physical AP radio DARRP channel change

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43587 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_START

**Message ID:** 43587

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_START

**Message Meaning:** Physical AP radio DARRP start

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10

Log Field Name	Description	Data Type	Length
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43588 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_CHAN

**Message ID:** 43588

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_CHAN

**Message Meaning:** Physical AP radio operation channel change

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096



Log Field Name	Description	Data Type	Length
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43589 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_RADAR

**Message ID:** 43589

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_RADAR

**Message Meaning:** Physical AP radio radar detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43590 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_NOL

**Message ID:** 43590

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_NOL

**Message Meaning:** Physical AP radio channel removed from NOL

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43591 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_COUNTRY\_CFG\_SUCCESS

**Message ID:** 43591

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_COUNTRY\_CFG\_SUCCESS

**Message Meaning:** Physical AP radio country config success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43592 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_COUNTRY

**Message ID:** 43592

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_COUNTRY

**Message Meaning:** Physical AP radio operation country

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43593 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_CFG\_TXPOWER

**Message ID:** 43593

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_CFG\_TXPOWER

**Message Meaning:** Physical AP radio config TX power

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42

Log Field Name	Description	Data Type	Length
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43594 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_TXPOWER

**Message ID:** 43594

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_TXPOWER

**Message Meaning:** Physical AP radio operation TX power

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43595 - LOG\_ID\_EVENT\_WIRELESS\_CLB\_DENY

**Message ID:** 43595

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_CLB\_DENY

**Message Meaning:** Wireless client load balancing denied

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43596 - LOG\_ID\_EVENT\_WIRELESS\_CLB\_RETRY

**Message ID:** 43596

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_CLB\_RETRY

**Message Meaning:** Wireless client load balancing retry

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice



Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43597 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD

**Message ID:** 43597

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD

**Message Meaning:** Physical AP add

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43598 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD\_XSS

**Message ID:** 43598

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD\_XSS

**Message Meaning:** Physical AP add XSS

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43599 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_DEL

**Message ID:** 43599

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_DEL

**Message Meaning:** Physical AP delete

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43600 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_STOP

**Message ID:** 43600

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_STOP

**Message Meaning:** Physical AP radio DARRP stop

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42

Log Field Name	Description	Data Type	Length
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43601 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON

**Message ID:** 43601

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON

**Message Meaning:** Wireless station sign on

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43602 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON\_SUCCESS

**Message ID:** 43602

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON\_SUCCESS

**Message Meaning:** Wireless station sign on success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43603 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON\_FAILURE****Message ID:** 43603**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON\_FAILURE**Message Meaning:** Wireless station sign on failed**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43604 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_REQUEST

**Message ID:** 43604

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_REQUEST

**Message Meaning:** Captive-portal VAP e-mail collect request sent

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43605 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_SUCCESS

**Message ID:** 43605

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_SUCCESS

**Message Meaning:** Captive-portal VAP e-mail collect success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43606 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_FAILURE

**Message ID:** 43606

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_FAILURE

**Message Meaning:** Captive-portal VAP e-mail collect failed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43607 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_DISCLAIMER\_CHECK

**Message ID:** 43607

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_DISCLAIMER\_CHECK

**Message Meaning:** Captive-portal VAP disclaimer agreed

**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43608 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_DISCLAIMER\_DECLINE****Message ID:** 43608**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_DISCLAIMER\_DECLINE**Message Meaning:** Captive-portal VAP disclaimer declined**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43609 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_OPTIMIZATION\_START

**Message ID:** 43609

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_OPTIMIZATION\_START

**Message Meaning:** DARRP optimization start

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43610 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_OPTIMIZATION\_STOP

**Message ID:** 43610

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_OPTIMIZATION\_STOP

**Message Meaning:** DARRP optimization stop

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4



Log Field Name	Description	Data Type	Length
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43611 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_UP

**Message ID:** 43611

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_UP

**Message Meaning:** Wireless controller start

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

**43612 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_CFG\_LOADED****Message ID:** 43612**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_CFG\_LOADED**Message Meaning:** Wireless controller configuration loaded**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

**43613 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_ERR****Message ID:** 43613**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_ERR**Message Meaning:** Physical AP error**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43614 - LOG\_ID\_EVENT\_WIRELESS\_DHCP\_STAVATION

**Message ID:** 43614

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_DHCP\_STAVATION

**Message Meaning:** DHCP Starvation detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
client_addr		string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
sn	Serial Number	string	64
source_mac		string	17
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vapmode		string	17
vd	Virtual Domain Name	string	32
xid		uint32	10

## 43615 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_IPSEC\_FAIL

**Message ID:** 43615

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_IPSEC\_FAIL

**Message Meaning:** Wireless controller IPsec setup failed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43616 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_NOL\_ADD

**Message ID:** 43616

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_NOL\_ADD

**Message Meaning:** Physical AP radio NOL added

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43618 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_IMAGE\_RC\_SUCCESS

**Message ID:** 43618

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_IMAGE\_RC\_SUCCESS

**Message Meaning:** Physical AP image receive success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43619 - LOG\_ID\_EVENT\_WIRELESS\_OFFENDINGAP\_DETECT

**Message ID:** 43619

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_OFFENDINGAP\_DETECT

**Message Meaning:** Offending AP detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43620 - LOG\_ID\_EVENT\_WIRELESS\_OFFENDINGAP\_ONAIR

**Message ID:** 43620

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_OFFENDINGAP\_ONAIR



**Message Meaning:** Offending AP on air

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	4096
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	4096
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36

Log Field Name	Description	Data Type	Length
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43621 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_DATA\_CHAN\_CHG

**Message ID:** 43621

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_DATA\_CHAN\_CHG

**Message Meaning:** Wireless wtp data channel changed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43622 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_VLAN\_PROBE

**Message ID:** 43622

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_VLAN\_PROBE

**Message Meaning:** WTP is probing vlan

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43623 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_VLAN\_MISSING

**Message ID:** 43623

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_VLAN\_MISSING

**Message Meaning:** VLAN not detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43624 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_VLAN\_DETECTED

**Message ID:** 43624

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_VLAN\_DETECTED

**Message Meaning:** VLAN detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	4096
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43625 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_CMCC\_SUCCESS

**Message ID:** 43625

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_CMCC\_SUCCESS

**Message Meaning:** Wireless station CMCC sign on success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43626 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_CMCC\_FAILURE

**Message ID:** 43626

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_CMCC\_FAILURE

**Message Meaning:** Wireless station CMCC sign on failed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43627 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_CMCC\_TIMEOUT

**Message ID:** 43627

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_CMCC\_TIMEOUT

**Message Meaning:** Wireless station CMCC sign on timeout

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36



Log Field Name	Description	Data Type	Length
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43628 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_CMCC\_MAC\_AUTH\_SUCCESS

**Message ID:** 43628

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_CMCC\_MAC\_AUTH\_SUCCESS

**Message Meaning:** Wireless station CMCC MAC auth success

**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	4096
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43629 - LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_AUTH\_FAILURE****Message ID:** 43629**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_AUTH\_FAILURE**Message Meaning:** Wireless client RADIUS authentication failure**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vap		string	36
vd	Virtual Domain Name	string	32

## 43630 - LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_AUTH\_SUCCESS

**Message ID:** 43630

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_AUTH\_SUCCESS

**Message Meaning:** Wireless client RADIUS authentication success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43631 - LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_AUTH\_NO\_RESP

**Message ID:** 43631

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_AUTH\_NO\_RESP

**Message Meaning:** Wireless client RADIUS authentication server not responding

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43632 - LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_MAC\_AUTH\_FAILURE

**Message ID:** 43632

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_MAC\_AUTH\_FAILURE

**Message Meaning:** Wireless client RADIUS MAC authentication failure

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43633 - LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_MAC\_AUTH\_SUCCESS

**Message ID:** 43633

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_MAC\_AUTH\_SUCCESS

**Message Meaning:** Wireless client RADIUS MAC authentication success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43634 - LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_MAC\_AUTH\_NO\_RESP

**Message ID:** 43634

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_RADIUS\_MAC\_AUTH\_NO\_RESP

**Message Meaning:** Wireless client RADIUS MAC authentication server not responding

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43635 - LOG\_ID\_EVENT\_WIRELESS\_STA\_OKC\_NO\_MATCH

**Message ID:** 43635

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_OKC\_NO\_MATCH

**Message Meaning:** Wireless client authenticates through OKC failed with no match

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43636 - LOG\_ID\_EVENT\_WIRELESS\_STA\_OKC\_LOCAL\_MATCH

**Message ID:** 43636

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_OKC\_LOCAL\_MATCH

**Message Meaning:** Wireless client authenticates through local OKC success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43637 - LOG\_ID\_EVENT\_WIRELESS\_STA\_OKC\_INTER\_AC\_MATCH****Message ID:** 43637**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_OKC\_INTER\_AC\_MATCH**Message Meaning:** Wireless client authenticates through inter AC OKC success

**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43638 - LOG\_ID\_EVENT\_WIRELESS\_STA\_OKC\_INTER\_AP\_MATCH****Message ID:** 43638

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_OKC\_INTER\_AP\_MATCH

**Message Meaning:** Wireless client authenticates through inter AP OKC success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43639 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_INVALID\_ACTION\_REQ****Message ID:** 43639**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_INVALID\_ACTION\_REQ**Message Meaning:** Wireless client sent invalid FT action request**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vap		string	36
vd	Virtual Domain Name	string	32

## 43640 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_INVALID\_AUTH\_REQ

**Message ID:** 43640

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_INVALID\_AUTH\_REQ

**Message Meaning:** Wireless client sent invalid FT auth request

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43641 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_INVALID\_REASSOC\_REQ

**Message ID:** 43641

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_INVALID\_REASSOC\_REQ

**Message Meaning:** Wireless client sent invalid FT reassociation request

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40



Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43642 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_ACTION\_REQ

**Message ID:** 43642

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_ACTION\_REQ

**Message Meaning:** Wireless client sent FT action request

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43643 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_ACTION\_RESP

**Message ID:** 43643

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_ACTION\_RESP

**Message Meaning:** FT action response was sent to wireless client

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43644 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_AUTH\_REQ

**Message ID:** 43644

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_AUTH\_REQ

**Message Meaning:** Wireless client sent FT auth request

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43645 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_AUTH\_RESP

**Message ID:** 43645

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_AUTH\_RESP

**Message Meaning:** FT auth response was sent to wireless client

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43646 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_REASSOC\_REQ

**Message ID:** 43646

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_REASSOC\_REQ

**Message Meaning:** Wireless client sent FT reassociation request

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43647 - LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_REASSOC\_RESP****Message ID:** 43647**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_FT\_REASSOC\_RESP**Message Meaning:** FT reassociation response was sent to wireless client

**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43648 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_INVALID\_SECOND\_MSG****Message ID:** 43648

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_INVALID\_SECOND\_MSG

**Message Meaning:** Wireless client 4 way handshake failed with invalid 2/4 message

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32



**43649 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_INVALID\_FOURTH\_MSG****Message ID:** 43649**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_INVALID\_FOURTH\_MSG**Message Meaning:** Wireless client 4 way handshake failed with invalid 4/4 message**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vap		string	36
vd	Virtual Domain Name	string	32

## 43650 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_FIRST\_MSG

**Message ID:** 43650

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_FIRST\_MSG

**Message Meaning:** AP sent 1/4 message of 4 way handshake to wireless client

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43651 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_SECOND\_MSG

**Message ID:** 43651

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_SECOND\_MSG

**Message Meaning:** Wireless client sent 2/4 message of 4 way handshake

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43652 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_THIRD\_MSG

**Message ID:** 43652

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_THIRD\_MSG

**Message Meaning:** AP sent 3/4 message of 4 way handshake to wireless client

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43653 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_FOURTH\_MSG

**Message ID:** 43653

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_FOURTH\_MSG

**Message Meaning:** Wireless client sent 4/4 message of 4 way handshake

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43654 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_FIRST\_GROUP\_MSG

**Message ID:** 43654

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_FIRST\_GROUP\_MSG

**Message Meaning:** AP sent 1/2 message of group key handshake to wireless client

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43655 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_SECOND\_GROUP\_MSG

**Message ID:** 43655

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_SECOND\_GROUP\_MSG

**Message Meaning:** Wireless client sent 2/2 message of group key handshake

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43656 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_MAX\_STA\_CNT

**Message ID:** 43656

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_MAX\_STA\_CNT

**Message Meaning:** Max sta count limit for the PSK was reached

**Type:** Event

**Category:** WIRELESS



**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43657 - LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSOC\_FAIL****Message ID:** 43657**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSOC\_FAIL**Message Meaning:** Wireless station association failed

**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43658 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_NO\_RESP

**Message ID:** 43658

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_NO\_RESP

**Message Meaning:** Wireless station DHCP process failed with no server response

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43659 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_DIFF\_OFFER

**Message ID:** 43659

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_DIFF\_OFFER

**Message Meaning:** Another DHCP server sent DHCP offer to wireless station

**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43660 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_NO\_ACK

**Message ID:** 43660**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_NO\_ACK**Message Meaning:** No DHCP ACK from server**Type:** Event**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

**43661 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_NAK****Message ID:** 43661**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_NAK**Message Meaning:** DHCP server sent DHCP NAK**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43662 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_DUP\_IP

**Message ID:** 43662

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_DUP\_IP

**Message Meaning:** IP offered has been used by another wireless station

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43663 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_DISCOVER

**Message ID:** 43663

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_DISCOVER

**Message Meaning:** Wireless station sent DHCP DISCOVER

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43664 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_OFFER

**Message ID:** 43664

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_OFFER

**Message Meaning:** DHCP server sent DHCP OFFER

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice



Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43665 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_DECLINE

**Message ID:** 43665

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_DECLINE

**Message Meaning:** Wireless station sent DHCP DECLINE

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43666 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_REQUEST

**Message ID:** 43666

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_REQUEST

**Message Meaning:** Wireless station sent DHCP REQUEST

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43667 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_ACK

**Message ID:** 43667

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_ACK

**Message Meaning:** DHCP server sent DHCP ACK

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43668 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_RELEASE

**Message ID:** 43668

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_RELEASE

**Message Meaning:** Wireless station sent DHCP RELEASE

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43669 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_INFORM

**Message ID:** 43669

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_INFORM

**Message Meaning:** Wireless station sent DHCP INFORM

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43670 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_SELF\_ASSIGNED

**Message ID:** 43670

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DHCP\_SELF\_ASSIGNED

**Message Meaning:** Wireless station is using self-assigned IP

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43671 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DNS\_NO\_RESP

**Message ID:** 43671

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DNS\_NO\_RESP

**Message Meaning:** Wireless station DNS process failed with no server response

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43672 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DNS\_SERVER\_FAILURE

**Message ID:** 43672

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DNS\_SERVER\_FAILURE

**Message Meaning:** Wireless station DNS process failed due to server failure

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice



Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43673 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DNS\_NO\_DOMAIN

**Message ID:** 43673

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DNS\_NO\_DOMAIN

**Message Meaning:** Wireless station DNS process failed due to non-existing domain

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vap		string	36
vd	Virtual Domain Name	string	32

## 43674 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_KRACK\_FT\_REASSOC

**Message ID:** 43674

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_KRACK\_FT\_REASSOC

**Message Meaning:** Wireless station WPA key reinstallation attack on FT reassociation

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43675 - LOG\_ID\_EVENT\_WIRELESS\_STA\_AUTH\_REQ

**Message ID:** 43675

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_AUTH\_REQ

**Message Meaning:** Authentication request from wireless station

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43676 - LOG\_ID\_EVENT\_WIRELESS\_STA\_AUTH\_RESP****Message ID:** 43676**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_AUTH\_RESP**Message Meaning:** Authentication response to wireless station

**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43677 - LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSOC\_REQ

**Message ID:** 43677

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSOC\_REQ

**Message Meaning:** Association request from wireless station

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

**43678 - LOG\_ID\_EVENT\_WIRELESS\_STA\_REASSOC\_REQ****Message ID:** 43678**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_REASSOC\_REQ**Message Meaning:** Reassociation request from wireless station**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vap		string	36
vd	Virtual Domain Name	string	32

## 43679 - LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSOC\_RESP

**Message ID:** 43679

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSOC\_RESP

**Message Meaning:** Association response to wireless station

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43680 - LOG\_ID\_EVENT\_WIRELESS\_STA\_REASSOC\_RESP

**Message ID:** 43680

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_REASSOC\_RESP

**Message Meaning:** Reassociation response to wireless station

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43681 - LOG\_ID\_EVENT\_WIRELESS\_STA\_PROBE\_REQ

**Message ID:** 43681

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_PROBE\_REQ

**Message Meaning:** Probe request from wireless station

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43682 - LOG\_ID\_EVENT\_WIRELESS\_STA\_PROBE\_RESP

**Message ID:** 43682

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_PROBE\_RESP

**Message Meaning:** Probe response to wireless station

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43683 - LOG\_ID\_EVENT\_WIRELESS\_BLE\_DEV\_LOCATE

**Message ID:** 43683

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_BLE\_DEV\_LOCATE

**Message Meaning:** Wireless ble dev detection

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
signal	Signal	int8	4
sn	Serial Number	string	64
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43684 - LOG\_ID\_EVENT\_WIRELESS\_ADDRGRP\_DUPLICATE\_MAC

**Message ID:** 43684

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ADDRGRP\_DUPLICATE\_MAC

**Message Meaning:** Wireless addrgrp duplicate mac

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
addrgrp		string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43685 - LOG\_ID\_EVENT\_WIRELESS\_ADDRGRP\_ADDR\_APPLY

**Message ID:** 43685

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ADDRGRP\_ADDR\_APPLY

**Message Meaning:** Wireless addrgrp address apply

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
addrgrp		string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

**43686 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_INVALID\_SCHEDULE****Message ID:** 43686**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WPA\_MSG\_INVALID\_SCHEDULE**Message Meaning:** PSK is out of any valid schedules**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
radioid	Radio ID	uint8	3
reason	Reason	string	256
remotewtptime		string	32
security	Security	string	40
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vap		string	36
vd	Virtual Domain Name	string	32

## 43687 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WL\_BRIDGE\_TRAFFIC\_STATS

**Message ID:** 43687

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WL\_BRIDGE\_TRAFFIC\_STATS

**Message Meaning:** Traffic stats for station with bridge wlan

**Type:** Event

**Category:** WIRELESS

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
nextstat		uint32	10
rcvdbyte		uint64	20
sentbyte		uint64	20
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16



Log Field Name	Description	Data Type	Length
tz		string	5
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43776 - LOG\_ID\_EVENT\_NAC\_QUARANTINE

**Message ID:** 43776

**Message Description:** LOG\_ID\_EVENT\_NAC\_QUARANTINE

**Message Meaning:** NAC quarantine

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
admin		string	64
banned_rule	NAC quarantine Banned Rule Name	string	80
banned_src	NAC quarantine Banned Source IP	string	16
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
proto	Protocol Number	uint8	3
sensor	NAC Sensor Name	string	36
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43777 - LOG\_ID\_EVENT\_NAC\_ANOMALY\_QUARANTINE

**Message ID:** 43777

**Message Description:** LOG\_ID\_EVENT\_NAC\_ANOMALY\_QUARANTINE

**Message Meaning:** NAC anomaly quarantine

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
admin		string	64
banned_rule	NAC quarantine Banned Rule Name	string	80
banned_src	NAC quarantine Banned Source IP	string	16
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
duration	Duration	uint32	10
eventtime		uint64	20
group	User group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
sensor	NAC Sensor Name	string	36
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43800 - LOG\_ID\_EVENT\_ELBC\_BLADE\_JOIN

**Message ID:** 43800

**Message Description:** LOG\_ID\_EVENT\_ELBC\_BLADE\_JOIN

**Message Meaning:** Blade ready to process traffic

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65

Log Field Name	Description	Data Type	Length
chassisid	Chassis ID	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
slot	Slot Number	uint8	3
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43801 - LOG\_ID\_EVENT\_ELBC\_BLADE\_LEAVE

**Message ID:** 43801

**Message Description:** LOG\_ID\_EVENT\_ELBC\_BLADE\_LEAVE

**Message Meaning:** Blade not ready to process traffic

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
chassisid	Chassis ID	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
slot	Slot Number	uint8	3
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43802 - LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_FOUND

**Message ID:** 43802

**Message Description:** LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_FOUND

**Message Meaning:** Master blade found

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
chassisid	Chassis ID	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
slot	Slot Number	uint8	3

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43803 - LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_LOST

**Message ID:** 43803

**Message Description:** LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_LOST

**Message Meaning:** Master blade lost

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
chassisid	Chassis ID	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
slot	Slot Number	uint8	3
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43804 - LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_CHANGE

**Message ID:** 43804

**Message Description:** LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_CHANGE

**Message Meaning:** Master blade changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
newchassisid	New Chassis ID	uint8	3
newslot	New Slot Number	uint8	3
oldchassisid	Original Chassis Number	uint8	3
oldslot	Original Slot Number	uint8	3
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43805 - LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_FOUND

**Message ID:** 43805

**Message Description:** LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_FOUND

**Message Meaning:** ELBC channel active

**Type:** Event

**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
chassisid	Chassis ID	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
newchannel	New Channel Number	uint8	3
slot	Slot Number	uint8	3
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43806 - LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_LOST

**Message ID:** 43806**Message Description:** LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_LOST**Message Meaning:** ELBC channel inactive**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
chassisid	Chassis ID	uint8	3
date	Date	string	10



Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
oldchannel	Original Channel Number	uint8	3
slot	Slot Number	uint8	3
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43807 - LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_CHANGE

**Message ID:** 43807

**Message Description:** LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_CHANGE

**Message Meaning:** ELBC channel failover

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
chassisid	Chassis ID	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
newchannel	New Channel Number	uint8	3
oldchannel	Original Channel Number	uint8	3
slot	Slot Number	uint8	3
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43808 - LOG\_ID\_EVENT\_ELBC\_CHASSIS\_ACTIVE

**Message ID:** 43808

**Message Description:** LOG\_ID\_EVENT\_ELBC\_CHASSIS\_ACTIVE

**Message Meaning:** ELBC chassis active

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
chassisid	Chassis ID	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 43809 - LOG\_ID\_EVENT\_ELBC\_CHASSIS\_INACTIVE

**Message ID:** 43809

**Message Description:** LOG\_ID\_EVENT\_ELBC\_CHASSIS\_INACTIVE

**Message Meaning:** ELBC chassis inactive

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	65
chassisid	Chassis ID	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	4096
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 44544 - LOGID\_EVENT\_CONFIG\_PATH

**Message ID:** 44544

**Message Description:** LOGID\_EVENT\_CONFIG\_PATH

**Message Meaning:** Path configured

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44545 - LOGID\_EVENT\_CONFIG\_OBJ

**Message ID:** 44545

**Message Description:** LOGID\_EVENT\_CONFIG\_OBJ

**Message Meaning:** Object configured

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

**44546 - LOGID\_EVENT\_CONFIG\_ATTR****Message ID:** 44546**Message Description:** LOGID\_EVENT\_CONFIG\_ATTR**Message Meaning:** Attribute configured**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cfgattr	configuration attribute	string	4096

Log Field Name	Description	Data Type	Length
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44547 - LOGID\_EVENT\_CONFIG\_OBJATTR

**Message ID:** 44547

**Message Description:** LOGID\_EVENT\_CONFIG\_OBJATTR

**Message Meaning:** Object attribute configured

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44548 - LOGID\_EVENT\_CONFIG\_EXEC

**Message ID:** 44548

**Message Description:** LOGID\_EVENT\_CONFIG\_EXEC

**Message Meaning:** Action performed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44549 - LOGID\_EVENT\_CONFIG\_OBJATTR\_MTNER

**Message ID:** 44549

**Message Description:** LOGID\_EVENT\_CONFIG\_OBJATTR\_MTNER

**Message Meaning:** Object attribute configured by maintainer

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44550 - LOGID\_EVENT\_CONFIG\_OBJ\_MTNER

**Message ID:** 44550

**Message Description:** LOGID\_EVENT\_CONFIG\_OBJ\_MTNER

**Message Meaning:** Object configured by maintainer

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44551 - LOGID\_EVENT\_CONFIG\_ATTR\_MTNER

**Message ID:** 44551

**Message Description:** LOGID\_EVENT\_CONFIG\_ATTR\_MTNER

**Message Meaning:** Attribute configured by maintainer

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
cfgattr	configuration attribute	string	4096
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44552 - LOGID\_EVENT\_CONFIG\_PATH\_MTNER

**Message ID:** 44552

**Message Description:** LOGID\_EVENT\_CONFIG\_PATH\_MTNER

**Message Meaning:** Path configured by maintainer

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44553 - LOGID\_EVENT\_CONFIG\_FIXEDPORT\_DIS

**Message ID:** 44553

**Message Description:** LOGID\_EVENT\_CONFIG\_FIXEDPORT\_DIS

**Message Meaning:** Policy attribute fixed port changed during upgrade

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
policyid	Policy ID	uint32	10
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

**44554 - LOGID\_EVENT\_CONFIG\_POL\_CHANGED****Message ID:** 44554**Message Description:** LOGID\_EVENT\_CONFIG\_POL\_CHANGED**Message Meaning:** Learning mode policy is converted to accept policy during upgrade.**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
policyid	Policy ID	uint32	10
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 44555 - LOGID\_EVENT\_CMDB\_DEADLOCK\_DETECTED

**Message ID:** 44555

**Message Description:** LOGID\_EVENT\_CMDB\_DEADLOCK\_DETECTED

**Message Meaning:** CMDB lock deadlock is detected.

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 45057 - LOG\_ID\_FCC\_ADD

**Message ID:** 45057

**Message Description:** LOG\_ID\_FCC\_ADD

**Message Meaning:** FortiClient connection added

**Type:** Event

**Category:** ENDPOINT

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	EndPoint Action	string	65
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
ip	Source IP	ip	39
level	Log Level	string	11
license_limit	Maximum Number of FortiClients for the License	string	32
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
name	Display Name of the Connection	string	128
status	Status	string	23
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
used_for_type	Connection for the type	uint32	10
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45058 - LOG\_ID\_FCC\_CLOSE

**Message ID:** 45058

**Message Description:** LOG\_ID\_FCC\_CLOSE

**Message Meaning:** FortiClient connection closed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 45061 - LOG\_ID\_FCC\_CLOSE\_BY\_TYPE

**Message ID:** 45061

**Message Description:** LOG\_ID\_FCC\_CLOSE\_BY\_TYPE

**Message Meaning:** FortiClient connection closed by type

**Type:** Event

**Category:** ENDPOINT

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	EndPoint Action	string	65
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
ip	Source IP	ip	39
level	Log Level	string	11
license_limit	Maximum Number of FortiClients for the License	string	32
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
name	Display Name of the Connection	string	128
status	Status	string	23
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
used_for_type	Connection for the type	uint32	10
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45071 - LOG\_ID\_FCC\_VULN\_SCAN

**Message ID:** 45071

**Message Description:** LOG\_ID\_FCC\_VULN\_SCAN

**Message Meaning:** FortiClient Vulnerability Scan

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
cveid	CVE ID	string	720
date	Date	string	10



Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
devtype		string	32
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
scantime		uint64	20
severity		string	10
srcip		ip	39
srcmac		string	17
srcname		string	64
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32
vendorurl		string	256
vulncat	Vulnerability Category	string	32
vulnid		uint32	10
vulnname		string	128

## 45109 - LOG\_ID\_EC\_FTCL\_LOGOFF

**Message ID:** 45109

**Message Description:** LOG\_ID\_EC\_FTCL\_LOGOFF

**Message Meaning:** FortiClient logged off

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45114 - LOG\_ID\_EC\_REG\_QUARANTINE

**Message ID:** 45114

**Message Description:** LOG\_ID\_EC\_REG\_QUARANTINE

**Message Meaning:** FortiClient endpoint quarantined

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctemssn		string	16

Log Field Name	Description	Data Type	Length
fctuid		string	32
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45115 - LOG\_ID\_EC\_REG\_UNQUARANTINE

**Message ID:** 45115

**Message Description:** LOG\_ID\_EC\_REG\_UNQUARANTINE

**Message Meaning:** FortiClient endpoint quarantine removed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctemssn		string	16
fctuid		string	32
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45119 - LOG\_ID\_EC\_FTCL\_DISCONN

**Message ID:** 45119

**Message Description:** LOG\_ID\_EC\_FTCL\_DISCONN

**Message Meaning:** FortiClient disconnected

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 46000 - LOG\_ID\_VIP\_REAL\_SVR\_ENA

**Message ID:** 46000

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_ENA

**Message Meaning:** VIP real server enabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46001 - LOG\_ID\_VIP\_REAL\_SVR\_DISA

**Message ID:** 46001

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_DISA

**Message Meaning:** VIP real server disabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46002 - LOG\_ID\_VIP\_REAL\_SVR\_UP

**Message ID:** 46002

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_UP

**Message Meaning:** VIP real server up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

**46003 - LOG\_ID\_VIP\_REAL\_SVR\_DOWN****Message ID:** 46003**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_DOWN**Message Meaning:** VIP real server down**Type:** Event**Category:** SYSTEM**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46004 - LOG\_ID\_VIP\_REAL\_SVR\_ENT\_HOLDDOWN

**Message ID:** 46004

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_ENT\_HOLDDOWN

**Message Meaning:** VIP real server entered hold-down

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10



Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46005 - LOG\_ID\_VIP\_REAL\_SVR\_FAIL\_HOLDDOWN

**Message ID:** 46005

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_FAIL\_HOLDDOWN

**Message Meaning:** VIP real server health check failed during hold-down

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46006 - LOG\_ID\_VIP\_REAL\_SVR\_FAIL

**Message ID:** 46006

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_FAIL

**Message Meaning:** VIP real server health check failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
monitor-name	Health Monitor Type	string	35
monitor-type	Health Monitor Name	string	32
msg	Message Text	string	4096
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46400 - LOG\_ID\_EVENT\_EXT\_SYS

**Message ID:** 46400

**Message Description:** LOG\_ID\_EVENT\_EXT\_SYS

**Message Meaning:** FortiExtender system activity

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46401 - LOG\_ID\_EVENT\_EXT\_LOCAL

**Message ID:** 46401

**Message Description:** LOG\_ID\_EVENT\_EXT\_LOCAL

**Message Meaning:** FortiExtender controller activity

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
level		string	11
logdesc		string	4096
logid		string	10
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46402 - LOG\_ID\_EVENT\_EXT\_LOCAL\_ERROR

**Message ID:** 46402

**Message Description:** LOG\_ID\_EVENT\_EXT\_LOCAL\_ERROR

**Message Meaning:** FortiExtender controller activity error

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Error

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
level		string	11
logdesc		string	4096
logid		string	10
subtype		string	20
time		string	8
type		string	16

Log Field Name	Description	Data Type	Length
tz		string	5
vd		string	32

## 46403 - LOG\_ID\_EVENT\_EXT\_REMOTE\_EMERG

**Message ID:** 46403

**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE\_EMERG

**Message Meaning:** Remote FortiExtender emergency activity

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
ip		ip	39
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096
sn		string	64
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46404 - LOG\_ID\_EVENT\_EXT\_REMOTE\_ALERT

**Message ID:** 46404

**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE\_ALERT

**Message Meaning:** Remote FortiExtender alert activity

**Type:** Event

**Category:** FORTIEXTENDER**Severity:** Alert

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
ip		ip	39
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096
sn		string	64
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46405 - LOG\_ID\_EVENT\_EXT\_REMOTE\_CRITICAL

**Message ID:** 46405**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE\_CRITICAL**Message Meaning:** Remote FortiExtender critical activity**Type:** Event**Category:** FORTIEXTENDER**Severity:** Critical

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
ip		ip	39
level		string	11
logdesc		string	4096

Log Field Name	Description	Data Type	Length
logid		string	10
msg		string	4096
sn		string	64
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46406 - LOG\_ID\_EVENT\_EXT\_REMOTE\_ERROR

**Message ID:** 46406

**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE\_ERROR

**Message Meaning:** Remote FortiExtender error activity

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Error

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
ip		ip	39
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096
sn		string	64
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46407 - LOG\_ID\_EVENT\_EXT\_REMOTE\_WARNING

**Message ID:** 46407

**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE\_WARNING

**Message Meaning:** Remote FortiExtender warning activity

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
ip		ip	39
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096
sn		string	64
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46408 - LOG\_ID\_EVENT\_EXT\_REMOTE\_NOTIF

**Message ID:** 46408

**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE\_NOTIF

**Message Meaning:** Remote FortiExtender notify activity

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Notice



Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
ip		ip	39
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096
sn		string	64
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46409 - LOG\_ID\_EVENT\_EXT\_REMOTE\_INFO

**Message ID:** 46409

**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE\_INFO

**Message Meaning:** Remote FortiExtender info activity

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Information

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
ip		ip	39
level		string	11
logdesc		string	4096
logid		string	10

Log Field Name	Description	Data Type	Length
msg		string	4096
sn		string	64
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46410 - LOG\_ID\_EVENT\_EXT\_REMOTE\_DEBUG

**Message ID:** 46410

**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE\_DEBUG

**Message Meaning:** Remote FortiExtender debug activity

**Type:** Event

**Category:** FORTIEXTENDER

**Severity:** Debug

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
ip		ip	39
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096
sn		string	64
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 46501 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_DETECTION

**Message ID:** 46501

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_DETECTION

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46502 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_GPSD

**Message ID:** 46502

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_GPSD

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46503 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_GPS\_LOC\_ACQUISITION

**Message ID:** 46503

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_GPS\_LOC\_ACQUISITION

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46504 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLD

**Message ID:** 46504

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLD

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46505 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLING\_PURGED

**Message ID:** 46505

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLING\_PURGED

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46506 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLING\_DAILY\_LOG

**Message ID:** 46506

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLING\_DAILY\_LOG

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46507 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_FW\_UPGRADE

**Message ID:** 46507

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_FW\_UPGRADE

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46508 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_QDL\_DETECTION

**Message ID:** 46508

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_QDL\_DETECTION

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46509 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_REBOOT

**Message ID:** 46509

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_REBOOT

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32



## 46510 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_OP\_MODE

**Message ID:** 46510

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_OP\_MODE

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46511 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_POWER\_ON\_OFF

**Message ID:** 46511

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_POWER\_ON\_OFF

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46512 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_SIM\_STATE

**Message ID:** 46512

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_SIM\_STATE

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46513 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_LINK\_CONNECTION

**Message ID:** 46513

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_LINK\_CONNECTION

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46514 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_MANUAL\_HANOVER

**Message ID:** 46514

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_MANUAL\_HANOVER

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46515 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_IP\_ADDR

**Message ID:** 46515

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_IP\_ADDR

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46600 - LOG\_ID\_EVENT\_AUTOMATION\_TRIGGERED

**Message ID:** 46600

**Message Description:** LOG\_ID\_EVENT\_AUTOMATION\_TRIGGERED

**Message Meaning:** Automation stitch triggered

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
stitch		string	36
subtype	Log Subtype	string	20
time	Time	string	8
trigger		string	36
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 46900 - LOG\_ID\_POE\_STATUS\_REPORT

**Message ID:** 46900

**Message Description:** LOG\_ID\_POE\_STATUS\_REPORT

**Message Meaning:** PoE device status reported

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 47000 - LOG\_ID\_MALWARE\_LIST\_TRUNCATED\_ENTER

**Message ID:** 47000

**Message Description:** LOG\_ID\_MALWARE\_LIST\_TRUNCATED\_ENTER

**Message Meaning:** External malware list is truncated

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 47001 - LOG\_ID\_MALWARE\_LIST\_TRUNCATED\_EXIT

**Message ID:** 47001

**Message Description:** LOG\_ID\_MALWARE\_LIST\_TRUNCATED\_EXIT

**Message Meaning:** External malware list is no longer truncated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 47203 - LOG\_ID\_ENTER\_BYPASS

**Message ID:** 47203

**Message Description:** LOG\_ID\_ENTER\_BYPASS

**Message Meaning:** Bypass ports pair entered bypass mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 47204 - LOG\_ID\_EXIT\_BYPASS

**Message ID:** 47204**Message Description:** LOG\_ID\_EXIT\_BYPASS**Message Meaning:** Bypass ports pair exited bypass mode**Type:** Event**Category:** SYSTEM**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48000 - LOG\_ID\_WAD\_SSL\_RCV\_HS

**Message ID:** 48000

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_HS

**Message Meaning:** SSL handshake received

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48001 - LOG\_ID\_WAD\_SSL\_RCV\_WRG\_HS

**Message ID:** 48001

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_WRG\_HS

**Message Meaning:** SSL handshake message incorrect

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48002 - LOG\_ID\_WAD\_SSL\_SENT\_HS

**Message ID:** 48002

**Message Description:** LOG\_ID\_WAD\_SSL\_SENT\_HS

**Message Meaning:** SSL handshake sent

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48003 - LOG\_ID\_WAD\_SSL\_WRG\_HS\_LEN

**Message ID:** 48003

**Message Description:** LOG\_ID\_WAD\_SSL\_WRG\_HS\_LEN

**Message Meaning:** SSL handshake length invalid

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48004 - LOG\_ID\_WAD\_SSL\_RCV\_CCS

**Message ID:** 48004

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_CCS

**Message Meaning:** SSL ChangeCipherSpec received

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48005 - LOG\_ID\_WAD\_SSL\_RSA\_DH\_FAIL

**Message ID:** 48005

**Message Description:** LOG\_ID\_WAD\_SSL\_RSA\_DH\_FAIL

**Message Meaning:** RSA verification of Diffie-Hellman parameters failed

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48006 - LOG\_ID\_WAD\_SSL\_SENT\_CCS

**Message ID:** 48006

**Message Description:** LOG\_ID\_WAD\_SSL\_SENT\_CCS

**Message Meaning:** SSL ChangeCipherSpec sent

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48007 - LOG\_ID\_WAD\_SSL\_BAD\_HASH

**Message ID:** 48007

**Message Description:** LOG\_ID\_WAD\_SSL\_BAD\_HASH

**Message Meaning:** SSL Finished hash mismatch

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
ssllocal		string	76
sslremote		string	76
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48009 - LOG\_ID\_WAD\_SSL\_DECRY\_FAIL

**Message ID:** 48009

**Message Description:** LOG\_ID\_WAD\_SSL\_DECRY\_FAIL

**Message Meaning:** SSL decryption failed

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20



Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
reason	Reason	string	256
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48011 - LOG\_ID\_WAD\_SSL\_LESS\_MINOR

**Message ID:** 48011

**Message Description:** LOG\_ID\_WAD\_SSL\_LESS\_MINOR

**Message Meaning:** SSL minor version less than configured minimum value

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48013 - LOG\_ID\_WAD\_SSL\_NOT\_SUPPORT\_CS

**Message ID:** 48013

**Message Description:** LOG\_ID\_WAD\_SSL\_NOT\_SUPPORT\_CS

**Message Meaning:** SSL Cipher Suites not supported

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48016 - LOG\_ID\_WAD\_SSL\_HS\_FIN

**Message ID:** 48016

**Message Description:** LOG\_ID\_WAD\_SSL\_HS\_FIN

**Message Meaning:** SSL handshake completed

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48017 - LOG\_ID\_WAD\_SSL\_HS\_TOO\_LONG

**Message ID:** 48017

**Message Description:** LOG\_ID\_WAD\_SSL\_HS\_TOO\_LONG

**Message Meaning:** SSL handshake too long

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48019 - LOG\_ID\_WAD\_SSL\_SENT\_ALERT

**Message ID:** 48019

**Message Description:** LOG\_ID\_WAD\_SSL\_SENT\_ALERT

**Message Meaning:** SSL alert sent

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48023 - LOG\_ID\_WAD\_SSL\_RCV\_ALERT

**Message ID:** 48023

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_ALERT

**Message Meaning:** SSL alert received

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	65
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48027 - LOG\_ID\_WAD\_SSL\_INVALID\_CONT\_TYPE

**Message ID:** 48027

**Message Description:** LOG\_ID\_WAD\_SSL\_INVALID\_CONT\_TYPE

**Message Meaning:** SSL Content Type invalid

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48029 - LOG\_ID\_WAD\_SSL\_BAD\_CCS\_LEN

**Message ID:** 48029

**Message Description:** LOG\_ID\_WAD\_SSL\_BAD\_CCS\_LEN

**Message Meaning:** SSL ChangeCipherSpec length invalid

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48031 - LOG\_ID\_WAD\_SSL\_BAD\_DH

**Message ID:** 48031

**Message Description:** LOG\_ID\_WAD\_SSL\_BAD\_DH

**Message Meaning:** SSL Diffie-Hellman value invalid

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48032 - LOG\_ID\_WAD\_SSL\_PUB\_KEY\_TOO\_BIG

**Message ID:** 48032

**Message Description:** LOG\_ID\_WAD\_SSL\_PUB\_KEY\_TOO\_BIG

**Message Meaning:** Certificate's public key too long

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48034 - LOG\_ID\_WAD\_SSL\_SERVER\_KEY\_HASH\_ALGORITHM\_MISMATCH

**Message ID:** 48034

**Message Description:** LOG\_ID\_WAD\_SSL\_SERVER\_KEY\_HASH\_ALGORITHM\_MISMATCH

**Message Meaning:** Server Key Exchange hash algorithm mismatch

**Type:** Event**Category:** WAD**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
received		uint8	3
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48035 - LOG\_ID\_WAD\_SSL\_SERVER\_KEY\_SIGNATURE\_ALGORITHM\_MISMATCH

**Message ID:** 48035**Message Description:** LOG\_ID\_WAD\_SSL\_SERVER\_KEY\_SIGNATURE\_ALGORITHM\_MISMATCH**Message Meaning:** Server Key Exchange signature algorithm mismatch**Type:** Event**Category:** WAD**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
expectedsignature		uint8	3
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
receivedsignature		uint8	3
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48038 - LOG\_ID\_WAD\_SSL\_RCV\_FATAL\_ALERT

**Message ID:** 48038

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_FATAL\_ALERT

**Message Meaning:** SSL Fatal Alert received

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48039 - LOG\_ID\_WAD\_SSL\_SENT\_FATAL\_ALERT

**Message ID:** 48039

**Message Description:** LOG\_ID\_WAD\_SSL\_SENT\_FATAL\_ALERT

**Message Meaning:** SSL fatal alert sent

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	65
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48101 - LOG\_ID\_WAD\_AUTH\_FAIL\_PSK

**Message ID:** 48101

**Message Description:** LOG\_ID\_WAD\_AUTH\_FAIL\_PSK

**Message Meaning:** WAN Optimization peer PSK authentication failed

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
authgrp	Authorization Group	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
host	Host Name	string	256
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48102 - LOG\_ID\_WAD\_AUTH\_FAIL\_OTH

**Message ID:** 48102

**Message Description:** LOG\_ID\_WAD\_AUTH\_FAIL\_OTH

**Message Meaning:** WAN Optimization peer authentication failed

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
authgrp	Authorization Group	string	36

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
peer		string	36
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48300 - LOG\_ID\_WRG\_SVR\_FGT\_CONF

**Message ID:** 48300

**Message Description:** LOG\_ID\_WRG\_SVR\_FGT\_CONF

**Message Meaning:** Server side WAN Optimization FortiGate configured incorrectly

**Type:** Event

**Category:** WAD

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 48301 - LOG\_ID\_UNEXP\_APP\_TYPE

**Message ID:** 48301

**Message Description:** LOG\_ID\_UNEXP\_APP\_TYPE

**Message Meaning:** Unexpected application type for WAN Optimization

**Type:** Event

**Category:** WAD

**Severity:** Critical

Log Field Name	Description	Data Type	Length
app-type	Address Type	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 51000 - LOG\_ID\_NB\_TBL\_CHG

**Message ID:** 51000

**Message Description:** LOG\_ID\_NB\_TBL\_CHG

**Message Meaning:** Neighbor table changed

**Type:** Event

**Category:** ROUTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
mac	Mac Address	string	17
msg	Message	string	4096
service	Name of Service	string	64
srcip		ip	39
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 52000 - LOG\_ID\_EVENT\_SECURITY\_AUDIT\_FABRIC\_SUMMARY

**Message ID:** 52000

**Message Description:** LOG\_ID\_EVENT\_SECURITY\_AUDIT\_FABRIC\_SUMMARY

**Message Meaning:** Security Rating summary

**Type:** Event

**Category:** SECURITY-RATING

**Severity:** Notice

Log Field Name	Description	Data Type	Length
auditid		uint64	20
auditscore		string	20
audittime		uint64	20
criticalcount		int32	10
date		string	10
devid		string	16
eventtime		uint64	20
highcount		int32	10
level		string	11
logdesc		string	4096
logid		string	10

Log Field Name	Description	Data Type	Length
lowcount		int32	10
mediumcount		int32	10
passedcount		int32	10
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 52001 - LOG\_ID\_EVENT\_SECURITY\_AUDIT\_FABRIC\_CHANGE

**Message ID:** 52001

**Message Description:** LOG\_ID\_EVENT\_SECURITY\_AUDIT\_FABRIC\_CHANGE

**Message Meaning:** Security Rating result change

**Type:** Event

**Category:** SECURITY-RATING

**Severity:** Notice

Log Field Name	Description	Data Type	Length
auditid		uint64	20
auditscore		string	20
audittime		uint64	20
criticalcount		int32	10
date		string	10
devid		string	16
eventtime		uint64	20
highcount		int32	10
level		string	11
logdesc		string	4096
logid		string	10
lowcount		int32	10
mediumcount		int32	10

Log Field Name	Description	Data Type	Length
passedcount		int32	10
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 53000 - LOG\_ID\_SDNC\_CONNECTED

**Message ID:** 53000

**Message Description:** LOG\_ID\_SDNC\_CONNECTED

**Message Meaning:** Connected to SDN server

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 53001 - LOG\_ID\_SDNC\_DISCONNECTED

**Message ID:** 53001

**Message Description:** LOG\_ID\_SDNC\_DISCONNECTED

**Message Meaning:** Disconnected from SDN server

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	65
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 53002 - LOG\_ID\_SDNC\_SUBSCRIBE

**Message ID:** 53002

**Message Description:** LOG\_ID\_SDNC\_SUBSCRIBE

**Message Meaning:** Dynamic SDN address channel opened

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 53003 - LOG\_ID\_SDNC\_UNSUBSCRIBE

**Message ID:** 53003

**Message Description:** LOG\_ID\_SDNC\_UNSUBSCRIBE

**Message Meaning:** Dynamic SDN address channel closed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message Text	string	4096
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 53100 - LOG\_ID\_VPN\_OCVPN\_REGISTERED

**Message ID:** 53100

**Message Description:** LOG\_ID\_VPN\_OCVPN\_REGISTERED

**Message Meaning:** Overlay Controller VPN registered

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 53101 - LOG\_ID\_VPN\_OCVPN\_UNREGISTERED

**Message ID:** 53101

**Message Description:** LOG\_ID\_VPN\_OCVPN\_UNREGISTERED

**Message Meaning:** Overlay Controller VPN unregistered

**Type:** Event



**Category:** VPN**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 53102 - LOG\_ID\_VPN\_OCVPN\_COMM\_ESTABLISHED

**Message ID:** 53102**Message Description:** LOG\_ID\_VPN\_OCVPN\_COMM\_ESTABLISHED**Message Meaning:** Overlay Controller VPN server communication established**Type:** Event**Category:** VPN**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 53103 - LOG\_ID\_VPN\_OCVPN\_COMM\_ERROR

**Message ID:** 53103

**Message Description:** LOG\_ID\_VPN\_OCVPN\_COMM\_ERROR

**Message Meaning:** Overlay Controller VPN server communication error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 53104 - LOG\_ID\_VPN\_OCVPN\_DNS\_ERROR

**Message ID:** 53104

**Message Description:** LOG\_ID\_VPN\_OCVPN\_DNS\_ERROR

**Message Meaning:** Overlay Controller VPN DNS error

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 53105 - LOG\_ID\_VPN\_OCVPN\_ROUTE\_ERROR

**Message ID:** 53105

**Message Description:** LOG\_ID\_VPN\_OCVPN\_ROUTE\_ERROR

**Message Meaning:** Overlay Controller VPN routing error

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	4096
logid	Log ID	string	10
msg	Message	string	4096
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32

## 53200 - LOG\_ID\_CONNECTOR\_OBJECT\_ADD

**Message ID:** 53200

**Message Description:** LOG\_ID\_CONNECTOR\_OBJECT\_ADD

**Message Meaning:** IP address added

**Type:** Event

**Category:** CONNECTOR

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	65
addr		string	80
cfgobj		string	256
cldobjid		string	128
date		string	10
devid		string	16
eventtime		uint64	20
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096

Log Field Name	Description	Data Type	Length
netid		string	128
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32

## 53201 - LOG\_ID\_CONNECTOR\_OBJECT\_REMOVE

**Message ID:** 53201

**Message Description:** LOG\_ID\_CONNECTOR\_OBJECT\_REMOVE

**Message Meaning:** IP address removed

**Type:** Event

**Category:** CONNECTOR

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	65
addr		string	80
cfgobj		string	256
cldobjid		string	128
date		string	10
devid		string	16
eventtime		uint64	20
level		string	11
logdesc		string	4096
logid		string	10
msg		string	4096
netid		string	128
subtype		string	20
time		string	8
type		string	16

Log Field Name	Description	Data Type	Length
tz		string	5
vd		string	32

## FILE-FILTER

### 64000 - LOG\_ID\_FILE\_FILTER\_BLOCK

**Message ID:** 64000

**Message Description:** LOG\_ID\_FILE\_FILTER\_BLOCK

**Message Meaning:** File was blocked by file filter

**Type:** FILE-FILTER

**Category:** FILE-FILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	20
agent		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
filetype		string	23
filtername		string	32

Log Field Name	Description	Data Type	Length
forwardedfor		string	128
from		string	128
group		string	64
hostname		string	256
level		string	11
logid		string	10
matchfilename		string	256
matchfiletype		string	23
msg		string	512
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
recipient		string	512
sender		string	128
service		string	36
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subject		string	256
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 64001 - LOG\_ID\_FILE\_FILTER\_LOG

**Message ID:** 64001

**Message Description:** LOG\_ID\_FILE\_FILTER\_LOG

**Message Meaning:** File was detected by file filter

**Type:** FILE-FILTER

**Category:** FILE-FILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	20
agent		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10



Log Field Name	Description	Data Type	Length
filetype		string	23
filtername		string	32
forwardedfor		string	128
from		string	128
group		string	64
hostname		string	256
level		string	11
logid		string	10
matchfilename		string	256
matchfiletype		string	23
msg		string	512
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
recipient		string	512
sender		string	128
service		string	36
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subject		string	256
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39

Log Field Name	Description	Data Type	Length
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## GTP

### 41216 - LOGID\_GTP\_FORWARD

**Message ID:** 41216

**Message Description:** LOGID\_GTP\_FORWARD

**Message Meaning:** GTP forward

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128

Log Field Name	Description	Data Type	Length
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41217 - LOGID\_GTP\_DENY

**Message ID:** 41217

**Message Description:** LOGID\_GTP\_DENY

**Message Meaning:** GTP deny

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32

Log Field Name	Description	Data Type	Length
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41218 - LOGID\_GTP\_RATE\_LIMIT

**Message ID:** 41218

**Message Description:** LOGID\_GTP\_RATE\_LIMIT

**Message Meaning:** GTP rate limit

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25

Log Field Name	Description	Data Type	Length
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41219 - LOGID\_GTP\_STATE\_INVALID

**Message ID:** 41219

**Message Description:** LOGID\_GTP\_STATE\_INVALID

**Message Meaning:** GTP state invalid

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41220 - LOGID\_GTP\_TUNNEL\_LIMIT

**Message ID:** 41220

**Message Description:** LOGID\_GTP\_TUNNEL\_LIMIT

**Message Meaning:** Tunnel limit GTP message. These messages occur only when the maximum number of GTP tunnels is reached. No new tunnels are created when the maximum number is reached



**Type:** GTP**Category:** GTP-ALL**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41221 - LOGID\_GTP\_TRAFFIC\_COUNT

**Message ID:** 41221

**Message Description:** LOGID\_GTP\_TRAFFIC\_COUNT

**Message Meaning:** Statistic summary information when the GTP tunnel is being torn down

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-bytes	Control Plane Data Bytes	uint64	20
c-ggsn	Control Plane GGSN IP Address	ip	39
c-ggsn-teid	Control Plane GGSN Tunnel Endpoint Identifier	uint32	10
c-pkts	Control Plane Packets	uint64	20
c-sgsn	Control Plane SGSN IP Address	ip	39
c-sgsn-teid	Control Plane SGSN Tunnel Endpoint Identifier	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
duration	tunnel duration	uint32	10
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-bytes	User Plane Data Bytes	uint64	20
u-ggsn	user plane ggsn IP address	ip	39
u-ggsn-teid	user plane ggsn teid	uint32	10
u-pkts	User Plane Packets	uint64	20
u-sgsn	user plane sgsn IP address	ip	39
u-sgsn-teid	user plane sgsn tunnel endpoint identifier	uint32	10
uli		string	32
ulimcc		uint16	3

Log Field Name	Description	Data Type	Length
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41222 - LOGID\_GTP\_USER\_DATA

**Message ID:** 41222

**Message Description:** LOGID\_GTP\_USER\_DATA

**Message Meaning:** GTP user data

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
devid		string	16
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
profile	Profile Name	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
user_data	user traffic content inside gtp-u tunnel	string	256
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41223 - LOGID\_GTPV2\_FORWARD

**Message ID:** 41223

**Message Description:** LOGID\_GTPV2\_FORWARD

**Message Meaning:** GTPv2 forward message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41224 - LOGID\_GTPV2\_DENY

**Message ID:** 41224

**Message Description:** LOGID\_GTPV2\_DENY

**Message Meaning:** GTPv2 deny message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128

Log Field Name	Description	Data Type	Length
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41225 - LOGID\_GTPV2\_RATE\_LIMIT

**Message ID:** 41225

**Message Description:** LOGID\_GTPV2\_RATE\_LIMIT

**Message Meaning:** GTPv2 rate limit message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3



Log Field Name	Description	Data Type	Length
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41226 - LOGID\_GTPV2\_STATE\_INVALID

**Message ID:** 41226

**Message Description:** LOGID\_GTPV2\_STATE\_INVALID

**Message Meaning:** GTPv2 state invalid message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41227 - LOGID\_GTPV2\_TUNNEL\_LIMIT

**Message ID:** 41227

**Message Description:** LOGID\_GTPV2\_TUNNEL\_LIMIT

**Message Meaning:** Tunnel limit GTP (version 2) message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128

Log Field Name	Description	Data Type	Length
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41228 - LOGID\_GTPV2\_TRAFFIC\_COUNT

**Message ID:** 41228

**Message Description:** LOGID\_GTPV2\_TRAFFIC\_COUNT

**Message Meaning:** Statistic summary information when the GTPv2 tunnel is being torn down

**Type:** GTP**Category:** GTP-ALL**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-bytes	Control Plane Data Bytes	uint64	20
c-pkts	Control Plane Packets	uint64	20
cpdladdr	Control Plane Downlink IP Address	ip	39
cpdlisraddr	Control Plane ISR Downlink IP Address	ip	39
cpdlisrteid	control plane ISR downlink tunnel endpoint identifier	uint32	10
cpdlteid	control plane downlink tunnel endpoint identifier	uint32	10
cpuladdr	control plane uplink IP address	ip	39
cpulteid	control plane uplink teid	uint32	10
date	Date	string	10
devid		string	16
duration	tunnel duration	uint32	10
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-bytes	User Plane Data Bytes	uint64	20
u-pkts	User Plane Packets	uint64	20
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41229 - LOGID\_GTPU\_FORWARD

**Message ID:** 41229

**Message Description:** LOGID\_GTPU\_FORWARD

**Message Meaning:** GTPU forward message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41230 - LOGID\_GTPU\_DENY

**Message ID:** 41230

**Message Description:** LOGID\_GTPU\_DENY

**Message Meaning:** GTPU deny message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10

Log Field Name	Description	Data Type	Length
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## IPS

### 16384 - LOGID\_ATTCK\_SIGNATURE\_TCP\_UDP

**Message ID:** 16384

**Message Description:** LOGID\_ATTCK\_SIGNATURE\_TCP\_UDP

**Message Meaning:** Attack detected by UCP/TCP signature

**Type:** IPS

**Category:** SIGNATURE

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256



Log Field Name	Description	Data Type	Length
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction		string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname		string	256
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rawdataid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	4096

Log Field Name	Description	Data Type	Length
service	Service name	string	80
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 16385 - LOGID\_ATTCK\_SIGNATURE\_ICMP

**Message ID:** 16385

**Message Description:** LOGID\_ATTCK\_SIGNATURE\_ICMP

**Message Meaning:** Attack detected by ICMP signature

**Type:** IPS

**Category:** SIGNATURE

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16

Log Field Name	Description	Data Type	Length
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction		string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
icmpcode	Destination Port of the ICMP message	string	6
icmpid	Source port of the ICMP message	string	8
icmpitype	The type of ICMP message	string	6
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480

Log Field Name	Description	Data Type	Length
rawdatabid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	4096
service	Service name	string	80
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 16386 - LOGID\_ATTCK\_SIGNATURE\_OTHERS

**Message ID:** 16386

**Message Description:** LOGID\_ATTCK\_SIGNATURE\_OTHERS

**Message Meaning:** Attack detected by other signature

**Type:** IPS

**Category:** SIGNATURE

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16

Log Field Name	Description	Data Type	Length
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rawdataid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	4096
service	Service name	string	80
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
severity	Severity of the attack	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 16399 - LOGID\_ATTACK\_MALICIOUS\_URL

**Message ID:** 16399

**Message Description:** LOGID\_ATTACK\_MALICIOUS\_URL

**Message Meaning:** Attack detected by a malicious URL

**Type:** IPS

**Category:** MALICIOUS-URL

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action		string	16
attack		string	256
attackcontext		string	2040
attackcontextid		string	10
authserver		string	32

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
forwardedfor		string	128
hostname		string	256
level		string	11
logid		string	10
msg		string	518
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
service		string	80
sessionid		uint32	10
severity		string	8
srccountry		string	64
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 16400 - LOGID\_ATTACK\_BOTNET\_WARNING

**Message ID:** 16400

**Message Description:** LOGID\_ATTACK\_BOTNET\_WARNING

**Message Meaning:** Botnet C&C Communication (warning)

**Type:** IPS

**Category:** BOTNET

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
attack		string	256
attackcontext		string	2040
attackcontextid		string	10
attackid		uint32	10
authserver		string	32
craction		uint32	10
crlevel		string	10



Log Field Name	Description	Data Type	Length
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
forwardedfor		string	128
group		string	64
level		string	11
logid		string	10
msg		string	518
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
ref		string	4096
service		string	80
sessionid		uint32	10
severity		string	8
srccountry		string	64
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39

Log Field Name	Description	Data Type	Length
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 16401 - LOGID\_ATTACK\_BOTNET\_NOTIF

**Message ID:** 16401

**Message Description:** LOGID\_ATTACK\_BOTNET\_NOTIF

**Message Meaning:** Botnet C&C Communication (notice)

**Type:** IPS

**Category:** BOTNET

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
attack		string	256
attackcontext		string	2040
attackcontextid		string	10
attackid		uint32	10
authserver		string	32
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
forwardedfor		string	128
group		string	64
level		string	11
logid		string	10
msg		string	518
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
ref		string	4096
service		string	80
sessionid		uint32	10
severity		string	8
srccountry		string	64
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## SSH

### 61000 - LOG\_ID\_SSH\_COMMAND\_BLOCK

**Message ID:** 61000

**Message Description:** LOG\_ID\_SSH\_COMMAND\_BLOCK

**Message Meaning:** SSH shell command is blocked

**Type:** SSH

**Category:** SSH-COMMAND

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61001 - LOG\_ID\_SSH\_COMMAND\_BLOCK\_ALERT

**Message ID:** 61001

**Message Description:** LOG\_ID\_SSH\_COMMAND\_BLOCK\_ALERT

**Message Meaning:** SSH shell command is blocked

**Type:** SSH

**Category:** SSH-COMMAND

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61002 - LOG\_ID\_SSH\_COMMAND\_PASS

**Message ID:** 61002

**Message Description:** LOG\_ID\_SSH\_COMMAND\_PASS

**Message Meaning:** SSH shell command is detected

**Type:** SSH

**Category:** SSH-COMMAND

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10

Log Field Name	Description	Data Type	Length
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61003 - LOG\_ID\_SSH\_COMMAND\_PASS\_ALERT

**Message ID:** 61003

**Message Description:** LOG\_ID\_SSH\_COMMAND\_PASS\_ALERT

**Message Meaning:** SSH shell command is detected

**Type:** SSH

**Category:** SSH-COMMAND

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15



Log Field Name	Description	Data Type	Length
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user		string	256
vd		string	32

## 61010 - LOG\_ID\_SSH\_CHANNEL\_BLOCK

**Message ID:** 61010

**Message Description:** LOG\_ID\_SSH\_CHANNEL\_BLOCK

**Message Meaning:** SSH channel is blocked

**Type:** SSH

**Category:** SSH-CHANNEL

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	17
channeleype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10

Log Field Name	Description	Data Type	Length
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61011 - LOG\_ID\_SSH\_CHANNEL\_PASS

**Message ID:** 61011

**Message Description:** LOG\_ID\_SSH\_CHANNEL\_PASS

**Message Meaning:** SSH channel is detected

**Type:** SSH

**Category:** SSH-CHANNEL

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## SSL

### 62000 - LOG\_ID\_SSL\_CERT\_BLACKLISTED

**Message ID:** 62000

**Message Description:** LOG\_ID\_SSL\_CERT\_BLACKLISTED

**Message Meaning:** Certificate blacklisted

**Type:** SSL

**Category:** SSL-ANOMALIES

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3

Log Field Name	Description	Data Type	Length
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 62001 - LOG\_ID\_SSL\_CERT\_PASS

**Message ID:** 62001

**Message Description:** LOG\_ID\_SSL\_CERT\_PASS

**Message Meaning:** Server certificate passed

**Type:** SSL

**Category:** SSL-ANOMALIES

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10

Log Field Name	Description	Data Type	Length
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user		string	256
vd		string	32

## 62002 - LOG\_ID\_SSL\_CERT\_BLOCK

**Message ID:** 62002

**Message Description:** LOG\_ID\_SSL\_CERT\_BLOCK

**Message Meaning:** Server certificate blocked

**Type:** SSL

**Category:** SSL-ANOMALIES

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10



Log Field Name	Description	Data Type	Length
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 62003 - LOG\_ID\_SSL\_EXEMPT

**Message ID:** 62003

**Message Description:** LOG\_ID\_SSL\_EXEMPT

**Message Meaning:** SSL connection exempted

**Type:** SSL

**Category:** SSL-ANOMALIES

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64

Log Field Name	Description	Data Type	Length
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 62050 - LOG\_ID\_SSL\_HS\_CERT\_REQ\_EXEMPT

**Message ID:** 62050

**Message Description:** LOG\_ID\_SSL\_HS\_CERT\_REQ\_EXEMPT

**Message Meaning:** Certificate request exempted

**Type:** SSL

**Category:** SSL-ANOMALIES

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10

Log Field Name	Description	Data Type	Length
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 62051 - LOG\_ID\_SSL\_HS\_CERT\_REQ\_BLOCK

**Message ID:** 62051

**Message Description:** LOG\_ID\_SSL\_HS\_CERT\_REQ\_BLOCK

**Message Meaning:** Certificate request blocked

**Type:** SSL

**Category:** SSL-ANOMALIES

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	17

Log Field Name	Description	Data Type	Length
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8

Log Field Name	Description	Data Type	Length
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 62052 - LOG\_ID\_SSL\_HS\_UNSUPPROTED\_EXEMPT

**Message ID:** 62052

**Message Description:** LOG\_ID\_SSL\_HS\_UNSUPPROTED\_EXEMPT

**Message Meaning:** Connection is bypassed due to unsupported SSL traffic

**Type:** SSL

**Category:** SSL-ANOMALIES

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256

Log Field Name	Description	Data Type	Length
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 62053 - LOG\_ID\_SSL\_HS\_UNSUPPORTED\_BLOCK

**Message ID:** 62053

**Message Description:** LOG\_ID\_SSL\_HS\_UNSUPPORTED\_BLOCK

**Message Meaning:** Connection is blocked due to unsupported SSL traffic

**Type:** SSL

**Category:** SSL-ANOMALIES

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20



Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 62200 - LOG\_ID\_SSL\_EXEMPT\_ADDR

**Message ID:** 62200

**Message Description:** LOG\_ID\_SSL\_EXEMPT\_ADDR

**Message Meaning:** SSL connection is exempted based on address

**Type:** SSL

**Category:** SSL-EXEMPT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64

Log Field Name	Description	Data Type	Length
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 62202 - LOG\_ID\_SSL\_EXEMPT\_FTGD\_CAT

**Message ID:** 62202

**Message Description:** LOG\_ID\_SSL\_EXEMPT\_FTGD\_CAT

**Message Meaning:** SSL connection is exempted based on FortiGuard category rating

**Type:** SSL

**Category:** SSL-EXEMPT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## Traffic

### 2 - LOG\_ID\_TRAFFIC\_ALLOW

**Message ID:** 2

**Message Description:** LOG\_ID\_TRAFFIC\_ALLOW

**Message Meaning:** Allowed traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16

Log Field Name	Description	Data Type	Length
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37

Log Field Name	Description	Data Type	Length
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentedelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10

Log Field Name	Description	Data Type	Length
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

### 3 - LOG\_ID\_TRAFFIC\_DENY

**Message ID:** 3

**Message Description:** LOG\_ID\_TRAFFIC\_DENY

**Message Meaning:** Traffic violation

**Type:** Traffic

**Category:** FORWARD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36



Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20

Log Field Name	Description	Data Type	Length
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16

Log Field Name	Description	Data Type	Length
tranip	NAT destination IP	ip	39
transport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 4 - LOG\_ID\_TRAFFIC\_OTHER\_START

**Message ID:** 4

**Message Description:** LOG\_ID\_TRAFFIC\_OTHER\_START

**Message Meaning:** Traffic other session start

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentedelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66

Log Field Name	Description	Data Type	Length
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwplanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 5 - LOG\_ID\_TRAFFIC\_OTHER\_ICMP\_ALLOW

**Message ID:** 5

**Message Description:** LOG\_ID\_TRAFFIC\_OTHER\_ICMP\_ALLOW



**Message Meaning:** Traffic allowed ICMP

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66

Log Field Name	Description	Data Type	Length
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36

Log Field Name	Description	Data Type	Length
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66

Log Field Name	Description	Data Type	Length
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 6 - LOG\_ID\_TRAFFIC\_OTHER\_ICMP\_DENY

**Message ID:** 6

**Message Description:** LOG\_ID\_TRAFFIC\_OTHER\_ICMP\_DENY

**Message Meaning:** Traffic denied ICMP

**Type:** Traffic

**Category:** FORWARD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64

Log Field Name	Description	Data Type	Length
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64

Log Field Name	Description	Data Type	Length
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentedelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64



Log Field Name	Description	Data Type	Length
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 7 - LOG\_ID\_TRAFFIC\_OTHER\_INVALID

**Message ID:** 7

**Message Description:** LOG\_ID\_TRAFFIC\_OTHER\_INVALID

**Message Meaning:** Traffic other invalid

**Type:** Traffic

**Category:** FORWARD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10

Log Field Name	Description	Data Type	Length
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20

Log Field Name	Description	Data Type	Length
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255

Log Field Name	Description	Data Type	Length
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32

Log Field Name	Description	Data Type	Length
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 8 - LOG\_ID\_TRAFFIC\_WANOPT

**Message ID:** 8

**Message Description:** LOG\_ID\_TRAFFIC\_WANOPT

**Message Meaning:** WAN optimization traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16

Log Field Name	Description	Data Type	Length
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3

Log Field Name	Description	Data Type	Length
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33



Log Field Name	Description	Data Type	Length
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 9 - LOG\_ID\_TRAFFIC\_WEBCACHE

**Message ID:** 9

**Message Description:** LOG\_ID\_TRAFFIC\_WEBCACHE

**Message Meaning:** Web cache traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10

Log Field Name	Description	Data Type	Length
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36

Log Field Name	Description	Data Type	Length
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 10 - LOG\_ID\_TRAFFIC\_EXPLICIT\_PROXY

**Message ID:** 10

**Message Description:** LOG\_ID\_TRAFFIC\_EXPLICIT\_PROXY

**Message Meaning:** Explicit proxy traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16

Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66

Log Field Name	Description	Data Type	Length
dsthwwendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10



Log Field Name	Description	Data Type	Length
polycyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17

Log Field Name	Description	Data Type	Length
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
wlid		uint32	10
wlquality		string	320
wlservice		string	64
wvpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20

Log Field Name	Description	Data Type	Length
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 11 - LOG\_ID\_TRAFFIC\_FAIL\_CONN

**Message ID:** 11

**Message Description:** LOG\_ID\_TRAFFIC\_FAIL\_CONN

**Message Meaning:** Failed connection attempts

**Type:** Traffic

**Category:** FORWARD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66

Log Field Name	Description	Data Type	Length
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

Log Field Name	Description	Data Type	Length
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 12 - LOG\_ID\_TRAFFIC\_MULTICAST

**Message ID:** 12

**Message Description:** LOG\_ID\_TRAFFIC\_MULTICAST

**Message Meaning:** Multicast traffic

**Type:** Traffic

**Category:** MULTICAST

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32

Log Field Name	Description	Data Type	Length
centralnatid		uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20



Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36

Log Field Name	Description	Data Type	Length
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
url		string	512
user	User name	string	256
utmaction		string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

### 13 - LOG\_ID\_TRAFFIC\_END\_FORWARD

**Message ID:** 13

**Message Description:** LOG\_ID\_TRAFFIC\_END\_FORWARD

**Message Meaning:** Forward traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16

Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66

Log Field Name	Description	Data Type	Length
dsthwwendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
polycyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17

Log Field Name	Description	Data Type	Length
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
wlid		uint32	10
wlquality		string	320
wlservice		string	64
wvpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20

Log Field Name	Description	Data Type	Length
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 14 - LOG\_ID\_TRAFFIC\_END\_LOCAL

**Message ID:** 14

**Message Description:** LOG\_ID\_TRAFFIC\_END\_LOCAL

**Message Meaning:** Local traffic

**Type:** Traffic

**Category:** LOCAL

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66

Log Field Name	Description	Data Type	Length
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction		string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

Log Field Name	Description	Data Type	Length
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

## 15 - LOG\_ID\_TRAFFIC\_START\_FORWARD

**Message ID:** 15

**Message Description:** LOG\_ID\_TRAFFIC\_START\_FORWARD

**Message Meaning:** Forward traffic session start

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32

Log Field Name	Description	Data Type	Length
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36

Log Field Name	Description	Data Type	Length
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 16 - LOG\_ID\_TRAFFIC\_START\_LOCAL

**Message ID:** 16

**Message Description:** LOG\_ID\_TRAFFIC\_START\_LOCAL

**Message Meaning:** Local traffic session start

**Type:** Traffic

**Category:** LOCAL

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16



Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33

Log Field Name	Description	Data Type	Length
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction		string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
wwpvlanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

## 17 - LOG\_ID\_TRAFFIC\_SNIFFER

**Message ID:** 17

**Message Description:** LOG\_ID\_TRAFFIC\_SNIFFER

**Message Meaning:** Sniffer traffic

**Type:** Traffic

**Category:** SNIFFER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16

Log Field Name	Description	Data Type	Length
agent		string	64
ap		string	36
app		string	96
appact		string	16
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
apsn		string	36
authserver		string	32
centralnatid		uint32	10
channel		uint32	10
comment		string	1024
countapp		uint32	10
countav		uint32	10
countcifs		uint32	10
countdlp		uint32	10
countdns		uint32	10
countemail		uint32	10
countff		uint32	10
countips		uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb		uint32	10
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16

Log Field Name	Description	Data Type	Length
devtype		string	66
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstmac		string	17
dstname		string	66
dstosname		string	66
dstport		uint16	5
dstserver		uint8	3
dstssid		string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid		string	37
duration		uint32	10
eventtime		uint64	20
fctuid		string	32
group		string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level		string	11
logid		string	10
masterdstmac		string	17

Log Field Name	Description	Data Type	Length
mastersrcmac		string	17
msg		string	64
osname		string	66
policyid		uint32	10
policyname		string	36
policytype		string	24
poluid		string	37
proto		uint8	3
radioband		string	64
rcvbyte		uint64	20
rcvdelta		uint64	20
rcvpkt		uint32	10
sentbyte		uint64	20
sentdelta		uint64	20
sentpkt		uint32	10
service		string	80
sessionid		uint32	10
shaperdroprcvbyte		uint32	10
shaperdropsentbyte		uint32	10
shaperperipdropbyte		uint32	10
shaperperipname		string	36
shaperrcvdname		string	36
shapersentname		string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64

Log Field Name	Description	Data Type	Length
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcmac		string	17
srcname		string	66
srcport		uint16	5
srcserver		uint8	3
srcssid		string	33
srcswversion		string	66
srcuuid		string	37
sslaction		string	26
subtype		string	20
time		string	8
trandisp		string	16
tranip		ip	39
tranport		uint16	5
transip		ip	39
transport		uint16	5
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
utmaction		string	32
vd		string	32
vpn		string	32
vpntype		string	14
vrf		uint8	3
vwlid		uint32	10



Log Field Name	Description	Data Type	Length
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

## 19 - LOG\_ID\_TRAFFIC\_BROADCAST

**Message ID:** 19

**Message Description:** LOG\_ID\_TRAFFIC\_BROADCAST

**Message Meaning:** Broadcast traffic

**Type:** Traffic

**Category:** MULTICAST

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid		uint32	10
channel		uint32	10

Log Field Name	Description	Data Type	Length
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64

Log Field Name	Description	Data Type	Length
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10

Log Field Name	Description	Data Type	Length
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256

Log Field Name	Description	Data Type	Length
utmaction		string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
wwpvlanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

## 20 - LOG\_ID\_TRAFFIC\_STAT

**Message ID:** 20

**Message Description:** LOG\_ID\_TRAFFIC\_STAT

**Message Meaning:** Forward traffic statistics

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10

Log Field Name	Description	Data Type	Length
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66

Log Field Name	Description	Data Type	Length
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10

Log Field Name	Description	Data Type	Length
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5



Log Field Name	Description	Data Type	Length
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
wpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 21 - LOG\_ID\_TRAFFIC\_SNIFFER\_STAT

**Message ID:** 21

**Message Description:** LOG\_ID\_TRAFFIC\_SNIFFER\_STAT

**Message Meaning:** Sniffer traffic statistics

**Type:** Traffic

**Category:** SNIFFER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
ap		string	36

Log Field Name	Description	Data Type	Length
app		string	96
appact		string	16
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
apsn		string	36
authserver		string	32
centralnatid		uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
devtype		string	66
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstmac		string	17
dstname		string	66
dstosname		string	66
dstport		uint16	5

Log Field Name	Description	Data Type	Length
dstserver		uint8	3
dstssid		string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid		string	37
duration		uint32	10
eventtime		uint64	20
fctuid		string	32
group		string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level		string	11
logid		string	10
masterdstmac		string	17
mastersrcmac		string	17
msg		string	64
osname		string	66
policyid		uint32	10
policyname		string	36
policytype		string	24
poluid		string	37
proto		uint8	3
radioband		string	64
rcvdbyte		uint64	20
rcvddelta		uint64	20
rcvdpkt		uint32	10
sentbyte		uint64	20
sentdelta		uint64	20

Log Field Name	Description	Data Type	Length
sentpkt		uint32	10
service		string	80
sessionid		uint32	10
shaperdroprcvdbyte		uint32	10
shaperdropsentbyte		uint32	10
shaperperipdropbyte		uint32	10
shaperperipname		string	36
shaperrcvdname		string	36
shapersentname		string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcmac		string	17
srcname		string	66
srcport		uint16	5
srcserver		uint8	3
srcssid		string	33
srcswversion		string	66
srcuuid		string	37
sslaction		string	26
subtype		string	20
time		string	8
trandisp		string	16

Log Field Name	Description	Data Type	Length
tranip		ip	39
transport		uint16	5
transip		ip	39
transport		uint16	5
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
utmaction		string	32
vd		string	32
vpn		string	32
vpntype		string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

## 22 - LOG\_ID\_TRAFFIC\_UTM\_CORRELATION

**Message ID:** 22

**Message Description:** LOG\_ID\_TRAFFIC\_UTM\_CORRELATION

**Message Meaning:** Forward traffic for UTM correlation

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66



Log Field Name	Description	Data Type	Length
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32

Log Field Name	Description	Data Type	Length
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## VoIP

### 44032 - LOGID\_EVENT\_VOIP\_SIP

**Message ID:** 44032

**Message Description:** LOGID\_EVENT\_VOIP\_SIP

**Message Meaning:** VoIP SIP

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
event_id		uint32	10
from		string	128
kind		string	10
level		string	11
logid		string	10
policy_id		uint32	10
profile		string	64
proto		uint8	3
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
to		string	512
type		string	16
tz		string	5
vd		string	32
voip_proto		string	4

## 44033 - LOGID\_EVENT\_VOIP\_SIP\_BLOCK

**Message ID:** 44033

**Message Description:** LOGID\_EVENT\_VOIP\_SIP\_BLOCK

**Message Meaning:** VoIP SIP blocked

**Type:** VoIP

**Category:** VOIP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
count		uint32	10
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
from		string	128
kind		string	10
level		string	11
logid		string	10
message_type		string	16
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
request_name		string	64
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8

Log Field Name	Description	Data Type	Length
to		string	512
type		string	16
tz		string	5
vd		string	32
voip_proto		string	4

## 44034 - LOGID\_EVENT\_VOIP\_SIP\_FUZZING

**Message ID:** 44034

**Message Description:** LOGID\_EVENT\_VOIP\_SIP\_FUZZING

**Message Meaning:** VoIP SIP fuzzing

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
column		uint32	10
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
line		string	128

Log Field Name	Description	Data Type	Length
logid		string	10
malform_data		uint32	10
malform_desc		string	47
message_type		string	16
policy_id		uint32	10
profile		string	64
proto		uint8	3
request_name		string	64
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32
voip_proto		string	4

## 44035 - LOGID\_EVENT\_VOIP\_SCCP\_REGISTER

**Message ID:** 44035

**Message Description:** LOGID\_EVENT\_VOIP\_SCCP\_REGISTER

**Message Meaning:** VoIP SCCP registered

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16

Log Field Name	Description	Data Type	Length
dstip		ip	39
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32
voip_proto		string	4

## 44036 - LOGID\_EVENT\_VOIP\_SCCP\_UNREGISTER

**Message ID:** 44036

**Message Description:** LOGID\_EVENT\_VOIP\_SCCP\_UNREGISTER

**Message Meaning:** VoIP SCCP unregistered

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32
voip_proto		string	4

## 44037 - LOGID\_EVENT\_VOIP\_SCCP\_CALL\_BLOCK

**Message ID:** 44037



**Message Description:** LOGID\_EVENT\_VOIP\_SCCP\_CALL\_BLOCK

**Message Meaning:** VoIP SCCP call blocked

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
tz		string	5

Log Field Name	Description	Data Type	Length
vd		string	32
voip_proto		string	4

## 44038 - LOGID\_EVENT\_VOIP\_SCCP\_CALL\_INFO

**Message ID:** 44038

**Message Description:** LOGID\_EVENT\_VOIP\_SCCP\_CALL\_INFO

**Message Meaning:** VoIP SCCP call information

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
locport		uint16	5
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3

Log Field Name	Description	Data Type	Length
remip		ip	39
rempport		uint16	5
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
tz		string	5
vd		string	32
voip_proto		string	4

## WAF

### 30248 - LOGID\_WAF\_SIGNATURE\_BLOCK

**Message ID:** 30248

**Message Description:** LOGID\_WAF\_SIGNATURE\_BLOCK

**Message Meaning:** Web application firewall blocked application by signature

**Type:** WAF

**Category:** WAF-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32

Log Field Name	Description	Data Type	Length
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg	Log Message	string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30249 - LOGID\_WAF\_SIGNATURE\_PASS

**Message ID:** 30249

**Message Description:** LOGID\_WAF\_SIGNATURE\_PASS

**Message Meaning:** Web application firewall passed application by signature

**Type:** WAF

**Category:** WAF-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg	Log Message	string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30250 - LOGID\_WAF\_SIGNATURE\_ERASE

**Message ID:** 30250

**Message Description:** LOGID\_WAF\_SIGNATURE\_ERASE

**Message Meaning:** Web application firewall erased application by signature

**Type:** WAF

**Category:** WAF-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
method		string	4096
msg	Log Message	string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30251 - LOGID\_WAF\_CUSTOM\_SIGNATURE\_BLOCK

**Message ID:** 30251

**Message Description:** LOGID\_WAF\_CUSTOM\_SIGNATURE\_BLOCK

**Message Meaning:** Web application firewall blocked application by custom signature

**Type:** WAF

**Category:** WAF-CUSTOM-SIGNATURE



**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30252 - LOGID\_WAF\_CUSTOM\_SIGNATURE\_PASS

**Message ID:** 30252

**Message Description:** LOGID\_WAF\_CUSTOM\_SIGNATURE\_PASS

**Message Meaning:** Web application firewall allowed application by custom signature

**Type:** WAF

**Category:** WAF-CUSTOM-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 30253 - LOGID\_WAF\_METHOD\_BLOCK

**Message ID:** 30253

**Message Description:** LOGID\_WAF\_METHOD\_BLOCK

**Message Meaning:** Web application firewall blocked application by HTTP method

**Type:** WAF

**Category:** WAF-HTTP-METHOD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent		string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Http Method	string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30255 - LOGID\_WAF\_ADDRESS\_LIST\_BLOCK

**Message ID:** 30255

**Message Description:** LOGID\_WAF\_ADDRESS\_LIST\_BLOCK

**Message Meaning:** Web application firewall blocked application by address list

**Type:** WAF

**Category:** WAF-ADDRESS-LIST

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30257 - LOGID\_WAF\_CONSTRAINTS\_BLOCK

**Message ID:** 30257

**Message Description:** LOGID\_WAF\_CONSTRAINTS\_BLOCK

**Message Meaning:** Web application firewall blocked application by HTTP constraints

**Type:** WAF

**Category:** WAF-HTTP-CONSTRAINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint	WAF http protocol restrictions	string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6



Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30258 - LOGID\_WAF\_CONSTRAINTS\_PASS

**Message ID:** 30258

**Message Description:** LOGID\_WAF\_CONSTRAINTS\_PASS

**Message Meaning:** Web application firewall allowed application by HTTP constraints

**Type:** WAF

**Category:** WAF-HTTP-CONSTRAINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint	WAF http protocol restrictions	string	4096
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 30259 - LOGID\_WAF\_URL\_ACCESS\_PERMIT

**Message ID:** 30259

**Message Description:** LOGID\_WAF\_URL\_ACCESS\_PERMIT

**Message Meaning:** Web application firewall allowed application by URL access permit

**Type:** WAF

**Category:** WAF-URL-ACCESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30260 - LOGID\_WAF\_URL\_ACCESS\_BYPASS

**Message ID:** 30260

**Message Description:** LOGID\_WAF\_URL\_ACCESS\_BYPASS

**Message Meaning:** Web application firewall allowed application by URL access bypass

**Type:** WAF

**Category:** WAF-URL-ACCESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30261 - LOGID\_WAF\_URL\_ACCESS\_BLOCK

**Message ID:** 30261

**Message Description:** LOGID\_WAF\_URL\_ACCESS\_BLOCK

**Message Meaning:** Web application firewall blocked application by URL access

**Type:** WAF

**Category:** WAF-URL-ACCESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## Web

### 12288 - LOG\_ID\_WEB\_CONTENT\_BANWORD

**Message ID:** 12288

**Message Description:** LOG\_ID\_WEB\_CONTENT\_BANWORD

**Message Meaning:** Web content banned word found

**Type:** Web

**Category:** CONTENT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64



Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12289 - LOG\_ID\_WEB\_CONTENT\_MMS\_BANWORD

**Message ID:** 12289

**Message Description:** LOG\_ID\_WEB\_CONTENT\_MMS\_BANWORD

**Message Meaning:** Web content MMS banned word found

**Type:** Web

**Category:** CONTENT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12290 - LOG\_ID\_WEB\_CONTENT\_EXEMPTWORD

**Message ID:** 12290

**Message Description:** LOG\_ID\_WEB\_CONTENT\_EXEMPTWORD

**Message Meaning:** Web content exempt word found

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12291 - LOG\_ID\_WEB\_CONTENT\_MMS\_EXEMPTWORD

**Message ID:** 12291

**Message Description:** LOG\_ID\_WEB\_CONTENT\_MMS\_EXEMPTWORD

**Message Meaning:** Web content MMS exempt word found

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12292 - LOG\_ID\_WEB\_CONTENT\_KEYWORD

**Message ID:** 12292

**Message Description:** LOG\_ID\_WEB\_CONTENT\_KEYWORD

**Message Meaning:** Message contained a key word in the profile list

**Type:** Web

**Category:** CONTENT

**Severity:** Notice



Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12293 - LOG\_ID\_WEB\_CONTENT\_SEARCH

**Message ID:** 12293

**Message Description:** LOG\_ID\_WEB\_CONTENT\_SEARCH

**Message Meaning:** Search phrase detected

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12305 - LOG\_ID\_WEB\_CONTENT\_MMS\_BANWORD\_NOTIF

**Message ID:** 12305

**Message Description:** LOG\_ID\_WEB\_CONTENT\_MMS\_BANWORD\_NOTIF

**Message Meaning:** Web content MMS banned word

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12544 - LOG\_ID\_URL\_FILTER\_BLOCK

**Message ID:** 12544

**Message Description:** LOG\_ID\_URL\_FILTER\_BLOCK

**Message Meaning:** URL address was blocked because it was found in the URL filter list

**Type:** Web

**Category:** URLFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urfilteridx	URL filter ID	uint32	10
urfilterlist	URL filter list	string	64
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12545 - LOG\_ID\_URL\_FILTER\_EXEMPT

**Message ID:** 12545

**Message Description:** LOG\_ID\_URL\_FILTER\_EXEMPT

**Message Meaning:** URL address was exempted because it was found in the URL filter list

**Type:** Web

**Category:** URLFILTER

**Severity:** Information



Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12546 - LOG\_ID\_URL\_FILTER\_ALLOW

**Message ID:** 12546

**Message Description:** LOG\_ID\_URL\_FILTER\_ALLOW

**Message Meaning:** URL address was allowed because it was found in the URL filter list

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12547 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTP\_BLK

**Message ID:** 12547

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTP\_BLK

**Message Meaning:** The request contained an invalid domain name

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12548 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTPS\_BLK

**Message ID:** 12548

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTPS\_BLK

**Message Meaning:** HTTP certificate request contained an invalid domain name

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12549 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTP\_PASS

**Message ID:** 12549

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTP\_PASS

**Message Meaning:** HTTP request contained an invalid name so the session has been filtered by IP only

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10



Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12550 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTPS\_PASS

**Message ID:** 12550

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTPS\_PASS

**Message Meaning:** HTTPS request contained an invalid name so the session has been filtered by IP only

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

**12551 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_SNI\_BLK****Message ID:** 12551**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_SNI\_BLK**Message Meaning:** Insufficient resources**Type:** Web**Category:** URLFILTER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12552 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_SNI\_PASS

**Message ID:** 12552

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_SNI\_PASS

**Message Meaning:** Getting the host name failed

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12553 - LOG\_ID\_URL\_FILTER\_INVALID\_CERT

**Message ID:** 12553

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_CERT

**Message Meaning:** Server certificate validation failed

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5



Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12554 - LOG\_ID\_URL\_FILTER\_INVALID\_SESSION

**Message ID:** 12554

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_SESSION

**Message Meaning:** SSL session blocked because its identification number was unknown

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12555 - LOG\_ID\_URL\_FILTER\_SRV\_CERT\_ERR\_BLK

**Message ID:** 12555

**Message Description:** LOG\_ID\_URL\_FILTER\_SRV\_CERT\_ERR\_BLK

**Message Meaning:** SSL session blocked

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

**12556 - LOG\_ID\_URL\_FILTER\_SRV\_CERT\_ERR\_PASS****Message ID:** 12556**Message Description:** LOG\_ID\_URL\_FILTER\_SRV\_CERT\_ERR\_PASS**Message Meaning:** SSL session ignored**Type:** Web**Category:** URLFILTER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12557 - LOG\_ID\_URL\_FILTER\_FAMS\_NOT\_ACTIVE

**Message ID:** 12557

**Message Description:** LOG\_ID\_URL\_FILTER\_FAMS\_NOT\_ACTIVE

**Message Meaning:** The FortiGuard Analysis and Management Service is not active. You must enable this service

**Type:** Web

**Category:** URLFILTER

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
eventtime		uint64	20
eventtype	Web Filter event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
tz		string	5
vd	Virtual domain name	string	32

## 12558 - LOG\_ID\_URL\_FILTER\_RATING\_ERR

**Message ID:** 12558

**Message Description:** LOG\_ID\_URL\_FILTER\_RATING\_ERR

**Message Meaning:** Rating error occurred

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
srcdomain		string	255
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urltype	URL filter type	string	8
user	User name	string	256
vd	Virtual domain name	string	32

## 12559 - LOG\_ID\_URL\_FILTER\_PASS

**Message ID:** 12559

**Message Description:** LOG\_ID\_URL\_FILTER\_PASS

**Message Meaning:** URL passed because it was in the URL filter list

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11



Log Field Name	Description	Data Type	Length
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urfilteridx	URL filter ID	uint32	10
urfilterlist	URL filter list	string	64
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12560 - LOG\_ID\_URL\_WISP\_BLOCK

**Message ID:** 12560

**Message Description:** LOG\_ID\_URL\_WISP\_BLOCK

**Message Meaning:** URL blocked by Websense service

**Type:** Web

**Category:** URLFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11

Log Field Name	Description	Data Type	Length
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12561 - LOG\_ID\_URL\_WISP\_REDIR

**Message ID:** 12561

**Message Description:** LOG\_ID\_URL\_WISP\_REDIR

**Message Meaning:** URL blocked with redirect message by Websense service

**Type:** Web

**Category:** URLFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12562 - LOG\_ID\_URL\_WISP\_ALLOW

**Message ID:** 12562

**Message Description:** LOG\_ID\_URL\_WISP\_ALLOW

**Message Meaning:** URL allowed by Websense service

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12688 - LOG\_ID\_WEB\_SSL\_EXEMPT

**Message ID:** 12688

**Message Description:** LOG\_ID\_WEB\_SSL\_EXEMPT

**Message Meaning:** URL address was exempted because it was found in the ssl-exempt

**Type:** Web

**Category:** SSL-EXEMPT

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	11
authserver		string	32
cat		uint8	3
catdesc		string	64
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32



Log Field Name	Description	Data Type	Length
fctuid		string	32
forwardedfor		string	128
group		string	64
hostname		string	256
initiator		string	64
level		string	11
logid		string	10
method		string	6
msg		string	512
policyid		uint32	10
profile		string	64
proto		uint8	3
quotamax		uint64	20
quotatype		string	16
quotaused		uint64	20
rawdata		string	20480
rcvdbyte		uint64	20
referralurl		string	512
reqtype		string	8
sentbyte		uint64	20
service		string	36
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39

Log Field Name	Description	Data Type	Length
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
urlsource		string	64
user		string	256
vd		string	32
vrf		uint8	3

## 12800 - LOG\_ID\_WEB\_FTGD\_ERR

**Message ID:** 12800

**Message Description:** LOG\_ID\_WEB\_FTGD\_ERR

**Message Meaning:** Rating error occurred (error)

**Type:** Web

**Category:** FTGD\_ERR

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
error	URL rating error message	string	256
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12801 - LOG\_ID\_WEB\_FTGD\_WARNING

**Message ID:** 12801

**Message Description:** LOG\_ID\_WEB\_FTGD\_WARNING

**Message Meaning:** Rating error occurred (warning)

**Type:** Web

**Category:** FTGD\_ERR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12802 - LOG\_ID\_WEB\_FTGD\_QUOTA

**Message ID:** 12802

**Message Description:** LOG\_ID\_WEB\_FTGD\_QUOTA

**Message Meaning:** Daily FortiGuard quota status

**Type:** Web

**Category:** FTGD\_QUOTA

**Severity:** Information

Log Field Name	Description	Data Type	Length
catdesc	Web category description	string	64
date	Date	string	10
devid		string	16
eventtime		uint64	20
eventtype	Web Filter event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
profile	Web Filter profile name	string	64
quotaexceeded	Quota has been exceeded	string	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
user	User name	string	256
vd	Virtual domain name	string	32

## 13056 - LOG\_ID\_WEB\_FTGD\_CAT\_BLK

**Message ID:** 13056

**Message Description:** LOG\_ID\_WEB\_FTGD\_CAT\_BLK

**Message Meaning:** URL belongs to an blocked category within the firewall policy

**Type:** Web

**Category:** FTGD\_BLK

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax		uint64	20
quotatype		string	16
quotaused		uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5



Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13057 - LOG\_ID\_WEB\_FTGD\_CAT\_WARN

**Message ID:** 13057

**Message Description:** LOG\_ID\_WEB\_FTGD\_CAT\_WARN

**Message Meaning:** URL belongs to a category with warnings enabled

**Type:** Web

**Category:** FTGD\_BLK

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax		uint64	20
quotatype		string	16
quotaused		uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13312 - LOG\_ID\_WEB\_FTGD\_CAT\_ALLOW

**Message ID:** 13312

**Message Description:** LOG\_ID\_WEB\_FTGD\_CAT\_ALLOW

**Message Meaning:** URL belongs to an allowed category within the firewall policy

**Type:** Web

**Category:** FTGD\_ALLOW

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax		uint64	20
quotatype		string	16
quotaused		uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13315 - LOG\_ID\_WEB\_FTGD\_QUOTA\_COUNTING

**Message ID:** 13315

**Message Description:** LOG\_ID\_WEB\_FTGD\_QUOTA\_COUNTING

**Message Meaning:** FortiGuard web filter category quota counting log message

**Type:** Web

**Category:** FTGD\_QUOTA\_COUNTING

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13316 - LOG\_ID\_WEB\_FTGD\_QUOTA\_EXPIRED

**Message ID:** 13316

**Message Description:** LOG\_ID\_WEB\_FTGD\_QUOTA\_EXPIRED

**Message Meaning:** FortiGuard web filter category quota expired log message

**Type:** Web

**Category:** URLFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11

Log Field Name	Description	Data Type	Length
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16



Log Field Name	Description	Data Type	Length
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13317 - LOG\_ID\_WEB\_URL

**Message ID:** 13317

**Message Description:** LOG\_ID\_WEB\_URL

**Message Meaning:** URL has been visited

**Type:** Web

**Category:** URLFILTER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20

Log Field Name	Description	Data Type	Length
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13568 - LOG\_ID\_WEB\_SCRIPTFILTER\_ACTIVEX

**Message ID:** 13568

**Message Description:** LOG\_ID\_WEB\_SCRIPTFILTER\_ACTIVEX

**Message Meaning:** ActiveX script removed

**Type:** Web**Category:** ACTIVEXFILTER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype		string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13573 - LOG\_ID\_WEB\_SCRIPTFILTER\_COOKIE

**Message ID:** 13573

**Message Description:** LOG\_ID\_WEB\_SCRIPTFILTER\_COOKIE

**Message Meaning:** Cookie removed

**Type:** Web

**Category:** COOKIEFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13584 - LOG\_ID\_WEB\_SCRIPTFILTER\_APPLET

**Message ID:** 13584

**Message Description:** LOG\_ID\_WEB\_SCRIPTFILTER\_APPLET

**Message Meaning:** Java applet removed

**Type:** Web

**Category:** APPLETFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype		string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36



Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13600 - LOG\_ID\_WEB\_SCRIPTFILTER\_OTHER

**Message ID:** 13600

**Message Description:** LOG\_ID\_WEB\_SCRIPTFILTER\_OTHER

**Message Meaning:** Script entity removed

**Type:** Web

**Category:** SCRIPTFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13601 - LOG\_ID\_WEB\_WF\_COOKIE

**Message ID:** 13601

**Message Description:** LOG\_ID\_WEB\_WF\_COOKIE

**Message Meaning:** Cookie removed entirely

**Type:** Web

**Category:** COOKIEFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13602 - LOG\_ID\_WEB\_WF\_REFERER

**Message ID:** 13602

**Message Description:** LOG\_ID\_WEB\_WF\_REFERER

**Message Meaning:** Referrer removed from request

**Type:** Web

**Category:** COOKIEFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13603 - LOG\_ID\_WEB\_WF\_COMMAND\_BLOCK

**Message ID:** 13603

**Message Description:** LOG\_ID\_WEB\_WF\_COMMAND\_BLOCK

**Message Meaning:** Command blocked

**Type:** Web

**Category:** WEBFILTER\_COMMAND\_BLOCK

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction		string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte		uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5



Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url		string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13616 - LOG\_ID\_CONTENT\_TYPE\_BLOCK

**Message ID:** 13616

**Message Description:** LOG\_ID\_CONTENT\_TYPE\_BLOCK

**Message Meaning:** Blocked by HTTP header content type

**Type:** Web

**Category:** CONTENT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512

Log Field Name	Description	Data Type	Length
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13632 - LOGID\_HTTP\_HDR\_CHG\_REQ

**Message ID:** 13632

**Message Description:** LOGID\_HTTP\_HDR\_CHG\_REQ

**Message Meaning:** Depends on info in msg field

**Type:** Web

**Category:** HTTP\_HEADER\_CHANGE

**Severity:** Information

Log Field Name	Description	Data Type	Length
agent		string	64
authserver		string	32
chgheaders		string	20480
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
group		string	64

Log Field Name	Description	Data Type	Length
level		string	11
logid		string	10
policyid		uint32	10
profile		string	64
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
transid		uint32	10
type		string	16
tz		string	5
url		string	512
user		string	256
vd		string	32

## 13633 - LOGID\_HTTP\_HDR\_CHG\_RESP

**Message ID:** 13633

**Message Description:** LOGID\_HTTP\_HDR\_CHG\_RESP

**Message Meaning:** Depends on info in msg field

**Type:** Web

**Category:** HTTP\_HEADER\_CHANGE

**Severity:** Information

Log Field Name	Description	Data Type	Length
agent		string	64
authserver		string	32

Log Field Name	Description	Data Type	Length
chgheaders		string	20480
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	64
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
transid		uint32	10
type		string	16
tz		string	5
url		string	512
user		string	256
vd		string	32



**FORTINET®**



Copyright© 2019 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. In no event does Fortinet make any commitment related to future deliverables, features or development, and circumstances may change such that any forward-looking statements herein are not accurate. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.