



CLI Reference

FortiBranchSASE 7.6.2



FORTINET DOCUMENT LIBRARY

<https://docs.fortinet.com>

FORTINET VIDEO LIBRARY

<https://video.fortinet.com>

FORTINET BLOG

<https://blog.fortinet.com>

CUSTOMER SERVICE & SUPPORT

<https://support.fortinet.com>

FORTINET TRAINING & CERTIFICATION PROGRAM

<https://www.fortinet.com/training-certification>

FORTINET TRAINING INSTITUTE

<https://training.fortinet.com>

FORTIGUARD LABS

<https://www.fortiguard.com>

END USER LICENSE AGREEMENT

<https://www.fortinet.com/doc/legal/EULA.pdf>

FEEDBACK

Email: techdoc@fortinet.com



Jun 23, 2025

FortiBranchSASE 7.6.2 CLI Reference

TABLE OF CONTENTS

Change Log	6
Introduction	7
Connect to the CLI	7
Console connection	7
SSH access	8
Enable SSH access to the CLI using a local console connection:	9
Access the FortiBranchSASE CLI using SSH	9
Header	11
config version	11
Firewall	12
config policy	12
config traffic-shaper	16
config shaping-policy	16
config vip	18
Router	20
config router policy	20
config static	22
config target	23
config multicast	24
config pim-sm-global	24
config rp-address	24
config interface	25
config OSPF	26
config area	27
config network	28
config ospf-interface	29
config redistribute	30
config prefix-list	31
config rule	31
config route-map	32
config rule	32
System	34
config system global	34
config system accprofile	35
config admin	38
config system bluetooth	41
config management	42
config fortigate	42
config cloud	43
config local	44
config local-access	45
config fortigate-backup	45

config interface	47
config VRRP	51
config vxlan	52
config aggregate-interface	53
config pppoe-interface	55
config dhcpserver	56
config reserved-addresses	56
config dhcprelay	59
config dns	60
config dns-server	62
config dns-database	63
config dns-entry	64
config vwan-member	66
config syslog	68
config remote-servers	69
config statistic-report	70
config api-user	72
config ntp	73
config ntpserver	73
config settings	74
config system switch-interface	74
config ssh-crypto	76
config system 802-1X-settings	79
SNMP	80
config sysinfo	80
config community	80
config user	83
config hosts	84
HMON	87
config interface-monitoring	87
config hchk	87
VPN	91
config ipsec	91
config phase1-interface	91
config phase2-interface	95
config vpn certificate	98
config vpn certificate ca	98
config vpn certificate local	99
Network	101
config address	101
config service	102
config service-custom	102
Execute	104
execute SSH username serverip	104
execute vpn certificate local generate rsa	104

WiFi	106
config vap	106
config ap-security	108
config wifi-networks	109
config radio-profile	110
config wifi-general	111
User	112
config user radius	112
config user group	113

Change Log

Date	Change Description
2025-06-23	Initial release.

Introduction



FortiBranchSASE is a member of the FortiExtender product family. While FortiExtender and FortiBranchSASE share many features, this guide provides information specific to FortiBranchSASE

This *Reference Guide* introduces the syntax of commonly used CLI commands to configure and manage a FortiBranchSASE unit.

CLI commands in this *Reference Guide* are based on FortiBranchSASE-20G-WiFi.

Connect to the CLI

You can connect to the CLI through the FortiBranchSASE or FortiCloud GUI.

To access the FortiBranchSASE CLI via FortiCloud GUI, go to the device page of a deployed FortiBranchSASE device and click the `>_Console` section to open a new instance of the FortiBranchSASE console.

To access the FortiBranchSASE CLI via the FortiBranchSASE GUI, click the `>_` tab on the left side of the GUI.



You can open only one console per GUI access.

You can also access the FortiBranchSASE CLI outside of the GUI using:

- Console connection — connect your computer directly to the console port of your FortiBranchSASE.
- SSH or Telnet access — connect your computer through any network interface attached to one of the network ports of your FortiBranchSASE.

Console connection

You can directly connect to the CLI by connecting your management computer or console to the FortiBranchSASE through its RJ-45 console port.

Direct console access to a FortiBranchSASE device may be necessary if:

- You are installing the device for the first time, and it is not configured to connect to your network.
- You are restoring the firmware using a boot interruption. Network access to the CLI will not be available until after the boot process has completed, making direct console access the only option.

To connect to the FortiBranchSASE console, you need a console cable to connect the console port on the FortiBranchSASE to the communications port on a computer. Depending on your device, this may require:

- A USB to RJ-45 cable
- A DB-9 to RJ-45 cable (a DB-9-to-USB adapter may be used)
- A computer with an available communications port
- A terminal emulation software app

To connect to the CLI through a direct console connection:

1. Using the console cable, connect the FortiBranchSASE console port to the serial communications (COM) port on your management computer.
2. Start a terminal emulation program on your management computer, select the COM port, and set the Baud speed to 115200 Bits per second.
3. Press Enter on the keyboard to connect to the CLI.
4. Log into the CLI using your username and password ("admin" by default; you will be prompted to create a new password upon your first login).

You can now enter CLI commands, including configuring access to the CLI via SSH.

SSH access

You can establish SSH access to the CLI by connecting your computer to the FortiBranchSASE using one of its network ports, either directly using a peer connection between the two or through any intermediary network.

SSH must be enabled on the network interface that is associated with the physical network port that is being used.

If your computer is not connected either directly or through a switch to the FortiBranchSASE, you must also configure the FortiBranchSASE using a static route that can forward packets from the FortiBranchSASE to the computer. This can be done using a local console connection or in the GUI.

To connect to the FortiBranchSASE using SSH, you need:

- A computer with an available serial communications (COM) port and an RJ-45 port
- An appropriate console cable
- A network cable
- Terminal emulation software
- Prior configuration of the operating mode, network interface, and static route.

Enable SSH access to the CLI using a local console connection:

1. Using the network cable, connect the FortiBranchSASE network port either directly to the network port on your computer or to a network through which your computer can reach the FortiBranchSASE.
2. Note down the port number of the physical network port.
3. Using the direct console connection, connect and log into the CLI.
4. Enter the following command:

```
config system interface
  edit <interface_str>
    set allowaccess ssh
  next
end
```

where <interface_str> is the name of the network interface associated with the physical network port, such as port4.

5. Confirm the configuration using the following commands to show the interface settings, for example:

```
config system interface
edit port4
  set type physical
  set status up
  set mode static
  set ip
  set gateway
  set mtu-override disable
  set distance 51
  set vrrp-virtual-mac enable
  config vrrp
    set status disable
  end
  set allowaccess ssh
next
```

Access the FortiBranchSASE CLI using SSH

Once the FortiBranchSASE is configured to accept SSH connections, use an SSH client on your management computer to connect to the CLI.

The following instructions use PuTTY. The steps may vary in other terminal emulators.

To connect to the CLI using SSH:

1. On your management computer, start PuTTY.
2. In the Host Name (or IP address) field, enter the IP address of the FortiBranchSASE network interface that you are connected to and has SSH access enabled.

3. Set the port number to 22, if it is not automatically set.
4. Set the connection type to SSH.
5. Click *Open*.

The SSH client starts to connect to the FortiBranchSASE.



The SSH client may display a warning if this is the first time that you are connecting to the FortiBranchSASE and its SSH key is not yet recognized by the SSH client, or if you previously connected to the FortiBranchSASE using a different IP address or SSH key. This is normal if the management computer is directly connected to the FortiBranchSASE with no network hosts in between.

6. Click *Yes* to accept the FortiBranchSASE's SSH key.
The CLI will display the login prompt.
7. Enter the administrator account name, such as *admin*, and press *Enter*.
8. Enter the administrator account password and press *Enter*.
The CLI console shows the command prompt (the FortiBranchSASE hostname followed by #). You can now enter CLI commands.

Header

This section shows the syntax of the following command:

- [config version on page 11](#)

config version

Description: Configure header version settings.

```
config version
  set config {integer}
  set carrier {string}
  unset
  show
end
```

Sample command:

```
config header
  config version
    set config 10517384
    set certificate 3876258
  end
end
```

Parameter	Description	Type	Size	Default
config	Device configuration version.	integer	-	none
certificate	VPN certificate version.	integer	-	none

Firewall

This section shows the syntax of the following commands:

- [config policy on page 12](#)
- [config traffic-shaper on page 16](#)
- [config shaping-policy on page 16](#)
- [config vip on page 18](#)

config policy

Description: Configure firewall policies.

```
config policy
  edit <name>
    set *srcintf <name1>, <name2>, ...
    set *dstintf <name1>, <name2>, ...
    set *srcaddr <name1>, <name2>, ...
    set dnat [enable | disable]
    set *dstaddr <name1>, <name2>, ...
    set action [accept | deny]
    set status [enable | disable]
    set *service <name1>, <name2>, ...
    set nat [enable | disable]
  next
  delete <name>
  move <name1> [after | before] <name2>
  end
  purge
  show
```

Sample command:

```
config firewall policy
  edit test1
    set srcintf lo
    set dstintf any
    set srcaddr all
    set dnat disable
    set dstaddr all
    set action accept
    set status enable
    set service AH
    set nat enable
  next
```

```

edit test2
  set srcintf any
  set dstintf lan
  set srcaddr all
  set dnat disable
  set dstaddr all
  set action accept
  set status disable
  set service ALL
  set nat enable
next
edit all-pass
  set srcintf any
  set dstintf any
  set srcaddr all
  set dnat disable
  set dstaddr all
  set action accept
  set status enable
  set service ALL
  set nat enable
next
end

```

Parameter	Description	Type	Size	Default
srcintf	Incoming (ingress) interface.	option	-	none
	Option	Description		
	lan	LAN as the incoming interface.		
	lo	Loopback as the incoming interface.		
	port4	Port 4 as the incoming interface.		
	any	Any port as the incoming interface.		
dstintf	Outgoing (egress) interface.	option	-	none
	Option	Description		
	lan	LAN as the outgoing interface.		
	lo	Loopback as the outgoing interface.		
	port4	Port 4 as the outgoing interface.		
	any	Any port as the outgoing interface.		
srcaddr	Source address.	option	-	none

Parameter	Description	Type	Size	Default										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>all</td><td>All network addresses.</td></tr><tr><td>none</td><td>None of the network addresses.</td></tr><tr><td>lan-src</td><td>LAN network address.</td></tr><tr><td>wan-src</td><td>WAN network address.</td></tr></table>	Option	Description	all	All network addresses.	none	None of the network addresses.	lan-src	LAN network address.	wan-src	WAN network address.			
	Option	Description												
	all	All network addresses.												
	none	None of the network addresses.												
	lan-src	LAN network address.												
wan-src	WAN network address.													
dnat	Destination NAT.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable destination NAT.</td></tr><tr><td>disable</td><td>Disable destination NAT.</td></tr></table>	Option	Description	enable	Enable destination NAT.	disable	Disable destination NAT.							
	Option	Description												
	enable	Enable destination NAT.												
disable	Disable destination NAT.													
dstaddr	Destination address.	option	-	none										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>all</td><td>All network addresses.</td></tr><tr><td>none</td><td>None of the network addresses.</td></tr><tr><td>lan-src</td><td>LAN network address.</td></tr><tr><td>wan-src</td><td>WAN network address.</td></tr></table>	Option	Description	all	All network addresses.	none	None of the network addresses.	lan-src	LAN network address.	wan-src	WAN network address.			
	Option	Description												
	all	All network addresses.												
	none	None of the network addresses.												
	lan-src	LAN network address.												
wan-src	WAN network address.													
action	Policy action.	option	-	accept										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>accept</td><td>Accept policy.</td></tr><tr><td>deny</td><td>Deny policy.</td></tr></table>	Option	Description	accept	Accept policy.	deny	Deny policy.							
	Option	Description												
	accept	Accept policy.												
deny	Deny policy.													
status	Status of the policy.	option	-	enable										
	<table><tr><th>Option</th><th>Decription</th></tr><tr><td>enable</td><td>Enable this policy.</td></tr><tr><td>disable</td><td>Disable this policy.</td></tr></table>	Option	Decription	enable	Enable this policy.	disable	Disable this policy.							
	Option	Decription												
	enable	Enable this policy.												
disable	Disable this policy.													
service	Service/service group name.	option	-	none										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>ALL</td><td>All services.</td></tr><tr><td>HTTP</td><td>HTTP service.</td></tr><tr><td>etc</td><td>Refer to config network service list.</td></tr></table>	Option	Description	ALL	All services.	HTTP	HTTP service.	etc	Refer to config network service list.					
	Option	Description												
	ALL	All services.												
	HTTP	HTTP service.												
etc	Refer to config network service list.													

Parameter	Description	Type	Size	Default						
nat	Source NAT.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable source NAT.</td></tr><tr><td>disable</td><td>Disable source NAT.</td></tr></table>				Option	Description	enable	Enable source NAT.	disable	Disable source NAT.
	Option	Description								
	enable	Enable source NAT.								
disable	Disable source NAT.									

```

(policy) # move test2 after all-pass
(policy) <M> # show
config firewall policy
  edit test1
    set srcintf lo
    set dstintf any
    set srcaddr all
    set dnat disable
    set dstaddr all
    set action accept
    set status enable
    set service AH
    set nat enable
  next
  edit all-pass
    set srcintf any
    set dstintf any
    set srcaddr all
    set dnat disable
    set dstaddr all
    set action accept
    set status enable
    set service ALL
    set nat enable
  next
  edit test2
    set srcintf any
    set dstintf lan
    set srcaddr all
    set dnat disable
    set dstaddr all
    set action accept
    set status disable
    set service ALL
    set nat enable
  next
end

```

config traffic-shaper

Description: Configure firewall shapers.

```
config firewall shaper
  config traffic-shaper
    edit <name>
      set max-bandwidth (1 - 16776000)
      set *bandwidth-unit [kbps | mbps | gbps]
    delete <name>
  purge
  show
end
```

Sample command:

```
config firewall shaper traffic-shaper
  edit 1
    set max-bandwidth 34
    set bandwidth-unit kbps
  next
end
```

Parameter	Description	Type	Size	Default
max-bandwidth	Upper bandwidth limit enforced by the shaper.	integer	1 - 16776000	100
bandwidth-unit	Unit of measurement for guaranteed and maximum bandwidth for the shaper.	option	-	none
		Option	Description	
		kbps	Kilobits per second.	
		mbps	Megabits per second.	
		gbps	Gigabits per second.	

config shaping-policy

Description: Configure firewall shaping policies.

```
config shaping-policy
  edit <name>
    set status [enable | disable]
```



```

        set *dstintf <name1>, <name2>, ...
        set *traffic-shaper <name1>, <name2>, ...
    delete <name>
    purge
    show
end

```

Sample command:

```

config firewall shaping-policy
edit 1_policy
set status enable
set dstintf port1
set traffic-shaper 1
next
end

```

Parameter	Description	Type	Size	Default										
status	Status of the traffic shaping policy.	option	-	enable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable the policy.</td></tr><tr><td>disable</td><td>Disable the policy.</td></tr></table>	Option	Description	enable	Enable the policy.	disable	Disable the policy.							
Option	Description													
enable	Enable the policy.													
disable	Disable the policy.													
dstintf	Outgoing (egress) interface.	option	-	none										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>lan</td><td>LAN as the outgoing interface.</td></tr><tr><td>lo</td><td>Loopback as the outgoing interface.</td></tr><tr><td>port4</td><td>Port 4 as the outgoing interface.</td></tr><tr><td>any</td><td>Any port as the outgoing interface.</td></tr></table>	Option	Description	lan	LAN as the outgoing interface.	lo	Loopback as the outgoing interface.	port4	Port 4 as the outgoing interface.	any	Any port as the outgoing interface.			
Option	Description													
lan	LAN as the outgoing interface.													
lo	Loopback as the outgoing interface.													
port4	Port 4 as the outgoing interface.													
any	Any port as the outgoing interface.													
traffic-shaper	Traffic shaper to apply to traffic forwarded by the firewall policy.	option	-	none										
	<table><tr><th>Option</th><th>Decription</th></tr><tr><td>1</td><td>Refer toconfig traffic-shaper on page 16.</td></tr></table>	Option	Decription	1	Refer to config traffic-shaper on page 16 .									
Option	Decription													
1	Refer to config traffic-shaper on page 16 .													

config vip

Description: Configure firewall virtual IPs.

```
config vip
  edit <name>
    set comment [255]
    set *extip <name1>
    set *mappedip <name1>
    set *extintf <name1>, <name2>, ...
    set portforward [enable | disable]
    set *protocol <name1>, <name2>, ... *only accessible when portforward is enabled
    set *extport (1 - 65535) *only accessible when portforward is enabled
    set *mappedport (1 - 65535) *only accessible when portforward is enabled
    unset
    next
    show
    abort
    end
  delete <name >
  purge
  show
  end
```

Sample command:

```
config firewall vip
  edit 1
    set comment this is a test vip
    set extip 10.153.24.44
    set mappedip 10.153.24.36
    set extintf any
    set portforward enable
    set protocol tcp
    set extport 25
    set mappedport 33
  next
end
```

Parameter	Description	Type	Size	Default
comment	Optional comments.	string	Up to 255 characters in length	none
extip	IP address on the external interface to be mapped to an address on the destination network.	IPv4 address	-	none
mappedip	IP address on the destination	IPv4 address	-	none

Parameer	Description	Type	Size	Default										
	network to which the external IP address is mapped.													
extintf	Interface connected to the source network that receives packets to be forwarded to the destination network.	option	-	none										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>lan</td><td>LAN as the outgoing interface.</td></tr><tr><td>lo</td><td>Loopback as the outgoing interface.</td></tr><tr><td>port4</td><td>Port 4 as the outgoing interface.</td></tr><tr><td>any</td><td>Any port as the outgoing interface.</td></tr></table>	Option	Description	lan	LAN as the outgoing interface.	lo	Loopback as the outgoing interface.	port4	Port 4 as the outgoing interface.	any	Any port as the outgoing interface.			
Option	Description													
lan	LAN as the outgoing interface.													
lo	Loopback as the outgoing interface.													
port4	Port 4 as the outgoing interface.													
any	Any port as the outgoing interface.													
portforward	Port forwarding.	option	-	disable										
	<table><tr><th>Option</th><th>Decription</th></tr><tr><td>enable</td><td>Enable port forwarding.</td></tr><tr><td>disable</td><td>Disable port forwarding.</td></tr></table>	Option	Decription	enable	Enable port forwarding.	disable	Disable port forwarding.							
Option	Decription													
enable	Enable port forwarding.													
disable	Disable port forwarding.													
protocol	Protocol to use when forwarding packets.	option	-	tcp										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>tcp</td><td>TCP protocol.</td></tr><tr><td>udp</td><td>UDP Protocol.</td></tr><tr><td>icmp</td><td>ICMP protocol.</td></tr></table>	Option	Description	tcp	TCP protocol.	udp	UDP Protocol.	icmp	ICMP protocol.					
Option	Description													
tcp	TCP protocol.													
udp	UDP Protocol.													
icmp	ICMP protocol.													
extport	Incoming port number to be mapped to a port number on the destination network.	number	1 - 65535	0										
mappedport	Port number on the destination network to which the external port number is mapped.	number	1 - 65535	0										

Router

This section shows the syntax of the following commands:

- [config router policy on page 20](#)
- [config static on page 22](#)
- [config target on page 23](#)
- [config multicast on page 24](#)
- [config OSPF on page 26](#)
- [config prefix-list on page 31](#)
- [config route-map on page 32](#)

config router policy

Description: Configure router policies.

```
config router policy
  edit <name>
    set input-device <name1>
    set srcaddr <name1>
    set dstaddr <name1>
    set service <name1>, <name2>, ...
    set *target <name1>
    set status [enable | disable]
    set comment {string}
    unset
    next
    show
    abort
    end
  delete <name>
  purge
  move <name1> [before | after] <name2>
  show
  end
```

Sample command:

```
config router policy
  edit 1
    set input-device lan
    set srcaddr all
    set dstaddr all
    set service ALL
```

```

    set target target.port1
    set status enable
    set comment this is a test policy
next
end

```

Parameter	Description	Type	Size	Default
input-device	Incoming interface name.	option	-	none
	Option	Description		
	lan	LAN as the input device.		
	lo	Loopback as the input device.		
	port4	Port 4 as the input device.		
	port1	Port 1 as the input device.		
srcaddr	Source address.	option	-	none
	Option	Description		
	lan	LAN network address.		
	all	All the network addresses.		
	none	None of the network addresses.		
dstaddr	destination address.	option	-	none
	Option	Description		
	lan	LAN network address.		
	all	All the network addresses.		
	none	None of the network addresses.		
service	Service/service group names.	option	-	none
	Option	Description		
	ALL_ICMP	ICMP.		
	ALL	All.		
	etc	Refer to the different services in this command.		
target	The PBR's out-going interface and next-hop.	option	-	none

Parameter	Description	Type	Size	Default										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>target.lan</td><td>LAN as the target.</td></tr><tr><td>target.lo</td><td>Loopback as the target.</td></tr><tr><td>target.port4</td><td>Port 4 as the target.</td></tr><tr><td>target.Port1</td><td>Port 1 as the target.</td></tr></table>	Option	Description	target.lan	LAN as the target.	target.lo	Loopback as the target.	target.port4	Port 4 as the target.	target.Port1	Port 1 as the target.			
	Option	Description												
	target.lan	LAN as the target.												
	target.lo	Loopback as the target.												
	target.port4	Port 4 as the target.												
target.Port1	Port 1 as the target.													
status	Status of the policy based the routing rule.	option	-	enable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable the policy.</td></tr><tr><td>disable</td><td>Disable the policy.</td></tr></table>	Option	Description	enable	Enable the policy.	disable	Disable the policy.							
	Option	Description												
	enable	Enable the policy.												
disable	Disable the policy.													
comment	Comment on the policy.	string	1 - 255 characters in length	none										

config static

Description: Configure static routes.

```

config static
  edit <name>
    set status [enable | disable]
    set dst {ipv4-address}
    set gateway {ipv4-address}
    set distance [1 - 255]
    set *device <name1>
    set comment {string}
    unset
    next
    show
    abort
  end
  delete <name>
  purge
  show

```

Sample command:

```

config router static
  edit 1
    set status enable

```

```

    set dst 10.124.23.0/24
    set gateway 192.168.200.99
    set distance 1
    set device port1
    set comment this is a sample static route
next
end

```

Parameter	Description	Type	Size	Default
status	Status of the static route.	option	-	enable
	Option	Description		
	enable	Enable static route.		
	disable	Disable static route.		
dst	Destination IP and mask for the route.	ipv4_address/netmask-	-	none
gateway	Gateway IP for the route.	ipv4_address	-	none
distance	Administrative distance. (This field is the metric of the route item. Set the value carefully and ensure that this route item matches your application scenario without affecting other route items.)	integer	1 - 255	1
device	Gateway outgoing interface or tunnel.	option	-	none
comment	Comment on the route. (Optional)	string	Up to 255 characters in length	none

config target

Description: Configure router targets.

```

config target
  edit <name>
    set *target <name1>
    set next-hop <name1>
    unset
    next
    show
    abort
  end
  delete <name>
purge

```

```
show
end
```

Sample command:

```
config router target
  edit target.lo
    set interface lo
    set next-hop
  next
```

Parameter	Description	Type	Size	Default
interface	Target interface.	option		none
	Option	Description		
	lan	LAN as the target interface.		
	lo	Loopback as the target interface.		
	port4	Port 4 as the target interface.		
	port1	Port 1 as the target interface.		
next-hop	Next-hop IP address in x.x.x.x format.	IPv4 address	-	none

config multicast

Description: Configure multicast router.

```
set join-prune-interval [1 - 65535]
set hello-interval [30 - 18724]
unset
```

- [config pim-sm-global on page 24](#)
- [config rp-address on page 24](#)
- [config interface on page 25](#)

config pim-sm-global

Description: Configure PIM sparse-mode interfaces.

config rp-address

Description: Configure static RP addresses.


```
config rp-address
  edit <rpaddressip>
    set *address <name1>
    set group <name1> *specified IPv4 subnet should be within 224.0.0.0/4 but not within
      232.0.0.0/8
    unset
    next
    show
    abort
    end
  delete <rpaddressip>
  purge
  show
  end
show
end
```

config interface

Description: Configure Protocol Independent Multicast (PIM) interfaces.



Although "set" is an available option, there's no entry for the "set" command.

```
config interface
  edit <name> *must be valid interface id in system interface list
    next
    show
    abort
    end
  delete <name>
  purge
  show
  end
show
end
```

Sample command:

```
config router multicast
  config pim-sm-global
    set join-prune-interval 60
    set hello-interval 30
    config rp-address
      edit 1
        set address 192.168.200.23
        set group 224.0.0.0/4
      next
    end
  end
end
```

```

config interface
end
end

```

Parameter	Description	Type	Size	Default
join-prune-interval	Interval (in seconds) between sending PIM join/prune messages.	integer	1 - 65535	60
hello-interval	Interval (in seconds) between sending PIM hello messages.	integer	30 - 18724	30
address	RP router address.	IPv4 address	-	none
group	Groups to use this RP. (Note: The specified IPv4 subnet should be within 224.0.0.0/4, but not within 232.0.0.0/8.)	IPv4 address/netmask	-	224.0.0.0/4
interface	PIM interfaces.	string	-	none

config OSPF

Description: Configure OSPF settings.

```

config ospf
    set status [enable | disable]
    set router-id <name1>
unset

```

Sample command:

```

config router ospf
    set status enable
    set router-id 192.168.100.127

```

Parameter	Description	Type	Size	Default
status	Set the status of the OSPF:	option	-	disable
	Option	Description		
	enable	Enable OSPF		
	disable	Disable OSPF		

Parameter	Description	Type	Size	Default
set router-id	The router-id is a unique identity to the OSPF router. If no router-id is specified, the system will automatically choose the highest IP address as the router-id.	IPv4 address	-	0.0.0.0

- [config area on page 27](#)
- [config network on page 28](#)
- [config ospf-interface on page 29](#)
- [config redistribute on page 30](#)

config area

Description: Configure OSPF area settings.

```
config area
    edit {ipv4-address}
        set
        unset
        next
        show
        abort
        end
    delete {ipv4-address}
    purge
    show
    end
```

Sample command:

```
config router ospf
    config area
        edit 0.0.0.0
```

Parameter	Description	Type	Size	Default
config area	OSPF area configuration. An area is a logical grouping of contiguous networks and routers in the same area with the same link-state database and topology. Note: The current release only supports Area 0 called the backbone area, and does not support multiple areas. All routers inside an area must have the same area ID to become OSPF neighbors. You can add Area 0 by editing Area 0.0.0.0	IPv4 address	-	none

config network

Description: Configure OSPF network settings.

```
config network
  edit <name>
    set *prefix {integer}
    set *area <name1>
    unset
    next
    show
    abort
    end
  delete <name>
  purge
  show
  end
```

Sample command:

```
config router ospf
  config network
    edit 1
      set prefix 192.168.100.127/32
      set area 0.0.0.0
    next
    edit 2
      set prefix 192.168.100.0/30
      set area 0.0.0.0
    next
  end
```

Parameter	Description	Type	Size	Default
config network	OSPF network configuration.	option	-	none
	Option	Description		
	prefix	Prefix used to identify network/subnet address for advertising to the OSPF domain.		
	area	Attach the network to area.		

CLI Command	Description
<pre>config network edit [id] set prefix [X.X.X.X/Y] set area 0.0.0. Prefix</pre>	- id—string - X.X.X.X—Network prefix - Y—Netmask

config ospf-interface

Description: Configure OSPF interface settings.

```
config ospf-interface
  edit <name>
    set status [enable | disable]
    set *interface <name1>
    set mtu-ignore [enable | disable]
    set cost [0 - 65535]
    unset
    next
    show
    abort
  end
delete <name>
purge
show
end
```

Sample command:

```
config ospf-interface
  edit 1
    set status enable
    set interface opaq
    set mtu-ignore enable
    set cost 5
  end
```

Parameter	Description	Type	Size	Default						
config ospf-interface	OSPF interface configuration.	option	-	none						
status	Enable/Disable OSPF processing on the said interface.	option		-						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable OSPF processing on the said interface.</td></tr><tr><td>disable</td><td>Disable OSPF processing on the said interface.</td></tr></table>				Option	Description	enable	Enable OSPF processing on the said interface.	disable	Disable OSPF processing on the said interface.
	Option	Description								
	enable	Enable OSPF processing on the said interface.								
disable	Disable OSPF processing on the said interface.									
set interface	Must be the VPN tunnel interface as OSPF is built over IPSEC VPN.									
set mtu-ignore	Prevents OSPF neighbor adjacency failure caused by mismatched MTUs.									
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>OSPF will stop detecting mismatched MTUs before</td></tr></table>				Option	Description	enable	OSPF will stop detecting mismatched MTUs before		
	Option	Description								
enable	OSPF will stop detecting mismatched MTUs before									

Parameter	Description	Type	Size	Default
	Option	Description		
		forming OSPF adjacency		
	disable	OSPF will detect mismatched MTUs, and OSPF adjacency is not established if MTU is mismatched.		
set cost	Interface cost used to calculate the best path to reach other routers in the same area. 0 means auto-cost.	integer	0—65535	

config redistribute

Description: Configure redistribute settings.

```
config router ospf
  config redistribute
    config [connected | static]
      set status [enable | disable]
      set metric-type [1 | 2]
      set metric <value>
      set route-map <route-map name>
```

Sample command:

```
config router ospf
  config redistribute
    config connected
      set status enable
      set metric-type 2
      set metric 10
      set routemap redist-local-connected
    end
    config static
      set status enable
      set metric-type 2
      set metric 10
      set routemap redist-static
    end
```

Parameter	Description	Type	Size	Default
status	Enable/disable redistributing routes.			
set metric-type	Specify the external link type to be used for the redistributed routes. The options are E1 and E2 (default).			E2

Parameter	Description	Type	Size	Default
set metric	Used for the redistributed routes.	integer	1 - 16777214	10
set routemap	Route map name.			

config prefix-list

Description: Configure IPv4 prefix lists.

```
edit <name>
  set
  unset
```



The "set" command is available, but there are no settings to "set" or "unset".

- [config rule on page 31](#)

config rule

Description: Configure IPv4 prefix list rule.

```
config prefix-list
  config rule
    edit <name>
      set action [permit | deny]
      set *prefix {ipv4-subnet}
      set ge (0 - 32)
      set le (0 - 32)
      unset
      next
      show
      abort
      end
    delete <name>
    purge
    show
    end
  next
  show
  abort
  end
delete <name>
purge
show
end
```

Sample command:

```

config router prefix-list
  edit 1
    config rule
      edit 1
        set action permit
        set prefix 192.168.200.0/24
        set ge 25
        set le 25
      next
    end
  next
end

```

Parameter	Description	Type	Size	Default
action	Action of the rule.	option	-	permit
	Option	Description		
	permit	Allow packets that match this rule.		
	deny	Deny packets that match this rule.		
prefix	IPv4 prefix to define the regular filter criteria.	IPv4 address/netmask	-	none
ge	Minimum prefix length to be matched.	integer	0 - 32	none
le	Maximum prefix length to be matched.	integer	0 - 32	none

config route-map

Description: Configure route maps.

```

edit <name>
  set
  unset

```

- [config rule on page 32](#)

config rule

Description: Configure route map rule.

```

config rule
  edit <name>

```



```

        set action [permit | deny]
        set match-ip-address {ipv4-address}
        unset
        next
        show
        abort
        end
    delete <name>
    purge
    show
    end
delete <name>
purge
show
end
show
end

```

Sample command:

```

config router route-map
  edit 1
    config rule
      edit 1
        set action permit
        set match-ip-address 1
      next
    end
  next
end

```

Parameter	Description	Type	Size	Default
action	Action of the rule.	option	-	permit
	Option	Description		
	permit	Allow packets that match this rule.		
	deny	Deny packets that match this rule.		
match-ip-address	Match IP address permitted by the prefix-list.	string	-	none

System

This section shows the syntax of the following commands:

- [config system global on page 34](#)
- [config system accprofile on page 35](#)
- [config admin on page 38](#)
- [config system bluetooth on page 41](#)
- [config management on page 42](#)
- [config interface on page 47](#)
- [config dhcpserver on page 56](#)
- [config dhcprelay on page 59](#)
- [config dns on page 60](#)
- [config dns-server on page 62](#)
- [config dns-database on page 63](#)
- [config dns-entry on page 64](#)
- [config vwan-member on page 66](#)
- [config syslog on page 68](#)
- [config api-user on page 72](#)
- [config ntp on page 73](#)
- [config settings on page 74](#)
- [config system switch-interface on page 74](#)
- [config ssh-crypto on page 76](#)
- [config system 802-1X-settings on page 79](#)

config system global

Description: Configure FortiBranchSASE global settings.

```
config system global
  set hostname {string}
  set timezone [0 - 87]
  set auto-install-image [enable | disable]
  set default-image-file {string} *available when auto-install-image is enabled
  set mdm-fw-server {string}
  set os-fw-server {string}
  set admin-server-cert {string}
end
```

Sample command:

```
config system global
  set hostname BS20GWS224000007
  set timezone 80
  set auto-install-image disable
  set mdm-fw-server Fortiextender-firmware.forticloud.com
  set os-fw-server Fortiextender-firmware.forticloud.com
  set admin-server-cert my_fex_cert
end
```

Parameter	Description	Type	Size	Default						
hostname	Device display name.	string	-	none						
timezone	System timezone setting. (Note: Use the 'get timezone list' command to check the timezone ID.)	integer	0 - 87	80						
auto-install-image	Automatically install image from USB.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable auto-install-image.</td></tr><tr><td>disable</td><td>Disable auto-install-image.</td></tr></table>				Option	Description	enable	Enable auto-install-image.	disable	Disable auto-install-image.
Option	Description									
enable	Enable auto-install-image.									
disable	Disable auto-install-image.									
default-image-file	Image file from USB.	string	-	none						
mdm-fw-server	Cloud modem image upgrade URL.	string	-	Fortiextender-firmware.forticloud.com						
os-fw-server	Cloud OS image upgrade URL.	string	-	Fortiextender-firmware.forticloud.com						
admin-server-cert	Server certificate that the FortiBranchSASE uses for HTTPS administrative connections.	string	-	Fortinet_Factory_Backup						

config system accprofile

Description: Configure administration access profiles.

```
config system accprofile
  edit <name>
```

```

set header [read-write | read | no-access]
set firewall [read-write | read | no-access]
set router [read-write | read | no-access]
set system [read-write | read | no-access]
set snmp [read-write | read | no-access]
set hmon [read-write | read | no-access]
set vpn [read-write | read | no-access]
set network [read-write | read | no-access]
set wifi [read-write | read | no-access]
set user [read-write | read | no-access]
unset
next
show
abort
end
delete <name>
purge
show
end

```

Sample command:

```

config system accprofile
edit some_access
    set header read-write
    set firewall read
    set router no-access
    set system read-write
    set snmp read
    set hmon read
    set vpn no-access
    set network read
    set wifi read
    set user read-write
next

```

Parameter	Description	Type	Size	Default
header	Header settings.	option	-	read
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		
firewall	Firewall configuration.	option	-	read

Parameter	Description	Type	Size	Default
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		
router	Router configuration.	option	-	read
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		
system	System configuration.	option	-	read
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		
snmp	SNMP configuration.	option	-	read
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		
hmon	Health monitor configuration.	option	-	read
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		
vpn	VPN configuration.	option	-	read
	Option	Description		
	read-write	Read-write access.		

Parameter	Description	Type	Size	Default
	Option	Description		
	read	Read access.		
	no-access	No access.		
network	Network configuration.	option	-	read
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		
wifi	Wi-Fi configuration	option	-	read
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		
user	User configuration	option	-	read
	Option	Description		
	read-write	Read-write access.		
	read	Read access.		
	no-access	No access.		

config admin

Description: Configure user access.

```
config admin
edit <name>
  set *accprofile <name1>
  set remote-auth {enable | disable}
  set wildcard {enable | disable}
  set *password {string}
  set remote-group {group name}
  set trusthost1 {ipv4-address}
  set trusthost2 {ipv4-address}
  set trusthost3 {ipv4-address}
```

```

set trusthost4 {ipv4-address}
set trusthost5 {ipv4-address}
set trusthost6 {ipv4-address}
set trusthost7 {ipv4-address}
set trusthost8 {ipv4-address}
set trusthost9 {ipv4-address}
set trusthost10 {ipv4-address}
next
end

```

Sample command:

```

config system admin
edit remote1
set accprofile super_admin
set remote-auth enable
set wildcard enable
set password ENC *
set remote-group group1
set trusthost1 192.168.200.110/24
set trusthost2
set trusthost3
set trusthost4
set trusthost5
set trusthost6
set trusthost7
set trusthost8
set trusthost9
set trusthost10
next
end

```

Parameter	Description	Typy	Size	Default
accprofile	Access profile.	string	-	none
remote-auth	Enable/disable authentication using a remote RADIUS server	option	-	disable
wildcard	Enable/disable wildcard RADIUS authentication Note: If wildcard is enabled, the remote user can share the account and log in without needing to create multiple user accounts. That means, you can use the user and password pair stored in the remote server without needing to match the table name.	option	-	disable

Parameter	Description	Typy	Size	Default
	Only one wildcard remote account is allowed to exist under system admin.			
password	Admin user password Note: If wildcard is enabled, you cannot set a password.	string	-	none
remote-group	Enter the FortiBranchSASE user group name you want to use for remote authentication. Note: If remote-auth is enabled, remote-group becomes mandatory. Otherwise remote-group is hidden. If remote-auth is enabled but wildcard is disabled, you must set a local password. If the RADIUS server is unreachable, FortiBranchSASE uses the local password. For other situations, such as if FortiBranchSASE receives a RADIUS reject message, the local password is omitted.	option	-	none
trusthost1	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none
Trusthost2	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none
Trusthost3	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none
Trusthost4	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none
Trusthost5	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none
Trusthost6	Address or subnet address and	IPv4 address	-	none

Parameter	Description	Typy	Size	Default
	netmask from which the administrator can connect to the device.			
Trusthost7	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none
Trusthost8	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none
Trusthost9	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none
Trusthost10	Address or subnet address and netmask from which the administrator can connect to the device.	IPv4 address	-	none

config system bluetooth

Description: Configure Bluetooth settings on BLE capable models.

```
config system bluetooth
  set status {enable | disable}
end
```

Sample command:

```
config system bluetooth
  set status enable
end
```

Parameter	Description	Type	Size	Default
status	Enable or disable the Bluetooth button on applicable models.	option	-	enable

Parameter	Description	Type	Size	Default
	Option	Description		
	enable	Enable the Bluetooth button. The Bluetooth button can be triggered to provide Bluetooth functionality.		
	disable	Disable the Bluetooth button. Pressing the Bluetooth button will not trigger anything.		

config management

Description: Configure Extender management settings.

```
config management
  set discovery-type [auto | fortigate | cloud | local]
unset
```

Sample command

```
set discovery-type fortigate
```

Parameter	Description	Type	Size	Default
discovery-type	AC discovery type.	option	-	auto
	Option	Description		
	auto	Automatic.		
	fortigate	FortiGate.		
	cloud	FortiEdge Cloud.		
	local	Local.		

- [config fortigate on page 42](#)
- [config cloud on page 43](#)
- [config local on page 44](#)
- [config local-access on page 45](#)
- [config fortigate-backup on page 45](#)

config fortigate

Description: Configure FortiGate settings.

```

set ac-discovery-type [static | broadcast]
  config static-ac-addr *only accessible when ac-discovery-type is static
    edit <name>
      set server <name>
    next
  end
set ac-ctl-port [1024 - 49150]
set ac-data-port [1024 - 49150]
set discovery-intf <name1>
set ingress-intf <name1>
unset
show
end

```

Parameter	Description	Type	Size	Default
ac-discovery-type	The method that the device uses to discover the AC, i.e., FortiGate.	option	-	broadcast
	Option		Description	
	broadcast		Broadcast.	
	static		Static IP address.	
server	IP address or hostname of the AC server.	string	-	none
ac-ctl-port	CAPWAP control port of the AC server.	integer	1024 - 49150	5246
ac-data-port	CAPWAP data port of the AC server.	integer	1024 - 49150	5246
discovery-intf	The physical port from which FortiBranchSASE sends broadcast packets in search for FortiGate.	option	-	none
	Option		Description	
	lan		LAN as the discovery interface.	
	Port1		Port 1 as the discovery interface.	
	port2		Port 2 as the discovery interface.	

config cloud

Description: Configure Cloud settings.

```

config cloud
  set dispatcher {string}
  set dispatcher-port {integer}
  set mode [ip-passthrough | nat]
  set proxy [enable | disable]

```

```

set proxy-server {ipv4-address} *available when proxy is enabled
set proxy-port [1 - 65535] *available when proxy is enabled
unset
show
end

```

Parameter	Description	Type	Size	Default
dispatcher	Cloud dispatch URL.	string	-	Fortiextender-dispatch.forticloud.com
dispatcher-port	Cloud dispatch port.	integer	0 - 9223372036854775807	443
mode	Networking mode.	option	-	nat
	Option		Description	
	nat		NAT.	
	ip-passthrough		IP-passthrough.	
proxy	Status of proxy connection.	option	-	disable
	Option		Description	
	enable		Enable proxy.	
	disable		Disable proxy.	
proxy-server	Proxy server IP address.	IPv4 address	-	none
proxy-port	Socks5 proxy port.	integer	1 - 65535	1080

config local

Description: Configure local settings.

```

config local
set mode [ip-passthrough | nat]
unset
show
end

```

Parameter	Description	Type	Size	Default
mode	Networking mode.	option	-	nat
	Option	Decription		
	nat	NAT.		
	ip-passthrough	IP-passthrough.		

config local-access

Description: Configure administrative access settings.

```
config local-access
  set http [1 - 65535]
  set https [1 - 65535]
  set ssh [1 - 65535]
  set telnet [1 - 65535]
  set idle-timeout [1 - 480]
unset
show
end
```

Parameter	Description	Type	Size	Default
http	HTTP port number.	integer	1 - 65535	80
https	HTTPS port number.	integer	1 - 65535	443
ssh	SSH port number.	integer	1 - 65535	22
telnet	Telnet port number.	integer	1 - 65535	23
idle-timeout	The number of minutes before an idle administrator session times out.	integer	1 - 480	5

config fortigate-backup

Description: Configure backup feature.

```
config fortigate-backup
  set vrrp-interface <name1>
  set status [enable | disable]
unset
show
end
show
end
```

Parameter	Description	Type	Size	Default
vrrp-interface	VRRP interface.	option	-	none
		Option	Description	
		lan	LAN as vrrp-interface.	

Parameter	Description	Type	Size	Default
	Option	Description		
	lo	Loopback as vrrp-interface.		
	Port1	Port 1 as vrrp-interface.		
status	Status of the VRRP interface.	option	-	disable
	Option	Description		
	enable	Enable the VRRP interface.		
	disable	Disable the VRRP interface.		

Sample command:

```

config system management
  set discovery-type auto
  config fortigate
    set ac-discovery-type static
    edit 1
      set server 10.107.41.66
    next
  set ac-ctl-port 5246
  set ac-data-port 25246
  set discovery-intf lan
  set ingress-intf
end

config cloud
  set dispatcher fortiextender-dispatch.forticloud.com
  set dispatcher-port 443
  set mode nat
  set proxy enable
  set proxy-server 10.107.34.22
  set proxy-port 3453
end

config local
  set mode nat
end

config local-access
  set http 80
  set https 443
  set ssh 22
  set telnet 23
  set idle-timeout 5
end

```

```

config fortigate-backup
  set vrrp-interface port1
  set status enable
end
end

```

config interface

Description: Configure interface settings.

```

config interface
  edit <name>
    set *type [loopback | virtual-wan | vlan | capwap | dummy]
    set status [enable | disable]
    set mode [static | dhcp]
    set ip {ipv4-address}
    set gateway {ipv4-address}
  set mtu-override [enable | disable]
  set mtu [512-1500] *available when mtu-override is set to enable
  set distance [1 - 512]
  set vrrp-virtual-mac [enable | disable]
  set allowaccess <name1>, <name2>, ...
  set defaultgw [enable | disable] *available when mode is set to dhcp
  set dns-server-override [enable | disable] *available when mode is set to dhcp
  set redundant-by [priority | cost] *available when type is set to virtual-wan
  set algorithm [redundant | WRR] *available when type is set to virtual-wan
  set FEC [source_ip | dest_ip | source_dest_ip_pair | connection] *available
  when type is set to virtual-wan
  set session-timeout [0 - 86400] *available when type is set to virtual-wan
  set grace-period [0 - 10000000] *available when type is set to virtual-wan
  set members <name1>, <name2>, ...*available when type is set to virtual-wan
  set rid [1 | 2] *available when type is set to capwap
  set *vid [1 - 4089] *available when type is set to vlan
  set *ingress-intf <name1>
unset

```

Parameter	Description	Type	Size	Default
type	Interface type.	option	-	none
	Option	Description		
	loopback	Loopback interface.		
	virtual-wan	Virtual-WAN interface.		
	vlan	VLAN interface.		

Parameter	Description	Type	Size	Default
	Option	Description		
	capwap	CAPWAP interface.		
	dummy	Dummy interface.		
status	Interface status.	option	-	up
	Option	Description		
	up	Bring the interface up.		
	down	Bring the interface down.		
mode	Addressing mode.	option	-	static
	Option	Description		
	static	Static mode.		
	dhcp	DHCP mode.		
ip	Interface IP address and subnet mask (in x.x.x.x/24 format).	IPv4 address	-	none
gateway	Interface's connected gateway.	string	-	none
mtu-override	Status of MTU override.	option	-	disable
	Option	Description		
	enable	Enable MTU override.		
	disable	Disable MTU override.		
mtu	MTU value for the interface.	integer	512 - 1500	1500
distance	Route metric of the interface gateway.	integer	1 - 512	5
vrrp-virtual-mac	Use of virtual MAC for VRRP.	option	-	disable
	Option	Description		
	enable	Enable VRRP virtual MAC.		
	disable	Disable VRRP virtual MAC.		

Parameter	Description	Type	Size	Default										
allowaccess	Types of management access allowed to this interface.	string	-	none										
defaultgw	Ability to get the gateway IP from the DHCP server.	option	-	enable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable getting the gateway IP from the DHCP server.</td></tr><tr><td>disable</td><td>Disable getting the gateway IP from the DHCP server.</td></tr></table>	Option	Description	enable	Enable getting the gateway IP from the DHCP server.	disable	Disable getting the gateway IP from the DHCP server.							
Option	Description													
enable	Enable getting the gateway IP from the DHCP server.													
disable	Disable getting the gateway IP from the DHCP server.													
dns-server-override	Use DNS acquired by DHCP.	option	-	enable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable DNS server override.</td></tr><tr><td>disable</td><td>Disable DNS server override.</td></tr></table>	Option	Description	enable	Enable DNS server override.	disable	Disable DNS server override.							
Option	Description													
enable	Enable DNS server override.													
disable	Disable DNS server override.													
redundant-by	Use of the benchmark for redundant algorithm.	option	-	priority										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>priority</td><td>Redundant by priority.</td></tr><tr><td>cost</td><td>Redundant by cost.</td></tr></table>	Option	Description	priority	Redundant by priority.	cost	Redundant by cost.							
Option	Description													
priority	Redundant by priority.													
cost	Redundant by cost.													
algorithm	LLB algorithm.	option	-	redundant										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>redundant</td><td>Redundant as algorithm.</td></tr><tr><td>WRR</td><td>WRR as algorithm.</td></tr></table>	Option	Description	redundant	Redundant as algorithm.	WRR	WRR as algorithm.							
Option	Description													
redundant	Redundant as algorithm.													
WRR	WRR as algorithm.													
FEC	Forward equivalence class.	option	-	source_ip										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>source_ip</td><td>Forward equivalence class by source IP.</td></tr><tr><td>dest_ip</td><td>Forward equivalence class by destination IP.</td></tr><tr><td>source_dest_ip_pair</td><td>Forward equivalence class by source and destination IP pair.</td></tr><tr><td>connection</td><td>Forward equivalence class by connection.</td></tr></table>	Option	Description	source_ip	Forward equivalence class by source IP.	dest_ip	Forward equivalence class by destination IP.	source_dest_ip_pair	Forward equivalence class by source and destination IP pair.	connection	Forward equivalence class by connection.			
Option	Description													
source_ip	Forward equivalence class by source IP.													
dest_ip	Forward equivalence class by destination IP.													
source_dest_ip_pair	Forward equivalence class by source and destination IP pair.													
connection	Forward equivalence class by connection.													

Parameter	Description	Type	Size	Default								
session-timeout	FEC session timeout in seconds.	integer	0 - 86400	60								
grace-period	Grace period measured in seconds before failback.	integer	0 - 10000000	0								
members	Link members of virtual WAN.	option	-	none								
rid	CAPWAP virtual interface ID.	integer	1, 2	1								
vid	VLAN ID.	integer	1 - 4089	0								
ingress-intf	CAPWAP or VLAN interface's parent interface.	option	-	none								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>lan</td><td>LAN as the ingress interface.</td></tr><tr><td>lo</td><td>Loopback as the ingress interface.</td></tr><tr><td>port4</td><td>Port 4 as the ingress interface.</td></tr></table>				Option	Description	lan	LAN as the ingress interface.	lo	Loopback as the ingress interface.	port4	Port 4 as the ingress interface.
Option	Description											
lan	LAN as the ingress interface.											
lo	Loopback as the ingress interface.											
port4	Port 4 as the ingress interface.											
Sfp-dsl	sfp-dsl status	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable sfp-dsl.</td></tr><tr><td>disable</td><td>Disable sfp-dsl.</td></tr></table>				Option	Description	enable	Enable sfp-dsl.	disable	Disable sfp-dsl.		
Option	Description											
enable	Enable sfp-dsl.											
disable	Disable sfp-dsl.											
Autodect	Enable/disable sfp-dsl auto-detect.	option	-	enable								
Phy-mode	DSL physical mode.	option	-	vdsl								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>Vdsl</td><td></td></tr><tr><td>Adsl</td><td></td></tr></table>				Option	Description	Vdsl		Adsl			
Option	Description											
Vdsl												
Adsl												

- [config VRRP on page 51](#)
- [config vxlan on page 52](#)
- [config aggregate-interface on page 53](#)
- [config pppoe-interface on page 55](#)

config VRRP

Description: Configure the VRRP settings.

```
config vrrp
    set status [enable | disable]
    set version [2]
    set *ip {ipv4-address}
    set *id [1 - 255]
    set priority [1 - 255]
    set adv-interval [1 - 255]
    set start-time [1 - 255]
    set preempt [enable | disable]
    unset
    show
end
next
show
abort
end
delete <name>
purge
show
end
```

Sample command:

```
config system interface
    edit lan
        set type physical
        set status up
        set mode dhcp
        set mtu-override enable
        set mtu 1500
        set distance 5
        set vrrp-virtual-mac disable
        config vrrp
            set status enable
            set version 2
            set ip 192.168.100.25
            set id 5
            set priority 1
            set adv-interval 23
            set start-time 33
            set preempt enable
        end
        set allowaccess http https ping snmp ssh telnet
        set defaultgw enable
        set dns-server-override enable
    next
end
```

Parameter	Description	Type	Size	Default
status	Status of the VRRP configuration.	option	-	disable
	Option	Description		
	enable	Enable the VRRP configuration.		
	disable	Disable VRRP configuration.		
version	VRRP version.	integer	2	2
ip	IP address of the virtual router.	IPv4 address	-	none
id	ID of the virtual router.	integer	1 - 255	0
priority	Priority of the virtual router.	integer	1 - 255	100
adv-interval	Advertisement interval.	integer	1 - 255	1
start-time	Start-up time.	integer	1 - 255	1
preempt	Preempt mode.	option	-	disable
	Option	Description		
	enable	Enable preempt mode.		
	disable	Disable preempt mode.		

config vxlan

Description: Configure VXLAN devices

```

config vxlan
    edit <name>
        set *vni [1 - 16777215]
        set *remote-ip {ipv4-address}
        set *local-ip {ipv4-address}
        set dstport [1 - 65535]
        unset
        next
        show
        abort
    end
    delete <name>
    purge
    show
end

```

Sample command:

```

config system vxlan
  edit 1
    set vni 500
    set remote-ip 192.168.201.1
    set local-ip 192.168.200.1
    set dstport 4789
  next
end

```

Parameter	Description	Type	Size	Default
vni	VXLAN network ID.	integer	1 - 1677721	0
remote-ip	IPv4 address of the VXLAN interface on the device at the remote end of the VXLAN.	IPv4 address	-	none
local-ip	IPv4 address of the VXLAN interface on the device at the local end of the VXLAN.	IPv4 address	-	none
dstport	VXLAN destination port.	integer	1 - 65535	4789

config aggregate-interface

Description: Configure the aggregate interface.

```

config aggregate-interface
  edit <name>
    set mode [activebackup | loadbalance]
    set mapping-timeout [0 - 86400] *available when mode is set to load balance
  unset

```

config members

Description: Configure interfaces to be aggregated.

```

config members
  edit <name>
    set *interface <name1>
    set weight [1 - 256]
    set health-check-event
    set health-check-fail-cnt [1 - 10]
    set health-check-recovery-cnt [1 - 10]
    unset
  next
  show
  abort

```

```

        end
        delete <name>
        purge
        show
        end
    next
    show
    abort
    end
delete <name>
purge
show
end

```

Sample command:

```

config system aggregate-interface
  edit agg1
    set mode loadbalance
    set mapping-timeout 244
    config members
      edit 23
        set interface port4
        set weight 1
        set health-check-event
        set health-check-fail-cnt 5
        set health-check-recovery-cnt 5
      next
    end
  next
end

```

Parameter	Description	Type	Size	Default
mode	Aggregate interface mode.	option	-	activebackup
	Option		Description	
	activebackup		Active backup.	
	loadbalance		Load balance.	
mapping-timeout	source-mac-to-member mapping timeout in seconds.	integer	0 - 86400	60
interface	Member interface.	option	-	none
weight	Member weight in load balancing.	integer	1 - 256	1
health-check-event	Member monitor.	option	-	none

Parameter	Description	Type	Size	Default
health-check-fail-cnt	Number of failures before the member is considered dead.	integer	1 - 10	5
health-check-recovery-cnt	Number of successes before the member is considered alive.	integer	1 - 10	5

config pppoe-interface

Description: Configure the aggregate interface.

```
config pppoe-interface
edit <name>
    set status [up | down]
    set device <name1>
    set username {string}
    set password {string}
unset
```

Sample command:

```
config system pppoe-interface
edit pppoe1
    set status up
    set device port1
    set username test
    set password *****
next
end
```

Parameter	Description	Type	Size	Default
status	Bring the PPPoE up or down	option	-	up
	Option	Description		
	up	Set interface status up.		
	down	Set interface status down.		
device	Name of the physical interface	option	-	none
username	The ISP provided username of the PPPoE account.	string	-	none

Parameter	Description	Type	Size	Default
password	The PPPoE account's password.	string	-	none

config dhcpserver

Description: Configure DHCP servers.

```
config dhcpserver
    edit <name>
        set status [enable | disable]
        set lease-time [300 - 8640000]
        set dns-service [default | specify | wan-dns]
        set dns-server1 {ipv4-address} *available when dns-service is set to specify
        set dns-server2 {ipv4-address} *available when dns-service is set to specify
        set dns-server3 {ipv4-address} *available when dns-service is set to specify
        set ntp-service [specify]
        set ntp-server1 {ipv4-address}
        set ntp-server2 {ipv4-address}
        set ntp-server3 {ipv4-address}
        set *default-gateway {ipv4-address}
        set *netmask {netmask}
        set *interface <name1>
        set *start-ip {ipv4-address}
        set *end-ip {ipv4-address}
        set mtu [512 - 9000]
        set reserved-address [enable | disable]
    unset
```

config reserved-addresses

Description: Configure options for the DHCP server to assign IP settings to specific MAC addresses.

```
Config reserved-addresses
    edit <name>
        set *ip {ipv4-address}
        set *mac {mac-address}
        set *action [block | reserved]
        unset
        next
        show
        abort
        end
    delete <name>
    purge
    show
    end
next
show
end
```



```

delete <name>
purge
show
end

```

Sample command:

```

config system dhcpserver
edit 1
    set status enable
    set lease-time 86400
    set dns-service default
    set ntp-service specify
    set ntp-server1
    set ntp-server2
    set ntp-server3
    set default-gateway 192.168.200.99
    set netmask 255.255.255.0
    set interface port4
    set start-ip 192.168.200.110
    set end-ip 192.168.200.210
    set mtu 1500
    set reserved-address disable
next
end

```

Parameter	Description	Type	Size	Default
status	Status of the DHCP configuration.	option	-	enable
	Option Decripton			
	enable	Enable the DHCP server.		
	disable	Disable the DHCP server.		
lease-time	Lease time in seconds. 0 means unlimited.	integer	300 - 8640000	86400
dns-service	Options for assigning DNS servers to DHCP clients.	Option	-	default
	Option Description			
	default	Use the default DNS server.		
	specify	Specify the DNS server to be used.		
	wan-dns	Use the WAN port DNS server.		
dns-server1	DNS server 1.	IPv4 address	-	none
dns-server2	DNS server 2.	IPv4 address	-	none

Parameter	Description	Type	Size	Default										
dns-server3	DNS server 3.	IPv4 address	-	none										
ntp-service	Options for assigning Network Time Protocol (NTP) servers to DHCP clients.	option	-	specify										
ntp-server1	NTP server 1.	string	-	none										
ntp-server2	NTP server 2.	string	-	none										
ntp-server3	NTP server 3.	string	-	none										
default-gateway	Default gateway IP address assigned by the DHCP server.	IPv4 address	-	none										
netmask	Network mask assigned by the DHCP server.	string	-	none										
interface	DHCP server can assign IP configurations to clients connected to this interface.	option	-	none										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>lan</td><td>LAN as the DHCP server interface.</td></tr><tr><td>lo</td><td>Loopback as the DHCP server interface.</td></tr><tr><td>port1</td><td>Port 1 as the DHCP server interface.</td></tr><tr><td>port4</td><td>Port 4 as the DHCP server interface.</td></tr></table>				Option	Description	lan	LAN as the DHCP server interface.	lo	Loopback as the DHCP server interface.	port1	Port 1 as the DHCP server interface.	port4	Port 4 as the DHCP server interface.
Option	Description													
lan	LAN as the DHCP server interface.													
lo	Loopback as the DHCP server interface.													
port1	Port 1 as the DHCP server interface.													
port4	Port 4 as the DHCP server interface.													
start-ip	The first IP address in the IP range.	IPv4 address	-	none										
end-ip	The last IP address in the IP range.	IPv4 address	-	none										
mtu	Client's MTU.	integer	512 - 9000	1500										
reserved-address	Status of reserved address and MAC mapping.	Option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable reserved-address.</td></tr><tr><td>disable</td><td>Disable reserved-address.</td></tr></table>				Option	Description	enable	Enable reserved-address.	disable	Disable reserved-address.				
Option	Description													
enable	Enable reserved-address.													
disable	Disable reserved-address.													
ip	IP address to be reserved for the MAC address.	IPv4 address	-	none										
mac	MAC address of the client that will get the reserved IP address.	string	-	none										

Parameter	Description	Type	Size	Default
action	Options for the DHCP server to configure the client with the reserved MAC address.	option	-	reserved
	Option	Description		
	block	Block the address.		
	reserved	Reserve the address.		

config dhcprelay

Description: Configure DHCP relay.

```
config dhcprelay
  edit <name>
    set status [enable | disable]
    set *client-interfaces <name1>, <name2>, ...
    set *server-interface <name1>
    set *server-ip {ipv4-address}
    unset
    next
    show
    abort
  end
  delete <name>
  purge
  show
end
```

Sample command:

```
config system dhcprelay
  edit 1
    set status enable
    set client-interfaces lan
    set server-interface port4
    set server-ip 192.168.200.124
  next
end
```

Parameter	Description	Type	Size	Default
status	Status of the DHCP relay configuration.	option	-	enable

Parameter	Description	Type	Size	Default										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable DHCP relay.</td></tr><tr><td>disable</td><td>Disable DHCP relay</td></tr></table>	Option	Description	enable	Enable DHCP relay.	disable	Disable DHCP relay							
	Option	Description												
	enable	Enable DHCP relay.												
disable	Disable DHCP relay													
client-interfaces	The interfaces connected to DHCP clients.	option	-	none										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>lan</td><td>LAN as client interfaces.</td></tr><tr><td>lo</td><td>Loopback as client interfaces.</td></tr><tr><td>port1</td><td>Port 1 as client interfaces.</td></tr><tr><td>port4</td><td>Port 4 as client interfaces.</td></tr></table>	Option	Description	lan	LAN as client interfaces.	lo	Loopback as client interfaces.	port1	Port 1 as client interfaces.	port4	Port 4 as client interfaces.			
	Option	Description												
	lan	LAN as client interfaces.												
	lo	Loopback as client interfaces.												
	port1	Port 1 as client interfaces.												
port4	Port 4 as client interfaces.													
server-interface	The interface used to reach out to the DHCP server.	option	-	none										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>lan</td><td>LAN as client interfaces.</td></tr><tr><td>lo</td><td>Loopback as client interfaces.</td></tr><tr><td>port1</td><td>Port1 as client interfaces.</td></tr><tr><td>port4</td><td>Port 4 as client interfaces.</td></tr></table>	Option	Description	lan	LAN as client interfaces.	lo	Loopback as client interfaces.	port1	Port1 as client interfaces.	port4	Port 4 as client interfaces.			
	Option	Description												
	lan	LAN as client interfaces.												
	lo	Loopback as client interfaces.												
	port1	Port1 as client interfaces.												
port4	Port 4 as client interfaces.													
server-ip	IP address of the DHCP server.	IPv4 address	-	none										

config dns

Description: Configure DNS settings used to resolve domain names to IP addresses.

```

config dns
    set primary {ipv4-address}
    set secondary {ipv4-address}
    set timeout [1 - 10]
    set retry [0 - 5]
    set dns-cache-limit [0 - 4294967295]
    set dns-cache-ttl [60 - 86400]
    set cache-notfound-response [enable | disable]
    set source-ip {ipv4-address}
    set server-select-method [least-rtt | failover]
    unset
    show
end

```

Sample command:

```

config system dns
    set primary 208.91.112.53
    set secondary 208.91.112.52
    set timeout 5
    set retry 3
    set dns-cache-limit 5000
    set dns-cache-ttl 1800
    set cache-notfound-responses disable
    set source-ip 0.0.0.0
    set server-select-method least-rtt
end

```

Parameter	Description	Type	Size	Default						
primary	Primary DNS server IP address. The default is the FortiGuard primary DNS server IP.	IPv4 address	-	208.91.112.53						
secondary	Secondary DNS server IP address. The default is the FortiGuard secondary DNS server.	IPv4 address	-	208.91.112.52						
timeout	DNS query timeout interval in seconds.	integer	1 - 10	5						
retry	Number of times to retry.	integer	0 - 5	3						
dns-cache-limit	Maximum number of records in DNS cache.	integer	0 - 4294967295	5000						
dns-cache-ttl	Duration in seconds that DNS cache retains information.	integer	60 - 86400	1800						
cache-notfound-responses	Status of response from the DNS server when a record is not in cache.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable cache-notfound-responses.</td></tr><tr><td>disable</td><td>Disable cache-notfound-responses.</td></tr></table>				Option	Description	enable	Enable cache-notfound-responses.	disable	Disable cache-notfound-responses.
Option	Description									
enable	Enable cache-notfound-responses.									
disable	Disable cache-notfound-responses.									
source-ip	IP address used by the DNS server as its source IP.	IPv4 address	-	0.0.0.0						
server-select-method	The way in which configured servers are prioritized.	option	-	least-rtt						

Parameter	Description	Type	Size	Default
	Option	Description		
	least-rtt	least-rtt as server-select-method.		
	failover	failover as server-select-method.		

config dns-server

Description: Configure DNS servers.

```

config dns-server
  edit <name>
    set *interface <name1>
    set *mode [recursive | non-recursive | forward-only]
    unset
    next
    show
    abort
  end
delete <name>
purge
show
end

```

Sample command:

```

config system dns-server
  edit 1
    set interface lan
    set mode recursive
  next
end

```

Parameter	Description	Type	Size	Type	Size	Default
Name	Name of the DNS server.	string	1 - 35 characters in length			none
interface	A system interface enabled for DNS service.	option	-			none
mode	DNS server mode.	option	-			none

Parameter	Description	Type	Size	Default
	Option		Description	
	recursive		Shadow the DNS database and forward.	
	non-recursive		Public DNS database only.	
	forward-only		Forward only.	

config dns-database

Description: Configure DNS databases.

```

config dns-database
    edit <name>
        set status [enable | disable]
        set *domain {string}
        set type [primary]
        set view [shadow | public]
        set primary-name {string}
        set contact {string}
        set ttl [1 - 2147483647]
        set authoritative [enable | disable]
        set forwarder {ipv4-address}, {ipv4-address}, ...
        set source-ip {ipv4-address}
        config dns-entry {{{ see next for more info }}}
    unset

```

Parameter	Description	Type	Size	Default
name	Name of the DNS database.	string	-	none
status	Status of the DNS zone.	option	-	enable
	Option		Description	
	enable		Enable the DNS zone.	
	disable		Disable the DNS zone.	
domain	Domain zone name.	string	-	none
type	Zone type.	option	-	primary
view	Zone view to serve internal or public DNS clients.	option	-	shadow
	Option		Description	
	shadow		Shadow the DNS zone to serve internal clients.	

Parameter	Description	Type	Size	Default
	Option	Description		
	public	Public DNS zone to serve public clients.		
primary-name	Domain name of the default DNS server for the zone.	string	-	none
contact	Email address of the administrator of the zone. It could be a simple username or full email address.	string	-	host
ttl	Default time-to-live value (in seconds) for the entries of the DNS zone.	integer	1 - 2147483647	86400
authoritative	Status of the authoritative zone.	option	-	disable
	Option	Description		
	enable	Enable authoritative zone.		
	disable	Disable authoritative zone.		
forwarder	The list of DNS zone forwarder IP addresses, separate by white space.	IPv4 address	-	none
source-ip	Source IP for forwarding to the DNS server.	IPv4 address	-	none

config dns-entry

Description: Configure DNS entries.

```

config dns-entry
    edit <name>
        set status [enable | disable]
        set type [A | NS | CNAME | MX | PTR]
        set *hostname {string}
        set *ip {ipv4-address} *available when type is set to A or PTR
        set *canonical-name {string} *available when type is set to CNAME
        set preference [0 - 65535] *available when type is set to MX
        unset
        next
        show
        abort
    end
    delete <name>
    purge
    show
end

```


next

Sample command:

```

config system dns-database
  edit 1
    set status enable
    set domain example.com
    set type primary
    set view public
    set primary-name dns
    set contact host
    set ttl 86400
    set authoritative enable
    set forwarder 1.2.4.8 8.8.4.4
    set source-ip
  config dns-entry
    edit 1
      set status enable
      set type A
      set ttl 0
      set hostname host1
      set ip 172.30.145.225
    next
  end
next
end

```

Parameter	Description	Type	Size	Default
name	The DNS entry ID number.	integer	1 - 4294967295	none
status	The resource record status.	option	-	enable
	Option	Description		
	enable	Enable resource record.		
	disable	Disable resource record.		
type	Resource record type.	option	-	A
	Option	Description		
	A	Address record.		
	NS	Name server record.		
	CNAME	Canonical name record.		
	MX	Mail exchange record.		
	PTR	PTR resource record.		
ttl	The time-to-live value (in seconds)	integer	0 - 2147483647	0

Parameter	Description	Type	Size	Default
	for the entry.			
hostname	Name of the host.	string	-	none
ip	IP address of the host.	IPv4 address	-	none

config vwan-member

Description: Configure virtual VWAN interface members.

```

config vwan-member
  edit <name>
    set target <name1>
    set priority [1 - 7]
    set weight [1 - 256]
    set in-bandwidth-threshold [0 - 2147483647]
    set out-bandwidth-threshold [0 - 2147483647]
    set total-bandwidth-threshold [0 - 2147483647]
    set health-check <name1>
    set health-check-fail-threshold [1 - 10]
    set health-check-success-threshold [1 - 10]
    set link-cost-factor [latency | jitter | packet-loss]
    set latency-threshold [0 - 10000000, default = 5]
    set jitter-threshold [0 - 10000000, default = 5]
    set packetloss--threshold [0 - 100, default = 100]
    unset
    next
    show
    abort
    end
  delete <name>
  purge
  show
end

```

Sample command:

```

config system vwan-member
  edit mb1
    set target target.port1
    set priority 1
    set weight 1
    set in-bandwidth-threshold 0
    set out-bandwidth-threshold 0
    set total-bandwidth-threshold 0
    set health-check vw_mb1_hc
    set health-check-fail-threshold 5
    set health-check-success-threshold 5
    set link-cost-factor packet-loss latency jitter
    set latency-threshold 5
    set jitter-threshold 5
  end
end

```

```

    set packetloss-threshold 100
next
edit mb2
    set target target.port2
    set priority 10
    set weight 1
    set in-bandwidth-threshold 0
    set out-bandwidth-threshold 0
    set total-bandwidth-threshold 0
    set health-check vw_mb2_hc
    set health-check-fail-threshold 5
    set link-cost-factor packet-loss latency jitter
    set latency-threshold 5
    set jitter-threshold 5
    set packetloss-threshold 100

```

Parameter	Description	Type	Size	Default
target	Forwarding target.	string	-	none
priority	Priority of the member. The lower the value, the higher the priority.	integer	1 - 7	1
weight	Weight of the member.	integer	1 - 256	1
in-bandwidth-threshold	Bandwidth threshold in MB for input traffic. 0 indicates infinity.	integer	0 - 2147483647	0
out-bandwidth-threshold	Bandwidth threshold in MB for output traffic. 0 indicates infinity.	integer	0 - 2147483647	0
health-check	Link health check of the virtual-wan member.	string	-	none
health-check-fail-threshold	The number of consecutive failed probes before the	integer	1 - 10	5

Parameter	Descrption	Type	Size	Default								
	member is considered dead.											
health-check-success-threshold	The number of consecutive successful probes before the member is considered alive.	integer	1 – 10	5								
link-cost-factor	Criteria by which link selection is made.	option	-	none								
	<table><tr><th>Option</th><th>Descr[iption</th></tr><tr><td>latency</td><td>link-cost-factor based on latency.</td></tr><tr><td>jitter</td><td>link-cost-factor based on jitter.</td></tr><tr><td>packetloss</td><td>link-cost-factor based on packet-loss.</td></tr></table>	Option	Descr[iption	latency	link-cost-factor based on latency.	jitter	link-cost-factor based on jitter.	packetloss	link-cost-factor based on packet-loss.			
Option	Descr[iption											
latency	link-cost-factor based on latency.											
jitter	link-cost-factor based on jitter.											
packetloss	link-cost-factor based on packet-loss.											
latency-threshold	Latency in milliseconds for SLA to make decisions.	integer	0 - 10000000	5								
jitter-threshold	Jitter in milliseconds for SLA to make decisions.	integer	0 - 10000000	5								
packetloss-threshold	Packet loss in percentage for SLA to make decisions.	integer	0 - 100	100								

config syslog

Description: Configure syslog server settings.

```
config system syslog
    config remote-servers {string}
```

```
edit <name>
    set ip* {ipv4-address}
    set port [1 - 65535]
unset
delete <name>
purge
show
end
config statistic-report
    set status [disable | enable]
    set interval [1 - 3600]
    config cpu-usage
        set threshold [0 - 100]
        thrset variance [0 - 100]
    end
    config memory-usage
        set threshold [0 - 100]
        set variance [0 - 100]
    end
    config cpu-temperature
        set threshold [0 - 120]
        set variance [0 - 120]
    end
end
show
end
```

config remote-servers

Description: Configure syslog remote servers settings.

```
config remote-servers
    edit <name>
        set ip* {ipv4-address}
        set port [1 - 65535]
        unset
        end
        next
        show
        abort
    delete
    purge
    end
    show
```

Parameter	Description	Type	Size	Default
ip	The IP address of the remote server.	IPv4 address	-	none
port	The remote syslog server port.	integer	1 - 65535	514

config statistic-report

Description: Configure syslog statistic report settings.

```
config statistic-report
    set status [enable | disable]
    set interval [1 - 3600]
unset
```

Parameter	Description	Type	Size	Default
status	Status syslog statistic report.	option	-	disable
	Option	Description		
	enable	Enable syslog statistic report.		
	disable	Disable Enable syslog statistic report.		
interval	The time interval (in seconds) of system status reports.	integer	1 - 3600	30

config cpu-usage

Description: Configures CPU usage rate statistic report settings.

```
config cpu-usage
    set threshold [0 - 100]
    set variance [0 - 100]
unset
show
end
```

Parameter	Description	Type	Size	Default
threshold	The percentage of CPU usage threshold for system abnormal event report. 0 means disabled.	integer	0 - 100	70
variance	The variance of the CPU usage report when it exceeds the threshold. 0 means report all the time.	integer	0 - 100	5

config memory-usage

Description: Configures memory usage statistic report settings.

```
config memory-usage
    set threshold [0 - 100]
    set variance [0 - 100]
unset
show
```

end

Parameter	Size	Type	Size	Default
threshold	The percentage of memory usage threshold for system abnormal event report. 0 means disabled.	integer	0 - 100	50
variance	The variance of the memory usage report when it exceeds the threshold. 0 means report all the time.	integer	0 - 100	5

config cpu-temperature

Description: Configures CPU temperature statistic report settings.

```
config cpu-temperature
  set threshold [0 - 120]
  set variance [0 - 120]
unset
show
end
```

Parameter	Description	Type	Size	Default
threshold	The CPU temperature threshold for system abnormal event report. 0 means disabled.	integer	0 - 120	80
variance	The variance of the CPU temperature report when it exceeds the threshold. 0 means report all the time.	integer	0 - 120	5

Sample command:

```
config system syslog
  config remote-servers
    edit serv1
      set ip 192.148.200.193
      set port 514
    next
  end
  config statistic-report
    set status enable
    set interval 30
    config cpu-usage
      set threshold 70
      set variance 5
```

```
end
config memory-usage
    set threshold 50
    set variance 5
end
config cpu-temperature
    set threshold 80
    set variance 5
end
end
end
```

config api-user

Description: Configure API user settings.

```
config api-user
    edit <name>
        set comment {string}
        unset
        next
        show
        abort
        end
    delete <name>
    purge
    show
end
```

Sample command:

```
config system api-user
    edit 1
        set comment this is a test api user
    next
end
```

Parameter	Description	Type	Size	Default
name	The name of the API user.	string	-	none
comment	A brief comment of the API user.	string	-	none

config ntp

Description: Configure NTP synchronization in local management mode.

```
config ntp
    set type [fortiguard | custom]
    unset
    config ntpserver
        edit <name>
            set *server {ipv4-address} OR {string}
            unset
            next
            show
            abort
            end
        delete <name>
    purge
    show
end

show
end
```

Parameter	Decription	Type	Size	Default
type	Type of NTP server.	option	-	fortiguard
	Option	Description		
	fortiguard	The FortiGuard NTP server.		
	custom	A custom NTP server.		

- [config ntpserver on page 73](#)

config ntpserver

Description: Configure available third-party NTP servers (up to 4 servers).

```
config ntpserver
    edit <name>
        set *server {ipv4-address} OR {string}
        unset
        next
        show
        abort
        end
    delete <name>
    purge
    show
end

show
end
```

Parameter	Description	Type	Size	Default
server	IP address or hostname of the NTP server.	string	-	none

Sample command:

```
config system ntp
  set type custom
  config ntpserver
    edit 1
      set server 10.139.20.54
    next
  end
end
```

config settings

Description: Configure system settings.

```
config settings
  set ike-port [1024 - 65535]
  unset
  show
end
```

Sample command:

```
config system settings
  set ike-port 500
end
```

Parameter	Description	Type	Size	Default
ike-port	IKE phase 1 port number.	integer	1024 - 65535	500

config system switch-interface

Description: View LAN extension settings synced from the FortiGate. You cannot configure these settings directly on the FortiBranchSASE; you must make them through the FortiGate LAN extension profile first.

```

config system switch-interface
edit <name>
set vlan-support [enable | disable]
config member
edit <name1>
set type [ aggregate | physical | vap]
set port
set vids {1-4089}
set pvid {1-4089}
set security-8021x-member-mode [enable | disable]
next
end
set stp [enable | disable]
set td-mode [disable | include]
set wired-security-mode [802.1X]
set wired-security-group <security group ID>
next
end

```

Sample syntax:

```

config system switch-interface
edit lan
set vlan-support disable
config member
edit port4
set type physical
set port port4
set vids
set pvid 1
set security-8021x-member-mode enable
next
end
set stp disable
set ts-mode disable
set wired-security-mode 802.1X
set wired-security-group test
next
end

```

Parameter	Description	Type	Size	Default
vlan-support	Enable/disable VLAN support.	option	-	
stp	Spanning Tree Protocol.	option	-	disable
	Option	Description		
	enable	Enable Spanning Tree Protocol.		
	disable	Disable Spanning Tree Protocol.		

Parametrer	Description	Type	Size	Default
ts-mode	Read-only: Split tunnel mode.	option	-	disable
	Option	Description		
	include	Enable Split tunnel mode		
	disable	Disable Split tunnel mode.		
wired-security-mode	Turn on 802.1x authentication for this interface.	option	-	
wired-security-group	Names of user groups that can authenticate with the 802.1X.	option	-	
dst-mac	Read-only: MAC address of the remote gateway pushed from FortiOS.	string	-	none
dst-addr	Read-only: Destination IP addresses	string	-	none
services	Read-only: Internet services.	options	-	none

config members

Parameter	Description	Type	Size	Default
config member	Interfaces within the virtual switch.	option	-	none
name	The LAN port ID.	string	-	none
type	Interface type.	option	-	
port	Interface within the virtual switch.	option	-	
vap	Virtual Access Point, which must NOT be configured as a WLAN bridge, will be added as a member of the switch-interface.	option	-	
vids	VLAN ID list.	integer	1 to 4089	
pvid	Port VLAN ID.	integer	1 to 4089	
security-8021x-member-mode	Enable/disable 802.1x authentication on a port.	option	-	

config ssh-crypto

Description: Configure system SSH crypto.

```

config system ssh-crypto
  set strong-crypto [enable | disable]
end

```

Sample command:

```

config system ssh-crypto
  set strong-crypto enable
  set ssh-enc-algo aes256-ctr aes256-gcm@openssh.com
  set ssh-hsk-algo ecdsa-sha2-nistp256 ecdsa-sha2-nistp384 ecdsa-sha2-nistp521 rsa-sha2-256 rsa-sha2-512 ssh-ed25519
  set ssh-kex-algo curve25519-sha256@libssh.org diffie-hellman-group-exchange-sha256 diffie-hellman-group14-sha256 diffie-hellman-group16-sha512 diffie-hellman-group18-sha512
  set ssh-mac-algo hmac-sha2-256 hmac-sha2-256-etm@openssh.com hmac-sha2-512 hmac-sha2-512-etm@openssh.com
end

```

Parameter	Description	Type	Size	Default						
strong-crypto	Enable/disable strong encryption for SSH	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable strong encryption for SSH</td></tr><tr><td>disable</td><td>Disable strong encryption for SSH</td></tr></table>	Option	Description	enable	Enable strong encryption for SSH	disable	Disable strong encryption for SSH			
Option	Description									
enable	Enable strong encryption for SSH									
disable	Disable strong encryption for SSH									
set ssh-enc-algo	Set supported ciphers for ssh-enc-algo.	option	-	aes256-ctr aes256-gcm@openssh.com						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>aes256-ctr</td><td>aes256-ctr</td></tr><tr><td>aes256-gcm@openssh.com</td><td>aes256-gcm@openssh.com</td></tr></table>	Option	Description	aes256-ctr	aes256-ctr	aes256-gcm@openssh.com	aes256-gcm@openssh.com			
Option	Description									
aes256-ctr	aes256-ctr									
aes256-gcm@openssh.com	aes256-gcm@openssh.com									
set ssh-hsk-algo	Set supported ciphers for ssh-hsk-algo.	option	-	ecdsa-sha2-nistp521 ecdsa-sha2-nistp384 ecdsa-sha2-nistp256 rsa-sha2-256 rsa-sha2-512 ssh-ed25519						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>ecdsa-sha2-nistp256</td><td>ecdsa-sha2-nistp256</td></tr></table>	Option	Description	ecdsa-sha2-nistp256	ecdsa-sha2-nistp256					
Option	Description									
ecdsa-sha2-nistp256	ecdsa-sha2-nistp256									

Parameter	Description	Type	Size	Default												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ecdsa-sha2-nistp384</i></td><td>ecdsa-sha2-nistp384</td></tr><tr><td><i>ecdsa-sha2-nistp521</i></td><td>ecdsa-sha2-nistp521</td></tr><tr><td><i>rsa-sha2-256</i></td><td>rsa-sha2-256</td></tr><tr><td><i>rsa-sha2-512</i></td><td>rsa-sha2-512</td></tr><tr><td><i>ssh-ed25519</i></td><td>ssh-ed25519</td></tr></table>	Option	Description	<i>ecdsa-sha2-nistp384</i>	ecdsa-sha2-nistp384	<i>ecdsa-sha2-nistp521</i>	ecdsa-sha2-nistp521	<i>rsa-sha2-256</i>	rsa-sha2-256	<i>rsa-sha2-512</i>	rsa-sha2-512	<i>ssh-ed25519</i>	ssh-ed25519			
	Option	Description														
	<i>ecdsa-sha2-nistp384</i>	ecdsa-sha2-nistp384														
	<i>ecdsa-sha2-nistp521</i>	ecdsa-sha2-nistp521														
	<i>rsa-sha2-256</i>	rsa-sha2-256														
	<i>rsa-sha2-512</i>	rsa-sha2-512														
<i>ssh-ed25519</i>	ssh-ed25519															
set ssh-kex-algo	Set supported ciphers for ssh-kex-algo.	option	-	diffie-hellman-group14-sha256 diffie-hellman-group16-sha512 diffie-hellman-group18-sha512 diffie-hellman-group-exchange-sha256 curve25519-sha256@libssh.org ecdh-sha2-nistp256 ecdh-sha2-nistp384 ecdh-sha2-nistp521												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>curve25519-sha256@libssh.org</i></td><td>curve25519-sha256@libssh.org</td></tr><tr><td><i>diffie-hellman-group-exchange-sha256</i></td><td>diffie-hellman-group-exchange-sha256</td></tr><tr><td><i>diffie-hellman-group14-sha256</i></td><td>diffie-hellman-group14-sha256</td></tr><tr><td><i>diffie-hellman-group16-sha512</i></td><td>diffie-hellman-group16-sha512</td></tr><tr><td><i>diffie-hellman-group18-sha512</i></td><td>diffie-hellman-group18-sha512</td></tr></table>	Option	Description	<i>curve25519-sha256@libssh.org</i>	curve25519-sha256@libssh.org	<i>diffie-hellman-group-exchange-sha256</i>	diffie-hellman-group-exchange-sha256	<i>diffie-hellman-group14-sha256</i>	diffie-hellman-group14-sha256	<i>diffie-hellman-group16-sha512</i>	diffie-hellman-group16-sha512	<i>diffie-hellman-group18-sha512</i>	diffie-hellman-group18-sha512			
	Option	Description														
	<i>curve25519-sha256@libssh.org</i>	curve25519-sha256@libssh.org														
	<i>diffie-hellman-group-exchange-sha256</i>	diffie-hellman-group-exchange-sha256														
	<i>diffie-hellman-group14-sha256</i>	diffie-hellman-group14-sha256														
<i>diffie-hellman-group16-sha512</i>	diffie-hellman-group16-sha512															
<i>diffie-hellman-group18-sha512</i>	diffie-hellman-group18-sha512															
set ssh-mac-algo	Set supported ciphers for ssh-mac-algo.	option	-	hmac-sha2-256 hmac-sha2-256-etm@openssh.com hmac-sha2-512 hmac-sha2-512-etm@openssh.com												

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>hmac-sha2-256</i>	hmac-sha2-256		
	<i>hmac-sha2-256-etm@openssh.com</i>	hmac-sha2-256-etm@openssh.com		
	<i>hmac-sha2-512</i>	hmac-sha2-512		
	<i>hmac-sha2-512-etm@openssh.com</i>	hmac-sha2-512-etm@openssh.com		

config system 802-1X-settings

Description: Configure global 802.1X settings.



Any change to the 802.1X setting may cause the supplicant to reauthenticate if wired security with 802.1x is enabled.

```
config system 802-1X-settings
  set reauth-period {integer}
  set retry-primary-interval {integer}
  set radius-client-failover-wait {integer}
end
```

Parameter	Description	Type	Size	Default
reauth-period	Period of time to allow for reauthentication in seconds (0 = disable reauthentication).	integer	1 - 1440	60
retry-primary-interval	Retry interval for attempting to switch back to the primary RADIUS server, specified in seconds. The default value is 0, which disables switching back to the primary server.	integer	-	0
radius-client-failover-wait	RADIUS force failover timeout (seconds). Time to wait for a response before triggering failover (15, 30, and 45 seconds, default 45 seconds).	integer	-	45

SNMP

This section shows the syntax of the following commands:

- [config sysinfo on page 80](#)
- [config community on page 80](#)
- [config user on page 83](#)
- [config hosts on page 84](#)

config sysinfo

Description: Configure SNMP system info settings.

```
config sysinfo
  set status [enable | disable]
  set description {string}
  set contact-info {string}
  set location {string}
  unset
  show
  end
```

Parameter	Description	Type	Size	Default
status	The status of sysinfo configuration.	option	-	disable
	Option	Description		
	enable	Enable the sysinfo configuration.		
	disable	Disable the sysinfo configuration.		
description	A brief description of the system.	string	1 - 127 characters in length	none
contact-info	Contact information.	string	1 - 127 characters in length	none
location	System location.	string	1 - 127 characters in length	none

config community

Description: Configure SNMP v1/v2 community settings.


```

config community
  edit <name>
    set *name {string}
    set status [enable | disable]
    set hosts <name1>, <name2>, ...
    set query-v1-status [enable | disable]
    set query-v1-port [1 - 65535]
    set query-v2-status [enable | disable]
    set query-v2-port [1 - 65535]
    set trap-v1-status [enable | disable]
    set trap-v1-lport [1 - 65535]
    set trap-v1-rport [1 - 65535]
    set trap-v2c-status [enable | disable]
    set trap-v2c-lport [1 - 65535]
    set trap-v2c-rport [1 - 65535]
    set events <name1>, <name2>, ...
    unset
    next
    show
  end
delete <name>
purge
show
end

```

Parameter	Description	Type	Size	Default
name	Name of the SNMP community.	string	-	none
status	The status of the SNMP community configuration.	option	-	disable
	Option	Description		
	enable	Enable the SNMP community configuration.		
	disable	Disable the SNMP community configuration.		
hosts	SNMP community host names.	option	-	none
query-v1-status	Status of SNMP v1 queries.	option	-	disable
	Option	Description		
	enable	Enable SNMP v1 queries.		
	disable	Disable SNMP v1 queries.		
query-v1-port	SNMP v1 query port number.	integer	1 - 65535	161
query-v2-status	Status of SNMP v2 queries.	option	-	disable

Parameter	Description	Type	Size	Default
	Option	Description		
	enable	Enable SNMP v2 queries.		
	disable	Disable SNMP v2 queries.		
query-v2-port	SNMP v2 query port number.	integer	1 - 65535	161
trap-v1-status	Status of SNMP v1 traps.	option	-	disable
	Option	Description		
	enable	Enable SNMP v1 traps.		
	disable	Disable SNMP v1 traps.		
trap-v1-lport	SNMP v1 trap local port.	integer	1 - 65535	162
trap-v1-rport	SNMP v1 trap remote port.	integer	1 - 65535	162
trap-v2-status	Status of SNMP v2 traps.	option	-	disable
	Option	Description		
	enable	Enable SNMP v2 traps.		
	disable	Disable SNMP v2 traps.		
trap-v2-lport	SNMP v2 trap local port.	integer	1 - 65535	162
trap-v2-rport	SNMP v2 trap remote port.	integer	1 - 65535	162
events	SNMP trap events.	option	-	none
	Option	Description		
	system-reboot	System reboot events.		
	data-exhausted	Data usage exhaustion events.		
	session-disconnect	Modem data session disconnect events.		
	low-signal-strength	Modem low signal strength events.		
	os-image-fallback	System OS image fallback events.		
	mode-switch	System mode switch events.		
	fgt-backup-mode-switch	System FGT VRRP backup mode switch events.		

config user

Description: Configure SNMP v3 user settings.

```
config user
    edit <name>
        set *name {string}
        set status [enable | disable]
        set notify-hosts <name1>, <name2>, ...
        set trap-status [enable | disable]
        set trap-lport [1 - 65535]
        set trap-rport [1 - 65535]
        set queries [enable | disable]
        set query-port [1 - 65535]
        set events <name1>, <name2>, ...
        set security-level [no-auth-no-priv | auth-no-priv | auth-priv]
        set auth-proto [md5 | sha1] *available when security level includes auth
        set *auth-pwd {string} *available when security level includes auth
        set priv-proto [aes | des] *available when security level includes priv
        set *priv-pwd {string}*available when security level includes priv
        unset
        next
        show
        abort
    end
delete <name>
purge
show
end
```

Parameter	Description	Type	Size	Default
name	Username of the SNMP user.	string	-	none
status	Status of the SNMP user configuration.	option	-	disable
	Option		Description	
	enable	Enable the SNMP user.		
	disable	Disable the SNMP user.		
notify-hosts	SNMP managers to which notifications (traps) are sent.	option	-	none
trap-status	Status of the traps for the SNMP user.	option	-	disable
	Option		Description	
	enable	Enable the traps for the SNMP user.		
	disable	Disable the traps for the SNMP user.		

Parameter	Description	Type	Size	Default																
trap-lport	SNMPv3 trap local port.	integer	1 - 65535	162																
trap-rport	SNMPv3 trap remote port.	integer	1 - 65535	162																
queries	Status of SNMP queries for the user.	option	-	disable																
query-port	SNMPv3 query port.	integer	1 - 65535	161																
events	SNMP trap events.	option	-	none																
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>system-reboot</td><td>System reboot events.</td></tr><tr><td>data-exhausted</td><td>Data usage is exhaustion events.</td></tr><tr><td>session-disconnect</td><td>Modem data session disconnect events.</td></tr><tr><td>low-signal-strength</td><td>Modem low signal strength events.</td></tr><tr><td>os-image-fallback</td><td>System OS image fall back events.</td></tr><tr><td>mode-switch</td><td>System mode switch events.</td></tr><tr><td>fgt-backup-mode-switch</td><td>System FGT VRRP backup mode switch events.</td></tr></table>				Option	Description	system-reboot	System reboot events.	data-exhausted	Data usage is exhaustion events.	session-disconnect	Modem data session disconnect events.	low-signal-strength	Modem low signal strength events.	os-image-fallback	System OS image fall back events.	mode-switch	System mode switch events.	fgt-backup-mode-switch	System FGT VRRP backup mode switch events.
Option	Description																			
system-reboot	System reboot events.																			
data-exhausted	Data usage is exhaustion events.																			
session-disconnect	Modem data session disconnect events.																			
low-signal-strength	Modem low signal strength events.																			
os-image-fallback	System OS image fall back events.																			
mode-switch	System mode switch events.																			
fgt-backup-mode-switch	System FGT VRRP backup mode switch events.																			
Security-level	Security level for message authentication and encryption.	option	-	no-auth-no-priv																
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>no-auth-no-priv</td><td>No authentication and no encryption.</td></tr><tr><td>auth-no-priv</td><td>Authentication and no encryption.</td></tr><tr><td>auth-priv</td><td>Authentication and encryption.</td></tr></table>				Option	Description	no-auth-no-priv	No authentication and no encryption.	auth-no-priv	Authentication and no encryption.	auth-priv	Authentication and encryption.								
Option	Description																			
no-auth-no-priv	No authentication and no encryption.																			
auth-no-priv	Authentication and no encryption.																			
auth-priv	Authentication and encryption.																			

config hosts

Description: Configure SNMP hosts settings.

```

config hosts
    edit <name>
        set *host-ip {ipv4-address}
        set host-type [any | query | trap]
        unset
        next
        show
        abort
        end
        delete <name>
        purge

```

```

        show
    end
show
end

```

Parameter	Description	Type	Size	Default
host-ip	IPv4 address of the SNMP manager (host) in x.x.x.x/24 format.	IPv4 address	-	none
host-type	Whether the SNMP manager sends SNMP queries, or receives SNMP traps, or both.	option	-	none
	Option	Description		
	any	Any type.		
	query	SNMP queries only.		
	trap	SNMP traps only.		

Sample command:

```

config snmp
    config sysinfo
        set status enable
        set description this is a test comment
        set contact-info +15082558567
        set location
    end
    config community
        edit comm1
            set name 1
            set status enable
            set hosts host1
            set query-v1-status enable
            set query-v1-port 161
            set query-v2c-status disable
            set query-v2c-port 161
            set trap-v1-status disable
            set trap-v1-lport 162
            set trap-v1-rport 162
            set trap-v2c-status disable
            set trap-v2c-lport 162
            set trap-v2c-rport 162
            set events data-exhausted fgt-backup-mode-switch
        next
    end
    config user
        edit user1
            set name user1

```

```
        set status enable
        set notify-hosts host1
        set trap-status enable
        set trap-lport 162
        set trap-rport 162
        set queries disable
        set query-port 161
        set events data-exhausted fgt-backup-mode-switch low-signal-strength
        set security-level auth-priv
        set auth-proto sha1
        set auth-pwd *****
        set priv-proto aes
        set priv-pwd *****
    next
end
config hosts
    edit host1
        set host-ip 192.168.1.100/24
        set host-type any
    next
end
end
```

HMON

This section shows the syntax of the following commands:

- [config interface-monitoring on page 87](#)
- [config hchk on page 87](#)

config interface-monitoring

Description: Configure monitoring interfaces.

```
config interface-monitoring
  edit <name>
    set interval [1 - 3600]
    set *interface <name1>, <name2>, ...
    set filter <name1>, <name2>, ...
    unset
    next
    show
    abort
    end
  delete <name>
  purge
  show
  end
```

config hchk

Description: Configure measuring latency/loss/jitter.

```
config hchk
```

```
edit <name>
  set protocol [ping | http | dns]
  set interval [1 - 3600]
  set probe-cnt [1 - 10]
  set probe-tm [1 - 10]
  set *probe-target {ipv4-address}
  set port [1 - 65535] *available when protocol is set to http
  set http-get {string} *available when protocol is set to http
  set interface <name1>
  set src-type [none | interface | ip]
  set *stc-iface <name1> *available when src-type is set to interval
```

```

        set *src-ip {ipv4-address} *available when src-type is set to ip
        set filter <name1>, <name2>, ...
        unset
        next
        show
        abort
        end
    delete <name>
    purge
    show
    end
show
end

```

Sample command:

```

config hmon
  config interface-monitoring
    edit 1
      set interval 30
      set interface port1
      set filter rx-bps rx-bytes rx-dropped rx-packets
    next
  end
  config hchk
    edit 1
      set protocol ping
      set interval 5
      set probe-cnt 1
      set probe-tm 2
      set probe-target 8.8.8.8
      set interface port1
      set src-type interface
      set src-iface port1
      set filter rtt loss
    next
  end
end

```

Parameter	Description	Type	Size	Default
interval	Monitoring interval in seconds.	integer	1 - 3600	30
interface	Interface to be monitored.	option	-	none
	Option	Description		
	lan	LAN as the outgoing interface.		
	lo	Loopback as the outgoing interface.		

Parameter	Description	Type	Size	Default																						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>port1</td><td>Port 1 as the outgoing interface.</td></tr><tr><td>port4</td><td>Port 4 as the outgoing interface.</td></tr></table>		Option	Description	port1	Port 1 as the outgoing interface.	port4	Port 4 as the outgoing interface.																		
	Option	Description																								
	port1	Port 1 as the outgoing interface.																								
port4	Port 4 as the outgoing interface.																									
filter	Filter types.	option	-	none																						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>tx-bytes</td><td>Transmitter bytes.</td></tr><tr><td>rx-bytes</td><td>Receiver bytes.</td></tr><tr><td>tx-packets</td><td>Transmitter packets.</td></tr><tr><td>rx-packets</td><td>Receiver packets.</td></tr><tr><td>tx-dropped</td><td>Transmitter dropped bytes.</td></tr><tr><td>rx-dropped</td><td>Receiver dropped bytes.</td></tr><tr><td>tx-bps</td><td>Transmitter bytes per second.</td></tr><tr><td>rx-bps</td><td>Receiver bytes per second.</td></tr><tr><td>tx-pps</td><td>Transmitter packets per second.</td></tr><tr><td>rx-pps</td><td>Receiver packets per second.</td></tr></table>		Option	Description	tx-bytes	Transmitter bytes.	rx-bytes	Receiver bytes.	tx-packets	Transmitter packets.	rx-packets	Receiver packets.	tx-dropped	Transmitter dropped bytes.	rx-dropped	Receiver dropped bytes.	tx-bps	Transmitter bytes per second.	rx-bps	Receiver bytes per second.	tx-pps	Transmitter packets per second.	rx-pps	Receiver packets per second.		
	Option	Description																								
	tx-bytes	Transmitter bytes.																								
	rx-bytes	Receiver bytes.																								
	tx-packets	Transmitter packets.																								
	rx-packets	Receiver packets.																								
	tx-dropped	Transmitter dropped bytes.																								
	rx-dropped	Receiver dropped bytes.																								
	tx-bps	Transmitter bytes per second.																								
	rx-bps	Receiver bytes per second.																								
tx-pps	Transmitter packets per second.																									
rx-pps	Receiver packets per second.																									
protocol	The protocol to use for status checks.	option	-	ping																						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>ping</td><td>Use PING to test the link with the probe-target.</td></tr><tr><td>http</td><td>Use HTTP-GET to test the link with the probe-target.</td></tr><tr><td>dns</td><td>Use DNS-Query to test the link with the probe-target.</td></tr></table>		Option	Description	ping	Use PING to test the link with the probe-target.	http	Use HTTP-GET to test the link with the probe-target.	dns	Use DNS-Query to test the link with the probe-target.																
	Option	Description																								
	ping	Use PING to test the link with the probe-target.																								
	http	Use HTTP-GET to test the link with the probe-target.																								
dns	Use DNS-Query to test the link with the probe-target.																									
interval	Monitoring Interval in seconds.	integer	1 - 3600	5																						
probe-cnt	Number of probes sent within an interval.	integer	1 - 10	1																						
probe-tm	Timeout for a probe in seconds.	integer	1 - 10	2																						
interface	The outbound interface of probe packets.	option	-	none																						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>lan</td><td>LAN as the outgoing interface.</td></tr></table>		Option	Description	lan	LAN as the outgoing interface.																				
	Option	Description																								
lan	LAN as the outgoing interface.																									

Parameter	Description	Type	Size	Default								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>lo</td><td>Loopback as the outgoing interface.</td></tr><tr><td>port1</td><td>Port 1 as the outgoing interface.</td></tr><tr><td>port4</td><td>Port 4 as the outgoing interface.</td></tr></table>		Option	Description	lo	Loopback as the outgoing interface.	port1	Port 1 as the outgoing interface.	port4	Port 4 as the outgoing interface.		
	Option	Description										
	lo	Loopback as the outgoing interface.										
	port1	Port 1 as the outgoing interface.										
port4	Port 4 as the outgoing interface.											
src-type	The way to set the source address for probes.	option	-	none								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>none</td><td>Do not set the source address.</td></tr><tr><td>interface</td><td>Set the source address as the address derived from a specific interface.</td></tr><tr><td>ip</td><td>Set the source address as a specific IP.</td></tr></table>		Option	Description	none	Do not set the source address.	interface	Set the source address as the address derived from a specific interface.	ip	Set the source address as a specific IP.		
	Option	Description										
	none	Do not set the source address.										
	interface	Set the source address as the address derived from a specific interface.										
ip	Set the source address as a specific IP.											
filter	Filter type.	option	-	rtt loss								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>rtt</td><td>Round trip time.</td></tr><tr><td>loss</td><td>Packet loss.</td></tr></table>		Option	Description	rtt	Round trip time.	loss	Packet loss.				
	Option	Description										
	rtt	Round trip time.										
loss	Packet loss.											

VPN

This section shows the syntax of the following commands:

- [config ipsec on page 91](#)
- [config vpn certificate on page 98](#)

config ipsec

Description: Configure IPsec VPN settings.

- [config phase1-interface on page 91](#)
- [config phase2-interface on page 95](#)

config phase1-interface

Description: Configure the VPN remote gateway.

```
config vpn ipsec phase1-interface
edit <name>
    set ike-version [1 | 2]
    set keylife [120 - 172800]
    set proposal [des-md5 | des-sha1 | des-sha256 | 3des-md5 | 3des-sha1 | 3dessha256 | aes128-md5
| aes128-sha1 | aes128-sha256 | aes256-md5 | aes256-sha1 | aes256-sha256]
    set dhgrp [1 | 2 | 5 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 27 | 28 | 29 | 30 | 31 | 32 ]
    set *interface <name1>
    set type [static | ddns]
    set *remote-gw {ipv4-address}
    set *remotegw-ddns {string} *available when type is set to ddns
    set authmethod [psk | signature]
    set *psksecret {string}
    set localid {string}
    set peerid {string}
    set add-gw-route [enable | disable]
    set dev-id-notification [enable | disable]
    set dev-id <name1> *available when dev-id-notification is enabled
    set monitor <name>
next
end
```

Sample command:

```

config vpn ipsec phase1-interface
edit phase1_1
    set ike-version 2
    set keylife 86400
    set proposal aes128-sha256 aes256-sha256 3des-sha256 aes128-sha1 aes256-sha1 3des-sha1
    set dhgrp 14 5 31 20
    set interface port1
    set type static
    set remote-gw 207.102.148.196
    set authmethod psk
    set psksecret *****
    set localid 92
    set peerid 22
    set add-gw-route disable
    set dev-id-notification disable
    set monitor pri
next
end

```

Parameter	Description	Type	Size	Default												
ike-version	IKE protocol version.	option	-	2												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>1</td><td>Version 1</td></tr><tr><td>2</td><td>Version 2</td></tr></table>				Option	Description	1	Version 1	2	Version 2						
	Option	Description														
	1	Version 1														
2	Version 2															
keylife	Time to wait in seconds before the phase 1 encryption key expires.	integer	120 - 172800	86400												
proposal	Phase1 proposal.	option	-	aes128-sha256 aes256-sha256 3des-sha256 aes128-sha1 aes256-sha1 3des-sha1												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>des-md5</td><td></td></tr><tr><td>des-sha1</td><td></td></tr><tr><td>des-sha256</td><td></td></tr><tr><td>3des-md5</td><td></td></tr><tr><td>3des-sha1</td><td></td></tr></table>				Option	Description	des-md5		des-sha1		des-sha256		3des-md5		3des-sha1	
	Option	Description														
	des-md5															
	des-sha1															
	des-sha256															
	3des-md5															
3des-sha1																

Parameter	Description	Type	Size	Default																																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>3des-sha256</td><td></td></tr><tr><td>aes128-md5</td><td></td></tr><tr><td>aes128-sha1</td><td></td></tr><tr><td>aes128-sha256</td><td></td></tr><tr><td>aes256-md5</td><td></td></tr><tr><td>aes256-sha1</td><td></td></tr><tr><td>aes256-sha256</td><td></td></tr></table>				Option	Description	3des-sha256		aes128-md5		aes128-sha1		aes128-sha256		aes256-md5		aes256-sha1		aes256-sha256																					
	Option	Description																																						
	3des-sha256																																							
	aes128-md5																																							
	aes128-sha1																																							
	aes128-sha256																																							
	aes256-md5																																							
	aes256-sha1																																							
	aes256-sha256																																							
dhgrp	DH group.	option	-	14, 5																																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>1</td><td></td></tr><tr><td>2</td><td></td></tr><tr><td>5</td><td></td></tr><tr><td>14</td><td></td></tr><tr><td>15</td><td></td></tr><tr><td>16</td><td></td></tr><tr><td>17</td><td></td></tr><tr><td>18</td><td></td></tr><tr><td>19</td><td></td></tr><tr><td>20</td><td></td></tr><tr><td>21</td><td></td></tr><tr><td>27</td><td></td></tr><tr><td>28</td><td></td></tr><tr><td>29</td><td></td></tr><tr><td>30</td><td></td></tr><tr><td>31</td><td></td></tr><tr><td>32</td><td></td></tr></table>				Option	Description	1		2		5		14		15		16		17		18		19		20		21		27		28		29		30		31		32	
	Option	Description																																						
	1																																							
	2																																							
	5																																							
	14																																							
	15																																							
	16																																							
	17																																							
	18																																							
	19																																							
	20																																							
	21																																							
	27																																							
	28																																							
	29																																							
	30																																							
	31																																							
32																																								
interface	The outgoing interface.	option	-	none																																				

Parameter	Description	Type	Size	Default
	Option	Description		
	lan	LAN as the outgoing interface.		
	lo	Loopback as the outgoing interface.		
	port1	Port 1 as the outgoing interface.		
remote-gw	The IPv4 address of the remote gateway's external interface.	IPv4 address	-	none
authmethod	Authentication method.	option	-	psk
	Option	Description		
	psk	Preshared key.		
	signature	Signature certificate.		
psksecret	Pre-shared secret for PSK authentication (ASCII string or hexadecimal encoded with a leading 0x).	string	-	none
localid	Local ID.	string	-	none
peerid	Peer identity.	string	-	none
add-gw-route	Whether to automatically add a route to the remote gateway.	option	-	disable
	Option	Description		
	enable	Enable automatically adding a route to the remote gateway.		
	disable	Disable automatically adding a route to the remote gateway.		
dev-id-notification	Whether to enable device ID notification for the first IKE message.	option	-	disable
	Option	Description		
	enable	Enable device ID notification.		
	disable	Disable device ID notification.		
dev-id	The Device ID carried by the device ID notification.	string	-	none
monitor	Specify the IPsec phase1 interface as primary.	string	-	none

config phase2-interface

Description: Configure VPN autokey tunnel.

```
config phase2-interface
edit <name>
set *phase1name
set pfs [enable | disable]
set dhgrp [1 | 2 | 5 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 27 | 28 | 29 | 30 | 31 | 32 ]
set keylife-type [seconds | kbs]
set keylifeseconds [120 - 172800]
set encapsulation [tunnel-mode | transport-mode]
set protocol [0 - 255]
set src-addr-type [subnet | range | ip | name]
set src-subnet {ipv4-subnet}
set *src-start-ip {ipv4-address} *available when src-addr-type is range and ip
set *src-end-ip {ipv4-address} *available when src-addr-type is range
set *src-name {string} *available when src-addr-type is name
set src-port [0 - 65535]
set dst-addr-type [subnet | range | ip | name]
set dst-subnet {ipv4-subnet}
set *dst-start-ip {ipv4-address} *available when dst-addr-type is range and ip
set *dst-end-ip {ipv4-address} *available when dst-addr-type is range
set *dst-name {string} *available when dst-addr-type is name
set dst-port [0 - 65535]
unset
next
show
abort
end
delete <name>
purge
show
end
show
end
```

Sample command:

```
config vpn ipsec phase2-interface
edit phase2_1
set phase1name phase1_1
set proposal aes128-sha1 aes256-sha1 3des-sha1 aes128-sha256 aes256-sha256 3dessha256
set pfs enable
set dhgrp 14 5 31 20
set keylife-type seconds
set keylifeseconds 43200
set encapsulation tunnel-mode
set protocol 0
set src-addr-type subnet
```

```

set src-subnet 0.0.0.0/0
set src-port 0
set dst-addr-type subnet
set dst-subnet 107.204.148.0/24
set dst-port 234
next
end

```

Parameter	Description	Type	Size	Default																								
phase1name	Phase 1 name (which determines the options required for phase 2).	string	-	none																								
proposal	Phase 2 proposal.	option	-	aes128-sha1 aes256-sha1 3des-sha1 aes128-sha256 aes256-sha256 3des-sha256																								
pfs	Status of the PFS feature.	option	-	enable																								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable PFS.</td></tr><tr><td>disable</td><td>Disable PFS.</td></tr></table>	Option	Description	enable	Enable PFS.	disable	Disable PFS.																					
Option	Description																											
enable	Enable PFS.																											
disable	Disable PFS.																											
dhgrp	Phase 2 DH group.	option	-	14, 5																								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>1</td><td></td></tr><tr><td>2</td><td></td></tr><tr><td>5</td><td></td></tr><tr><td>14</td><td></td></tr><tr><td>15</td><td></td></tr><tr><td>16</td><td></td></tr><tr><td>17</td><td></td></tr><tr><td>18</td><td></td></tr><tr><td>19</td><td></td></tr><tr><td>20</td><td></td></tr><tr><td>21</td><td></td></tr></table>	Option	Description	1		2		5		14		15		16		17		18		19		20		21				
Option	Description																											
1																												
2																												
5																												
14																												
15																												
16																												
17																												
18																												
19																												
20																												
21																												

Parameter	Description	Type	Size	Default
	Option Description			
	27			
	28			
	29			
	30			
	31			
	32			
keylife-type	Keylife type	option	-	seconds
	Option Description			
	seconds	Seconds.		
	kbs	Kbs.		
keylifeseconds	Phase 2 key life in seconds.	integer	120 – 172800	43200
keylifekbs	Phase 2 key life in the number of bytes of traffic.	integer	5120 - 4294967295	5120
encapsulation	ESP encapsulation mode.	option	-	tunnel-mode
	Option Description			
	tunnel-mode	Tunnel mode.		
	transport-mode	Transport mode.		
protocol	Quick mode protocol selector.	integer	1 - 255	0
src-addr-type	Local proxy ID type.	option	-	subnet
	Option Description			
	subnet	IPv4 subnet.		
	range	IPv4 range.		
	ip	IPv4 IP.		
	name	IPv4 network address name.		
src-subnet	Local proxy ID subnet.	IPv4 address	-	0.0.0.0/0
src-port	Quick mode source port.	integer	1 - 65535, or 0 for all	0
dst-addr-type	Remote proxy ID type.	option	-	subnet

Parameter	Description	Type	Size	Default
	Option	Description		
	subnet	IPv4 subnet.		
	range	IPv4 range.		
	ip	IPv4 IP.		
	name	IPv4 network address name.		
dst-subnet	Remote proxy ID subnet.	IPv4 address	-	0.0.0.0/0
dst-port	Quick mode source port.	integer	1 - 65535, or 0 for all	0
src-start-ip	Local proxy ID start.	IPv4 address	-	none
src-end-ip	Local proxy ID end.	IPv4 address	-	none
dst-start-ip	Remote proxy ID start.	IPv4 address	-	none
dst-end-ip	Remote proxy ID end	IPv4 address	-	none
src-name	Local proxy ID name.	string	-	none
dst-name	Remote proxy ID name.	string	-	none

config vpn certificate

Description: Configure VPN certificates.

- [config vpn certificate ca on page 98](#)
- [config vpn certificate local on page 99](#)

config vpn certificate ca

Description: Configure CA certificates.

```

config ca
  edit <name>
    set comment {string}
    set *source [factory | user]
    unset
    next
    abort
    show
  end
  delete <name>
  purge
  show

```

```
end
```

Sample command:

```
config vpn certificate ca
  edit Fortinet_CA
    set comment
    set source factory
  next
end
```

config vpn certificate local

Description: Configure local keys and certificates.

```
config vpn certificate local
  edit <name>
    set comment {string}
    set source [factory | user]
    set enroll-protocol [none | scep]
    unset
  next
  show
  abort
end
delete <name>
purge
show
end
```

Sample command:

```
config vpn certificate local
  edit Fortinet_Factory
    set comment
    set source factory
    set enroll-protocol scep
  next
end
```

Parameter	Description	Type	Size	Default
comment	Optional comments.	string	Up to 255 characters in length.	none
source	Source of CA certificate.	option	-	factory

Parameter	Description	Type	Size	Default
	Option	Description		
	factory	From the manufacturer.		
	user	From the user.		
enroll-protocol	Certificate enrollment protocol.	option	-	
	Option	Description		
	None	None.		
	scep	Use SCEP.		

Network

This section shows the syntax of the following commands:

- [config address on page 101](#)
- [config service-custom on page 102](#)

config address

Description: Configure IPv4 addresses.

```
config address
  edit <name>
    set type [ipmask | iprange]
    set subnet {ipv4-address}
    set start-ip {ipv4-address} *available when type is set to iprange
    set end-ip {ipv4-address} *available when type is set to iprange
    unset
    next
    show
    abort
    end
  delete <name>
  purge
  show
  end
```

Sample command:

```
config network address
  edit lan
    set type ipmask
    set subnet 192.168.200.0/24
  next
```

Parameter	Description	Type	Size	Default
type	Type of address.	option	-	ipmask
		Option	Description	
		ipmask	IP address and subnet mask.	
		iprange	IP range.	

Parameter	Description	Type	Size	Default
subnet	IP address and subnet mask.	IPv4 address	-	none
start-ip	The first IP address (inclusive) in the range of IP addresses.	IPv4 address	-	none
end-ip	The last IP address (inclusive) in the range of IP addresses.	IPv4 address	-	none

config service

Description: Configure firewall service.

config service-custom

Description: Configure custom services.

```
config service-custom
    edit <name>
        set protocol [TCP | UDP | ICMP | IP]
        set protocol number (0 - 254)
        set tcp-portrange <dstport_low>[-<dstport_high>:<srcport_low>-<srcport_high>] *available
            when protocol is set to TCP
        set udp-portrange <dstport_low>[-<dstport_high>:<srcport_low>-<srcport_high>] *available
            when protocol is set to UDP
        unset
        next
        show
        abort
    end
    delete <name>
    purge
    show
end
show
end
```

Sample command:

```
config network service
    config service-custom
        edit ALL
            set protocol IP
            set protocol-number 0
        next
```

Parameter	Size	Type	Size	Default
protocol	Protocol type based on IANA numbers.	option	-	ip
	Option		Description	
	tcp		TCP protocol.	
	udp		UDP protocol.	
	icmp		ICMP protocol.	
	ip		IP protocol.	
protocol-number	IP protocol number.	integer	0 - 254	0

Execute

This section shows the syntax of the following command:

- [execute SSH username serverip on page 104](#)
- [execute vpn certificate local generate rsa on page 104](#)

execute SSH username serverip

Description: Configure SSH client log into other devices from FortiBranchSASE.

```
#execute ssh username serverip
```

Sample command:

```
execute ssh admin 192.168.1.115
```

execute vpn certificate local generate rsa

Description: Generate a Certificate Signing Request.

```
# execute vpn certificate local generate rsa <cert_name> <key_size> <subject> <country name>  
<state> <city> <org> <Units> <email> <subject_alter_name> <URL> <challenge>
```

Sample command:

```
# execute vpn certificate local generate rsa test1 1024 cert US CA Sunnyvale Fortinet  
102,203,303 test@fortinet.com null http://192.168.100.99/app/cert/scep/ fortinet
```

Field	Description	Mandatory	Type	Value Range
cert_name	Specify the certificate name.	Yes	String	
key_size	Specify the key size.	Yes	Number	1024, 1536, 2048, 4096

Field	Description	Mandatory	Type	Value Range
subject	Specify the subject(Host-IP/Domain Name/E-Mail).	Yes	String	
country name	Specify the country name.	No	String	
state	Specify the state name.	No	String	
city	Specify the city name.	No	String	
org	Specify the organization name.	No	String	
Units	Specify the unit name. If there are multiple units, use ';' as a delimiter.	No	String	
email	Specify the email address.	No	String	
subject_alter_name	Specify the subject alternative name.	No	String	
URL	Specify the URL.	Yes	String	
challenge	Specify the challenge password.	No	String	

WiFi

This section presents the CLI commands for configuring Wi-Fi network settings on Wi-Fi enabled platforms.

- [config vap on page 106](#)
- [config ap-security on page 108](#)
- [config wifi-networks on page 109](#)
- [config radio-profile on page 110](#)
- [config wifi-general on page 111](#)

config vap

Description: Configure WiFi virtual access point.

```
Edit <WiFi Access Point Name>
    set ssid <name>
    set broadcast-ssid [enable | disable]
    set dtim {1-255}
    set rts-threshold {256-2347}
    set max-clients {0-512}
    set target-wake-time[enable | disable]
    set bss-color-partial [enable | disable]
    set mu-mimo [enable | disable]
    set wlan-bridge [yes |no ]
    set wlan-members
config ap-security
set security-mode <encryption mode>
```

FortiBranchSASE supports the following security modes:

- OPEN
- WPA2-Personal
- WPA-WPA2-Personal
- WPA3-SAE
- WPA3-SAE-Transition
- WPA2-Enterprise
- WPA3-Enterprise-Only
- WPA3-Enterprise-Transition
- WPA3-Enterprise-192-bit





If security-mode is set to WPA2-Personal, WPA-WPA2-Personal, WPA3-SAE, or WPA3-SAE-Transition, you must also configure the following settings:

```
set pmf <option>
set passphrase <password>
```



If security-mode is set to WPA2-Enterprise, WPA3-Enterprise-Only, WPA3-Enterprise-Transition, or WPA3-Enterprise-192-bit, you must configure the following settings:

```
set auth-server-addr <url>
set auth-server-port <port number> # default as 1812
set auth-server-secret <password>
```

Sample command:

```
config wifi vap
edit fbs-home-2g-1
    set ssid fbs-home-2g-1
    set broadcast-ssid enable
    set dtim 1
    set rts-threshold 2347
    set max-clients 9
    set target-wake-time enable
    set bss-color-partial enable
    set mu-mimo enable
    set wlan-bridge no
    set wlan-members
config ap-security
set security-mode WPA2-Enterprise
set auth-server-addr 192.168.11.99
set auth-server-port 1812
set auth-server-secret *****
set pmf optional
end
next
edit fbs-home-5g-1
    set ssid fbs-home-5g-1
    set broadcast-ssid enable
    set dtim 1
    set rts-threshold 2347
    set max-clients 9
    set target-wake-time enable
    set bss-color-partial enable
    set mu-mimo enable
    set wlan-bridge yes
    set wlan-members
config ap-security
    set security-mode WPA2-Personal
```

```

        set pmf required
        set passphrase *****
    end
next

```

config ap-security

Description: Configure security mode for WiFi access point.

```

config ap-security
    set security-mode <encryption mode>
    # Security encryption modes including:
        OPEN
        WPA2-Personal
        WPA-WPA2-Personal
        WPA3-SAE
        WPA3-SAE-Transition
        WPA2-Enterprise
        WPA3-Enterprise-Only
        WPA3-Enterprise-Transition
        WPA3-Enterprise-192-bit
    if security-mode chooses OPEN:
        set pmf <option>
        # pmf option includes the options:
            disabled
            optional
            required
    if security-mode chooses these options: WPA2-Personal, WPA-WPA2-Personal, WPA3-SAE,WPA3-SAE-
        Transition, configure the following commands:
            set pmf <option>
            set passphrase <password>
    if security-mode chooses these options: WPA2-Enterprise, WPA3-Enterprise-Only, WPA3-Enterprise-
        Transition, WPA3-Enterprise-192-bit, configure the following commands:
            set auth-server-addr <url>
            set auth-server-port <port number> # default as 1812
            set auth-server-secret <password>

```

Sample command

```

config wifi vap
    edit fbs-home-2g-1
        set ssid fbs-home-2g-1
        set broadcast-ssid enable
        set wlan-members
        config ap-security
            set security-mode WPA2-Enterprise
            set auth-server-addr 192.168.11.99
            set auth-server-port 1812
            set auth-server-secret *****
            set pmf optional

```

```

        end
    next
edit fbs-home-5g-1
    set ssid fbs-home-5g-1
    set broadcast-ssid enable
    set wlan-members
    config ap-security
        set security-mode WPA2-Personal
        set pmf disabled
        set passphrase *****
    end
next
end

```

config wifi-networks

Description: Configure WiFi networks for Station Mode.

```

edit <name>
    set ssid <id>
    set security-mode <encryption mode>
    # the security mode has the following options:
        OPEN
        WPA-Personal
        WPA2-Personal
        WPA-WPA2-Personal
        WPA3-SAE
        WPA3-SAE-Transition
        WPA-Enterprise
        WPA2-Enterprise
        WPA-WPA2-Enterprise
        WPA3-Enterprise-Only
        WPA3-Enterprise-Transition
    set pmf <option>
    # pmf option includes the options:
        disabled
        optional
        required

```

Sample command:

```

config wifi wifi-networks
    edit 2g-ArloNetwork
        set ssid ArloNetwork
        set security-mode WPA3-Enterprise-Only
        set pmf required
        set identity *****
        set password *****
    next
    edit 5g-Dream

```

```

        set ssid Dream
        set security-mode WPA3-SAE
        set pmf
        set sae-password *****
    next
    edit 5g-Hope
        set ssid Hope
        set security-mode WPA2-Enterprise
        set pmf
        set identity *****
        set password *****
    next
end

```

config radio-profile

Description: Configure WiFi Radio profile.

```

config wifi radio-profile
edit <radio profile name>
set band <2GHz/5GHz>
set status <enable/disable>
set role <lan/wan> # two options for role, as lan and wan
If role is set as lan, configure the following parameters for the WiFi lan interface:
set operating-standards auto
set beacon-interval {100-3500}
set 80211d [ enable | disable]
set max-clients {0-512}
set power-mode auto
    set channel
set bandwidth auto
set extension-channel auto
set guard-interval auto
set vap <ap names> #maximum 4 APs for the vap configure

```

Sample command:

```

config wifi radio-profile
edit 2g-profile
    set band 2GHz
    set enable enable
    set role lan
    set operating-standards auto
    set power-mode auto
    set channel
    set bandwidth auto
    set extension-channel auto
    set guard-interval auto

```

```
        set vap fbs-home-2g-1 fbs-home-2g-3 fbs-home-2g-4
    next

edit 5g-profile
    set band 5GHz
    set enable enable
    set role wan
    set wifi-networks 5g-Dream
next
end
```

config wifi-general

Description: Configure general WiFi settings.

```
set country-code
AS    AMERICAN SAMOA
AR    ARGENTINA
BS    BAHAMAS
BM    BERMUDA
KY    CAYMAN ISLANDS
DM    DOMINICA
GU    GUAM
HT    HAITI
MH    MARSHALL ISLANDS
AW    ARUBA
NI    NICARAGUA
MP    NORTHERN MARIANA ISLANDS
PW    PALAU
PR    PUERTO RICO
KN    SAINT KITTS AND NEVIS
LC    SAINT LUCIA
VC    SAINT VINCENT AND GRENADIENS
US    UNITED STATES
VI    VIRGIN ISLANDS
CA    CANADA
```



The list of county codes varies with the region code of the devices in use. The list of country codes shown above applies to devices with the region code "A" only.

User

This section shows the syntax of the following commands:

- [config user radius on page 112](#)
- [config user group on page 113](#)

config user radius

Configure the FortiBranchSASE to access a RADIUS server.

```
config user radius
edit <name>
    set server {string}
    set secret {password}
    set auth-type [auto|ms_chap_v2|...]
    set timeout {integer}
    set transport-protocol [udp]
    set nas-ip {string}
next
end
```

Sample command:

```
config user radius
edit example_radius
    set server fortinet.com
    set secret *****
    set auth-type auto
    set timeout 5
    set transport-protocol udp
    set nas-ip 0.0.0.0
next
end
```

Parameter	Description	Type	Size	Default
name	Name of the RADIUS server table.	string	-	none
server	Primary RADIUS FQDN or IP address.	string	-	none
secret	Pre-shared secret key used to access the primary RADIUS server.	password	1-128	none

Parameter	Description	Type	Size	Default
auth-type	Authentication protocols permitted for this RADIUS server. You can select the following options: • auto • ms_chap_v2 • ms_chap • chap • pap If the authentication type is set to auto, FortiBranchSASE uses the following protocols in sequence: PAP → MSCHAP_v2 → CHAP FortiBranchSASE will only try the next protocol once it receives a RADIUS-reject message	option	-	auto
timeout	Time in seconds to retry connecting to the RADIUS server.	integer	-	5
transport-protocol	Transport protocol to be used. • udp	option	-	udp
nas-ip	IPv4 address used for the FortiBranchSASE to communicate with the RADIUS server. It is also used as the NAS-IP-Address and Called-Station-ID attributes.	string	-	none
nas-identifier	Optional NAS-Identifier string for RADIUS messages	string	-	none
port	Primary RADIUS server port number	integer	-	none

config user group

Apply a RADIUS server table to a user group.

```
config user group
  edit group1
    set member [RADIUS server name1] [RADIUS server name2]
  next
end
```

Parameter	Description
name	Name of the FortiBranchSASE user group.
member	Names of users and RADIUS server tables you want to add to the user group. You can apply multiple RADIUS server tables to a user group.



www.fortinet.com

Copyright© 2025 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's Chief Legal Officer, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.