FORTINET
High Performance Network Security

FortiOS - Log Reference

VERSION 5.4.7



FORTINET DOCUMENT LIBRARY

http://docs.fortinet.com

FORTINET VIDEO GUIDE

http://video.fortinet.com

FORTINET BLOG

https://blog.fortinet.com

CUSTOMER SERVICE & SUPPORT

https://support.fortinet.com

FORTIGATE COOKBOOK

http://cookbook.fortinet.com

FORTINET TRAINING SERVICES

http://www.fortinet.com/training

FORTIGUARD CENTER

http://www.fortiguard.com

END USER LICENSE AGREEMENT

http://www.fortinet.com/doc/legal/EULA.pdf

FEEDBACK

Email: techdocs@fortinet.com

December 7, 2017

FortiOS 5.4.7 Log Reference

01-547-299610-20171207

TABLE OF CONTENTS

Change Log **4**
Introduction **5**
Before you begin 5
Overview 5
What's New 5
Log Types and Subtypes **7**
Log Schema Structure **11**
Header and Body Fields 11
Log ID Numbers 13
Log ID Definitions 14
Log Messages **17**
Anomaly 17
App 22
AV 39
DLP 126
Email 132
Event 188
GTP 862
IPS 884
Traffic 889
VoIP 921
WAF 931
Web 949

Change Log

Date	Change Description
2017-12-07	Initial release.

Introduction

This document provides information about all log messages applicable to FortiGate devices running FortiOS version 5.4.7 or higher. The logs are intended for administrators to be used as reference for more information about a specific log entry and message that is generated.

Before you begin

Before you begin using this reference, read the following notes:

- The information in this document applies to all FortiGate units currently running FortiOS 5.4.7 or higher.
- Ensure you have enabled logging for the FortiOS unit. See *Logging and Reporting* in the *FortiOS Handbook*.
- Each log message displays in RAW format in the Log View of the web-based manager.
- Each log message is documented similar to how it appears in the log viewer table based on the RAW format. See *Logging and Reporting* in the *FortiOS Handbook*.

This reference contains detailed information for each log type and subtype; however, this reference contains only information gathered at publication and, as a result, not every log message field contains detailed information.

Overview

The log types described in this document report traffic, security, and event log information useful for system administrators when recording, monitoring, and tracing the operation of a FortiOS device running FortiOS. The logs provide information regarding the following:

- Firewall attacks
- Configuration changes
- Successful and unsuccessful system operations

What's New

This section identifies major changes in the Log Reference from version 5.4.0 and later.

FortiOS 5.4.7

There are no major log changes between FortiOS 5.4.6 and 5.4.7.

FortiOS 5.4.6

There are no major log changes between FortiOS 5.4.5 and 5.4.6.

FortiOS 5.4.5

There are no major log changes between FortiOS 5.4.4 and 5.4.5.

FortiOS 5.4.4

There are no major log changes between FortiOS 5.4.3 and 5.4.4.

FortiOS 5.4.3

There are no major log changes between FortiOS 5.4.2 and 5.4.3.

FortiOS 5.4.2

There are no major log changes between FortiOS 5.4.1 and 5.4.2.

FortiOS 5.4.1

There are no major log changes between FortiOS 5.4.0 and 5.4.1.

FortiOS 5.4.0

Content

- Content log type was removed from FortiOS 5.4.0.

Event

- Compliance-check log subtype was added to Event log type.
- GTP log subtype was removed from Event log type.
- Router log subtype was added to Event log type.

GTP

- GTP was added as a new log type with a category of 14. Previously GTP was a log subtype of the Event log type.

WAF

- WAF was added as a new log type with a category of 12.

Log Types and Subtypes

FortiOS devices can record the following types and subtypes of log entry information:

Type	Description	Subtype
Traffic	Records traffic flow information, such as an HTTP/HTTPS request and its response, if any.	• Local • Forward • Multicast
Event	Records system and administrative events, such as downloading a backup copy of the configuration, or daemon activities.	• Compliance-check • Endpoint Control • High Availability • Router • System • User • Virtual Private Network (VPN) • WAD • Wireless
Anomaly	Records intrusion attempts.	• Anomaly
App	Records intrusion attempts.	• App-CTRL-All
AV	Records virus attack.	• Analytics • Botnet • Filename • Infected • Mime Fragnmented • Oversize • Scan Error • Switch Proto
DLP	Records data leak prevention events.	• DLP

Type	Description	Subtype
Email	Records email filter events.	• Carrier Endpoint Filter • Gmail • IMAP • MAPI • Mass MMS • MSN Hotmail • POP3 • SMTP • Yahoo Mail
GTP	Records GPRS Tunneling Protocol (GTP) traffic for FortiCarrier devices.	• GTP All
IPS	Records intrusion prevention events.	• Signature
VoIP	Records voice over IP events.	• VoIP
WAF	Records web application firewall information for FortiWeb appliances and virtual appliances	• WAF Address List • WAF Custom Signature • WAF HTTP Constraint • WAF HTTP Method • WAF Signature • WAF URL Access
Web	Records web filter events.	• ActiveX Filter • Applet Filter • Content • Cookie Filter • FortiGuard Allow • FortiGuard Block • FortiGuard Error • FortiGuard Quota • FortiGuard Quota Counting • Script Filter • URL Filter • Web Filter Command Block

Type

Each log entry contains a Type (type) field that indicates its log type, and in which log file it is stored.

Subtype

Each log entry contains a Sub Type (subtype), or category, field within a log type, based on the feature associated with the cause of the log entry.

For example:

- In event logs, some log entries have a subtype of user, system, or other subtypes.
- In traffic logs, the subtypes are: local, forward, multicast, and sniffer.

Priority Level

Each log entry contains a Level (level) field that indicates the estimated severity of the event that caused the log entry, such as `level=warning`, and therefore how high a priority it is likely to be. Level (level) associations with the descriptions below are not always uniform. They also may not correspond with your own definitions of how severe each event is. If you require notification when a specific event occurs, either configure SNMP traps or alert email by administrator-defined Severity Level (severity_level) or ID (logid), not by Level (level).

Level (0 is highest)	Name	Description
0	Emergency	The system is unusable or not responding.
1	Alert	Immediate action required. Used in security logs.
2	Critical	Functionality is affected.
3	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
5	Notification	Information about normal events.
6	Information	General information about system operations. Used in event logs to record configuration changes.

For each location where the FortiOS device can store log files (disk, memory, Syslog or FortiAnalyzer), you can define a severity threshold. The FortiOS stores all log messages equal to or exceeding the log severity level selected. For example, if you select Error, FortiOS will store log messages whose log severity level is Error, Critical, Alert, and Emergency.

Message IDs

The MSG ID (msg_id) field is a 10-digit number located in the header, incremented with each individual log message generated by FortiOS. It is used only for numbering each entry in the database, and does not necessarily reflect its cause.

Each msg_id number is a unique identifier for that specific log entry. No other log messages, regardless of cause, share the same msg_id.

LOG ID field	10-digit number
MSG-ID(msg_id)	Last 6 digits at the end of the LOG ID field.

Log Field Format

The following table describes the standard format in which each log type is described in this document. For documentation purposes, all log types and subtypes follow this generic table format to present the log entry information.

Log Field Name	Description	Data Type	Length
appact	The security action from app control	string	16

Log Schema Structure

This section describes the schema of the FortiOS log messages.

Header and Body Fields

Each log message consists of several fields and values. In the web-based manager, the logs are displayed in a **Formatted** table view or **Raw** format. You can download the logs in the raw format for further analysis.

- Header - Contains the date and time the log originated, log identifier, message identifier, virtual domain (VDOM), the log category, severity level, and where the log originated. These fields are common to all log categories.
- Body - Describes the reason why the log was created and actions taken by the FortiOS device to address it. These fields vary by log category.

Following is an example of traffic log message in raw format. The body fields are highlighted in bold.

```
date=2014-07-04 time=14:26:59 logid=0001000014 type=traffic subtype=local
level=notice vd=vdom1 srcip=10.6.30.254 srcport=54705 srcintf="mgmt1"
dstip=10.6.30.1 dstport=80 dstintf="vdom1" sessionid=350696 status=close
policyid=0 dstcountry="Reserved" srccountry="Reserved" trandisp=noop
service=HTTP proto=6 app="Web Management" duration=13 sentbyte=1948
rcvdbyte=3553 sentpkt=9 rcvdpkt=9 devtype="Fortinet Device"
osname="Fortinet OS" mastersrcmac=00:09:0f:67:6c:31
srcmac=00:09:0f:67:6c:31
```

The following table provides an example of the log field information that is contained in the header and body fields, according to its name as it appears in the **Formatted** or **Raw** view.

Field Name (Raw format view in par-entheses)	Field Description	Exists in Log Type			Example Field - Value (raw format)
		Traffic	Event	Security	
Header					
Date (date)	The day, month, and year when the log message was reported.	✓	✓	✓	`date=2014-07-04`
Time (time)	The hour clock when the log message was recorded.	✓	✓	✓	`time=14:26:59`
ID (logid)	See Log ID	✓	✓	✓	`logid=0001000014`
MSG (msg)	See Message IDs	✓	✓	✓	`msg=000100000012`
Type (type)	See Type	✓	✓	✓	`type=traffic`

Field Name (Raw format view in parentheses)	Field Description	Exists in Log Type			Example Field - Value (raw format)
		Traffic	Event	Security	
Sub Type (subtype)	See Sub Type	✓	✓	✓	`subtype=local`
VDOM (vd)	The virtual domain in which the log message was recorded.	✓	✓	✓	`vd=vdom1`
Level (pri)	Priority level	✓	✓	✓	`level=notice`
Body					
Protocol (proto)	tcp: The protocol used by web traffic (tcp by default)	✓	✓	✓	`proto=6`
Source IP (srcip)	The IP address of the traffic's origin. The source varies by the direction: • In HTTP requests, this is the web browser or other client. • In HTTP responses, this is the physical server.	✓	✓	✓	`srcip=10.6.30.254`
Source Port (srcport)	The port number of the traffic's origin.	✓	✓	✓	`srcport=54705`
Source Interface (srcintf)	The interface of the traffic's origin.	✓	✓	✓	`srcintf="mgmt1"`
Destination IP (dstip)	The destination IP address for the web.	✓	✓	✓	`dstip=10.6.30.1`
Destination Port (dstport)	The port number of the traffic's destination.	✓	✓	✓	`dstport=80`
Destination Interface (dstintf)	The interface of the traffic's destination.	✓	✓	✓	`dstintf="vdom1"`
Session ID (sessionid)	The session number for the traffic connection	✓	✓	✓	`sessionid=350696`
Status (status)	The status of the session	✓	✓	✓	`status=close`

Field Name (Raw format view in parentheses)	Field Description	Exists in Log Type			Example Field - Value (raw format)
		Traffic	Event	Security	
Policy (policyid)	The name of the server policy governing the traffic which caused the log message.	✓	✓	✓	`policyid=0`
Service (service)	http or https The name of the application-layer protocol used by the traffic.	✓	✓	✓	`service=HTTP`
User (user)	The daemon or name of the administrator account that performed the action that caused the log message.	✓	✓	✓	`user=admin`

Log ID Numbers

The ID (logid) is a 10-digit field located in the header, immediately following the time and date fields. It is a unique identifier for that specific log and includes the following information about the log entry.

Log ID number components	Description	Examples
Log Type	Represented by the first two digits of the log ID.	• Traffic log IDs begin with "`00`". • Event log IDs begin with "`01`".
Sub Type or Event Type	Represented by the second two digits of the log ID.	• VPN log subtype is represented with "`01`" which belongs to the Event log type that is represented with "`01`". Therefore, all VPN related Event log IDs will begin with the `0101` log ID series.
Message ID	The last six digits of the log ID represent the message ID.	• An administrator account always has the log ID `0000003401`.

The logid field is a number assigned to all permutations of the same message. It classifies a log entry by the nature of the cause of the log message, such as administrator authentication failures or traffic. Other log messages that share the same cause will share the same logid.

Log ID Definitions

Following are the definitions for the log type IDs and subtype IDs applicable to FortiOS version 5.2.1 and later.

Log Type IDs	Subtype IDs
traffic: 0	• forward: 0 • local: 1 • multicast: 2 • sniffer: 4
event: 1	• system: 0 • vpn: 1 • user: 2 • router: 3 • wireless: 4 • wad: 5 • endpoint: 7 • ha: 8 • compliance-check: 9 • security_audit: 10
virus: 2	• infected: 11 • blocked: 12 • oversized: 13 • scanerror: 62 • suspicious: 0 • analytics: 1 • switchproto: 63 • mimefragmented: 61 • virus_filetype_exe: 3 • botnet: 2

Log Type IDs	Subtype IDs
webfilter: 3	• content: 14 • urlfilter: 15 • ftgd_blk: 16 • ftgd_allow: 17 • ftgd_err: 18 • url_monitor: 19 • scriptfilter_activex: 35 • scriptfilter_ cookie: 36 • scriptfilter_applet: 37 • ftgd_quota_counting: 38 • ftgd_quota_expired: 39 • ftgd_quota: 40 • scriptfilter_other: 41 • webfilter_command_block: 43
ips: 4	• signature: 19 • malicious_url: 21
antispam: 5	• smtp: 8 • pop3: 9 • imap: 10 • mapi: 11 • endpoint_filter: 47 • mms: 52 • msn: 5 • yahoo: 6 • google: 7 • ftgd_err: 53
anomaly: 7	• anomaly: 20
voip: 8	• viop: 14
dlp: 9	• dlp: 54 • dlp-docsource: 55
app_ctrl: 10	• app-ctrl-all: 59

Log Type IDs	Subtype IDs
WAF: 12	• signature: 0 • custom_signature: 1 • method: 2 • constraints: 3 • address_list: 4 • url_access: 5
GTP: 14	• all: 0
DNS: 15	• dns-query: 0 • dns-response: 1

Log Messages

The following sections list the FortiOS 5.4.7 log messages by log ID number.

Anomaly

18432 - LOGID_ATTCK_ANOMALY_TCP_UDP

Message ID: 18432

Message Description: LOGID_ATTCK_ANOMALY_TCP_UDP

Type: Anomaly

Subtype: ANOMALY

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Event Type	string	32
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36
sessionid	Session ID	uint32	10
severity	Severity	string	8
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User	string	256
vd	Virtual Domain Name	string	32

18433 - LOGID_ATTCK_ANOMALY_ICMP

Message ID: 18433

Message Description: LOGID_ATTCK_ANOMALY_ICMP

Type: Anomaly

Subtype: ANOMALY

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Event Type	string	32
group	User Group Name	string	64
icmpcode	ICMP code	string	6
icmpid	ICMP ID	string	8
icmptype	ICMP Type	string	6
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
severity	Severity	string	8
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User	string	256
vd	Virtual Domain Name	string	32

18434 - LOGID_ATTCK_ANOMALY_OTHERS

Message ID: 18434

Message Description: LOGID_ATTCK_ANOMALY_OTHERS

Type: Anomaly

Subtype: ANOMALY

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36
sessionid	Session ID	uint32	10
severity	Severity	string	8
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User	string	256
vd	Virtual Domain Name	string	32

App

28672 - LOGID_APP_CTRL_IM_BASIC

Message ID: 28672

Message Description: LOGID_APP_CTRL_IM_BASIC

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

28673 - LOGID_APP_CTRL_IM_BASIC_WITH_STATUS

Message ID: 28673

Message Description: LOGID_APP_CTRL_IM_BASIC_WITH_STATUS

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

28674 - LOGID_APP_CTRL_IM_BASIC_WITH_COUNT

Message ID: 28674

Message Description: LOGID_APP_CTRL_IM_BASIC_WITH_COUNT

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32

28675 - LOGID_APP_CTRL_IM_FILE

Message ID: 28675

Message Description: LOGID_APP_CTRL_IM_FILE

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36

Log Field Name	Description	Data Type	Length
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

28676 - LOGID_APP_CTRL_IM_CHAT

Message ID: 28676

Message Description: LOGID_APP_CTRL_IM_CHAT

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

28677 - LOGID_APP_CTRL_IM_CHAT_BLOCK

Message ID: 28677

Message Description: LOGID_APP_CTRL_IM_CHAT_BLOCK

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

28678 - LOGID_APP_CTRL_IM_BLOCK

Message ID: 28678

Message Description: LOGID_APP_CTRL_IM_BLOCK

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

28704 - LOGID_APP_CTRL_IPS_PASS

Message ID: 28704

Message Description: LOGID_APP_CTRL_IPS_PASS

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
appid	Application ID	uint32	10
applist	Application Control profile name	string	64

Log Field Name	Description	Data Type	Length
apprisk	Application risk level	string	16
cloudaction	Action performed by cloud application	string	32
clouduser	User login ID detected by the Deep Application Control feature	string	256
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

28705 - LOGID_APP_CTRL_IPS_BLOCK

Message ID: 28705

Message Description: LOGID_APP_CTRL_IPS_BLOCK

Type: App

Subtype: APP-CTRL-ALL

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
appid	Application ID	uint32	10
applist	Application Control profile name	string	64
apprisk	Application risk level	string	16
cloudaction	Action performed by cloud application	string	32
clouduser	User login ID detected by the Deep Application Control feature	string	256
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32

28706 - LOGID_APP_CTRL_IPS_RESET

Message ID: 28706

Message Description: LOGID_APP_CTRL_IPS_RESET

Type: App

Subtype: APP-CTRL-ALL

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
appid	Application ID	uint32	10
applist	Application Control profile name	string	64
apprisk	Application risk level	string	16
cloudaction	Action performed by cloud application	string	32
clouduser	User login ID detected by the Deep Application Control feature	string	256
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32

Log Field Name	Description	Data Type	Length
filename	File name	string	256
filesize	File size in bytes	uint64	10
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

28720 - LOGID_APP_CTRL_SSH_PASS

Message ID: 28720

Message Description: LOGID_APP_CTRL_SSH_PASS

Type: App

Subtype: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

28721 - LOGID_APP_CTRL_SSH_BLOCK

Message ID: 28721

Message Description: LOGID_APP_CTRL_SSH_BLOCK

Type: App

Subtype: APP-CTRL-ALL

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	App Control Event Type	string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

AV

8192 - MESGID_INFECT_WARNING

Message ID: 8192

Message Description: MESGID_INFECT_WARNING

Type: AV

Subtype: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8193 - MESGID_INFECT_NOTIF

Message ID: 8193

Message Description: MESGID_INFECT_NOTIF

Type: AV

Subtype: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8194 - MESGID_INFECT_MIME_WARNING

Message ID: 8194

Message Description: MESGID_INFECT_MIME_WARNING

Type: AV

Subtype: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8195 - MESGID_INFECT_MIME_NOTIF

Message ID: 8195

Message Description: MESGID_INFECT_MIME_NOTIF

Type: AV

Subtype: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8196 - MESGID_WORM_WARNING

Message ID: 8196

Message Description: MESGID_WORM_WARNING

Type: AV

Subtype: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
vd	VDOM name	string	32
virus	Virus Name	string	128

8197 - MESGID_WORM_NOTIF

Message ID: 8197

Message Description: MESGID_WORM_NOTIF

Type: AV

Subtype: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
vd	VDOM name	string	32
virus	Virus Name	string	128

8198 - MESGID_WORM_MIME_WARNING

Message ID: 8198

Message Description: MESGID_WORM_MIME_WARNING

Type: AV

Subtype: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
vd	VDOM name	string	32
virus	Virus Name	string	128

8199 - MESGID_WORM_MIME_NOTIF

Message ID: 8199

Message Description: MESGID_WORM_MIME_NOTIF

Type: AV

Subtype: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
vd	VDOM name	string	32
virus	Virus Name	string	128

8448 - MESGID_BLOCK_WARNING

Message ID: 8448

Message Description: MESGID_BLOCK_WARNING

Type: AV

Subtype: FILENAME

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8449 - MESGID_BLOCK_NOTIF

Message ID: 8449

Message Description: MESGID_BLOCK_NOTIF

Type: AV

Subtype: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8450 - MESGID_BLOCK_MIME_WARNING

Message ID: 8450

Message Description: MESGID_BLOCK_MIME_WARNING

Type: AV

Subtype: MIMEFRAGMENTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8451 - MESGID_BLOCK_MIME_NOTIF

Message ID: 8451

Message Description: MESGID_BLOCK_MIME_NOTIF

Type: AV

Subtype: MIMEFRAGMENTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8452 - MESGID_BLOCK_COMMAND

Message ID: 8452

Message Description: MESGID_BLOCK_COMMAND

Type: AV

Subtype: FILENAME

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
command	FTP Command info	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8453 - MESGID_INTERCEPT

Message ID: 8453

Message Description: MESGID_INTERCEPT

Type: AV

Subtype: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8454 - MESGID_INTERCEPT_MIME

Message ID: 8454

Message Description: MESGID_INTERCEPT_MIME

Type: AV

Subtype: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8455 - MESGID_EXEMPT

Message ID: 8455

Message Description: MESGID_EXEMPT

Type: AV

Subtype: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8456 - MESGID_EXEMPT_MIME

Message ID: 8456

Message Description: MESGID_EXEMPT_MIME

Type: AV

Subtype: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8457 - MESGID_MMS_CHECKSUM

Message ID: 8457

Message Description: MESGID_MMS_CHECKSUM

Type: AV

Subtype: FILENAME

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filename	File name	string	256

Log Field Name	Description	Data Type	Length
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8458 - MESGID_MMS_CHECKSUM_NOTIF

Message ID: 8458

Message Description: MESGID_MMS_CHECKSUM_NOTIF

Type: AV

Subtype: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8704 - MESGID_OVERSIZE_WARNING

Message ID: 8704

Message Description: MESGID_OVERSIZE_WARNING

Type: AV

Subtype: OVERSIZE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8705 - MESGID_OVERSIZE_NOTIF

Message ID: 8705

Message Description: MESGID_OVERSIZE_NOTIF

Type: AV

Subtype: OVERSIZE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8706 - MESGID_OVERSIZE_MIME_WARNING

Message ID: 8706

Message Description: MESGID_OVERSIZE_MIME_WARNING

Type: AV

Subtype: OVERSIZE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8707 - MESGID_OVERSIZE_MIME_NOTIF

Message ID: 8707

Message Description: MESGID_OVERSIZE_MIME_NOTIF

Type: AV

Subtype: OVERSIZE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8720 - MESGID_SWITCH_PROTO_WARNING

Message ID: 8720

Message Description: MESGID_SWITCH_PROTO_WARNING

Type: AV

Subtype: SWITCHPROTO

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512

Log Field Name	Description	Data Type	Length
user	Username (authentication)	string	256
vd	VDOM name	string	32

8721 - MESGID_SWITCH_PROTO_NOTIF

Message ID: 8721

Message Description: MESGID_SWITCH_PROTO_NOTIF

Type: AV

Subtype: SWITCHPROTO

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event type of AV	string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8960 - MESGID_SCAN_UNCOMPSIZELIMIT_WARNING

Message ID: 8960

Message Description: MESGID_SCAN_UNCOMPSIZELIMIT_WARNING

Type: AV

Subtype: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8961 - MESGID_SCAN_UNCOMPSIZELIMIT_NOTIF

Message ID: 8961

Message Description: MESGID_SCAN_UNCOMPSIZELIMIT_NOTIF

Type: AV

Subtype: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8962 - MESGID_SCAN_ARCHIVE_ENCRYPTED_WARNING

Message ID: 8962

Message Description: MESGID_SCAN_ARCHIVE_ENCRYPTED_WARNING

Type: AV

Subtype: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8963 - MESGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF

Message ID: 8963

Message Description: MESGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF

Type: AV

Subtype: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8964 - MESGID_SCAN_ARCHIVE_CORRUPTED_WARNING

Message ID: 8964

Message Description: MESGID_SCAN_ARCHIVE_CORRUPTED_WARNING

Type: AV

Subtype: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8965 - MESGID_SCAN_ARCHIVE_CORRUPTED_NOTIF

Message ID: 8965

Message Description: MESGID_SCAN_ARCHIVE_CORRUPTED_NOTIF

Type: AV

Subtype: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8966 - MESGID_SCAN_ARCHIVE_MULTIPART_WARNING

Message ID: 8966

Message Description: MESGID_SCAN_ARCHIVE_MULTIPART_WARNING

Type: AV

Subtype: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8967 - MESGID_SCAN_ARCHIVE_MULTIPART_NOTIF

Message ID: 8967

Message Description: MESGID_SCAN_ARCHIVE_MULTIPART_NOTIF

Type: AV

Subtype: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8968 - MESGID_SCAN_ARCHIVE_NESTED_WARNING

Message ID: 8968

Message Description: MESGID_SCAN_ARCHIVE_NESTED_WARNING

Type: AV

Subtype: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8969 - MESGID_SCAN_ARCHIVE_NESTED_NOTIF

Message ID: 8969

Message Description: MESGID_SCAN_ARCHIVE_NESTED_NOTIF

Type: AV

Subtype: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8970 - MESGID_SCAN_ARCHIVE_OVERSIZE_WARNING

Message ID: 8970

Message Description: MESGID_SCAN_ARCHIVE_OVERSIZE_WARNING

Type: AV

Subtype: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8971 - MESGID_SCAN_ARCHIVE_OVERSIZE_NOTIF

Message ID: 8971

Message Description: MESGID_SCAN_ARCHIVE_OVERSIZE_NOTIF

Type: AV

Subtype: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8972 - MESGID_SCAN_ARCHIVE_UNHANDLED_WARNING

Message ID: 8972

Message Description: MESGID_SCAN_ARCHIVE_UNHANDLED_WARNING

Type: AV

Subtype: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8973 - MESGID_SCAN_ARCHIVE_UNHANDLED_NOTIF

Message ID: 8973

Message Description: MESGID_SCAN_ARCHIVE_UNHANDLED_NOTIF

Type: AV

Subtype: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9233 - MESGID_ANALYTICS_SUBMITTED

Message ID: 9233

Message Description: MESGID_ANALYTICS_SUBMITTED

Type: AV

Subtype: ANALYTICS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9234 - MESGID_ANALYTICS_INFECT_WARNING

Message ID: 9234

Message Description: MESGID_ANALYTICS_INFECT_WARNING

Type: AV

Subtype: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9235 - MESGID_ANALYTICS_INFECT_NOTIF

Message ID: 9235

Message Description: MESGID_ANALYTICS_INFECT_NOTIF

Type: AV

Subtype: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9236 - MESGID_ANALYTICS_INFECT_MIME_WARNING

Message ID: 9236

Message Description: MESGID_ANALYTICS_INFECT_MIME_WARNING

Type: AV

Subtype: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9237 - MESGID_ANALYTICS_INFECT_MIME_NOTIF

Message ID: 9237

Message Description: MESGID_ANALYTICS_INFECT_MIME_NOTIF

Type: AV

Subtype: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9238 - MESGID_ANALYTICS_FSA_RESULT

Message ID: 9238

Message Description: MESGID_ANALYTICS_FSA_RESULT

Type: AV

Subtype: ANALYTICS

Severity: Notice

Log Field Name	Description	Data Type	Length
analyticscksum	The checksum of the file submitted for analytics	string	64
date	Date	string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
service	Proxy service which scanned this traffic	string	5
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
type	Log type	string	16
url	The url address	string	512
vd	VDOM name	string	32

9248 - MESGID_BOTNET_WARNING

Message ID: 9248

Message Description: MESGID_BOTNET_WARNING

Type: AV

Subtype: BOTNET

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9249 - MESGID_BOTNET_NOTIF

Message ID: 9249

Message Description: MESGID_BOTNET_NOTIF

Type: AV

Subtype: BOTNET

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

DLP

24576 - LOG_ID_DLP_WARN

Message ID: 24576

Message Description: LOG_ID_DLP_WARN

Type: DLP

Subtype: DLP

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
date	Date	string	10
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtype	DLP event type	string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	128
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

24577 - LOG_ID_DLP_NOTIF

Message ID: 24577

Message Description: LOG_ID_DLP_NOTIF

Type: DLP

Subtype: DLP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
date	Date	string	10
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtype	DLP event type	string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64

Log Field Name	Description	Data Type	Length
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	128
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

24578 - LOG_ID_DLP_DOC_SOURCE

Message ID: 24578

Message Description: LOG_ID_DLP_DOC_SOURCE

Type: DLP

Subtype: DLP

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
dlpextra	DLP extra information	string	256
docsource	DLP fingerprint document source	string	515
eventtype	DLP event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
sensitivity	Sensitivity for document fingerprint	string	36
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
vd	Virtual domain name	string	32

24579 - LOG_ID_DLP_DOC_SOURCE_ERROR

Message ID: 24579

Message Description: LOG_ID_DLP_DOC_SOURCE_ERROR

Type: DLP

Subtype: DLP

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
dlpextra	DLP extra information	string	256
docsource	DLP fingerprint document source	string	515
eventtype	DLP event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
sensitivity	Sensitivity for document fingerprint	string	36
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
vd	Virtual domain name	string	32

Email

20480 - LOGID_ANTISPAM_EMAIL_SMTP_NOTIF

Message ID: 20480

Message Description: LOGID_ANTISPAM_EMAIL_SMTP_NOTIF

Type: Email

Subtype: SMTP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20481 - LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF

Message ID: 20481

Message Description: LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF

Type: Email

Subtype: SMTP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20482 - LOGID_ANTISPAM_EMAIL_POP3_NOTIF

Message ID: 20482

Message Description: LOGID_ANTISPAM_EMAIL_POP3_NOTIF

Type: Email

Subtype: POP3

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32

Log Field Name	Description	Data Type	Length
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20483 - LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF

Message ID: 20483

Message Description: LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF

Type: Email

Subtype: POP3

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20484 - LOGID_ANTISPAM_EMAIL_IMAP_NOTIF

Message ID: 20484

Message Description: LOGID_ANTISPAM_EMAIL_IMAP_NOTIF

Type: Email

Subtype: IMAP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20485 - LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING

Message ID: 20485

Message Description: LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING

Type: Email

Subtype: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20486 - LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF

Message ID: 20486

Message Description: LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF

Type: Email

Subtype: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3

Log Field Name	Description	Data Type	Length
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20487 - LOGID_ANTISPAM_ENDPOINT_MM7_WARNING

Message ID: 20487

Message Description: LOGID_ANTISPAM_ENDPOINT_MM7_WARNING

Type: Email

Subtype: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20488 - LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF

Message ID: 20488

Message Description: LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF

Type: Email

Subtype: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20489 - LOGID_ANTISPAM_ENDPOINT_MM1_WARNING

Message ID: 20489

Message Description: LOGID_ANTISPAM_ENDPOINT_MM1_WARNING

Type: Email

Subtype: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32

Log Field Name	Description	Data Type	Length
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20490 - LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF

Message ID: 20490

Message Description: LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF

Type: Email

Subtype: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20491 - LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF

Message ID: 20491

Message Description: LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF

Type: Email

Subtype: IMAP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20492 - LOGID_ANTISPAM_MM1_FLOOD_WARNING

Message ID: 20492

Message Description: LOGID_ANTISPAM_MM1_FLOOD_WARNING

Type: Email

Subtype: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20493 - LOGID_ANTISPAM_MM1_FLOOD_NOTIF

Message ID: 20493

Message Description: LOGID_ANTISPAM_MM1_FLOOD_NOTIF

Type: Email

Subtype: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3

Log Field Name	Description	Data Type	Length
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20494 - LOGID_ANTISPAM_MM4_FLOOD_WARNING

Message ID: 20494

Message Description: LOGID_ANTISPAM_MM4_FLOOD_WARNING

Type: Email

Subtype: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20495 - LOGID_ANTISPAM_MM4_FLOOD_NOTIF

Message ID: 20495

Message Description: LOGID_ANTISPAM_MM4_FLOOD_NOTIF

Type: Email

Subtype: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20496 - LOGID_ANTISPAM_MM1_DUPE_WARNING

Message ID: 20496

Message Description: LOGID_ANTISPAM_MM1_DUPE_WARNING

Type: Email

Subtype: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32

Log Field Name	Description	Data Type	Length
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20497 - LOGID_ANTISPAM_MM1_DUPE_NOTIF

Message ID: 20497

Message Description: LOGID_ANTISPAM_MM1_DUPE_NOTIF

Type: Email

Subtype: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20498 - LOGID_ANTISPAM_MM4_DUPE_WARNING

Message ID: 20498

Message Description: LOGID_ANTISPAM_MM4_DUPE_WARNING

Type: Email

Subtype: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20499 - LOGID_ANTISPAM_MM4_DUPE_NOTIF

Message ID: 20499

Message Description: LOGID_ANTISPAM_MM4_DUPE_NOTIF

Type: Email

Subtype: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20500 - LOGID_ANTISPAM_EMAIL_MSN_NOTIF

Message ID: 20500

Message Description: LOGID_ANTISPAM_EMAIL_MSN_NOTIF

Type: Email

Subtype: MSN-HOTMAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3

Log Field Name	Description	Data Type	Length
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20501 - LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF

Message ID: 20501

Message Description: LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF

Type: Email

Subtype: YAHOO-MAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20502 - LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF

Message ID: 20502

Message Description: LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF

Type: Email

Subtype: GMAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20503 - LOGID_EMAIL_SMTP_GENERAL_NOTIF

Message ID: 20503

Message Description: LOGID_EMAIL_SMTP_GENERAL_NOTIF

Type: Email

Subtype: SMTP

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32

Log Field Name	Description	Data Type	Length
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20504 - LOGID_EMAIL_POP3_GENERAL_NOTIF

Message ID: 20504

Message Description: LOGID_EMAIL_POP3_GENERAL_NOTIF

Type: Email

Subtype: POP3

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20505 - LOGID_EMAIL_IMAP_GENERAL_NOTIF

Message ID: 20505

Message Description: LOGID_EMAIL_IMAP_GENERAL_NOTIF

Type: Email

Subtype: IMAP

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20506 - LOGID_EMAIL_MAPI_GENERAL_NOTIF

Message ID: 20506

Message Description: LOGID_EMAIL_MAPI_GENERAL_NOTIF

Type: Email

Subtype: MAPI

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20507 - LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF

Message ID: 20507

Message Description: LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF

Type: Email

Subtype: MAPI

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3

Log Field Name	Description	Data Type	Length
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20508 - LOGID_ANTISPAM_EMAIL_MAPI_NOTIF

Message ID: 20508

Message Description: LOGID_ANTISPAM_EMAIL_MAPI_NOTIF

Type: Email

Subtype: MAPI

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

20509 - LOGID_ANTISPAM_FTGD_ERR

Message ID: 20509

Message Description: LOGID_ANTISPAM_FTGD_ERR

Type: Email

Subtype: MAPI

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Email Filter event type	string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	12

Event

20001 - LOG_ID_CLIENT_DISASSOCIATED

Message ID: 20001

Message Description: LOG_ID_CLIENT_DISASSOCIATED

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20002 - LOG_ID_DOMAIN_UNRESOLVABLE

Message ID: 20002

Message Description: LOG_ID_DOMAIN_UNRESOLVABLE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20003 - LOG_ID_MAIL_SENT_FAIL

Message ID: 20003

Message Description: LOG_ID_MAIL_SENT_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20004 - LOG_ID_POLICY_TOO_BIG

Message ID: 20004

Message Description: LOG_ID_POLICY_TOO_BIG

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20005 - LOG_ID_PPP_LINK_UP

Message ID: 20005

Message Description: LOG_ID_PPP_LINK_UP

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20006 - LOG_ID_PPP_LINK_DOWN

Message ID: 20006

Message Description: LOG_ID_PPP_LINK_DOWN

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20007 - 20007

Message ID: 20007

Message Description: 20007

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
proto	Protocol Number	uint8	3
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20008 - LOG_ID_POLICY6_TOO_BIG

Message ID: 20008

Message Description: LOG_ID_POLICY6_TOO_BIG

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20010 - LOG_ID_KERNEL_ERROR

Message ID: 20010

Message Description: LOG_ID_KERNEL_ERROR

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20011 - LOG_ID_CLIENT_NEW_ASSOCIATION

Message ID: 20011

Message Description: LOG_ID_CLIENT_NEW_ASSOCIATION

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20012 - LOG_ID_CLIENT_WPA_1X

Message ID: 20012

Message Description: LOG_ID_CLIENT_WPA_1X

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20013 - LOG_ID_CLIENT_WPA_SSN

Message ID: 20013

Message Description: LOG_ID_CLIENT_WPA_SSN

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20015 - LOG_ID_IEEE802_NEW_STATION

Message ID: 20015

Message Description: LOG_ID_IEEE802_NEW_STATION

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20016 - LOG_ID_MODEM_EXCEED_REDIAL_COUNT

Message ID: 20016

Message Description: LOG_ID_MODEM_EXCEED_REDIAL_COUNT

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20017 - LOG_ID_MODEM_FAIL_TO_OPEN

Message ID: 20017

Message Description: LOG_ID_MODEM_FAIL_TO_OPEN

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20020 - LOG_ID_MODEM_USB_DETECTED

Message ID: 20020

Message Description: LOG_ID_MODEM_USB_DETECTED

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20021 - LOG_ID_MAIL_RESENT

Message ID: 20021

Message Description: LOG_ID_MAIL_RESENT

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20022 - LOG_ID_MODEM_USB_REMOVED

Message ID: 20022

Message Description: LOG_ID_MODEM_USB_REMOVED

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20023 - LOG_ID_MODEM_USBLTE_DETECTED

Message ID: 20023

Message Description: LOG_ID_MODEM_USBLTE_DETECTED

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20024 - LOG_ID_MODEM_USBLTE_REMOVED

Message ID: 20024

Message Description: LOG_ID_MODEM_USBLTE_REMOVED

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20025 - LOG_ID_REPORTD_REPORT_SUCCESS

Message ID: 20025

Message Description: LOG_ID_REPORTD_REPORT_SUCCESS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
datarange	data range for reports	string	50
date	Date	string	10
devid	Device ID	string	16
file	File Name for Generated Report?	string	256
filesize	Report File Size in Bytes	uint32	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
processtime	process time for reports	uint32	
reporttype	Report Type	string	20
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20026 - LOG_ID_REPORTD_REPORT_FAILURE

Message ID: 20026

Message Description: LOG_ID_REPORTD_REPORT_FAILURE

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20027 - LOG_ID_REPORT_DEL_OLD_REC

Message ID: 20027

Message Description: LOG_ID_REPORT_DEL_OLD_REC

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20028 - LOG_ID_REPORT_RECREATE_DB

Message ID: 20028

Message Description: LOG_ID_REPORT_RECREATE_DB

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20031 - LOG_ID_RAD_OUT_OF_MEM

Message ID: 20031

Message Description: LOG_ID_RAD_OUT_OF_MEM

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20032 - LOG_ID_RAD_NOT_FOUND

Message ID: 20032

Message Description: LOG_ID_RAD_NOT_FOUND

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20033 - LOG_ID_RAD_MOBILE_IPV6

Message ID: 20033

Message Description: LOG_ID_RAD_MOBILE_IPV6

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20034 - LOG_ID_RAD_IPV6_OUT_OF_RANGE

Message ID: 20034

Message Description: LOG_ID_RAD_IPV6_OUT_OF_RANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20035 - LOG_ID_RAD_MIN_OUT_OF_RANGE

Message ID: 20035

Message Description: LOG_ID_RAD_MIN_OUT_OF_RANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20036 - LOG_ID_RAD_MAX_OUT_OF_RANGE

Message ID: 20036

Message Description: LOG_ID_RAD_MAX_OUT_OF_RANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20037 - LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE

Message ID: 20037

Message Description: LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20038 - LOG_ID_RAD_MTU_OUT_OF_RANGE

Message ID: 20038

Message Description: LOG_ID_RAD_MTU_OUT_OF_RANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20039 - LOG_ID_RAD_MTU_TOO_SMALL

Message ID: 20039

Message Description: LOG_ID_RAD_MTU_TOO_SMALL

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20040 - LOG_ID_RAD_TIME_TOO_SMALL

Message ID: 20040

Message Description: LOG_ID_RAD_TIME_TOO_SMALL

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20041 - LOG_ID_RAD_HOP_OUT_OF_RANGE

Message ID: 20041

Message Description: LOG_ID_RAD_HOP_OUT_OF_RANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20042 - LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE

Message ID: 20042

Message Description: LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20043 - LOG_ID_RAD_AGENT_OUT_OF_RANGE

Message ID: 20043

Message Description: LOG_ID_RAD_AGENT_OUT_OF_RANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20044 - LOG_ID_RAD_AGENT_FLAG_NOT_SET

Message ID: 20044

Message Description: LOG_ID_RAD_AGENT_FLAG_NOT_SET

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20045 - LOG_ID_RAD_PREFIX_TOO_LONG

Message ID: 20045

Message Description: LOG_ID_RAD_PREFIX_TOO_LONG

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20046 - LOG_ID_RAD_PREF_TIME_TOO_SMALL

Message ID: 20046

Message Description: LOG_ID_RAD_PREF_TIME_TOO_SMALL

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20047 - LOG_ID_RAD_FAIL_IPV6_SOCKET

Message ID: 20047

Message Description: LOG_ID_RAD_FAIL_IPV6_SOCKET

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20048 - LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO

Message ID: 20048

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20049 - LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM

Message ID: 20049

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20050 - LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS

Message ID: 20050

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20051 - LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS

Message ID: 20051

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20052 - LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT

Message ID: 20052

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20053 - LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6

Message ID: 20053

Message Description: LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20054 - LOG_ID_RAD_EXIT_BY_SIGNAL

Message ID: 20054

Message Description: LOG_ID_RAD_EXIT_BY_SIGNAL

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20055 - LOG_ID_RAD_FAIL_CMDB_QUERY

Message ID: 20055

Message Description: LOG_ID_RAD_FAIL_CMDB_QUERY

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20056 - LOG_ID_RAD_FAIL_CMDB_FOR_EACH

Message ID: 20056

Message Description: LOG_ID_RAD_FAIL_CMDB_FOR_EACH

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20057 - LOG_ID_RAD_FAIL_FIND_VIRT_INTF

Message ID: 20057

Message Description: LOG_ID_RAD_FAIL_FIND_VIRT_INTF

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20058 - LOG_ID_RAD_UNLOAD_INTF

Message ID: 20058

Message Description: LOG_ID_RAD_UNLOAD_INTF

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20059 - LOG_ID_RAD_NO_PKT_INFO

Message ID: 20059

Message Description: LOG_ID_RAD_NO_PKT_INFO

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20060 - LOG_ID_RAD_INV_ICMPV6_LEN

Message ID: 20060

Message Description: LOG_ID_RAD_INV_ICMPV6_LEN

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20061 - LOG_ID_RAD_INV_ICMPV6_TYPE

Message ID: 20061

Message Description: LOG_ID_RAD_INV_ICMPV6_TYPE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20062 - LOG_ID_RAD_INV_ICMPV6_RA_LEN

Message ID: 20062

Message Description: LOG_ID_RAD_INV_ICMPV6_RA_LEN

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20063 - LOG_ID_RAD_ICMPV6_NO_SRC_ADDR

Message ID: 20063

Message Description: LOG_ID_RAD_ICMPV6_NO_SRC_ADDR

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20064 - LOG_ID_RAD_INV_ICMPV6_RS_LEN

Message ID: 20064

Message Description: LOG_ID_RAD_INV_ICMPV6_RS_LEN

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20065 - LOG_ID_RAD_INV_ICMPV6_CODE

Message ID: 20065

Message Description: LOG_ID_RAD_INV_ICMPV6_CODE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20066 - LOG_ID_RAD_INV_ICMPV6_HOP

Message ID: 20066

Message Description: LOG_ID_RAD_INV_ICMPV6_HOP

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20067 - LOG_ID_RAD_MISMATCH_HOP

Message ID: 20067

Message Description: LOG_ID_RAD_MISMATCH_HOP

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20068 - LOG_ID_RAD_MISMATCH_MGR_FLAG

Message ID: 20068

Message Description: LOG_ID_RAD_MISMATCH_MGR_FLAG

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20069 - LOG_ID_RAD_MISMATCH_OTH_FLAG

Message ID: 20069

Message Description: LOG_ID_RAD_MISMATCH_OTH_FLAG

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20070 - LOG_ID_RAD_MISMATCH_TIME

Message ID: 20070

Message Description: LOG_ID_RAD_MISMATCH_TIME

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20071 - LOG_ID_RAD_MISMATCH_TIMER

Message ID: 20071

Message Description: LOG_ID_RAD_MISMATCH_TIMER

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20072 - LOG_ID_RAD_EXTRA_DATA

Message ID: 20072

Message Description: LOG_ID_RAD_EXTRA_DATA

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20073 - LOG_ID_RAD_NO_OPT_DATA

Message ID: 20073

Message Description: LOG_ID_RAD_NO_OPT_DATA

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20074 - LOG_ID_RAD_INV_OPT_LEN

Message ID: 20074

Message Description: LOG_ID_RAD_INV_OPT_LEN

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20075 - LOG_ID_RAD_MISMATCH_MTU

Message ID: 20075

Message Description: LOG_ID_RAD_MISMATCH_MTU

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20077 - LOG_ID_RAD_MISMATCH_PREF_TIME

Message ID: 20077

Message Description: LOG_ID_RAD_MISMATCH_PREF_TIME

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20078 - LOG_ID_RAD_INV_OPT

Message ID: 20078

Message Description: LOG_ID_RAD_INV_OPT

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20079 - LOG_ID_RAD_READY

Message ID: 20079

Message Description: LOG_ID_RAD_READY

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20080 - LOG_ID_RAD_FAIL_TO_RCV

Message ID: 20080

Message Description: LOG_ID_RAD_FAIL_TO_RCV

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20081 - LOG_ID_RAD_INV_HOP

Message ID: 20081

Message Description: LOG_ID_RAD_INV_HOP

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20082 - LOG_ID_RAD_INV_PKTINFO

Message ID: 20082

Message Description: LOG_ID_RAD_INV_PKTINFO

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20083 - LOG_ID_RAD_FAIL_TO_CHECK

Message ID: 20083

Message Description: LOG_ID_RAD_FAIL_TO_CHECK

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20084 - LOG_ID_RAD_FAIL_TO_SEND

Message ID: 20084

Message Description: LOG_ID_RAD_FAIL_TO_SEND

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20085 - 20085

Message ID: 20085

Message Description: 20085

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
proto	Protocol Number	uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20086 - 20086

Message ID: 20086

Message Description: 20086

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20090 - LOG_ID_INTF_LINK_STA_CHG

Message ID: 20090

Message Description: LOG_ID_INTF_LINK_STA_CHG

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
intf	Interface	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20099 - LOG_ID_INTF_STA_CHG

Message ID: 20099

Message Description: LOG_ID_INTF_STA_CHG

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20100 - LOG_ID_WEB_CAT_UPDATED

Message ID: 20100

Message Description: LOG_ID_WEB_CAT_UPDATED

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20101 - LOG_ID_WEB_LIC_EXPIRE

Message ID: 20101

Message Description: LOG_ID_WEB_LIC_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20102 - LOG_ID_SPAM_LIC_EXPIRE

Message ID: 20102

Message Description: LOG_ID_SPAM_LIC_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20103 - LOG_ID_AV_LIC_EXPIRE

Message ID: 20103

Message Description: LOG_ID_AV_LIC_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20104 - LOG_ID_IPS_LIC_EXPIRE

Message ID: 20104

Message Description: LOG_ID_IPS_LIC_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20105 - LOG_ID_LOG_UPLOAD_SKIP

Message ID: 20105

Message Description: LOG_ID_LOG_UPLOAD_SKIP

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
error	Error Reason for Log Upload to Forticloud	string	256
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

20107 - LOG_ID_LOG_UPLOAD_ERR

Message ID: 20107

Message Description: LOG_ID_LOG_UPLOAD_ERR

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
error	Error Reason for Log Upload to Forticloud	string	256
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

20108 - LOG_ID_LOG_UPLOAD_DONE

Message ID: 20108

Message Description: LOG_ID_LOG_UPLOAD_DONE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

20109 - LOG_ID_WEB_LIC_EXPIRED

Message ID: 20109

Message Description: LOG_ID_WEB_LIC_EXPIRED

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20110 - LOG_ID_HPAPI_ESPD_START

Message ID: 20110

Message Description: LOG_ID_HPAPI_ESPD_START

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20111 - LOG_ID_HPAPI_ESPD_RESET

Message ID: 20111

Message Description: LOG_ID_HPAPI_ESPD_RESET

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20113 - LOG_ID_IPSA_DOWNLOAD_FAIL

Message ID: 20113

Message Description: LOG_ID_IPSA_DOWNLOAD_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20114 - LOG_ID_IPSA_SELFTEST_FAIL

Message ID: 20114

Message Description: LOG_ID_IPSA_SELFTEST_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20115 - LOG_ID_IPSA_STATUSUPD_FAIL

Message ID: 20115

Message Description: LOG_ID_IPSA_STATUSUPD_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20116 - LOG_ID_SPAM_LIC_EXPIRED

Message ID: 20116

Message Description: LOG_ID_SPAM_LIC_EXPIRED

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20118 - LOG_ID_WEBF_STATUS_REACH

Message ID: 20118

Message Description: LOG_ID_WEBF_STATUS_REACH

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20119 - LOG_ID_WEBF_STATUS_UNREACH

Message ID: 20119

Message Description: LOG_ID_WEBF_STATUS_UNREACH

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20200 - LOG_ID_FIPS_SELF_TEST

Message ID: 20200

Message Description: LOG_ID_FIPS_SELF_TEST

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20201 - LOG_ID_FIPS_SELF_ALL_TEST

Message ID: 20201

Message Description: LOG_ID_FIPS_SELF_ALL_TEST

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20202 - LOG_ID_DISK_FORMAT_ERROR

Message ID: 20202

Message Description: LOG_ID_DISK_FORMAT_ERROR

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20203 - LOG_ID_DAEMON_SHUTDOWN

Message ID: 20203

Message Description: LOG_ID_DAEMON_SHUTDOWN

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20204 - LOG_ID_DAEMON_START

Message ID: 20204

Message Description: LOG_ID_DAEMON_START

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20205 - LOG_ID_DISK_FORMAT_REQ

Message ID: 20205

Message Description: LOG_ID_DISK_FORMAT_REQ

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20206 - LOG_ID_DISK_SCAN_REQ

Message ID: 20206

Message Description: LOG_ID_DISK_SCAN_REQ

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20207 - LOG_ID_RAD_MISMATCH_VALID_TIME

Message ID: 20207

Message Description: LOG_ID_RAD_MISMATCH_VALID_TIME

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20208 - LOG_ID_ZOMBIE_DAEMON_CLEANUP

Message ID: 20208

Message Description: LOG_ID_ZOMBIE_DAEMON_CLEANUP

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20209 - LOG_ID_DISK_UNAVAIL

Message ID: 20209

Message Description: LOG_ID_DISK_UNAVAIL

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20210 - LOG_ID_DISK_TRIM_START

Message ID: 20210

Message Description: LOG_ID_DISK_TRIM_START

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20211 - LOG_ID_DISK_TRIM_END

Message ID: 20211

Message Description: LOG_ID_DISK_TRIM_END

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20220 - 20220

Message ID: 20220

Message Description: 20220

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
intf	Interface	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20221 - 20221

Message ID: 20221

Message Description: 20221

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
intf	Interface	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20300 - LOG_ID_BGP_NB_STAT_CHG

Message ID: 20300

Message Description: LOG_ID_BGP_NB_STAT_CHG

Type: Event

Subtype: ROUTER

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20301 - LOG_ID_VZ_LOG

Message ID: 20301

Message Description: LOG_ID_VZ_LOG

Type: Event

Subtype: ROUTER

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20302 - LOG_ID_OSPF_NB_STAT_CHG

Message ID: 20302

Message Description: LOG_ID_OSPF_NB_STAT_CHG

Type: Event

Subtype: ROUTER

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20303 - LOG_ID_OSPF6_NB_STAT_CHG

Message ID: 20303

Message Description: LOG_ID_OSPF6_NB_STAT_CHG

Type: Event

Subtype: ROUTER

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20401 - LOG_ID_ROUTER_CLEAR

Message ID: 20401

Message Description: LOG_ID_ROUTER_CLEAR

Type: Event

Subtype: ROUTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui		string	64
user		string	256
vd	Virtual Domain Name	string	32

22000 - LOG_ID_INV_PKT_LEN

Message ID: 22000

Message Description: LOG_ID_INV_PKT_LEN

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22001 - LOG_ID_UNSUPPORTED_PROT_VER

Message ID: 22001

Message Description: LOG_ID_UNSUPPORTED_PROT_VER

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22002 - LOG_ID_INV_REQ_TYPE

Message ID: 22002

Message Description: LOG_ID_INV_REQ_TYPE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22003 - LOG_ID_FAIL_SET_SIG_HANDLER

Message ID: 22003

Message Description: LOG_ID_FAIL_SET_SIG_HANDLER

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22004 - LOG_ID_FAIL_CREATE_SOCKET

Message ID: 22004

Message Description: LOG_ID_FAIL_CREATE_SOCKET

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22005 - LOG_ID_FAIL_CREATE_SOCKET_RETRY

Message ID: 22005

Message Description: LOG_ID_FAIL_CREATE_SOCKET_RETRY

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22006 - LOG_ID_FAIL_REG_CMDB_EVENT

Message ID: 22006

Message Description: LOG_ID_FAIL_REG_CMDB_EVENT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22009 - LOG_ID_FAIL_FIND_AV_PROFILE

Message ID: 22009

Message Description: LOG_ID_FAIL_FIND_AV_PROFILE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22010 - LOG_ID_SENDTO_FAIL

Message ID: 22010

Message Description: LOG_ID_SENDTO_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
process	Process	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22011 - LOG_ID_ENTER_MEM_CONSERVE_MODE

Message ID: 22011

Message Description: LOG_ID_ENTER_MEM_CONSERVE_MODE

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
date	Date	string	10
devid	Device ID	string	16
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
service	Name of Service	string	64

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22012 - LOG_ID_LEAVE_MEM_CONSERVE_MODE

Message ID: 22012

Message Description: LOG_ID_LEAVE_MEM_CONSERVE_MODE

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
date	Date	string	10
devid	Device ID	string	16
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
service	Name of Service	string	64
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22013 - 22013

Message ID: 22013

Message Description: 22013

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
poolname	IP Pool Name	string	36
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22014 - 22014

Message ID: 22014

Message Description: 22014

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
poolname	IP Pool Name	string	36
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22015 - 22015

Message ID: 22015

Message Description: 22015

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22016 - 22016

Message ID: 22016

Message Description: 22016

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22017 - LOG_ID_EXCEED_GLOB_RES_LIMIT

Message ID: 22017

Message Description: LOG_ID_EXCEED_GLOB_RES_LIMIT

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22018 - LOG_ID_EXCEED_VD_RES_LIMIT

Message ID: 22018

Message Description: LOG_ID_EXCEED_VD_RES_LIMIT

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22020 - LOG_ID_FAIL_CREATE_HA_SOCKET

Message ID: 22020

Message Description: LOG_ID_FAIL_CREATE_HA_SOCKET

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22021 - LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY

Message ID: 22021

Message Description: LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22100 - LOG_ID_QUAR_DROP_TRAN_JOB

Message ID: 22100

Message Description: LOG_ID_QUAR_DROP_TRAN_JOB

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
fams_pause	Fortinet Analysis and Management Service Pause	uint32	10
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22101 - LOG_ID_QUAR_DROP_TLL_JOB

Message ID: 22101

Message Description: LOG_ID_QUAR_DROP_TLL_JOB

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22102 - LOG_ID_LOG_DISK_FAILURE

Message ID: 22102

Message Description: LOG_ID_LOG_DISK_FAILURE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22103 - LOG_ID_QUAR_DAILY_LIMIT_REACHED

Message ID: 22103

Message Description: LOG_ID_QUAR_DAILY_LIMIT_REACHED

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22104 - LOG_ID_POWER_RESTORE

Message ID: 22104

Message Description: LOG_ID_POWER_RESTORE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unit	Unit	uint32	10
vd	Virtual Domain Name	string	32

22105 - LOG_ID_POWER_FAILURE

Message ID: 22105

Message Description: LOG_ID_POWER_FAILURE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unit	Unit	uint32	10
vd	Virtual Domain Name	string	32

22106 - LOG_ID_POWER_OPTIONAL_NOT_DETECTED

Message ID: 22106

Message Description: LOG_ID_POWER_OPTIONAL_NOT_DETECTED

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22107 - LOG_ID_VOLT_ANOM

Message ID: 22107

Message Description: LOG_ID_VOLT_ANOM

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22108 - LOG_ID_FAN_ANOM

Message ID: 22108

Message Description: LOG_ID_FAN_ANOM

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22109 - LOG_ID_TEMP_TOO_HIGH

Message ID: 22109

Message Description: LOG_ID_TEMP_TOO_HIGH

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22110 - LOG_ID_SPARE_BLOCK_LOW

Message ID: 22110

Message Description: LOG_ID_SPARE_BLOCK_LOW

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22150 - LOG_ID_VOLT_NOM

Message ID: 22150

Message Description: LOG_ID_VOLT_NOM

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22151 - LOG_ID_FAN_NOM

Message ID: 22151

Message Description: LOG_ID_FAN_NOM

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22152 - LOG_ID_TEMP_TOO_LOW

Message ID: 22152

Message Description: LOG_ID_TEMP_TOO_LOW

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22153 - LOG_ID_TEMP_NORM

Message ID: 22153

Message Description: LOG_ID_TEMP_NORM

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22200 - LOG_ID_AUTO_UPT_CERT

Message ID: 22200

Message Description: LOG_ID_AUTO_UPT_CERT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert	Certificate	string	36
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22201 - LOG_ID_AUTO_GEN_CERT

Message ID: 22201

Message Description: LOG_ID_AUTO_GEN_CERT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert	Certificate	string	36
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22203 - LOG_ID_AUTO_GEN_CERT_FAIL

Message ID: 22203

Message Description: LOG_ID_AUTO_GEN_CERT_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22204 - LOG_ID_AUTO_GEN_CERT_PENDING

Message ID: 22204

Message Description: LOG_ID_AUTO_GEN_CERT_PENDING

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22205 - LOG_ID_AUTO_GEN_CERT_SUCC

Message ID: 22205

Message Description: LOG_ID_AUTO_GEN_CERT_SUCC

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22206 - LOG_ID_CRL_EXPIRED

Message ID: 22206

Message Description: LOG_ID_CRL_EXPIRED

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22700 - LOG_ID_IPS_FAIL_OPEN

Message ID: 22700

Message Description: LOG_ID_IPS_FAIL_OPEN

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22701 - LOG_ID_IPS_FAIL_OPEN_END

Message ID: 22701

Message Description: LOG_ID_IPS_FAIL_OPEN_END

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22800 - LOG_ID_SCAN_SERV_FAIL

Message ID: 22800

Message Description: LOG_ID_SCAN_SERV_FAIL

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
mode	Mode	string	12
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22802 - LOG_ID_ENTER_FD_CONSERVE_MODE

Message ID: 22802

Message Description: LOG_ID_ENTER_FD_CONSERVE_MODE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22803 - LOG_ID_LEAVE_FD_CONSERVE_MODE

Message ID: 22803

Message Description: LOG_ID_LEAVE_FD_CONSERVE_MODE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22804 - LOG_ID_LIC_STATUS_CHG

Message ID: 22804

Message Description: LOG_ID_LIC_STATUS_CHG

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22805 - LOG_ID_FAIL_TO_VALIDATE_LIC

Message ID: 22805

Message Description: LOG_ID_FAIL_TO_VALIDATE_LIC

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22806 - LOG_ID_DUP_LIC

Message ID: 22806

Message Description: LOG_ID_DUP_LIC

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22891 - LOG_ID_FLCFGD

Message ID: 22891

Message Description: LOG_ID_FLCFGD

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22900 - LOG_ID_CAPUTP_SESSION

Message ID: 22900

Message Description: LOG_ID_CAPUTP_SESSION

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22901 - LOG_ID_FAZ_CON

Message ID: 22901

Message Description: LOG_ID_FAZ_CON

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22902 - LOG_ID_FAZ_DISCON

Message ID: 22902

Message Description: LOG_ID_FAZ_DISCON

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22903 - LOG_ID_FAZ_CON_ERR

Message ID: 22903

Message Description: LOG_ID_FAZ_CON_ERR

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22913 - LOG_ID_FDS_SRV_DISCON

Message ID: 22913

Message Description: LOG_ID_FDS_SRV_DISCON

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
server	Server IP Address	string	64

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22914 - LOG_ID_FDS_SRV_CHG

Message ID: 22914

Message Description: LOG_ID_FDS_SRV_CHG

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22915 - LOG_ID_FDS_SRV_CON

Message ID: 22915

Message Description: LOG_ID_FDS_SRV_CON

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22916 - LOG_ID_FDS_STATUS

Message ID: 22916

Message Description: LOG_ID_FDS_STATUS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22917 - LOG_ID_FDS_SMS_QUOTA

Message ID: 22917

Message Description: LOG_ID_FDS_SMS_QUOTA

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22918 - LOG_ID_FDS_CTRL_STATUS

Message ID: 22918

Message Description: LOG_ID_FDS_CTRL_STATUS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22921 - LOG_ID_EVENT_ROUTE_INFO_CHANGED

Message ID: 22921

Message Description: LOG_ID_EVENT_ROUTE_INFO_CHANGED

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22922 - LOG_ID_EVENT_LINK_MONITOR_STATUS

Message ID: 22922

Message Description: LOG_ID_EVENT_LINK_MONITOR_STATUS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
interface	Interface	string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
probeproto	Link Monitor Probe Protocol	string	16
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22923 - LOG_ID_EVENT_VWL_LQTY_STATUS

Message ID: 22923

Message Description: LOG_ID_EVENT_VWL_LQTY_STATUS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22924 - LOG_ID_EVENT_VWL_VOLUME_STATUS

Message ID: 22924

Message Description: LOG_ID_EVENT_VWL_VOLUME_STATUS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26001 - LOG_ID_DHCP_ACK

Message ID: 26001

Message Description: LOG_ID_DHCP_ACK

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
hostname	Hostname	string	128
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26002 - LOG_ID_DHCP_RELEASE

Message ID: 26002

Message Description: LOG_ID_DHCP_RELEASE

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
hostname	Hostname	string	128
interface	Interface	string	32
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26003 - LOG_ID_DHCP_STAT

Message ID: 26003

Message Description: LOG_ID_DHCP_STAT

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
interface	Interface	string	32

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

26004 - LOG_ID_DHCP_CLIENT_LEASE

Message ID: 26004

Message Description: LOG_ID_DHCP_CLIENT_LEASE

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26005 - LOG_ID_DHCP_LEASE_USAGE_HIGH

Message ID: 26005

Message Description: LOG_ID_DHCP_LEASE_USAGE_HIGH

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26006 - LOG_ID_DHCP_LEASE_USAGE_FULL

Message ID: 26006

Message Description: LOG_ID_DHCP_LEASE_USAGE_FULL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26007 - LOG_ID_DHCP_BLOCKED_MAC

Message ID: 26007

Message Description: LOG_ID_DHCP_BLOCKED_MAC

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26008 - LOG_ID_DHCP_DDNS_ADD

Message ID: 26008

Message Description: LOG_ID_DHCP_DDNS_ADD

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26009 - LOG_ID_DHCP_DDNS_DELETE

Message ID: 26009

Message Description: LOG_ID_DHCP_DDNS_DELETE

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26010 - LOG_ID_DHCP_DDNS_COMPLETED

Message ID: 26010

Message Description: LOG_ID_DHCP_DDNS_COMPLETED

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26011 - LOG_ID_DHCPV6_REPLY

Message ID: 26011

Message Description: LOG_ID_DHCPV6_REPLY

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
duid		string	128
iaid		uint32	10
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26012 - LOG_ID_DHCPV6_RELEASE

Message ID: 26012

Message Description: LOG_ID_DHCPV6_RELEASE

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
duid		string	128
iaid		uint32	10
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

27001 - LOG_ID_VRRP_STATE_CHG

Message ID: 27001

Message Description: LOG_ID_VRRP_STATE_CHG

Type: Event

Subtype: ROUTER

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29001 - LOG_ID_PPPD_MSG

Message ID: 29001

Message Description: LOG_ID_PPPD_MSG

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
remote	Remote IP Address	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

29002 - LOG_ID_PPPD_AUTH_SUC

Message ID: 29002

Message Description: LOG_ID_PPPD_AUTH_SUC

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
remote	Remote IP Address	ip	39

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

29003 - LOG_ID_PPPD_AUTH_FAIL

Message ID: 29003

Message Description: LOG_ID_PPPD_AUTH_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
remote	Remote IP Address	ip	39
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29009 - LOG_ID_PPPOE_STATUS_REPORT

Message ID: 29009

Message Description: LOG_ID_PPPOE_STATUS_REPORT

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
gateway	gateway ip address for PPPoE status report	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
mtu	Max Transmission Unit Value	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29011 - LOG_ID_PPPD_FAIL_TO_EXEC

Message ID: 29011

Message Description: LOG_ID_PPPD_FAIL_TO_EXEC

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29012 - LOG_ID_PPP_OPT_ERR

Message ID: 29012

Message Description: LOG_ID_PPP_OPT_ERR

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29013 - LOG_ID_PPPD_START

Message ID: 29013

Message Description: LOG_ID_PPPD_START

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29014 - LOG_ID_PPPD_EXIT

Message ID: 29014

Message Description: LOG_ID_PPPD_EXIT

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29015 - LOG_ID_PPP_RCV_BAD_PEER_IP

Message ID: 29015

Message Description: LOG_ID_PPP_RCV_BAD_PEER_IP

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29016 - LOG_ID_PPP_RCV_BAD_LOCAL_IP

Message ID: 29016

Message Description: LOG_ID_PPP_RCV_BAD_LOCAL_IP

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29017 - LOG_ID_PPP_OPT_NOTIF

Message ID: 29017

Message Description: LOG_ID_PPP_OPT_NOTIF

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29020 - LOG_ID_WIRELESS_SET_FAIL

Message ID: 29020

Message Description: LOG_ID_WIRELESS_SET_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29021 - LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED

Message ID: 29021

Message Description: LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
community	Community	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
version	Version	string	64

29022 - LOG_ID_DDNS_UPDATE_FAIL

Message ID: 29022

Message Description: LOG_ID_DDNS_UPDATE_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32001 - LOG_ID_ADMIN_LOGIN_SUCC

Message ID: 32001

Message Description: LOG_ID_ADMIN_LOGIN_SUCC

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32002 - LOG_ID_ADMIN_LOGIN_FAIL

Message ID: 32002

Message Description: LOG_ID_ADMIN_LOGIN_FAIL

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32003 - LOG_ID_ADMIN_LOGOUT

Message ID: 32003

Message Description: LOG_ID_ADMIN_LOGOUT

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32005 - LOG_ID_ADMIN_OVERIDE_VDOM

Message ID: 32005

Message Description: LOG_ID_ADMIN_OVERIDE_VDOM

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32006 - LOG_ID_ADMIN_ENTER_VDOM

Message ID: 32006

Message Description: LOG_ID_ADMIN_ENTER_VDOM

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32007 - LOG_ID_ADMIN_LEFT_VDOM

Message ID: 32007

Message Description: LOG_ID_ADMIN_LEFT_VDOM

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32008 - LOG_ID_VIEW_DISK_LOG_FAIL

Message ID: 32008

Message Description: LOG_ID_VIEW_DISK_LOG_FAIL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32009 - LOG_ID_SYSTEM_START

Message ID: 32009

Message Description: LOG_ID_SYSTEM_START

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32010 - LOG_ID_DISK_LOG_FULL

Message ID: 32010

Message Description: LOG_ID_DISK_LOG_FULL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32011 - LOG_ID_LOG_ROLL

Message ID: 32011

Message Description: LOG_ID_LOG_ROLL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32014 - LOG_ID_CS_LIC_EXPIRE

Message ID: 32014

Message Description: LOG_ID_CS_LIC_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32015 - LOG_ID_DISK_LOG_USAGE

Message ID: 32015

Message Description: LOG_ID_DISK_LOG_USAGE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32016 - LOG_ID_FDS_QUOTA_WARN

Message ID: 32016

Message Description: LOG_ID_FDS_QUOTA_WARN

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32017 - LOG_ID_FDS_DAILY_QUOTA_FULL

Message ID: 32017

Message Description: LOG_ID_FDS_DAILY_QUOTA_FULL

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32018 - LOG_ID_FIPS_ENTER_ERR_MOD

Message ID: 32018

Message Description: LOG_ID_FIPS_ENTER_ERR_MOD

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32019 - LOG_ID_CC_ENTER_ERR_MOD

Message ID: 32019

Message Description: LOG_ID_CC_ENTER_ERR_MOD

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32020 - LOG_ID_SSH_CORRPUT_MAC

Message ID: 32020

Message Description: LOG_ID_SSH_CORRPUT_MAC

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

32021 - LOG_ID_ADMIN_LOGIN_DISABLE

Message ID: 32021

Message Description: LOG_ID_ADMIN_LOGIN_DISABLE

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32022 - LOG_ID_VDOM_ENABLED

Message ID: 32022

Message Description: LOG_ID_VDOM_ENABLED

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32023 - LOG_ID_MEM_LOG_FIRST_FULL

Message ID: 32023

Message Description: LOG_ID_MEM_LOG_FIRST_FULL

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32024 - LOG_ID_ADMIN_PASSWD_EXPIRE

Message ID: 32024

Message Description: LOG_ID_ADMIN_PASSWD_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32027 - LOG_ID_VIEW_DISK_LOG_SUCC

Message ID: 32027

Message Description: LOG_ID_VIEW_DISK_LOG_SUCC

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32028 - LOG_ID_LOG_DEL_DIR

Message ID: 32028

Message Description: LOG_ID_LOG_DEL_DIR

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32029 - LOG_ID_LOG_DEL_FILE

Message ID: 32029

Message Description: LOG_ID_LOG_DEL_FILE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
filesize	Report File Size in Bytes	uint32	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32030 - LOG_ID_SEND_FDS_STAT

Message ID: 32030

Message Description: LOG_ID_SEND_FDS_STAT

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32031 - LOG_ID_VIEW_MEM_LOG_FAIL

Message ID: 32031

Message Description: LOG_ID_VIEW_MEM_LOG_FAIL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32032 - LOG_ID_DISK_DLP_ARCH_FULL

Message ID: 32032

Message Description: LOG_ID_DISK_DLP_ARCH_FULL

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32033 - LOG_ID_DISK_QUAR_FULL

Message ID: 32033

Message Description: LOG_ID_DISK_QUAR_FULL

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32034 - LOG_ID_DISK_REPORT_FULL

Message ID: 32034

Message Description: LOG_ID_DISK_REPORT_FULL

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32035 - LOG_ID_VDOM_DISABLED

Message ID: 32035

Message Description: LOG_ID_VDOM_DISABLED

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32036 - LOG_ID_DISK_IPS_ARCH_FULL

Message ID: 32036

Message Description: LOG_ID_DISK_IPS_ARCH_FULL

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32037 - LOG_ID_DISK_LOG_FIRST_FULL

Message ID: 32037

Message Description: LOG_ID_DISK_LOG_FIRST_FULL

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32038 - LOG_ID_LOG_ROLL_FORTICRON

Message ID: 32038

Message Description: LOG_ID_LOG_ROLL_FORTICRON

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32039 - LOG_ID_VIEW_MEM_LOG_SUCC

Message ID: 32039

Message Description: LOG_ID_VIEW_MEM_LOG_SUCC

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32040 - LOG_ID_REPORT_DELETED

Message ID: 32040

Message Description: LOG_ID_REPORT_DELETED

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32041 - LOG_ID_REPORT_DELETED_GUI

Message ID: 32041

Message Description: LOG_ID_REPORT_DELETED_GUI

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32042 - LOG_ID_MEM_LOG_SECOND_FULL

Message ID: 32042

Message Description: LOG_ID_MEM_LOG_SECOND_FULL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32043 - LOG_ID_MEM_LOG_FINAL_FULL

Message ID: 32043

Message Description: LOG_ID_MEM_LOG_FINAL_FULL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32044 - LOG_ID_LOG_DELETE

Message ID: 32044

Message Description: LOG_ID_LOG_DELETE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32045 - LOG_ID_MGR_LIC_EXPIRE

Message ID: 32045

Message Description: LOG_ID_MGR_LIC_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32046 - LOG_ID_SSL_CORRPUT_MAC

Message ID: 32046

Message Description: LOG_ID_SSL_CORRPUT_MAC

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

32048 - LOG_ID_SCHEDULE_EXPIRE

Message ID: 32048

Message Description: LOG_ID_SCHEDULE_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32049 - LOG_ID_FC_EXPIRE

Message ID: 32049

Message Description: LOG_ID_FC_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32051 - LOG_ID_LOG_UPLOAD

Message ID: 32051

Message Description: LOG_ID_LOG_UPLOAD

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

32086 - LOG_ID_ENTER_TRANSPARENT

Message ID: 32086

Message Description: LOG_ID_ENTER_TRANSPARENT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32087 - LOG_ID_ENTER_NAT

Message ID: 32087

Message Description: LOG_ID_ENTER_NAT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32095 - LOG_ID_GUI_CHG_SUB_MODULE

Message ID: 32095

Message Description: LOG_ID_GUI_CHG_SUB_MODULE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32096 - LOG_ID_GUI_DOWNLOAD_LOG

Message ID: 32096

Message Description: LOG_ID_GUI_DOWNLOAD_LOG

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
file	File Name for Generated Report?	string	256
hash	Hash Value of Downloaded File	string	32
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32100 - LOG_ID_FORTI_TOKEN_SYNC

Message ID: 32100

Message Description: LOG_ID_FORTI_TOKEN_SYNC

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32101 - LOG_ID_LCD_CHG_CONF

Message ID: 32101

Message Description: LOG_ID_LCD_CHG_CONF

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32102 - LOG_ID_CHG_CONFIG

Message ID: 32102

Message Description: LOG_ID_CHG_CONFIG

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Configuration Module Name	string	32
msg	Message Text	string	
submodule	Configuration Sub-Module Name	string	32
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32103 - LOG_ID_NEW_FIRMWARE

Message ID: 32103

Message Description: LOG_ID_NEW_FIRMWARE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32104 - LOG_ID_CHG_CONFIG_GUI

Message ID: 32104

Message Description: LOG_ID_CHG_CONFIG_GUI

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
module	Configuration Module Name	string	32
msg	Message Text	string	
submodule	Configuration Sub-Module Name	string	32
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32105 - LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE

Message ID: 32105

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32106 - LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE

Message ID: 32106

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32107 - LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE

Message ID: 32107

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32108 - LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE

Message ID: 32108

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32109 - LOG_ID_UPD_SIGN_AV_DB

Message ID: 32109

Message Description: LOG_ID_UPD_SIGN_AV_DB

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32110 - LOG_ID_UPD_SIGN_IPS_DB

Message ID: 32110

Message Description: LOG_ID_UPD_SIGN_IPS_DB

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32111 - LOG_ID_UPD_SIGN_AVIPS_DB

Message ID: 32111

Message Description: LOG_ID_UPD_SIGN_AVIPS_DB

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32113 - LOG_ID_UPD_SIGN_SRCVIS_DB

Message ID: 32113

Message Description: LOG_ID_UPD_SIGN_SRCVIS_DB

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32114 - LOG_ID_UPD_SIGN_GEOIP_DB

Message ID: 32114

Message Description: LOG_ID_UPD_SIGN_GEOIP_DB

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32115 - LOG_ID_UPD_SIGN_SERVER_LIST

Message ID: 32115

Message Description: LOG_ID_UPD_SIGN_SERVER_LIST

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32116 - LOG_ID_UPD_SIGN_AVPKG_FAILURE

Message ID: 32116

Message Description: LOG_ID_UPD_SIGN_AVPKG_FAILURE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32117 - LOG_ID_UPD_SIGN_AVPKG_SUCCESS

Message ID: 32117

Message Description: LOG_ID_UPD_SIGN_AVPKG_SUCCESS

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32118 - LOG_ID_UPD_ADMIN_AV_DB

Message ID: 32118

Message Description: LOG_ID_UPD_ADMIN_AV_DB

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32119 - LOG_ID_UPD_SCANUNIT_AV_DB

Message ID: 32119

Message Description: LOG_ID_UPD_SCANUNIT_AV_DB

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32120 - LOG_ID_RPT_ADD_DATASET

Message ID: 32120

Message Description: LOG_ID_RPT_ADD_DATASET

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32122 - LOG_ID_RPT_DEL_DATASET

Message ID: 32122

Message Description: LOG_ID_RPT_DEL_DATASET

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32125 - LOG_ID_RPT_ADD_CHART

Message ID: 32125

Message Description: LOG_ID_RPT_ADD_CHART

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32126 - LOG_ID_RPT_DEL_CHART

Message ID: 32126

Message Description: LOG_ID_RPT_DEL_CHART

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32129 - LOG_ID_ADD_GUEST

Message ID: 32129

Message Description: LOG_ID_ADD_GUEST

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32130 - LOG_ID_CHG_USER

Message ID: 32130

Message Description: LOG_ID_CHG_USER

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
new_status	New Status	string	512
old_status	Original Status	string	512
passwd	Password	string	20
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32131 - LOG_ID_DEL_GUEST

Message ID: 32131

Message Description: LOG_ID_DEL_GUEST

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32132 - LOG_ID_ADD_USER

Message ID: 32132

Message Description: LOG_ID_ADD_USER

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32138 - LOG_ID_REBOOT

Message ID: 32138

Message Description: LOG_ID_REBOOT

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32140 - LOG_ID_TIME_USER_SETTING_CHG

Message ID: 32140

Message Description: LOG_ID_TIME_USER_SETTING_CHG

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32141 - LOG_ID_TIME_NTP_SETTING_CHG

Message ID: 32141

Message Description: LOG_ID_TIME_NTP_SETTING_CHG

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32142 - LOG_ID_BACKUP_CONF

Message ID: 32142

Message Description: LOG_ID_BACKUP_CONF

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32143 - LOG_ID_BACKUP_CONF_BY_SCP

Message ID: 32143

Message Description: LOG_ID_BACKUP_CONF_BY_SCP

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32148 - LOG_ID_GET_CRL

Message ID: 32148

Message Description: LOG_ID_GET_CRL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
crl		string	
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32149 - LOG_ID_COMMAND_FAIL

Message ID: 32149

Message Description: LOG_ID_COMMAND_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32151 - LOG_ID_ADD_IP6_LOCAL_POL

Message ID: 32151

Message Description: LOG_ID_ADD_IP6_LOCAL_POL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32152 - LOG_ID_CHG_IP6_LOCAL_POL

Message ID: 32152

Message Description: LOG_ID_CHG_IP6_LOCAL_POL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32153 - LOG_ID_DEL_IP6_LOCAL_POL

Message ID: 32153

Message Description: LOG_ID_DEL_IP6_LOCAL_POL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32

32155 - LOG_ID_ACT_FTOKEN_REQ

Message ID: 32155

Message Description: LOG_ID_ACT_FTOKEN_REQ

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32156 - LOG_ID_ACT_FTOKEN_SUCC

Message ID: 32156

Message Description: LOG_ID_ACT_FTOKEN_SUCC

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32157 - LOG_ID_SYNC_FTOKEN_SUCC

Message ID: 32157

Message Description: LOG_ID_SYNC_FTOKEN_SUCC

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32158 - LOG_ID_SYNC_FTOKEN_FAIL

Message ID: 32158

Message Description: LOG_ID_SYNC_FTOKEN_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32159 - LOG_ID_ACT_FTOKEN_FAIL

Message ID: 32159

Message Description: LOG_ID_ACT_FTOKEN_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32168 - LOG_ID_REACH_VDOM_LIMIT

Message ID: 32168

Message Description: LOG_ID_REACH_VDOM_LIMIT

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32169 - LOG_ID_ALARM_DLP_DB

Message ID: 32169

Message Description: LOG_ID_ALARM_DLP_DB

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32170 - LOG_ID_ALARM_MSG

Message ID: 32170

Message Description: LOG_ID_ALARM_MSG

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
alarmid	Alarm ID	uint32	10
date	Date	string	10
devid	Device ID	string	16
groupid	User Group ID	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32171 - LOG_ID_ALARM_ACK

Message ID: 32171

Message Description: LOG_ID_ALARM_ACK

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
acktime	Alarm Acknowledge Time	string	24
action	Action	string	32
alarmid	Alarm ID	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32172 - LOG_ID_ADD_IP4_LOCAL_POL

Message ID: 32172

Message Description: LOG_ID_ADD_IP4_LOCAL_POL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32173 - LOG_ID_CHG_IP4_LOCAL_POL

Message ID: 32173

Message Description: LOG_ID_CHG_IP4_LOCAL_POL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32174 - LOG_ID_DEL_IP4_LOCAL_POL

Message ID: 32174

Message Description: LOG_ID_DEL_IP4_LOCAL_POL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32190 - LOG_ID_UPT_INVALID_IMG

Message ID: 32190

Message Description: LOG_ID_UPT_INVALID_IMG

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32191 - LOG_ID_UPT_INVALID_IMG_CC

Message ID: 32191

Message Description: LOG_ID_UPT_INVALID_IMG_CC

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32192 - LOG_ID_UPT_INVALID_IMG_RSA

Message ID: 32192

Message Description: LOG_ID_UPT_INVALID_IMG_RSA

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32193 - LOG_ID_UPT_IMG_RSA

Message ID: 32193

Message Description: LOG_ID_UPT_IMG_RSA

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32194 - LOG_ID_UPT_IMG_FAIL

Message ID: 32194

Message Description: LOG_ID_UPT_IMG_FAIL

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32199 - LOG_ID_RESTORE_IMG_USB

Message ID: 32199

Message Description: LOG_ID_RESTORE_IMG_USB

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32200 - LOG_ID_SHUTDOWN

Message ID: 32200

Message Description: LOG_ID_SHUTDOWN

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32201 - LOG_ID_LOAD_IMG_SUCC

Message ID: 32201

Message Description: LOG_ID_LOAD_IMG_SUCC

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32202 - LOG_ID_RESTORE_IMG

Message ID: 32202

Message Description: LOG_ID_RESTORE_IMG

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32203 - LOG_ID_RESTORE_CONF

Message ID: 32203

Message Description: LOG_ID_RESTORE_CONF

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32204 - LOG_ID_RESTORE_FGD_SVR

Message ID: 32204

Message Description: LOG_ID_RESTORE_FGD_SVR

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32205 - LOG_ID_RESTORE_VDOM_LIC

Message ID: 32205

Message Description: LOG_ID_RESTORE_VDOM_LIC

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32206 - LOG_ID_RESTORE_SCRIPT

Message ID: 32206

Message Description: LOG_ID_RESTORE_SCRIPT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32207 - LOG_ID_RETRIEVE_CONF_LIST

Message ID: 32207

Message Description: LOG_ID_RETRIEVE_CONF_LIST

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32208 - LOG_ID_IMP_PKCS12_CERT

Message ID: 32208

Message Description: LOG_ID_IMP_PKCS12_CERT

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32209 - LOG_ID_RESTORE_USR_DEF_IPS

Message ID: 32209

Message Description: LOG_ID_RESTORE_USR_DEF_IPS

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32210 - LOG_ID_BACKUP_IMG_SUCC

Message ID: 32210

Message Description: LOG_ID_BACKUP_IMG_SUCC

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32211 - LOG_ID_UPLOAD_REVISION

Message ID: 32211

Message Description: LOG_ID_UPLOAD_REVISION

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32212 - LOG_ID_DEL_REVISION

Message ID: 32212

Message Description: LOG_ID_DEL_REVISION

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32213 - LOG_ID_RESTORE_TEMPLATE

Message ID: 32213

Message Description: LOG_ID_RESTORE_TEMPLATE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32214 - LOG_ID_RESTORE_FILE

Message ID: 32214

Message Description: LOG_ID_RESTORE_FILE

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32215 - LOG_ID_UPT_IMG

Message ID: 32215

Message Description: LOG_ID_UPT_IMG

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32217 - LOG_ID_UPD_IPS

Message ID: 32217

Message Description: LOG_ID_UPD_IPS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32218 - LOG_ID_UPD_DLP

Message ID: 32218

Message Description: LOG_ID_UPD_DLP

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32219 - LOG_ID_BACKUP_OUTPUT

Message ID: 32219

Message Description: LOG_ID_BACKUP_OUTPUT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32220 - LOG_ID_BACKUP_COMMAND

Message ID: 32220

Message Description: LOG_ID_BACKUP_COMMAND

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32221 - LOG_ID_UPD_VDOM_LIC

Message ID: 32221

Message Description: LOG_ID_UPD_VDOM_LIC

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32222 - LOG_ID_GLB_SETTING_CHG

Message ID: 32222

Message Description: LOG_ID_GLB_SETTING_CHG

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
new_value	New Virtual Domain Name	string	128
old_value	Original Virtual Domain name	string	128
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32223 - LOG_ID_BACKUP_USER_DEF_IPS

Message ID: 32223

Message Description: LOG_ID_BACKUP_USER_DEF_IPS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32224 - LOG_ID_BACKUP_DISK_LOG

Message ID: 32224

Message Description: LOG_ID_BACKUP_DISK_LOG

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
file	File Name for Generated Report?	string	256
hash	Hash Value of Downloaded File	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32225 - LOG_ID_DEL_ALL_REVISION

Message ID: 32225

Message Description: LOG_ID_DEL_ALL_REVISION

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32226 - LOG_ID_LOAD_IMG_FAIL

Message ID: 32226

Message Description: LOG_ID_LOAD_IMG_FAIL

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32227 - LOG_ID_UPD_DLP_FAIL

Message ID: 32227

Message Description: LOG_ID_UPD_DLP_FAIL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32228 - LOG_ID_LOAD_IMG_FAIL_WRONG_IMG

Message ID: 32228

Message Description: LOG_ID_LOAD_IMG_FAIL_WRONG_IMG

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32229 - LOG_ID_LOAD_IMG_FAIL_NO_RSA

Message ID: 32229

Message Description: LOG_ID_LOAD_IMG_FAIL_NO_RSA

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32230 - LOG_ID_LOAD_IMG_FAIL_INVALID_RSA

Message ID: 32230

Message Description: LOG_ID_LOAD_IMG_FAIL_INVALID_RSA

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32231 - LOG_ID_RESTORE_FGD_SVR_FAIL

Message ID: 32231

Message Description: LOG_ID_RESTORE_FGD_SVR_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32232 - LOG_ID_RESTORE_VDOM_LIC_FAIL

Message ID: 32232

Message Description: LOG_ID_RESTORE_VDOM_LIC_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32233 - LOG_ID_BACKUP_IMG_FAIL

Message ID: 32233

Message Description: LOG_ID_BACKUP_IMG_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32234 - LOG_ID_RESTORE_IMG_INVALID_CC

Message ID: 32234

Message Description: LOG_ID_RESTORE_IMG_INVALID_CC

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32235 - LOG_ID_RESTORE_IMG_FORTIGUARD

Message ID: 32235

Message Description: LOG_ID_RESTORE_IMG_FORTIGUARD

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32236 - LOG_ID_BACKUP_MEM_LOG

Message ID: 32236

Message Description: LOG_ID_BACKUP_MEM_LOG

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32237 - LOG_ID_BACKUP_MEM_LOG_FAIL

Message ID: 32237

Message Description: LOG_ID_BACKUP_MEM_LOG_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32238 - LOG_ID_BACKUP_DISK_LOG_FAIL

Message ID: 32238

Message Description: LOG_ID_BACKUP_DISK_LOG_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32239 - LOG_ID_BACKUP_DISK_LOG_USB

Message ID: 32239

Message Description: LOG_ID_BACKUP_DISK_LOG_USB

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32240 - LOG_ID_SYS_USB_MODE

Message ID: 32240

Message Description: LOG_ID_SYS_USB_MODE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32241 - LOG_ID_BACKUP_DISK_LOG_USB_FAIL

Message ID: 32241

Message Description: LOG_ID_BACKUP_DISK_LOG_USB_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32242 - LOG_ID_UPD_VDOM_LIC_FAIL

Message ID: 32242

Message Description: LOG_ID_UPD_VDOM_LIC_FAIL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32243 - LOG_ID_UPD_IPS_SCP

Message ID: 32243

Message Description: LOG_ID_UPD_IPS_SCP

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32244 - LOG_ID_UPD_IPS_SCP_FAIL

Message ID: 32244

Message Description: LOG_ID_UPD_IPS_SCP_FAIL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32245 - LOG_ID_BACKUP_USER_DEF_IPS_FAIL

Message ID: 32245

Message Description: LOG_ID_BACKUP_USER_DEF_IPS_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32252 - LOG_ID_FACTORY_RESET

Message ID: 32252

Message Description: LOG_ID_FACTORY_RESET

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32253 - LOG_ID_FORMAT_RAID

Message ID: 32253

Message Description: LOG_ID_FORMAT_RAID

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32254 - LOG_ID_ENABLE_RAID

Message ID: 32254

Message Description: LOG_ID_ENABLE_RAID

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32255 - LOG_ID_DISABLE_RAID

Message ID: 32255

Message Description: LOG_ID_DISABLE_RAID

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32300 - LOG_ID_UPLOAD_RPT_IMG

Message ID: 32300

Message Description: LOG_ID_UPLOAD_RPT_IMG

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32301 - LOG_ID_ADD_VDOM

Message ID: 32301

Message Description: LOG_ID_ADD_VDOM

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32302 - LOG_ID_DEL_VDOM

Message ID: 32302

Message Description: LOG_ID_DEL_VDOM

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32400 - LOG_ID_CONF_CHG

Message ID: 32400

Message Description: LOG_ID_CONF_CHG

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32545 - LOG_ID_SYS_RESTART

Message ID: 32545

Message Description: LOG_ID_SYS_RESTART

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32546 - LOG_ID_APPLICATION_CRASH

Message ID: 32546

Message Description: LOG_ID_APPLICATION_CRASH

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32547 - LOG_ID_AUTOSCRIPT_START

Message ID: 32547

Message Description: LOG_ID_AUTOSCRIPT_START

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32548 - LOG_ID_AUTOSCRIPT_STOP

Message ID: 32548

Message Description: LOG_ID_AUTOSCRIPT_STOP

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32561 - LOG_ID_ADMIN_LOGOUT_DISCONNECT

Message ID: 32561

Message Description: LOG_ID_ADMIN_LOGOUT_DISCONNECT

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32562 - LOG_ID_STORE_CONF_FAIL_SPACE

Message ID: 32562

Message Description: LOG_ID_STORE_CONF_FAIL_SPACE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32564 - LOG_ID_RESTORE_CONF_FAIL

Message ID: 32564

Message Description: LOG_ID_RESTORE_CONF_FAIL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32565 - LOG_ID_RESTORE_CONF_BY_MGMT

Message ID: 32565

Message Description: LOG_ID_RESTORE_CONF_BY_MGMT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32566 - LOG_ID_RESTORE_CONF_BY_SCP

Message ID: 32566

Message Description: LOG_ID_RESTORE_CONF_BY_SCP

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32567 - LOG_ID_RESTORE_CONF_BY_USB

Message ID: 32567

Message Description: LOG_ID_RESTORE_CONF_BY_USB

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32568 - LOG_ID_DEL_REVISION_DB

Message ID: 32568

Message Description: LOG_ID_DEL_REVISION_DB

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32569 - LOG_ID_FSW_SWITCH_LOG_EVENT

Message ID: 32569

Message Description: LOG_ID_FSW_SWITCH_LOG_EVENT

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgpath	configuration path	string	128
cpu	CPU Usage	uint8	3
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mem	Memory Usage	uint8	3
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

35001 - LOG_ID_HA_SYNC_VIRDB

Message ID: 35001

Message Description: LOG_ID_HA_SYNC_VIRDB

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35002 - LOG_ID_HA_SYNC_ETDB

Message ID: 35002

Message Description: LOG_ID_HA_SYNC_ETDB

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35003 - LOG_ID_HA_SYNC_EXDB

Message ID: 35003

Message Description: LOG_ID_HA_SYNC_EXDB

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35004 - LOG_ID_HA_SYNC_FLDB

Message ID: 35004

Message Description: LOG_ID_HA_SYNC_FLDB

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35005 - LOG_ID_HA_SYNC_IPS

Message ID: 35005

Message Description: LOG_ID_HA_SYNC_IPS

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35007 - LOG_ID_HA_SYNC_AV

Message ID: 35007

Message Description: LOG_ID_HA_SYNC_AV

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35009 - LOG_ID_HA_SYNC_CID

Message ID: 35009

Message Description: LOG_ID_HA_SYNC_CID

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35010 - LOG_ID_HA_SYNC_UWDB

Message ID: 35010

Message Description: LOG_ID_HA_SYNC_UWDB

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35011 - LOG_ID_HA_SYNC_FAIL

Message ID: 35011

Message Description: LOG_ID_HA_SYNC_FAIL

Type: Event

Subtype: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35012 - LOG_ID_CONF_SYNC_FAIL

Message ID: 35012

Message Description: LOG_ID_CONF_SYNC_FAIL

Type: Event

Subtype: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

36880 - LOG_ID_EVENT_SYSTEM_MAC_HOST_STORE_LIMIT

Message ID: 36880

Message Description: LOG_ID_EVENT_SYSTEM_MAC_HOST_STORE_LIMIT

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37120 - MESGID_NEG_GENERIC_P1_NOTIF

Message ID: 37120

Message Description: MESGID_NEG_GENERIC_P1_NOTIF

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37121 - MESGID_NEG_GENERIC_P1_ERROR

Message ID: 37121

Message Description: MESGID_NEG_GENERIC_P1_ERROR

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37122 - MESGID_NEG_GENERIC_P2_NOTIF

Message ID: 37122

Message Description: MESGID_NEG_GENERIC_P2_NOTIF

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	11
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37123 - MESGID_NEG_GENERIC_P2_ERROR

Message ID: 37123

Message Description: MESGID_NEG_GENERIC_P2_ERROR

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	11
group	User Name Group	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37124 - MESGID_NEG_I_P1_ERROR

Message ID: 37124

Message Description: MESGID_NEG_I_P1_ERROR

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128

Log Field Name	Description	Data Type	Length
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37125 - MESGID_NEG_I_P2_ERROR

Message ID: 37125

Message Description: MESGID_NEG_I_P2_ERROR

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37126 - MESGID_NEG_NO_STATE_ERROR

Message ID: 37126

Message Description: MESGID_NEG_NO_STATE_ERROR

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37127 - MESGID_NEG_PROGRESS_P1_NOTIF

Message ID: 37127

Message Description: MESGID_NEG_PROGRESS_P1_NOTIF

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37128 - MESGID_NEG_PROGRESS_P1_ERROR

Message ID: 37128

Message Description: MESGID_NEG_PROGRESS_P1_ERROR

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37129 - MESGID_NEG_PROGRESS_P2_NOTIF

Message ID: 37129

Message Description: MESGID_NEG_PROGRESS_P2_NOTIF

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37130 - MESGID_NEG_PROGRESS_P2_ERROR

Message ID: 37130

Message Description: MESGID_NEG_PROGRESS_P2_ERROR

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37131 - MESGID_ESP_ERROR

Message ID: 37131

Message Description: MESGID_ESP_ERROR

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37132 - MESGID_ESP_CRITICAL

Message ID: 37132

Message Description: MESGID_ESP_CRITICAL

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37133 - MESGID_INSTALL_SA

Message ID: 37133

Message Description: MESGID_INSTALL_SA

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37134 - MESGID_DELETE_P1_SA

Message ID: 37134

Message Description: MESGID_DELETE_P1_SA

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128

Log Field Name	Description	Data Type	Length
xauthuser	XAuth User Name	string	128

37135 - MESGID_DELETE_P2_SA

Message ID: 37135

Message Description: MESGID_DELETE_P2_SA

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37136 - MESGID_DPD_FAILURE

Message ID: 37136

Message Description: MESGID_DPD_FAILURE

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39

Log Field Name	Description	Data Type	Length
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37137 - MESGID_CONN_FAILURE

Message ID: 37137

Message Description: MESGID_CONN_FAILURE

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37138 - MESGID_CONN_UPDOWN

Message ID: 37138

Message Description: MESGID_CONN_UPDOWN

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37139 - MESGID_P2_UPDOWN

Message ID: 37139

Message Description: MESGID_P2_UPDOWN

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39

Log Field Name	Description	Data Type	Length
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
phase2_name	Phase 2 Name	string	128
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37141 - MESGID_CONN_STATS

Message ID: 37141

Message Description: MESGID_CONN_STATS

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37184 - MESGID_NEG_GENERIC_P1_NOTIF_IKEV2

Message ID: 37184

Message Description: MESGID_NEG_GENERIC_P1_NOTIF_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	

Log Field Name	Description	Data Type	Length
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37185 - MESGID_NEG_GENERIC_P1_ERROR_IKEV2

Message ID: 37185

Message Description: MESGID_NEG_GENERIC_P1_ERROR_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37186 - MESGID_NEG_GENERIC_P2_NOTIF_IKEV2

Message ID: 37186

Message Description: MESGID_NEG_GENERIC_P2_NOTIF_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	11
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37187 - MESGID_NEG_GENERIC_P2_ERROR_IKEV2

Message ID: 37187

Message Description: MESGID_NEG_GENERIC_P2_ERROR_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	11
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37188 - MESGID_NEG_I_P1_ERROR_IKEV2

Message ID: 37188

Message Description: MESGID_NEG_I_P1_ERROR_IKEV2

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37189 - MESGID_NEG_I_P2_ERROR_IKEV2

Message ID: 37189

Message Description: MESGID_NEG_I_P2_ERROR_IKEV2

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37190 - MESGID_NEG_NO_STATE_ERROR_IKEV2

Message ID: 37190

Message Description: MESGID_NEG_NO_STATE_ERROR_IKEV2

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37191 - MESGID_NEG_PROGRESS_P1_NOTIF_IKEV2

Message ID: 37191

Message Description: MESGID_NEG_PROGRESS_P1_NOTIF_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
exch	In SPI	string	14
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64

Log Field Name	Description	Data Type	Length
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37192 - MESGID_NEG_PROGRESS_P1_ERROR_IKEV2

Message ID: 37192

Message Description: MESGID_NEG_PROGRESS_P1_ERROR_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
exch	In SPI	string	14
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37193 - MESGID_NEG_PROGRESS_P2_NOTIF_IKEV2

Message ID: 37193

Message Description: MESGID_NEG_PROGRESS_P2_NOTIF_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
exch	In SPI	string	14
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37194 - MESGID_NEG_PROGRESS_P2_ERROR_IKEV2

Message ID: 37194

Message Description: MESGID_NEG_PROGRESS_P2_ERROR_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
exch	In SPI	string	14
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37195 - MESGID_ESP_ERROR_IKEV2

Message ID: 37195

Message Description: MESGID_ESP_ERROR_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37196 - MESGID_ESP_CRITICAL_IKEV2

Message ID: 37196

Message Description: MESGID_ESP_CRITICAL_IKEV2

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37197 - MESGID_INSTALL_SA_IKEV2

Message ID: 37197

Message Description: MESGID_INSTALL_SA_IKEV2

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37198 - MESGID_DELETE_P1_SA_IKEV2

Message ID: 37198

Message Description: MESGID_DELETE_P1_SA_IKEV2

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128

Log Field Name	Description	Data Type	Length
xauthuser	XAuth User Name	string	128

37199 - MESGID_DELETE_P2_SA_IKEV2

Message ID: 37199

Message Description: MESGID_DELETE_P2_SA_IKEV2

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37200 - MESGID_DPD_FAILURE_IKEV2

Message ID: 37200

Message Description: MESGID_DPD_FAILURE_IKEV2

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39

Log Field Name	Description	Data Type	Length
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37201 - MESGID_CONN_FAILURE_IKEV2

Message ID: 37201

Message Description: MESGID_CONN_FAILURE_IKEV2

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37202 - MESGID_CONN_UPDOWN_IKEV2

Message ID: 37202

Message Description: MESGID_CONN_UPDOWN_IKEV2

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37203 - MESGID_P2_UPDOWN_IKEV2

Message ID: 37203

Message Description: MESGID_P2_UPDOWN_IKEV2

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39

Log Field Name	Description	Data Type	Length
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
phase2_name	Phase 2 Name	string	128
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37204 - MESGID_CONN_STATS_IKEV2

Message ID: 37204

Message Description: MESGID_CONN_STATS_IKEV2

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	128

37888 - MESGID_HA_GROUP_DELETE

Message ID: 37888

Message Description: MESGID_HA_GROUP_DELETE

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37889 - MESGID_VC_DELETE

Message ID: 37889

Message Description: MESGID_VC_DELETE

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37890 - MESGID_VC_MOVE_VDOM

Message ID: 37890

Message Description: MESGID_VC_MOVE_VDOM

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
from_vcluster	source virtual cluster number	uint32	10

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
to_vcluster	destination virtual cluster number	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vdname	vdom name	string	16

37891 - MESGID_VC_ADD_VDOM

Message ID: 37891

Message Description: MESGID_VC_ADD_VDOM

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to_vcluster	destination virtual cluster number	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vdname	vdom name	string	16

37892 - MESGID_VC_MOVE_MEMB_STATE

Message ID: 37892

Message Description: MESGID_VC_MOVE_MEMB_STATE

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37893 - MESGID_VC_DETECT_MEMB_DEAD

Message ID: 37893

Message Description: MESGID_VC_DETECT_MEMB_DEAD

Type: Event

Subtype: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37894 - MESGID_VC_DETECT_MEMB_JOIN

Message ID: 37894

Message Description: MESGID_VC_DETECT_MEMB_JOIN

Type: Event

Subtype: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37895 - MESGID_VC_ADD_HADEV

Message ID: 37895

Message Description: MESGID_VC_ADD_HADEV

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37896 - MESGID_VC_DEL_HADEV

Message ID: 37896

Message Description: MESGID_VC_DEL_HADEV

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37897 - MESGID_HADEV_READY

Message ID: 37897

Message Description: MESGID_HADEV_READY

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37898 - MESGID_HADEV_FAIL

Message ID: 37898

Message Description: MESGID_HADEV_FAIL

Type: Event

Subtype: HA

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37899 - MESGID_HADEV_PEERINFO

Message ID: 37899

Message Description: MESGID_HADEV_PEERINFO

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37900 - MESGID_HBDEV_DELETE

Message ID: 37900

Message Description: MESGID_HBDEV_DELETE

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37901 - MESGID_HBDEV_DOWN

Message ID: 37901

Message Description: MESGID_HBDEV_DOWN

Type: Event

Subtype: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6
hbdn_reason	heartbeat down reason	string	18
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37902 - MESGID_HBDEV_UP

Message ID: 37902

Message Description: MESGID_HBDEV_UP

Type: Event

Subtype: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37903 - MESGID_SYNC_STATUS

Message ID: 37903

Message Description: MESGID_SYNC_STATUS

Type: Event

Subtype: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
sync_status	The sync status with the master	string	11
sync_type	The sync type with the master	string	14
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37904 - MESGID_HA_ACTIVITY

Message ID: 37904

Message Description: MESGID_HA_ACTIVITY

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128
date	Date	string	10
devid	Device ID	string	16
ha-prio	HA Priority	uint8	3
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37905 - MESGID_HA_ENABLE_SET_AS_MASTER

Message ID: 37905

Message Description: MESGID_HA_ENABLE_SET_AS_MASTER

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37906 - MESGID_HA_DISABLE_SET_AS_MASTER

Message ID: 37906

Message Description: MESGID_HA_DISABLE_SET_AS_MASTER

Type: Event

Subtype: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37907 - MESGID_VLAN_HB_UP

Message ID: 37907

Message Description: MESGID_VLAN_HB_UP

Type: Event

Subtype: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37908 - MESGID_VLAN_HB_DOWN

Message ID: 37908

Message Description: MESGID_VLAN_HB_DOWN

Type: Event

Subtype: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37909 - MESGID_VLAN_HB_DOWN_SUM

Message ID: 37909

Message Description: MESGID_VLAN_HB_DOWN_SUM

Type: Event

Subtype: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38010 - LOG_ID_FIPS_ENCRY_FAIL

Message ID: 38010

Message Description: LOG_ID_FIPS_ENCRY_FAIL

Type: Event

Subtype: USER

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38011 - LOG_ID_FIPS_DECRY_FAIL

Message ID: 38011

Message Description: LOG_ID_FIPS_DECRY_FAIL

Type: Event

Subtype: USER

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

38012 - LOG_ID_ENTROPY_TOKEN

Message ID: 38012

Message Description: LOG_ID_ENTROPY_TOKEN

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38031 - LOG_ID_FSSO_LOGON

Message ID: 38031

Message Description: LOG_ID_FSSO_LOGON

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38032 - LOG_ID_FSSO_LOGOFF

Message ID: 38032

Message Description: LOG_ID_FSSO_LOGOFF

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38033 - LOG_ID_FSSO_SVR_STATUS

Message ID: 38033

Message Description: LOG_ID_FSSO_SVR_STATUS

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38400 - LOGID_EVENT_NOTIF_SEND_SUCC

Message ID: 38400

Message Description: LOGID_EVENT_NOTIF_SEND_SUCC

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
duration	Duration	uint32	10
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
profile	Profile Name	string	64
profilegroup	Profile Group Name	string	4
profiletype	Profile Type	string	64
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
to	Recipient Email Addresses for Notification	string	512
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
virus	Virus Name	string	128

38401 - LOGID_EVENT_NOTIF_SEND_FAIL

Message ID: 38401

Message Description: LOGID_EVENT_NOTIF_SEND_FAIL

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
profile	Profile Name	string	64
profilegroup	Profile Group Name	string	4
profiletype	Profile Type	string	64
service	Name of Service	string	64
sess_duration	Session Duration	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
to	Recipient Email Addresses for Notification	string	512
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
virus	Virus Name	string	128

38402 - LOGID_EVENT_NOTIF_DNS_FAIL

Message ID: 38402

Message Description: LOGID_EVENT_NOTIF_DNS_FAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
hostname	Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
profile	Profile Name	string	64
profiletype	Profile Type	string	64
profile_vd	Virtual Domain Name	string	64
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38403 - LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE

Message ID: 38403

Message Description: LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38404 - LOGID_EVENT_NOTIF_HOSTNAME_ERROR

Message ID: 38404

Message Description: LOGID_EVENT_NOTIF_HOSTNAME_ERROR

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
hostname	Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38405 - LOGID_NOTIF_CODE_SENDTO_SMS_PHONE

Message ID: 38405

Message Description: LOGID_NOTIF_CODE_SENDTO_SMS_PHONE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38406 - LOGID_NOTIF_CODE_SENDTO_SMS_TO

Message ID: 38406

Message Description: LOGID_NOTIF_CODE_SENDTO_SMS_TO

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38407 - LOGID_NOTIF_CODE_SENDTO_EMAIL

Message ID: 38407

Message Description: LOGID_NOTIF_CODE_SENDTO_EMAIL

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38408 - LOGID_EVENT_OFTP_SSL_CONNECTED

Message ID: 38408

Message Description: LOGID_EVENT_OFTP_SSL_CONNECTED

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38409 - LOGID_EVENT_OFTP_SSL_DISCONNECTED

Message ID: 38409

Message Description: LOGID_EVENT_OFTP_SSL_DISCONNECTED

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38410 - LOGID_EVENT_OFTP_SSL_FAILED

Message ID: 38410

Message Description: LOGID_EVENT_OFTP_SSL_FAILED

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38411 - LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO

Message ID: 38411

Message Description: LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38412 - LOGID_EVENT_TOKEN_CODE_SENDTO

Message ID: 38412

Message Description: LOGID_EVENT_TOKEN_CODE_SENDTO

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38656 - LOGID_EVENT_RAD_RPT_PROTO_ERROR

Message ID: 38656

Message Description: LOGID_EVENT_RAD_RPT_PROTO_ERROR

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38657 - LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND

Message ID: 38657

Message Description: LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38658 - LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND

Message ID: 38658

Message Description: LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38659 - LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED

Message ID: 38659

Message Description: LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38660 - LOGID_EVENT_RAD_RPT_ACCT_EVENT

Message ID: 38660

Message Description: LOGID_EVENT_RAD_RPT_ACCT_EVENT

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38661 - LOGID_EVENT_RAD_RPT_OTHER

Message ID: 38661

Message Description: LOGID_EVENT_RAD_RPT_OTHER

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38662 - LOGID_EVENT_RAD_STAT_PROTO_ERROR

Message ID: 38662

Message Description: LOGID_EVENT_RAD_STAT_PROTO_ERROR

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38663 - LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND

Message ID: 38663

Message Description: LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38665 - LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED

Message ID: 38665

Message Description: LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38666 - LOGID_EVENT_RAD_STAT_ACCT_EVENT

Message ID: 38666

Message Description: LOGID_EVENT_RAD_STAT_ACCT_EVENT

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38667 - LOGID_EVENT_RAD_STAT_OTHER

Message ID: 38667

Message Description: LOGID_EVENT_RAD_STAT_OTHER

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38668 - LOGID_EVENT_RAD_STAT_EP_BLK

Message ID: 38668

Message Description: LOGID_EVENT_RAD_STAT_EP_BLK

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

39424 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP

Message ID: 39424

Message Description: LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39425 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN

Message ID: 39425

Message Description: LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
rcvdbyte	Received Bytes	uint64	20
reason	Reason	string	256
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39426 - LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL

Message ID: 39426

Message Description: LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39936 - LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS

Message ID: 39936

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
group	User Name Group	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39937 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY

Message ID: 39937

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39938 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS

Message ID: 39938

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39939 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT

Message ID: 39939

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39940 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE

Message ID: 39940

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39941 - LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY

Message ID: 39941

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39942 - LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK

Message ID: 39942

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39943 - LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON

Message ID: 39943

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39944 - LOG_ID_EVENT_SSL_VPN_SESSION_ALERT

Message ID: 39944

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_ALERT

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
desc		string	128
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39945 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL

Message ID: 39945

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39946 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR

Message ID: 39946

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39947 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP

Message ID: 39947

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39948 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN

Message ID: 39948

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
rcvdbyte	Received Bytes	uint64	20
reason	Reason	string	256
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39949 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS

Message ID: 39949

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39950 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG

Message ID: 39950

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39951 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR

Message ID: 39951

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39952 - LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE

Message ID: 39952

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39953 - LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE

Message ID: 39953

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40001 - LOG_ID_PPTP_TUNNEL_UP

Message ID: 40001

Message Description: LOG_ID_PPTP_TUNNEL_UP

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40002 - LOG_ID_PPTP_TUNNEL_DOWN

Message ID: 40002

Message Description: LOG_ID_PPTP_TUNNEL_DOWN

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40003 - LOG_ID_PPTP_TUNNEL_STAT

Message ID: 40003

Message Description: LOG_ID_PPTP_TUNNEL_STAT

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40014 - LOG_ID_PPTP_REACH_MAX_CON

Message ID: 40014

Message Description: LOG_ID_PPTP_REACH_MAX_CON

Type: Event

Subtype: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40017 - LOG_ID_L2TPD_CLIENT_CON_FAIL

Message ID: 40017

Message Description: LOG_ID_L2TPD_CLIENT_CON_FAIL

Type: Event

Subtype: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40019 - LOG_ID_L2TPD_CLIENT_DISCON

Message ID: 40019

Message Description: LOG_ID_L2TPD_CLIENT_DISCON

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40021 - LOG_ID_PPTP_NOT_CONIG

Message ID: 40021

Message Description: LOG_ID_PPTP_NOT_CONIG

Type: Event

Subtype: VPN

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40022 - LOG_ID_PPTP_NO_IP_AVAIL

Message ID: 40022

Message Description: LOG_ID_PPTP_NO_IP_AVAIL

Type: Event

Subtype: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40024 - LOG_ID_PPTP_OUT_MEM

Message ID: 40024

Message Description: LOG_ID_PPTP_OUT_MEM

Type: Event

Subtype: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40034 - LOG_ID_PPTP_START

Message ID: 40034

Message Description: LOG_ID_PPTP_START

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40035 - LOG_ID_PPTP_START_FAIL

Message ID: 40035

Message Description: LOG_ID_PPTP_START_FAIL

Type: Event

Subtype: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40036 - LOG_ID_PPTP_EXIT

Message ID: 40036

Message Description: LOG_ID_PPTP_EXIT

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40037 - LOG_ID_PPTPD_SVR_DISCON

Message ID: 40037

Message Description: LOG_ID_PPTPD_SVR_DISCON

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40038 - LOG_ID_PPTPD_CLIENT_CON

Message ID: 40038

Message Description: LOG_ID_PPTPD_CLIENT_CON

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40039 - LOG_ID_PPTPD_CLIENT_DISCON

Message ID: 40039

Message Description: LOG_ID_PPTPD_CLIENT_DISCON

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40101 - LOG_ID_L2TP_TUNNEL_UP

Message ID: 40101

Message Description: LOG_ID_L2TP_TUNNEL_UP

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40102 - LOG_ID_L2TP_TUNNEL_DOWN

Message ID: 40102

Message Description: LOG_ID_L2TP_TUNNEL_DOWN

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40103 - LOG_ID_L2TP_TUNNEL_STAT

Message ID: 40103

Message Description: LOG_ID_L2TP_TUNNEL_STAT

Type: Event

Subtype: VPN

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40114 - LOG_ID_L2TPD_START

Message ID: 40114

Message Description: LOG_ID_L2TPD_START

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40115 - LOG_ID_L2TPD_EXIT

Message ID: 40115

Message Description: LOG_ID_L2TPD_EXIT

Type: Event

Subtype: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40118 - LOG_ID_L2TPD_CLIENT_CON

Message ID: 40118

Message Description: LOG_ID_L2TPD_CLIENT_CON

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40704 - LOG_ID_EVENT_SYS_PERF

Message ID: 40704

Message Description: LOG_ID_EVENT_SYS_PERF

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
bandwidth	Bandwidth	string	42
cpu	CPU Usage	uint8	3
date	Date	string	10
devid	Device ID	string	16
disk	Disk Usage	uint8	3
disklograte	Disk Log Rate	uint64	20
fazlograte	FortiAnalyzer Logging Rate	uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mem	Memory Usage	uint8	3
msg	Message Text	string	
setuprate	Session Setup Rate	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
totalsession	Total Number of Sessions	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40960 - LOGID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR

Message ID: 40960

Message Description: LOGID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR

Type: Event

Subtype: WAD

Severity: Notice

Log Field Name	Description	Data Type	Length
addr_type	Address Type	string	4
date	Date	string	10
devid	Device ID	string	16
fqdn	Fully Qualified Domain Name	string	256
fwserver_name		string	32
ip		ip	39

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
port	Port Number	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41000 - LOG_ID_UPD_FGT_SUCC

Message ID: 41000

Message Description: LOG_ID_UPD_FGT_SUCC

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41001 - LOG_ID_UPD_FGT_FAIL

Message ID: 41001

Message Description: LOG_ID_UPD_FGT_FAIL

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41002 - LOG_ID_UPD_SRC_VIS

Message ID: 41002

Message Description: LOG_ID_UPD_SRC_VIS

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41003 - LOG_ID_INVALID_UPD_LIC

Message ID: 41003

Message Description: LOG_ID_INVALID_UPD_LIC

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41006 - LOG_ID_UPD_FSA_VIRDB

Message ID: 41006

Message Description: LOG_ID_UPD_FSA_VIRDB

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

41984 - LOG_ID_EVENT_VPN_CERT_LOAD

Message ID: 41984

Message Description: LOG_ID_EVENT_VPN_CERT_LOAD

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41985 - LOG_ID_EVENT_VPN_CERT_REMOVAL

Message ID: 41985

Message Description: LOG_ID_EVENT_VPN_CERT_REMOVAL

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

41986 - LOG_ID_EVENT_VPN_CERT_REGEN

Message ID: 41986

Message Description: LOG_ID_EVENT_VPN_CERT_REGEN

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41987 - LOG_ID_EVENT_VPN_CERT_UPDATE

Message ID: 41987

Message Description: LOG_ID_EVENT_VPN_CERT_UPDATE

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41988 - LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE

Message ID: 41988

Message Description: LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41989 - LOG_ID_EVENT_VPN_CERT_ERR

Message ID: 41989

Message Description: LOG_ID_EVENT_VPN_CERT_ERR

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41990 - LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED

Message ID: 41990

Message Description: LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41991 - LOG_ID_EVENT_VPN_CERT_EXPORT

Message ID: 41991

Message Description: LOG_ID_EVENT_VPN_CERT_EXPORT

Type: Event

Subtype: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	

Log Field Name	Description	Data Type	Length
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

42201 - LOG_ID_NETX_VMX_ATTACH

Message ID: 42201

Message Description: LOG_ID_NETX_VMX_ATTACH

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

42203 - LOG_ID_NETX_VMX_DENIED

Message ID: 42203

Message Description: LOG_ID_NETX_VMX_DENIED

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43008 - LOG_ID_EVENT_AUTH_SUCCESS

Message ID: 43008

Message Description: LOG_ID_EVENT_AUTH_SUCCESS

Type: Event

Subtype: USER

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43009 - LOG_ID_EVENT_AUTH_FAILED

Message ID: 43009

Message Description: LOG_ID_EVENT_AUTH_FAILED

Type: Event

Subtype: USER

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43010 - LOG_ID_EVENT_AUTH_LOCKOUT

Message ID: 43010

Message Description: LOG_ID_EVENT_AUTH_LOCKOUT

Type: Event

Subtype: USER

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43011 - LOG_ID_EVENT_AUTH_TIME_OUT

Message ID: 43011

Message Description: LOG_ID_EVENT_AUTH_TIME_OUT

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43012 - LOG_ID_EVENT_AUTH_FSAE_AUTH_SUCCESS

Message ID: 43012

Message Description: LOG_ID_EVENT_AUTH_FSAE_AUTH_SUCCESS

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43013 - LOG_ID_EVENT_AUTH_FSAE_AUTH_FAIL

Message ID: 43013

Message Description: LOG_ID_EVENT_AUTH_FSAE_AUTH_FAIL

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43014 - LOG_ID_EVENT_AUTH_FSAE_LOGON

Message ID: 43014

Message Description: LOG_ID_EVENT_AUTH_FSAE_LOGON

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43015 - LOG_ID_EVENT_AUTH_FSAE_LOGOFF

Message ID: 43015

Message Description: LOG_ID_EVENT_AUTH_FSAE_LOGOFF

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43016 - LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS

Message ID: 43016

Message Description: LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43017 - LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL

Message ID: 43017

Message Description: LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43018 - LOG_ID_EVENT_AUTH_FGOVRD_FAIL

Message ID: 43018

Message Description: LOG_ID_EVENT_AUTH_FGOVRD_FAIL

Type: Event

Subtype: USER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43020 - LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS

Message ID: 43020

Message Description: LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
expiry	FortiGuard override expiry timestamp	string	64
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
oldwprof	Old Web Filter Profile	string	64
reason	Reason	string	256
scope	FortiGuard Override Scope	string	16
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43025 - LOG_ID_EVENT_AUTH_PROXY_SUCCESS

Message ID: 43025

Message Description: LOG_ID_EVENT_AUTH_PROXY_SUCCESS

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43026 - LOG_ID_EVENT_AUTH_PROXY_FAILED

Message ID: 43026

Message Description: LOG_ID_EVENT_AUTH_PROXY_FAILED

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43027 - LOG_ID_EVENT_AUTH_PROXY_TIME_OUT

Message ID: 43027

Message Description: LOG_ID_EVENT_AUTH_PROXY_TIME_OUT

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43028 - LOG_ID_EVENT_AUTH_PROXY_AUTHORIZATION_FAILED

Message ID: 43028

Message Description: LOG_ID_EVENT_AUTH_PROXY_AUTHORIZATION_FAILED

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43029 - LOG_ID_EVENT_AUTH_WARNING_SUCCESS

Message ID: 43029

Message Description: LOG_ID_EVENT_AUTH_WARNING_SUCCESS

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
expiry	FortiGuard override expiry timestamp	string	64
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
oldwprof	Old Web Filter Profile	string	64
reason	Reason	string	256
scope	FortiGuard Override Scope	string	16
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43030 - LOG_ID_EVENT_AUTH_WARNING_TBL_FULL

Message ID: 43030

Message Description: LOG_ID_EVENT_AUTH_WARNING_TBL_FULL

Type: Event

Subtype: USER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43040 - LOG_ID_EVENT_AUTH_LOGOUT

Message ID: 43040

Message Description: LOG_ID_EVENT_AUTH_LOGOUT

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43041 - LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT

Message ID: 43041

Message Description: LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT

Type: Event

Subtype: USER

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43042 - LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE

Message ID: 43042

Message Description: LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE

Type: Event

Subtype: USER

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43043 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS

Message ID: 43043

Message Description: LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS

Type: Event

Subtype: USER

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43044 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL

Message ID: 43044

Message Description: LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL

Type: Event

Subtype: USER

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43045 - LOG_ID_EVENT_AUTH_8021X_SUCCESS

Message ID: 43045

Message Description: LOG_ID_EVENT_AUTH_8021X_SUCCESS

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
stamac		string	17
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43046 - LOG_ID_EVENT_AUTH_8021X_FAIL

Message ID: 43046

Message Description: LOG_ID_EVENT_AUTH_8021X_FAIL

Type: Event

Subtype: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
stamac		string	17
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43264 - LOGID_MMS_STATS

Message ID: 43264

Message Description: LOGID_MMS_STATS

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
blocked	Blocked MMS	uint32	10

Log Field Name	Description	Data Type	Length
checksum	for MMS Statistics	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
infected	Infected MMS	uint32	10
intercepted	Intercepted MMS	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msgproto	Message Protocol Number	string	16
scanned	Number of Scanned MMSs	uint32	10
subtype	Log Subtype	string	20
suspicious	Number of Suspicious MMSs	uint32	10
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43521 - LOG_ID_EVENT_WIRELESS_ROGUE

Message ID: 43521

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4

Log Field Name	Description	Data Type	Length
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43525 - LOG_ID_EVENT_WIRELESS_ONWIRE

Message ID: 43525

Message Description: LOG_ID_EVENT_WIRELESS_ONWIRE

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10

Log Field Name	Description	Data Type	Length
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43528 - LOG_ID_EVENT_WIRELESS_WTPR_ERROR

Message ID: 43528

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_ERROR

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43530 - LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE

Message ID: 43530

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43531 - LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH

Message ID: 43531

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17

Log Field Name	Description	Data Type	Length
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43532 - LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP

Message ID: 43532

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43533 - LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI

Message ID: 43533

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
frametype	Frame Type	string	32
invalidmac	the MAC address with invalid OUI	string	17
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43534 - LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR

Message ID: 43534

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
ds	direction with distribution system	string	8
duration	Duration of the last threatening packed captured from TA	uint32	10
encrypt	whether the packet is encrypted or not	uint8	3
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43535 - LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV

Message ID: 43535

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
weakwepiv	Weak Wep Initiation Vector	string	8

43542 - LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD

Message ID: 43542

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eapolcnt	EAPOL packet count	uint32	10
eapoltype	EAPOL packet type	string	16
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
sndetected	SN of the AP which detected the rogue AP	string	36

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43544 - LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD

Message ID: 43544

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
manuf	Manufacturer name	string	20
mgmtcnt	The number of unauthorized client flooding managemet frames	uint32	10
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43546 - LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH

Message ID: 43546

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43548 - LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP

Message ID: 43548

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43550 - LOG_ID_EVENT_WIRELESS_STA_LOCATE

Message ID: 43550

Message Description: LOG_ID_EVENT_WIRELESS_STA_LOCATE

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
noise		int8	4
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
signal	Signal	int8	4
sn	Serial Number	string	64
stamac	Station/Client MAC address	string	17

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43551 - LOG_ID_EVENT_WIRELESS_WTP_JOIN

Message ID: 43551

Message Description: LOG_ID_EVENT_WIRELESS_WTP_JOIN

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43552 - LOG_ID_EVENT_WIRELESS_WTP_LEAVE

Message ID: 43552

Message Description: LOG_ID_EVENT_WIRELESS_WTP_LEAVE

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43553 - LOG_ID_EVENT_WIRELESS_WTP_FAIL

Message ID: 43553

Message Description: LOG_ID_EVENT_WIRELESS_WTP_FAIL

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43554 - LOG_ID_EVENT_WIRELESS_WTP_UPDATE

Message ID: 43554

Message Description: LOG_ID_EVENT_WIRELESS_WTP_UPDATE

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43555 - LOG_ID_EVENT_WIRELESS_WTP_RESET

Message ID: 43555

Message Description: LOG_ID_EVENT_WIRELESS_WTP_RESET

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43556 - LOG_ID_EVENT_WIRELESS_WTP_KICK

Message ID: 43556

Message Description: LOG_ID_EVENT_WIRELESS_WTP_KICK

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43557 - LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE

Message ID: 43557

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43558 - LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR

Message ID: 43558

Message Description: LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43559 - LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH

Message ID: 43559

Message Description: LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH

Type: Event

Subtype: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43560 - LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED

Message ID: 43560

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43561 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP

Message ID: 43561

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43562 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN

Message ID: 43562

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43563 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT

Message ID: 43563

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_DETECT

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4

Log Field Name	Description	Data Type	Length
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43564 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR

Message ID: 43564

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10

Log Field Name	Description	Data Type	Length
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43565 - LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR

Message ID: 43565

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43566 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE

Message ID: 43566

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40

Log Field Name	Description	Data Type	Length
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43567 - LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT

Message ID: 43567

Message Description: LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43568 - LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR

Message ID: 43568

Message Description: LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43569 - LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED

Message ID: 43569

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4

Log Field Name	Description	Data Type	Length
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43570 - LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED

Message ID: 43570

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17

Log Field Name	Description	Data Type	Length
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43571 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG

Message ID: 43571

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
level	Log Level	string	11
live	time in seconds	uint32	10

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43572 - LOG_ID_EVENT_WIRELESS_STA_ASSO

Message ID: 43572

Message Description: LOG_ID_EVENT_WIRELESS_STA_ASSO

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43573 - LOG_ID_EVENT_WIRELESS_STA_AUTH

Message ID: 43573

Message Description: LOG_ID_EVENT_WIRELESS_STA_AUTH

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43574 - LOG_ID_EVENT_WIRELESS_STA_DASS

Message ID: 43574

Message Description: LOG_ID_EVENT_WIRELESS_STA_DASS

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43575 - LOG_ID_EVENT_WIRELESS_STA_DAUT

Message ID: 43575

Message Description: LOG_ID_EVENT_WIRELESS_STA_DAUT

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43576 - LOG_ID_EVENT_WIRELESS_STA_IDLE

Message ID: 43576

Message Description: LOG_ID_EVENT_WIRELESS_STA_IDLE

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43577 - LOG_ID_EVENT_WIRELESS_STA_DENY

Message ID: 43577

Message Description: LOG_ID_EVENT_WIRELESS_STA_DENY

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43578 - LOG_ID_EVENT_WIRELESS_STA_KICK

Message ID: 43578

Message Description: LOG_ID_EVENT_WIRELESS_STA_KICK

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43579 - LOG_ID_EVENT_WIRELESS_STA_IP

Message ID: 43579

Message Description: LOG_ID_EVENT_WIRELESS_STA_IP

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43580 - LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP

Message ID: 43580

Message Description: LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43581 - LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN

Message ID: 43581

Message Description: LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43582 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED

Message ID: 43582

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43583 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED

Message ID: 43583

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43584 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE

Message ID: 43584

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43585 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED

Message ID: 43585

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43586 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN

Message ID: 43586

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43587 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START

Message ID: 43587

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43588 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN

Message ID: 43588

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10

Log Field Name	Description	Data Type	Length
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43589 - LOG_ID_EVENT_WIRELESS_WTPR_RADAR

Message ID: 43589

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_RADAR

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43590 - LOG_ID_EVENT_WIRELESS_WTPR_NOL

Message ID: 43590

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_NOL

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43591 - LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS

Message ID: 43591

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43592 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY

Message ID: 43592

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43593 - LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER

Message ID: 43593

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43594 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER

Message ID: 43594

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43595 - LOG_ID_EVENT_WIRELESS_CLB_DENY

Message ID: 43595

Message Description: LOG_ID_EVENT_WIRELESS_CLB_DENY

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

43596 - LOG_ID_EVENT_WIRELESS_CLB_RETRY

Message ID: 43596

Message Description: LOG_ID_EVENT_WIRELESS_CLB_RETRY

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

43597 - LOG_ID_EVENT_WIRELESS_WTP_ADD

Message ID: 43597

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ADD

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43598 - LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS

Message ID: 43598

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43599 - LOG_ID_EVENT_WIRELESS_WTP_DEL

Message ID: 43599

Message Description: LOG_ID_EVENT_WIRELESS_WTP_DEL

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43600 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP

Message ID: 43600

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP

Type: Event

Subtype: WIRELESS

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43601 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON

Message ID: 43601

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43602 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS

Message ID: 43602

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43603 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE

Message ID: 43603

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43604 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST

Message ID: 43604

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43605 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS

Message ID: 43605

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43606 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE

Message ID: 43606

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43607 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK

Message ID: 43607

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43608 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE

Message ID: 43608

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43609 - LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_START

Message ID: 43609

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_START

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43610 - LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_STOP

Message ID: 43610

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_STOP

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43611 - LOG_ID_EVENT_WIRELESS_SYS_AC_UP

Message ID: 43611

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_UP

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43612 - LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED

Message ID: 43612

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43613 - LOG_ID_EVENT_WIRELESS_WTP_ERR

Message ID: 43613

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ERR

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43614 - LOG_ID_EVENT_WIRELESS_DHCP_STAVATION

Message ID: 43614

Message Description: LOG_ID_EVENT_WIRELESS_DHCP_STAVATION

Type: Event

Subtype: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
addr		string	80
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

43776 - LOG_ID_EVENT_NAC_QUARANTINE

Message ID: 43776

Message Description: LOG_ID_EVENT_NAC_QUARANTINE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
admin		string	64
banned_rule	NAC quarantine Banned Rule Name	string	36
banned_src	NAC quarantine Banned Source IP	string	16
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64
duration	Duration	uint32	10
group	User group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
sensor	NAC Sensor Name	string	36
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43777 - LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE

Message ID: 43777

Message Description: LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
admin		string	64
banned_rule	NAC quarantine Banned Rule Name	string	36
banned_src	NAC quarantine Banned Source IP	string	16
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64
duration	Duration	uint32	10
group	User group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
sensor	NAC Sensor Name	string	36
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43800 - LOG_ID_EVENT_ELBC_BLADE_JOIN

Message ID: 43800

Message Description: LOG_ID_EVENT_ELBC_BLADE_JOIN

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43801 - LOG_ID_EVENT_ELBC_BLADE_LEAVE

Message ID: 43801

Message Description: LOG_ID_EVENT_ELBC_BLADE_LEAVE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43802 - LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND

Message ID: 43802

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43803 - LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST

Message ID: 43803

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43804 - LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE

Message ID: 43804

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchassisid	New Chassis ID	uint8	
newslot	New Slot Number	uint8	
oldchassisid	Original Chassis Number	uint8	
oldslot	Original Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43805 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND

Message ID: 43805

Message Description: LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchannel	New Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43806 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST

Message ID: 43806

Message Description: LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
oldchannel	Original Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43807 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE

Message ID: 43807

Message Description: LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchannel	New Channel Number	uint8	
oldchannel	Original Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43808 - LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE

Message ID: 43808

Message Description: LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43809 - LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE

Message ID: 43809

Message Description: LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE

Type: Event

Subtype: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

44544 - LOGID_EVENT_CONFIG_PATH

Message ID: 44544

Message Description: LOGID_EVENT_CONFIG_PATH

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44545 - LOGID_EVENT_CONFIG_OBJ

Message ID: 44545

Message Description: LOGID_EVENT_CONFIG_OBJ

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

44546 - LOGID_EVENT_CONFIG_ATTR

Message ID: 44546

Message Description: LOGID_EVENT_CONFIG_ATTR

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44547 - LOGID_EVENT_CONFIG_OBJATTR

Message ID: 44547

Message Description: LOGID_EVENT_CONFIG_OBJATTR

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44548 - LOGID_EVENT_CONFIG_EXEC

Message ID: 44548

Message Description: LOGID_EVENT_CONFIG_EXEC

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

45000 - LOG_ID_VSD_SSL_RCV_HS

Message ID: 45000

Message Description: LOG_ID_VSD_SSL_RCV_HS

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45001 - LOG_ID_VSD_SSL_RCV_WRG_HS

Message ID: 45001

Message Description: LOG_ID_VSD_SSL_RCV_WRG_HS

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
expectedhandshake	Expected Handshake	string	
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
receivedhandshake	Received Handshake	string	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45002 - LOG_ID_VSD_SSL_SENT_HS

Message ID: 45002

Message Description: LOG_ID_VSD_SSL_SENT_HS

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45003 - LOG_ID_VSD_SSL_WRG_HS_LEN

Message ID: 45003

Message Description: LOG_ID_VSD_SSL_WRG_HS_LEN

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
len	SSL Handshake Message Length	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45004 - LOG_ID_VSD_SSL_RCV_CCS

Message ID: 45004

Message Description: LOG_ID_VSD_SSL_RCV_CCS

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45005 - LOG_ID_VSD_SSL_RSA_DH_FAIL

Message ID: 45005

Message Description: LOG_ID_VSD_SSL_RSA_DH_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45006 - LOG_ID_VSD_SSL_SENT_CCS

Message ID: 45006

Message Description: LOG_ID_VSD_SSL_SENT_CCS

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45007 - LOG_ID_VSD_SSL_BAD_HASH

Message ID: 45007

Message Description: LOG_ID_VSD_SSL_BAD_HASH

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
remote	Remote IP Address	ip	39
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45009 - LOG_ID_VSD_SSL_DECRY_FAIL

Message ID: 45009

Message Description: LOG_ID_VSD_SSL_DECRY_FAIL

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45010 - LOG_ID_VSD_SSL_SESSION_CLOSED

Message ID: 45010

Message Description: LOG_ID_VSD_SSL_SESSION_CLOSED

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45011 - LOG_ID_VSD_SSL_LESS_MINOR

Message ID: 45011

Message Description: LOG_ID_VSD_SSL_LESS_MINOR

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
minminor		uint8	

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
policyid	Policy ID	uint32	10
recvminor		uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45012 - LOG_ID_VSD_SSL_REACH_MAX_CON

Message ID: 45012

Message Description: LOG_ID_VSD_SSL_REACH_MAX_CON

Type: Event

Subtype: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45013 - LOG_ID_VSD_SSL_NOT_SUPPORT_CS

Message ID: 45013

Message Description: LOG_ID_VSD_SSL_NOT_SUPPORT_CS

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45016 - LOG_ID_VSD_SSL_HS_FIN

Message ID: 45016

Message Description: LOG_ID_VSD_SSL_HS_FIN

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45017 - LOG_ID_VSD_SSL_HS_TOO_LONG

Message ID: 45017

Message Description: LOG_ID_VSD_SSL_HS_TOO_LONG

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
len	SSL Handshake Message Length	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
max	Max Value	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45018 - LOG_ID_VSD_SSL_MORE_MINOR

Message ID: 45018

Message Description: LOG_ID_VSD_SSL_MORE_MINOR

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
maxminor		uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
recvminor		uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45019 - LOG_ID_VSD_SSL_SENT_ALERT_ERR

Message ID: 45019

Message Description: LOG_ID_VSD_SSL_SENT_ALERT_ERR

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45020 - LOG_ID_VSD_SSL_SESSION_EXPIRE

Message ID: 45020

Message Description: LOG_ID_VSD_SSL_SESSION_EXPIRE

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
addr	IP Address	string	80
created	Sessions Created	string	64
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
session_id	Session ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45021 - LOG_ID_VSD_SSL_SENT_ALERT

Message ID: 45021

Message Description: LOG_ID_VSD_SSL_SENT_ALERT

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45022 - LOG_ID_VSD_SSL_RCV_CH

Message ID: 45022

Message Description: LOG_ID_VSD_SSL_RCV_CH

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
major	Major Version	uint8	
minor	SSL Minor Version	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10

Log Field Name	Description	Data Type	Length
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
ssl2		uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45023 - LOG_ID_VSD_SSL_RCV_SH

Message ID: 45023

Message Description: LOG_ID_VSD_SSL_RCV_SH

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
cipher	Encryption Type	uint16	
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
major	Major Version	uint8	
minor	SSL Minor Version	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45024 - LOG_ID_VSD_SSL_SENT_SH

Message ID: 45024

Message Description: LOG_ID_VSD_SSL_SENT_SH

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
cipher	Encryption Type	uint16	
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
major	Major Version	uint8	
minor	SSL Minor Version	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45025 - LOG_ID_VSD_SSL_RCV_ALERT

Message ID: 45025

Message Description: LOG_ID_VSD_SSL_RCV_ALERT

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45027 - LOG_ID_VSD_SSL_INVALID_CONT_TYPE

Message ID: 45027

Message Description: LOG_ID_VSD_SSL_INVALID_CONT_TYPE

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45029 - LOG_ID_VSD_SSL_BAD_CCS_LEN

Message ID: 45029

Message Description: LOG_ID_VSD_SSL_BAD_CCS_LEN

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45031 - LOG_ID_VSD_SSL_BAD_DH

Message ID: 45031

Message Description: LOG_ID_VSD_SSL_BAD_DH

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
max	Max Value	uint8	
min	Minimum Value	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
received	Received Packet	uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45032 - LOG_ID_VSD_SSL_PUB_KEY_TOO_BIG

Message ID: 45032

Message Description: LOG_ID_VSD_SSL_PUB_KEY_TOO_BIG

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
len	SSL Handshake Message Length	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
max	Max Value	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45033 - LOG_ID_VSD_SSL_NOT_SUPPORT_CM

Message ID: 45033

Message Description: LOG_ID_VSD_SSL_NOT_SUPPORT_CM

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45034 - LOG_ID_VSD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH

Message ID: 45034

Message Description: LOG_ID_VSD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
received	Received Packet	uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45035 - LOG_ID_VSD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_MISMATCH

Message ID: 45035

Message Description: LOG_ID_VSD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_MISMATCH

Type: Event

Subtype: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
expectedsignature	Expected Signature	uint8	
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
receivedsignature	Received Signature	uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45057 - LOG_ID_FCC_ADD

Message ID: 45057

Message Description: LOG_ID_FCC_ADD

Type: Event

Subtype: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
action	EndPoint Action	string	32

Log Field Name	Description	Data Type	Length
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
ip	Source IP	ip	39
level	Log Level	string	11
license_limit	Maximum Number of FortiClients for the License	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
name	Display Name of the Connection	string	128
status	Status	string	23
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
used_for_type	Connection for the type	uint16	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

45058 - LOG_ID_FCC_CLOSE

Message ID: 45058

Message Description: LOG_ID_FCC_CLOSE

Type: Event

Subtype: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45061 - LOG_ID_FCC_CLOSE_BY_TYPE

Message ID: 45061

Message Description: LOG_ID_FCC_CLOSE_BY_TYPE

Type: Event

Subtype: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
action	EndPoint Action	string	32
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
ip	Source IP	ip	39
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
license_limit	Maximum Number of FortiClients for the License	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
name	Display Name of the Connection	string	128
status	Status	string	23
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
used_for_type	Connection for the type	uint16	5
user	User Name	string	256
vd	Virtual Domain Name	string	32

45071 - LOG_ID_FCC_VULN_SCAN

Message ID: 45071

Message Description: LOG_ID_FCC_VULN_SCAN

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
cveid	CVE ID	string	1024
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
scantime		uint64	20
severity		string	10
srcip		ip	39
srcname		string	64
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vendorurl		string	256
vulncat	Vulnerability Category	string	32
vulnid		uint32	10
vulnname		string	128

45100 - LOG_ID_EC_REG_FAIL_LIMIT

Message ID: 45100

Message Description: LOG_ID_EC_REG_FAIL_LIMIT

Type: Event

Subtype: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45101 - LOG_ID_EC_REG_SUCCEED

Message ID: 45101

Message Description: LOG_ID_EC_REG_SUCCEED

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45102 - LOG_ID_EC_REG_RENEWED

Message ID: 45102

Message Description: LOG_ID_EC_REG_RENEWED

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128

Log Field Name	Description	Data Type	Length
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45103 - LOG_ID_EC_REG_BLOCK

Message ID: 45103

Message Description: LOG_ID_EC_REG_BLOCK

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45104 - LOG_ID_EC_REG_UNBLOCK

Message ID: 45104

Message Description: LOG_ID_EC_REG_UNBLOCK

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45105 - LOG_ID_EC_REG_DEREG

Message ID: 45105

Message Description: LOG_ID_EC_REG_DEREG

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45106 - LOG_ID_EC_REG_LIC_UPGRADED

Message ID: 45106

Message Description: LOG_ID_EC_REG_LIC_UPGRADED

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45107 - LOG_ID_EC_CONF_DISTRIBUTED

Message ID: 45107

Message Description: LOG_ID_EC_CONF_DISTRIBUTED

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45108 - LOG_ID_EC_FTCL_UNREG

Message ID: 45108

Message Description: LOG_ID_EC_FTCL_UNREG

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45109 - LOG_ID_EC_FTCL_LOGOFF

Message ID: 45109

Message Description: LOG_ID_EC_FTCL_LOGOFF

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45110 - LOG_ID_EC_FTCL_ENABLE_NOTSYNC

Message ID: 45110

Message Description: LOG_ID_EC_FTCL_ENABLE_NOTSYNC

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45111 - LOG_ID_EC_REG_SYNC_FAIL

Message ID: 45111

Message Description: LOG_ID_EC_REG_SYNC_FAIL

Type: Event

Subtype: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45112 - LOG_ID_EC_REG_FAIL_KEY

Message ID: 45112

Message Description: LOG_ID_EC_REG_FAIL_KEY

Type: Event

Subtype: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33

Log Field Name	Description	Data Type	Length
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45113 - LOG_ID_EC_REG_FAIL_BLOCKED

Message ID: 45113

Message Description: LOG_ID_EC_REG_FAIL_BLOCKED

Type: Event

Subtype: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
interface	Interface	string	32

Log Field Name	Description	Data Type	Length
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45114 - LOG_ID_EC_REG_QUARANTINE

Message ID: 45114

Message Description: LOG_ID_EC_REG_QUARANTINE

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45115 - LOG_ID_EC_REG_UNQUARANTINE

Message ID: 45115

Message Description: LOG_ID_EC_REG_UNQUARANTINE

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45116 - LOG_ID_EC_REG_UNQUARANTINE_ALL

Message ID: 45116

Message Description: LOG_ID_EC_REG_UNQUARANTINE_ALL

Type: Event

Subtype: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45117 - LOG_ID_EC_REG_FAIL_VER

Message ID: 45117

Message Description: LOG_ID_EC_REG_FAIL_VER

Type: Event

Subtype: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
forticlient_id	Unique FortiClient ID	string	33
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45151 - LOG_ID_EVENT_DSSCC_FAIL

Message ID: 45151

Message Description: LOG_ID_EVENT_DSSCC_FAIL

Type: Event

Subtype: COMPLIANCE-CHECK

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Module	string	32
msg	Log Message	string	
reason	Reason	string	256
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45152 - LOG_ID_EVENT_DSSCC_PASS

Message ID: 45152

Message Description: LOG_ID_EVENT_DSSCC_PASS

Type: Event

Subtype: COMPLIANCE-CHECK

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
module	Module	string	32
msg	Log Message	string	
reason	Reason	string	256
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45161 - LOG_ID_EVENT_DSSCC_EXEC

Message ID: 45161

Message Description: LOG_ID_EVENT_DSSCC_EXEC

Type: Event

Subtype: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

46000 - LOG_ID_VIP_REAL_SVR_ENA

Message ID: 46000

Message Description: LOG_ID_VIP_REAL_SVR_ENA

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46001 - LOG_ID_VIP_REAL_SVR_DISA

Message ID: 46001

Message Description: LOG_ID_VIP_REAL_SVR_DISA

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46002 - LOG_ID_VIP_REAL_SVR_UP

Message ID: 46002

Message Description: LOG_ID_VIP_REAL_SVR_UP

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46003 - LOG_ID_VIP_REAL_SVR_DOWN

Message ID: 46003

Message Description: LOG_ID_VIP_REAL_SVR_DOWN

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46004 - LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN

Message ID: 46004

Message Description: LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN

Type: Event

Subtype: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46005 - LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN

Message ID: 46005

Message Description: LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN

Type: Event

Subtype: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46006 - LOG_ID_VIP_REAL_SVR_FAIL

Message ID: 46006

Message Description: LOG_ID_VIP_REAL_SVR_FAIL

Type: Event

Subtype: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
monitor-name	Health Monitor Type	string	35
monitor-type	Health Monitor Name	string	32
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46400 - LOG_ID_EVENT_EXT_SYS

Message ID: 46400

Message Description: LOG_ID_EVENT_EXT_SYS

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46401 - LOG_ID_EVENT_EXT_LOCAL

Message ID: 46401

Message Description: LOG_ID_EVENT_EXT_LOCAL

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46402 - LOG_ID_EVENT_EXT_REMOTE

Message ID: 46402

Message Description: LOG_ID_EVENT_EXT_REMOTE

Type: Event

Subtype: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

47201 - LOG_ID_AMC_ENTER_BYPASS

Message ID: 47201

Message Description: LOG_ID_AMC_ENTER_BYPASS

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

47202 - LOG_ID_AMC_EXIT_BYPASS

Message ID: 47202

Message Description: LOG_ID_AMC_EXIT_BYPASS

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

47203 - LOG_ID_ENTER_BYPASS

Message ID: 47203

Message Description: LOG_ID_ENTER_BYPASS

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

47204 - LOG_ID_EXIT_BYPASS

Message ID: 47204

Message Description: LOG_ID_EXIT_BYPASS

Type: Event

Subtype: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48000 - LOG_ID_WAD_SSL_RCV_HS

Message ID: 48000

Message Description: LOG_ID_WAD_SSL_RCV_HS

Type: Event

Subtype: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48001 - LOG_ID_WAD_SSL_RCV_WRG_HS

Message ID: 48001

Message Description: LOG_ID_WAD_SSL_RCV_WRG_HS

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48002 - LOG_ID_WAD_SSL_SENT_HS

Message ID: 48002

Message Description: LOG_ID_WAD_SSL_SENT_HS

Type: Event

Subtype: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48003 - LOG_ID_WAD_SSL_WRG_HS_LEN

Message ID: 48003

Message Description: LOG_ID_WAD_SSL_WRG_HS_LEN

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48004 - LOG_ID_WAD_SSL_RCV_CCS

Message ID: 48004

Message Description: LOG_ID_WAD_SSL_RCV_CCS

Type: Event

Subtype: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48005 - LOG_ID_WAD_SSL_RSA_DH_FAIL

Message ID: 48005

Message Description: LOG_ID_WAD_SSL_RSA_DH_FAIL

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48006 - LOG_ID_WAD_SSL_SENT_CCS

Message ID: 48006

Message Description: LOG_ID_WAD_SSL_SENT_CCS

Type: Event

Subtype: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48007 - LOG_ID_WAD_SSL_BAD_HASH

Message ID: 48007

Message Description: LOG_ID_WAD_SSL_BAD_HASH

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
local		ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
remote		ip	39
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48009 - LOG_ID_WAD_SSL_DECRY_FAIL

Message ID: 48009

Message Description: LOG_ID_WAD_SSL_DECRY_FAIL

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48011 - LOG_ID_WAD_SSL_LESS_MINOR

Message ID: 48011

Message Description: LOG_ID_WAD_SSL_LESS_MINOR

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48013 - LOG_ID_WAD_SSL_NOT_SUPPORT_CS

Message ID: 48013

Message Description: LOG_ID_WAD_SSL_NOT_SUPPORT_CS

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48016 - LOG_ID_WAD_SSL_HS_FIN

Message ID: 48016

Message Description: LOG_ID_WAD_SSL_HS_FIN

Type: Event

Subtype: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48017 - LOG_ID_WAD_SSL_HS_TOO_LONG

Message ID: 48017

Message Description: LOG_ID_WAD_SSL_HS_TOO_LONG

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48019 - LOG_ID_WAD_SSL_SENT_ALERT

Message ID: 48019

Message Description: LOG_ID_WAD_SSL_SENT_ALERT

Type: Event

Subtype: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256

Log Field Name	Description	Data Type	Length
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48023 - LOG_ID_WAD_SSL_RCV_ALERT

Message ID: 48023

Message Description: LOG_ID_WAD_SSL_RCV_ALERT

Type: Event

Subtype: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48027 - LOG_ID_WAD_SSL_INVALID_CONT_TYPE

Message ID: 48027

Message Description: LOG_ID_WAD_SSL_INVALID_CONT_TYPE

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48029 - LOG_ID_WAD_SSL_BAD_CCS_LEN

Message ID: 48029

Message Description: LOG_ID_WAD_SSL_BAD_CCS_LEN

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48030 - LOG_ID_WAD_SSL_CLIENT_CERT_REQUEST

Message ID: 48030

Message Description: LOG_ID_WAD_SSL_CLIENT_CERT_REQUEST

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48031 - LOG_ID_WAD_SSL_BAD_DH

Message ID: 48031

Message Description: LOG_ID_WAD_SSL_BAD_DH

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48032 - LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG

Message ID: 48032

Message Description: LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48038 - LOG_ID_WAD_SSL_RCV_FATAL_ALERT

Message ID: 48038

Message Description: LOG_ID_WAD_SSL_RCV_FATAL_ALERT

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48039 - LOG_ID_WAD_SSL_SENT_FATAL_ALERT

Message ID: 48039

Message Description: LOG_ID_WAD_SSL_SENT_FATAL_ALERT

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48100 - LOG_ID_WAD_AUTH_FAIL_CERT

Message ID: 48100

Message Description: LOG_ID_WAD_AUTH_FAIL_CERT

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48101 - LOG_ID_WAD_AUTH_FAIL_PSK

Message ID: 48101

Message Description: LOG_ID_WAD_AUTH_FAIL_PSK

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
authgrp	Authorization Group	string	36

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
host	Host Name	string	256
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48102 - LOG_ID_WAD_AUTH_FAIL_OTH

Message ID: 48102

Message Description: LOG_ID_WAD_AUTH_FAIL_OTH

Type: Event

Subtype: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
authgrp	Authorization Group	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
peer		string	36
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48300 - LOG_ID_WRG_SVR_FGT_CONF

Message ID: 48300

Message Description: LOG_ID_WRG_SVR_FGT_CONF

Type: Event

Subtype: WAD

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48301 - LOG_ID_UNEXP_APP_TYPE

Message ID: 48301

Message Description: LOG_ID_UNEXP_APP_TYPE

Type: Event

Subtype: WAD

Severity: Critical

Log Field Name	Description	Data Type	Length
app-type	Address Type	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

51000 - 51000

Message ID: 51000

Message Description: 51000

Type: Event

Subtype: ROUTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message	string	
service	Name of Service	string	64
srcip		ip	39
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

GTP

41216 - LOGID_GTP_FORWARD

Message ID: 41216

Message Description: LOGID_GTP_FORWARD

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128

Log Field Name	Description	Data Type	Length
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	string	64

41217 - LOGID_GTP_DENY

Message ID: 41217

Message Description: LOGID_GTP_DENY

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3

Log Field Name	Description	Data Type	Length
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	string	64

41218 - LOGID_GTP_RATE_LIMIT

Message ID: 41218

Message Description: LOGID_GTP_RATE_LIMIT

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7

Log Field Name	Description	Data Type	Length
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	string	64

41219 - LOGID_GTP_STATE_INVALID

Message ID: 41219

Message Description: LOGID_GTP_STATE_INVALID

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	string	64

41220 - LOGID_GTP_TUNNEL_LIMIT

Message ID: 41220

Message Description: LOGID_GTP_TUNNEL_LIMIT

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	string	64

41221 - LOGID_GTP_TRAFFIC_COUNT

Message ID: 41221

Message Description: LOGID_GTP_TRAFFIC_COUNT

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-bytes	Control Plane Data Bytes	uint64	20
c-ggsn	Control Plane GGSN IP Address	ip	39
c-ggsn-teid	Control Plane GGSN Tunnel Endpoint Identifier	uint32	10
c-pkts	Control Plane Packets	uint64	20
c-sgsn	Control Plane SGSN IP Address	ip	39
c-sgsn-teid	Control Plane SGSN Tunnel Endpoint Identifier	uint32	10
date	Date	string	10
duration	tunnel duration	uint32	10
end-usr-address	End user IP Address	ip	39
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-bytes	User Plane Data Bytes	uint64	20
u-ggsn	user plane ggsn IP address	ip	39
u-ggsn-teid	user plane ggsn teid	uint32	10
u-pkts	User Plane Packets	uint64	20
u-sgsn	user plane sgsn IP address	ip	39
u-sgsn-teid	user plane sgsn tunnel endpoint identifier	uint32	10
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	string	64

41222 - LOGID_GTP_USER_DATA

Message ID: 41222

Message Description: LOGID_GTP_USER_DATA

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
end-usr-address	End user IP Address	ip	39
from	From	string	128
imsi	International mobile subscriber ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
profile	Profile Name	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
user_data	user traffic content inside gtp-u tunnel	string	256
vd	Virtual Domain Name	string	32
version	Version	string	64

41223 - LOGID_GTPV2_FORWARD

Message ID: 41223

Message Description: LOGID_GTPV2_FORWARD

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

41224 - LOGID_GTPV2_DENY

Message ID: 41224

Message Description: LOGID_GTPV2_DENY

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64

Log Field Name	Description	Data Type	Length
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

41225 - LOGID_GTPV2_RATE_LIMIT

Message ID: 41225

Message Description: LOGID_GTPV2_RATE_LIMIT

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

41226 - LOGID_GTPV2_STATE_INVALID

Message ID: 41226

Message Description: LOGID_GTPV2_STATE_INVALID

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14

Log Field Name	Description	Data Type	Length
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

41227 - LOGID_GTPV2_TUNNEL_LIMIT

Message ID: 41227

Message Description: LOGID_GTPV2_TUNNEL_LIMIT

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39

Log Field Name	Description	Data Type	Length
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

41228 - LOGID_GTPV2_TRAFFIC_COUNT

Message ID: 41228

Message Description: LOGID_GTPV2_TRAFFIC_COUNT

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-bytes	Control Plane Data Bytes	uint64	20
c-pkts	Control Plane Packets	uint64	20
cpdladdr	Control Plane Downlink IP Address	ip	39
cpdlisraddr	Control Plane ISR Downlink IP Address	ip	39
cpdlisrteid	control plane ISR downlink tunnel endpoint identifier	uint32	10
cpdlteid	control plane downlink tunnel endpoint identifier	uint32	10
cpuladdr	control plane uplink IP address	ip	39
cpulteid	control plane uplink teid	uint32	10
date	Date	string	10
duration	tunnel duration	uint32	10
end-usr-address	End user IP Address	ip	39
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14

Log Field Name	Description	Data Type	Length
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-bytes	User Plane Data Bytes	uint64	20
u-pkts	User Plane Packets	uint64	20
vd	Virtual Domain Name	string	32
version	Version	string	64

41229 - LOGID_GTPU_FORWARD

Message ID: 41229

Message Description: LOGID_GTPU_FORWARD

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
dstport	Destination Port	uint16	5
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

41230 - LOGID_GTPU_DENY

Message ID: 41230

Message Description: LOGID_GTPU_DENY

Type: GTP

Subtype: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
from	From	string	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	string	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

IPS

16384 - LOGID_ATTCK_SIGNATURE_TCP_UDP

Message ID: 16384

Message Description: LOGID_ATTCK_SIGNATURE_TCP_UDP

Type: IPS

Subtype: SIGNATURE

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	IPS Event Type	string	32
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
ref	URL of the FortiGuard IPS database entry for the attack.	string	
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

16385 - LOGID_ATTCK_SIGNATURE_ICMP

Message ID: 16385

Message Description: LOGID_ATTCK_SIGNATURE_ICMP

Type: IPS

Subtype: SIGNATURE

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
eventtype	IPS Event Type	string	32
group	User group name	string	64
icmpcode	Destination Port of the ICMP message	string	6
icmpid	Source port of the ICMP message	string	8
icmptype	The type of ICMP message	string	6
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
ref	URL of the FortiGuard IPS database entry for the attack.	string	
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

16386 - LOGID_ATTCK_SIGNATURE_OTHERS

Message ID: 16386

Message Description: LOGID_ATTCK_SIGNATURE_OTHERS

Type: IPS

Subtype: SIGNATURE

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstip	Destination IP	ip	39
eventtype	IPS Event Type	string	32
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64

Log Field Name	Description	Data Type	Length
proto	Protocol number	uint8	3
ref	URL of the FortiGuard IPS database entry for the attack.	string	
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srcintf	Source Interface	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

Traffic

10 - LOG_ID_TRAFFIC_EXPLICIT_PROXY

Message ID: 10

Message Description: LOG_ID_TRAFFIC_EXPLICIT_PROXY

Type: Traffic

Subtype: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64

Log Field Name	Description	Data Type	Length
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
dstcountry	Country name for the destination IP	string	64
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslexempt		string	11
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vwpvlanid		uint32	10

Log Field Name	Description	Data Type	Length
wanin	WAN incoming traffic in bytes	uint32	10
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint32	10

12 - LOG_ID_TRAFFIC_MULTICAST

Message ID: 12

Message Description: LOG_ID_TRAFFIC_MULTICAST

Type: Traffic

Subtype: MULTICAST

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10

Log Field Name	Description	Data Type	Length
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32

Log Field Name	Description	Data Type	Length
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

13 - LOG_ID_TRAFFIC_END_FORWARD

Message ID: 13

Message Description: LOG_ID_TRAFFIC_END_FORWARD

Type: Traffic

Subtype: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
centralnatid	Central NAT ID	uint32	10
collectedemail	Email address from Email Collection Captive Portal	string	66
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countemail	Number of the email logs associated with the session	uint32	10

Log Field Name	Description	Data Type	Length
countips	Number of the IPS logs associated with the session	uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policymode		string	8
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37

Log Field Name	Description	Data Type	Length
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslexempt		string	11
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16

Log Field Name	Description	Data Type	Length
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwpvlanid		uint32	10

14 - LOG_ID_TRAFFIC_END_LOCAL

Message ID: 14

Message Description: LOG_ID_TRAFFIC_END_LOCAL

Type: Traffic

Subtype: LOCAL

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16

Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
poluuid	UUID of the Firewall Policy	string	37

Log Field Name	Description	Data Type	Length
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39

Log Field Name	Description	Data Type	Length
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

15 - LOG_ID_TRAFFIC_START_FORWARD

Message ID: 15

Message Description: LOG_ID_TRAFFIC_START_FORWARD

Type: Traffic

Subtype: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10

Log Field Name	Description	Data Type	Length
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
centralnatid	Central NAT ID	uint32	10
collectedemail	Email address from Email Collection Captive Portal	string	66
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37

Log Field Name	Description	Data Type	Length
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39

Log Field Name	Description	Data Type	Length
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwpvlanid		uint32	10

16 - LOG_ID_TRAFFIC_START_LOCAL

Message ID: 16

Message Description: LOG_ID_TRAFFIC_START_LOCAL

Type: Traffic

Subtype: LOCAL

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64

Log Field Name	Description	Data Type	Length
apprisk	Application Risk Level	string	16
centralnatid	Central NAT ID	uint32	10
collectedemail	Email address from Email Collection Captive Portal	string	66
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5

Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

17 - LOG_ID_TRAFFIC_SNIFFER

Message ID: 17

Message Description: LOG_ID_TRAFFIC_SNIFFER

Type: Traffic

Subtype: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66

Log Field Name	Description	Data Type	Length
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66

Log Field Name	Description	Data Type	Length
policyid	Firewall Policy ID	uint32	10
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

19 - LOG_ID_TRAFFIC_BROADCAST

Message ID: 19

Message Description: LOG_ID_TRAFFIC_BROADCAST

Type: Traffic

Subtype: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96

Log Field Name	Description	Data Type	Length
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

2 - LOG_ID_TRAFFIC_ALLOW

Message ID: 2

Message Description: LOG_ID_TRAFFIC_ALLOW

Type: Traffic

Subtype: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16

Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policytype		string	24

Log Field Name	Description	Data Type	Length
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwpvlanid		uint32	10

8 - LOG_ID_TRAFFIC_WANOPT

Message ID: 8

Message Description: LOG_ID_TRAFFIC_WANOPT

Type: Traffic

Subtype: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
countapp	Number of App Ctrl logs associated with the session	uint32	10

Log Field Name	Description	Data Type	Length
countav	Number of AV logs associated with the session	uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
dstcountry	Country name for the destination IP	string	64
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslexempt		string	11
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint32	10
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint32	10

9 - LOG_ID_TRAFFIC_WEBCACHE

Message ID: 9

Message Description: LOG_ID_TRAFFIC_WEBCACHE

Type: Traffic

Subtype: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
dstcountry	Country name for the destination IP	string	64
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	64

Log Field Name	Description	Data Type	Length
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslexempt		string	11
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint32	10
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint32	10

VoIP

44032 - LOGID_EVENT_VOIP_SIP

Message ID: 44032

Message Description: LOGID_EVENT_VOIP_SIP

Type: VoIP

Subtype: GENERAL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	15
call_id	Call ID	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
dstip	Destination IP	ip	39
dst_int	Destination Interface	string	16
dst_port	Destination Port	uint16	5
duration	Duration	uint32	10

Log Field Name	Description	Data Type	Length
epoch		uint32	10
event_id	Event ID	uint32	10
from	From	string	128
kind		string	10
level	Log Level	string	11
logid	Log ID	string	10
policy_id	Policy ID	uint32	10
profile	Profile Name	string	64
proto	Protocol	uint8	3
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
src_int	Source Interface	string	16
src_port	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to		string	512
type	Log Type	string	16
vd	Virtual Domain Name	string	32
voip_proto	VoIP Protocol	string	4

44033 - LOGID_EVENT_VOIP_SIP_BLOCK

Message ID: 44033

Message Description: LOGID_EVENT_VOIP_SIP_BLOCK

Type: VoIP

Subtype: GENERAL

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	15
call_id	Call ID	string	64
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
dstip	Destination IP	ip	39
dst_int	Destination Interface	string	16
dst_port	Destination Port	uint16	5
duration	Duration	uint32	10
epoch		uint32	10
event_id	Event ID	uint32	10
from	From	string	128
kind		string	10
level	Log Level	string	11
logid	Log ID	string	10
message_type	Message Type	string	16
policy_id	Policy ID	uint32	10
profile	Profile Name	string	64
proto	Protocol	uint8	3
reason	Reason	string	128
request_name	Request Name	string	64
session_id	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
src_int	Source Interface	string	16
src_port	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to		string	512
type	Log Type	string	16
vd	Virtual Domain Name	string	32
voip_proto	VoIP Protocol	string	4

44034 - LOGID_EVENT_VOIP_SIP_FUZZING

Message ID: 44034

Message Description: LOGID_EVENT_VOIP_SIP_FUZZING

Type: VoIP

Subtype: GENERAL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	15
call_id	Call ID	string	64
column		uint32	10
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dst_int	Destination Interface	string	16
dst_port	Destination Port	uint16	5
duration	Duration	uint32	10
epoch		uint32	10
event_id	Event ID	uint32	10
kind		string	10
level	Log Level	string	11
line		string	128
logid	Log ID	string	10
malform_data	Malformed data	uint32	10
malform_desc	Malformed data Description	string	47
message_type	Message Type	string	16
policy_id	Policy ID	uint32	10
profile	Profile Name	string	64
proto	Protocol	uint8	3
request_name	Request Name	string	64
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
src_int	Source Interface	string	16
src_port	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
voip_proto	VoIP Protocol	string	4

44035 - LOGID_EVENT_VOIP_SCCP_REGISTER

Message ID: 44035

Message Description: LOGID_EVENT_VOIP_SCCP_REGISTER

Type: VoIP

Subtype: GENERAL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	15
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dst_port	Destination Port	uint16	5
epoch		uint32	10
event_id	Event ID	uint32	10
kind		string	10
level	Log Level	string	11
locip	Local IP	ip	39
logid	Log ID	string	10
phone		string	64
policy_id	Policy ID	uint32	10
profile	Profile Name	string	64
proto	Protocol	uint8	3
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
src_int	Source Interface	string	16
src_port	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
voip_proto	VoIP Protocol	string	4

44036 - LOGID_EVENT_VOIP_SCCP_UNREGISTER

Message ID: 44036

Message Description: LOGID_EVENT_VOIP_SCCP_UNREGISTER

Type: VoIP

Subtype: GENERAL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	15
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dst_port	Destination Port	uint16	5
epoch		uint32	10
event_id	Event ID	uint32	10
kind		string	10
level	Log Level	string	11
locip	Local IP	ip	39
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
phone		string	64
policy_id	Policy ID	uint32	10
profile	Profile Name	string	64
proto	Protocol	uint8	3
reason	Reason	string	128
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
src_int	Source Interface	string	16
src_port	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
voip_proto	VoIP Protocol	string	4

44037 - LOGID_EVENT_VOIP_SCCP_CALL_BLOCK

Message ID: 44037

Message Description: LOGID_EVENT_VOIP_SCCP_CALL_BLOCK

Type: VoIP

Subtype: GENERAL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	15
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
dst_port	Destination Port	uint16	5
epoch		uint32	10
event_id	Event ID	uint32	10
kind		string	10
level	Log Level	string	11
locip	Local IP	ip	39
logid	Log ID	string	10
phone		string	64
policy_id	Policy ID	uint32	10
profile	Profile Name	string	64
proto	Protocol	uint8	3
reason	Reason	string	128
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
src_int	Source Interface	string	16
src_port	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
voip_proto	VoIP Protocol	string	4

44038 - LOGID_EVENT_VOIP_SCCP_CALL_INFO

Message ID: 44038

Message Description: LOGID_EVENT_VOIP_SCCP_CALL_INFO

Type: VoIP

Subtype: GENERAL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	15
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dst_int	Destination Interface	string	16
dst_port	Destination Port	uint16	5
duration	Duration	uint32	10
epoch		uint32	10
event_id	Event ID	uint32	10
kind		string	10
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logid	Log ID	string	10
phone		string	64
policy_id	Policy ID	uint32	10
profile	Profile Name	string	64
proto	Protocol	uint8	3
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
remport	Remote Port	uint16	5
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
src_int	Source Interface	string	16
src_port	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
voip_proto	VoIP Protocol	string	4

WAF

30248 - LOGID_WAF_SIGNATURE_BLOCK

Message ID: 30248

Message Description: LOGID_WAF_SIGNATURE_BLOCK

Type: WAF

Subtype: WAF-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url	URL	string	512

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

30249 - LOGID_WAF_SIGNATURE_PASS

Message ID: 30249

Message Description: LOGID_WAF_SIGNATURE_PASS

Type: WAF

Subtype: WAF-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30250 - LOGID_WAF_SIGNATURE_ERASE

Message ID: 30250

Message Description: LOGID_WAF_SIGNATURE_ERASE

Type: WAF

Subtype: WAF-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30251 - LOGID_WAF_CUSTOM_SIGNATURE_BLOCK

Message ID: 30251

Message Description: LOGID_WAF_CUSTOM_SIGNATURE_BLOCK

Type: WAF

Subtype: WAF-CUSTOM-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event Type	string	32
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30252 - LOGID_WAF_CUSTOM_SIGNATURE_PASS

Message ID: 30252

Message Description: LOGID_WAF_CUSTOM_SIGNATURE_PASS

Type: WAF

Subtype: WAF-CUSTOM-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30253 - LOGID_WAF_METHOD_BLOCK

Message ID: 30253

Message Description: LOGID_WAF_METHOD_BLOCK

Type: WAF

Subtype: WAF-HTTP-METHOD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
method	Http Method	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30255 - LOGID_WAF_ADDRESS_LIST_BLOCK

Message ID: 30255

Message Description: LOGID_WAF_ADDRESS_LIST_BLOCK

Type: WAF

Subtype: WAF-ADDRESS-LIST

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30257 - LOGID_WAF_CONSTRAINTS_BLOCK

Message ID: 30257

Message Description: LOGID_WAF_CONSTRAINTS_BLOCK

Type: WAF

Subtype: WAF-HTTP-CONSTRAINT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
constraint	WAF http protocol restrictions	string	
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30258 - LOGID_WAF_CONSTRAINTS_PASS

Message ID: 30258

Message Description: LOGID_WAF_CONSTRAINTS_PASS

Type: WAF

Subtype: WAF-HTTP-CONSTRAINT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
constraint	WAF http protocol restrictions	string	
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30259 - LOGID_WAF_URL_ACCESS_PERMIT

Message ID: 30259

Message Description: LOGID_WAF_URL_ACCESS_PERMIT

Type: WAF

Subtype: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtype	Event Type	string	32
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30260 - LOGID_WAF_URL_ACCESS_BYPASS

Message ID: 30260

Message Description: LOGID_WAF_URL_ACCESS_BYPASS

Type: WAF

Subtype: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtype	Event Type	string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30261 - LOGID_WAF_URL_ACCESS_BLOCK

Message ID: 30261

Message Description: LOGID_WAF_URL_ACCESS_BLOCK

Type: WAF

Subtype: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtype	Event Type	string	32
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

Web

12288 - LOG_ID_WEB_CONTENT_BANWORD

Message ID: 12288

Message Description: LOG_ID_WEB_CONTENT_BANWORD

Type: Web

Subtype: CONTENT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12289 - LOG_ID_WEB_CONTENT_MMS_BANWORD

Message ID: 12289

Message Description: LOG_ID_WEB_CONTENT_MMS_BANWORD

Type: Web

Subtype: CONTENT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12290 - LOG_ID_WEB_CONTENT_EXEMPTWORD

Message ID: 12290

Message Description: LOG_ID_WEB_CONTENT_EXEMPTWORD

Type: Web

Subtype: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
url	The URL address	string	512

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32

12291 - LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD

Message ID: 12291

Message Description: LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD

Type: Web

Subtype: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12292 - LOG_ID_WEB_CONTENT_KEYWORD

Message ID: 12292

Message Description: LOG_ID_WEB_CONTENT_KEYWORD

Type: Web

Subtype: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12293 - LOG_ID_WEB_CONTENT_SEARCH

Message ID: 12293

Message Description: LOG_ID_WEB_CONTENT_SEARCH

Type: Web

Subtype: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12305 - LOG_ID_WEB_CONTENT_BANWORD_NOTIF

Message ID: 12305

Message Description: LOG_ID_WEB_CONTENT_BANWORD_NOTIF

Type: Web

Subtype: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12544 - LOG_ID_URL_FILTER_BLOCK

Message ID: 12544

Message Description: LOG_ID_URL_FILTER_BLOCK

Type: Web

Subtype: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32

12545 - LOG_ID_URL_FILTER_EXEMPT

Message ID: 12545

Message Description: LOG_ID_URL_FILTER_EXEMPT

Type: Web

Subtype: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32

12546 - LOG_ID_URL_FILTER_ALLOW

Message ID: 12546

Message Description: LOG_ID_URL_FILTER_ALLOW

Type: Web

Subtype: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10

Log Field Name	Description	Data Type	Length
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32

12547 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK

Message ID: 12547

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK

Type: Web

Subtype: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12548 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK

Message ID: 12548

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK

Type: Web

Subtype: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12549 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS

Message ID: 12549

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS

Type: Web

Subtype: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12550 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS

Message ID: 12550

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS

Type: Web

Subtype: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32

Log Field Name	Description	Data Type	Length
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12551 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK

Message ID: 12551

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK

Type: Web

Subtype: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12552 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS

Message ID: 12552

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS

Type: Web

Subtype: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12553 - LOG_ID_URL_FILTER_INVALID_CERT

Message ID: 12553

Message Description: LOG_ID_URL_FILTER_INVALID_CERT

Type: Web

Subtype: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12554 - LOG_ID_URL_FILTER_INVALID_SESSION

Message ID: 12554

Message Description: LOG_ID_URL_FILTER_INVALID_SESSION

Type: Web

Subtype: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12555 - LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK

Message ID: 12555

Message Description: LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK

Type: Web

Subtype: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12556 - LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS

Message ID: 12556

Message Description: LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS

Type: Web

Subtype: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

12557 - LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE

Message ID: 12557

Message Description: LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE

Type: Web

Subtype: URLFILTER

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
eventtype	Web Filter event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
vd	Virtual domain name	string	32

12558 - LOG_ID_URL_FILTER_RATING_ERR

Message ID: 12558

Message Description: LOG_ID_URL_FILTER_RATING_ERR

Type: Web

Subtype: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtype	Web Filter event type	string	32
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
urltype	URL filter type	string	8
user	User name	string	256
vd	Virtual domain name	string	32

12559 - LOG_ID_URL_FILTER_PASS

Message ID: 12559

Message Description: LOG_ID_URL_FILTER_PASS

Type: Web

Subtype: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32

12560 - LOG_ID_URL_WISP_BLOCK

Message ID: 12560

Message Description: LOG_ID_URL_WISP_BLOCK

Type: Web

Subtype: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12561 - LOG_ID_URL_WISP_REDIR

Message ID: 12561

Message Description: LOG_ID_URL_WISP_REDIR

Type: Web

Subtype: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12562 - LOG_ID_URL_WISP_ALLOW

Message ID: 12562

Message Description: LOG_ID_URL_WISP_ALLOW

Type: Web

Subtype: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32

12800 - LOG_ID_WEB_FTGD_ERR

Message ID: 12800

Message Description: LOG_ID_WEB_FTGD_ERR

Type: Web

Subtype: FTGD_ERR

Severity: Error

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12801 - LOG_ID_WEB_FTGD_WARNING

Message ID: 12801

Message Description: LOG_ID_WEB_FTGD_WARNING

Type: Web

Subtype: FTGD_ERR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12802 - LOG_ID_WEB_FTGD_QUOTA

Message ID: 12802

Message Description: LOG_ID_WEB_FTGD_QUOTA

Type: Web

Subtype: FTGD_QUOTA

Severity: Information

Log Field Name	Description	Data Type	Length
catdesc	Web category description	string	64
date	Date	string	10
eventtype	Web Filter event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
profile	Web Filter profile name	string	64
quotaexceeded	Quota has been exceeded	string	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20

Log Field Name	Description	Data Type	Length
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

13056 - LOG_ID_WEB_FTGD_CAT_BLK

Message ID: 13056

Message Description: LOG_ID_WEB_FTGD_CAT_BLK

Type: Web

Subtype: FTGD_BLK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32

13057 - LOG_ID_WEB_FTGD_CAT_WARN

Message ID: 13057

Message Description: LOG_ID_WEB_FTGD_CAT_WARN

Type: Web

Subtype: FTGD_BLK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13312 - LOG_ID_WEB_FTGD_CAT_ALLOW

Message ID: 13312

Message Description: LOG_ID_WEB_FTGD_CAT_ALLOW

Type: Web

Subtype: FTGD_ALLOW

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13313 - LOG_ID_WEB_FTGD_RULE_ALLOW

Message ID: 13313

Message Description: LOG_ID_WEB_FTGD_RULE_ALLOW

Type: Web

Subtype: FTGD_ALLOW

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
mode	Rating override mode	string	32
msg	Log message	string	512
ovrdid	URL rating override ID	uint32	10
ovrdtbl	Rating override table	string	128
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
ruledata	Rule data	string	512
ruletype	Rule type	string	9
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13314 - LOG_ID_WEB_FTGD_OFF_SITE_ALLOW

Message ID: 13314

Message Description: LOG_ID_WEB_FTGD_OFF_SITE_ALLOW

Type: Web

Subtype: FTGD_ALLOW

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
mode	Rating override mode	string	32
msg	Log message	string	512
ovrdid	URL rating override ID	uint32	10
ovrdtbl	Rating override table	string	128
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
ruledata	Rule data	string	512
ruletype	Rule type	string	9
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13315 - LOG_ID_WEB_FTGD_QUOTA_COUNTING

Message ID: 13315

Message Description: LOG_ID_WEB_FTGD_QUOTA_COUNTING

Type: Web

Subtype: FTGD_QUOTA_COUNTING

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13316 - LOG_ID_WEB_FTGD_QUOTA_EXPIRED

Message ID: 13316

Message Description: LOG_ID_WEB_FTGD_QUOTA_EXPIRED

Type: Web

Subtype: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13317 - LOG_ID_WEB_URL

Message ID: 13317

Message Description: LOG_ID_WEB_URL

Type: Web

Subtype: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64

Log Field Name	Description	Data Type	Length
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13568 - LOG_ID_WEB_SCRIPTFILTER_ACTIVEX

Message ID: 13568

Message Description: LOG_ID_WEB_SCRIPTFILTER_ACTIVEX

Type: Web

Subtype: ACTIVEXFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13573 - LOG_ID_WEB_SCRIPTFILTER_COOKIE

Message ID: 13573

Message Description: LOG_ID_WEB_SCRIPTFILTER_COOKIE

Type: Web

Subtype: COOKIEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13584 - LOG_ID_WEB_SCRIPTFILTER_APPLET

Message ID: 13584

Message Description: LOG_ID_WEB_SCRIPTFILTER_APPLET

Type: Web

Subtype: APPLETFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13600 - LOG_ID_WEB_SCRIPTFILTER_OTHER

Message ID: 13600

Message Description: LOG_ID_WEB_SCRIPTFILTER_OTHER

Type: Web

Subtype: SCRIPTFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13601 - LOG_ID_WEB_WF_COOKIE

Message ID: 13601

Message Description: LOG_ID_WEB_WF_COOKIE

Type: Web

Subtype: COOKIEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13602 - LOG_ID_WEB_WF_REFERER

Message ID: 13602

Message Description: LOG_ID_WEB_WF_REFERER

Type: Web

Subtype: COOKIEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13603 - LOG_ID_WEB_WF_COMMAND_BLOCK

Message ID: 13603

Message Description: LOG_ID_WEB_WF_COMMAND_BLOCK

Type: Web

Subtype: WEBFILTER_COMMAND_BLOCK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
reqtype	Request type	string	8
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
user	User name	string	256
vd	Virtual domain name	string	32

13616 - LOG_ID_CONTENT_TYPE_BLOCK

Message ID: 13616

Message Description: LOG_ID_CONTENT_TYPE_BLOCK

Type: Web

Subtype: CONTENT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
contenttype	Content Type from HTTP header	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtype	Web Filter event type	string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

FORTINET®

High Performance Network Security

Copyright© 2017 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. In no event does Fortinet make any commitment related to future deliverables, features or development, and circumstances may change such that any forward-looking statements herein are not accurate. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.