

# FortiOS - Log Reference

Version 6.0.17

**FORTINET DOCUMENT LIBRARY**

<https://docs.fortinet.com>

**FORTINET VIDEO GUIDE**

<https://video.fortinet.com>

**FORTINET BLOG**

<https://blog.fortinet.com>

**CUSTOMER SERVICE & SUPPORT**

<https://support.fortinet.com>

**FORTINET TRAINING & CERTIFICATION PROGRAM**

<https://www.fortinet.com/training-certification>

**FORTINET TRAINING INSTITUTE**

<https://training.fortinet.com>

**FORTIGUARD CENTER**

<https://www.fortiguard.com>

**END USER LICENSE AGREEMENT**

<https://www.fortinet.com/doc/legal/EULA.pdf>

**FEEDBACK**

Email: [techdoc@fortinet.com](mailto:techdoc@fortinet.com)



June 08, 2023

FortiOS 6.0.17 Log Reference

01-6017-478339-20230608

# TABLE OF CONTENTS

<b>Change Log</b> .....	<b>26</b>
<b>Introduction</b> .....	<b>27</b>
Before you begin .....	27
Overview .....	27
What's new .....	28
FortiOS 6.0.17 .....	28
FortiOS 6.0.16 .....	28
FortiOS 6.0.15 .....	28
FortiOS 6.0.14 .....	28
FortiOS 6.0.13 .....	28
FortiOS 6.0.12 .....	28
FortiOS 6.0.11 .....	28
FortiOS 6.0.10 .....	28
FortiOS 6.0.9 .....	28
FortiOS 6.0.8 .....	29
FortiOS 6.0.7 .....	29
FortiOS 6.0.6 .....	29
FortiOS 6.0.5 .....	29
FortiOS 6.0.4 .....	29
FortiOS 6.0.3 .....	29
FortiOS 6.0.2 .....	29
FortiOS 6.0.1 .....	29
FortiOS 6.0.0 .....	29
<b>Log Types and Subtypes</b> .....	<b>31</b>
Type .....	31
Subtype .....	31
List of log types and subtypes .....	31
UTM log subtypes .....	32
FortiOS priority levels .....	33
Log field format .....	34
<b>Log Schema Structure</b> .....	<b>35</b>
Log message fields .....	35
Log ID numbers .....	38
Log ID definitions .....	39
<b>FortiGuard Web Filter Categories</b> .....	<b>42</b>
<b>CEF Support</b> .....	<b>45</b>
FortiOS to CEF log field mapping guidelines .....	45
CEF priority levels .....	46
Examples of CEF support .....	46
Traffic log support for CEF .....	46
Event log support for CEF .....	48
Antivirus log support for CEF .....	49
Webfilter log support for CEF .....	50

IPS log support for CEF .....	51
Email Spamfilter log support for CEF .....	51
Anomaly log support for CEF .....	52
VoIP log support for CEF .....	52
DLP log support for CEF .....	53
Application log support for CEF .....	54
WAF log support for CEF .....	54
DNS log support for CEF .....	55
SSH log support for CEF .....	55
<b>UTM Extended Logging .....</b>	<b>56</b>
Enabling extended logging .....	56
Extended logging option in UTM profiles .....	56
Syslog server mode .....	57
Example of an extended log .....	57
<b>Log Messages .....</b>	<b>58</b>
Anomaly .....	59
18432 - LOGID_ATTCK_ANOMALY_TCP_UDP .....	59
18433 - LOGID_ATTCK_ANOMALY_ICMP .....	60
18434 - LOGID_ATTCK_ANOMALY_OTHERS .....	62
App .....	64
28672 - LOGID_APP_CTRL_IM_BASIC .....	64
28673 - LOGID_APP_CTRL_IM_BASIC_WITH_STATUS .....	65
28674 - LOGID_APP_CTRL_IM_BASIC_WITH_COUNT .....	66
28675 - LOGID_APP_CTRL_IM_FILE .....	68
28676 - LOGID_APP_CTRL_IM_CHAT .....	69
28677 - LOGID_APP_CTRL_IM_CHAT_BLOCK .....	70
28678 - LOGID_APP_CTRL_IM_BLOCK .....	72
28704 - LOGID_APP_CTRL_IPS_PASS .....	73
28705 - LOGID_APP_CTRL_IPS_BLOCK .....	75
28706 - LOGID_APP_CTRL_IPS_RESET .....	77
28720 - LOGID_APP_CTRL_SSH_PASS .....	79
28721 - LOGID_APP_CTRL_SSH_BLOCK .....	80
AV .....	83
8192 - MSGID_INFECT_WARNING .....	83
8193 - MSGID_INFECT_NOTIF .....	85
8194 - MSGID_INFECT_MIME_WARNING .....	86
8195 - MSGID_INFECT_MIME_NOTIF .....	88
8200 - MSGID_MIME_FILETYPE_EXE_WARNING .....	90
8201 - MSGID_MIME_FILETYPE_EXE_NOTIF .....	92
8448 - MSGID_BLOCK_WARNING .....	94
8449 - MSGID_BLOCK_NOTIF .....	96
8450 - MSGID_BLOCK_MIME_WARNING .....	98
8451 - MSGID_BLOCK_MIME_NOTIF .....	99
8452 - MSGID_BLOCK_COMMAND .....	101
8453 - MSGID_INTERCEPT .....	103
8454 - MSGID_INTERCEPT_MIME .....	104
8455 - MSGID_EXEMPT .....	106
8456 - MSGID_EXEMPT_MIME .....	108

8457 - MMSGID_MMS_CHECKSUM .....	110
8458 - MMSGID_MMS_CHECKSUM_NOTIF .....	111
8704 - MMSGID_OVERSIZE_WARNING .....	113
8705 - MMSGID_OVERSIZE_NOTIF .....	115
8706 - MMSGID_OVERSIZE_MIME_WARNING .....	116
8707 - MMSGID_OVERSIZE_MIME_NOTIF .....	118
8720 - MMSGID_SWITCH_PROTO_WARNING .....	120
8721 - MMSGID_SWITCH_PROTO_NOTIF .....	121
8960 - MMSGID_SCAN_UNCOMPSIZELIMIT_WARNING .....	123
8961 - MMSGID_SCAN_UNCOMPSIZELIMIT_NOTIF .....	125
8962 - MMSGID_SCAN_ARCHIVE_ENCRYPTED_WARNING .....	127
8963 - MMSGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF .....	129
8964 - MMSGID_SCAN_ARCHIVE_CORRUPTED_WARNING .....	130
8965 - MMSGID_SCAN_ARCHIVE_CORRUPTED_NOTIF .....	132
8966 - MMSGID_SCAN_ARCHIVE_MULTIPART_WARNING .....	134
8967 - MMSGID_SCAN_ARCHIVE_MULTIPART_NOTIF .....	136
8968 - MMSGID_SCAN_ARCHIVE_NESTED_WARNING .....	138
8969 - MMSGID_SCAN_ARCHIVE_NESTED_NOTIF .....	140
8970 - MMSGID_SCAN_ARCHIVE_OVERSIZE_WARNING .....	142
8971 - MMSGID_SCAN_ARCHIVE_OVERSIZE_NOTIF .....	144
8972 - MMSGID_SCAN_ARCHIVE_UNHANDLED_WARNING .....	146
8973 - MMSGID_SCAN_ARCHIVE_UNHANDLED_NOTIF .....	148
8974 - MMSGID_SCAN_AV_ENGINE_LOAD_FAILED_ERROR .....	149
8975 - MMSGID_SCAN_ARCHIVE_PARTIALLYCORRUPTED_WARNING .....	151
8976 - MMSGID_SCAN_ARCHIVE_PARTIALLYCORRUPTED_NOTIF .....	153
8977 - MMSGID_SCAN_ARCHIVE_FILESLIMIT_WARNING .....	155
8978 - MMSGID_SCAN_ARCHIVE_FILESLIMIT_NOTIF .....	157
8979 - MMSGID_SCAN_ARCHIVE_TIMEOUT_WARNING .....	159
8980 - MMSGID_SCAN_ARCHIVE_TIMEOUT_NOTIF .....	161
9233 - MMSGID_ANALYTICS_SUBMITTED .....	163
9234 - MMSGID_ANALYTICS_INFECT_WARNING .....	165
9235 - MMSGID_ANALYTICS_INFECT_NOTIF .....	166
9236 - MMSGID_ANALYTICS_INFECT_MIME_WARNING .....	168
9237 - MMSGID_ANALYTICS_INFECT_MIME_NOTIF .....	170
9238 - MMSGID_ANALYTICS_FSA_RESULT .....	172
9239 - MMSGID_CONTENT_DISARM_NOTIF .....	173
9240 - MMSGID_CONTENT_DISARM_WARNING .....	175
9248 - MMSGID_BOTNET_WARNING .....	177
9249 - MMSGID_BOTNET_NOTIF .....	179
DLP .....	181
24576 - LOG_ID_DLP_WARN .....	181
24577 - LOG_ID_DLP_NOTIF .....	183
24578 - LOG_ID_DLP_DOC_SOURCE .....	185
24579 - LOG_ID_DLP_DOC_SOURCE_ERROR .....	186
DNS .....	187
54000 - LOG_ID_DNS_QUERY .....	187
54200 - LOG_ID_DNS_RESOLV_ERROR .....	188
54400 - LOG_ID_DNS_URL_FILTER_BLOCK .....	189
54401 - LOG_ID_DNS_URL_FILTER_ALLOW .....	191

54600 - LOG_ID_DNS_BOTNET_IP .....	192
54601 - LOG_ID_DNS_BOTNET_DOMAIN .....	194
54800 - LOG_ID_DNS_FTGD_WARNING .....	195
54801 - LOG_ID_DNS_FTGD_ERROR .....	197
54802 - LOG_ID_DNS_FTGD_CAT_ALLOW .....	198
54803 - LOG_ID_DNS_FTGD_CAT_BLOCK .....	200
Email .....	202
20480 - LOGID_ANTISPAM_EMAIL_SMTP_NOTIF .....	202
20481 - LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF .....	203
20482 - LOGID_ANTISPAM_EMAIL_POP3_NOTIF .....	205
20483 - LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF .....	207
20484 - LOGID_ANTISPAM_EMAIL_IMAP_NOTIF .....	209
20485 - LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING .....	211
20486 - LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF .....	212
20487 - LOGID_ANTISPAM_ENDPOINT_MM7_WARNING .....	214
20488 - LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF .....	216
20489 - LOGID_ANTISPAM_ENDPOINT_MM1_WARNING .....	218
20490 - LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF .....	219
20491 - LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF .....	221
20492 - LOGID_ANTISPAM_MM1_FLOOD_WARNING .....	223
20493 - LOGID_ANTISPAM_MM1_FLOOD_NOTIF .....	225
20494 - LOGID_ANTISPAM_MM4_FLOOD_WARNING .....	227
20495 - LOGID_ANTISPAM_MM4_FLOOD_NOTIF .....	228
20496 - LOGID_ANTISPAM_MM1_DUPE_WARNING .....	230
20497 - LOGID_ANTISPAM_MM1_DUPE_NOTIF .....	232
20498 - LOGID_ANTISPAM_MM4_DUPE_WARNING .....	234
20499 - LOGID_ANTISPAM_MM4_DUPE_NOTIF .....	236
20500 - LOGID_ANTISPAM_EMAIL_MSN_NOTIF .....	237
20501 - LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF .....	239
20502 - LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF .....	241
20503 - LOGID_EMAIL_SMTP_GENERAL_NOTIF .....	243
20504 - LOGID_EMAIL_POP3_GENERAL_NOTIF .....	244
20505 - LOGID_EMAIL_IMAP_GENERAL_NOTIF .....	246
20506 - LOGID_EMAIL_MAPI_GENERAL_NOTIF .....	248
20507 - LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF .....	250
20508 - LOGID_ANTISPAM_EMAIL_MAPI_NOTIF .....	252
20509 - LOGID_ANTISPAM_FTGD_ERR .....	253
Event .....	256
20002 - LOG_ID_DOMAIN_UNRESOLVABLE .....	256
20003 - LOG_ID_MAIL_SENT_FAIL .....	256
20004 - LOG_ID_POLICY_TOO_BIG .....	257
20005 - LOG_ID_PPP_LINK_UP .....	258
20006 - LOG_ID_PPP_LINK_DOWN .....	259
20007 - LOG_ID_SOCKET_EXHAUSTED .....	259
20008 - LOG_ID_POLICY6_TOO_BIG .....	260
20010 - LOG_ID_KERNEL_ERROR .....	261
20016 - LOG_ID_MODEM_EXCEED_REDIAL_COUNT .....	262
20017 - LOG_ID_MODEM_FAIL_TO_OPEN .....	262
20020 - LOG_ID_MODEM_USB_DETECTED .....	263

20021 - LOG_ID_MAIL_RESENT .....	264
20022 - LOG_ID_MODEM_USB_REMOVED .....	264
20023 - LOG_ID_MODEM_USBLTE_DETECTED .....	265
20024 - LOG_ID_MODEM_USBLTE_REMOVED .....	266
20025 - LOG_ID_REPORTD_REPORT_SUCCESS .....	266
20026 - LOG_ID_REPORTD_REPORT_FAILURE .....	267
20027 - LOG_ID_REPORT_DEL_OLD_REC .....	268
20028 - LOG_ID_REPORT_RECREATE_DB .....	268
20031 - LOG_ID_RAD_OUT_OF_MEM .....	269
20032 - LOG_ID_RAD_NOT_FOUND .....	270
20033 - LOG_ID_RAD_MOBILE_IPV6 .....	270
20034 - LOG_ID_RAD_IPV6_OUT_OF_RANGE .....	271
20035 - LOG_ID_RAD_MIN_OUT_OF_RANGE .....	271
20036 - LOG_ID_RAD_MAX_OUT_OF_RANGE .....	272
20037 - LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE .....	273
20039 - LOG_ID_RAD_MTU_TOO_SMALL .....	273
20040 - LOG_ID_RAD_TIME_TOO_SMALL .....	274
20041 - LOG_ID_RAD_HOP_OUT_OF_RANGE .....	275
20042 - LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE .....	275
20043 - LOG_ID_RAD_AGENT_OUT_OF_RANGE .....	276
20044 - LOG_ID_RAD_AGENT_FLAG_NOT_SET .....	277
20045 - LOG_ID_RAD_PREFIX_TOO_LONG .....	277
20046 - LOG_ID_RAD_PREF_TIME_TOO_SMALL .....	278
20047 - LOG_ID_RAD_FAIL_IPV6_SOCKET .....	279
20048 - LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO .....	279
20049 - LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM .....	280
20050 - LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS .....	280
20051 - LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS .....	281
20052 - LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT .....	282
20053 - LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6 .....	282
20054 - LOG_ID_RAD_EXIT_BY_SIGNAL .....	283
20055 - LOG_ID_RAD_FAIL_CMDB_QUERY .....	284
20056 - LOG_ID_RAD_FAIL_CMDB_FOR_EACH .....	284
20057 - LOG_ID_RAD_FAIL_FIND_VIRT_INTF .....	285
20058 - LOG_ID_RAD_UNLOAD_INTF .....	286
20059 - LOG_ID_RAD_NO_PKT_INFO .....	286
20060 - LOG_ID_RAD_INV_ICMPV6_LEN .....	287
20061 - LOG_ID_RAD_INV_ICMPV6_TYPE .....	288
20062 - LOG_ID_RAD_INV_ICMPV6_RA_LEN .....	288
20063 - LOG_ID_RAD_ICMPV6_NO_SRC_ADDR .....	289
20064 - LOG_ID_RAD_INV_ICMPV6_RS_LEN .....	289
20065 - LOG_ID_RAD_INV_ICMPV6_CODE .....	290
20066 - LOG_ID_RAD_INV_ICMPV6_HOP .....	291
20067 - LOG_ID_RAD_MISMATCH_HOP .....	291
20068 - LOG_ID_RAD_MISMATCH_MGR_FLAG .....	292
20069 - LOG_ID_RAD_MISMATCH_OTH_FLAG .....	293
20070 - LOG_ID_RAD_MISMATCH_TIME .....	293
20071 - LOG_ID_RAD_MISMATCH_TIMER .....	294
20072 - LOG_ID_RAD_EXTRA_DATA .....	295

20073 - LOG_ID_RAD_NO_OPT_DATA .....	295
20074 - LOG_ID_RAD_INV_OPT_LEN .....	296
20075 - LOG_ID_RAD_MISMATCH_MTU .....	297
20077 - LOG_ID_RAD_MISMATCH_PREF_TIME .....	297
20078 - LOG_ID_RAD_INV_OPT .....	298
20079 - LOG_ID_RAD_READY .....	298
20080 - LOG_ID_RAD_FAIL_TO_RCV .....	299
20081 - LOG_ID_RAD_INV_HOP .....	300
20082 - LOG_ID_RAD_INV_PKTINFO .....	300
20083 - LOG_ID_RAD_FAIL_TO_CHECK .....	301
20084 - LOG_ID_RAD_FAIL_TO_SEND .....	302
20085 - LOG_ID_SESSION_CLASH .....	302
20086 - LOG_ID_XHO_EVENT .....	303
20090 - LOG_ID_INTF_LINK_STA_CHG .....	304
20099 - LOG_ID_INTF_STA_CHG .....	304
20100 - LOG_ID_WEB_CAT_UPDATED .....	305
20101 - LOG_ID_WEB_LIC_EXPIRE .....	306
20102 - LOG_ID_SPAM_LIC_EXPIRE .....	306
20103 - LOG_ID_AV_LIC_EXPIRE .....	307
20104 - LOG_ID_IPS_LIC_EXPIRE .....	308
20105 - LOG_ID_LOG_UPLOAD_SKIP .....	308
20107 - LOG_ID_LOG_UPLOAD_ERR .....	309
20108 - LOG_ID_LOG_UPLOAD_DONE .....	310
20109 - LOG_ID_WEB_LIC_EXPIRED .....	311
20113 - LOG_ID_IPSA_DOWNLOAD_FAIL .....	311
20115 - LOG_ID_IPSA_STATUSUPD_FAIL .....	312
20116 - LOG_ID_SPAM_LIC_EXPIRED .....	313
20117 - LOG_ID_AV_LIC_EXPIRED .....	313
20118 - LOG_ID_WEBF_STATUS_REACH .....	314
20119 - LOG_ID_WEBF_STATUS_UNREACH .....	315
20200 - LOG_ID_FIPS_SELF_TEST .....	315
20201 - LOG_ID_FIPS_SELF_ALL_TEST .....	316
20202 - LOG_ID_DISK_FORMAT_ERROR .....	317
20203 - LOG_ID_DAEMON_SHUTDOWN .....	317
20204 - LOG_ID_DAEMON_START .....	318
20205 - LOG_ID_DISK_FORMAT_REQ .....	319
20206 - LOG_ID_DISK_SCAN_REQ .....	320
20207 - LOG_ID_RAD_MISMATCH_VALID_TIME .....	320
20208 - LOG_ID_ZOMBIE_DAEMON_CLEANUP .....	321
20209 - LOG_ID_DISK_UNAVAIL .....	322
20210 - LOG_ID_DISK_TRIM_START .....	322
20211 - LOG_ID_DISK_TRIM_END .....	323
20212 - LOG_ID_DISK_SCAN_NEEDED .....	324
20220 - LOGID_EVENT_SHAPER_OUTBOUND_MAXED_OUT .....	324
20221 - LOGID_EVENT_SHAPER_INBOUND_MAXED_OUT .....	325
20300 - LOG_ID_BGP_NB_STAT_CHG .....	326
20301 - LOG_ID_VZ_LOG .....	327
20302 - LOG_ID_OSPF_NB_STAT_CHG .....	327
20303 - LOG_ID_OSPF6_NB_STAT_CHG .....	328



20401 - LOG_ID_ROUTER_CLEAR .....	328
22000 - LOG_ID_INV_PKT_LEN .....	329
22001 - LOG_ID_UNSUPPORTED_PROT_VER .....	330
22002 - LOG_ID_INV_REQ_TYPE .....	331
22003 - LOG_ID_FAIL_SET_SIG_HANDLER .....	331
22004 - LOG_ID_FAIL_CREATE_SOCKET .....	332
22005 - LOG_ID_FAIL_CREATE_SOCKET_RETRY .....	332
22006 - LOG_ID_FAIL_REG_CMDB_EVENT .....	333
22009 - LOG_ID_FAIL_FIND_AV_PROFILE .....	334
22010 - LOG_ID_SENDTO_FAIL .....	334
22011 - LOG_ID_ENTER_MEM_CONSERVE_MODE .....	335
22012 - LOG_ID_LEAVE_MEM_CONSERVE_MODE .....	336
22013 - LOG_ID_IPPOOLPBA_BLOCK_EXHAUSTED .....	337
22014 - LOG_ID_IPPOOLPBA_NATIP_EXHAUSTED .....	338
22015 - LOG_ID_IPPOOLPBA_CREATE .....	338
22016 - LOG_ID_IPPOOLPBA_DEALLOCATE .....	339
22017 - LOG_ID_EXCEED_GLOB_RES_LIMIT .....	340
22018 - LOG_ID_EXCEED_VD_RES_LIMIT .....	341
22020 - LOG_ID_FAIL_CREATE_HA_SOCKET .....	341
22021 - LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY .....	342
22030 - LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FAZ .....	343
22031 - LOG_ID_SUCCESS_CSF_LOG_SYNC_CONFIG_CHANGED .....	343
22032 - LOG_ID_CSF_LOOP_FOUND .....	344
22033 - LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FSA .....	345
22035 - LOG_ID_CSF_UPSTREAM_SN_CHANGED .....	346
22100 - LOG_ID_QUAR_DROP_TRAN_JOB .....	347
22101 - LOG_ID_QUAR_DROP_TLL_JOB .....	347
22102 - LOG_ID_LOG_DISK_FAILURE .....	348
22103 - LOG_ID_QUAR_LIMIT_REACHED .....	349
22104 - LOG_ID_POWER_RESTORE .....	350
22105 - LOG_ID_POWER_FAILURE .....	350
22106 - LOG_ID_POWER_OPTIONAL_NOT_DETECTED .....	351
22107 - LOG_ID_VOLT_ANOM .....	352
22108 - LOG_ID_FAN_ANOM .....	352
22109 - LOG_ID_TEMP_TOO_HIGH .....	353
22110 - LOG_ID_SPARE_BLOCK_LOW .....	354
22113 - LOG_ID_FNBAM_FAILURE .....	355
22150 - LOG_ID_VOLT_NOM .....	355
22151 - LOG_ID_FAN_NOM .....	356
22152 - LOG_ID_TEMP_TOO_LOW .....	357
22153 - LOG_ID_TEMP_NORM .....	357
22200 - LOG_ID_AUTO_UPT_CERT .....	358
22201 - LOG_ID_AUTO_GEN_CERT .....	359
22203 - LOG_ID_AUTO_GEN_CERT_FAIL .....	360
22204 - LOG_ID_AUTO_GEN_CERT_PENDING .....	360
22205 - LOG_ID_AUTO_GEN_CERT_SUCC .....	361
22206 - LOG_ID_CRL_EXPIRED .....	362
22700 - LOG_ID_IPS_FAIL_OPEN .....	363
22701 - LOG_ID_IPS_FAIL_OPEN_END .....	363

22800 - LOG_ID_SCAN_SERV_FAIL .....	364
22802 - LOG_ID_ENTER_FD_CONSERVE_MODE .....	365
22803 - LOG_ID_LEAVE_FD_CONSERVE_MODE .....	366
22804 - LOG_ID_LIC_STATUS_CHG .....	366
22805 - LOG_ID_FAIL_TO_VALIDATE_LIC .....	367
22806 - LOG_ID_DUP_LIC .....	368
22808 - LOG_ID_LIC_EXPIRE .....	369
22809 - LOG_ID_LIC_WILL_EXPIRE .....	369
22891 - LOG_ID_FLCFGD_SYNC_ERROR .....	370
22892 - LOG_ID_FLCFGD_SYNC_COMPLETE .....	371
22893 - LOG_ID_FLCFGD_SYNC_STATE .....	371
22894 - LOG_ID_FLCFGD_UPGRADE_ERROR .....	372
22895 - LOG_ID_FLCFGD_UPGRADE_STATUS .....	373
22900 - LOG_ID_CAPUTP_SESSION .....	374
22901 - LOG_ID_FAZ_CON .....	374
22902 - LOG_ID_FAZ_DISCON .....	375
22903 - LOG_ID_FAZ_CON_ERR .....	376
22904 - LOG_ID_CAPUTP_SESSION_NOTIF .....	377
22912 - LOG_ID_FDS_SRV_ERRCON .....	377
22913 - LOG_ID_FDS_SRV_DISCON .....	378
22914 - LOG_ID_FDS_SRV_CHG .....	379
22915 - LOG_ID_FDS_SRV_CON .....	379
22916 - LOG_ID_FDS_STATUS .....	380
22917 - LOG_ID_FDS_SMS_QUOTA .....	381
22918 - LOG_ID_FDS_CTRL_STATUS .....	382
22921 - LOG_ID_EVENT_ROUTE_INFO_CHANGED .....	382
22922 - LOG_ID_EVENT_LINK_MONITOR_STATUS .....	383
22923 - LOG_ID_EVENT_VWL_LQTY_STATUS .....	384
22924 - LOG_ID_EVENT_VWL_VOLUME_STATUS .....	384
22949 - LOG_ID_FDS_JOIN .....	385
22950 - LOG_ID_FDS_LOGIN_SUCC .....	386
22951 - LOG_ID_FDS_LOGOUT .....	387
22952 - LOG_ID_FDS_LOGIN_FAIL .....	387
22953 - LOG_ID_IOC_DETECTED .....	388
23101 - LOG_ID_IPSEC_TUNNEL_UP .....	389
23102 - LOG_ID_IPSEC_TUNNEL_DOWN .....	389
23103 - LOG_ID_IPSEC_TUNNEL_STAT .....	390
26001 - LOG_ID_DHCP_ACK .....	391
26002 - LOG_ID_DHCP_RELEASE .....	392
26003 - LOG_ID_DHCP_STAT .....	393
26004 - LOG_ID_DHCP_CLIENT_LEASE .....	394
26005 - LOG_ID_DHCP_LEASE_USAGE_HIGH .....	394
26006 - LOG_ID_DHCP_LEASE_USAGE_FULL .....	395
26007 - LOG_ID_DHCP_BLOCKED_MAC .....	396
26008 - LOG_ID_DHCP_DDNS_ADD .....	396
26009 - LOG_ID_DHCP_DDNS_DELETE .....	397
26010 - LOG_ID_DHCP_DDNS_COMPLETED .....	398
26011 - LOG_ID_DHCPV6_REPLY .....	399
26012 - LOG_ID_DHCPV6_RELEASE .....	399

27001 - LOG_ID_VRRP_STATE_CHG .....	400
29001 - LOG_ID_PPPD_MSG .....	401
29002 - LOG_ID_PPPD_AUTH_SUC .....	402
29003 - LOG_ID_PPPD_AUTH_FAIL .....	403
29010 - LOG_ID_PPPOE_STATUS_REPORT_NOTIF .....	403
29011 - LOG_ID_PPPD_FAIL_TO_EXEC .....	404
29012 - LOG_ID_PPP_OPT_ERR .....	405
29013 - LOG_ID_PPPD_START .....	405
29014 - LOG_ID_PPPD_EXIT .....	406
29015 - LOG_ID_PPP_RCV_BAD_PEER_IP .....	407
29016 - LOG_ID_PPP_RCV_BAD_LOCAL_IP .....	407
29017 - LOG_ID_PPP_OPT_NOTIF .....	408
29021 - LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED .....	409
29022 - LOG_ID_DDNS_UPDATE_FAIL .....	409
32001 - LOG_ID_ADMIN_LOGIN_SUCC .....	410
32002 - LOG_ID_ADMIN_LOGIN_FAIL .....	411
32003 - LOG_ID_ADMIN_LOGOUT .....	412
32005 - LOG_ID_ADMIN_OVERRIDE_VDOM .....	413
32006 - LOG_ID_ADMIN_ENTER_VDOM .....	414
32007 - LOG_ID_ADMIN_LEFT_VDOM .....	415
32008 - LOG_ID_VIEW_DISK_LOG_FAIL .....	415
32009 - LOG_ID_SYSTEM_START .....	416
32010 - LOG_ID_DISK_LOG_FULL .....	417
32011 - LOG_ID_LOG_ROLL .....	417
32014 - LOG_ID_CS_LIC_EXPIRE .....	418
32015 - LOG_ID_DISK_LOG_USAGE .....	419
32016 - LOG_ID_FDS_QUOTA_WARN .....	419
32017 - LOG_ID_FDS_DAILY_QUOTA_FULL .....	420
32018 - LOG_ID_FIPS_ENTER_ERR_MOD .....	421
32019 - LOG_ID_CC_ENTER_ERR_MOD .....	421
32020 - LOG_ID_SSH_CORRPUT_MAC .....	422
32021 - LOG_ID_ADMIN_LOGIN_DISABLE .....	423
32022 - LOG_ID_VDOM_ENABLED .....	424
32023 - LOG_ID_MEM_LOG_FIRST_FULL .....	424
32024 - LOG_ID_ADMIN_PASSWD_EXPIRE .....	425
32025 - LOG_ID_SSH_REKEY .....	426
32026 - LOG_ID_SSH_BAD_PACKET_LENGTH .....	426
32027 - LOG_ID_VIEW_DISK_LOG_SUCC .....	427
32028 - LOG_ID_LOG_DEL_DIR .....	428
32029 - LOG_ID_LOG_DEL_FILE .....	428
32030 - LOG_ID_SEND_FDS_STAT .....	429
32031 - LOG_ID_VIEW_MEM_LOG_FAIL .....	430
32032 - LOG_ID_DISK_DLP_ARCH_FULL .....	431
32033 - LOG_ID_DISK_QUAR_FULL .....	431
32034 - LOG_ID_DISK_REPORT_FULL .....	432
32035 - LOG_ID_VDOM_DISABLED .....	432
32036 - LOG_ID_DISK_IPS_ARCH_FULL .....	433
32037 - LOG_ID_DISK_LOG_FIRST_FULL .....	434
32038 - LOG_ID_LOG_ROLL_FORTICRON .....	434

32039 - LOG_ID_VIEW_MEM_LOG_SUCC .....	435
32040 - LOG_ID_REPORT_DELETED .....	436
32041 - LOG_ID_REPORT_DELETED_GUI .....	437
32042 - LOG_ID_MEM_LOG_SECOND_FULL .....	437
32043 - LOG_ID_MEM_LOG_FINAL_FULL .....	438
32044 - LOG_ID_LOG_DELETE .....	439
32045 - LOG_ID_MGR_LIC_EXPIRE .....	439
32046 - LOG_ID_SSL_CORRPUT_MAC .....	440
32048 - LOG_ID_SCHEDULE_EXPIRE .....	441
32049 - LOG_ID_FC_EXPIRE .....	441
32050 - LOG_ID_POL_PKT_CAPTURE_FULL .....	442
32051 - LOG_ID_LOG_UPLOAD .....	443
32052 - LOG_ID_UPLOAD_RUN_SCRIPT .....	443
32053 - LOG_ID_ADMIN_MTNER_LOGIN_SUCC .....	444
32054 - LOG_ID_ADMIN_MTNER_LOGOUT .....	445
32055 - LOG_ID_FDS_QUOTA_WARN_WARNING .....	446
32056 - LOG_ID_FDS_QUOTA_WARN_INFO .....	447
32057 - LOG_ID_VIEW_FAZ_LOG_FAIL .....	447
32058 - LOG_ID_VIEW_FAZ_LOG_SUCC .....	448
32095 - LOG_ID_GUI_CHG_SUB_MODULE .....	449
32097 - LOG_ID_DELETE_CAPTURE_PKT .....	450
32100 - LOG_ID_FORTI_TOKEN_SYNC .....	450
32102 - LOG_ID_CHG_CONFIG .....	451
32103 - LOG_ID_NEW_FIRMWARE .....	452
32104 - LOG_ID_CHG_CONFIG_GUI .....	453
32105 - LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE .....	453
32106 - LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE .....	454
32107 - LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE .....	455
32108 - LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE .....	456
32109 - LOG_ID_UPD_SIGN_AV_DB .....	456
32110 - LOG_ID_UPD_SIGN_IPS_DB .....	457
32111 - LOG_ID_UPD_SIGN_AVIPS_DB .....	458
32113 - LOG_ID_UPD_SIGN_SRCVIS_DB .....	459
32114 - LOG_ID_UPD_SIGN_GEOIP_DB .....	459
32116 - LOG_ID_UPD_SIGN_AVPKG_FAILURE .....	460
32117 - LOG_ID_UPD_SIGN_AVPKG_SUCCESS .....	461
32118 - LOG_ID_UPD_ADMIN_AV_DB .....	462
32119 - LOG_ID_UPD_SCANUNIT_AV_DB .....	462
32120 - LOG_ID_RPT_ADD_DATASET .....	463
32122 - LOG_ID_RPT_DEL_DATASET .....	464
32125 - LOG_ID_RPT_ADD_CHART .....	464
32126 - LOG_ID_RPT_DEL_CHART .....	465
32129 - LOG_ID_ADD_GUEST .....	466
32130 - LOG_ID_CHG_USER .....	467
32131 - LOG_ID_DEL_GUEST .....	468
32132 - LOG_ID_ADD_USER .....	468
32138 - LOG_ID_REBOOT .....	469
32140 - LOG_ID_TIME_USER_SETTING_CHG .....	470
32141 - LOG_ID_TIME_NTP_SETTING_CHG .....	471

32142 - LOG_ID_BACKUP_CONF .....	472
32143 - LOG_ID_BACKUP_CONF_BY_SCP .....	472
32144 - LOG_ID_BACKUP_CONF_ERROR .....	473
32145 - LOG_ID_BACKUP_CONF_ALERT .....	474
32148 - LOG_ID_GET_CRL .....	475
32149 - LOG_ID_COMMAND_FAIL .....	475
32151 - LOG_ID_ADD_IP6_LOCAL_POL .....	476
32152 - LOG_ID_CHG_IP6_LOCAL_POL .....	477
32153 - LOG_ID_DEL_IP6_LOCAL_POL .....	478
32155 - LOG_ID_ACT_FTOKEN_REQ .....	478
32156 - LOG_ID_ACT_FTOKEN_SUCC .....	479
32157 - LOG_ID_SYNC_FTOKEN_SUCC .....	480
32158 - LOG_ID_SYNC_FTOKEN_FAIL .....	481
32159 - LOG_ID_ACT_FTOKEN_FAIL .....	481
32160 - LOG_ID_FTM_PUSH_SUCC .....	482
32161 - LOG_ID_FTM_PUSH_FAIL .....	483
32168 - LOG_ID_REACH_VDOM_LIMIT .....	484
32169 - LOG_ID_ALARM_DLP_DB .....	484
32170 - LOG_ID_ALARM_MSG .....	485
32171 - LOG_ID_ALARM_ACK .....	486
32172 - LOG_ID_ADD_IP4_LOCAL_POL .....	487
32173 - LOG_ID_CHG_IP4_LOCAL_POL .....	487
32174 - LOG_ID_DEL_IP4_LOCAL_POL .....	488
32190 - LOG_ID_UPT_INVALID_IMG .....	489
32191 - LOG_ID_UPT_INVALID_IMG_CC .....	490
32192 - LOG_ID_UPT_INVALID_IMG_RSA .....	490
32193 - LOG_ID_UPT_IMG_RSA .....	491
32194 - LOG_ID_UPT_IMG_FAIL .....	492
32199 - LOG_ID_RESTORE_IMG_USB .....	493
32200 - LOG_ID_SHUTDOWN .....	493
32201 - LOG_ID_LOAD_IMG_SUCC .....	494
32202 - LOG_ID_RESTORE_IMG .....	495
32203 - LOG_ID_RESTORE_CONF .....	496
32204 - LOG_ID_RESTORE_FGD_SVR .....	496
32205 - LOG_ID_RESTORE_VDOM_LIC .....	497
32206 - LOG_ID_RESTORE_SCRIPT .....	498
32207 - LOG_ID_RETRIEVE_CONF_LIST .....	499
32208 - LOG_ID_IMP_PKCS12_CERT .....	499
32209 - LOG_ID_RESTORE_USR_DEF_IPS .....	500
32210 - LOG_ID_BACKUP_IMG_SUCC .....	501
32211 - LOG_ID_UPLOAD_REVISION .....	502
32212 - LOG_ID_DEL_REVISION .....	502
32213 - LOG_ID_RESTORE_TEMPLATE .....	503
32214 - LOG_ID_RESTORE_FILE .....	504
32215 - LOG_ID_UPT_IMG .....	505
32217 - LOG_ID_UPD_IPS .....	505
32218 - LOG_ID_UPD_DLP .....	506
32219 - LOG_ID_BACKUP_OUTPUT .....	507
32220 - LOG_ID_BACKUP_COMMAND .....	508

32221 - LOG_ID_UPD_VDOM_LIC .....	508
32222 - LOG_ID_GLB_SETTING_CHG .....	509
32223 - LOG_ID_BACKUP_USER_DEF_IPS .....	510
32224 - LOG_ID_BACKUP_DISK_LOG .....	511
32225 - LOG_ID_DEL_ALL_REVISION .....	512
32226 - LOG_ID_LOAD_IMG_FAIL .....	512
32227 - LOG_ID_UPD_DLP_FAIL .....	513
32228 - LOG_ID_LOAD_IMG_FAIL_WRONG_IMG .....	514
32229 - LOG_ID_LOAD_IMG_FAIL_NO_RSA .....	515
32230 - LOG_ID_LOAD_IMG_FAIL_INVALID_RSA .....	515
32231 - LOG_ID_RESTORE_FGD_SVR_FAIL .....	516
32232 - LOG_ID_RESTORE_VDOM_LIC_FAIL .....	517
32233 - LOG_ID_BACKUP_IMG_FAIL .....	517
32234 - LOG_ID_RESTORE_IMG_INVALID_CC .....	518
32235 - LOG_ID_RESTORE_IMG_FORTIGUARD .....	519
32236 - LOG_ID_BACKUP_MEM_LOG .....	520
32237 - LOG_ID_BACKUP_MEM_LOG_FAIL .....	520
32238 - LOG_ID_BACKUP_DISK_LOG_FAIL .....	521
32239 - LOG_ID_BACKUP_DISK_LOG_USB .....	522
32240 - LOG_ID_SYS_USB_MODE .....	523
32241 - LOG_ID_BACKUP_DISK_LOG_USB_FAIL .....	523
32242 - LOG_ID_UPD_VDOM_LIC_FAIL .....	524
32243 - LOG_ID_UPD_IPS_SCP .....	525
32244 - LOG_ID_UPD_IPS_SCP_FAIL .....	526
32245 - LOG_ID_BACKUP_USER_DEF_IPS_FAIL .....	526
32246 - LOG_ID_RESTORE_USR_DEF_IPS_CRITICAL .....	527
32247 - LOG_ID_SSH_NEGOTIATION_FAILURE .....	528
32252 - LOG_ID_FACTORY_RESET .....	529
32253 - LOG_ID_FORMAT_RAID .....	529
32254 - LOG_ID_ENABLE_RAID .....	530
32255 - LOG_ID_DISABLE_RAID .....	531
32300 - LOG_ID_UPLOAD_RPT_IMG .....	532
32301 - LOG_ID_ADD_VDOM .....	533
32302 - LOG_ID_DEL_VDOM .....	533
32545 - LOG_ID_SYS_RESTART .....	534
32546 - LOG_ID_APPLICATION_CRASH .....	535
32547 - LOG_ID_AUTOSCRIP_START .....	535
32548 - LOG_ID_AUTOSCRIP_STOP .....	536
32549 - LOG_ID_AUTOSCRIP_STOP_AUTO .....	537
32550 - LOG_ID_AUTOSCRIP_DELETE_RSLT .....	538
32551 - LOG_ID_AUTOSCRIP_BACKUP_RSLT .....	538
32552 - LOG_ID_AUTOSCRIP_CHECK_STATUS .....	539
32553 - LOG_ID_AUTOSCRIP_STOP_REACH_LIMIT .....	540
32561 - LOG_ID_ADMIN_LOGOUT_DISCONNECT .....	540
32562 - LOG_ID_STORE_CONF_FAIL_SPACE .....	541
32564 - LOG_ID_RESTORE_CONF_FAIL .....	542
32565 - LOG_ID_RESTORE_CONF_BY_MGMT .....	543
32566 - LOG_ID_RESTORE_CONF_BY_SCP .....	544
32567 - LOG_ID_RESTORE_CONF_BY_USB .....	544

32568 - LOG_ID_DEL_REVISION_DB .....	545
32569 - LOG_ID_FSW_SWITCH_LOG_EVENT .....	546
32570 - LOG_ID_ADMIN_MTNER_LOGOUT_DISCONNECT .....	547
32601 - LOG_ID_FGT_SWITCH_LOG_DISCOVER .....	548
32602 - LOG_ID_FGT_SWITCH_LOG_AUTH .....	548
32603 - LOG_ID_FGT_SWITCH_LOG_DEAUTH .....	549
32604 - LOG_ID_FGT_SWITCH_LOG_DELETE .....	550
32605 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_UP .....	550
32606 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_DOWN .....	551
32607 - LOG_ID_FGT_SWITCH_PUSH_IMAGE .....	552
32608 - LOG_ID_FGT_SWITCH_STAGE_IMAGE .....	553
32609 - LOG_ID_FGT_SWITCH_DISABLE_DISCOVERY .....	553
32610 - LOG_ID_FGT_SWITCH_LOG_WARNING .....	554
32693 - LOG_ID_FGT_SWITCH_GROUP_SWC .....	555
32694 - LOG_ID_FGT_SWITCH_GROUP_POE .....	556
32695 - LOG_ID_FGT_SWITCH_GROUP_LINK .....	556
32696 - LOG_ID_FGT_SWITCH_GROUP_STP .....	557
32697 - LOG_ID_FGT_SWITCH_GROUP_SWITCH .....	558
32698 - LOG_ID_FGT_SWITCH_GROUP_ROUTER .....	559
32699 - LOG_ID_FGT_SWITCH_GROUP_SYSTEM .....	560
35001 - LOG_ID_HA_SYNC_VIRDB .....	561
35002 - LOG_ID_HA_SYNC_ETDB .....	561
35003 - LOG_ID_HA_SYNC_EXDB .....	562
35004 - LOG_ID_HA_SYNC_FLDB .....	563
35005 - LOG_ID_HA_SYNC_IPS .....	563
35007 - LOG_ID_HA_SYNC_AV .....	564
35009 - LOG_ID_HA_SYNC_CID .....	565
35010 - LOG_ID_HA_SYNC_UWDB .....	565
35011 - LOG_ID_HA_SYNC_FAIL .....	566
35012 - LOG_ID_CONF_SYNC_FAIL .....	566
36880 - LOG_ID_EVENT_SYSTEM_MAC_HOST_STORE_LIMIT .....	567
36881 - LOG_ID_EVENT_SYSTEM_CFG_REVERT .....	568
36882 - LOG_ID_EVENT_SYSTEM_CFG_MANUALLY_SAVED .....	568
37120 - MSGID_NEG_GENERIC_P1_NOTIF .....	569
37121 - MSGID_NEG_GENERIC_P1_ERROR .....	570
37122 - MSGID_NEG_GENERIC_P2_NOTIF .....	571
37123 - MSGID_NEG_GENERIC_P2_ERROR .....	573
37124 - MSGID_NEG_I_P1_ERROR .....	574
37125 - MSGID_NEG_I_P2_ERROR .....	575
37126 - MSGID_NEG_NO_STATE_ERROR .....	576
37127 - MSGID_NEG_PROGRESS_P1_NOTIF .....	577
37128 - MSGID_NEG_PROGRESS_P1_ERROR .....	579
37129 - MSGID_NEG_PROGRESS_P2_NOTIF .....	580
37130 - MSGID_NEG_PROGRESS_P2_ERROR .....	581
37131 - MSGID_ESP_ERROR .....	583
37132 - MSGID_ESP_CRITICAL .....	584
37133 - MSGID_INSTALL_SA .....	585
37134 - MSGID_DELETE_P1_SA .....	586
37135 - MSGID_DELETE_P2_SA .....	587

37136 - MESSAGESID_DPDI_FAILURE .....	589
37137 - MESSAGESID_CONN_FAILURE .....	590
37138 - MESSAGESID_CONN_UPDOWN .....	591
37139 - MESSAGESID_P2_UPDOWN .....	592
37141 - MESSAGESID_CONN_STATS .....	593
37889 - MESSAGESID_VC_DELETE .....	595
37890 - MESSAGESID_VC_MOVE_VDOM .....	595
37891 - MESSAGESID_VC_ADD_VDOM .....	596
37892 - MESSAGESID_VC_MOVE_MEMBERSHIP_STATE .....	597
37893 - MESSAGESID_VC_DETECT_MEMBERSHIP_DEAD .....	597
37894 - MESSAGESID_VC_DETECT_MEMBERSHIP_JOIN .....	598
37895 - MESSAGESID_VC_ADD_HADEV .....	599
37896 - MESSAGESID_VC_DELETE_HADEV .....	600
37897 - MESSAGESID_HADEV_READY .....	600
37898 - MESSAGESID_HADEV_FAILURE .....	601
37899 - MESSAGESID_HADEV_PEERINFO .....	602
37900 - MESSAGESID_HBDEV_DELETE .....	602
37901 - MESSAGESID_HBDEV_DOWN .....	603
37902 - MESSAGESID_HBDEV_UP .....	604
37903 - MESSAGESID_SYNC_STATUS .....	605
37904 - MESSAGESID_HA_ACTIVITY .....	605
37907 - MESSAGESID_VLAN_HB_UP .....	606
37908 - MESSAGESID_VLAN_HB_DOWN .....	607
37909 - MESSAGESID_VLAN_HB_DOWN_SUM .....	607
38010 - LOG_ID_FIPS_ENCRYPT_FAIL .....	608
38011 - LOG_ID_FIPS_DECRYPT_FAIL .....	609
38012 - LOG_ID_ENTROPY_TOKEN .....	610
38031 - LOG_ID_FSSO_LOGON .....	610
38032 - LOG_ID_FSSO_LOGOFF .....	611
38033 - LOG_ID_FSSO_SERVER_STATUS .....	612
38400 - LOGID_EVENT_NOTIFICATION_SEND_SUCCESS .....	613
38401 - LOGID_EVENT_NOTIFICATION_SEND_FAILURE .....	614
38402 - LOGID_EVENT_NOTIFICATION_DNS_FAILURE .....	615
38403 - LOGID_EVENT_NOTIFICATION_INSUFFICIENT_RESOURCE .....	616
38404 - LOGID_EVENT_NOTIFICATION_HOSTNAME_ERROR .....	617
38405 - LOGID_NOTIFICATION_CODE_SENDTO_SMS_PHONE .....	617
38406 - LOGID_NOTIFICATION_CODE_SENDTO_SMS_TO .....	618
38407 - LOGID_NOTIFICATION_CODE_SENDTO_EMAIL .....	619
38408 - LOGID_EVENT_OFTP_SSL_CONNECTED .....	619
38409 - LOGID_EVENT_OFTP_SSL_DISCONNECTED .....	620
38410 - LOGID_EVENT_OFTP_SSL_FAILED .....	621
38411 - LOGID_EVENT_TWO_FACTOR_AUTH_CODE_SENDTO .....	622
38412 - LOGID_EVENT_TOKEN_CODE_SENDTO .....	622
38420 - LOGID_EVENT_HTTPS_CONNECTION .....	623
38656 - LOGID_EVENT_RAD_REPORT_PROTOCOL_ERROR .....	624
38657 - LOGID_EVENT_RAD_REPORT_PROFILE_NOT_FOUND .....	625
38658 - LOGID_EVENT_RAD_REPORT_CONTEXT_NOT_FOUND .....	625
38659 - LOGID_EVENT_RAD_REPORT_ACCOUNT_STOP_MISSED .....	626
38660 - LOGID_EVENT_RAD_REPORT_ACCOUNT_EVENT .....	627



38661 - LOGID_EVENT_RAD_RPT_OTHER .....	627
38662 - LOGID_EVENT_RAD_STAT_PROTO_ERROR .....	628
38663 - LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND .....	629
38665 - LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED .....	630
38666 - LOGID_EVENT_RAD_STAT_ACCT_EVENT .....	631
38667 - LOGID_EVENT_RAD_STAT_OTHER .....	631
38668 - LOGID_EVENT_RAD_STAT_EP_BLK .....	632
39424 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP .....	633
39425 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN .....	634
39426 - LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL .....	635
39936 - LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS .....	636
39937 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY .....	637
39938 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS .....	638
39939 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT .....	639
39940 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE .....	640
39941 - LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY .....	641
39942 - LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK .....	642
39943 - LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON .....	643
39944 - LOG_ID_EVENT_SSL_VPN_SESSION_ALERT .....	644
39945 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL .....	644
39946 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR .....	645
39947 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP .....	646
39948 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN .....	647
39949 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS .....	648
39950 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG .....	649
39951 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR .....	650
39952 - LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE .....	651
39953 - LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE .....	652
40001 - LOG_ID_PPTP_TUNNEL_UP .....	653
40002 - LOG_ID_PPTP_TUNNEL_DOWN .....	654
40003 - LOG_ID_PPTP_TUNNEL_STAT .....	655
40014 - LOG_ID_PPTP_REACH_MAX_CON .....	656
40017 - LOG_ID_L2TPD_CLIENT_CON_FAIL .....	656
40019 - LOG_ID_L2TPD_CLIENT_DISCON .....	657
40021 - LOG_ID_PPTP_NOT_CONIG .....	658
40022 - LOG_ID_PPTP_NO_IP_AVAIL .....	659
40024 - LOG_ID_PPTP_OUT_MEM .....	659
40034 - LOG_ID_PPTP_START .....	660
40035 - LOG_ID_PPTP_START_FAIL .....	661
40036 - LOG_ID_PPTP_EXIT .....	661
40037 - LOG_ID_PPTPD_SVR_DISCON .....	662
40038 - LOG_ID_PPTPD_CLIENT_CON .....	663
40039 - LOG_ID_PPTPD_CLIENT_DISCON .....	664
40101 - LOG_ID_L2TP_TUNNEL_UP .....	664
40102 - LOG_ID_L2TP_TUNNEL_DOWN .....	665
40103 - LOG_ID_L2TP_TUNNEL_STAT .....	666
40114 - LOG_ID_L2TPD_START .....	667
40115 - LOG_ID_L2TPD_EXIT .....	668
40118 - LOG_ID_L2TPD_CLIENT_CON .....	668

40704 - LOG_ID_EVENT_SYS_PERF .....	669
40705 - LOG_ID_EVENT_SYS_CPU_USAGE .....	670
40960 - LOGID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR .....	671
41000 - LOG_ID_UPD_FGT_SUCC .....	672
41001 - LOG_ID_UPD_FGT_FAIL .....	672
41002 - LOG_ID_UPD_SRC_VIS .....	673
41006 - LOG_ID_UPD_FSA_VIRDB .....	674
41984 - LOG_ID_EVENT_VPN_CERT_LOAD .....	675
41985 - LOG_ID_EVENT_VPN_CERT_REMOVAL .....	675
41986 - LOG_ID_EVENT_VPN_CERT_REGEN .....	676
41987 - LOG_ID_EVENT_VPN_CERT_UPDATE .....	677
41988 - LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE .....	678
41989 - LOG_ID_EVENT_VPN_CERT_ERR .....	679
41990 - LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED .....	679
41991 - LOG_ID_EVENT_VPN_CERT_EXPORT .....	680
42201 - LOG_ID_NETX_VMX_ATTACH .....	681
42202 - LOG_ID_NETX_VMX_DETACH .....	682
42203 - LOG_ID_NETX_VMX_DENIED .....	682
43008 - LOG_ID_EVENT_AUTH_SUCCESS .....	683
43009 - LOG_ID_EVENT_AUTH_FAILED .....	684
43010 - LOG_ID_EVENT_AUTH_LOCKOUT .....	685
43011 - LOG_ID_EVENT_AUTH_TIME_OUT .....	686
43014 - LOG_ID_EVENT_AUTH_FSAE_LOGON .....	687
43015 - LOG_ID_EVENT_AUTH_FSAE_LOGOFF .....	688
43016 - LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS .....	689
43017 - LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL .....	690
43018 - LOG_ID_EVENT_AUTH_FGOVRD_FAIL .....	691
43020 - LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS .....	692
43025 - LOG_ID_EVENT_AUTH_PROXY_SUCCESS .....	692
43026 - LOG_ID_EVENT_AUTH_PROXY_FAILED .....	693
43027 - LOG_ID_EVENT_AUTH_PROXY_TIME_OUT .....	694
43028 - LOG_ID_EVENT_AUTH_PROXY_GROUP_INFO_FAILED .....	695
43029 - LOG_ID_EVENT_AUTH_WARNING_SUCCESS .....	696
43030 - LOG_ID_EVENT_AUTH_WARNING_TBL_FULL .....	697
43032 - LOG_ID_EVENT_AUTH_PROXY_USER_LIMIT_REACHED .....	698
43033 - LOG_ID_EVENT_AUTH_PROXY_MULTIPLE_LOGIN .....	699
43034 - LOG_ID_EVENT_AUTH_PROXY_NO_RESP .....	700
43037 - LOG_ID_EVENT_AUTH_IPV4_FLUSH .....	701
43038 - LOG_ID_EVENT_AUTH_IPV6_FLUSH .....	702
43039 - LOG_ID_EVENT_AUTH_LOGON .....	702
43040 - LOG_ID_EVENT_AUTH_LOGOUT .....	703
43041 - LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT .....	704
43042 - LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE .....	705
43043 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS .....	706
43044 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL .....	707
43045 - LOG_ID_EVENT_AUTH_8021X_SUCCESS .....	708
43046 - LOG_ID_EVENT_AUTH_8021X_FAIL .....	709
43050 - LOG_ID_EVENT_AUTH_FSAE_CONNECT .....	710
43051 - LOG_ID_EVENT_AUTH_FSAE_DISCONNECT .....	710

43264 - LOGID_MMS_STATS .....	711
43520 - LOG_ID_EVENT_WIRELESS_SYS .....	712
43521 - LOG_ID_EVENT_WIRELESS_ROGUE .....	713
43522 - LOG_ID_EVENT_WIRELESS_WTP .....	714
43524 - LOG_ID_EVENT_WIRELESS_STA .....	715
43525 - LOG_ID_EVENT_WIRELESS_ONWIRE .....	716
43526 - LOG_ID_EVENT_WIRELESS_WTPR .....	718
43527 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG .....	719
43528 - LOG_ID_EVENT_WIRELESS_WTPR_ERROR .....	719
43529 - LOG_ID_EVENT_WIRELESS_CLB .....	720
43530 - LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE .....	721
43531 - LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH .....	722
43532 - LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP .....	723
43533 - LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI .....	725
43534 - LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR .....	726
43535 - LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV .....	727
43542 - LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD .....	728
43544 - LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD .....	729
43546 - LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH .....	730
43548 - LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP .....	731
43550 - LOG_ID_EVENT_WIRELESS_STA_LOCATE .....	732
43551 - LOG_ID_EVENT_WIRELESS_WTP_JOIN .....	733
43552 - LOG_ID_EVENT_WIRELESS_WTP_LEAVE .....	734
43553 - LOG_ID_EVENT_WIRELESS_WTP_FAIL .....	735
43554 - LOG_ID_EVENT_WIRELESS_WTP_UPDATE .....	736
43555 - LOG_ID_EVENT_WIRELESS_WTP_RESET .....	737
43556 - LOG_ID_EVENT_WIRELESS_WTP_KICK .....	738
43557 - LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE .....	739
43558 - LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR .....	740
43559 - LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH .....	741
43560 - LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED .....	742
43561 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP .....	742
43562 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN .....	743
43563 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT .....	744
43564 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR .....	745
43565 - LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR .....	747
43566 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE .....	748
43567 - LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT .....	750
43568 - LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR .....	751
43569 - LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED .....	752
43570 - LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED .....	754
43571 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG .....	755
43572 - LOG_ID_EVENT_WIRELESS_STA ASSO .....	757
43573 - LOG_ID_EVENT_WIRELESS_STA_AUTH .....	758
43574 - LOG_ID_EVENT_WIRELESS_STA_DASS .....	759
43575 - LOG_ID_EVENT_WIRELESS_STA_DAUT .....	760
43576 - LOG_ID_EVENT_WIRELESS_STA_IDLE .....	761
43577 - LOG_ID_EVENT_WIRELESS_STA_DENY .....	763
43578 - LOG_ID_EVENT_WIRELESS_STA_KICK .....	764

43579 - LOG_ID_EVENT_WIRELESS_STA_IP .....	765
43580 - LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP .....	766
43581 - LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN .....	767
43582 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED .....	768
43583 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED .....	769
43584 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE .....	770
43585 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED .....	771
43586 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN .....	772
43587 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START .....	773
43588 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN .....	774
43589 - LOG_ID_EVENT_WIRELESS_WTPR_RADAR .....	775
43590 - LOG_ID_EVENT_WIRELESS_WTPR_NOL .....	776
43591 - LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS .....	777
43592 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY .....	778
43593 - LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER .....	779
43594 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER .....	780
43595 - LOG_ID_EVENT_WIRELESS_CLB_DENY .....	781
43596 - LOG_ID_EVENT_WIRELESS_CLB_RETRY .....	781
43597 - LOG_ID_EVENT_WIRELESS_WTP_ADD .....	782
43598 - LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS .....	783
43599 - LOG_ID_EVENT_WIRELESS_WTP_DEL .....	784
43600 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP .....	785
43601 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON .....	786
43602 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS .....	787
43603 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE .....	788
43604 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST .....	790
43605 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS .....	791
43606 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE .....	792
43607 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK .....	793
43608 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE .....	794
43609 - LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_START .....	795
43610 - LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_STOP .....	796
43611 - LOG_ID_EVENT_WIRELESS_SYS_AC_UP .....	797
43612 - LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED .....	797
43613 - LOG_ID_EVENT_WIRELESS_WTP_ERR .....	798
43614 - LOG_ID_EVENT_WIRELESS_DHCP_STAVATION .....	799
43615 - LOG_ID_EVENT_WIRELESS_SYS_AC_IPSEC_FAIL .....	800
43616 - LOG_ID_EVENT_WIRELESS_WTPR_NOL_ADD .....	801
43617 - LOG_ID_EVENT_WIRELESS_WTPPROF_ADJUSTED .....	802
43618 - LOG_ID_EVENT_WIRELESS_WTP_IMAGE_RC_SUCCESS .....	803
43621 - LOG_ID_EVENT_WIRELESS_WTP_DATA_CHAN_CHG .....	803
43776 - LOG_ID_EVENT_NAC_QUARANTINE .....	804
43777 - LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE .....	805
43800 - LOG_ID_EVENT_ELBC_BLADE_JOIN .....	807
43801 - LOG_ID_EVENT_ELBC_BLADE_LEAVE .....	807
43802 - LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND .....	808
43803 - LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST .....	809
43804 - LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE .....	810
43805 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND .....	811

43806 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST	811
43807 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE	812
43808 - LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE	813
43809 - LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE	814
44544 - LOGID_EVENT_CONFIG_PATH	815
44545 - LOGID_EVENT_CONFIG_OBJ	815
44546 - LOGID_EVENT_CONFIG_ATTR	816
44547 - LOGID_EVENT_CONFIG_OBJATTR	817
44548 - LOGID_EVENT_CONFIG_EXEC	818
44549 - LOGID_EVENT_CONFIG_OBJATTR_MTNER	819
44550 - LOGID_EVENT_CONFIG_OBJ_MTNER	820
44551 - LOGID_EVENT_CONFIG_ATTR_MTNER	821
44552 - LOGID_EVENT_CONFIG_PATH_MTNER	821
44553 - LOGID_EVENT_CONFIG_FIXEDPORT_DIS	822
45057 - LOG_ID_FCC_ADD	823
45058 - LOG_ID_FCC_CLOSE	824
45061 - LOG_ID_FCC_CLOSE_BY_TYPE	824
45071 - LOG_ID_FCC_VULN_SCAN	825
45081 - LOG_ID_FCC_COMPL_CHANGE	826
45082 - LOG_ID_FCC_NOT_COMPL	827
45083 - LOG_ID_FCC_NOT_COMPL_DEBUG	828
45084 - LOG_ID_FCC_SIG_IDS_DETAILS	829
45100 - LOG_ID_EC_REG_FAIL_LIMIT	830
45101 - LOG_ID_EC_REG_SUCCEED	831
45102 - LOG_ID_EC_REG_RENEWED	832
45103 - LOG_ID_EC_REG_BLOCK	833
45104 - LOG_ID_EC_REG_UNBLOCK	833
45105 - LOG_ID_EC_REG_DEREG	834
45106 - LOG_ID_EC_REG_LIC_UPGRADED	835
45107 - LOG_ID_EC_CONF_DISTRIBUTED	835
45108 - LOG_ID_EC_FTCL_UNREG	836
45109 - LOG_ID_EC_FTCL_LOGOFF	837
45110 - LOG_ID_EC_FTCL_ENABLE_NOTSYNC	838
45111 - LOG_ID_EC_REG_SYNC_FAIL	839
45112 - LOG_ID_EC_REG_FAIL_KEY	839
45113 - LOG_ID_EC_REG_FAIL_BLOCKED	840
45114 - LOG_ID_EC_REG_QUARANTINE	841
45115 - LOG_ID_EC_REG_UNQUARANTINE	842
45116 - LOG_ID_EC_REG_UNQUARANTINE_ALL	842
45117 - LOG_ID_EC_REG_FAIL_VER	843
45118 - LOG_ID_EC_REG_FAIL_UNSUPPORTED	844
45151 - LOG_ID_EVENT_DSSCC_FAIL	845
45152 - LOG_ID_EVENT_DSSCC_PASS	846
45161 - LOG_ID_EVENT_DSSCC_EXEC	846
46000 - LOG_ID_VIP_REAL_SVR_ENA	847
46001 - LOG_ID_VIP_REAL_SVR_DISA	848
46002 - LOG_ID_VIP_REAL_SVR_UP	849
46003 - LOG_ID_VIP_REAL_SVR_DOWN	850
46004 - LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN	850

46005 - LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN	851
46006 - LOG_ID_VIP_REAL_SVR_FAIL	852
46400 - LOG_ID_EVENT_EXT_SYS	853
46401 - LOG_ID_EVENT_EXT_LOCAL	853
46402 - LOG_ID_EVENT_EXT_REMOTE	854
46403 - LOG_ID_EVENT_EXT_LOCAL_ERROR	855
46501 - LOG_ID_INTERNAL_LTE_MODEM_DETECTION	856
46502 - LOG_ID_INTERNAL_LTE_MODEM_GPSD	856
46503 - LOG_ID_INTERNAL_LTE_MODEM_GPS_LOC_ACQUISITION	857
46504 - LOG_ID_INTERNAL_LTE_MODEM_BILLD	858
46505 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_PURGED	858
46506 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_DAILY_LOG	859
46507 - LOG_ID_INTERNAL_LTE_MODEM_FW_UPGRADE	860
46508 - LOG_ID_INTERNAL_LTE_MODEM_QDL_DETECTION	860
46509 - LOG_ID_INTERNAL_LTE_MODEM_REBOOT	861
46510 - LOG_ID_INTERNAL_LTE_MODEM_OP_MODE	861
46511 - LOG_ID_INTERNAL_LTE_MODEM_POWER_ON_OFF	862
46512 - LOG_ID_INTERNAL_LTE_MODEM_SIM_STATE	863
46513 - LOG_ID_INTERNAL_LTE_MODEM_LINK_CONNECTION	863
46514 - LOG_ID_INTERNAL_LTE_MODEM_MANUAL_HANOVER	864
46515 - LOG_ID_INTERNAL_LTE_MODEM_IP_ADDR	865
46600 - LOG_ID_EVENT_AUTOMATION_TRIGGERED	865
46900 - LOG_ID_POE_STATUS_REPORT	866
47203 - LOG_ID_ENTER_BYPASS	867
47204 - LOG_ID_EXIT_BYPASS	867
48000 - LOG_ID_WAD_SSL_RCV_HS	868
48001 - LOG_ID_WAD_SSL_RCV_WRG_HS	869
48002 - LOG_ID_WAD_SSL_SENT_HS	870
48003 - LOG_ID_WAD_SSL_WRG_HS_LEN	871
48004 - LOG_ID_WAD_SSL_RCV_CCS	872
48005 - LOG_ID_WAD_SSL_RSA_DH_FAIL	873
48006 - LOG_ID_WAD_SSL_SENT_CCS	873
48007 - LOG_ID_WAD_SSL_BAD_HASH	874
48009 - LOG_ID_WAD_SSL_DECRY_FAIL	875
48011 - LOG_ID_WAD_SSL_LESS_MINOR	876
48013 - LOG_ID_WAD_SSL_NOT_SUPPORT_CS	877
48016 - LOG_ID_WAD_SSL_HS_FIN	878
48017 - LOG_ID_WAD_SSL_HS_TOO_LONG	879
48019 - LOG_ID_WAD_SSL_SENT_ALERT	880
48023 - LOG_ID_WAD_SSL_RCV_ALERT	881
48027 - LOG_ID_WAD_SSL_INVALID_CONT_TYPE	882
48029 - LOG_ID_WAD_SSL_BAD_CCS_LEN	883
48031 - LOG_ID_WAD_SSL_BAD_DH	883
48032 - LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG	884
48034 - LOG_ID_WAD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH	885
48035 - LOG_ID_WAD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_MISMATCH	886
48038 - LOG_ID_WAD_SSL_RCV_FATAL_ALERT	887
48039 - LOG_ID_WAD_SSL_SENT_FATAL_ALERT	888

48101 - LOG_ID_WAD_AUTH_FAIL_PSK .....	889
48102 - LOG_ID_WAD_AUTH_FAIL_OTH .....	890
48300 - LOG_ID_WRG_SVR_FGT_CONF .....	891
48301 - LOG_ID_UNEXP_APP_TYPE .....	892
51000 - LOG_ID_NB_TBL_CHG .....	893
52000 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_SUMMARY .....	893
53000 - LOG_ID_SDNC_CONNECTED .....	894
53001 - LOG_ID_SDNC_DISCONNECTED .....	895
53002 - LOG_ID_SDNC_SUBSCRIBE .....	896
53003 - LOG_ID_SDNC_UNSUBSCRIBE .....	896
99951 - LOG_ID_NP6_IPSEC_ENGINE_BUSY .....	897
99952 - LOG_ID_NP6_IPSEC_ENGINE_POSSIBLY_LOCKUP .....	898
99953 - LOG_ID_NP6_IPSEC_ENGINE_LOCKUP .....	898
GTP .....	900
41216 - LOGID_GTP_FORWARD .....	900
41217 - LOGID_GTP_DENY .....	901
41218 - LOGID_GTP_RATE_LIMIT .....	902
41219 - LOGID_GTP_STATE_INVALID .....	904
41220 - LOGID_GTP_TUNNEL_LIMIT .....	905
41221 - LOGID_GTP_TRAFFIC_COUNT .....	907
41222 - LOGID_GTP_USER_DATA .....	908
41223 - LOGID_GTPV2_FORWARD .....	909
41224 - LOGID_GTPV2_DENY .....	910
41225 - LOGID_GTPV2_RATE_LIMIT .....	912
41226 - LOGID_GTPV2_STATE_INVALID .....	913
41227 - LOGID_GTPV2_TUNNEL_LIMIT .....	914
41228 - LOGID_GTPV2_TRAFFIC_COUNT .....	915
41229 - LOGID_GTPU_FORWARD .....	917
41230 - LOGID_GTPU_DENY .....	918
IPS .....	919
16384 - LOGID_ATTCK_SIGNATURE_TCP_UDP .....	919
16385 - LOGID_ATTCK_SIGNATURE_ICMP .....	920
16386 - LOGID_ATTCK_SIGNATURE_OTHERS .....	922
16399 - LOGID_ATTACK_MALICIOUS_URL .....	924
SSH .....	926
61000 - LOG_ID_SSH_COMMAND_BLOCK .....	926
61001 - LOG_ID_SSH_COMMAND_BLOCK_ALERT .....	927
61002 - LOG_ID_SSH_COMMAND_PASS .....	928
61003 - LOG_ID_SSH_COMMAND_PASS_ALERT .....	929
61010 - LOG_ID_SSH_CHANNEL_BLOCK .....	931
61011 - LOG_ID_SSH_CHANNEL_PASS .....	932
Traffic .....	934
2 - LOG_ID_TRAFFIC_ALLOW .....	934
3 - LOG_ID_TRAFFIC_DENY .....	937
4 - LOG_ID_TRAFFIC_OTHER_START .....	940
5 - LOG_ID_TRAFFIC_OTHER_ICMP_ALLOW .....	943
6 - LOG_ID_TRAFFIC_OTHER_ICMP_DENY .....	946
7 - LOG_ID_TRAFFIC_OTHER_INVALID .....	949
8 - LOG_ID_TRAFFIC_WANOPT .....	952

9 - LOG_ID_TRAFFIC_WEBCACHE .....	955
10 - LOG_ID_TRAFFIC_EXPLICIT_PROXY .....	957
11 - LOG_ID_TRAFFIC_FAIL_CONN .....	960
12 - LOG_ID_TRAFFIC_MULTICAST .....	961
13 - LOG_ID_TRAFFIC_END_FORWARD .....	964
14 - LOG_ID_TRAFFIC_END_LOCAL .....	968
15 - LOG_ID_TRAFFIC_START_FORWARD .....	971
16 - LOG_ID_TRAFFIC_START_LOCAL .....	974
17 - LOG_ID_TRAFFIC_SNIFFER .....	977
19 - LOG_ID_TRAFFIC_BROADCAST .....	981
20 - LOG_ID_TRAFFIC_STAT .....	984
21 - LOG_ID_TRAFFIC_SNIFFER_STAT .....	987
22 - LOG_ID_TRAFFIC_UTM_CORRELATION .....	990
VoIP .....	995
44032 - LOGID_EVENT_VOIP_SIP .....	995
44033 - LOGID_EVENT_VOIP_SIP_BLOCK .....	996
44034 - LOGID_EVENT_VOIP_SIP_FUZZING .....	997
44035 - LOGID_EVENT_VOIP_SCCP_REGISTER .....	999
44036 - LOGID_EVENT_VOIP_SCCP_UNREGISTER .....	1000
44037 - LOGID_EVENT_VOIP_SCCP_CALL_BLOCK .....	1001
44038 - LOGID_EVENT_VOIP_SCCP_CALL_INFO .....	1002
WAF .....	1004
30248 - LOGID_WAF_SIGNATURE_BLOCK .....	1004
30249 - LOGID_WAF_SIGNATURE_PASS .....	1005
30250 - LOGID_WAF_SIGNATURE_ERASE .....	1007
30251 - LOGID_WAF_CUSTOM_SIGNATURE_BLOCK .....	1008
30252 - LOGID_WAF_CUSTOM_SIGNATURE_PASS .....	1009
30253 - LOGID_WAF_METHOD_BLOCK .....	1011
30255 - LOGID_WAF_ADDRESS_LIST_BLOCK .....	1012
30257 - LOGID_WAF_CONSTRAINTS_BLOCK .....	1014
30258 - LOGID_WAF_CONSTRAINTS_PASS .....	1015
30259 - LOGID_WAF_URL_ACCESS_PERMIT .....	1017
30260 - LOGID_WAF_URL_ACCESS_BYPASS .....	1018
30261 - LOGID_WAF_URL_ACCESS_BLOCK .....	1019
Web .....	1022
12288 - LOG_ID_WEB_CONTENT_BANWORD .....	1022
12289 - LOG_ID_WEB_CONTENT_MMS_BANWORD .....	1023
12290 - LOG_ID_WEB_CONTENT_EXEMPTWORD .....	1025
12291 - LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD .....	1027
12292 - LOG_ID_WEB_CONTENT_KEYWORD .....	1029
12293 - LOG_ID_WEB_CONTENT_SEARCH .....	1030
12305 - LOG_ID_WEB_CONTENT_MMS_BANWORD_NOTIF .....	1032
12544 - LOG_ID_URL_FILTER_BLOCK .....	1034
12545 - LOG_ID_URL_FILTER_EXEMPT .....	1036
12546 - LOG_ID_URL_FILTER_ALLOW .....	1037
12547 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK .....	1039
12548 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK .....	1041
12549 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS .....	1042
12550 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS .....	1043



12551 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK .....	1045
12552 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS .....	1046
12553 - LOG_ID_URL_FILTER_INVALID_CERT .....	1048
12554 - LOG_ID_URL_FILTER_INVALID_SESSION .....	1049
12555 - LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK .....	1051
12556 - LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS .....	1052
12557 - LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE .....	1054
12558 - LOG_ID_URL_FILTER_RATING_ERR .....	1054
12559 - LOG_ID_URL_FILTER_PASS .....	1055
12560 - LOG_ID_URL_WISP_BLOCK .....	1057
12561 - LOG_ID_URL_WISP_REDIR .....	1059
12562 - LOG_ID_URL_WISP_ALLOW .....	1060
12688 - LOG_ID_WEB_SSL_EXEMPT .....	1062
12800 - LOG_ID_WEB_FTGD_ERR .....	1063
12801 - LOG_ID_WEB_FTGD_WARNING .....	1065
12802 - LOG_ID_WEB_FTGD_QUOTA .....	1067
13056 - LOG_ID_WEB_FTGD_CAT_BLK .....	1068
13057 - LOG_ID_WEB_FTGD_CAT_WARN .....	1070
13312 - LOG_ID_WEB_FTGD_CAT_ALLOW .....	1071
13313 - LOG_ID_WEB_FTGD_RULE_ALLOW .....	1073
13314 - LOG_ID_WEB_FTGD_OFF_SITE_ALLOW .....	1075
13315 - LOG_ID_WEB_FTGD_QUOTA_COUNTING .....	1077
13316 - LOG_ID_WEB_FTGD_QUOTA_EXPIRED .....	1079
13317 - LOG_ID_WEB_URL .....	1081
13568 - LOG_ID_WEB_SCRIPTFILTER_ACTIVEX .....	1082
13573 - LOG_ID_WEB_SCRIPTFILTER_COOKIE .....	1084
13584 - LOG_ID_WEB_SCRIPTFILTER_APPLET .....	1086
13600 - LOG_ID_WEB_SCRIPTFILTER_OTHER .....	1087
13601 - LOG_ID_WEB_WF_COOKIE .....	1089
13602 - LOG_ID_WEB_WF_REFERERER .....	1091
13603 - LOG_ID_WEB_WF_COMMAND_BLOCK .....	1092
13616 - LOG_ID_CONTENT_TYPE_BLOCK .....	1094
13632 - LOGID_HTTP_HDR_CHG_REQ .....	1095
13633 - LOGID_HTTP_HDR_CHG_RESP .....	1096

# Change Log

Date	Change Description
2023-06-08	Initial release.

# Introduction

This document provides information about all the log messages applicable to the FortiGate devices running FortiOS version 6.0.17 or higher. The logs are intended for administrators to use as reference for more information about a specific log entry and message generated by FortiOS.

This document also provides information about log fields when FortiOS sends log messages to remote syslog servers in Common Event Format (CEF). See [CEF Support on page 45](#). It also describes how to enable extended logging. See [UTM Extended Logging on page 56](#).



Performance statistics are not logged to disk. Performance statistics can be received by a syslog server or by FortiAnalyzer.

---

## Before you begin

Before you begin using this reference, read the following notes:

- Information in this document applies to all FortiGate units that are currently running FortiOS 6.0.17 or higher.
- Ensure that you have enabled logging for the FortiOS unit. For more information, see the *Logging and Reporting* chapter in the *FortiOS Handbook*.
- Each log message is displayed in the *Log & Report* pane of the GUI. You can also download the RAW format from the *Log & Report* pane.
- Each log message is documented similar to how it appears in the RAW format. For more information, see the *Logging and Reporting* chapter in the *FortiOS Handbook*.



This reference contains detailed information for each log type and subtype; however, this reference contains only information gathered at publication and, as a result, not every log message field contains detailed information.

---

## Overview

The log types described in this document report traffic, security, and event log information useful for system administrators when recording, monitoring, and tracing the operation of a FortiGate device running FortiOS. The logs provide information regarding the following:

- Firewall attacks
- Configuration changes
- Successful and unsuccessful system operations

## What's new

This section identifies major changes in the Log Reference from version 6.0.0 and later.

### FortiOS 6.0.17

There are no major log changes between FortiOS 6.0.16 and 6.0.17.

### FortiOS 6.0.16

There are no major log changes between FortiOS 6.0.15 and 6.0.16.

### FortiOS 6.0.15

There are no major log changes between FortiOS 6.0.14 and 6.0.15.

### FortiOS 6.0.14

There are no major log changes between FortiOS 6.0.13 and 6.0.14.

### FortiOS 6.0.13

There are no major log changes between FortiOS 6.0.12 and 6.0.13.

### FortiOS 6.0.12

There are no major log changes between FortiOS 6.0.11 and 6.0.12.

### FortiOS 6.0.11

There are no major log changes between FortiOS 6.0.10 and 6.0.11.

### FortiOS 6.0.10

There are no major log changes between FortiOS 6.0.9 and 6.0.10.

### FortiOS 6.0.9

There are no major log changes between FortiOS 6.0.8 and 6.0.9.

## FortiOS 6.0.8

There are no major log changes between FortiOS 6.0.7 and 6.0.8.

## FortiOS 6.0.7

There are no major log changes between FortiOS 6.0.6 and 6.0.7.

## FortiOS 6.0.6

There are no major log changes between FortiOS 6.0.5 and 6.0.6.

## FortiOS 6.0.5

There are no major log changes between FortiOS 6.0.4 and 6.0.5.

## FortiOS 6.0.4

There are no major log changes between FortiOS 6.0.3 and 6.0.4.

## FortiOS 6.0.3

There are no major log changes between FortiOS 6.0.2 and 6.0.3.

## FortiOS 6.0.2

There are no major log changes between FortiOS 6.0.1 and 6.0.2.

## FortiOS 6.0.1

There are no major log changes between FortiOS 6.0.0 and 6.0.1.

## FortiOS 6.0.0

### SSH

- SSH (Secure Socket Shell) was added as a new log type with a log ID of 16.

## Extended logging

- Extended logging is supported for UTM log types. A new `rawdata` field contains the information, and the full information is available when sending extended logs to reliable Syslog servers. See [UTM Extended Logging on page 56](#).



As of FortiOS 5.6.0, the value of every string type field is now enclosed in double quotes.

---

# Log Types and Subtypes

This section describes the log types, subtypes, and priority levels. It also describes the log field format.

## Type

Each log entry contains a Type (type) or category field that indicates its log type and which log file stores the log entry.

## Subtype

Each log entry contains a Sub Type (subtype) or subcategory field within a log type, based on the feature associated with the cause of the log entry.

For example:

- In event logs, some log entries have a subtype of user, system, or other subtypes.
- In traffic logs, the subtypes are: local, forward, multicast, and sniffer.

## List of log types and subtypes

FortiGate devices can record the following types and subtypes of log entry information:

Type	Description	Subtype
<b>Traffic</b>	Records traffic flow information, such as an HTTP/HTTPS request and its response, if any.	<ul style="list-style-type: none"><li>• FORWARD</li><li>• LOCAL</li><li>• MULTICAST</li><li>• SNIFFER</li></ul>
<b>Event</b>	Records system and administrative events, such as downloading a backup copy of the configuration, or daemon activities.	<ul style="list-style-type: none"><li>• COMPLIANCE-CHECK</li><li>• ENDPOINT</li><li>• HA</li><li>• ROUTER</li><li>• SECURITY-RATING</li><li>• SYSTEM</li><li>• USER</li><li>• VPN</li><li>• WAD</li></ul>

Type	Description	Subtype
		<ul style="list-style-type: none"> <li>• WIRELESS</li> </ul>
<b>UTM</b>	Records UTM events.	See list of UTM log subtypes below

## UTM log subtypes

UTM Log Subtypes	Description	Event Type
Anomaly	Records intrusion attempts.	<ul style="list-style-type: none"> <li>• ANOMALY</li> </ul>
App	Records intrusion attempts. Application control log is output when a signature matches an application pattern.	<ul style="list-style-type: none"> <li>• APP-CTRL-ALL</li> </ul>
AV	Records virus attacks.	<ul style="list-style-type: none"> <li>• ANALYTICS</li> <li>• BOTNET</li> <li>• COMMAND-BLOCKED</li> <li>• CONTENT-DISARM</li> <li>• FILENAME</li> <li>• FILETYPE-EXECUTABLE</li> <li>• INFECTED</li> <li>• MIMEFRACTURED</li> <li>• OVERSIZE</li> <li>• SCANERROR</li> <li>• SWITCHPROTO</li> </ul>
DLP	Records data leak prevention events.	<ul style="list-style-type: none"> <li>• DLP</li> </ul>
DNS	Records domain name server events.	<ul style="list-style-type: none"> <li>• DNS-QUERY</li> <li>• DNS-RESPONSE</li> </ul>
Email	Records email filter events.	<ul style="list-style-type: none"> <li>• CARRIER-ENDPOINT-FILTER</li> <li>• GMAIL</li> <li>• IMAP</li> <li>• MAPI</li> <li>• MASS-MMS</li> <li>• MSN-HOTMAIL</li> <li>• POP3</li> <li>• SMTP</li> <li>• YAHOO-MAIL</li> </ul>
GTP	Records GTP events.	<ul style="list-style-type: none"> <li>• GTP-ALL</li> </ul>
IPS	Records intrusion prevention events.	<ul style="list-style-type: none"> <li>• MALICIOUS-URL</li> </ul>



UTM Log Subtypes	Description	Event Type
		<ul style="list-style-type: none"> <li>SIGNATURE</li> </ul>
SSH	Records Secure Socket Shell events.	<ul style="list-style-type: none"> <li>SSH-CHANNEL</li> <li>SSH-COMMAND</li> </ul>
VoIP	Records voice over IP events.	<ul style="list-style-type: none"> <li>VOIP</li> </ul>
WAF	Records web application firewall information for FortiWeb appliances and virtual appliances.	<ul style="list-style-type: none"> <li>WAF-ADDRESS-LIST</li> <li>WAF-CUSTOM-SIGNATURE</li> <li>WAF-HTTP-CONSTRAINT</li> <li>WAF-HTTP-METHOD</li> <li>WAF-SIGNATURE</li> <li>WAF-URL-ACCESS</li> </ul>
Web	Records web filter events.	<ul style="list-style-type: none"> <li>ACTIVEXFILTER</li> <li>APPLETFILTER</li> <li>CONTENT</li> <li>COOKIEFILTER</li> <li>FTGD_ALLOW</li> <li>FTGD_BLK</li> <li>FTGD_ERR</li> <li>FTGD_QUOTA</li> <li>FTGD_QUOTA_COUNTING</li> <li>HTTP_HEADER_CHANGE</li> <li>SCRIPTFILTER</li> <li>SSL-EXEMPT</li> <li>URLFILTER</li> <li>WEBFILTER_COMMAND_BLOCK</li> </ul>

## FortiOS priority levels

Each log entry contains a Level (level) field that indicates the estimated severity of the event that caused the log entry, such as `level=warning`, and therefore how high a priority it is likely to be. Level (level) associations with the descriptions below are not always uniform. They also may not correspond with your own definitions of how severe each event is. If you require notification when a specific event occurs, either configure SNMP traps or alert email by administrator-defined Severity Level (severity\_level) or ID (logid), not by Level (level).

Level (0 is highest)	Name	Description
0	Emergency	The system is unusable or not responding.

Level (0 is highest)	Name	Description
1	Alert	Immediate action required. Used in security logs.
2	Critical	Functionality is affected.
3	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
5	Notification	Information about normal events.
6	Information	General information about system operations. Used in event logs to record configuration changes.

For each location where the FortiGate device can store log files (disk, memory, Syslog or FortiAnalyzer), you can define a severity threshold. FortiOS stores all log messages equal to or exceeding the log severity level selected. For example, if you select Error, FortiOS will store log messages whose log severity level is Error, Critical, Alert, and Emergency.

## Log field format

The following table describes the standard format in which each log type is described in this document. For documentation purposes, all log types and subtypes follow this generic table format to present the log entry information.

Log Field Name	Description	Data Type	Length
appact	The security action from app control	string	16

# Log Schema Structure

This section describes the schema of the FortiOS log messages.

## Log message fields

Each log message consists of several sections of fields. In the FortiOS GUI, you can view the logs in the *Log & Report* pane, which displays the formatted view. If you want to view logs in raw format, you must download the log and view it in a text editor.

Following is an example of a traffic log message in raw format:

```
date=2017-11-15 time=11:44:16 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1510775056 srcip=10.1.100.155 srcname="pc1"
srcport=40772 srcintf="port12" srcintfrole="undefined" dstip=35.197.51.42
dstname="fortiguard.com" dstport=443 dstintf="port11" dstintfrole="undefined"
poluid="707a0d88-c972-51e7-bbc7-4d421660557b" sessionid=8058 proto=6 action="close"
policyid=1 policytype="policy" policymode="learn" service="HTTPS" dstcountry="United
States" srccountry="Reserved"trandisp="snat" transip=172.16.200.2 transport=40772
appid=40568 app="HTTPS.BROWSER" appcat="Web.Client" apprisk="medium" duration=2
sentbyte=1850 rcvbyte=39898 sentpkt=25 rcvpkt=37 utmaction="allow" countapp=1
devtype="Linux PC" osname="Linux" mastersrcmac="a2:e9:00:ec:40:01"
srcmac="a2:e9:00:ec:40:01" srcserver=0 utmref=0-220586
```

The following table provides an example of the log field information in the FortiOS GUI in the detailed view of the *Log & Report* pane and in the downloaded, raw log file.

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
<b>General</b>		
Date (date)	Day, month, and year when the log message was recorded.	date=2017-11-15
Time (time)	Hour clock when the log message was recorded.	time=11:44:16
Duration (seconds)	Duration of the session, in seconds.	duration=2
Session ID (sessionid)	ID for the session.	sessionid=8058
Virtual Domain (vd)	Name of the virtual domain in which the log message was recorded.	vd="vdom1"
NAT Translation (transport)	NAT source port.	transport=40772
<b>Source</b>		

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
IP (srcip)	IP address of the traffic's origin. The source varies by the direction: <ul style="list-style-type: none"> <li>In HTTP requests, this is the web browser or other client.</li> <li>In HTTP responses, this is the physical server.</li> </ul>	srcip=10.1.100.155
NAT IP (transip)	NAT source IP.	transip=172.16.200.2
Source Port (srcport)	Port number of the traffic's origin.	srcport=40772
Country (srccountry)	Name of the source country.	srccountry="Reserved"
Source Interface(srcintf)	Interface name of the traffic's origin.	srcintf="port12"
Source Name (srcname)	Name of the source.	srcname="pc1"
Source Interface Name (srcintfrole)	Name of the source interface.	srcintfrole="undefined"
Device Type (devtype)	Device type of the source.	devtype="Linux PC"
OS Name (osname)	OS of the source.	osname="Linux"
Master Source MAC (mastersrcmac)	The master MAC address for a host that has multiple network interfaces.	mastersrcmac="a2:e9:00:ec:40:01"
Source MAC (srcmac)	MAC address associated with the source IP address.	srcmac="a2:e9:00:ec:40:01"
Source Server (srcserver)	Server of the source.	srcserver=0
Device ID (devid)	Serial number of the device for the traffic's origin.	devid="FGVM02Q105060010"
<b>Destination</b>		
IP (dstip)	Destination IP address for the web.	dstip=35.197.51.42
Port (dstport)	Port number of the traffic's destination.	dstport=443
Country (dstcountry)	Name of the destination country.	dstcountry="United States"
Destination Interface (dstintf)	Interface of the traffic's destination.	dstintf="port11"
Destination Name (dstname)	Name of the destination.	dstname="fortiguard.com"
Destination Interface Name (dstintfrole)	Name of the destination interface.	dstintfrole="undefined"

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
<b>Application</b>		
Application Name (app)	Name of the application.	app="HTTPS.BROWSER"
Category (appcat)	Category of the application.	appcat="Web.Client"
Service (service)	Name of the service.	service="HTTPS"
Application ID (appid)	ID of the application.	appid=40568
Application Risk (apprisk)	Risk level of the application.	apprisk="medium"
countapp	Number of App Ctrl logs associated with the session.	countapp=1
<b>Data</b>		
Received bytes (rcvdbyte)	Number of bytes received.	rcvdbyte=39898
Received packets (rcvdpkt)	Number of packets received.	rcvdpkt=37
Sent bytes (sentbyte)	Number of bytes sent.	sentbyte=1850
Sent packets (sentpkt)	Number of packets sent.	sentpkt=25
<b>Action</b>		
Action (action)	Status of the session. Uses following definitions: <ul style="list-style-type: none"> <li>Deny: blocked by firewall policy</li> <li>Start: session start log (special option to enable logging at start of a session). This means firewall allowed.</li> <li>All Others: allowed by Firewall Policy and the status indicates how it was closed.</li> </ul>	action=close
Policy (policyid)	Name of the firewall policy governing the traffic which caused the log message.	policyid=1
Policy UUID (poluuid)	UUID for the firewall policy.	poluuid="707a0d88-c972-51e7-bbc7-4d421660557b"
Policy Type (policytype)		policytype="policy"
Policy Mode (policymode)	Firewall policy mode.	policymode="learn"

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
<b>Security</b>		
Level (level)	Security level rating.	level="notice"
<b>Other</b>		
Event Time (eventtime)	Epoch time the log was triggered by FortiGate. If you convert the epoch time to human readable time, it might not match the Date and Time in the header owing to a small delay between the time the log was triggered and recorded. The Log Time field is the same for the same log among all log devices, but the Date and Time might differ.	eventtime=1510775056
Protocol Number (proto)	tcp: The protocol used by web traffic (tcp by default)	proto=6
Type (type)	Log type. See <a href="#">Type on page 31</a>	type="traffic"
Log ID (logid)	Log ID. See <a href="#">Log ID definitions on page 39</a>	logid="0000000013"
Sub Type(subtype)	Subtype of the traffic. See <a href="#">Subtype on page 31</a> .	subtype="forward"
trandisp	NAT translation type.	trandisp="snat"
UTM Action (utmaction)	Security action performed by UTM.	utmaction="allow"
UTM Reference (utmref)	UTM reference number.	utmref=0-220586
UTM Reference (utmref)	UTM reference number.	utmref=0-220586

## Log ID numbers

The ID (logid) is a 10-digit field. It is a unique identifier for that specific log and includes the following information about the log entry.

Log ID number components	Description	Examples
Log Type	Represented by the first two digits of the log ID.	<ul style="list-style-type: none"> <li>Traffic log IDs begin with "00".</li> <li>Event log IDs begin with "01".</li> </ul>
Sub Type or Event Type	Represented by the second two digits of the log ID.	<ul style="list-style-type: none"> <li>VPN log subtype is represented with "01" which belongs to the Event log type</li> </ul>

Log ID number components	Description	Examples
		that is represented with "01". Therefore, all VPN related Event log IDs will begin with the 0101 log ID series.
Message ID	The last six digits of the log ID represent the message ID.	<ul style="list-style-type: none"> <li>An administrator account always has the log ID 0000003401.</li> </ul>

The logid field is a number assigned to all permutations of the same message. It classifies a log entry by the nature of the cause of the log message, such as administrator authentication failures or traffic. Other log messages that share the same cause will share the same logid.

## Log ID definitions

Following are the definitions for the log type IDs and subtype IDs applicable to FortiOS:

Log Category IDs	Subtype IDs
traffic: 0	<ul style="list-style-type: none"> <li>forward: 0</li> <li>local: 1</li> <li>multicast: 2</li> <li>sniffer: 4</li> </ul>
event: 1	<ul style="list-style-type: none"> <li>system: 0</li> <li>vpn: 1</li> <li>user: 2</li> <li>router: 3</li> <li>wireless: 4</li> <li>wad: 5</li> <li>endpoint: 7</li> <li>ha: 8</li> <li>compliance-check: 9</li> <li>security-rating: 10</li> </ul>
voip: 2	<ul style="list-style-type: none"> <li>voip: 14</li> </ul>
av: 3	<ul style="list-style-type: none"> <li>analytics: 1</li> <li>botnet: 2</li> <li>filetype-executable: 3</li> <li>content-disarm: 5</li> <li>command-blocked: 6</li> <li>infected: 11</li> <li>filename: 12</li> <li>oversize: 13</li> </ul>

Log Category IDs	Subtype IDs
	<ul style="list-style-type: none"> <li>• mimefragmented: 61</li> <li>• scanerror: 62</li> <li>• switchproto: 63</li> </ul>
web: 4	<ul style="list-style-type: none"> <li>• content: 14</li> <li>• urlfilter: 15</li> <li>• ftgd_blk: 16</li> <li>• ftgd_allow: 17</li> <li>• ftgd_err: 18</li> <li>• activexfilter: 35</li> <li>• cookiefilter: 36</li> <li>• appletfilter: 37</li> <li>• ftgd_quota_counting: 38</li> <li>• ftgd_quota: 40</li> <li>• scriptfilter: 41</li> <li>• webfilter_command_block: 43</li> <li>• http_header_change: 44</li> <li>• ssl-exempt: 45</li> </ul>
ips: 5	<ul style="list-style-type: none"> <li>• signature: 19</li> <li>• malicious-url: 21</li> </ul>
anomaly: 6	<ul style="list-style-type: none"> <li>• anomaly: 20</li> </ul>
email: 7	<ul style="list-style-type: none"> <li>• msn-hotmail: 5</li> <li>• yahoo-mail: 6</li> <li>• gmail: 7</li> <li>• smtp: 8</li> <li>• pop3: 9</li> <li>• imap: 10</li> <li>• mapi: 11</li> <li>• carrier-endpoint-filter: 47</li> <li>• mass-mms: 52</li> </ul>
dlp: 8	<ul style="list-style-type: none"> <li>• dlp: 54</li> </ul>
app: 9	<ul style="list-style-type: none"> <li>• app-ctrl-all: 59</li> </ul>
waf: 10	<ul style="list-style-type: none"> <li>• waf-signature: 0</li> <li>• waf-custom-signature: 1</li> <li>• waf-http-method: 2</li> <li>• waf-http-constraint: 3</li> <li>• waf-address-list: 4</li> <li>• waf-url-access: 5</li> </ul>



Log Category IDs	Subtype IDs
gtp: 11	<ul style="list-style-type: none"><li>• gtp-all: 0</li></ul>
dns: 12	<ul style="list-style-type: none"><li>• dns-query: 0</li><li>• dns-response: 1</li></ul>
ssh: 13	<ul style="list-style-type: none"><li>• ssh-command: 0</li><li>• ssh-channel: 1</li></ul>

# FortiGuard Web Filter Categories

The below details the mapping between FortiGuard Web Filter category names and numbers.

Number	Category
0	Unrated
1	Drug abuse
2	Alternative beliefs
3	Hacking
4	Illegal or unethical
5	Discrimination
6	Explicit violence
7	Abortion
8	Other adult materials
9	Advocacy organizations
11	Gambling
12	Extremist groups
13	Nudity and risque
14	Pornography
15	Dating
16	Weapons (sales)
17	Advertising
18	Brokerage and trading
19	Freeware and software downloads
20	Games
23	Web-based email
24	File sharing and storage
25	Streaming media and download
26	Malicious websites
28	Entertainment
29	Arts and culture
30	Education

Number	Category
31	Finance and banking
33	Health and wellness
34	Job search
35	Medicine
36	News and media
37	Social networking
38	Political organizations
39	Reference
40	Global religion
41	Search engines and portals
42	Shopping
43	General organizations
44	Society and lifestyles
46	Sports
47	Travel
48	Personal vehicles
49	Business
50	Information and computer security
51	Government and legal organizations
52	Information technology
53	Armed forces
54	Dynamic content
55	Meaningless content
56	Web hosting
57	Marijuana
58	Folklore
59	Proxy avoidance
61	Phishing
62	Plagiarism
63	Sex education

Number	Category
64	Alcohol
65	Tobacco
66	Lingerie and swimsuit
67	Sports hunting and war games
68	Web chat
69	Instant messaging
70	Newsgroups and message boards
71	Digital postcards
72	Peer-to-peer file sharing
75	Internet radio and TV
76	Internet telephony
77	Child education
78	Real estate
79	Restaurant and dining
80	Personal websites and blogs
81	Secure websites
82	Content servers
83	Child abuse
84	Web-based applications
85	Domain parking
86	Spam URLs
87	Personal privacy
88	Dynamic DNS
89	Auction
90	Newly observed domain
91	Newly registered domain
92	Charitable organizations
93	Remote access
94	Web analytics
95	Online meeting

# CEF Support

You can configure FortiOS 6.0.17 to send logs to remote syslog servers in Common Event Format (CEF) by using the `config log syslogd setting` command. For more information, see the *Logging and Reporting* chapter in the *FortiOS Handbook* and the *FortiOS CLI Reference*.

When CEF is enabled, FortiOS sends logs to syslog servers in CEF. This section describes how FortiOS logs support CEF.



You can view logs in CEF on remote syslog servers or FortiAnalyzer, but not in the FortiOS GUI.

---

## FortiOS to CEF log field mapping guidelines

The following CEF format:

```
Date/Time host CEF:Version|Device Vendor|Device Product|Device Version|Signature
ID|Name|Severity| [Extension]
```

Displays as following in FortiOS logs with CEF enabled:

```
"MMM dd HH:mm:ss" "hostname of the fortigate"
CEF:0|Fortinet|Fortigate|version|logid|type:subtype +[eventtype] +[action] +
[status]|reversed level|...
```

The `SignatureId` field in FortiOS logs maps to the `logid` field in CEF and should be last 5 digits of `logid`.

The `Name` field in CEF uses the following formula:

```
type:subtype + [eventtype] + [action] + [status]
```

Following is an example of the header and one key-value pair for extension from the Event VPN log in CEF:

```
#Feb 12 10:31:04 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|37127|event:vpn negotiate
success|3|FTNTFGTlogid=0101037127
```

The `type:subtype` field in FortiOS logs maps to the `cat` field in CEF.

Any fields in FortiOS logs that are unmatched to fields in CEF include the `FTNTFGT` prefix.

Quotes (" ") are removed from FortiOS logs to support CEF.

Forward slashes (/) in string values as well as the equal sign (=) and backward slashes (\) are escaped in FortiOS logs to support CEF.

## CEF priority levels

Following are the CEF priority levels. They are opposite of FortiOS priority levels. See also [FortiOS priority levels on page 33](#).

Level (8 is highest)	Name	Description
8	Emergency	The system is unusable or not responding.
7	Alert	Immediate action required. Used in security logs.
6	Critical	Functionality is affected.
5	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
3	Notification	Information about normal events.
2	Information	General information about system operations. Used in event logs to record configuration changes.
1	Debug	Debug information.

## Examples of CEF support

This section includes examples of how the different types of log message support CEF.

### Traffic log support for CEF

The following is an example of a traffic log on the FortiGate disk:

```
date=2018-12-27 time=11:07:55 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1545937675 srcip=10.1.100.11 srcport=54190
srcintf="port12" srcintfrole="undefined" dstip=52.53.140.235 dstport=443
dstintf="port11" dstintfrole="undefined" poluid="c2d460aa-fe6f-51e8-9505-
41b5117dfdd4" sessionid=402 proto=6 action="close" policyid=1 policytype="policy"
service="HTTPS" dstcountry="United States" srccountry="Reserved" trandisp="snat"
transip=172.16.200.1 transport=54190 appid=40568 app="HTTPS.BROWSER"
appcat="Web.Client" apprisk="medium" applist="g-default" duration=2 sentbyte=3652
rcvbyte=146668 sentpkt=58 rcvpkt=105 utmaction="allow" countapp=2 utmref=65532-56
```

The following is an example of a traffic log sent in CEF format to a syslog server:

```
Dec 27 11:07:55 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|00013|traffic:forward
close|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0000000013
cat=traffic:forward FTNTFGTsubtype=forward FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545937675 src=10.1.100.11 spt=54190 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined dst=52.53.140.235 dpt=443
deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined FTNTFGTpoluid=c2d460aa-
fe6f-51e8-9505-41b5117dfdd4 externalId=402 proto=6 act=close FTNTFGTpolicyid=1
FTNTFGTpolicytype=policy app=HTTPS FTNTFGTdstcountry=United States
FTNTFGTsrccountry=Reserved FTNTFGTtrandisp=snat sourceTranslatedAddress=172.16.200.1
```

```
sourceTranslatedPort=54190 FTNTFGTappid=40568 FTNTFGTapp=HTTPS.BROWSER
FTNTFGTappcat=Web.Client FTNTFGTapprisk=medium FTNTFGTapplist=g-default
FTNTFGTduration=2 out=3652 in=146668 FTNTFGTsentpkt=58 FTNTFGTrcvdpkt=105
FTNTFGTutmaction=allow FTNTFGTcountapp=2
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
type: subtype	cat
srcip	src
srcport	spt
srcintf	deviceInboundInterface
dstip	dst
dstport	dpt
dstintf	deviceOutboundInterface
sessionid	externalID
proto	proto
action	act
transip	sourceTranslatedAddress
transport	sourceTranslatedPort
service	app
sentbyte	out
rcvbyte	in

## Custom fields

To configure the traffic log with custom fields, enter the following CLI commands:

```
config log custom-field
  edit 1
    set name "custom_name1"
    set value "HN123456"
  next
  edit 2
    set name "custom_name2"
    set value "accounting_dpt"
  next
end
config firewall policy
  edit 1
    set name "A-v4-out"
    set uuid c2d460aa-fe6f-51e8-9505-41b5117dfdd4
    set srcintf "port12"
    set dstintf "port11"
    set srcaddr "all"
```

```

set dstaddr "all"
set action accept
set schedule "always"
set service "ALL"
set utm-status enable
set logtraffic all
set custom-log-fields "1" "2"
set application-list "g-default"
set ssl-ssh-profile "certificate-inspection"
set nat enable
next
end

```

The following is an example of a traffic log with custom fields on the FortiGate disk:

```

date=2018-12-27 time=11:12:30 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1545937950 srcip=10.1.100.11 srcport=58843
srcintf="port12" srcintfrole="undefined" dstip=172.16.200.55 dstport=53
dstintf="port11" dstintfrole="undefined" poluid="c2d460aa-fe6f-51e8-9505-41b5117dfdd4"
sessionid=440 proto=17 action="accept" policyid=1 policytype="policy"
service="DNS" dstcountry="Reserved" srccountry="Reserved"trandisp="snat"
transip=172.16.200.1 transport=58843 appid=16195 app="DNS" appcat="Network.Service"
apprisk="elevated" applist="g-default" duration=180 sentbyte=70 rcvdbyte=528
sentpkt=1 rcvdpkt=1 custom_name1="HN123456" custom_name2="accounting_dpt"

```

The following is an example of a traffic log with custom fields sent in CEF format to a syslog server:

```

Dec 27 11:12:30 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|00013|traffic:forward
accept|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0000000013
cat=traffic:forward FTNTFGTsubtype=forward FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545937950 src=10.1.100.11 spt=58843 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined dst=172.16.200.55 dpt=53 deviceOutboundInterface=port11
FTNTFGTdstintfrole=undefined FTNTFGTpoluid=c2d460aa-fe6f-51e8-9505-41b5117dfdd4
externalId=440 proto=17 act=accept FTNTFGTpolicyid=1 FTNTFGTpolicytype=policy
app=DNS FTNTFGTdstcountry=Reserved FTNTFGTsrccountry=Reserved FTNTFGTtrandisp=snat
sourceTranslatedAddress=172.16.200.1 sourceTranslatedPort=58843 FTNTFGTappid=16195
FTNTFGTapp=DNS FTNTFGTappcat=Network.Service FTNTFGTapprisk=elevated
FTNTFGTapplist=g-default FTNTFGTduration=180 out=70 in=528 FTNTFGTsentpkt=1
FTNTFGTrcvdpkt=1 FTNTFGTcustom_name1=HN123456 FTNTFGTcustom_name2=accounting_dpt

```

The following table maps FortiOS custom log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
custom_name1	FTNTFGTcustom_name1
custom_name2	FTNTFGTcustom_name2

## Event log support for CEF

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
msg	msg
cookies	requestCookies



FortiOS Log Field Name	CEF Field Name
user	duser
status	outcome
role	sourceServiceName
ui	sproc
reason	reason
action	act

## system subtype

The following is an example of a system subtype event log on the FortiGate disk:

```
date=2018-12-27 time=11:15:40 logid="0100032002" type="event" subtype="system"
  level="alert" vd="vdom1" eventtime=1545938140 logdesc="Admin login failed" sn="0"
  user="admin1" ui="https(172.16.200.254)" method="https" srcip=172.16.200.254
  dstip=172.16.200.1 action="login" status="failed" reason="name_invalid"
  msg="Administrator admin1 login failed from https(172.16.200.254) because of invalid
  user name"
```

The following is an example of a system subtype event log sent in CEF format to a syslog server:

```
Dec 27 11:15:40 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|32002|event:system login
  failed|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0100032002 cat=event:system
  FTNTFGTsubtype=system FTNTFGTlevel=alert FTNTFGTvd=vdom1 FTNTFGTeventtime=1545938140
  FTNTFGTlogdesc=Admin login failed FTNTFGTsn=0 duser=admin1 sproc=https
  (172.16.200.254) FTNTFGTmethod=https src=172.16.200.254 dst=172.16.200.1 act=login
  outcome=failed reason=name_invalid msg=Administrator admin1 login failed from https
  (172.16.200.254) because of invalid user name
```

## user subtype

The following is an example of a user subtype log on the FortiGate disk:

```
date=2018-12-27 time=11:17:35 logid="0102043008" type="event" subtype="user"
  level="notice" vd="vdom1" eventtime=1545938255 logdesc="Authentication success"
  srcip=10.1.100.11 dstip=172.16.200.55 policyid=1 interface="port12" user="bob"
  group="N/A" authproto="TELNET(10.1.100.11)" action="authentication" status="success"
  reason="N/A" msg="User bob succeeded in authentication"
```

The following is an example of a user subtype log sent in CEF format to a syslog server:

```
Dec 27 11:17:35 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|43008|event:user
  authentication success|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0102043008
  cat=event:user FTNTFGTsubtype=user FTNTFGTlevel=notice FTNTFGTvd=vdom1
  FTNTFGTeventtime=1545938255 FTNTFGTlogdesc=Authentication success src=10.1.100.11
  dst=172.16.200.55 FTNTFGTpolicyid=1 deviceInboundInterface=port12 duser=bob
  FTNTFGTgroup=N/A FTNTFGTauthproto=TELNET(10.1.100.11) act=authentication
  outcome=success reason=N/A msg=User bob succeeded in authentication
```

## Antivirus log support for CEF

The following is an example of an antivirus log on the FortiGate disk:

```
date=2018-12-27 time=11:20:49 logid="0211008192" type="utm" subtype="virus"
eventtype="infected" level="warning" vd="vdom1" eventtime=1545938448 msg="File is
infected." action="blocked" service="HTTP" sessionid=695 srcip=10.1.100.11
dstip=172.16.200.55 srcport=44356 dstport=80 srcintf="port12"
srcintfrole="undefined" dstintf="port11" dstintfrole="undefined" policyid=1 proto=6
direction="incoming" filename="eicar.com" quarskip="File-was-not-quarantined."
virus="EICAR_TEST_FILE" dtype="Virus" ref="http://www.fortinet.com/ve?vn=EICAR_TEST_
FILE" virusid=2172 url="http://172.16.200.55/virus/eicar.com" profile="g-default"
user="bob" agent="curl/7.47.0"
analyticscksum="275a021bbfb6489e54d471899f7db9d1663fc695ec2fe2a2c4538aabf651fd0f"
analyticssubmit="false" crscore=50 crlevel="critical"
```

The following is an example of an antivirus log sent in CEF format to a syslog server:

```
Dec 27 11:20:48 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|08192|utm:virus infected
blocked|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0211008192 cat=utm:virus
FTNTFGTsubtype=virus FTNTFGTeventtype=infected FTNTFGTlevel=warning FTNTFGTvd=vdom1
FTNTFGTeventtime=1545938448 msg=File is infected. act=blocked app=HTTP
externalId=695 src=10.1.100.11 dst=172.16.200.55 spt=44356 dpt=80
deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined
deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined FTNTFGTpolicyid=1
proto=6 deviceDirection=0 fname=eicar.com FTNTFGTquarskip=File-was-not-quarantined.
FTNTFGTvirus=EICAR_TEST_FILE FTNTFGTdtype=Virus
FTNTFGTref=http://www.fortinet.com/ve?vn=EICAR_TEST_FILE FTNTFGTvirusid=2172
request=http://172.16.200.55/virus/eicar.com FTNTFGTprofile=g-default duser=bob
requestClientApplication=curl/7.47.0
FTNTFGTanalyticscksum=275a021bbfb6489e54d471899f7db9d1663fc695ec2fe2a2c4538aabf651fd
0f FTNTFGTanalyticssubmit=false FTNTFGTcrrscore=50 FTNTFGTcrlevel=critical
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
direction	deviceDirection (inbound/outbound mapping to 0/1)
filename	fname
ref	FTNTFGTref (There is \ added to escape = )
url	request
agent	requestClientApplication

## Webfilter log support for CEF

The following is an example of a webfilter log on the FortiGate disk:

```
date=2018-12-27 time=11:23:50 logid="0316013056" type="utm" subtype="webfilter"
eventtype="ftgd_blk" level="warning" vd="vdom1" eventtime=1545938629 policyid=1
sessionid=764 user="bob" srcip=10.1.100.11 srcport=59194 srcintf="port12"
srcintfrole="undefined" dstip=185.230.61.185 dstport=80 dstintf="port11"
dstintfrole="undefined" proto=6 service="HTTP" hostname="ambrishsriv.wixsite.com"
profile="g-default" action="blocked" reqtype="direct" url="/bizsquads" sentbyte=96
rcvdbyte=0 direction="outgoing" msg="URL belongs to a denied category in policy"
method="domain" cat=26 catdesc="Malicious Websites" crscore=60 crlevel="high"
```

The following is an example of a webfilter log sent in CEF format to a syslog server:

```
Dec 27 11:23:49 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|13056|utm:webfilter ftgd_blk
blocked|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0316013056
cat=utm:webfilter FTNTFGTsubtype=webfilter FTNTFGTeventtype=ftgd_blk
```

```
FTNTFGTlevel=warning FTNTFGTvd=vdom1 FTNTFGTeventtime=1545938629 FTNTFGTpolicyid=1
externalId=764 duser=bob src=10.1.100.11 spt=59194 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined dst=185.230.61.185 dpt=80
deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined proto=6 app=HTTP
dhost=ambrishsriv.wixsite.com FTNTFGTprofile=g-default act=blocked
FTNTFGTreqtype=direct request=/bizsquads out=96 in=0 deviceDirection=1 msg=URL
belongs to a denied category in policy FTNTFGTmethod=domain FTNTFGTcat=26
requestContext=Malicious Websites FTNTFGTcrscore=60 FTNTFGTcrlevel=high
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
hostname	dhost
catdesc	requestContext

## IPS log support for CEF

The following is an example of an IPS log on the FortiGate disk:

```
date=2018-12-27 time=11:28:07 logid="0419016384" type="utm" subtype="ips"
eventtype="signature" level="alert" vd="vdom1" eventtime=1545938887 severity="info"
srcip=172.16.200.55 srccountry="Reserved" dstip=10.1.100.11 srcintf="port11"
srcintfrole="undefined" dstintf="port12" dstintfrole="undefined" sessionid=901
action="reset" proto=6 service="HTTP" policyid=1 attack="Eicar.Virus.Test.File"
srcport=80 dstport=44362 hostname="172.16.200.55" url="/virus/eicar.com"
direction="incoming" attackid=29844 profile="test-ips"
ref="http://www.fortinet.com/ids/VID29844" user="bob" incidentserialno=877326946
msg="file_transfer: Eicar.Virus.Test.File,"
```

The following is an example of an IPS sent in CEF format to a syslog server:

```
Dec 27 11:28:07 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|16384|utm:ips signature
reset|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0419016384 cat=utm:ips
FTNTFGTsubtype=ips FTNTFGTeventtype=signature FTNTFGTlevel=alert FTNTFGTvd=vdom1
FTNTFGTeventtime=1545938887 FTNTFGTseverity=info src=172.16.200.55
FTNTFGTsrccountry=Reserved dst=10.1.100.11 deviceInboundInterface=port11
FTNTFGTsrcintfrole=undefined deviceOutboundInterface=port12
FTNTFGTdstintfrole=undefined externalId=901 act=reset proto=6 app=HTTP
FTNTFGTpolicyid=1 FTNTFGTattack=Eicar.Virus.Test.File spt=80 dpt=44362
dhost=172.16.200.55 request=/virus/eicar.com deviceDirection=0 FTNTFGTattackid=29844
FTNTFGTprofile=test-ips FTNTFGTref=http://www.fortinet.com/ids/VID29844 duser=bob
FTNTFGTincidentserialno=877326946 msg=file_transfer: Eicar.Virus.Test.File,
```

## Email Spamfilter log support for CEF

The following is an example of an email spamfilter log on the FortiGate disk:

```
date=2018-12-27 time=11:36:58 logid="0508020503" type="utm" subtype="emailfilter"
eventtype="smtp" level="information" vd="vdom1" eventtime=1545939418 policyid=1
sessionid=1135 user="bob" srcip=10.1.100.11 srcport=35969 srcintf="port12"
srcintfrole="undefined" dstip=172.18.62.158 dstport=25 dstintf="port11"
dstintfrole="undefined" proto=6 service="SMTP" profile="test-spam" action="log-only"
from="testp1@qa.fortinet.com" to="test1@server88.qa.fortinet.com"
sender="testp1@qa.fortinet.com" recipient="test1@server88.qa.fortinet.com"
direction="outgoing" msg="general email log" subject="hello_world2" size="216"
attachment="no"
```

The following is an example of an email spamfilter log sent in CEF format to a syslog server:

```
Dec 27 11:36:58 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|20503|utm:emailfilter smtp
log-only|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0508020503
cat=utm:emailfilter FTNTFGTsubtype=emailfilter FTNTFGTeventtype=smtp
FTNTFGTlevel=information FTNTFGTvd=vdom1 FTNTFGTeventtime=1545939418
FTNTFGTpolicyid=1 externalId=1135 duser=bob src=10.1.100.11 spt=35969
deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined dst=172.18.62.158 dpt=25
deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined proto=6 app=SMTP
FTNTFGTprofile=test-spam act=log-only suser=testpcl@qa.fortinet.com
duser=testl1@server88.qa.fortinet.com FTNTFGTsender=testpcl@qa.fortinet.com
FTNTFGTrecipient=testl1@server88.qa.fortinet.com deviceDirection=1 msg=general email
log FTNTFGTsubject=hello_world2 FTNTFGTsize=216 FTNTFGTattachment=no
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
from	suser
to	duser

## Anomaly log support for CEF

The following is an example of an anomaly log on the FortiGate disk:

```
date=2018-12-27 time=11:40:04 logid="0720018433" type="utm" subtype="anomaly"
eventtype="anomaly" level="alert" vd="vdom1" eventtime=1545939604
severity="critical" srcip=10.1.100.11 srccountry="Reserved" dstip=172.16.200.55
srcintf="port12" srcintfrole="undefined" sessionid=0 action="clear_session" proto=1
service="PING" count=1 attack="icmp_flood" icmpid="0x3053" icmptype="0x08"
icmpcode="0x00" attackid=16777316 policyid=1 policytype="DoS-policy"
ref="http://www.fortinet.com/ids/VID16777316" msg="anomaly: icmp_flood, 51 >
threshold 50" crscore=50 crlevel="critical"
```

The following is an example of an anomaly log sent in CEF format to a syslog server:

```
Dec 27 11:40:04 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|18433|utm:anomaly anomaly
clear_session|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0720018433
cat=utm:anomaly FTNTFGTsubtype=anomaly FTNTFGTeventtype=anomaly FTNTFGTlevel=alert
FTNTFGTvd=vdom1 FTNTFGTeventtime=1545939604 FTNTFGTseverity=critical src=10.1.100.11
FTNTFGTsrccountry=Reserved dst=172.16.200.55 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined externalId=0 act=clear_session proto=1 app=PING cnt=1
FTNTFGTattack=icmp_flood FTNTFGTicmpid=0x3053 FTNTFGTicmptype=0x08
FTNTFGTicmpcode=0x00 FTNTFGTattackid=16777316 FTNTFGTpolicyid=1
FTNTFGTpolicytype=DoS-policy FTNTFGTref=http://www.fortinet.com/ids/VID16777316
msg=anomaly: icmp_flood, 51 > threshold 50 FTNTFGTcrscore=50 FTNTFGTcrlevel=critical
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
count	cnt

## VoIP log support for CEF

The following is an example of an VoIP log on the FortiGate disk:

```
date=2018-12-27 time=16:47:09 logid="0814044032" type="utm" subtype="voip"
eventtype="voip" level="information" vd="vdom1" eventtime=1545958028 session_
id=18975 epoch=0 event_id=6857 srcip=10.1.100.11 src_port=5060 dstip=172.16.200.55
dst_port=5060 proto=17 src_int="port12" dst_int="port11" policy_id=1
profile="default" voip_proto="sip" kind="call" action="permit" status="start"
duration=0 dir="session_origin" call_id="3444-13134@127.0.0.1"
from="sip:sipp@127.0.0.1:5060" to="sip:service@172.16.200.55:5060"
```

The following is an example of an VoIP sent in CEF format to a syslog server:

```
Dec 27 16:47:08 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|44032|utm:voip voip permit
start|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0814044032 cat=utm:voip
FTNTFGTsubtype=voip FTNTFGTeventtype=voip FTNTFGTlevel=information FTNTFGTvd=vdom1
FTNTFGTeventtime=1545958028 externalId=18975 FTNTFGTepoch=0 FTNTFGTevent_id=6857
src=10.1.100.11 spt=5060 dst=172.16.200.55 dpt=5060 proto=17
deviceInboundInterface=port12 deviceOutboundInterface=port11 FTNTFGTpolicy_id=1
FTNTFGTprofile=default FTNTFGTvoip_proto=sip FTNTFGTkind=call act=permit
outcome=start FTNTFGTduration=0 FTNTFGTdir=session_origin FTNTFGTcall_id=3444-
13134@127.0.0.1 suser=sip:sipp@127.0.0.1:5060 duser=sip:service@172.16.200.55:5060
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
status	outcome
from	suser
to	duser

## DLP log support for CEF

The following is an example of a DLP log on the FortiGate disk:

```
date=2018-12-27 time=14:29:36 logid="0954024576" type="utm" subtype="dlp" eventtype="dlp"
level="warning" vd="vdom1" eventtime=1545949776 filteridx=1 dlpextra="test-dlp3"
filtertype="file-type" filtercat="file" severity="medium" policyid=1 sessionid=12680
epoch=418303178 eventid=0 user="bob" srcip=10.1.100.11 srcport=33638
srcintf="port12" srcintfrole="undefined" dstip=172.18.62.158 dstport=80
dstintf="port11" dstintfrole="undefined" proto=6 service="HTTP" filetype="gif"
direction="incoming" action="block" hostname="172.18.62.158" url="/dlp/flower.gif"
agent="curl/7.47.0" filename="flower.gif" filesize=1209 profile="test-dlp"
```

The following is an example of a DLP log sent in CEF format to a syslog server:

```
Dec 27 14:29:36 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|24576|utm:dlp dlp
block|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0954024576 cat=utm:dlp
FTNTFGTsubtype=dlp FTNTFGTeventtype=dlp FTNTFGTlevel=warning FTNTFGTvd=vdom1
FTNTFGTeventtime=1545949776 FTNTFGTfilteridx=1 FTNTFGTdlpextra=test-dlp3
FTNTFGTfiltertype=file-type FTNTFGTfiltercat=file FTNTFGTseverity=medium
FTNTFGTpolicyid=1 externalId=12680 FTNTFGTepoch=418303178 FTNTFGTeventid=0 duser=bob
src=10.1.100.11 spt=33638 deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined
dst=172.18.62.158 dpt=80 deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined
proto=6 app=HTTP FTNTFGTfiletype=gif deviceDirection=0 act=block dhost=172.18.62.158
request=/dlp/flower.gif requestClientApplication=curl/7.47.0 fname=flower.gif
fsize=1209 FTNTFGTprofile=test-dlp
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
filename	fname

## Application log support for CEF

The following is an example of an application log on the FortiGate disk:

```
date=2018-12-27 time=14:28:08 logid="1059028704" type="utm" subtype="app-ctrl"
eventtype="app-ctrl-all" level="information" vd="vdom1" eventtime=1545949688
appid=34050 srcip=10.1.100.11 dstip=104.80.89.24 srcport=56826 dstport=80
srcintf="port12" srcintfrole="undefined" dstintf="port11" dstintfrole="undefined"
proto=6 service="HTTP" direction="outgoing" policyid=1 sessionid=12567 applist="g-
default" appcat="Web.Client" app="HTTP.BROWSER_Firefox" action="pass"
hostname="detectportal.firefox.com" incidentserialno=1702350499 url="/success.txt"
msg="Web.Client: HTTP.BROWSER_Firefox," apprisk="elevated"
```

The following is an example of an application sent in CEF format to a syslog server:

```
Dec 27 14:28:08 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|28704|utm:app-ctrl app-ctrl-
all pass|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1059028704 cat=utm:app-
ctrl FTNTFGTsubtype=app-ctrl FTNTFGTeventtype=app-ctrl-all FTNTFGTlevel=information
FTNTFGTvd=vdom1 FTNTFGTeventtime=1545949688 FTNTFGTappid=34050 src=10.1.100.11
dst=104.80.89.24 spt=56826 dpt=80 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined deviceOutboundInterface=port11
FTNTFGTdstintfrole=undefined proto=6 app=HTTP deviceDirection=1 FTNTFGTpolicyid=1
externalId=12567 FTNTFGTapplist=g-default FTNTFGTappcat=Web.Client
FTNTFGTapp=HTTP.BROWSER_Firefox act=pass dhost=detectportal.firefox.com
FTNTFGTincidentserialno=1702350499 request=/success.txt msg=Web.Client:
HTTP.BROWSER_Firefox, FTNTFGTapprisk=elevated
```

## WAF log support for CEF

The following is an example of an WAF log on the FortiGate disk:

```
date=2018-12-27 time=14:55:20 logid="1203030258" type="utm" subtype="waf" eventtype="waf-
http-constraint" level="warning" vd="vdom1" eventtime=1545951320 policyid=1
sessionid=13614 user="bob" profile="waf_test" srcip=10.1.100.11 srcport=57304
dstip=172.16.200.55 dstport=80 srcintf="port12" srcintfrole="lan" dstintf="port11"
dstintfrole="wan" proto=6 service="HTTP"
url="http://172.16.200.55/index.html?a=0123456789&b=0123456789&c=0123456789"
severity="medium" action="passthrough" direction="request" agent="curl/7.47.0"
constraint="url-param-num" rawdata="Method=GET|User-Agent=curl/7.47.0"
```

The following is an example of an WAF sent in CEF format to a syslog server:

```
Dec 27 14:55:20 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|30258|utm:waf waf-http-
constraint passthrough|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1203030258
cat=utm:waf FTNTFGTsubtype=waf FTNTFGTeventtype=waf-http-constraint
FTNTFGTlevel=warning FTNTFGTvd=vdom1 FTNTFGTeventtime=1545951320 FTNTFGTpolicyid=1
externalId=13614 duser=bob FTNTFGTprofile=waf_test src=10.1.100.11 spt=57304
dst=172.16.200.55 dpt=80 deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan
deviceOutboundInterface=port11 FTNTFGTdstintfrole=wan proto=6 app=HTTP
request=http://172.16.200.55/index.html?a\=0123456789&b\=0123456789&c\=0123456789
FTNTFGTseverity=medium act=passthrough deviceDirection=0
requestClientApplication=curl/7.47.0 FTNTFGTconstraint=url-param-num
FTNTFGTrawdata=Method\=GET|User-Agent\=curl/7.47.0
```

## DNS log support for CEF

The following is an example of a DNS log on the FortiGate disk:

```
date=2018-12-27 time=14:45:26 logid="1501054802" type="dns" subtype="dns-response"
level="notice" vd="vdom1" eventtime=1545950726 policyid=1 sessionid=13355 user="bob"
srcip=10.1.100.11 srcport=54621 srcintf="port12" srcintfrole="lan"
dstip=172.16.200.55 dstport=53 dstintf="port11" dstintfrole="wan" proto=17
profile="default" srcmac="a2:e9:00:ec:40:01" xid=5137
qname="detectportal.firefox.com" qtype="A" qtypeval=1 qclass="IN"
ipaddr="104.80.89.26, 104.80.89.24" msg="Domain is monitored" action="pass" cat=52
catdesc="Information Technology"
```

The following is an example of a DNS sent in CEF format to a syslog server:

```
Dec 27 14:45:26 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|54802|dns:dns-response
pass|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1501054802 cat=dns:dns-
response FTNTFGTsubtype=dns-response FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545950726 FTNTFGTpolicyid=1 externalId=13355 duser=bob
src=10.1.100.11 spt=54621 deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan
dst=172.16.200.55 dpt=53 deviceOutboundInterface=port11 FTNTFGTdstintfrole=wan
proto=17 FTNTFGTprofile=default FTNTFGTsrcmac=a2:e9:00:ec:40:01 FTNTFGTxid=5137
FTNTFGTqname=detectportal.firefox.com FTNTFGTqtype=A FTNTFGTqtypeval=1
FTNTFGTqclass=IN FTNTFGTipaddr=104.80.89.26, 104.80.89.24 msg=Domain is monitored
act=pass FTNTFGTcat=52 FTNTFGTcatdesc=Information Technology
```

## SSH log support for CEF

The following is an example of an SSH log on the FortiGate disk:

```
date=2018-12-27 time=14:36:15 logid="1600061002" type="utm" subtype="ssh" eventtype="ssh-
command" level="notice" vd="vdom1" eventtime=1545950175 policyid=1 sessionid=12921
user="bob" profile="test-ssh" srcip=10.1.100.11 srcport=56698 dstip=172.16.200.55
dstport=22 srcintf="port12" srcintfrole="lan" dstintf="port11" dstintfrole="wan"
proto=6 action="passthrough" direction="outgoing" login="root" command="ls"
severity="low"
```

The following is an example of an SSH sent in CEF format to a syslog server:

```
Dec 27 14:36:15 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|61002|utm:ssh ssh-command
passthrough|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1600061002 cat=utm:ssh
FTNTFGTsubtype=ssh FTNTFGTeventtype=ssh-command FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545950175 FTNTFGTpolicyid=1 externalId=12921 duser=bob
FTNTFGTprofile=test-ssh src=10.1.100.11 spt=56698 dst=172.16.200.55 dpt=22
deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan deviceOutboundInterface=port11
FTNTFGTdstintfrole=wan proto=6 act=passthrough FTNTFGTlogin=root FTNTFGTcommand=ls
FTNTFGTseverity=low
```

# UTM Extended Logging

FortiOS 6.0.0 and later supports extended logging for UTM log types to reliable Syslog servers over TCP. Extended logging adds HTTP header information to the `rawdata` field in UTM log types. You must enable extended logging before you can use the feature.

When extended logging is enabled, the following HTTP header information can be added to the `rawdata` field in UTM logs:

- Method
- X-Forwarded-For
- Request-Content-Type | Response-Content-Type
- Referer
- User-Agent

The full `rawdata` field of 20KB is only sent to reliable Syslog servers. Other logging devices, such as disk, FortiAnalyzer, and UDP Syslog servers, receive the information, but only keep a maximum of 2KB total log length, including the `rawdata` field, and discard the rest of the extended log information.

## Enabling extended logging

You can enable extended logging for the following UTM profiles:

- antivirus
- application
- dlp
- ips
- waf
- webfilter

When you enable the `extended-log` option for UTM profiles, all HTTP header information for HTTP-deny traffic is logged.

When you enable the `web-extended-all-action-log-enable` option for webfilter profile, all HTTP header information for HTTP-allow traffic is logged.

## Extended logging option in UTM profiles

The `extended-log` option has been added to all UTM profiles, for example:

```
# webfilter profile
config webfilter profile
  edit "test-webfilter"
    set extended-log enable
    set web-extended-all-action-log enable
  next
end
# av profile
```



```
config antivirus profile
  edit "av-proxy-test"
    set extended-log enable
  next
end
# waf profile
config waf profile
  edit "test-waf"
    set extended-log enable
  next
end
```

## Syslog server mode

The Syslog server mode changed to `udp`, `reliable`, and `legacy-reliable`. You must set the mode to `reliable` to support extended logging, for example:

```
config log syslogd setting
  set status enable
  set server "<ip address>"
  set mode reliable
  set facility local6
end
```

## Example of an extended log

Following is an example extended log for a `utm` log type with a `webfilter` subtype for a reliable Syslog server. The `rawdata` field contains the extended log data.

```
Dec 18 15:40:15 10.6.30.254 date=2017-12-18 time=15:40:14 devname="600D-9"
devid="FGT6HD3915800120" logid="0316013056" type="utm" subtype="webfilter"
eventtype="ftgd_blk" level="warning" vd="vdom1" eventtime=1513640414 policyid=2
sessionid=440522 srcip=10.1.100.128 srcport=60995 srcintf="port2" srcintfrole="lan"
dstip=209.121.139.177 dstport=80 dstintf="port1" dstintfrole="wan" proto=6
service="HTTP" hostname="detectportal.firefox.com" profile="test-webfilter"
action="blocked" reqtype="direct" url="/success.txt" sentbyte=285 rcvbyte=0
direction="outgoing" msg="URL belongs to a denied category in policy"
method="domain" cat=52 catdesc="Information Technology" crscore=30 crlevel="high"
rawdata="Method=GET|User-Agent=Mozilla/5.0 (Windows NT 6.1; rv:57.0) Gecko/20100101
Firefox/57.0"
```

# Log Messages

The following sections list the FortiOS 6.0.12 log messages by log ID number.

# Anomaly

## 18432 - LOGID\_ATTCK\_ANOMALY\_TCP\_UDP

**Message ID:** 18432

**Message Description:** LOGID\_ATTCK\_ANOMALY\_TCP\_UDP

**Message Meaning:** Attack detected by UCP/TCP anomaly

**Type:** Anomaly

**Category:** ANOMALY

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36
sessionid	Session ID	uint32	10
severity	Severity	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3

## 18433 - LOGID\_ATTCK\_ANOMALY\_ICMP

**Message ID:** 18433

**Message Description:** LOGID\_ATTCK\_ANOMALY\_ICMP

**Message Meaning:** Attack detected by ICMP anomaly

**Type:** Anomaly

**Category:** ANOMALY

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
icmpcode	ICMP code	string	6
icmpid	ICMP ID	string	8
icmptype	ICMP Type	string	6
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36
sessionid	Session ID	uint32	10
severity	Severity	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3

## 18434 - LOGID\_ATTCK\_ANOMALY\_OTHERS

**Message ID:** 18434

**Message Description:** LOGID\_ATTCK\_ANOMALY\_OTHERS

**Message Meaning:** Attack detected by other anomaly

**Type:** Anomaly

**Category:** ANOMALY

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36
sessionid	Session ID	uint32	10
severity	Severity	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3

# App

## 28672 - LOGID\_APP\_CTRL\_IM\_BASIC

**Message ID:** 28672

**Message Description:** LOGID\_APP\_CTRL\_IM\_BASIC

**Message Meaning:** Application control IM-basic

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profiletype		string	36
proto		uint8	3
service		string	36



Log Field Name	Description	Data Type	Length
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28673 - LOGID\_APP\_CTRL\_IM\_BASIC\_WITH\_STATUS

**Message ID:** 28673

**Message Description:** LOGID\_APP\_CTRL\_IM\_BASIC\_WITH\_STATUS

**Message Meaning:** Application control IM

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profiletype		string	36
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28674 - LOGID\_APP\_CTRL\_IM\_BASIC\_WITH\_COUNT

**Message ID:** 28674

**Message Description:** LOGID\_APP\_CTRL\_IM\_BASIC\_WITH\_COUNT

**Message Meaning:** Application control IM (chat message count)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profiletype		string	36
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user		string	256
vd		string	32
vrf		uint8	3

## 28675 - LOGID\_APP\_CTRL\_IM\_FILE

**Message ID:** 28675

**Message Description:** LOGID\_APP\_CTRL\_IM\_FILE

**Message Meaning:** Application control IM (file)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profiletype		string	36

Log Field Name	Description	Data Type	Length
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28676 - LOGID\_APP\_CTRL\_IM\_CHAT

**Message ID:** 28676

**Message Description:** LOGID\_APP\_CTRL\_IM\_CHAT

**Message Meaning:** Application control IM (chat)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8

Log Field Name	Description	Data Type	Length
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profiletype		string	36
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28677 - LOGID\_APP\_CTRL\_IM\_CHAT\_BLOCK

**Message ID:** 28677

**Message Description:** LOGID\_APP\_CTRL\_IM\_CHAT\_BLOCK

**Message Meaning:** Application control IM (chat blocked)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profiletype		string	36
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8

Log Field Name	Description	Data Type	Length
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28678 - LOGID\_APP\_CTRL\_IM\_BLOCK

**Message ID:** 28678

**Message Description:** LOGID\_APP\_CTRL\_IM\_BLOCK

**Message Meaning:** Application control IM (blocked)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11



Log Field Name	Description	Data Type	Length
logid		string	10
policyid		uint32	10
profiletype		string	36
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28704 - LOGID\_APP\_CTRL\_IPS\_PASS

**Message ID:** 28704

**Message Description:** LOGID\_APP\_CTRL\_IPS\_PASS

**Message Meaning:** Application control (IPS) (pass)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64

Log Field Name	Description	Data Type	Length
appid		uint32	10
applist		string	64
apprisk		string	16
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
crlevel		string	10
crscore		uint32	10
date		string	10
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profiletype		string	36
proto		uint8	3
scertcname		string	64
scertissuer		string	64

Log Field Name	Description	Data Type	Length
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 28705 - LOGID\_APP\_CTRL\_IPS\_BLOCK

**Message ID:** 28705

**Message Description:** LOGID\_APP\_CTRL\_IPS\_BLOCK

**Message Meaning:** Application control (IPS) (block)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10
applist		string	64

Log Field Name	Description	Data Type	Length
apprisk		string	16
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
crlevel		string	10
crscore		uint32	10
date		string	10
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profiletype		string	36
proto		uint8	3
scertcname		string	64
scertissuer		string	64
service		string	36
sessionid		uint32	10

Log Field Name	Description	Data Type	Length
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 28706 - LOGID\_APP\_CTRL\_IPS\_RESET

**Message ID:** 28706

**Message Description:** LOGID\_APP\_CTRL\_IPS\_RESET

**Message Meaning:** Application control (IPS) (reset)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
ccertissuer		string	64

Log Field Name	Description	Data Type	Length
cloudaction		string	32
clouduser		string	256
crlevel		string	10
crscore		uint32	10
date		string	10
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profiletype		string	36
proto		uint8	3
scertcname		string	64
scertissuer		string	64
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 28720 - LOGID\_APP\_CTRL\_SSH\_PASS

**Message ID:** 28720

**Message Description:** LOGID\_APP\_CTRL\_SSH\_PASS

**Message Meaning:** Application control IM (SSH) (pass)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profiletype		string	36
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

## 28721 - LOGID\_APP\_CTRL\_SSH\_BLOCK

**Message ID:** 28721

**Message Description:** LOGID\_APP\_CTRL\_SSH\_BLOCK

**Message Meaning:** Application control IM (SSH) (block)

**Type:** App

**Category:** APP-CTRL-ALL

**Severity:** Warning



Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profiletype		string	36
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66

---

Log Field Name	Description	Data Type	Length
user		string	256
vd		string	32
vrf		uint8	3

# AV

## 8192 - MESGID\_INFECT\_WARNING

**Message ID:** 8192

**Message Description:** MESGID\_INFECT\_WARNING

**Message Meaning:** Infected file detected by the FortiGate unit and blocked

**Type:** AV

**Category:** INFECTED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticsscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128

Log Field Name	Description	Data Type	Length
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8193 - MESGID\_INFECT\_NOTIF

**Message ID:** 8193

**Message Description:** MESGID\_INFECT\_NOTIF

**Message Meaning:** Infected file detected by the FortiGate unit and it passed

**Type:** AV

**Category:** INFECTED

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8194 - MESGID\_INFECT\_MIME\_WARNING

**Message ID:** 8194

**Message Description:** MESGID\_INFECT\_MIME\_WARNING

**Message Meaning:** MIME header detected to have a virus and blocked

**Type:** AV

**Category:** INFECTED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8195 - MESGID\_INFECT\_MIME\_NOTIF

**Message ID:** 8195

**Message Description:** MESGID\_INFECT\_MIME\_NOTIF

**Message Meaning:** MIME header infected and passed

**Type:** AV

**Category:** INFECTED

**Severity:** Notice



Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8200 - MESGID\_MIME\_FILETYPE\_EXE\_WARNING

**Message ID:** 8200

**Message Description:** MESGID\_MIME\_FILETYPE\_EXE\_WARNING

**Message Meaning:** File is an executable (warning)

**Type:** AV

**Category:** FILETYPE-EXECUTABLE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64

Log Field Name	Description	Data Type	Length
analyticscksum		string	64
analyticssubmit		string	10
checksum		string	16
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
recipient		string	512
ref		string	512
sender		string	128
service		string	5

Log Field Name	Description	Data Type	Length
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8201 - MESSAGESID\_MIME\_FILETYPE\_EXE\_NOTIF

**Message ID:** 8201

**Message Description:** MESSAGESID\_MIME\_FILETYPE\_EXE\_NOTIF

**Message Meaning:** File is an executable (notice)

**Type:** AV

**Category:** FILETYPE-EXECUTABLE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64

Log Field Name	Description	Data Type	Length
analyticssubmit		string	10
checksum		string	16
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10

Log Field Name	Description	Data Type	Length
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

## 8448 - MESGID\_BLOCK\_WARNING

**Message ID:** 8448

**Message Description:** MESGID\_BLOCK\_WARNING

**Message Meaning:** FortiGate unit blocked a file because it contains a virus

**Type:** AV

**Category:** FILENAME

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8449 - MMSGID\_BLOCK\_NOTIF

**Message ID:** 8449

**Message Description:** MMSGID\_BLOCK\_NOTIF

**Message Meaning:** FortiGate unit blocked a file because it contains a virus

**Type:** AV

**Category:** FILENAME

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39



Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8450 - MESGID\_BLOCK\_MIME\_WARNING

**Message ID:** 8450

**Message Description:** MESGID\_BLOCK\_MIME\_WARNING

**Message Meaning:** FortiGate unit blocked a file because it contains a virus (MIME)

**Type:** AV

**Category:** MIMEFRAGMENTED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16

Log Field Name	Description	Data Type	Length
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8451 - MESGID\_BLOCK\_MIME\_NOTIF

**Message ID:** 8451

**Message Description:** MESGID\_BLOCK\_MIME\_NOTIF

**Message Meaning:** FortiGate unit blocked a file because it contains a virus (MIME)

**Type:** AV

**Category:** MIMEFRAGMENTED

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8452 - MESGID\_BLOCK\_COMMAND

**Message ID:** 8452

**Message Description:** MESGID\_BLOCK\_COMMAND

**Message Meaning:** FortiGate unit blocked a virus command

**Type:** AV

**Category:** COMMAND-BLOCKED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64

Log Field Name	Description	Data Type	Length
command		string	16
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
service		string	5
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 8453 - MESGID\_INTERCEPT

**Message ID:** 8453

**Message Description:** MESGID\_INTERCEPT

**Message Meaning:** FortiGate unit intercepted a file containing a virus

**Type:** AV

**Category:** FILENAME

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16

Log Field Name	Description	Data Type	Length
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8454 - MESGID\_INTERCEPT\_MIME

**Message ID:** 8454

**Message Description:** MESGID\_INTERCEPT\_MIME



**Message Meaning:** FortiGate unit intercepted a file (MIME)

**Type:** AV

**Category:** FILENAME

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8455 - MESSAGES\_EXEMPT

**Message ID:** 8455

**Message Description:** MESSAGES\_EXEMPT

**Message Meaning:** File exempted

**Type:** AV

**Category:** FILENAME

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8456 - MESGID\_EXEMPT\_MIME

**Message ID:** 8456

**Message Description:** MESGID\_EXEMPT\_MIME

**Message Meaning:** File exempted

**Type:** AV

**Category:** FILENAME

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8457 - MESGID\_MMS\_CHECKSUM

**Message ID:** 8457

**Message Description:** MESGID\_MMS\_CHECKSUM

**Message Meaning:** MMS content checksum blocked an infected file

**Type:** AV

**Category:** FILENAME

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256

Log Field Name	Description	Data Type	Length
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8458 - MESGID\_MMS\_CHECKSUM\_NOTIF

**Message ID:** 8458

**Message Description:** MESGID\_MMS\_CHECKSUM\_NOTIF

**Message Meaning:** MMS content checksum was matched

**Type:** AV

**Category:** FILENAME

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10



Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8704 - MESGID\_OVERSIZE\_WARNING

**Message ID:** 8704

**Message Description:** MESGID\_OVERSIZE\_WARNING

**Message Meaning:** Defined file size limit was exceeded

**Type:** AV

**Category:** OVERSIZE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8705 - MESGID\_OVERSIZE\_NOTIF

**Message ID:** 8705

**Message Description:** MESGID\_OVERSIZE\_NOTIF

**Message Meaning:** File size limit was exceeded

**Type:** AV

**Category:** OVERSIZE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8706 - MESSGID\_OVERSIZE\_MIME\_WARNING

**Message ID:** 8706

**Message Description:** MESSGID\_OVERSIZE\_MIME\_WARNING

**Message Meaning:** File (MIME) size exceed the defined size limit

**Type:** AV

**Category:** OVERSIZE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8707 - MESGID\_OVERSIZE\_MIME\_NOTIF

**Message ID:** 8707

**Message Description:** MESGID\_OVERSIZE\_MIME\_NOTIF

**Message Meaning:** File (MIME) size exceed the defined size limit

**Type:** AV

**Category:** OVERSIZE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256

Log Field Name	Description	Data Type	Length
vd	VDOM name	string	32
vrf		uint8	3

## 8720 - MESGID\_SWITCH\_PROTO\_WARNING

**Message ID:** 8720

**Message Description:** MESGID\_SWITCH\_PROTO\_WARNING

**Message Meaning:** Switching protocols request (warning)

**Type:** AV

**Category:** SWITCHPROTO

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10



Log Field Name	Description	Data Type	Length
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8721 - MESGID\_SWITCH\_PROTO\_NOTIF

**Message ID:** 8721

**Message Description:** MESGID\_SWITCH\_PROTO\_NOTIF

**Message Meaning:** Switching protocols request (notice)

**Type:** AV

**Category:** SWITCHPROTO

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
switchproto	Protocol change information	string	128
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

## 8960 - MESGID\_SCAN\_UNCOMPSizeLIMIT\_WARNING

**Message ID:** 8960

**Message Description:** MESGID\_SCAN\_UNCOMPSizeLIMIT\_WARNING

**Message Meaning:** File reached the uncompressed nested limit

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8961 - MESSID\_SCAN\_UNCOMPSizeLIMIT\_NOTIF

**Message ID:** 8961

**Message Description:** MESSID\_SCAN\_UNCOMPSizeLIMIT\_NOTIF

**Message Meaning:** File reached the uncompressed size limit

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8962 - MESGID\_SCAN\_ARCHIVE\_ENCRYPTED\_WARNING

**Message ID:** 8962

**Message Description:** MESGID\_SCAN\_ARCHIVE\_ENCRYPTED\_WARNING

**Message Meaning:** Archived file is corrupted

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256

Log Field Name	Description	Data Type	Length
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3



## 8963 - MESGID\_SCAN\_ARCHIVE\_ENCRYPTED\_NOTIF

**Message ID:** 8963

**Message Description:** MESGID\_SCAN\_ARCHIVE\_ENCRYPTED\_NOTIF

**Message Meaning:** Archived file is encrypted

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8964 - MESSAGES\_SCAN\_ARCHIVE\_CORRUPTED\_WARNING

**Message ID:** 8964

**Message Description:** MESSAGES\_SCAN\_ARCHIVE\_CORRUPTED\_WARNING

**Message Meaning:** Corrupted archive (warning)

**Type:** AV

**Category:** SCANERROR**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512

Log Field Name	Description	Data Type	Length
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8965 - MESGID\_SCAN\_ARCHIVE\_CORRUPTED\_NOTIF

**Message ID:** 8965

**Message Description:** MESGID\_SCAN\_ARCHIVE\_CORRUPTED\_NOTIF

**Message Meaning:** Corrupted archive (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8966 - MESGID\_SCAN\_ARCHIVE\_MULTIPART\_WARNING

**Message ID:** 8966

**Message Description:** MESGID\_SCAN\_ARCHIVE\_MULTIPART\_WARNING

**Message Meaning:** File is a multipart archive or contains multiple files within the archive

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64

Log Field Name	Description	Data Type	Length
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8967 - MESGID\_SCAN\_ARCHIVE\_MULTIPART\_NOTIF

**Message ID:** 8967

**Message Description:** MESGID\_SCAN\_ARCHIVE\_MULTIPART\_NOTIF

**Message Meaning:** File is a multipart archive or contains multiple files within the archive

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16



Log Field Name	Description	Data Type	Length
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8968 - MESGID\_SCAN\_ARCHIVE\_NESTED\_WARNING

**Message ID:** 8968

**Message Description:** MESGID\_SCAN\_ARCHIVE\_NESTED\_WARNING

**Message Meaning:** File is a nested archived file

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticsscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8969 - MESGID\_SCAN\_ARCHIVE\_NESTED\_NOTIF

**Message ID:** 8969

**Message Description:** MESGID\_SCAN\_ARCHIVE\_NESTED\_NOTIF

**Message Meaning:** File is an archived type unhandled

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticsscksum	The checksum of the file submitted for analytics	string	64
analyticsssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8970 - MESSAGESID\_SCAN\_ARCHIVE\_OVERSIZE\_WARNING

**Message ID:** 8970

**Message Description:** MESSAGESID\_SCAN\_ARCHIVE\_OVERSIZE\_WARNING

**Message Meaning:** Archived file is oversized

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8971 - MESGID\_SCAN\_ARCHIVE\_OVERSIZE\_NOTIF

**Message ID:** 8971

**Message Description:** MESGID\_SCAN\_ARCHIVE\_OVERSIZE\_NOTIF

**Message Meaning:** Archived file is oversized

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20



Log Field Name	Description	Data Type	Length
eventype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8972 - MESSAGES\_SCAN\_ARCHIVE\_UNHANDLED\_WARNING

**Message ID:** 8972

**Message Description:** MESSAGES\_SCAN\_ARCHIVE\_UNHANDLED\_WARNING

**Message Meaning:** Unhandled archive (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256

Log Field Name	Description	Data Type	Length
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8973 - MESGID\_SCAN\_ARCHIVE\_UNHANDLED\_NOTIF

**Message ID:** 8973

**Message Description:** MESGID\_SCAN\_ARCHIVE\_UNHANDLED\_NOTIF

**Message Meaning:** Unhandled archive (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8974 - MESSAGES\_SCAN\_AV\_ENGINE\_LOAD\_FAILED\_ERROR

**Message ID:** 8974

**Message Description:** MESSAGES\_SCAN\_AV\_ENGINE\_LOAD\_FAILED\_ERROR

**Message Meaning:** AV Engine load failed

**Type:** AV

**Category:** SCANERROR**Severity:** Error

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512

Log Field Name	Description	Data Type	Length
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8975 - MESGID\_SCAN\_ARCHIVE\_PARTIALLYCORRUPTED\_WARNING

**Message ID:** 8975

**Message Description:** MESGID\_SCAN\_ARCHIVE\_PARTIALLYCORRUPTED\_WARNING

**Message Meaning:** Partially corrupted archive (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10



Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8976 - MESGID\_SCAN\_ARCHIVE\_PARTIALLYCORRUPTED\_NOTIF

**Message ID:** 8976

**Message Description:** MESGID\_SCAN\_ARCHIVE\_PARTIALLYCORRUPTED\_NOTIF

**Message Meaning:** Partially corrupted archive (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10

Log Field Name	Description	Data Type	Length
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8977 - MESGID\_SCAN\_ARCHIVE\_FILESLIMIT\_WARNING

**Message ID:** 8977

**Message Description:** MESGID\_SCAN\_ARCHIVE\_FILESLIMIT\_WARNING

**Message Meaning:** Exceeded archive files limit (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticsscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8978 - MESGID\_SCAN\_ARCHIVE\_FILESLIMIT\_NOTIF

**Message ID:** 8978

**Message Description:** MESGID\_SCAN\_ARCHIVE\_FILESLIMIT\_NOTIF

**Message Meaning:** Exceeded archive files limit (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticsscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8979 - MESGID\_SCAN\_ARCHIVE\_TIMEOUT\_WARNING

**Message ID:** 8979

**Message Description:** MESGID\_SCAN\_ARCHIVE\_TIMEOUT\_WARNING

**Message Meaning:** Archive scan timeout (warning)

**Type:** AV

**Category:** SCANERROR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32

Log Field Name	Description	Data Type	Length
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32



Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 8980 - MESGID\_SCAN\_ARCHIVE\_TIMEOUT\_NOTIF

**Message ID:** 8980

**Message Description:** MESGID\_SCAN\_ARCHIVE\_TIMEOUT\_NOTIF

**Message Meaning:** Archive scan timeout (notice)

**Type:** AV

**Category:** SCANERROR

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9233 - MESGID\_ANALYTICS\_SUBMITTED

**Message ID:** 9233

**Message Description:** MESGID\_ANALYTICS\_SUBMITTED

**Message Meaning:** File submitted to Sandbox

**Type:** AV

**Category:** ANALYTICS

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9234 - MESGID\_ANALYTICS\_INFECT\_WARNING

**Message ID:** 9234

**Message Description:** MESGID\_ANALYTICS\_INFECT\_WARNING

**Message Meaning:** File reported infected by FortiSandbox (warning)

**Type:** AV

**Category:** INFECTED

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9235 - MESGID\_ANALYTICS\_INFECT\_NOTIF

**Message ID:** 9235

**Message Description:** MESGID\_ANALYTICS\_INFECT\_NOTIF

**Message Meaning:** File reported infected by FortiSandbox (notice)

**Type:** AV

**Category:** INFECTED

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64

Log Field Name	Description	Data Type	Length
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9236 - MESGID\_ANALYTICS\_INFECT\_MIME\_WARNING

**Message ID:** 9236

**Message Description:** MESGID\_ANALYTICS\_INFECT\_MIME\_WARNING

**Message Meaning:** File reported infected by FortiSandbox (warning)

**Type:** AV

**Category:** INFECTED



**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9237 - MMSGID\_ANALYTICS\_INFECT\_MIME\_NOTIF

**Message ID:** 9237

**Message Description:** MMSGID\_ANALYTICS\_INFECT\_MIME\_NOTIF

**Message Meaning:** File reported infected by FortiSandbox (notice)

**Type:** AV

**Category:** INFECTED

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512

Log Field Name	Description	Data Type	Length
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

## 9238 - MESGID\_ANALYTICS\_FSA\_RESULT

**Message ID:** 9238

**Message Description:** MESGID\_ANALYTICS\_FSA\_RESULT

**Message Meaning:** File verdict returned from FortiSandbox

**Type:** AV

**Category:** ANALYTICS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
analyticscksum	The checksum of the file submitted for analytics	string	64
date	Date	string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
fsaverdict		string	32
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
service	Proxy service which scanned this traffic	string	5
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
vd	VDOM name	string	32

## 9239 - MESGID\_CONTENT\_DISARM\_NOTIF

**Message ID:** 9239

**Message Description:** MESGID\_CONTENT\_DISARM\_NOTIF

**Message Meaning:** Active content detected by Content Disarm engine

**Type:** AV

**Category:** CONTENT-DISARM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
contentdisarmed		string	13
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcintf		string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32

## 9240 - MESGID\_CONTENT\_DISARM\_WARNING

**Message ID:** 9240

**Message Description:** MESGID\_CONTENT\_DISARM\_WARNING

**Message Meaning:** File was disarmed by Content Disarm engine

**Type:** AV

**Category:** CONTENT-DISARM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
contentdisarmed		string	13
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8

Log Field Name	Description	Data Type	Length
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16



Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32

## 9248 - MESGID\_BOTNET\_WARNING

**Message ID:** 9248

**Message Description:** MESGID\_BOTNET\_WARNING

**Message Meaning:** Botnet C&C Communication (warning)

**Type:** AV

**Category:** BOTNET

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
checksum		string	16
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
filename		string	256
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
to		string	512
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128

Log Field Name	Description	Data Type	Length
virusid		uint32	10
vrf		uint8	3

## 9249 - MESGID\_BOTNET\_NOTIF

**Message ID:** 9249

**Message Description:** MESGID\_BOTNET\_NOTIF

**Message Meaning:** Botnet C&C Communication (notice)

**Type:** AV

**Category:** BOTNET

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
checksum		string	16
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
from		string	128

Log Field Name	Description	Data Type	Length
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
to		string	512
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

# DLP

## 24576 - LOG\_ID\_DLP\_WARN

**Message ID:** 24576

**Message Description:** LOG\_ID\_DLP\_WARN

**Message Meaning:** Data leak detected by specified DLP sensor rule

**Type:** DLP

**Category:** DLP

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
date	Date	string	10
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128

Log Field Name	Description	Data Type	Length
filtertype	DLP filter type	string	23
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
infectedfilelevel		uint32	10
infectedfilename		string	256
infectedfilesize		uint64	10
infectedfiletype		string	23
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	128
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39

Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 24577 - LOG\_ID\_DLP\_NOTIF

**Message ID:** 24577

**Message Description:** LOG\_ID\_DLP\_NOTIF

**Message Meaning:** Data leak detected by specified DLP sensor rule

**Type:** DLP

**Category:** DLP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
date	Date	string	10
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
infectedfilelevel		uint32	10
infectedfilename		string	256
infectedfilesize		uint64	10
infectedfiletype		string	23
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39



Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	128
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 24578 - LOG\_ID\_DLP\_DOC\_SOURCE

**Message ID:** 24578

**Message Description:** LOG\_ID\_DLP\_DOC\_SOURCE

**Message Meaning:** DLP fingerprint document source notice

**Type:** DLP

**Category:** DLP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
dlpextra	DLP extra information	string	256
docsource	DLP fingerprint document source	string	515
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
sensitivity	Sensitivity for document fingerprint	string	36
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
vd	Virtual domain name	string	32

## 24579 - LOG\_ID\_DLP\_DOC\_SOURCE\_ERROR

**Message ID:** 24579

**Message Description:** LOG\_ID\_DLP\_DOC\_SOURCE\_ERROR

**Message Meaning:** DLP fingerprint document source error

**Type:** DLP

**Category:** DLP

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
dlpextra	DLP extra information	string	256
docsource	DLP fingerprint document source	string	515
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
level	Log Level	string	11
logid	Log ID	string	10
sensitivity	Sensitivity for document fingerprint	string	36
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
vd	Virtual domain name	string	32

# DNS

## 54000 - LOG\_ID\_DNS\_QUERY

**Message ID:** 54000

**Message Description:** LOG\_ID\_DNS\_QUERY

**Message Meaning:** DNS query message

**Type:** DNS

**Category:** DNS-QUERY

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54200 - LOG\_ID\_DNS\_RESOLV\_ERROR

**Message ID:** 54200

**Message Description:** LOG\_ID\_DNS\_RESOLV\_ERROR

**Message Meaning:** DNS resolution error message

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54400 - LOG\_ID\_DNS\_URL\_FILTER\_BLOCK

**Message ID:** 54400

**Message Description:** LOG\_ID\_DNS\_URL\_FILTER\_BLOCK

**Message Meaning:** Domain blocked because it is in the domain-filter list

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
date	Date	string	10
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54401 - LOG\_ID\_DNS\_URL\_FILTER\_ALLOW

**Message ID:** 54401

**Message Description:** LOG\_ID\_DNS\_URL\_FILTER\_ALLOW

**Message Meaning:** Domain allowed because it is in the domain-filter list

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
date	Date	string	10
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54600 - LOG\_ID\_DNS\_BOTNET\_IP

**Message ID:** 54600

**Message Description:** LOG\_ID\_DNS\_BOTNET\_IP

**Message Meaning:** Domain blocked by DNS botnet C&C (IP)

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning



Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54601 - LOG\_ID\_DNS\_BOTNET\_DOMAIN

**Message ID:** 54601

**Message Description:** LOG\_ID\_DNS\_BOTNET\_DOMAIN

**Message Meaning:** Domain blocked by DNS botnet C&C (Domain)

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54800 - LOG\_ID\_DNS\_FTGD\_WARNING

**Message ID:** 54800

**Message Description:** LOG\_ID\_DNS\_FTGD\_WARNING

**Message Meaning:** FortiGuard rating error warning

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54801 - LOG\_ID\_DNS\_FTGD\_ERROR

**Message ID:** 54801

**Message Description:** LOG\_ID\_DNS\_FTGD\_ERROR

**Message Meaning:** FortiGuard rating error occurred

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54802 - LOG\_ID\_DNS\_FTGD\_CAT\_ALLOW

**Message ID:** 54802

**Message Description:** LOG\_ID\_DNS\_FTGD\_CAT\_ALLOW

**Message Meaning:** Domain is monitored

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

## 54803 - LOG\_ID\_DNS\_FTGD\_CAT\_BLOCK

**Message ID:** 54803

**Message Description:** LOG\_ID\_DNS\_FTGD\_CAT\_BLOCK

**Message Meaning:** Domain belongs to a denied category in policy

**Type:** DNS

**Category:** DNS-RESPONSE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

# Email

## 20480 - LOGID\_ANTISPAM\_EMAIL\_SMTP\_NOTIF

**Message ID:** 20480

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_SMTP\_NOTIF

**Message Meaning:** SMTP warning

**Type:** Email

**Category:** SMTP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20481 - LOGID\_ANTISPAM\_EMAIL\_SMTP\_BWORD\_NOTIF

**Message ID:** 20481

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_SMTP\_BWORD\_NOTIF

**Message Meaning:** SMTP warning

**Type:** Email

**Category:** SMTP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20482 - LOGID\_ANTISPAM\_EMAIL\_POP3\_NOTIF

**Message ID:** 20482

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_POP3\_NOTIF

**Message Meaning:** POP3 warning

**Type:** Email

**Category:** POP3

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128

Log Field Name	Description	Data Type	Length
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20483 - LOGID\_ANTISPAM\_EMAIL\_POP3\_BWORD\_NOTIF

**Message ID:** 20483

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_POP3\_BWORD\_NOTIF

**Message Meaning:** POP3 notice

**Type:** Email

**Category:** POP3

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512



Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20484 - LOGID\_ANTISPAM\_EMAIL\_IMAP\_NOTIF

**Message ID:** 20484

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_IMAP\_NOTIF

**Message Meaning:** IMAP notice

**Type:** Email

**Category:** IMAP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512

Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20485 - LOGID\_ANTISPAM\_ENDPOINT\_FILTER\_WARNING

**Message ID:** 20485

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_FILTER\_WARNING

**Message Meaning:** Endpoint filter warning

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64

Log Field Name	Description	Data Type	Length
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20486 - LOGID\_ANTISPAM\_ENDPOINT\_FILTER\_NOTIF

**Message ID:** 20486

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_FILTER\_NOTIF

**Message Meaning:** Endpoint filter notice

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20487 - LOGID\_ANTISPAM\_ENDPOINT\_MM7\_WARNING

**Message ID:** 20487

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_MM7\_WARNING

**Message Meaning:** MM7 warning

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20488 - LOGID\_ANTISPAM\_ENDPOINT\_MM7\_NOTIF

**Message ID:** 20488

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_MM7\_NOTIF

**Message Meaning:** MM7 notice

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20489 - LOGID\_ANTISPAM\_ENDPOINT\_MM1\_WARNING

**Message ID:** 20489

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_MM1\_WARNING

**Message Meaning:** MM1 warning

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20490 - LOGID\_ANTISPAM\_ENDPOINT\_MM1\_NOTIF

**Message ID:** 20490

**Message Description:** LOGID\_ANTISPAM\_ENDPOINT\_MM1\_NOTIF

**Message Meaning:** MM1 notice

**Type:** Email

**Category:** CARRIER-ENDPOINT-FILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20491 - LOGID\_ANTISPAM\_EMAIL\_IMAP\_BWORD\_NOTIF

**Message ID:** 20491

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_IMAP\_BWORD\_NOTIF

**Message Meaning:** IMAP banned word notice

**Type:** Email

**Category:** IMAP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20492 - LOGID\_ANTISPAM\_MM1\_FLOOD\_WARNING

**Message ID:** 20492

**Message Description:** LOGID\_ANTISPAM\_MM1\_FLOOD\_WARNING

**Message Meaning:** MM1 flood detection warning

**Type:** Email

**Category:** MASS-MMS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20493 - LOGID\_ANTISPAM\_MM1\_FLOOD\_NOTIF

**Message ID:** 20493

**Message Description:** LOGID\_ANTISPAM\_MM1\_FLOOD\_NOTIF

**Message Meaning:** MM1 flood detection notice

**Type:** Email

**Category:** MASS-MMS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32
vrf		uint8	3

## 20494 - LOGID\_ANTISPAM\_MM4\_FLOOD\_WARNING

**Message ID:** 20494

**Message Description:** LOGID\_ANTISPAM\_MM4\_FLOOD\_WARNING

**Message Meaning:** MM4 flood detection warning

**Type:** Email

**Category:** MASS-MMS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20495 - LOGID\_ANTISPAM\_MM4\_FLOOD\_NOTIF

**Message ID:** 20495

**Message Description:** LOGID\_ANTISPAM\_MM4\_FLOOD\_NOTIF

**Message Meaning:** MM4 flood detection notice

**Type:** Email

**Category:** MASS-MMS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20496 - LOGID\_ANTISPAM\_MM1\_DUPE\_WARNING

**Message ID:** 20496

**Message Description:** LOGID\_ANTISPAM\_MM1\_DUPE\_WARNING

**Message Meaning:** MM1 duplicate detection warning

**Type:** Email

**Category:** MASS-MMS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128

Log Field Name	Description	Data Type	Length
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20497 - LOGID\_ANTISPAM\_MM1\_DUPE\_NOTIF

**Message ID:** 20497

**Message Description:** LOGID\_ANTISPAM\_MM1\_DUPE\_NOTIF

**Message Meaning:** MM1 duplicate detection notice

**Type:** Email

**Category:** MASS-MMS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10



Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20498 - LOGID\_ANTISPAM\_MM4\_DUPE\_WARNING

**Message ID:** 20498

**Message Description:** LOGID\_ANTISPAM\_MM4\_DUPE\_WARNING

**Message Meaning:** MM4 duplicate detection warning

**Type:** Email

**Category:** MASS-MMS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512

Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20499 - LOGID\_ANTISPAM\_MM4\_DUPE\_NOTIF

**Message ID:** 20499

**Message Description:** LOGID\_ANTISPAM\_MM4\_DUPE\_NOTIF

**Message Meaning:** MM4 duplicate detection notice

**Type:** Email

**Category:** MASS-MMS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64

Log Field Name	Description	Data Type	Length
proto	Protocol number	uint8	3
rcvbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20500 - LOGID\_ANTISPAM\_EMAIL\_MSN\_NOTIF

**Message ID:** 20500

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_MSN\_NOTIF

**Message Meaning:** MSN Hotmail email message

**Type:** Email

**Category:** MSN-HOTMAIL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20501 - LOGID\_ANTISPAM\_EMAIL\_YAHOO\_NOTIF

**Message ID:** 20501

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_YAHOO\_NOTIF

**Message Meaning:** Yahoo! email message

**Type:** Email

**Category:** YAHOO-MAIL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256



Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20502 - LOGID\_ANTISPAM\_EMAIL\_GOOGLE\_NOTIF

**Message ID:** 20502

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_GOOGLE\_NOTIF

**Message Meaning:** Gmail email message

**Type:** Email

**Category:** GMAIL

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20503 - LOGID\_EMAIL\_SMTP\_GENERAL\_NOTIF

**Message ID:** 20503

**Message Description:** LOGID\_EMAIL\_SMTP\_GENERAL\_NOTIF

**Message Meaning:** SMTP warning

**Type:** Email

**Category:** SMTP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20504 - LOGID\_EMAIL\_POP3\_GENERAL\_NOTIF

**Message ID:** 20504

**Message Description:** LOGID\_EMAIL\_POP3\_GENERAL\_NOTIF

**Message Meaning:** POP3 warning

**Type:** Email

**Category:** POP3

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20505 - LOGID\_EMAIL\_IMAP\_GENERAL\_NOTIF

**Message ID:** 20505

**Message Description:** LOGID\_EMAIL\_IMAP\_GENERAL\_NOTIF

**Message Meaning:** IMAP notice

**Type:** Email

**Category:** IMAP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20506 - LOGID\_EMAIL\_MAPI\_GENERAL\_NOTIF

**Message ID:** 20506

**Message Description:** LOGID\_EMAIL\_MAPI\_GENERAL\_NOTIF

**Message Meaning:** MAPI notice

**Type:** Email

**Category:** MAPI

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8



Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20507 - LOGID\_ANTISPAM\_EMAIL\_MAPI\_BWORD\_NOTIF

**Message ID:** 20507

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_MAPI\_BWORD\_NOTIF

**Message Meaning:** MAPI banned word notice

**Type:** Email

**Category:** MAPI

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32
vrf		uint8	3

## 20508 - LOGID\_ANTISPAM\_EMAIL\_MAPI\_NOTIF

**Message ID:** 20508

**Message Description:** LOGID\_ANTISPAM\_EMAIL\_MAPI\_NOTIF

**Message Meaning:** MAPI email message

**Type:** Email

**Category:** MAPI

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 20509 - LOGID\_ANTISPAM\_FTGD\_ERR

**Message ID:** 20509

**Message Description:** LOGID\_ANTISPAM\_FTGD\_ERR

**Message Meaning:** FortiGuard error message

**Type:** Email

**Category:** MAPI

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte		uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte		uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## Event

### 20002 - LOG\_ID\_DOMAIN\_UNRESOLVABLE

**Message ID:** 20002

**Message Description:** LOG\_ID\_DOMAIN\_UNRESOLVABLE

**Message Meaning:** Domain name of alert email sender unresolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

### 20003 - LOG\_ID\_MAIL\_SENT\_FAIL

**Message ID:** 20003

**Message Description:** LOG\_ID\_MAIL\_SENT\_FAIL

**Message Meaning:** Alert email send status failed



**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20004 - LOG\_ID\_POLICY\_TOO\_BIG

**Message ID:** 20004

**Message Description:** LOG\_ID\_POLICY\_TOO\_BIG

**Message Meaning:** Policy too big for installation

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20005 - LOG\_ID\_PPP\_LINK\_UP

**Message ID:** 20005

**Message Description:** LOG\_ID\_PPP\_LINK\_UP

**Message Meaning:** Modem PPP link up

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20006 - LOG\_ID\_PPP\_LINK\_DOWN

**Message ID:** 20006

**Message Description:** LOG\_ID\_PPP\_LINK\_DOWN

**Message Meaning:** Modem PPP link down

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20007 - LOG\_ID\_SOCKET\_EXHAUSTED

**Message ID:** 20007

**Message Description:** LOG\_ID\_SOCKET\_EXHAUSTED

**Message Meaning:** NAT port exhausted

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
proto	Protocol Number	uint8	3
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vrf		uint8	3

## 20008 - LOG\_ID\_POLICY6\_TOO\_BIG

**Message ID:** 20008

**Message Description:** LOG\_ID\_POLICY6\_TOO\_BIG

**Message Meaning:** IPv6 policy too big for installation

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20010 - LOG\_ID\_KERNEL\_ERROR

**Message ID:** 20010

**Message Description:** LOG\_ID\_KERNEL\_ERROR

**Message Meaning:** Kernel error

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20016 - LOG\_ID\_MODEM\_EXCEED\_REDIAL\_COUNT

**Message ID:** 20016

**Message Description:** LOG\_ID\_MODEM\_EXCEED\_REDIAL\_COUNT

**Message Meaning:** Modem exceeded redial limit

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20017 - LOG\_ID\_MODEM\_FAIL\_TO\_OPEN

**Message ID:** 20017

**Message Description:** LOG\_ID\_MODEM\_FAIL\_TO\_OPEN

**Message Meaning:** Modem failed to open

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20020 - LOG\_ID\_MODEM\_USB\_DETECTED

**Message ID:** 20020

**Message Description:** LOG\_ID\_MODEM\_USB\_DETECTED

**Message Meaning:** USB modem detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20021 - LOG\_ID\_MAIL\_RESENT

**Message ID:** 20021

**Message Description:** LOG\_ID\_MAIL\_RESENT

**Message Meaning:** Alert email resent

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20022 - LOG\_ID\_MODEM\_USB\_REMOVED

**Message ID:** 20022

**Message Description:** LOG\_ID\_MODEM\_USB\_REMOVED

**Message Meaning:** USB modem removed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20023 - LOG\_ID\_MODEM\_USBLTE\_DETECTED

**Message ID:** 20023

**Message Description:** LOG\_ID\_MODEM\_USBLTE\_DETECTED

**Message Meaning:** USB LTE modem detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20024 - LOG\_ID\_MODEM\_USBLTE\_REMOVED

**Message ID:** 20024

**Message Description:** LOG\_ID\_MODEM\_USBLTE\_REMOVED

**Message Meaning:** USB LTE modem removed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20025 - LOG\_ID\_REPORTD\_REPORT\_SUCCESS

**Message ID:** 20025

**Message Description:** LOG\_ID\_REPORTD\_REPORT\_SUCCESS

**Message Meaning:** Report generated successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
datarange	data range for reports	string	50
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
file	File Name for Generated Report?	string	256
filesize	Report File Size in Bytes	uint32	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
processtime	process time for reports	uint32	
reporttype	Report Type	string	20
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20026 - LOG\_ID\_REPORTD\_REPORT\_FAILURE

**Message ID:** 20026

**Message Description:** LOG\_ID\_REPORTD\_REPORT\_FAILURE

**Message Meaning:** Report generation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20027 - LOG\_ID\_REPORT\_DEL\_OLD\_REC

**Message ID:** 20027

**Message Description:** LOG\_ID\_REPORT\_DEL\_OLD\_REC

**Message Meaning:** Outdated report files deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20028 - LOG\_ID\_REPORT\_RECREATE\_DB

**Message ID:** 20028

**Message Description:** LOG\_ID\_REPORT\_RECREATE\_DB

**Message Meaning:** Report database recreated

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20031 - LOG\_ID\_RAD\_OUT\_OF\_MEM

**Message ID:** 20031

**Message Description:** LOG\_ID\_RAD\_OUT\_OF\_MEM

**Message Meaning:** RADVD out of memory

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20032 - LOG\_ID\_RAD\_NOT\_FOUND

**Message ID:** 20032

**Message Description:** LOG\_ID\_RAD\_NOT\_FOUND

**Message Meaning:** RADVD interface not found

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20033 - LOG\_ID\_RAD\_MOBILE\_IPV6

**Message ID:** 20033

**Message Description:** LOG\_ID\_RAD\_MOBILE\_IPV6

**Message Meaning:** RADVD mobile IPv6 extensions used

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20034 - LOG\_ID\_RAD\_IPV6\_OUT\_OF\_RANGE

**Message ID:** 20034

**Message Description:** LOG\_ID\_RAD\_IPV6\_OUT\_OF\_RANGE

**Message Meaning:** RADVD mobile IPv6 MinRtrAdvInterval out of range

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20035 - LOG\_ID\_RAD\_MIN\_OUT\_OF\_RANGE

**Message ID:** 20035

**Message Description:** LOG\_ID\_RAD\_MIN\_OUT\_OF\_RANGE

**Message Meaning:** RADVD MinRtrAdvInterval out of range

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20036 - LOG\_ID\_RAD\_MAX\_OUT\_OF\_RANGE

**Message ID:** 20036

**Message Description:** LOG\_ID\_RAD\_MAX\_OUT\_OF\_RANGE

**Message Meaning:** RADVD mobile IPv6 MaxRtrAdvInterval out of range

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20037 - LOG\_ID\_RAD\_MAX\_ADV\_OUT\_OF\_RANGE

**Message ID:** 20037

**Message Description:** LOG\_ID\_RAD\_MAX\_ADV\_OUT\_OF\_RANGE

**Message Meaning:** RADVD MaxRtrAdvInterval out of range

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20039 - LOG\_ID\_RAD\_MTU\_TOO\_SMALL

**Message ID:** 20039

**Message Description:** LOG\_ID\_RAD\_MTU\_TOO\_SMALL

**Message Meaning:** RADVD AdvLinkMTU too small

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20040 - LOG\_ID\_RAD\_TIME\_TOO\_SMALL

**Message ID:** 20040

**Message Description:** LOG\_ID\_RAD\_TIME\_TOO\_SMALL

**Message Meaning:** RADVD AdvReachableTime too small

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20041 - LOG\_ID\_RAD\_HOP\_OUT\_OF\_RANGE

**Message ID:** 20041

**Message Description:** LOG\_ID\_RAD\_HOP\_OUT\_OF\_RANGE

**Message Meaning:** RADVD AdvCurHopLimit too big

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20042 - LOG\_ID\_RAD\_DFT\_HOP\_OUT\_OF\_RANGE

**Message ID:** 20042

**Message Description:** LOG\_ID\_RAD\_DFT\_HOP\_OUT\_OF\_RANGE

**Message Meaning:** RADVD AdvCurHopLimit out of range

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20043 - LOG\_ID\_RAD\_AGENT\_OUT\_OF\_RANGE

**Message ID:** 20043

**Message Description:** LOG\_ID\_RAD\_AGENT\_OUT\_OF\_RANGE

**Message Meaning:** RADVD HomeAgentLifetime out of range

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20044 - LOG\_ID\_RAD\_AGENT\_FLAG\_NOT\_SET

**Message ID:** 20044

**Message Description:** LOG\_ID\_RAD\_AGENT\_FLAG\_NOT\_SET

**Message Meaning:** RADVD AdvHomeAgentFlag not set

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20045 - LOG\_ID\_RAD\_PREFIX\_TOO\_LONG

**Message ID:** 20045

**Message Description:** LOG\_ID\_RAD\_PREFIX\_TOO\_LONG

**Message Meaning:** RADVD invalid prefix length

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20046 - LOG\_ID\_RAD\_PREF\_TIME\_TOO\_SMALL

**Message ID:** 20046

**Message Description:** LOG\_ID\_RAD\_PREF\_TIME\_TOO\_SMALL

**Message Meaning:** RADVD AdvValidLifetime less than AdvPreferredLifetime

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20047 - LOG\_ID\_RAD\_FAIL\_IPV6\_SOCKET

**Message ID:** 20047

**Message Description:** LOG\_ID\_RAD\_FAIL\_IPV6\_SOCKET

**Message Meaning:** RADVD failed to create an IPv6 socket

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20048 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_PKTINFO

**Message ID:** 20048

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_PKTINFO

**Message Meaning:** RADVD failed to set IPv6 packet info

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20049 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_CHECKSUM

**Message ID:** 20049

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_CHECKSUM

**Message Meaning:** RADVD failed to set IPv6 checksum

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20050 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_UNICAST\_HOPS

**Message ID:** 20050



**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_UNICAST\_HOPS

**Message Meaning:** RADVD failed to set IPv6 unicast hops

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20051 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_MULTICAST\_HOPS

**Message ID:** 20051

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_MULTICAST\_HOPS

**Message Meaning:** RADVD failed to set IPv6 multicast hops

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20052 - LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_HOPLIMIT

**Message ID:** 20052

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPV6\_HOPLIMIT

**Message Meaning:** RADVD failed to set IPv6 hop limit

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20053 - LOG\_ID\_RAD\_FAIL\_OPT\_IPPROTO\_ICMPV6

**Message ID:** 20053

**Message Description:** LOG\_ID\_RAD\_FAIL\_OPT\_IPPROTO\_ICMPV6

**Message Meaning:** RADVD failed to set ICMPv6 filter

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20054 - LOG\_ID\_RAD\_EXIT\_BY\_SIGNAL

**Message ID:** 20054

**Message Description:** LOG\_ID\_RAD\_EXIT\_BY\_SIGNAL

**Message Meaning:** RADVD exited due to received signal

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20055 - LOG\_ID\_RAD\_FAIL\_CMDB\_QUERY

**Message ID:** 20055

**Message Description:** LOG\_ID\_RAD\_FAIL\_CMDB\_QUERY

**Message Meaning:** RADVD interface query creation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20056 - LOG\_ID\_RAD\_FAIL\_CMDB\_FOR\_EACH

**Message ID:** 20056

**Message Description:** LOG\_ID\_RAD\_FAIL\_CMDB\_FOR\_EACH

**Message Meaning:** RADVD query error

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20057 - LOG\_ID\_RAD\_FAIL\_FIND\_VIRT\_INTF

**Message ID:** 20057

**Message Description:** LOG\_ID\_RAD\_FAIL\_FIND\_VIRT\_INTF

**Message Meaning:** RADVD virtual interface not found

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20058 - LOG\_ID\_RAD\_UNLOAD\_INTF

**Message ID:** 20058

**Message Description:** LOG\_ID\_RAD\_UNLOAD\_INTF

**Message Meaning:** RADVD unloaded interface

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20059 - LOG\_ID\_RAD\_NO\_PKT\_INFO

**Message ID:** 20059

**Message Description:** LOG\_ID\_RAD\_NO\_PKT\_INFO

**Message Meaning:** RADVD received packet with no information

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20060 - LOG\_ID\_RAD\_INV\_ICMPV6\_LEN

**Message ID:** 20060

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_LEN

**Message Meaning:** RADVD received ICMPv6 packet with invalid length

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20061 - LOG\_ID\_RAD\_INV\_ICMPV6\_TYPE

**Message ID:** 20061

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_TYPE

**Message Meaning:** RADVD received unwanted ICMPv6 packet

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20062 - LOG\_ID\_RAD\_INV\_ICMPV6\_RA\_LEN

**Message ID:** 20062

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_RA\_LEN

**Message Meaning:** RADVD received ICMPv6 RA packet with invalid length

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20



Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20063 - LOG\_ID\_RAD\_ICMPV6\_NO\_SRC\_ADDR

**Message ID:** 20063

**Message Description:** LOG\_ID\_RAD\_ICMPV6\_NO\_SRC\_ADDR

**Message Meaning:** RADVD received ICMPv6 RA packet with non-link local source address

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20064 - LOG\_ID\_RAD\_INV\_ICMPV6\_RS\_LEN

**Message ID:** 20064

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_RS\_LEN

**Message Meaning:** RADVD received ICMPv6 RS packet with invalid length

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20065 - LOG\_ID\_RAD\_INV\_ICMPV6\_CODE

**Message ID:** 20065

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_CODE

**Message Meaning:** RADVD received ICMPv6 RS/RA packet with invalid code

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20066 - LOG\_ID\_RAD\_INV\_ICMPV6\_HOP

**Message ID:** 20066

**Message Description:** LOG\_ID\_RAD\_INV\_ICMPV6\_HOP

**Message Meaning:** RADVD received ICMPv6 RS/RA packet with invalid hop limit

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20067 - LOG\_ID\_RAD\_MISMATCH\_HOP

**Message ID:** 20067

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_HOP

**Message Meaning:** RADVD local AdvCurHopLimit disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20068 - LOG\_ID\_RAD\_MISMATCH\_MGR\_FLAG

**Message ID:** 20068

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_MGR\_FLAG

**Message Meaning:** RADVD local AdvManagedFlag disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20069 - LOG\_ID\_RAD\_MISMATCH\_OTH\_FLAG

**Message ID:** 20069

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_OTH\_FLAG

**Message Meaning:** RADVD local AdvOtherConfigFlag disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20070 - LOG\_ID\_RAD\_MISMATCH\_TIME

**Message ID:** 20070

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_TIME

**Message Meaning:** RADVD local AdvReachableTime disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20071 - LOG\_ID\_RAD\_MISMATCH\_TIMER

**Message ID:** 20071

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_TIMER

**Message Meaning:** RADVD local AdvRetransTimer disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20072 - LOG\_ID\_RAD\_EXTRA\_DATA

**Message ID:** 20072

**Message Description:** LOG\_ID\_RAD\_EXTRA\_DATA

**Message Meaning:** RADVD extra data in RA packet found

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20073 - LOG\_ID\_RAD\_NO\_OPT\_DATA

**Message ID:** 20073

**Message Description:** LOG\_ID\_RAD\_NO\_OPT\_DATA

**Message Meaning:** RADVD RA packet option length zero

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20074 - LOG\_ID\_RAD\_INV\_OPT\_LEN

**Message ID:** 20074

**Message Description:** LOG\_ID\_RAD\_INV\_OPT\_LEN

**Message Meaning:** RADVD RA packet option length greater than total length

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32



## 20075 - LOG\_ID\_RAD\_MISMATCH\_MTU

**Message ID:** 20075

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_MTU

**Message Meaning:** RADVD local AdvLinkMTU disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20077 - LOG\_ID\_RAD\_MISMATCH\_PREF\_TIME

**Message ID:** 20077

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_PREF\_TIME

**Message Meaning:** Interface AdvPreferredLifetime on our interface does not agree with a remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20078 - LOG\_ID\_RAD\_INV\_OPT

**Message ID:** 20078

**Message Description:** LOG\_ID\_RAD\_INV\_OPT

**Message Meaning:** RADVD found invalid option in RA packet from remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20079 - LOG\_ID\_RAD\_READY

**Message ID:** 20079

**Message Description:** LOG\_ID\_RAD\_READY

**Message Meaning:** RADVD daemon started

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20080 - LOG\_ID\_RAD\_FAIL\_TO\_RCV

**Message ID:** 20080

**Message Description:** LOG\_ID\_RAD\_FAIL\_TO\_RCV

**Message Meaning:** RADVD receive message failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20081 - LOG\_ID\_RAD\_INV\_HOP

**Message ID:** 20081

**Message Description:** LOG\_ID\_RAD\_INV\_HOP

**Message Meaning:** RADVD received invalid IPv6 hop limit

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20082 - LOG\_ID\_RAD\_INV\_PKTINFO

**Message ID:** 20082

**Message Description:** LOG\_ID\_RAD\_INV\_PKTINFO

**Message Meaning:** RADVD received invalid IPv6 packet info

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20083 - LOG\_ID\_RAD\_FAIL\_TO\_CHECK

**Message ID:** 20083

**Message Description:** LOG\_ID\_RAD\_FAIL\_TO\_CHECK

**Message Meaning:** RADVD all-routers membership check failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20084 - LOG\_ID\_RAD\_FAIL\_TO\_SEND

**Message ID:** 20084

**Message Description:** LOG\_ID\_RAD\_FAIL\_TO\_SEND

**Message Meaning:** RADVD send message failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20085 - LOG\_ID\_SESSION\_CLASH

**Message ID:** 20085

**Message Description:** LOG\_ID\_SESSION\_CLASH

**Message Meaning:** Session clashed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
proto	Protocol Number	uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
trace_id		string	32
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20086 - LOG\_ID\_XH0\_EVENT

**Message ID:** 20086

**Message Description:** LOG\_ID\_XH0\_EVENT

**Message Meaning:** xh0 crashed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20090 - LOG\_ID\_INTF\_LINK\_STA\_CHG

**Message ID:** 20090

**Message Description:** LOG\_ID\_INTF\_LINK\_STA\_CHG

**Message Meaning:** Interface link status changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
intf	Interface	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20099 - LOG\_ID\_INTF\_STA\_CHG

**Message ID:** 20099

**Message Description:** LOG\_ID\_INTF\_STA\_CHG



**Message Meaning:** Interface status changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20100 - LOG\_ID\_WEB\_CAT\_UPDATED

**Message ID:** 20100

**Message Description:** LOG\_ID\_WEB\_CAT\_UPDATED

**Message Meaning:** FortiGuard web filter category list updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20101 - LOG\_ID\_WEB\_LIC\_EXPIRE

**Message ID:** 20101

**Message Description:** LOG\_ID\_WEB\_LIC\_EXPIRE

**Message Meaning:** FortiGuard web filter license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20102 - LOG\_ID\_SPAM\_LIC\_EXPIRE

**Message ID:** 20102

**Message Description:** LOG\_ID\_SPAM\_LIC\_EXPIRE

**Message Meaning:** FortiGuard antispam license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20103 - LOG\_ID\_AV\_LIC\_EXPIRE

**Message ID:** 20103

**Message Description:** LOG\_ID\_AV\_LIC\_EXPIRE

**Message Meaning:** FortiGuard antivirus license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20104 - LOG\_ID\_IPS\_LIC\_EXPIRE

**Message ID:** 20104

**Message Description:** LOG\_ID\_IPS\_LIC\_EXPIRE

**Message Meaning:** FortiGuard IPS license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20105 - LOG\_ID\_LOG\_UPLOAD\_SKIP

**Message ID:** 20105

**Message Description:** LOG\_ID\_LOG\_UPLOAD\_SKIP

**Message Meaning:** Log upload to FortiCloud skipped

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
error	Error Reason for Log Upload to Forticloud	string	256
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 20107 - LOG\_ID\_LOG\_UPLOAD\_ERR

**Message ID:** 20107

**Message Description:** LOG\_ID\_LOG\_UPLOAD\_ERR

**Message Meaning:** Log upload error

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
error	Error Reason for Log Upload to Forticloud	string	256
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20108 - LOG\_ID\_LOG\_UPLOAD\_DONE

**Message ID:** 20108

**Message Description:** LOG\_ID\_LOG\_UPLOAD\_DONE

**Message Meaning:** Log upload completed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20109 - LOG\_ID\_WEB\_LIC\_EXPIRED

**Message ID:** 20109

**Message Description:** LOG\_ID\_WEB\_LIC\_EXPIRED

**Message Meaning:** FortiGuard web filter license expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20113 - LOG\_ID\_IPSA\_DOWNLOAD\_FAIL

**Message ID:** 20113

**Message Description:** LOG\_ID\_IPSA\_DOWNLOAD\_FAIL

**Message Meaning:** IPSA database download failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20115 - LOG\_ID\_IPSA\_STATUSUPD\_FAIL

**Message ID:** 20115

**Message Description:** LOG\_ID\_IPSA\_STATUSUPD\_FAIL

**Message Meaning:** IPSA driver update failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20116 - LOG\_ID\_SPAM\_LIC\_EXPIRED

**Message ID:** 20116

**Message Description:** LOG\_ID\_SPAM\_LIC\_EXPIRED

**Message Meaning:** FortiGuard antispam license expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20117 - LOG\_ID\_AV\_LIC\_EXPIRED

**Message ID:** 20117

**Message Description:** LOG\_ID\_AV\_LIC\_EXPIRED

**Message Meaning:** FortiGuard antivirus license expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20118 - LOG\_ID\_WEBF\_STATUS\_REACH

**Message ID:** 20118

**Message Description:** LOG\_ID\_WEBF\_STATUS\_REACH

**Message Meaning:** FortiGuard webfilter reachable

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20119 - LOG\_ID\_WEBF\_STATUS\_UNREACH

**Message ID:** 20119

**Message Description:** LOG\_ID\_WEBF\_STATUS\_UNREACH

**Message Meaning:** FortiGuard webfilter unreachable

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20200 - LOG\_ID\_FIPS\_SELF\_TEST

**Message ID:** 20200

**Message Description:** LOG\_ID\_FIPS\_SELF\_TEST

**Message Meaning:** FIPS CC self-test initiated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20201 - LOG\_ID\_FIPS\_SELF\_ALL\_TEST

**Message ID:** 20201

**Message Description:** LOG\_ID\_FIPS\_SELF\_ALL\_TEST

**Message Meaning:** FIPS ALL CC self-tests initiated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20202 - LOG\_ID\_DISK\_FORMAT\_ERROR

**Message ID:** 20202

**Message Description:** LOG\_ID\_DISK\_FORMAT\_ERROR

**Message Meaning:** Disk partitioning or formatting Error

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20203 - LOG\_ID\_DAEMON\_SHUTDOWN

**Message ID:** 20203

**Message Description:** LOG\_ID\_DAEMON\_SHUTDOWN

**Message Meaning:** Daemon shutdown

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20204 - LOG\_ID\_DAEMON\_START

**Message ID:** 20204

**Message Description:** LOG\_ID\_DAEMON\_START

**Message Meaning:** Daemon started

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20205 - LOG\_ID\_DISK\_FORMAT\_REQ

**Message ID:** 20205

**Message Description:** LOG\_ID\_DISK\_FORMAT\_REQ

**Message Meaning:** Format disk requested

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

---

## 20206 - LOG\_ID\_DISK\_SCAN\_REQ

**Message ID:** 20206

**Message Description:** LOG\_ID\_DISK\_SCAN\_REQ

**Message Meaning:** Scan disk requested

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20207 - LOG\_ID\_RAD\_MISMATCH\_VALID\_TIME

**Message ID:** 20207

**Message Description:** LOG\_ID\_RAD\_MISMATCH\_VALID\_TIME

**Message Meaning:** RADVD local AdvValidLifetime disagrees with remote site

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20208 - LOG\_ID\_ZOMBIE\_DAEMON\_CLEANUP

**Message ID:** 20208

**Message Description:** LOG\_ID\_ZOMBIE\_DAEMON\_CLEANUP

**Message Meaning:** Zombie daemon cleanup

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20209 - LOG\_ID\_DISK\_UNAVAIL

**Message ID:** 20209

**Message Description:** LOG\_ID\_DISK\_UNAVAIL

**Message Meaning:** Disk unavailable

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20210 - LOG\_ID\_DISK\_TRIM\_START

**Message ID:** 20210

**Message Description:** LOG\_ID\_DISK\_TRIM\_START

**Message Meaning:** SSD TRIM started

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20211 - LOG\_ID\_DISK\_TRIM\_END

**Message ID:** 20211

**Message Description:** LOG\_ID\_DISK\_TRIM\_END

**Message Meaning:** SSD TRIM finished

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 20212 - LOG\_ID\_DISK\_SCAN\_NEEDED

**Message ID:** 20212

**Message Description:** LOG\_ID\_DISK\_SCAN\_NEEDED

**Message Meaning:** Disk scan is needed

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20220 - LOGID\_EVENT\_SHAPER\_OUTBOUND\_MAXED\_OUT

**Message ID:** 20220

**Message Description:** LOGID\_EVENT\_SHAPER\_OUTBOUND\_MAXED\_OUT

**Message Meaning:** Outbound bandwidth rate exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
intf	Interface	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20221 - LOGID\_EVENT\_SHAPER\_INBOUND\_MAXED\_OUT

**Message ID:** 20221

**Message Description:** LOGID\_EVENT\_SHAPER\_INBOUND\_MAXED\_OUT

**Message Meaning:** Inbound bandwidth rate exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
intf	Interface	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20300 - LOG\_ID\_BGP\_NB\_STAT\_CHG

**Message ID:** 20300

**Message Description:** LOG\_ID\_BGP\_NB\_STAT\_CHG

**Message Meaning:** BGP neighbor status changed

**Type:** Event

**Category:** ROUTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20301 - LOG\_ID\_VZ\_LOG

**Message ID:** 20301

**Message Description:** LOG\_ID\_VZ\_LOG

**Message Meaning:** Routing log

**Type:** Event

**Category:** ROUTER

**Severity:** Warning, Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20302 - LOG\_ID\_OSPF\_NB\_STAT\_CHG

**Message ID:** 20302

**Message Description:** LOG\_ID\_OSPF\_NB\_STAT\_CHG

**Message Meaning:** OSPF neighbor status changed

**Type:** Event

**Category:** ROUTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20303 - LOG\_ID\_OSPF6\_NB\_STAT\_CHG

**Message ID:** 20303

**Message Description:** LOG\_ID\_OSPF6\_NB\_STAT\_CHG

**Message Meaning:** OSPF6 neighbor status changed

**Type:** Event

**Category:** ROUTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 20401 - LOG\_ID\_ROUTER\_CLEAR

**Message ID:** 20401



**Message Description:** LOG\_ID\_ROUTER\_CLEAR

**Message Meaning:** Router cleared

**Type:** Event

**Category:** ROUTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui		string	64
user		string	256
vd	Virtual Domain Name	string	32

## 22000 - LOG\_ID\_INV\_PKT\_LEN

**Message ID:** 22000

**Message Description:** LOG\_ID\_INV\_PKT\_LEN

**Message Meaning:** Packet length mismatch

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22001 - LOG\_ID\_UNSUPPORTED\_PROT\_VER

**Message ID:** 22001

**Message Description:** LOG\_ID\_UNSUPPORTED\_PROT\_VER

**Message Meaning:** Protocol version unsupported

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22002 - LOG\_ID\_INV\_REQ\_TYPE

**Message ID:** 22002

**Message Description:** LOG\_ID\_INV\_REQ\_TYPE

**Message Meaning:** Request type not supported

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22003 - LOG\_ID\_FAIL\_SET\_SIG\_HANDLER

**Message ID:** 22003

**Message Description:** LOG\_ID\_FAIL\_SET\_SIG\_HANDLER

**Message Meaning:** Signal handler setup failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22004 - LOG\_ID\_FAIL\_CREATE\_SOCKET

**Message ID:** 22004

**Message Description:** LOG\_ID\_FAIL\_CREATE\_SOCKET

**Message Meaning:** Socket creation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22005 - LOG\_ID\_FAIL\_CREATE\_SOCKET\_RETRY

**Message ID:** 22005

**Message Description:** LOG\_ID\_FAIL\_CREATE\_SOCKET\_RETRY

**Message Meaning:** Socket creation retry failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22006 - LOG\_ID\_FAIL\_REG\_CMDB\_EVENT

**Message ID:** 22006

**Message Description:** LOG\_ID\_FAIL\_REG\_CMDB\_EVENT

**Message Meaning:** Registration for CMDB events failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22009 - LOG\_ID\_FAIL\_FIND\_AV\_PROFILE

**Message ID:** 22009

**Message Description:** LOG\_ID\_FAIL\_FIND\_AV\_PROFILE

**Message Meaning:** AntiVirus profile not found

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22010 - LOG\_ID\_SENDTO\_FAIL

**Message ID:** 22010

**Message Description:** LOG\_ID\_SENDTO\_FAIL

**Message Meaning:** URL filter packet send failure

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
process	Process	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22011 - LOG\_ID\_ENTER\_MEM\_CONSERVE\_MODE

**Message ID:** 22011

**Message Description:** LOG\_ID\_ENTER\_MEM\_CONSERVE\_MODE

**Message Meaning:** Memory conserve mode entered

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22012 - LOG\_ID\_LEAVE\_MEM\_CONSERVE\_MODE

**Message ID:** 22012

**Message Description:** LOG\_ID\_LEAVE\_MEM\_CONSERVE\_MODE

**Message Meaning:** Memory conserve mode exited

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	



Log Field Name	Description	Data Type	Length
red		string	32
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22013 - LOG\_ID\_IPPOOLPBA\_BLOCK\_EXHAUSTED

**Message ID:** 22013

**Message Description:** LOG\_ID\_IPPOOLPBA\_BLOCK\_EXHAUSTED

**Message Meaning:** IP pool PBA block exhausted

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
poolname	IP Pool Name	string	36
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22014 - LOG\_ID\_IPPOOLPBA\_NATIP\_EXHAUSTED

**Message ID:** 22014

**Message Description:** LOG\_ID\_IPPOOLPBA\_NATIP\_EXHAUSTED

**Message Meaning:** IP pool PBA NAT IP exhausted

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
poolname	IP Pool Name	string	36
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22015 - LOG\_ID\_IPPOOLPBA\_CREATE

**Message ID:** 22015

**Message Description:** LOG\_ID\_IPPOOLPBA\_CREATE

**Message Meaning:** IP pool PBA created

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22016 - LOG\_ID\_IPPOOLPBA\_DEALLOCATE

**Message ID:** 22016

**Message Description:** LOG\_ID\_IPPOOLPBA\_DEALLOCATE

**Message Meaning:** Deallocate IP pool PBA

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22017 - LOG\_ID\_EXCEED\_GLOB\_RES\_LIMIT

**Message ID:** 22017

**Message Description:** LOG\_ID\_EXCEED\_GLOB\_RES\_LIMIT

**Message Meaning:** Global resource limit exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22018 - LOG\_ID\_EXCEED\_VD\_RES\_LIMIT

**Message ID:** 22018

**Message Description:** LOG\_ID\_EXCEED\_VD\_RES\_LIMIT

**Message Meaning:** VDOM resource limit exceeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22020 - LOG\_ID\_FAIL\_CREATE\_HA\_SOCKET

**Message ID:** 22020

**Message Description:** LOG\_ID\_FAIL\_CREATE\_HA\_SOCKET

**Message Meaning:** HA socket creation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22021 - LOG\_ID\_FAIL\_CREATE\_HA\_SOCKET\_RETRY

**Message ID:** 22021

**Message Description:** LOG\_ID\_FAIL\_CREATE\_HA\_SOCKET\_RETRY

**Message Meaning:** UDP socket creation to relay URL request failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22030 - LOG\_ID\_FAIL\_CSF\_LOG\_SYNC\_NO\_VALID\_FAZ

**Message ID:** 22030

**Message Description:** LOG\_ID\_FAIL\_CSF\_LOG\_SYNC\_NO\_VALID\_FAZ

**Message Meaning:** FortiAnalyzer is not configured for Security Fabric service

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
server	Server IP Address	string	64
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22031 - LOG\_ID\_SUCCESS\_CSF\_LOG\_SYNC\_CONFIG\_CHANGED

**Message ID:** 22031

**Message Description:** LOG\_ID\_SUCCESS\_CSF\_LOG\_SYNC\_CONFIG\_CHANGED

**Message Meaning:** Settings modified by Security Fabric service

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22032 - LOG\_ID\_CSF\_LOOP\_FOUND

**Message ID:** 22032

**Message Description:** LOG\_ID\_CSF\_LOOP\_FOUND

**Message Meaning:** Looped configuration in Security Fabric service

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
path		string	512
reason	Reason	string	256
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22033 - LOG\_ID\_FAIL\_CSF\_LOG\_SYNC\_NO\_VALID\_FSA

**Message ID:** 22033

**Message Description:** LOG\_ID\_FAIL\_CSF\_LOG\_SYNC\_NO\_VALID\_FSA

**Message Meaning:** CSF root FSA configuration is not properly set

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
server	Server IP Address	string	64
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22035 - LOG\_ID\_CSF\_UPSTREAM\_SN\_CHANGED

**Message ID:** 22035

**Message Description:** LOG\_ID\_CSF\_UPSTREAM\_SN\_CHANGED

**Message Meaning:** Serial number of upstream is changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
oldsn		string	64
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22100 - LOG\_ID\_QUAR\_DROP\_TRAN\_JOB

**Message ID:** 22100

**Message Description:** LOG\_ID\_QUAR\_DROP\_TRAN\_JOB

**Message Meaning:** Files dropped by quarantine daemon

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
fams_pause	Fortinet Analysis and Management Service Pause	uint32	10
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22101 - LOG\_ID\_QUAR\_DROP\_TLL\_JOB

**Message ID:** 22101

**Message Description:** LOG\_ID\_QUAR\_DROP\_TLL\_JOB

**Message Meaning:** Files dropped due to poor network connection

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22102 - LOG\_ID\_LOG\_DISK\_FAILURE

**Message ID:** 22102

**Message Description:** LOG\_ID\_LOG\_DISK\_FAILURE

**Message Meaning:** Log disk failure imminent

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22103 - LOG\_ID\_QUAR\_LIMIT\_REACHED

**Message ID:** 22103

**Message Description:** LOG\_ID\_QUAR\_LIMIT\_REACHED

**Message Meaning:** Sandbox limit reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

---

## 22104 - LOG\_ID\_POWER\_RESTORE

**Message ID:** 22104

**Message Description:** LOG\_ID\_POWER\_RESTORE

**Message Meaning:** Power supply restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical, Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unit	Unit	uint32	10
vd	Virtual Domain Name	string	32

## 22105 - LOG\_ID\_POWER\_FAILURE

**Message ID:** 22105

**Message Description:** LOG\_ID\_POWER\_FAILURE

**Message Meaning:** Power supply failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical, Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unit	Unit	uint32	10
vd	Virtual Domain Name	string	32

## 22106 - LOG\_ID\_POWER\_OPTIONAL\_NOT\_DETECTED

**Message ID:** 22106

**Message Description:** LOG\_ID\_POWER\_OPTIONAL\_NOT\_DETECTED

**Message Meaning:** Optional power supply not detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22107 - LOG\_ID\_VOLT\_ANOM

**Message ID:** 22107

**Message Description:** LOG\_ID\_VOLT\_ANOM

**Message Meaning:** Voltage anomaly

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22108 - LOG\_ID\_FAN\_ANOM

**Message ID:** 22108



**Message Description:** LOG\_ID\_FAN\_ANOM

**Message Meaning:** Fan anomaly

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22109 - LOG\_ID\_TEMP\_TOO\_HIGH

**Message ID:** 22109

**Message Description:** LOG\_ID\_TEMP\_TOO\_HIGH

**Message Meaning:** Temperature too high

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22110 - LOG\_ID\_SPARE\_BLOCK\_LOW

**Message ID:** 22110

**Message Description:** LOG\_ID\_SPARE\_BLOCK\_LOW

**Message Meaning:** Spare blocks availability low

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22113 - LOG\_ID\_FNBAM\_FAILURE

**Message ID:** 22113

**Message Description:** LOG\_ID\_FNBAM\_FAILURE

**Message Meaning:** Authentication error

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22150 - LOG\_ID\_VOLT\_NOM

**Message ID:** 22150

**Message Description:** LOG\_ID\_VOLT\_NOM

**Message Meaning:** Voltage normal

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22151 - LOG\_ID\_FAN\_NOM

**Message ID:** 22151

**Message Description:** LOG\_ID\_FAN\_NOM

**Message Meaning:** Fan normal

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22152 - LOG\_ID\_TEMP\_TOO\_LOW

**Message ID:** 22152

**Message Description:** LOG\_ID\_TEMP\_TOO\_LOW

**Message Meaning:** Temperature too low

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22153 - LOG\_ID\_TEMP\_NORM

**Message ID:** 22153

**Message Description:** LOG\_ID\_TEMP\_NORM

**Message Meaning:** Temperature normal

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22200 - LOG\_ID\_AUTO\_UPT\_CERT

**Message ID:** 22200

**Message Description:** LOG\_ID\_AUTO\_UPT\_CERT

**Message Meaning:** Certificate will be auto-updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert	Certificate	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22201 - LOG\_ID\_AUTO\_GEN\_CERT

**Message ID:** 22201

**Message Description:** LOG\_ID\_AUTO\_GEN\_CERT

**Message Meaning:** Certificate will be auto-regenerated

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert	Certificate	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22203 - LOG\_ID\_AUTO\_GEN\_CERT\_FAIL

**Message ID:** 22203

**Message Description:** LOG\_ID\_AUTO\_GEN\_CERT\_FAIL

**Message Meaning:** Certificate failed to auto-generate

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22204 - LOG\_ID\_AUTO\_GEN\_CERT\_PENDING

**Message ID:** 22204

**Message Description:** LOG\_ID\_AUTO\_GEN\_CERT\_PENDING

**Message Meaning:** Certificate pending to auto-generate



**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22205 - LOG\_ID\_AUTO\_GEN\_CERT\_SUCC

**Message ID:** 22205

**Message Description:** LOG\_ID\_AUTO\_GEN\_CERT\_SUCC

**Message Meaning:** Certificate succeed to auto-generate

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22206 - LOG\_ID\_CRL\_EXPIRED

**Message ID:** 22206

**Message Description:** LOG\_ID\_CRL\_EXPIRED

**Message Meaning:** CRL is expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22700 - LOG\_ID\_IPS\_FAIL\_OPEN

**Message ID:** 22700

**Message Description:** LOG\_ID\_IPS\_FAIL\_OPEN

**Message Meaning:** IPS session scan paused

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22701 - LOG\_ID\_IPS\_FAIL\_OPEN\_END

**Message ID:** 22701

**Message Description:** LOG\_ID\_IPS\_FAIL\_OPEN\_END

**Message Meaning:** IPS session scan resumed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22800 - LOG\_ID\_SCAN\_SERV\_FAIL

**Message ID:** 22800

**Message Description:** LOG\_ID\_SCAN\_SERV\_FAIL

**Message Meaning:** Scan services session failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22802 - LOG\_ID\_ENTER\_FD\_CONSERVE\_MODE

**Message ID:** 22802

**Message Description:** LOG\_ID\_ENTER\_FD\_CONSERVE\_MODE

**Message Meaning:** File descriptor conserve mode entered

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22803 - LOG\_ID\_LEAVE\_FD\_CONSERVE\_MODE

**Message ID:** 22803

**Message Description:** LOG\_ID\_LEAVE\_FD\_CONSERVE\_MODE

**Message Meaning:** File descriptor conserve mode exited

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical, Notice

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 22804 - LOG\_ID\_LIC\_STATUS\_CHG

**Message ID:** 22804

**Message Description:** LOG\_ID\_LIC\_STATUS\_CHG

**Message Meaning:** License status changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22805 - LOG\_ID\_FAIL\_TO\_VALIDATE\_LIC

**Message ID:** 22805

**Message Description:** LOG\_ID\_FAIL\_TO\_VALIDATE\_LIC

**Message Meaning:** License validation failure

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22806 - LOG\_ID\_DUP\_LIC

**Message ID:** 22806

**Message Description:** LOG\_ID\_DUP\_LIC

**Message Meaning:** Duplicate license detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22808 - LOG\_ID\_LIC\_EXPIRE

**Message ID:** 22808

**Message Description:** LOG\_ID\_LIC\_EXPIRE

**Message Meaning:** VM license expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22809 - LOG\_ID\_LIC\_WILL\_EXPIRE

**Message ID:** 22809

**Message Description:** LOG\_ID\_LIC\_WILL\_EXPIRE

**Message Meaning:** VM license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22891 - LOG\_ID\_FLCFGD\_SYNC\_ERROR

**Message ID:** 22891

**Message Description:** LOG\_ID\_FLCFGD\_SYNC\_ERROR

**Message Meaning:** Switch-Controller Switch Sync Error

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22892 - LOG\_ID\_FLCFGD\_SYNC\_COMPLETE

**Message ID:** 22892

**Message Description:** LOG\_ID\_FLCFGD\_SYNC\_COMPLETE

**Message Meaning:** Switch-Controller Switch Sync Complete

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22893 - LOG\_ID\_FLCFGD\_SYNC\_STATE

**Message ID:** 22893

**Message Description:** LOG\_ID\_FLCFGD\_SYNC\_STATE

**Message Meaning:** Switch-Controller Switch Sync State

**Type:** Event

**Category:** SYSTEM

**Severity:** Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22894 - LOG\_ID\_FLCFGD\_UPGRADE\_ERROR

**Message ID:** 22894

**Message Description:** LOG\_ID\_FLCFGD\_UPGRADE\_ERROR

**Message Meaning:** Switch-Controller Switch Upgrade Error

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22895 - LOG\_ID\_FLCFGD\_UPGRADE\_STATUS

**Message ID:** 22895

**Message Description:** LOG\_ID\_FLCFGD\_UPGRADE\_STATUS

**Message Meaning:** Switch-Controller Switch Upgrade Status

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22900 - LOG\_ID\_CAPUTP\_SESSION

**Message ID:** 22900

**Message Description:** LOG\_ID\_CAPUTP\_SESSION

**Message Meaning:** CAPUTP session status

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22901 - LOG\_ID\_FAZ\_CON

**Message ID:** 22901

**Message Description:** LOG\_ID\_FAZ\_CON

**Message Meaning:** FortiAnalyzer connection up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22902 - LOG\_ID\_FAZ\_DISCON

**Message ID:** 22902

**Message Description:** LOG\_ID\_FAZ\_DISCON

**Message Meaning:** FortiAnalyzer connection down

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22903 - LOG\_ID\_FAZ\_CON\_ERR

**Message ID:** 22903

**Message Description:** LOG\_ID\_FAZ\_CON\_ERR

**Message Meaning:** FortiAnalyzer connection failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32



## 22904 - LOG\_ID\_CAPUTP\_SESSION\_NOTIF

**Message ID:** 22904

**Message Description:** LOG\_ID\_CAPUTP\_SESSION\_NOTIF

**Message Meaning:** CAPUTP session status notification

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22912 - LOG\_ID\_FDS\_SRV\_ERRCON

**Message ID:** 22912

**Message Description:** LOG\_ID\_FDS\_SRV\_ERRCON

**Message Meaning:** FortiCloud server connection failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22913 - LOG\_ID\_FDS\_SRV\_DISCON

**Message ID:** 22913

**Message Description:** LOG\_ID\_FDS\_SRV\_DISCON

**Message Meaning:** FortiCloud server disconnected

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22914 - LOG\_ID\_FDS\_SRV\_CHG

**Message ID:** 22914

**Message Description:** LOG\_ID\_FDS\_SRV\_CHG

**Message Meaning:** FortiCloud server changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22915 - LOG\_ID\_FDS\_SRV\_CON

**Message ID:** 22915

**Message Description:** LOG\_ID\_FDS\_SRV\_CON

**Message Meaning:** FortiCloud server connected

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22916 - LOG\_ID\_FDS\_STATUS

**Message ID:** 22916

**Message Description:** LOG\_ID\_FDS\_STATUS

**Message Meaning:** FortiGuard Message Service status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22917 - LOG\_ID\_FDS\_SMS\_QUOTA

**Message ID:** 22917

**Message Description:** LOG\_ID\_FDS\_SMS\_QUOTA

**Message Meaning:** SMS quota reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22918 - LOG\_ID\_FDS\_CTRL\_STATUS

**Message ID:** 22918

**Message Description:** LOG\_ID\_FDS\_CTRL\_STATUS

**Message Meaning:** FortiGuard Message Service controller status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22921 - LOG\_ID\_EVENT\_ROUTE\_INFO\_CHANGED

**Message ID:** 22921

**Message Description:** LOG\_ID\_EVENT\_ROUTE\_INFO\_CHANGED

**Message Meaning:** Routing information changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22922 - LOG\_ID\_EVENT\_LINK\_MONITOR\_STATUS

**Message ID:** 22922

**Message Description:** LOG\_ID\_EVENT\_LINK\_MONITOR\_STATUS

**Message Meaning:** Link monitor status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128

Log Field Name	Description	Data Type	Length
probeprotocol	Link Monitor Probe Protocol	string	16
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22923 - LOG\_ID\_EVENT\_VWL\_LQTY\_STATUS

**Message ID:** 22923

**Message Description:** LOG\_ID\_EVENT\_VWL\_LQTY\_STATUS

**Message Meaning:** Virtual WAN Link status

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22924 - LOG\_ID\_EVENT\_VWL\_VOLUME\_STATUS

**Message ID:** 22924

**Message Description:** LOG\_ID\_EVENT\_VWL\_VOLUME\_STATUS

**Message Meaning:** Virtual WAN Link volume status



**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 22949 - LOG\_ID\_FDS\_JOIN

**Message ID:** 22949

**Message Description:** LOG\_ID\_FDS\_JOIN

**Message Meaning:** FortiCloud auto-join attempted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22950 - LOG\_ID\_FDS\_LOGIN\_SUCC

**Message ID:** 22950

**Message Description:** LOG\_ID\_FDS\_LOGIN\_SUCC

**Message Meaning:** FortiCloud activation successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22951 - LOG\_ID\_FDS\_LOGOUT

**Message ID:** 22951

**Message Description:** LOG\_ID\_FDS\_LOGOUT

**Message Meaning:** FortiCloud logout

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22952 - LOG\_ID\_FDS\_LOGIN\_FAIL

**Message ID:** 22952

**Message Description:** LOG\_ID\_FDS\_LOGIN\_FAIL

**Message Meaning:** FortiCloud activation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 22953 - LOG\_ID\_IOC\_DETECTED

**Message ID:** 22953

**Message Description:** LOG\_ID\_IOC\_DETECTED

**Message Meaning:** Compromised host detected

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 23101 - LOG\_ID\_IPSEC\_TUNNEL\_UP

**Message ID:** 23101

**Message Description:** LOG\_ID\_IPSEC\_TUNNEL\_UP

**Message Meaning:** IPsec VPN tunnel up

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 23102 - LOG\_ID\_IPSEC\_TUNNEL\_DOWN

**Message ID:** 23102

**Message Description:** LOG\_ID\_IPSEC\_TUNNEL\_DOWN

**Message Meaning:** IPsec VPN tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 23103 - LOG\_ID\_IPSEC\_TUNNEL\_STAT

**Message ID:** 23103

**Message Description:** LOG\_ID\_IPSEC\_TUNNEL\_STAT

**Message Meaning:** IPsec VPN tunnel statistics

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 26001 - LOG\_ID\_DHCP\_ACK

**Message ID:** 26001

**Message Description:** LOG\_ID\_DHCP\_ACK

**Message Meaning:** DHCP Ack log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
hostname	Hostname	string	128

Log Field Name	Description	Data Type	Length
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26002 - LOG\_ID\_DHCP\_RELEASE

**Message ID:** 26002

**Message Description:** LOG\_ID\_DHCP\_RELEASE

**Message Meaning:** DHCP Release log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
hostname	Hostname	string	128
interface	Interface	string	32
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	



Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26003 - LOG\_ID\_DHCP\_STAT

**Message ID:** 26003

**Message Description:** LOG\_ID\_DHCP\_STAT

**Message Meaning:** DHCP statistics

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

## 26004 - LOG\_ID\_DHCP\_CLIENT\_LEASE

**Message ID:** 26004

**Message Description:** LOG\_ID\_DHCP\_CLIENT\_LEASE

**Message Meaning:** DHCP client lease granted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26005 - LOG\_ID\_DHCP\_LEASE\_USAGE\_HIGH

**Message ID:** 26005

**Message Description:** LOG\_ID\_DHCP\_LEASE\_USAGE\_HIGH

**Message Meaning:** DHCP lease usage high

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26006 - LOG\_ID\_DHCP\_LEASE\_USAGE\_FULL

**Message ID:** 26006

**Message Description:** LOG\_ID\_DHCP\_LEASE\_USAGE\_FULL

**Message Meaning:** DHCP lease usage full

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26007 - LOG\_ID\_DHCP\_BLOCKED\_MAC

**Message ID:** 26007

**Message Description:** LOG\_ID\_DHCP\_BLOCKED\_MAC

**Message Meaning:** DHCP client blocked log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26008 - LOG\_ID\_DHCP\_DDNS\_ADD

**Message ID:** 26008

**Message Description:** LOG\_ID\_DHCP\_DDNS\_ADD

**Message Meaning:** DHCP DDNS add query

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26009 - LOG\_ID\_DHCP\_DDNS\_DELETE

**Message ID:** 26009

**Message Description:** LOG\_ID\_DHCP\_DDNS\_DELETE

**Message Meaning:** DHCP DDNS delete query

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
fqdn		string	256
ip		ip	39

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26010 - LOG\_ID\_DHCP\_DDNS\_COMPLETED

**Message ID:** 26010

**Message Description:** LOG\_ID\_DHCP\_DDNS\_COMPLETED

**Message Meaning:** DHCP DDNS query completed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
fqn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26011 - LOG\_ID\_DHCPV6\_REPLY

**Message ID:** 26011

**Message Description:** LOG\_ID\_DHCPV6\_REPLY

**Message Meaning:** DHCPv6 Ack log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
duid		string	128
eventtime		uint64	20
iaid		uint32	10
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 26012 - LOG\_ID\_DHCPV6\_RELEASE

**Message ID:** 26012

**Message Description:** LOG\_ID\_DHCPV6\_RELEASE

**Message Meaning:** DHCPv6 Release log

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
duid		string	128
eventtime		uint64	20
iaid		uint32	10
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 27001 - LOG\_ID\_VRRP\_STATE\_CHG

**Message ID:** 27001

**Message Description:** LOG\_ID\_VRRP\_STATE\_CHG

**Message Meaning:** VRRP state changed

**Type:** Event

**Category:** ROUTER

**Severity:** Information



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29001 - LOG\_ID\_PPPD\_MSG

**Message ID:** 29001

**Message Description:** LOG\_ID\_PPPD\_MSG

**Message Meaning:** PPP status

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
remote	Remote IP Address	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 29002 - LOG\_ID\_PPPD\_AUTH\_SUC

**Message ID:** 29002

**Message Description:** LOG\_ID\_PPPD\_AUTH\_SUC

**Message Meaning:** PPP authentication successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
remote	Remote IP Address	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 29003 - LOG\_ID\_PPPD\_AUTH\_FAIL

**Message ID:** 29003

**Message Description:** LOG\_ID\_PPPD\_AUTH\_FAIL

**Message Meaning:** PPP authentication failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
remote	Remote IP Address	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29010 - LOG\_ID\_PPPOE\_STATUS\_REPORT\_NOTIF

**Message ID:** 29010

**Message Description:** LOG\_ID\_PPPOE\_STATUS\_REPORT\_NOTIF

**Message Meaning:** PPPoE status report

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
gateway	gateway ip address for PPPoE status report	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
mtu	Max Transmission Unit Value	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29011 - LOG\_ID\_PPPD\_FAIL\_TO\_EXEC

**Message ID:** 29011

**Message Description:** LOG\_ID\_PPPD\_FAIL\_TO\_EXEC

**Message Meaning:** PPP execution failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29012 - LOG\_ID\_PPP\_OPT\_ERR

**Message ID:** 29012

**Message Description:** LOG\_ID\_PPP\_OPT\_ERR

**Message Meaning:** PPP received incorrect options

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29013 - LOG\_ID\_PPPD\_START

**Message ID:** 29013

**Message Description:** LOG\_ID\_PPPD\_START

**Message Meaning:** PPP daemon started

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29014 - LOG\_ID\_PPPD\_EXIT

**Message ID:** 29014

**Message Description:** LOG\_ID\_PPPD\_EXIT

**Message Meaning:** PPP daemon exited

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29015 - LOG\_ID\_PPP\_RCV\_BAD\_PEER\_IP

**Message ID:** 29015

**Message Description:** LOG\_ID\_PPP\_RCV\_BAD\_PEER\_IP

**Message Meaning:** PPP received invalid peer IP

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29016 - LOG\_ID\_PPP\_RCV\_BAD\_LOCAL\_IP

**Message ID:** 29016

**Message Description:** LOG\_ID\_PPP\_RCV\_BAD\_LOCAL\_IP

**Message Meaning:** PPP received invalid local IP

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 29017 - LOG\_ID\_PPP\_OPT\_NOTIF

**Message ID:** 29017

**Message Description:** LOG\_ID\_PPP\_OPT\_NOTIF

**Message Meaning:** PPP received incorrect notifications

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32



## 29021 - LOG\_ID\_EVENT\_AUTH\_SNMP\_QUERY\_FAILED

**Message ID:** 29021

**Message Description:** LOG\_ID\_EVENT\_AUTH\_SNMP\_QUERY\_FAILED

**Message Meaning:** SNMP query failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
community	Community	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version	Version	string	64

## 29022 - LOG\_ID\_DDNS\_UPDATE\_FAIL

**Message ID:** 29022

**Message Description:** LOG\_ID\_DDNS\_UPDATE\_FAIL

**Message Meaning:** DDNS update failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32001 - LOG\_ID\_ADMIN\_LOGIN\_SUCC

**Message ID:** 32001

**Message Description:** LOG\_ID\_ADMIN\_LOGIN\_SUCC

**Message Meaning:** Admin login successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial number for login or logout events. Used to correlate login and logout events.	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32002 - LOG\_ID\_ADMIN\_LOGIN\_FAIL

**Message ID:** 32002

**Message Description:** LOG\_ID\_ADMIN\_LOGIN\_FAIL

**Message Meaning:** Admin login failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
reason	Reason	string	256
sn	Serial number for login or logout events. Used to correlate login and logout events.	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32003 - LOG\_ID\_ADMIN\_LOGOUT

**Message ID:** 32003

**Message Description:** LOG\_ID\_ADMIN\_LOGOUT

**Message Meaning:** Admin logout successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
reason	Reason	string	256
sn	Serial number for login or logout events. Used to correlate login and logout events.	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32005 - LOG\_ID\_ADMIN\_OVERRIDE\_VDOM

**Message ID:** 32005

**Message Description:** LOG\_ID\_ADMIN\_OVERRIDE\_VDOM

**Message Meaning:** Admin overrode VDOM

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32006 - LOG\_ID\_ADMIN\_ENTER\_VDOM

**Message ID:** 32006

**Message Description:** LOG\_ID\_ADMIN\_ENTER\_VDOM

**Message Meaning:** Super admin entered VDOM

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

---

## 32007 - LOG\_ID\_ADMIN\_LEFT\_VDOM

**Message ID:** 32007

**Message Description:** LOG\_ID\_ADMIN\_LEFT\_VDOM

**Message Meaning:** Super admin left VDOM

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32008 - LOG\_ID\_VIEW\_DISK\_LOG\_FAIL

**Message ID:** 32008

**Message Description:** LOG\_ID\_VIEW\_DISK\_LOG\_FAIL

**Message Meaning:** Disk log access failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32009 - LOG\_ID\_SYSTEM\_START

**Message ID:** 32009

**Message Description:** LOG\_ID\_SYSTEM\_START

**Message Meaning:** FortiGate started

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32010 - LOG\_ID\_DISK\_LOG\_FULL

**Message ID:** 32010

**Message Description:** LOG\_ID\_DISK\_LOG\_FULL

**Message Meaning:** Disk full

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32011 - LOG\_ID\_LOG\_ROLL

**Message ID:** 32011

**Message Description:** LOG\_ID\_LOG\_ROLL

**Message Meaning:** Disk log rolled

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32014 - LOG\_ID\_CS\_LIC\_EXPIRE

**Message ID:** 32014

**Message Description:** LOG\_ID\_CS\_LIC\_EXPIRE

**Message Meaning:** Support license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32015 - LOG\_ID\_DISK\_LOG\_USAGE

**Message ID:** 32015

**Message Description:** LOG\_ID\_DISK\_LOG\_USAGE

**Message Meaning:** Log disk full

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32016 - LOG\_ID\_FDS\_QUOTA\_WARN

**Message ID:** 32016

**Message Description:** LOG\_ID\_FDS\_QUOTA\_WARN

**Message Meaning:** FortiCloud quota full third warning

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32017 - LOG\_ID\_FDS\_DAILY\_QUOTA\_FULL

**Message ID:** 32017

**Message Description:** LOG\_ID\_FDS\_DAILY\_QUOTA\_FULL

**Message Meaning:** FortiCloud daily quota full

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32018 - LOG\_ID\_FIPS\_ENTER\_ERR\_MOD

**Message ID:** 32018

**Message Description:** LOG\_ID\_FIPS\_ENTER\_ERR\_MOD

**Message Meaning:** FIPS CC entered error mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32019 - LOG\_ID\_CC\_ENTER\_ERR\_MOD

**Message ID:** 32019

**Message Description:** LOG\_ID\_CC\_ENTER\_ERR\_MOD

**Message Meaning:** CC entered error mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32020 - LOG\_ID\_SSH\_CORRPUT\_MAC

**Message ID:** 32020

**Message Description:** LOG\_ID\_SSH\_CORRPUT\_MAC

**Message Meaning:** Message Authentication Code corrupted

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 32021 - LOG\_ID\_ADMIN\_LOGIN\_DISABLE

**Message ID:** 32021

**Message Description:** LOG\_ID\_ADMIN\_LOGIN\_DISABLE

**Message Meaning:** Admin login disabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32022 - LOG\_ID\_VDOM\_ENABLED

**Message ID:** 32022

**Message Description:** LOG\_ID\_VDOM\_ENABLED

**Message Meaning:** VDOM enabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32023 - LOG\_ID\_MEM\_LOG\_FIRST\_FULL

**Message ID:** 32023

**Message Description:** LOG\_ID\_MEM\_LOG\_FIRST\_FULL

**Message Meaning:** Memory log full over first warning level

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10



Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32024 - LOG\_ID\_ADMIN\_PASSWD\_EXPIRE

**Message ID:** 32024

**Message Description:** LOG\_ID\_ADMIN\_PASSWD\_EXPIRE

**Message Meaning:** Admin password expired

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32025 - LOG\_ID\_SSH\_REKEY

**Message ID:** 32025

**Message Description:** LOG\_ID\_SSH\_REKEY

**Message Meaning:** SSH server re-key

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 32026 - LOG\_ID\_SSH\_BAD\_PACKET\_LENGTH

**Message ID:** 32026

**Message Description:** LOG\_ID\_SSH\_BAD\_PACKET\_LENGTH

**Message Meaning:** SSH server received bad length packet

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 32027 - LOG\_ID\_VIEW\_DISK\_LOG\_SUCC

**Message ID:** 32027

**Message Description:** LOG\_ID\_VIEW\_DISK\_LOG\_SUCC

**Message Meaning:** Disk logs viewed successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32028 - LOG\_ID\_LOG\_DEL\_DIR

**Message ID:** 32028

**Message Description:** LOG\_ID\_LOG\_DEL\_DIR

**Message Meaning:** Disk log directory deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32029 - LOG\_ID\_LOG\_DEL\_FILE

**Message ID:** 32029

**Message Description:** LOG\_ID\_LOG\_DEL\_FILE

**Message Meaning:** Disk log file deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
filesize	Report File Size in Bytes	uint32	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32030 - LOG\_ID\_SEND\_FDS\_STAT

**Message ID:** 32030

**Message Description:** LOG\_ID\_SEND\_FDS\_STAT

**Message Meaning:** FDS statistics sent

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32031 - LOG\_ID\_VIEW\_MEM\_LOG\_FAIL

**Message ID:** 32031

**Message Description:** LOG\_ID\_VIEW\_MEM\_LOG\_FAIL

**Message Meaning:** Memory log access failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32032 - LOG\_ID\_DISK\_DLP\_ARCH\_FULL

**Message ID:** 32032

**Message Description:** LOG\_ID\_DISK\_DLP\_ARCH\_FULL

**Message Meaning:** DLP archive full

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32033 - LOG\_ID\_DISK\_QUAR\_FULL

**Message ID:** 32033

**Message Description:** LOG\_ID\_DISK\_QUAR\_FULL

**Message Meaning:** Quarantine full

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32034 - LOG\_ID\_DISK\_REPORT\_FULL

**Message ID:** 32034

**Message Description:** LOG\_ID\_DISK\_REPORT\_FULL

**Message Meaning:** Report full

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32035 - LOG\_ID\_VDOM\_DISABLED

**Message ID:** 32035



**Message Description:** LOG\_ID\_VDOM\_DISABLED

**Message Meaning:** VDOM disabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32036 - LOG\_ID\_DISK\_IPS\_ARCH\_FULL

**Message ID:** 32036

**Message Description:** LOG\_ID\_DISK\_IPS\_ARCH\_FULL

**Message Meaning:** IPS archive full

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32037 - LOG\_ID\_DISK\_LOG\_FIRST\_FULL

**Message ID:** 32037

**Message Description:** LOG\_ID\_DISK\_LOG\_FIRST\_FULL

**Message Meaning:** Disk log full over first warning

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32038 - LOG\_ID\_LOG\_ROLL\_FORTICRON

**Message ID:** 32038

**Message Description:** LOG\_ID\_LOG\_ROLL\_FORTICRON

**Message Meaning:** Log rotation requested by FortiCron

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32039 - LOG\_ID\_VIEW\_MEM\_LOG\_SUCC

**Message ID:** 32039

**Message Description:** LOG\_ID\_VIEW\_MEM\_LOG\_SUCC

**Message Meaning:** Memory logs viewed successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32040 - LOG\_ID\_REPORT\_DELETED

**Message ID:** 32040

**Message Description:** LOG\_ID\_REPORT\_DELETED

**Message Meaning:** Report deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32041 - LOG\_ID\_REPORT\_DELETED\_GUI

**Message ID:** 32041

**Message Description:** LOG\_ID\_REPORT\_DELETED\_GUI

**Message Meaning:** Report deleted from GUI

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32042 - LOG\_ID\_MEM\_LOG\_SECOND\_FULL

**Message ID:** 32042

**Message Description:** LOG\_ID\_MEM\_LOG\_SECOND\_FULL

**Message Meaning:** Memory log full over second warning level

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32043 - LOG\_ID\_MEM\_LOG\_FINAL\_FULL

**Message ID:** 32043

**Message Description:** LOG\_ID\_MEM\_LOG\_FINAL\_FULL

**Message Meaning:** Memory log full over final warning level

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32044 - LOG\_ID\_LOG\_DELETE

**Message ID:** 32044

**Message Description:** LOG\_ID\_LOG\_DELETE

**Message Meaning:** Log deleted by user

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32045 - LOG\_ID\_MGR\_LIC\_EXPIRE

**Message ID:** 32045

**Message Description:** LOG\_ID\_MGR\_LIC\_EXPIRE

**Message Meaning:** FortiGuard management service license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32046 - LOG\_ID\_SSL\_CORRPUT\_MAC

**Message ID:** 32046

**Message Description:** LOG\_ID\_SSL\_CORRPUT\_MAC

**Message Meaning:** SSL Message Authentication Code corrupted

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	



Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 32048 - LOG\_ID\_SCHEDULE\_EXPIRE

**Message ID:** 32048

**Message Description:** LOG\_ID\_SCHEDULE\_EXPIRE

**Message Meaning:** One time schedule expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32049 - LOG\_ID\_FC\_EXPIRE

**Message ID:** 32049

**Message Description:** LOG\_ID\_FC\_EXPIRE

**Message Meaning:** FortiCloud license expiring

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32050 - LOG\_ID\_POL\_PKT\_CAPTURE\_FULL

**Message ID:** 32050

**Message Description:** LOG\_ID\_POL\_PKT\_CAPTURE\_FULL

**Message Meaning:** Policy packet capture full

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32051 - LOG\_ID\_LOG\_UPLOAD

**Message ID:** 32051

**Message Description:** LOG\_ID\_LOG\_UPLOAD

**Message Meaning:** Disk logs upload started

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

## 32052 - LOG\_ID\_UPLOAD\_RUN\_SCRIPT

**Message ID:** 32052

**Message Description:** LOG\_ID\_UPLOAD\_RUN\_SCRIPT

**Message Meaning:** Upload and run a script

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32053 - LOG\_ID\_ADMIN\_MTNER\_LOGIN\_SUCC

**Message ID:** 32053

**Message Description:** LOG\_ID\_ADMIN\_MTNER\_LOGIN\_SUCC

**Message Meaning:** Admin monitor login successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32054 - LOG\_ID\_ADMIN\_MTNER\_LOGOUT

**Message ID:** 32054

**Message Description:** LOG\_ID\_ADMIN\_MTNER\_LOGOUT

**Message Meaning:** Admin monitor logout successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32055 - LOG\_ID\_FDS\_QUOTA\_WARN\_WARNING

**Message ID:** 32055

**Message Description:** LOG\_ID\_FDS\_QUOTA\_WARN\_WARNING

**Message Meaning:** FortiCloud quota full second warning

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32056 - LOG\_ID\_FDS\_QUOTA\_WARN\_INFO

**Message ID:** 32056

**Message Description:** LOG\_ID\_FDS\_QUOTA\_WARN\_INFO

**Message Meaning:** FortiCloud quota full first warning

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32057 - LOG\_ID\_VIEW\_FAZ\_LOG\_FAIL

**Message ID:** 32057

**Message Description:** LOG\_ID\_VIEW\_FAZ\_LOG\_FAIL

**Message Meaning:** FortiAnalyzer log access failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32058 - LOG\_ID\_VIEW\_FAZ\_LOG\_SUCC

**Message ID:** 32058

**Message Description:** LOG\_ID\_VIEW\_FAZ\_LOG\_SUCC

**Message Meaning:** FortiAnalyzer logs viewed successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	



Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32095 - LOG\_ID\_GUI\_CHG\_SUB\_MODULE

**Message ID:** 32095

**Message Description:** LOG\_ID\_GUI\_CHG\_SUB\_MODULE

**Message Meaning:** Admin performed an action from GUI

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32097 - LOG\_ID\_DELETE\_CAPTURE\_PKT

**Message ID:** 32097

**Message Description:** LOG\_ID\_DELETE\_CAPTURE\_PKT

**Message Meaning:** Policy packet capture file deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32100 - LOG\_ID\_FORTI\_TOKEN\_SYNC

**Message ID:** 32100

**Message Description:** LOG\_ID\_FORTI\_TOKEN\_SYNC

**Message Meaning:** FortiToken synchronized

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32102 - LOG\_ID\_CHG\_CONFIG

**Message ID:** 32102

**Message Description:** LOG\_ID\_CHG\_CONFIG

**Message Meaning:** Configuration changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert, Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Configuration Module Name	string	32
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
submodule	Configuration Sub-Module Name	string	32
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32103 - LOG\_ID\_NEW\_FIRMWARE

**Message ID:** 32103

**Message Description:** LOG\_ID\_NEW\_FIRMWARE

**Message Meaning:** New firmware available on FortiGuard

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32104 - LOG\_ID\_CHG\_CONFIG\_GUI

**Message ID:** 32104

**Message Description:** LOG\_ID\_CHG\_CONFIG\_GUI

**Message Meaning:** Configuration changed via GUI

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Configuration Module Name	string	32
msg	Message Text	string	
submodule	Configuration Sub-Module Name	string	32
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32105 - LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_REACHABLE

**Message ID:** 32105

**Message Description:** LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_REACHABLE

**Message Meaning:** NTP server status changes to reachable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32106 - LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_RESOLVABLE

**Message ID:** 32106

**Message Description:** LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_RESOLVABLE

**Message Meaning:** NTP server status changes to resolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32107 - LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_UNRESOLVABLE

**Message ID:** 32107

**Message Description:** LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_UNRESOLVABLE

**Message Meaning:** NTP server status changes to unresolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32108 - LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_UNREACHABLE

**Message ID:** 32108

**Message Description:** LOG\_ID\_NTP\_SVR\_STAUS\_CHG\_UNREACHABLE

**Message Meaning:** NTP server status changes to unreachable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32109 - LOG\_ID\_UPD\_SIGN\_AV\_DB

**Message ID:** 32109

**Message Description:** LOG\_ID\_UPD\_SIGN\_AV\_DB

**Message Meaning:** Updating virus database

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical



Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32110 - LOG\_ID\_UPD\_SIGN\_IPS\_DB

**Message ID:** 32110

**Message Description:** LOG\_ID\_UPD\_SIGN\_IPS\_DB

**Message Meaning:** IPS database updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32111 - LOG\_ID\_UPD\_SIGN\_AVIPS\_DB

**Message ID:** 32111

**Message Description:** LOG\_ID\_UPD\_SIGN\_AVIPS\_DB

**Message Meaning:** Virus and IPS database updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32113 - LOG\_ID\_UPD\_SIGN\_SRCVIS\_DB

**Message ID:** 32113

**Message Description:** LOG\_ID\_UPD\_SIGN\_SRCVIS\_DB

**Message Meaning:** SRC-VIS object updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32114 - LOG\_ID\_UPD\_SIGN\_GEOIP\_DB

**Message ID:** 32114

**Message Description:** LOG\_ID\_UPD\_SIGN\_GEOIP\_DB

**Message Meaning:** GeoIP object updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32116 - LOG\_ID\_UPD\_SIGN\_AVPKG\_FAILURE

**Message ID:** 32116

**Message Description:** LOG\_ID\_UPD\_SIGN\_AVPKG\_FAILURE

**Message Meaning:** AV package update by SCP failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32117 - LOG\_ID\_UPD\_SIGN\_AVPKG\_SUCCESS

**Message ID:** 32117

**Message Description:** LOG\_ID\_UPD\_SIGN\_AVPKG\_SUCCESS

**Message Meaning:** AV package update by SCP successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32118 - LOG\_ID\_UPD\_ADMIN\_AV\_DB

**Message ID:** 32118

**Message Description:** LOG\_ID\_UPD\_ADMIN\_AV\_DB

**Message Meaning:** AV updated by admin

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32119 - LOG\_ID\_UPD\_SCANUNIT\_AV\_DB

**Message ID:** 32119

**Message Description:** LOG\_ID\_UPD\_SCANUNIT\_AV\_DB

**Message Meaning:** AV database updated by scanunit

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32120 - LOG\_ID\_RPT\_ADD\_DATASET

**Message ID:** 32120

**Message Description:** LOG\_ID\_RPT\_ADD\_DATASET

**Message Meaning:** Report data set added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32122 - LOG\_ID\_RPT\_DEL\_DATASET

**Message ID:** 32122

**Message Description:** LOG\_ID\_RPT\_DEL\_DATASET

**Message Meaning:** Report data set deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32125 - LOG\_ID\_RPT\_ADD\_CHART

**Message ID:** 32125



**Message Description:** LOG\_ID\_RPT\_ADD\_CHART

**Message Meaning:** Report chart widget added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32126 - LOG\_ID\_RPT\_DEL\_CHART

**Message ID:** 32126

**Message Description:** LOG\_ID\_RPT\_DEL\_CHART

**Message Meaning:** Report chart widget deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32129 - LOG\_ID\_ADD\_GUEST

**Message ID:** 32129

**Message Description:** LOG\_ID\_ADD\_GUEST

**Message Meaning:** Guest user added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32130 - LOG\_ID\_CHG\_USER

**Message ID:** 32130

**Message Description:** LOG\_ID\_CHG\_USER

**Message Meaning:** User changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
new_status	New Status	string	512
old_status	Original Status	string	512
passwd	Password	string	20
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32131 - LOG\_ID\_DEL\_GUEST

**Message ID:** 32131

**Message Description:** LOG\_ID\_DEL\_GUEST

**Message Meaning:** Guest user deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32132 - LOG\_ID\_ADD\_USER

**Message ID:** 32132

**Message Description:** LOG\_ID\_ADD\_USER

**Message Meaning:** Local user added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32138 - LOG\_ID\_REBOOT

**Message ID:** 32138

**Message Description:** LOG\_ID\_REBOOT

**Message Meaning:** Device rebooted

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32140 - LOG\_ID\_TIME\_USER\_SETTING\_CHG

**Message ID:** 32140

**Message Description:** LOG\_ID\_TIME\_USER\_SETTING\_CHG

**Message Meaning:** Global time setting changed by user

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32141 - LOG\_ID\_TIME\_NTP\_SETTING\_CHG

**Message ID:** 32141

**Message Description:** LOG\_ID\_TIME\_NTP\_SETTING\_CHG

**Message Meaning:** Global time setting changed by NTP

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32142 - LOG\_ID\_BACKUP\_CONF

**Message ID:** 32142

**Message Description:** LOG\_ID\_BACKUP\_CONF

**Message Meaning:** System configuration backed up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32143 - LOG\_ID\_BACKUP\_CONF\_BY\_SCP

**Message ID:** 32143

**Message Description:** LOG\_ID\_BACKUP\_CONF\_BY\_SCP

**Message Meaning:** System configuration backed up by SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning



Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32144 - LOG\_ID\_BACKUP\_CONF\_ERROR

**Message ID:** 32144

**Message Description:** LOG\_ID\_BACKUP\_CONF\_ERROR

**Message Meaning:** System configuration backed up error

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32145 - LOG\_ID\_BACKUP\_CONF\_ALERT

**Message ID:** 32145

**Message Description:** LOG\_ID\_BACKUP\_CONF\_ALERT

**Message Meaning:** System configuration backed up alert

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

---

## 32148 - LOG\_ID\_GET\_CRL

**Message ID:** 32148

**Message Description:** LOG\_ID\_GET\_CRL

**Message Meaning:** CRL update requested

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
crl		string	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32149 - LOG\_ID\_COMMAND\_FAIL

**Message ID:** 32149

**Message Description:** LOG\_ID\_COMMAND\_FAIL

**Message Meaning:** Command failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32151 - LOG\_ID\_ADD\_IP6\_LOCAL\_POL

**Message ID:** 32151

**Message Description:** LOG\_ID\_ADD\_IP6\_LOCAL\_POL

**Message Meaning:** IPv6 firewall local in policy added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32152 - LOG\_ID\_CHG\_IP6\_LOCAL\_POL

**Message ID:** 32152

**Message Description:** LOG\_ID\_CHG\_IP6\_LOCAL\_POL

**Message Meaning:** IPv6 firewall local in policy setting changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32153 - LOG\_ID\_DEL\_IP6\_LOCAL\_POL

**Message ID:** 32153

**Message Description:** LOG\_ID\_DEL\_IP6\_LOCAL\_POL

**Message Meaning:** IPv6 firewall local in policy deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32155 - LOG\_ID\_ACT\_FTOKEN\_REQ

**Message ID:** 32155

**Message Description:** LOG\_ID\_ACT\_FTOKEN\_REQ

**Message Meaning:** FortiToken activation requested

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32156 - LOG\_ID\_ACT\_FTOKEN\_SUCC

**Message ID:** 32156

**Message Description:** LOG\_ID\_ACT\_FTOKEN\_SUCC

**Message Meaning:** FortiToken activation successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32157 - LOG\_ID\_SYNC\_FTOKEN\_SUCC

**Message ID:** 32157

**Message Description:** LOG\_ID\_SYNC\_FTOKEN\_SUCC

**Message Meaning:** FortiToken re-synchronized

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16



Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32158 - LOG\_ID\_SYNC\_FTOKEN\_FAIL

**Message ID:** 32158

**Message Description:** LOG\_ID\_SYNC\_FTOKEN\_FAIL

**Message Meaning:** FortiToken re-synchronization failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32159 - LOG\_ID\_ACT\_FTOKEN\_FAIL

**Message ID:** 32159

**Message Description:** LOG\_ID\_ACT\_FTOKEN\_FAIL

**Message Meaning:** FortiToken activation failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32160 - LOG\_ID\_FTM\_PUSH\_SUCC

**Message ID:** 32160

**Message Description:** LOG\_ID\_FTM\_PUSH\_SUCC

**Message Meaning:** FortiToken mobile push message succeeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32161 - LOG\_ID\_FTM\_PUSH\_FAIL

**Message ID:** 32161

**Message Description:** LOG\_ID\_FTM\_PUSH\_FAIL

**Message Meaning:** FortiToken mobile push message failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32168 - LOG\_ID\_REACH\_VDOM\_LIMIT

**Message ID:** 32168

**Message Description:** LOG\_ID\_REACH\_VDOM\_LIMIT

**Message Meaning:** VDOM limit reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32169 - LOG\_ID\_ALARM\_DLP\_DB

**Message ID:** 32169

**Message Description:** LOG\_ID\_ALARM\_DLP\_DB

**Message Meaning:** DLP database space alarm

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32170 - LOG\_ID\_ALARM\_MSG

**Message ID:** 32170

**Message Description:** LOG\_ID\_ALARM\_MSG

**Message Meaning:** Alarm created

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
alarmid	Alarm ID	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
groupid	User Group ID	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32171 - LOG\_ID\_ALARM\_ACK

**Message ID:** 32171

**Message Description:** LOG\_ID\_ALARM\_ACK

**Message Meaning:** Alarm acknowledged

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
acktime	Alarm Acknowledge Time	string	24
action	Action	string	32
alarmid	Alarm ID	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32172 - LOG\_ID\_ADD\_IP4\_LOCAL\_POL

**Message ID:** 32172

**Message Description:** LOG\_ID\_ADD\_IP4\_LOCAL\_POL

**Message Meaning:** IPv4 firewall local in policy added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32173 - LOG\_ID\_CHG\_IP4\_LOCAL\_POL

**Message ID:** 32173

**Message Description:** LOG\_ID\_CHG\_IP4\_LOCAL\_POL

**Message Meaning:** IPv4 firewall local in policy's setting changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32174 - LOG\_ID\_DEL\_IP4\_LOCAL\_POL

**Message ID:** 32174

**Message Description:** LOG\_ID\_DEL\_IP4\_LOCAL\_POL

**Message Meaning:** IPv4 firewall local in policy deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16



Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32190 - LOG\_ID\_UPT\_INVALID\_IMG

**Message ID:** 32190

**Message Description:** LOG\_ID\_UPT\_INVALID\_IMG

**Message Meaning:** Invalid image loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32191 - LOG\_ID\_UPT\_INVALID\_IMG\_CC

**Message ID:** 32191

**Message Description:** LOG\_ID\_UPT\_INVALID\_IMG\_CC

**Message Meaning:** Image with invalid CC signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32192 - LOG\_ID\_UPT\_INVALID\_IMG\_RSA

**Message ID:** 32192

**Message Description:** LOG\_ID\_UPT\_INVALID\_IMG\_RSA

**Message Meaning:** Image with invalid RSA signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32193 - LOG\_ID\_UPT\_IMG\_RSA

**Message ID:** 32193

**Message Description:** LOG\_ID\_UPT\_IMG\_RSA

**Message Meaning:** Image with valid RSA signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32194 - LOG\_ID\_UPT\_IMG\_FAIL

**Message ID:** 32194

**Message Description:** LOG\_ID\_UPT\_IMG\_FAIL

**Message Meaning:** System upgrade failed due to file operation failure

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

---

## 32199 - LOG\_ID\_RESTORE\_IMG\_USB

**Message ID:** 32199

**Message Description:** LOG\_ID\_RESTORE\_IMG\_USB

**Message Meaning:** Image restored from USB

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32200 - LOG\_ID\_SHUTDOWN

**Message ID:** 32200

**Message Description:** LOG\_ID\_SHUTDOWN

**Message Meaning:** Device shutdown

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32201 - LOG\_ID\_LOAD\_IMG\_SUCC

**Message ID:** 32201

**Message Description:** LOG\_ID\_LOAD\_IMG\_SUCC

**Message Meaning:** Image loaded successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32202 - LOG\_ID\_RESTORE\_IMG

**Message ID:** 32202

**Message Description:** LOG\_ID\_RESTORE\_IMG

**Message Meaning:** Image restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32203 - LOG\_ID\_RESTORE\_CONF

**Message ID:** 32203

**Message Description:** LOG\_ID\_RESTORE\_CONF

**Message Meaning:** Configuration restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32204 - LOG\_ID\_RESTORE\_FGD\_SVR

**Message ID:** 32204

**Message Description:** LOG\_ID\_RESTORE\_FGD\_SVR

**Message Meaning:** FortiGuard service restored

**Type:** Event



**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32205 - LOG\_ID\_RESTORE\_VDOM\_LIC

**Message ID:** 32205

**Message Description:** LOG\_ID\_RESTORE\_VDOM\_LIC

**Message Meaning:** VM license restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32206 - LOG\_ID\_RESTORE\_SCRIPT

**Message ID:** 32206

**Message Description:** LOG\_ID\_RESTORE\_SCRIPT

**Message Meaning:** Script restored from management station

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning, Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32207 - LOG\_ID\_RETRIEVE\_CONF\_LIST

**Message ID:** 32207

**Message Description:** LOG\_ID\_RETRIEVE\_CONF\_LIST

**Message Meaning:** Configuration list retrieval failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32208 - LOG\_ID\_IMP\_PKCS12\_CERT

**Message ID:** 32208

**Message Description:** LOG\_ID\_IMP\_PKCS12\_CERT

**Message Meaning:** PKCS12 certificate imported

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32209 - LOG\_ID\_RESTORE\_USR\_DEF\_IPS

**Message ID:** 32209

**Message Description:** LOG\_ID\_RESTORE\_USR\_DEF\_IPS

**Message Meaning:** IPS custom signatures restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32210 - LOG\_ID\_BACKUP\_IMG\_SUCC

**Message ID:** 32210

**Message Description:** LOG\_ID\_BACKUP\_IMG\_SUCC

**Message Meaning:** Firmware image backed up successfully

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32211 - LOG\_ID\_UPLOAD\_REVISION

**Message ID:** 32211

**Message Description:** LOG\_ID\_UPLOAD\_REVISION

**Message Meaning:** Revision uploaded to flash disk

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32212 - LOG\_ID\_DEL\_REVISION

**Message ID:** 32212

**Message Description:** LOG\_ID\_DEL\_REVISION

**Message Meaning:** Revision deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32213 - LOG\_ID\_RESTORE\_TEMPLATE

**Message ID:** 32213

**Message Description:** LOG\_ID\_RESTORE\_TEMPLATE

**Message Meaning:** Template restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32214 - LOG\_ID\_RESTORE\_FILE

**Message ID:** 32214

**Message Description:** LOG\_ID\_RESTORE\_FILE

**Message Meaning:** File restore failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16



Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32215 - LOG\_ID\_UPT\_IMG

**Message ID:** 32215

**Message Description:** LOG\_ID\_UPT\_IMG

**Message Meaning:** Image updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32217 - LOG\_ID\_UPD\_IPS

**Message ID:** 32217

**Message Description:** LOG\_ID\_UPD\_IPS

**Message Meaning:** IPS package - Admin update successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32218 - LOG\_ID\_UPD\_DLP

**Message ID:** 32218

**Message Description:** LOG\_ID\_UPD\_DLP

**Message Meaning:** DLP fingerprint database update via SCP failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32219 - LOG\_ID\_BACKUP\_OUTPUT

**Message ID:** 32219

**Message Description:** LOG\_ID\_BACKUP\_OUTPUT

**Message Meaning:** Error output backup via SCP successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

---

## 32220 - LOG\_ID\_BACKUP\_COMMAND

**Message ID:** 32220

**Message Description:** LOG\_ID\_BACKUP\_COMMAND

**Message Meaning:** Batch mode command output backup via SCP successful

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32221 - LOG\_ID\_UPD\_VDOM\_LIC

**Message ID:** 32221

**Message Description:** LOG\_ID\_UPD\_VDOM\_LIC

**Message Meaning:** VM license installed via SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32222 - LOG\_ID\_GLB\_SETTING\_CHG

**Message ID:** 32222

**Message Description:** LOG\_ID\_GLB\_SETTING\_CHG

**Message Meaning:** Global setting changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
new_value	New Virtual Domain Name	string	128
old_value	Original Virtual Domain name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32223 - LOG\_ID\_BACKUP\_USER\_DEF\_IPS

**Message ID:** 32223

**Message Description:** LOG\_ID\_BACKUP\_USER\_DEF\_IPS

**Message Meaning:** IPS custom signatures backup success

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32224 - LOG\_ID\_BACKUP\_DISK\_LOG

**Message ID:** 32224

**Message Description:** LOG\_ID\_BACKUP\_DISK\_LOG

**Message Meaning:** Disk logs backed up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
file	File Name for Generated Report?	string	256
hash	Hash Value of Downloaded File	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32225 - LOG\_ID\_DEL\_ALL\_REVISION

**Message ID:** 32225

**Message Description:** LOG\_ID\_DEL\_ALL\_REVISION

**Message Meaning:** Revision database reset due to data corruption

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32226 - LOG\_ID\_LOAD\_IMG\_FAIL

**Message ID:** 32226

**Message Description:** LOG\_ID\_LOAD\_IMG\_FAIL

**Message Meaning:** Image failed to load

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32227 - LOG\_ID\_UPD\_DLP\_FAIL

**Message ID:** 32227

**Message Description:** LOG\_ID\_UPD\_DLP\_FAIL

**Message Meaning:** DLP fingerprint database failed to update by SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32228 - LOG\_ID\_LOAD\_IMG\_FAIL\_WRONG\_IMG

**Message ID:** 32228

**Message Description:** LOG\_ID\_LOAD\_IMG\_FAIL\_WRONG\_IMG

**Message Meaning:** Firmware image loaded incorrect

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32229 - LOG\_ID\_LOAD\_IMG\_FAIL\_NO\_RSA

**Message ID:** 32229

**Message Description:** LOG\_ID\_LOAD\_IMG\_FAIL\_NO\_RSA

**Message Meaning:** Firmware image without valid RSA signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32230 - LOG\_ID\_LOAD\_IMG\_FAIL\_INVALID\_RSA

**Message ID:** 32230

**Message Description:** LOG\_ID\_LOAD\_IMG\_FAIL\_INVALID\_RSA

**Message Meaning:** Firmware image with invalid RSA signature loaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32231 - LOG\_ID\_RESTORE\_FGD\_SVR\_FAIL

**Message ID:** 32231

**Message Description:** LOG\_ID\_RESTORE\_FGD\_SVR\_FAIL

**Message Meaning:** FortiGuard service failed to restore

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32232 - LOG\_ID\_RESTORE\_VDOM\_LIC\_FAIL

**Message ID:** 32232

**Message Description:** LOG\_ID\_RESTORE\_VDOM\_LIC\_FAIL

**Message Meaning:** VM license failed to restore

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32233 - LOG\_ID\_BACKUP\_IMG\_FAIL

**Message ID:** 32233

**Message Description:** LOG\_ID\_BACKUP\_IMG\_FAIL

**Message Meaning:** Firmware image backup failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32234 - LOG\_ID\_RESTORE\_IMG\_INVALID\_CC

**Message ID:** 32234

**Message Description:** LOG\_ID\_RESTORE\_IMG\_INVALID\_CC

**Message Meaning:** Image with invalid CC signature restored

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32235 - LOG\_ID\_RESTORE\_IMG\_FORTIGUARD

**Message ID:** 32235

**Message Description:** LOG\_ID\_RESTORE\_IMG\_FORTIGUARD

**Message Meaning:** Image restored from FortiGuard Management

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32236 - LOG\_ID\_BACKUP\_MEM\_LOG

**Message ID:** 32236

**Message Description:** LOG\_ID\_BACKUP\_MEM\_LOG

**Message Meaning:** Memory logs backed up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32237 - LOG\_ID\_BACKUP\_MEM\_LOG\_FAIL

**Message ID:** 32237

**Message Description:** LOG\_ID\_BACKUP\_MEM\_LOG\_FAIL



**Message Meaning:** Memory logs failed to back up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32238 - LOG\_ID\_BACKUP\_DISK\_LOG\_FAIL

**Message ID:** 32238

**Message Description:** LOG\_ID\_BACKUP\_DISK\_LOG\_FAIL

**Message Meaning:** Disk logs failed to back up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32239 - LOG\_ID\_BACKUP\_DISK\_LOG\_USB

**Message ID:** 32239

**Message Description:** LOG\_ID\_BACKUP\_DISK\_LOG\_USB

**Message Meaning:** Disk logs backed up to USB

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32240 - LOG\_ID\_SYS\_USB\_MODE

**Message ID:** 32240

**Message Description:** LOG\_ID\_SYS\_USB\_MODE

**Message Meaning:** System operating in USB mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32241 - LOG\_ID\_BACKUP\_DISK\_LOG\_USB\_FAIL

**Message ID:** 32241

**Message Description:** LOG\_ID\_BACKUP\_DISK\_LOG\_USB\_FAIL

**Message Meaning:** Disk logs failed to back up to USB

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32242 - LOG\_ID\_UPD\_VDOM\_LIC\_FAIL

**Message ID:** 32242

**Message Description:** LOG\_ID\_UPD\_VDOM\_LIC\_FAIL

**Message Meaning:** VM license failed to install via SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32243 - LOG\_ID\_UPD\_IPS\_SCP

**Message ID:** 32243

**Message Description:** LOG\_ID\_UPD\_IPS\_SCP

**Message Meaning:** IPS package updated via SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32244 - LOG\_ID\_UPD\_IPS\_SCP\_FAIL

**Message ID:** 32244

**Message Description:** LOG\_ID\_UPD\_IPS\_SCP\_FAIL

**Message Meaning:** IPS package failed to update via SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32245 - LOG\_ID\_BACKUP\_USER\_DEF\_IPS\_FAIL

**Message ID:** 32245

**Message Description:** LOG\_ID\_BACKUP\_USER\_DEF\_IPS\_FAIL

**Message Meaning:** IPS custom signatures backup failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32246 - LOG\_ID\_RESTORE\_USR\_DEF\_IPS\_CRITICAL

**Message ID:** 32246

**Message Description:** LOG\_ID\_RESTORE\_USR\_DEF\_IPS\_CRITICAL

**Message Meaning:** IPS custom signatures restored critical

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32247 - LOG\_ID\_SSH\_NEGOTIATION\_FAILURE

**Message ID:** 32247

**Message Description:** LOG\_ID\_SSH\_NEGOTIATION\_FAILURE

**Message Meaning:** SSH protocol cannot be negotiated

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
addr	IP Address	string	80
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5



Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32252 - LOG\_ID\_FACTORY\_RESET

**Message ID:** 32252

**Message Description:** LOG\_ID\_FACTORY\_RESET

**Message Meaning:** Factory settings reset

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32253 - LOG\_ID\_FORMAT\_RAID

**Message ID:** 32253

**Message Description:** LOG\_ID\_FORMAT\_RAID

**Message Meaning:** RAID disk formatted

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32254 - LOG\_ID\_ENABLE\_RAID

**Message ID:** 32254

**Message Description:** LOG\_ID\_ENABLE\_RAID

**Message Meaning:** RAID enabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32255 - LOG\_ID\_DISABLE\_RAID

**Message ID:** 32255

**Message Description:** LOG\_ID\_DISABLE\_RAID

**Message Meaning:** RAID disabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32300 - LOG\_ID\_UPLOAD\_RPT\_IMG

**Message ID:** 32300

**Message Description:** LOG\_ID\_UPLOAD\_RPT\_IMG

**Message Meaning:** Report image file uploaded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32301 - LOG\_ID\_ADD\_VDOM

**Message ID:** 32301

**Message Description:** LOG\_ID\_ADD\_VDOM

**Message Meaning:** VDOM added

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32302 - LOG\_ID\_DEL\_VDOM

**Message ID:** 32302

**Message Description:** LOG\_ID\_DEL\_VDOM

**Message Meaning:** VDOM deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32545 - LOG\_ID\_SYS\_RESTART

**Message ID:** 32545

**Message Description:** LOG\_ID\_SYS\_RESTART

**Message Meaning:** Scheduled daily reboot started

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32546 - LOG\_ID\_APPLICATION\_CRASH

**Message ID:** 32546

**Message Description:** LOG\_ID\_APPLICATION\_CRASH

**Message Meaning:** Application crashed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32547 - LOG\_ID\_AUTOSCRIPT\_START

**Message ID:** 32547

**Message Description:** LOG\_ID\_AUTOSCRIPT\_START

**Message Meaning:** Autoscript start

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32548 - LOG\_ID\_AUTOSCRIPT\_STOP

**Message ID:** 32548

**Message Description:** LOG\_ID\_AUTOSCRIPT\_STOP

**Message Meaning:** Autoscript stop

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10



Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32549 - LOG\_ID\_AUTOSCRIPT\_STOP\_AUTO

**Message ID:** 32549

**Message Description:** LOG\_ID\_AUTOSCRIPT\_STOP\_AUTO

**Message Meaning:** Autoscript stop automatically

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32550 - LOG\_ID\_AUTOSCRIPRT\_DELETE\_RSLT

**Message ID:** 32550

**Message Description:** LOG\_ID\_AUTOSCRIPRT\_DELETE\_RSLT

**Message Meaning:** Autoscript delete result

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32551 - LOG\_ID\_AUTOSCRIPRT\_BACKUP\_RSLT

**Message ID:** 32551

**Message Description:** LOG\_ID\_AUTOSCRIPRT\_BACKUP\_RSLT

**Message Meaning:** Autoscript backup result

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32552 - LOG\_ID\_AUTOSCRIP\_CHECK\_STATUS

**Message ID:** 32552

**Message Description:** LOG\_ID\_AUTOSCRIP\_CHECK\_STATUS

**Message Meaning:** Autoscript check status

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32553 - LOG\_ID\_AUTOSCRIPPT\_STOP\_REACH\_LIMIT

**Message ID:** 32553

**Message Description:** LOG\_ID\_AUTOSCRIPPT\_STOP\_REACH\_LIMIT

**Message Meaning:** Autoscript stop due to limit reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32561 - LOG\_ID\_ADMIN\_LOGOUT\_DISCONNECT

**Message ID:** 32561

**Message Description:** LOG\_ID\_ADMIN\_LOGOUT\_DISCONNECT

**Message Meaning:** Admin disconnected

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32562 - LOG\_ID\_STORE\_CONF\_FAIL\_SPACE

**Message ID:** 32562

**Message Description:** LOG\_ID\_STORE\_CONF\_FAIL\_SPACE

**Message Meaning:** Store config failed - not enough flash space

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32564 - LOG\_ID\_RESTORE\_CONF\_FAIL

**Message ID:** 32564

**Message Description:** LOG\_ID\_RESTORE\_CONF\_FAIL

**Message Meaning:** Configuration failed to restore

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning, Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32565 - LOG\_ID\_RESTORE\_CONF\_BY\_MGMT

**Message ID:** 32565

**Message Description:** LOG\_ID\_RESTORE\_CONF\_BY\_MGMT

**Message Meaning:** Configuration restored from management station

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32566 - LOG\_ID\_RESTORE\_CONF\_BY\_SCP

**Message ID:** 32566

**Message Description:** LOG\_ID\_RESTORE\_CONF\_BY\_SCP

**Message Meaning:** Configuration restored by SCP

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32567 - LOG\_ID\_RESTORE\_CONF\_BY\_USB

**Message ID:** 32567

**Message Description:** LOG\_ID\_RESTORE\_CONF\_BY\_USB

**Message Meaning:** Configuration restored by USB

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical



Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32568 - LOG\_ID\_DEL\_REVISION\_DB

**Message ID:** 32568

**Message Description:** LOG\_ID\_DEL\_REVISION\_DB

**Message Meaning:** Revision Database deletion

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 32569 - LOG\_ID\_FSW\_SWITCH\_LOG\_EVENT

**Message ID:** 32569

**Message Description:** LOG\_ID\_FSW\_SWITCH\_LOG\_EVENT

**Message Meaning:** Switch-Controller

**Type:** Event

**Category:** SYSTEM

**Severity:** Unknown

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32570 - LOG\_ID\_ADMIN\_MTNER\_LOGOUT\_DISCONNECT

**Message ID:** 32570

**Message Description:** LOG\_ID\_ADMIN\_MTNER\_LOGOUT\_DISCONNECT

**Message Meaning:** Admin monitor disconnected

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32601 - LOG\_ID\_FGT\_SWITCH\_LOG\_DISCOVER

**Message ID:** 32601

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_DISCOVER

**Message Meaning:** Switch-Controller discovered

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32602 - LOG\_ID\_FGT\_SWITCH\_LOG\_AUTH

**Message ID:** 32602

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_AUTH

**Message Meaning:** Switch-Controller authorized

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32603 - LOG\_ID\_FGT\_SWITCH\_LOG\_DEAUTH

**Message ID:** 32603

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_DEAUTH

**Message Meaning:** Switch-Controller deauthorized

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32604 - LOG\_ID\_FGT\_SWITCH\_LOG\_DELETE

**Message ID:** 32604

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_DELETE

**Message Meaning:** Switch-Controller deleted

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32605 - LOG\_ID\_FGT\_SWITCH\_LOG\_TUNNEL\_UP

**Message ID:** 32605

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_TUNNEL\_UP

**Message Meaning:** Switch-Controller Tunnel Up

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32606 - LOG\_ID\_FGT\_SWITCH\_LOG\_TUNNEL\_DOWN

**Message ID:** 32606

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_TUNNEL\_DOWN

**Message Meaning:** Switch-Controller Tunnel Down

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32607 - LOG\_ID\_FGT\_SWITCH\_PUSH\_IMAGE

**Message ID:** 32607

**Message Description:** LOG\_ID\_FGT\_SWITCH\_PUSH\_IMAGE

**Message Meaning:** Image push to FortiSwitch

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64



Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32608 - LOG\_ID\_FGT\_SWITCH\_STAGE\_IMAGE

**Message ID:** 32608

**Message Description:** LOG\_ID\_FGT\_SWITCH\_STAGE\_IMAGE

**Message Meaning:** Image stage to FortiSwitch

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32609 - LOG\_ID\_FGT\_SWITCH\_DISABLE\_DISCOVERY

**Message ID:** 32609

**Message Description:** LOG\_ID\_FGT\_SWITCH\_DISABLE\_DISCOVERY

**Message Meaning:** Disable FortiSwitch Discovery

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32610 - LOG\_ID\_FGT\_SWITCH\_LOG\_WARNING

**Message ID:** 32610

**Message Description:** LOG\_ID\_FGT\_SWITCH\_LOG\_WARNING

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32693 - LOG\_ID\_FGT\_SWITCH\_GROUP\_SWC

**Message ID:** 32693

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_SWC

**Message Meaning:** FortiSwitch switch controller

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32694 - LOG\_ID\_FGT\_SWITCH\_GROUP\_POE

**Message ID:** 32694

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_POE

**Message Meaning:** FortiSwitch PoE

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32695 - LOG\_ID\_FGT\_SWITCH\_GROUP\_LINK

**Message ID:** 32695

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_LINK

**Message Meaning:** FortiSwitch link

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32696 - LOG\_ID\_FGT\_SWITCH\_GROUP\_STP

**Message ID:** 32696

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_STP

**Message Meaning:** FortiSwitch spanning Tree

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32697 - LOG\_ID\_FGT\_SWITCH\_GROUP\_SWITCH

**Message ID:** 32697

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_SWITCH

**Message Meaning:** FortiSwitch switch

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32698 - LOG\_ID\_FGT\_SWITCH\_GROUP\_ROUTER

**Message ID:** 32698

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_ROUTER

**Message Meaning:** FortiSwitch router

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 32699 - LOG\_ID\_FGT\_SWITCH\_GROUP\_SYSTEM

**Message ID:** 32699

**Message Description:** LOG\_ID\_FGT\_SWITCH\_GROUP\_SYSTEM

**Message Meaning:** FortiSwitch system

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 35001 - LOG\_ID\_HA\_SYNC\_VIRDB

**Message ID:** 35001

**Message Description:** LOG\_ID\_HA\_SYNC\_VIRDB

**Message Meaning:** HA slave synchronized Virus database

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35002 - LOG\_ID\_HA\_SYNC\_ETDB

**Message ID:** 35002

**Message Description:** LOG\_ID\_HA\_SYNC\_ETDB

**Message Meaning:** HA slave synchronized Extended database

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35003 - LOG\_ID\_HA\_SYNC\_EXDB

**Message ID:** 35003

**Message Description:** LOG\_ID\_HA\_SYNC\_EXDB

**Message Meaning:** HA slave synchronized Extreme database

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35004 - LOG\_ID\_HA\_SYNC\_FLDB

**Message ID:** 35004

**Message Description:** LOG\_ID\_HA\_SYNC\_FLDB

**Message Meaning:** HA slave synchronized FLDB

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35005 - LOG\_ID\_HA\_SYNC\_IPS

**Message ID:** 35005

**Message Description:** LOG\_ID\_HA\_SYNC\_IPS

**Message Meaning:** HA slave synchronized IDS package

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35007 - LOG\_ID\_HA\_SYNC\_AV

**Message ID:** 35007

**Message Description:** LOG\_ID\_HA\_SYNC\_AV

**Message Meaning:** HA slave synchronized AntiVirus package

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35009 - LOG\_ID\_HA\_SYNC\_CID

**Message ID:** 35009

**Message Description:** LOG\_ID\_HA\_SYNC\_CID

**Message Meaning:** HA slave synchronized CID package

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35010 - LOG\_ID\_HA\_SYNC\_UWDB

**Message ID:** 35010

**Message Description:** LOG\_ID\_HA\_SYNC\_UWDB

**Message Meaning:** HA slave synchronization URL database

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35011 - LOG\_ID\_HA\_SYNC\_FAIL

**Message ID:** 35011

**Message Description:** LOG\_ID\_HA\_SYNC\_FAIL

**Message Meaning:** HA slave synchronization failed

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 35012 - LOG\_ID\_CONF\_SYNC\_FAIL

**Message ID:** 35012

**Message Description:** LOG\_ID\_CONF\_SYNC\_FAIL

**Message Meaning:** Slave sync failed

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 36880 - LOG\_ID\_EVENT\_SYSTEM\_MAC\_HOST\_STORE\_LIMIT

**Message ID:** 36880

**Message Description:** LOG\_ID\_EVENT\_SYSTEM\_MAC\_HOST\_STORE\_LIMIT

**Message Meaning:** Device detection storage limit reached

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 36881 - LOG\_ID\_EVENT\_SYSTEM\_CFG\_REVERT

**Message ID:** 36881

**Message Description:** LOG\_ID\_EVENT\_SYSTEM\_CFG\_REVERT

**Message Meaning:** Configuration reverted due to timeout

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 36882 - LOG\_ID\_EVENT\_SYSTEM\_CFG\_MANUALLY\_SAVED

**Message ID:** 36882

**Message Description:** LOG\_ID\_EVENT\_SYSTEM\_CFG\_MANUALLY\_SAVED

**Message Meaning:** Configuration manually saved



**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 37120 - MESGID\_NEG\_GENERIC\_P1\_NOTIF

**Message ID:** 37120

**Message Description:** MESGID\_NEG\_GENERIC\_P1\_NOTIF

**Message Meaning:** Negotiate IPsec phase 1

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37121 - MESGID\_NEG\_GENERIC\_P1\_ERROR

**Message ID:** 37121

**Message Description:** MESGID\_NEG\_GENERIC\_P1\_ERROR

**Message Meaning:** Negotiate IPsec phase 1

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37122 - MESGID\_NEG\_GENERIC\_P2\_NOTIF

**Message ID:** 37122

**Message Description:** MESGID\_NEG\_GENERIC\_P2\_NOTIF

**Message Meaning:** Negotiate IPsec phase 2

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	21
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37123 - MESSGID\_NEG\_GENERIC\_P2\_ERROR

**Message ID:** 37123

**Message Description:** MESSGID\_NEG\_GENERIC\_P2\_ERROR

**Message Meaning:** Negotiate IPsec phase 2

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	21
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37124 - MESGID\_NEG\_I\_P1\_ERROR

**Message ID:** 37124

**Message Description:** MESGID\_NEG\_I\_P1\_ERROR

**Message Meaning:** IPsec phase 1 error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
rempoort	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37125 - MMSGID\_NEG\_I\_P2\_ERROR

**Message ID:** 37125

**Message Description:** MMSGID\_NEG\_I\_P2\_ERROR

**Message Meaning:** IPsec phase 2 error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37126 - MESGID\_NEG\_NO\_STATE\_ERROR

**Message ID:** 37126

**Message Description:** MESGID\_NEG\_NO\_STATE\_ERROR

**Message Meaning:** IPsec no state error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37127 - MESGID\_NEG\_PROGRESS\_P1\_NOTIF

**Message ID:** 37127

**Message Description:** MESGID\_NEG\_PROGRESS\_P1\_NOTIF

**Message Meaning:** Progress IPsec phase 1

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch		string	14
group	User Group Name	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64

Log Field Name	Description	Data Type	Length
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37128 - MESGID\_NEG\_PROGRESS\_P1\_ERROR

**Message ID:** 37128

**Message Description:** MESGID\_NEG\_PROGRESS\_P1\_ERROR

**Message Meaning:** Progress IPsec phase 1

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch		string	14
group	User Group Name	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37129 - MESSGID\_NEG\_PROGRESS\_P2\_NOTIF

**Message ID:** 37129

**Message Description:** MESSGID\_NEG\_PROGRESS\_P2\_NOTIF

**Message Meaning:** Progress IPsec phase 2

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
exch		string	14
group	User Group Name	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37130 - MESGID\_NEG\_PROGRESS\_P2\_ERROR

**Message ID:** 37130

**Message Description:** MESGID\_NEG\_PROGRESS\_P2\_ERROR

**Message Meaning:** Progress IPsec phase 2

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch		string	14
group	User Group Name	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37131 - MMSGID\_ESP\_ERROR

**Message ID:** 37131

**Message Description:** MMSGID\_ESP\_ERROR

**Message Meaning:** IPsec ESP

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
rempoort	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37132 - MESGID\_ESP\_CRITICAL

**Message ID:** 37132

**Message Description:** MESGID\_ESP\_CRITICAL

**Message Meaning:** IPsec ESP

**Type:** Event

**Category:** VPN

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
eventtime		uint64	20
group	User Group Name	string	64



Log Field Name	Description	Data Type	Length
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37133 - MESSGID\_INSTALL\_SA

**Message ID:** 37133

**Message Description:** MESSGID\_INSTALL\_SA

**Message Meaning:** IPsec SA installed

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37134 - MESSGID\_DELETE\_P1\_SA

**Message ID:** 37134

**Message Description:** MESSGID\_DELETE\_P1\_SA

**Message Meaning:** IPsec phase 1 SA deleted

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37135 - MMSGID\_DELETE\_P2\_SA

**Message ID:** 37135

**Message Description:** MMSGID\_DELETE\_P2\_SA

**Message Meaning:** IPsec phase 2 SA deleted

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37136 - MESSGID\_DPD\_FAILURE

**Message ID:** 37136

**Message Description:** MESSGID\_DPD\_FAILURE

**Message Meaning:** IPsec DPD failed

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
rempport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128

Log Field Name	Description	Data Type	Length
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37137 - MESGID\_CONN\_FAILURE

**Message ID:** 37137

**Message Description:** MESGID\_CONN\_FAILURE

**Message Meaning:** IPsec connection failed

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37138 - MESGID\_CONN\_UPDOWN

**Message ID:** 37138

**Message Description:** MESGID\_CONN\_UPDOWN

**Message Meaning:** IPsec connection status changed

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10

Log Field Name	Description	Data Type	Length
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37139 - MESGID\_P2\_UPDOWN

**Message ID:** 37139

**Message Description:** MESGID\_P2\_UPDOWN

**Message Meaning:** IPsec phase 2 status changed

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
phase2_name	Phase 2 Name	string	128
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37141 - MESSGID\_CONN\_STATS

**Message ID:** 37141

**Message Description:** MESSGID\_CONN\_STATS

**Message Meaning:** IPsec tunnel statistics

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

## 37889 - MESSAGES\_VC\_DELETE

**Message ID:** 37889

**Message Description:** MESSAGES\_VC\_DELETE

**Message Meaning:** Virtual cluster deleted

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37890 - MESSAGES\_VC\_MOVE\_VDOM

**Message ID:** 37890

**Message Description:** MESSAGES\_VC\_MOVE\_VDOM

**Message Meaning:** Virtual cluster VDOM moved

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
from_vcluster	source virtual cluster number	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
to_vcluster	destination virtual cluster number	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vdname	vdom name	string	32

## 37891 - MESSID\_VC\_ADD\_VDOM

**Message ID:** 37891

**Message Description:** MESSID\_VC\_ADD\_VDOM

**Message Meaning:** Virtual cluster VDOM added

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
to_vcluster	destination virtual cluster number	uint32	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vdname	vdom name	string	32

## 37892 - MESSAGES\_VC\_MOVE\_MEMBERSHIP\_STATE

**Message ID:** 37892

**Message Description:** MESSAGES\_VC\_MOVE\_MEMBERSHIP\_STATE

**Message Meaning:** Virtual cluster member state moved

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster_member		uint32	10
vcluster_state		string	7
vd	Virtual Domain Name	string	32

## 37893 - MESSAGES\_VC\_DETECT\_MEMBERSHIP\_DEAD

**Message ID:** 37893

**Message Description:** MESSAGES\_VC\_DETECT\_MEMBERSHIP\_DEAD

**Message Meaning:** Virtual cluster member dead

**Type:** Event

**Category:** HA

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37894 - MMSGID\_VC\_DETECT\_MEMB\_JOIN

**Message ID:** 37894

**Message Description:** MMSGID\_VC\_DETECT\_MEMB\_JOIN

**Message Meaning:** Virtual cluster member joined

**Type:** Event

**Category:** HA

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37895 - MESGID\_VC\_ADD\_HADEV

**Message ID:** 37895

**Message Description:** MESGID\_VC\_ADD\_HADEV

**Message Meaning:** Virtual cluster added HA device interface

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37896 - MESSAGES\_VC\_DEL\_HADEV

**Message ID:** 37896

**Message Description:** MESSAGES\_VC\_DEL\_HADEV

**Message Meaning:** Virtual cluster deleted HA device interface

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

## 37897 - MESSAGES\_HADEV\_READY

**Message ID:** 37897

**Message Description:** MESSAGES\_HADEV\_READY

**Message Meaning:** HA device interface ready

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10



Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37898 - MESSAGESID\_HADEV\_FAIL

**Message ID:** 37898

**Message Description:** MESSAGESID\_HADEV\_FAIL

**Message Meaning:** HA device interface failed

**Type:** Event

**Category:** HA

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37899 - MESSAGESID\_HADEV\_PEERINFO

**Message ID:** 37899

**Message Description:** MESSAGESID\_HADEV\_PEERINFO

**Message Meaning:** HA device interface peer information

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37900 - MESSAGESID\_HBDEV\_DELETE

**Message ID:** 37900

**Message Description:** MESSAGESID\_HBDEV\_DELETE

**Message Meaning:** Heartbeat device interface deleted

**Type:** Event

**Category:** HA

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37901 - MMSGID\_HBDEV\_DOWN

**Message ID:** 37901

**Message Description:** MMSGID\_HBDEV\_DOWN

**Message Meaning:** Heartbeat device interface down

**Type:** Event

**Category:** HA

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
hbdn_reason	heartbeat down reason	string	18

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37902 - MMSGID\_HBDEV\_UP

**Message ID:** 37902

**Message Description:** MMSGID\_HBDEV\_UP

**Message Meaning:** Heartbeat device interface up

**Type:** Event

**Category:** HA

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37903 - MESSAGESID\_SYNC\_STATUS

**Message ID:** 37903

**Message Description:** MESSAGESID\_SYNC\_STATUS

**Message Meaning:** Synchronization status with master

**Type:** Event

**Category:** HA

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
sync_status	The sync status with the primary	string	11
sync_type	The sync type with the primary	string	14
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37904 - MESSAGESID\_HA\_ACTIVITY

**Message ID:** 37904

**Message Description:** MESSAGESID\_HA\_ACTIVITY

**Message Meaning:** Device set as HA master

**Type:** Event

**Category:** HA

**Severity:** Notice, Information

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha-prio	HA Priority	uint8	3
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37907 - MESSAGES\_VLAN\_HB\_UP

**Message ID:** 37907

**Message Description:** MESSAGES\_VLAN\_HB\_UP

**Message Meaning:** VLAN heartbeat started

**Type:** Event

**Category:** HA

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37908 - MMSGID\_VLAN\_HB\_DOWN

**Message ID:** 37908

**Message Description:** MMSGID\_VLAN\_HB\_DOWN

**Message Meaning:** VLAN heartbeat lost

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 37909 - MMSGID\_VLAN\_HB\_DOWN\_SUM

**Message ID:** 37909

**Message Description:** MMSGID\_VLAN\_HB\_DOWN\_SUM

**Message Meaning:** VLAN heartbeat lost summary

**Type:** Event

**Category:** HA

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38010 - LOG\_ID\_FIPS\_ENCRY\_FAIL

**Message ID:** 38010

**Message Description:** LOG\_ID\_FIPS\_ENCRY\_FAIL

**Message Meaning:** FIPS CC encryption failed

**Type:** Event

**Category:** USER

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23



Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38011 - LOG\_ID\_FIPS\_DECRY\_FAIL

**Message ID:** 38011

**Message Description:** LOG\_ID\_FIPS\_DECRY\_FAIL

**Message Meaning:** FIPS CC decryption failed

**Type:** Event

**Category:** USER

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38012 - LOG\_ID\_ENTROPY\_TOKEN

**Message ID:** 38012

**Message Description:** LOG\_ID\_ENTROPY\_TOKEN

**Message Meaning:** Seeding from entropy source

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38031 - LOG\_ID\_FSSO\_LOGON

**Message ID:** 38031

**Message Description:** LOG\_ID\_FSSO\_LOGON

**Message Meaning:** FSSO logon successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38032 - LOG\_ID\_FSSO\_LOGOFF

**Message ID:** 38032

**Message Description:** LOG\_ID\_FSSO\_LOGOFF

**Message Meaning:** FSSO logout successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38033 - LOG\_ID\_FSSO\_SVR\_STATUS

**Message ID:** 38033

**Message Description:** LOG\_ID\_FSSO\_SVR\_STATUS

**Message Meaning:** FSSO Active Directory server authentication status

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38400 - LOGID\_EVENT\_NOTIF\_SEND\_SUCC

**Message ID:** 38400

**Message Description:** LOGID\_EVENT\_NOTIF\_SEND\_SUCC

**Message Meaning:** Notification message sent

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
eventtime		uint64	20
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
profile	Profile Name	string	64
profilegroup	Profile Group Name	string	4

Log Field Name	Description	Data Type	Length
profiletype	Profile Type	string	64
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
to	Recipient Email Addresses for Notification	string	512
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
virus	Virus Name	string	128

## 38401 - LOGID\_EVENT\_NOTIF\_SEND\_FAIL

**Message ID:** 38401

**Message Description:** LOGID\_EVENT\_NOTIF\_SEND\_FAIL

**Message Meaning:** Notification message send failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
eventtime		uint64	20
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
profile	Profile Name	string	64
profilegroup	Profile Group Name	string	4
profiletype	Profile Type	string	64
service	Name of Service	string	64
sess_duration	Session Duration	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
to	Recipient Email Addresses for Notification	string	512
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
virus	Virus Name	string	128

## 38402 - LOGID\_EVENT\_NOTIF\_DNS\_FAIL

**Message ID:** 38402

**Message Description:** LOGID\_EVENT\_NOTIF\_DNS\_FAIL

**Message Meaning:** MMSC hostname unresolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
hostname	Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
profile	Profile Name	string	64
profiletype	Profile Type	string	64
profile_vd	Virtual Domain Name	string	64
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38403 - LOGID\_EVENT\_NOTIF\_INSUFFICIENT\_RESOURCE

**Message ID:** 38403

**Message Description:** LOGID\_EVENT\_NOTIF\_INSUFFICIENT\_RESOURCE

**Message Meaning:** Insufficient system resource notification

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32



## 38404 - LOGID\_EVENT\_NOTIF\_HOSTNAME\_ERROR

**Message ID:** 38404

**Message Description:** LOGID\_EVENT\_NOTIF\_HOSTNAME\_ERROR

**Message Meaning:** FortiGuard hostname unresolvable

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
hostname	Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38405 - LOGID\_NOTIF\_CODE\_SENDTO\_SMS\_PHONE

**Message ID:** 38405

**Message Description:** LOGID\_NOTIF\_CODE\_SENDTO\_SMS\_PHONE

**Message Meaning:** Guest user account login information sent to phone

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38406 - LOGID\_NOTIF\_CODE\_SENDTO\_SMS\_TO

**Message ID:** 38406

**Message Description:** LOGID\_NOTIF\_CODE\_SENDTO\_SMS\_TO

**Message Meaning:** Guest user account login information sent as SMS

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38407 - LOGID\_NOTIF\_CODE\_SENDTO\_EMAIL

**Message ID:** 38407

**Message Description:** LOGID\_NOTIF\_CODE\_SENDTO\_EMAIL

**Message Meaning:** Guest user account login information sent to email

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38408 - LOGID\_EVENT\_OFTP\_SSL\_CONNECTED

**Message ID:** 38408

**Message Description:** LOGID\_EVENT\_OFTP\_SSL\_CONNECTED

**Message Meaning:** SSL connection established

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38409 - LOGID\_EVENT\_OFTP\_SSL\_DISCONNECTED

**Message ID:** 38409

**Message Description:** LOGID\_EVENT\_OFTP\_SSL\_DISCONNECTED

**Message Meaning:** SSL connection closed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38410 - LOGID\_EVENT\_OFTP\_SSL\_FAILED

**Message ID:** 38410

**Message Description:** LOGID\_EVENT\_OFTP\_SSL\_FAILED

**Message Meaning:** SSL connection failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38411 - LOGID\_EVENT\_TWO\_F\_AUTH\_CODE\_SENDTO

**Message ID:** 38411

**Message Description:** LOGID\_EVENT\_TWO\_F\_AUTH\_CODE\_SENDTO

**Message Meaning:** Two-factor authentication code sent

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38412 - LOGID\_EVENT\_TOKEN\_CODE\_SENDTO

**Message ID:** 38412

**Message Description:** LOGID\_EVENT\_TOKEN\_CODE\_SENDTO

**Message Meaning:** Token activation code sent

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 38420 - LOGID\_EVENT\_HTTPS\_CONNECTION

**Message ID:** 38420

**Message Description:** LOGID\_EVENT\_HTTPS\_CONNECTION

**Message Meaning:** HTTPS connection

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
reason	Reason	string	256
remote	Remote IP Address	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38656 - LOGID\_EVENT\_RAD\_RPT\_PROTO\_ERROR

**Message ID:** 38656

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_PROTO\_ERROR

**Message Meaning:** RADIUS protocol error summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8



Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38657 - LOGID\_EVENT\_RAD\_RPT\_PROF\_NOT\_FOUND

**Message ID:** 38657

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_PROF\_NOT\_FOUND

**Message Meaning:** RADIUS profile not found summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38658 - LOGID\_EVENT\_RAD\_RPT\_CTX\_NOT\_FOUND

**Message ID:** 38658

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_CTX\_NOT\_FOUND

**Message Meaning:** RADIUS profile CTX not found summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38659 - LOGID\_EVENT\_RAD\_RPT\_ACCT\_STOP\_MISSED

**Message ID:** 38659

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_ACCT\_STOP\_MISSED

**Message Meaning:** RADIUS accounting stop message missing summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38660 - LOGID\_EVENT\_RAD\_RPT\_ACCT\_EVENT

**Message ID:** 38660

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_ACCT\_EVENT

**Message Meaning:** RADIUS accounting event summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38661 - LOGID\_EVENT\_RAD\_RPT\_OTHER

**Message ID:** 38661

**Message Description:** LOGID\_EVENT\_RAD\_RPT\_OTHER

**Message Meaning:** RADIUS endpoint block event or other event summary

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38662 - LOGID\_EVENT\_RAD\_STAT\_PROTO\_ERROR

**Message ID:** 38662

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_PROTO\_ERROR

**Message Meaning:** RADIUS accounting protocol error

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38663 - LOGID\_EVENT\_RAD\_STAT\_PROF\_NOT\_FOUND

**Message ID:** 38663

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_PROF\_NOT\_FOUND

**Message Meaning:** RADIUS accounting profile not found

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38665 - LOGID\_EVENT\_RAD\_STAT\_ACCT\_STOP\_MISSED

**Message ID:** 38665

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_ACCT\_STOP\_MISSED

**Message Meaning:** RADIUS accounting stop message missing

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38666 - LOGID\_EVENT\_RAD\_STAT\_ACCT\_EVENT

**Message ID:** 38666

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_ACCT\_EVENT

**Message Meaning:** RADIUS accounting event

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38667 - LOGID\_EVENT\_RAD\_STAT\_OTHER

**Message ID:** 38667

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_OTHER

**Message Meaning:** RADIUS other accounting event

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 38668 - LOGID\_EVENT\_RAD\_STAT\_EP\_BLK

**Message ID:** 38668

**Message Description:** LOGID\_EVENT\_RAD\_STAT\_EP\_BLK

**Message Meaning:** RADIUS endpoint block event

**Type:** Event

**Category:** USER

**Severity:** Notice



Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 39424 - LOG\_ID\_EVENT\_SSL\_VPN\_USER\_TUNNEL\_UP

**Message ID:** 39424

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_USER\_TUNNEL\_UP

**Message Meaning:** SSL VPN tunnel up

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39425 - LOG\_ID\_EVENT\_SSL\_VPN\_USER\_TUNNEL\_DOWN

**Message ID:** 39425

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_USER\_TUNNEL\_DOWN

**Message Meaning:** SSL VPN tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
rcvdbyte	Received Bytes	uint64	20
reason	Reason	string	256
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39426 - LOG\_ID\_EVENT\_SSL\_VPN\_USER\_SSL\_LOGIN\_FAIL

**Message ID:** 39426

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_USER\_SSL\_LOGIN\_FAIL

**Message Meaning:** SSL VPN login fail

**Type:** Event

**Category:** VPN

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39936 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEB\_TUNNEL\_STATS

**Message ID:** 39936

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEB\_TUNNEL\_STATS

**Message Meaning:** SSL VPN statistics

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39937 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_DENY

**Message ID:** 39937

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_DENY

**Message Meaning:** SSL VPN deny

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39938 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_PASS

**Message ID:** 39938

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_PASS

**Message Meaning:** SSL VPN pass

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39939 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_TIMEOUT

**Message ID:** 39939

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_TIMEOUT

**Message Meaning:** SSL VPN timeout

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39940 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_CLOSE

**Message ID:** 39940

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_WEBAPP\_CLOSE

**Message Meaning:** SSL VPN close

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39941 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_SYS\_BUSY

**Message ID:** 39941

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_SYS\_BUSY

**Message Meaning:** SSL VPN system busy

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10

Log Field Name	Description	Data Type	Length
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39942 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_CERT\_OK

**Message ID:** 39942

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_CERT\_OK

**Message Meaning:** SSL VPN certificate OK

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39943 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_NEW\_CON

**Message ID:** 39943

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_NEW\_CON

**Message Meaning:** SSL VPN new connection

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39944 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_ALERT

**Message ID:** 39944

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_ALERT

**Message Meaning:** SSL VPN alert

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
desc		string	128
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39945 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_EXIT\_FAIL

**Message ID:** 39945

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_EXIT\_FAIL

**Message Meaning:** SSL VPN exit fail

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39946 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_EXIT\_ERR

**Message ID:** 39946

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_EXIT\_ERR

**Message Meaning:** SSL VPN exit error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39947 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_UP

**Message ID:** 39947

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_UP

**Message Meaning:** SSL VPN tunnel up

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39948 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_DOWN

**Message ID:** 39948

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_DOWN

**Message Meaning:** SSL VPN tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64

Log Field Name	Description	Data Type	Length
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
rcvdbyte	Received Bytes	uint64	20
reason	Reason	string	256
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39949 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_STATS

**Message ID:** 39949

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_STATS

**Message Meaning:** SSL VPN statistics

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39950 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_UNKNOWNTAG

**Message ID:** 39950

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_UNKNOWNTAG

**Message Meaning:** SSL VPN unknown tag

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39951 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_ERROR

**Message ID:** 39951

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_TUNNEL\_ERROR

**Message Meaning:** SSL VPN tunnel error

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39952 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_ENTER\_CONSERVE\_MODE

**Message ID:** 39952

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_ENTER\_CONSERVE\_MODE

**Message Meaning:** SSL VPN enter conserve mode

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 39953 - LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_LEAVE\_CONSERVE\_MODE

**Message ID:** 39953

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SESSION\_LEAVE\_CONSERVE\_MODE

**Message Meaning:** SSL VPN leave conserve mode

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40001 - LOG\_ID\_PPTP\_TUNNEL\_UP

**Message ID:** 40001

**Message Description:** LOG\_ID\_PPTP\_TUNNEL\_UP

**Message Meaning:** PPTP tunnel up

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40002 - LOG\_ID\_PPTP\_TUNNEL\_DOWN

**Message ID:** 40002

**Message Description:** LOG\_ID\_PPTP\_TUNNEL\_DOWN

**Message Meaning:** PPTP tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10

Log Field Name	Description	Data Type	Length
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40003 - LOG\_ID\_PPTP\_TUNNEL\_STAT

**Message ID:** 40003

**Message Description:** LOG\_ID\_PPTP\_TUNNEL\_STAT

**Message Meaning:** PPTP tunnel status

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40014 - LOG\_ID\_PPTP\_REACH\_MAX\_CON

**Message ID:** 40014

**Message Description:** LOG\_ID\_PPTP\_REACH\_MAX\_CON

**Message Meaning:** PPTP client connection limit reached

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40017 - LOG\_ID\_L2TPD\_CLIENT\_CON\_FAIL

**Message ID:** 40017

**Message Description:** LOG\_ID\_L2TPD\_CLIENT\_CON\_FAIL

**Message Meaning:** L2TP client connection failed

**Type:** Event

**Category:** VPN



**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40019 - LOG\_ID\_L2TPD\_CLIENT\_DISCON

**Message ID:** 40019

**Message Description:** LOG\_ID\_L2TPD\_CLIENT\_DISCON

**Message Meaning:** L2TP client disconnected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40021 - LOG\_ID\_PPTP\_NOT\_CONIG

**Message ID:** 40021

**Message Description:** LOG\_ID\_PPTP\_NOT\_CONIG

**Message Meaning:** PPTP not configured in VDOM

**Type:** Event

**Category:** VPN

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40022 - LOG\_ID\_PPTP\_NO\_IP\_AVAIL

**Message ID:** 40022

**Message Description:** LOG\_ID\_PPTP\_NO\_IP\_AVAIL

**Message Meaning:** PPTP IP addresses unavailable

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40024 - LOG\_ID\_PPTP\_OUT\_MEM

**Message ID:** 40024

**Message Description:** LOG\_ID\_PPTP\_OUT\_MEM

**Message Meaning:** PPTP config list insufficient memory

**Type:** Event

**Category:** VPN

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40034 - LOG\_ID\_PPTP\_START

**Message ID:** 40034

**Message Description:** LOG\_ID\_PPTP\_START

**Message Meaning:** PPTP daemon started

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40035 - LOG\_ID\_PPTP\_START\_FAIL

**Message ID:** 40035

**Message Description:** LOG\_ID\_PPTP\_START\_FAIL

**Message Meaning:** PPTP daemon failed to start

**Type:** Event

**Category:** VPN

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40036 - LOG\_ID\_PPTP\_EXIT

**Message ID:** 40036

**Message Description:** LOG\_ID\_PPTP\_EXIT

**Message Meaning:** PPTP daemon exited

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40037 - LOG\_ID\_PPTPD\_SVR\_DISCON

**Message ID:** 40037

**Message Description:** LOG\_ID\_PPTPD\_SVR\_DISCON

**Message Meaning:** PPTP daemon disconnected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40038 - LOG\_ID\_PPTPD\_CLIENT\_CON

**Message ID:** 40038

**Message Description:** LOG\_ID\_PPTPD\_CLIENT\_CON

**Message Meaning:** PPTP client connected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40039 - LOG\_ID\_PPTPD\_CLIENT\_DISCON

**Message ID:** 40039

**Message Description:** LOG\_ID\_PPTPD\_CLIENT\_DISCON

**Message Meaning:** PPTP client disconnected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40101 - LOG\_ID\_L2TP\_TUNNEL\_UP

**Message ID:** 40101

**Message Description:** LOG\_ID\_L2TP\_TUNNEL\_UP

**Message Meaning:** L2TP tunnel up

**Type:** Event

**Category:** VPN



**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40102 - LOG\_ID\_L2TP\_TUNNEL\_DOWN

**Message ID:** 40102

**Message Description:** LOG\_ID\_L2TP\_TUNNEL\_DOWN

**Message Meaning:** L2TP tunnel down

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40103 - LOG\_ID\_L2TP\_TUNNEL\_STAT

**Message ID:** 40103

**Message Description:** LOG\_ID\_L2TP\_TUNNEL\_STAT

**Message Meaning:** L2TP tunnel status

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 40114 - LOG\_ID\_L2TPD\_START

**Message ID:** 40114

**Message Description:** LOG\_ID\_L2TPD\_START

**Message Meaning:** L2TP daemon started

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40115 - LOG\_ID\_L2TPD\_EXIT

**Message ID:** 40115

**Message Description:** LOG\_ID\_L2TPD\_EXIT

**Message Meaning:** L2TP daemon exited

**Type:** Event

**Category:** VPN

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40118 - LOG\_ID\_L2TPD\_CLIENT\_CON

**Message ID:** 40118

**Message Description:** LOG\_ID\_L2TPD\_CLIENT\_CON

**Message Meaning:** L2TP client connected

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40704 - LOG\_ID\_EVENT\_SYS\_PERF

**Message ID:** 40704

**Message Description:** LOG\_ID\_EVENT\_SYS\_PERF

**Message Meaning:** System performance statistics

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
bandwidth	Bandwidth	string	42
cpu	CPU Usage	uint8	3
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
disk	Disk Usage	uint8	3
disklograte	Disk Log Rate	uint64	20
eventtime		uint64	20
fazlograte	FortiAnalyzer Logging Rate	uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mem	Memory Usage	uint8	3
msg	Message Text	string	
setuprate	Session Setup Rate	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
totalsession	Total Number of Sessions	uint32	10
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32



This log message is only sent to remote FortiAnalyzer and memory, but not to disk.

## 40705 - LOG\_ID\_EVENT\_SYS\_CPU\_USAGE

**Message ID:** 40705

**Message Description:** LOG\_ID\_EVENT\_SYS\_CPU\_USAGE

**Message Meaning:** CPU usage statistics

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
cpu	CPU Usage	uint8	3
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 40960 - LOGID\_EVENT\_WAD\_WEBPROXY\_FWD\_SRV\_ERROR

**Message ID:** 40960

**Message Description:** LOGID\_EVENT\_WAD\_WEBPROXY\_FWD\_SRV\_ERROR

**Message Meaning:** Web proxy forward server error

**Type:** Event

**Category:** WAD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
addr_type	Address Type	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fqdn	Fully Qualified Domain Name	string	256
fwserver_name		string	32
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
port	Port Number	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 41000 - LOG\_ID\_UPD\_FGT\_SUCC

**Message ID:** 41000

**Message Description:** LOG\_ID\_UPD\_FGT\_SUCC

**Message Meaning:** FortiGate update succeeded

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 41001 - LOG\_ID\_UPD\_FGT\_FAIL

**Message ID:** 41001



**Message Description:** LOG\_ID\_UPD\_FGT\_FAIL

**Message Meaning:** FortiGate update failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 41002 - LOG\_ID\_UPD\_SRC\_VIS

**Message ID:** 41002

**Message Description:** LOG\_ID\_UPD\_SRC\_VIS

**Message Meaning:** Source visibility signature package updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 41006 - LOG\_ID\_UPD\_FSA\_VIRDB

**Message ID:** 41006

**Message Description:** LOG\_ID\_UPD\_FSA\_VIRDB

**Message Meaning:** FortiSandbox AV database updated

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

## 41984 - LOG\_ID\_EVENT\_VPN\_CERT\_LOAD

**Message ID:** 41984

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_LOAD

**Message Meaning:** Certificate loaded

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 41985 - LOG\_ID\_EVENT\_VPN\_CERT\_REMOVAL

**Message ID:** 41985

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_REMOVAL

**Message Meaning:** Certificate removed

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 41986 - LOG\_ID\_EVENT\_VPN\_CERT\_REGEN

**Message ID:** 41986

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_REGEN

**Message Meaning:** Certificate regenerated

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 41987 - LOG\_ID\_EVENT\_VPN\_CERT\_UPDATE

**Message ID:** 41987

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_UPDATE

**Message Meaning:** Certificate updated

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 41988 - LOG\_ID\_EVENT\_SSL\_VPN\_SETTING\_UPDATE

**Message ID:** 41988

**Message Description:** LOG\_ID\_EVENT\_SSL\_VPN\_SETTING\_UPDATE

**Message Meaning:** SSL setting changed

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 41989 - LOG\_ID\_EVENT\_VPN\_CERT\_ERR

**Message ID:** 41989

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_ERR

**Message Meaning:** Certificate error

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 41990 - LOG\_ID\_EVENT\_VPN\_CERT\_UPDATE\_FAILED

**Message ID:** 41990

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_UPDATE\_FAILED

**Message Meaning:** Certificate update failed

**Type:** Event

**Category:** VPN

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 41991 - LOG\_ID\_EVENT\_VPN\_CERT\_EXPORT

**Message ID:** 41991

**Message Description:** LOG\_ID\_EVENT\_VPN\_CERT\_EXPORT

**Message Meaning:** Certificate exported

**Type:** Event

**Category:** VPN

**Severity:** Information



Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 42201 - LOG\_ID\_NETX\_VMX\_ATTACH

**Message ID:** 42201

**Message Description:** LOG\_ID\_NETX\_VMX\_ATTACH

**Message Meaning:** VMX instance successfully attached

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 42202 - LOG\_ID\_NETX\_VMX\_DETACH

**Message ID:** 42202

**Message Description:** LOG\_ID\_NETX\_VMX\_DETACH

**Message Meaning:** VMX instance successfully detached

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 42203 - LOG\_ID\_NETX\_VMX\_DENIED

**Message ID:** 42203

**Message Description:** LOG\_ID\_NETX\_VMX\_DENIED

**Message Meaning:** VMX instance successfully denied

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43008 - LOG\_ID\_EVENT\_AUTH\_SUCCESS

**Message ID:** 43008

**Message Description:** LOG\_ID\_EVENT\_AUTH\_SUCCESS

**Message Meaning:** Authentication success

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43009 - LOG\_ID\_EVENT\_AUTH\_FAILED

**Message ID:** 43009

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FAILED

**Message Meaning:** Authentication failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43010 - LOG\_ID\_EVENT\_AUTH\_LOCKOUT

**Message ID:** 43010

**Message Description:** LOG\_ID\_EVENT\_AUTH\_LOCKOUT

**Message Meaning:** Authentication lockout

**Type:** Event

**Category:** USER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43011 - LOG\_ID\_EVENT\_AUTH\_TIME\_OUT

**Message ID:** 43011

**Message Description:** LOG\_ID\_EVENT\_AUTH\_TIME\_OUT

**Message Meaning:** Authentication timed out

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
authserver		string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43014 - LOG\_ID\_EVENT\_AUTH\_FSAE\_LOGON

**Message ID:** 43014

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FSAE\_LOGON

**Message Meaning:** FSSO logon authentication status

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43015 - LOG\_ID\_EVENT\_AUTH\_FSAE\_LOGOFF

**Message ID:** 43015

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FSAE\_LOGOFF

**Message Meaning:** FSSO log off authentication status

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43016 - LOG\_ID\_EVENT\_AUTH\_NTLM\_AUTH\_SUCCESS

**Message ID:** 43016

**Message Description:** LOG\_ID\_EVENT\_AUTH\_NTLM\_AUTH\_SUCCESS

**Message Meaning:** NTLM authentication successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43017 - LOG\_ID\_EVENT\_AUTH\_NTLM\_AUTH\_FAIL

**Message ID:** 43017

**Message Description:** LOG\_ID\_EVENT\_AUTH\_NTLM\_AUTH\_FAIL

**Message Meaning:** NTLM authentication failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43018 - LOG\_ID\_EVENT\_AUTH\_FGOVRD\_FAIL

**Message ID:** 43018

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FGOVRD\_FAIL

**Message Meaning:** FortiGuard override failed

**Type:** Event

**Category:** USER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43020 - LOG\_ID\_EVENT\_AUTH\_FGOVRD\_SUCCESS

**Message ID:** 43020

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FGOVRD\_SUCCESS

**Message Meaning:** FortiGuard override successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
expiry	FortiGuard override expiry timestamp	string	64
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
oldwprof	Old Web Filter Profile	string	64
reason	Reason	string	256
scope	FortiGuard Override Scope	string	16
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43025 - LOG\_ID\_EVENT\_AUTH\_PROXY\_SUCCESS

**Message ID:** 43025

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_SUCCESS

**Message Meaning:** Explicit proxy authentication successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43026 - LOG\_ID\_EVENT\_AUTH\_PROXY\_FAILED

**Message ID:** 43026

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_FAILED

**Message Meaning:** Explicit proxy authentication failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43027 - LOG\_ID\_EVENT\_AUTH\_PROXY\_TIME\_OUT

**Message ID:** 43027

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_TIME\_OUT

**Message Meaning:** Explicit proxy authentication timed out

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43028 - LOG\_ID\_EVENT\_AUTH\_PROXY\_GROUP\_INFO\_FAILED

**Message ID:** 43028

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_GROUP\_INFO\_FAILED

**Message Meaning:** Explicit proxy user group query failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43029 - LOG\_ID\_EVENT\_AUTH\_WARNING\_SUCCESS

**Message ID:** 43029

**Message Description:** LOG\_ID\_EVENT\_AUTH\_WARNING\_SUCCESS

**Message Meaning:** FortiGuard authentication override successful

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
category		uint32	10
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
eventtime		uint64	20
expiry	FortiGuard override expiry timestamp	string	64
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
oldwprof	Old Web Filter Profile	string	64
reason	Reason	string	256
scope	FortiGuard Override Scope	string	16
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43030 - LOG\_ID\_EVENT\_AUTH\_WARNING\_TBL\_FULL

**Message ID:** 43030

**Message Description:** LOG\_ID\_EVENT\_AUTH\_WARNING\_TBL\_FULL

**Message Meaning:** FortiGuard authentication override failed

**Type:** Event

**Category:** USER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43032 - LOG\_ID\_EVENT\_AUTH\_PROXY\_USER\_LIMIT\_REACHED

**Message ID:** 43032

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_USER\_LIMIT\_REACHED

**Message Meaning:** Explicit proxy authentication user limit reached

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43033 - LOG\_ID\_EVENT\_AUTH\_PROXY\_MULTIPLE\_LOGIN

**Message ID:** 43033

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_MULTIPLE\_LOGIN

**Message Meaning:** Explicit proxy authentication user concurrent check failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43034 - LOG\_ID\_EVENT\_AUTH\_PROXY\_NO\_RESP

**Message ID:** 43034

**Message Description:** LOG\_ID\_EVENT\_AUTH\_PROXY\_NO\_RESP

**Message Meaning:** Explicit proxy authentication no response

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
agent		string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url		string	512
vd	Virtual Domain Name	string	32

## 43037 - LOG\_ID\_EVENT\_AUTH\_IPV4\_FLUSH

**Message ID:** 43037

**Message Description:** LOG\_ID\_EVENT\_AUTH\_IPV4\_FLUSH

**Message Meaning:** Authentication IPv4 logon flush

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43038 - LOG\_ID\_EVENT\_AUTH\_IPV6\_FLUSH

**Message ID:** 43038

**Message Description:** LOG\_ID\_EVENT\_AUTH\_IPV6\_FLUSH

**Message Meaning:** Authentication IPv6 logon flush

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43039 - LOG\_ID\_EVENT\_AUTH\_LOGON

**Message ID:** 43039

**Message Description:** LOG\_ID\_EVENT\_AUTH\_LOGON

**Message Meaning:** Authentication logon

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
authserver		string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43040 - LOG\_ID\_EVENT\_AUTH\_LOGOUT

**Message ID:** 43040

**Message Description:** LOG\_ID\_EVENT\_AUTH\_LOGOUT

**Message Meaning:** Authentication logout

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authserver		string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43041 - LOG\_ID\_EVENT\_AUTH\_DISCLAIMER\_ACCEPT

**Message ID:** 43041

**Message Description:** LOG\_ID\_EVENT\_AUTH\_DISCLAIMER\_ACCEPT

**Message Meaning:** Disclaimer accepted

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10



Log Field Name	Description	Data Type	Length
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43042 - LOG\_ID\_EVENT\_AUTH\_DISCLAIMER\_DECLINE

**Message ID:** 43042

**Message Description:** LOG\_ID\_EVENT\_AUTH\_DISCLAIMER\_DECLINE

**Message Meaning:** Disclaimer declined

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43043 - LOG\_ID\_EVENT\_AUTH\_EMAIL\_COLLECTING\_SUCCESS

**Message ID:** 43043

**Message Description:** LOG\_ID\_EVENT\_AUTH\_EMAIL\_COLLECTING\_SUCCESS

**Message Meaning:** Email collecting succeeded

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43044 - LOG\_ID\_EVENT\_AUTH\_EMAIL\_COLLECTING\_FAIL

**Message ID:** 43044

**Message Description:** LOG\_ID\_EVENT\_AUTH\_EMAIL\_COLLECTING\_FAIL

**Message Meaning:** Email collecting failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User Group Name	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43045 - LOG\_ID\_EVENT\_AUTH\_8021X\_SUCCESS

**Message ID:** 43045

**Message Description:** LOG\_ID\_EVENT\_AUTH\_8021X\_SUCCESS

**Message Meaning:** 802.1x authentication succeeded

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
stamac		string	17

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43046 - LOG\_ID\_EVENT\_AUTH\_8021X\_FAIL

**Message ID:** 43046

**Message Description:** LOG\_ID\_EVENT\_AUTH\_8021X\_FAIL

**Message Meaning:** 802.1x authentication failed

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
stamac		string	17
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43050 - LOG\_ID\_EVENT\_AUTH\_FSAE\_CONNECT

**Message ID:** 43050

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FSAE\_CONNECT

**Message Meaning:** FSSO server connected

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43051 - LOG\_ID\_EVENT\_AUTH\_FSAE\_DISCONNECT

**Message ID:** 43051

**Message Description:** LOG\_ID\_EVENT\_AUTH\_FSAE\_DISCONNECT

**Message Meaning:** FSSO server disconnected

**Type:** Event

**Category:** USER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43264 - LOGID\_MMS\_STATS

**Message ID:** 43264

**Message Description:** LOGID\_MMS\_STATS

**Message Meaning:** MMS statistics

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
checksum	for MMS Statistics	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
infected	Infected MMS	uint32	10
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msgproto	Message Protocol Number	string	16
scanned	Number of Scanned MMSs	uint32	10
subtype	Log Subtype	string	20
suspicious	Number of Suspicious MMSs	uint32	10
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43520 - LOG\_ID\_EVENT\_WIRELESS\_SYS

**Message ID:** 43520

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS

**Message Meaning:** Wireless system activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32



## 43521 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE

**Message ID:** 43521

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE

**Message Meaning:** Rogue AP activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3

Log Field Name	Description	Data Type	Length
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43522 - LOG\_ID\_EVENT\_WIRELESS\_WTP

**Message ID:** 43522

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP

**Message Meaning:** Physical AP activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43524 - LOG\_ID\_EVENT\_WIRELESS\_STA

**Message ID:** 43524

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA

**Message Meaning:** Wireless client activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43525 - LOG\_ID\_EVENT\_WIRELESS\_ONWIRE

**Message ID:** 43525

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ONWIRE

**Message Meaning:** Rogue AP on wire

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3

Log Field Name	Description	Data Type	Length
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43526 - LOG\_ID\_EVENT\_WIRELESS\_WTPR

**Message ID:** 43526

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR

**Message Meaning:** Physical AP radio activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43527 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG

**Message ID:** 43527

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG

**Message Meaning:** Rogue AP status configured

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43528 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_ERROR

**Message ID:** 43528

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_ERROR

**Message Meaning:** Physical AP radio error activity

**Type:** Event

**Category:** WIRELESS

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43529 - LOG\_ID\_EVENT\_WIRELESS\_CLB

**Message ID:** 43529

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_CLB

**Message Meaning:** Wireless client load balancing

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice



Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

## 43530 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_WL\_BRIDGE

**Message ID:** 43530

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_WL\_BRIDGE

**Message Meaning:** Wireless bridge intrusion detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threatype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43531 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_BR\_DEAUTH

**Message ID:** 43531

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_BR\_DEAUTH

**Message Meaning:** Wireless broadcasting deauthentication detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

**43532 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_NL\_PBRESP****Message ID:** 43532**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_NL\_PBRESP

**Message Meaning:** Wireless null SSID probe response detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43533 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_MAC\_OUI

**Message ID:** 43533

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_MAC\_OUI

**Message Meaning:** Wireless invalid MAC OUI detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
invalidmac	the MAC address with invalid OUI	string	17
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17

Log Field Name	Description	Data Type	Length
threatype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43534 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_LONG\_DUR

**Message ID:** 43534

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_LONG\_DUR

**Message Meaning:** Wireless long duration attack detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
duration	Duration of the last threatening packet captured from TA	uint32	10
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43535 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_WEP\_IV

**Message ID:** 43535

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_WEP\_IV

**Message Meaning:** Wireless Weak WEP IV detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsssi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
weakwepiv	Weak Wep Initiation Vector	string	8

## 43542 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_EAPOL\_FLOOD

**Message ID:** 43542

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_EAPOL\_FLOOD

**Message Meaning:** Wireless EAPOL packet flooding detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eapolcnt	EAPOL packet count	uint32	10
eapoltype	EAPOL packet type	string	16



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43544 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_MGMT\_FLOOD

**Message ID:** 43544

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_MGMT\_FLOOD

**Message Meaning:** Wireless management flooding detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
ds	direction with distribution system	string	8
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
mgmtcnt	The number of unauthorized client flooding managemet frames	uint32	10
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsssi	Received signal strength indicator	uint8	3
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43546 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_SPOOF\_DEAUTH

**Message ID:** 43546

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_SPOOF\_DEAUTH

**Message Meaning:** Wireless spoofed deauthentication detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10

Log Field Name	Description	Data Type	Length
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43548 - LOG\_ID\_EVENT\_WIRELESS\_WIDS\_ASLEAP

**Message ID:** 43548

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WIDS\_ASLEAP

**Message Meaning:** Wireless Asleep attack detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43550 - LOG\_ID\_EVENT\_WIRELESS\_STA\_LOCATE

**Message ID:** 43550

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_LOCATE

**Message Meaning:** Wireless station presence detection

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
noise		int8	4
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
signal	Signal	int8	4
sn	Serial Number	string	64
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43551 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_JOIN

**Message ID:** 43551

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_JOIN

**Message Meaning:** Physical AP join

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43552 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_LEAVE

**Message ID:** 43552

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_LEAVE

**Message Meaning:** Physical AP leave

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43553 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_FAIL

**Message ID:** 43553

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_FAIL

**Message Meaning:** Physical AP fail

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43554 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_UPDATE

**Message ID:** 43554

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_UPDATE

**Message Meaning:** Physical AP update

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39



Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43555 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_RESET

**Message ID:** 43555

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_RESET

**Message Meaning:** Physical AP reset

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43556 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_KICK

**Message ID:** 43556

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_KICK

**Message Meaning:** Physical AP kick

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43557 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD\_FAILURE

**Message ID:** 43557

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD\_FAILURE

**Message Meaning:** Physical AP add failure

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43558 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_CFG\_ERR

**Message ID:** 43558

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_CFG\_ERR

**Message Meaning:** Physical AP config error

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43559 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_SN\_MISMATCH

**Message ID:** 43559

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_SN\_MISMATCH

**Message Meaning:** Physical AP SN mismatch

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43560 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_RESTARTED

**Message ID:** 43560

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_RESTARTED

**Message Meaning:** Wireless system restarted

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43561 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_HOSTAPD\_UP

**Message ID:** 43561

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_HOSTAPD\_UP

**Message Meaning:** Wireless system hostapd up

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43562 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_HOSTAPD\_DOWN

**Message ID:** 43562

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_HOSTAPD\_DOWN

**Message Meaning:** Wireless system hostapd down

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43563 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_DETECT

**Message ID:** 43563

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_DETECT

**Message Meaning:** Rogue AP detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20



Log Field Name	Description	Data Type	Length
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43564 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_OFFAIR

**Message ID:** 43564

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_OFFAIR

**Message Meaning:** Rogue AP off air

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36

Log Field Name	Description	Data Type	Length
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43565 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_ONAIR

**Message ID:** 43565

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_ONAIR

**Message Meaning:** Rogue AP on air

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4

Log Field Name	Description	Data Type	Length
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43566 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_OFFWIRE

**Message ID:** 43566

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_OFFWIRE

**Message Meaning:** Rogue AP off wire

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3

Log Field Name	Description	Data Type	Length
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43567 - LOG\_ID\_EVENT\_WIRELESS\_FAKEAP\_DETECT

**Message ID:** 43567

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_FAKEAP\_DETECT

**Message Meaning:** Fake AP detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3

Log Field Name	Description	Data Type	Length
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43568 - LOG\_ID\_EVENT\_WIRELESS\_FAKEAP\_ONAIR

**Message ID:** 43568

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_FAKEAP\_ONAIR

**Message Meaning:** Fake AP on air

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43569 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_SUPPRESSED

**Message ID:** 43569

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_SUPPRESSED

**Message Meaning:** Rogue AP suppressed



**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36

Log Field Name	Description	Data Type	Length
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43570 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_UNSUPPRESSED

**Message ID:** 43570

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_UNSUPPRESSED

**Message Meaning:** Rogue AP unsuppressed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43571 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_DETECT\_CHG

**Message ID:** 43571

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_DETECT\_CHG

**Message Meaning:** Rogue AP change detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint16	6
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10

Log Field Name	Description	Data Type	Length
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43572 - LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSO

**Message ID:** 43572

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_ASSO

**Message Meaning:** Wireless client associated

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43573 - LOG\_ID\_EVENT\_WIRELESS\_STA\_AUTH

**Message ID:** 43573

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_AUTH

**Message Meaning:** Wireless client authenticated

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43574 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DASS

**Message ID:** 43574

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DASS

**Message Meaning:** Wireless client disassociated

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43575 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DAUT

**Message ID:** 43575

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DAUT

**Message Meaning:** Wireless client deauthenticated

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice



Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43576 - LOG\_ID\_EVENT\_WIRELESS\_STA\_IDLE

**Message ID:** 43576

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_IDLE

**Message Meaning:** Wireless client idle

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43577 - LOG\_ID\_EVENT\_WIRELESS\_STA\_DENY

**Message ID:** 43577

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_DENY

**Message Meaning:** Wireless client denied

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43578 - LOG\_ID\_EVENT\_WIRELESS\_STA\_KICK

**Message ID:** 43578

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_KICK

**Message Meaning:** Wireless client kicked

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43579 - LOG\_ID\_EVENT\_WIRELESS\_STA\_IP

**Message ID:** 43579

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_IP

**Message Meaning:** Wireless client IP assigned

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43580 - LOG\_ID\_EVENT\_WIRELESS\_STA\_LEAVE\_WTP

**Message ID:** 43580

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_LEAVE\_WTP

**Message Meaning:** Wireless client left WTP

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43581 - LOG\_ID\_EVENT\_WIRELESS\_STA\_WTP\_DISCONN

**Message ID:** 43581

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_WTP\_DISCONN

**Message Meaning:** Wireless client WTP disconnected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43582 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_UNCLASSIFIED

**Message ID:** 43582

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_UNCLASSIFIED



**Message Meaning:** Rogue AP status configured as unclassified

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43583 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_ACCEPTED

**Message ID:** 43583

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_ACCEPTED

**Message Meaning:** Rogue AP status configured as accepted

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3

Log Field Name	Description	Data Type	Length
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43584 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_ROGUE

**Message ID:** 43584

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_ROGUE

**Message Meaning:** Rogue AP status configured as rogue

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43585 - LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_SUPPRESSED

**Message ID:** 43585

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_ROGUE\_CFG\_SUPPRESSED

**Message Meaning:** Rogue AP status configured as suppressed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43586 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_CHAN

**Message ID:** 43586

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_CHAN

**Message Meaning:** Physical AP radio DARRP channel change

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43587 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_START

**Message ID:** 43587

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_START

**Message Meaning:** Physical AP radio DARRP start

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43588 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_CHAN

**Message ID:** 43588

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_CHAN

**Message Meaning:** Physical AP radio operation channel change

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43589 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_RADAR

**Message ID:** 43589

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_RADAR

**Message Meaning:** Physical AP radio radar detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43590 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_NOL

**Message ID:** 43590

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_NOL

**Message Meaning:** Physical AP radio channel removed from NOL

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32



## 43591 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_COUNTRY\_CFG\_SUCCESS

**Message ID:** 43591

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_COUNTRY\_CFG\_SUCCESS

**Message Meaning:** Physical AP radio country config success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43592 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_COUNTRY

**Message ID:** 43592

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_COUNTRY

**Message Meaning:** Physical AP radio operation country

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43593 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_CFG\_TXPOWER

**Message ID:** 43593

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_CFG\_TXPOWER

**Message Meaning:** Physical AP radio config TX power

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43594 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_TXPOWER

**Message ID:** 43594

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_OPER\_TXPOWER

**Message Meaning:** Physical AP radio operation TX power

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43595 - LOG\_ID\_EVENT\_WIRELESS\_CLB\_DENY

**Message ID:** 43595

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_CLB\_DENY

**Message Meaning:** Wireless client load balancing denied

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

## 43596 - LOG\_ID\_EVENT\_WIRELESS\_CLB\_RETRY

**Message ID:** 43596

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_CLB\_RETRY

**Message Meaning:** Wireless client load balancing retry

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

## 43597 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD

**Message ID:** 43597

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD

**Message Meaning:** Physical AP add

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43598 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD\_XSS

**Message ID:** 43598

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_ADD\_XSS

**Message Meaning:** Physical AP add XSS

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43599 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_DEL

**Message ID:** 43599

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_DEL

**Message Meaning:** Physical AP delete

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16



Log Field Name	Description	Data Type	Length
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43600 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_STOP

**Message ID:** 43600

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_DARRP\_STOP

**Message Meaning:** Physical AP radio DARRP stop

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43601 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON

**Message ID:** 43601

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON

**Message Meaning:** Wireless station sign on

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43602 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON\_SUCCESS

**Message ID:** 43602

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON\_SUCCESS

**Message Meaning:** Wireless station sign on success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43603 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON\_FAILURE

**Message ID:** 43603

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_SIGNON\_FAILURE

**Message Meaning:** Wireless station sign on failed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43604 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_REQUEST

**Message ID:** 43604

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_REQUEST

**Message Meaning:** Captive-portal VAP e-mail collect request sent

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43605 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_SUCCESS

**Message ID:** 43605

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_SUCCESS

**Message Meaning:** Captive-portal VAP e-mail collect success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43606 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_FAILURE

**Message ID:** 43606

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_EMAIL\_FAILURE

**Message Meaning:** Captive-portal VAP e-mail collect failed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10



Log Field Name	Description	Data Type	Length
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43607 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_DISCLAIMER\_CHECK

**Message ID:** 43607

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_DISCLAIMER\_CHECK

**Message Meaning:** Captive-portal VAP disclaimer agreed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43608 - LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_DISCLAIMER\_DECLINE

**Message ID:** 43608

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_STA\_CAP\_DISCLAIMER\_DECLINE

**Message Meaning:** Captive-portal VAP disclaimer declined

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

## 43609 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_DARRP\_START

**Message ID:** 43609

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_DARRP\_START

**Message Meaning:** DARRP optimization start

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43610 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_DARRP\_STOP

**Message ID:** 43610

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_DARRP\_STOP

**Message Meaning:** DARRP optimization stop

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43611 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_UP

**Message ID:** 43611

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_UP

**Message Meaning:** Wireless controller start

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43612 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_CFG\_LOADED

**Message ID:** 43612

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_CFG\_LOADED

**Message Meaning:** Wireless controller configuration loaded

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43613 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_ERR

**Message ID:** 43613

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_ERR

**Message Meaning:** Physical AP error

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43614 - LOG\_ID\_EVENT\_WIRELESS\_DHCP\_STAVATION

**Message ID:** 43614

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_DHCP\_STAVATION

**Message Meaning:** DHCP Starvation detected

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
client_addr		string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
source_mac		string	17
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vapmode		string	17
vd	Virtual Domain Name	string	32
xid		uint32	10

## 43615 - LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_IPSEC\_FAIL

**Message ID:** 43615

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_SYS\_AC\_IPSEC\_FAIL

**Message Meaning:** Wireless controller IPsec setup failed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10



Log Field Name	Description	Data Type	Length
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43616 - LOG\_ID\_EVENT\_WIRELESS\_WTPR\_NOL\_ADD

**Message ID:** 43616

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPR\_NOL\_ADD

**Message Meaning:** Physical AP radio NOL added

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43617 - LOG\_ID\_EVENT\_WIRELESS\_WTPPROF\_ADJUSTED

**Message ID:** 43617

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTPPROF\_ADJUSTED

**Message Meaning:** Wireless WTP profile has been adjusted

**Type:** Event

**Category:** WIRELESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43618 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_IMAGE\_RC\_SUCCESS

**Message ID:** 43618

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_IMAGE\_RC\_SUCCESS

**Message Meaning:** Physical AP image receive success

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43621 - LOG\_ID\_EVENT\_WIRELESS\_WTP\_DATA\_CHAN\_CHG

**Message ID:** 43621

**Message Description:** LOG\_ID\_EVENT\_WIRELESS\_WTP\_DATA\_CHAN\_CHG

**Message Meaning:** Wireless wtp data channel changed

**Type:** Event

**Category:** WIRELESS

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43776 - LOG\_ID\_EVENT\_NAC\_QUARANTINE

**Message ID:** 43776

**Message Description:** LOG\_ID\_EVENT\_NAC\_QUARANTINE

**Message Meaning:** NAC quarantine

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
admin		string	64
banned_rule	NAC quarantine Banned Rule Name	string	80
banned_src	NAC quarantine Banned Source IP	string	16
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
sensor	NAC Sensor Name	string	36
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43777 - LOG\_ID\_EVENT\_NAC\_ANOMALY\_QUARANTINE

**Message ID:** 43777

**Message Description:** LOG\_ID\_EVENT\_NAC\_ANOMALY\_QUARANTINE

**Message Meaning:** NAC anomaly quarantine

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
admin		string	64
banned_rule	NAC quarantine Banned Rule Name	string	80
banned_src	NAC quarantine Banned Source IP	string	16
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
sensor	NAC Sensor Name	string	36
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 43800 - LOG\_ID\_EVENT\_ELBC\_BLADE\_JOIN

**Message ID:** 43800

**Message Description:** LOG\_ID\_EVENT\_ELBC\_BLADE\_JOIN

**Message Meaning:** Blade ready to process traffic

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43801 - LOG\_ID\_EVENT\_ELBC\_BLADE\_LEAVE

**Message ID:** 43801

**Message Description:** LOG\_ID\_EVENT\_ELBC\_BLADE\_LEAVE

**Message Meaning:** Blade not ready to process traffic

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43802 - LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_FOUND

**Message ID:** 43802

**Message Description:** LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_FOUND

**Message Meaning:** Master blade found

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10



Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43803 - LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_LOST

**Message ID:** 43803

**Message Description:** LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_LOST

**Message Meaning:** Master blade lost

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43804 - LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_CHANGE

**Message ID:** 43804

**Message Description:** LOG\_ID\_EVENT\_ELBC\_MASTER\_BLADE\_CHANGE

**Message Meaning:** Master blade changed

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchassisid	New Chassis ID	uint8	
newslot	New Slot Number	uint8	
oldchassisid	Original Chassis Number	uint8	
oldslot	Original Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43805 - LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_FOUND

**Message ID:** 43805

**Message Description:** LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_FOUND

**Message Meaning:** ELBC channel active

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchannel	New Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43806 - LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_LOST

**Message ID:** 43806

**Message Description:** LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_LOST

**Message Meaning:** ELBC channel inactive

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
oldchannel	Original Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43807 - LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_CHANGE

**Message ID:** 43807

**Message Description:** LOG\_ID\_EVENT\_ELBC\_ACTIVE\_CHANNEL\_CHANGE

**Message Meaning:** ELBC channel failover

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchannel	New Channel Number	uint8	
oldchannel	Original Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43808 - LOG\_ID\_EVENT\_ELBC\_CHASSIS\_ACTIVE

**Message ID:** 43808

**Message Description:** LOG\_ID\_EVENT\_ELBC\_CHASSIS\_ACTIVE

**Message Meaning:** ELBC chassis active

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 43809 - LOG\_ID\_EVENT\_ELBC\_CHASSIS\_INACTIVE

**Message ID:** 43809

**Message Description:** LOG\_ID\_EVENT\_ELBC\_CHASSIS\_INACTIVE

**Message Meaning:** ELBC chassis inactive

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 44544 - LOGID\_EVENT\_CONFIG\_PATH

**Message ID:** 44544

**Message Description:** LOGID\_EVENT\_CONFIG\_PATH

**Message Meaning:** Path configured

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44545 - LOGID\_EVENT\_CONFIG\_OBJ

**Message ID:** 44545

**Message Description:** LOGID\_EVENT\_CONFIG\_OBJ

**Message Meaning:** Object configured

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44546 - LOGID\_EVENT\_CONFIG\_ATTR

**Message ID:** 44546

**Message Description:** LOGID\_EVENT\_CONFIG\_ATTR

**Message Meaning:** Attribute configured

**Type:** Event

**Category:** SYSTEM

**Severity:** Information



Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44547 - LOGID\_EVENT\_CONFIG\_OBJATTR

**Message ID:** 44547

**Message Description:** LOGID\_EVENT\_CONFIG\_OBJATTR

**Message Meaning:** Object attribute configured

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128

Log Field Name	Description	Data Type	Length
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44548 - LOGID\_EVENT\_CONFIG\_EXEC

**Message ID:** 44548

**Message Description:** LOGID\_EVENT\_CONFIG\_EXEC

**Message Meaning:** Action performed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44549 - LOGID\_EVENT\_CONFIG\_OBJATTR\_MTNER

**Message ID:** 44549

**Message Description:** LOGID\_EVENT\_CONFIG\_OBJATTR\_MTNER

**Message Meaning:** Object attribute configured by maintainer

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44550 - LOGID\_EVENT\_CONFIG\_OBJ\_MTNER

**Message ID:** 44550

**Message Description:** LOGID\_EVENT\_CONFIG\_OBJ\_MTNER

**Message Meaning:** Object configured by maintainer

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44551 - LOGID\_EVENT\_CONFIG\_ATTR\_MTNER

**Message ID:** 44551

**Message Description:** LOGID\_EVENT\_CONFIG\_ATTR\_MTNER

**Message Meaning:** Attribute configured by maintainer

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44552 - LOGID\_EVENT\_CONFIG\_PATH\_MTNER

**Message ID:** 44552

**Message Description:** LOGID\_EVENT\_CONFIG\_PATH\_MTNER

**Message Meaning:** Path configured by maintainer

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 44553 - LOGID\_EVENT\_CONFIG\_FIXEDPORT\_DIS

**Message ID:** 44553

**Message Description:** LOGID\_EVENT\_CONFIG\_FIXEDPORT\_DIS

**Message Meaning:** Policy attribute fixed port changed during upgrade

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45057 - LOG\_ID\_FCC\_ADD

**Message ID:** 45057

**Message Description:** LOG\_ID\_FCC\_ADD

**Message Meaning:** FortiClient connection added

**Type:** Event

**Category:** ENDPOINT

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	EndPoint Action	string	32
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
ip	Source IP	ip	39
level	Log Level	string	11
license_limit	Maximum Number of FortiClients for the License	string	32
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
name	Display Name of the Connection	string	128
status	Status	string	23
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
used_for_type	Connection for the type	uint32	10
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45058 - LOG\_ID\_FCC\_CLOSE

**Message ID:** 45058

**Message Description:** LOG\_ID\_FCC\_CLOSE

**Message Meaning:** FortiClient connection closed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45061 - LOG\_ID\_FCC\_CLOSE\_BY\_TYPE

**Message ID:** 45061



**Message Description:** LOG\_ID\_FCC\_CLOSE\_BY\_TYPE

**Message Meaning:** FortiClient connection closed by type

**Type:** Event

**Category:** ENDPOINT

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	EndPoint Action	string	32
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
ip	Source IP	ip	39
level	Log Level	string	11
license_limit	Maximum Number of FortiClients for the License	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
name	Display Name of the Connection	string	128
status	Status	string	23
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
used_for_type	Connection for the type	uint32	10
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45071 - LOG\_ID\_FCC\_VULN\_SCAN

**Message ID:** 45071

**Message Description:** LOG\_ID\_FCC\_VULN\_SCAN

**Message Meaning:** FortiClient Vulnerability Scan

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
cveid	CVE ID	string	720
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
scantime		uint64	20
severity		string	10
srcip		ip	39
srcmac		string	17
srcname		string	64
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vendorurl		string	256
vulncat	Vulnerability Category	string	32
vulnid		uint32	10
vulnname		string	128

## 45081 - LOG\_ID\_FCC\_COMPL\_CHANGE

**Message ID:** 45081

**Message Description:** LOG\_ID\_FCC\_COMPL\_CHANGE

**Message Meaning:** FortiClient compliance state changed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
srcip		ip	39
srcmac		string	17
srcname		string	64
srcport		uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45082 - LOG\_ID\_FCC\_NOT\_COMPL

**Message ID:** 45082

**Message Description:** LOG\_ID\_FCC\_NOT\_COMPL

**Message Meaning:** FortiClient not compliant

**Type:** Event

**Category:** ENDPOINT

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
srcip		ip	39
srcmac		string	17
srcport		uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45083 - LOG\_ID\_FCC\_NOT\_COMPL\_DEBUG

**Message ID:** 45083

**Message Description:** LOG\_ID\_FCC\_NOT\_COMPL\_DEBUG

**Message Meaning:** FortiClient not compliant debug message

**Type:** Event

**Category:** ENDPOINT

**Severity:** Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
devtype		string	32
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
srcip		ip	39
srcmac		string	17
srcport		uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45084 - LOG\_ID\_FCC\_SIG\_IDS\_DETAILS

**Message ID:** 45084

**Message Description:** LOG\_ID\_FCC\_SIG\_IDS\_DETAILS

**Message Meaning:** FortiClient signatures details

**Type:** Event

**Category:** ENDPOINT

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
srcip		ip	39
srcmac		string	17
srcname		string	64
srcport		uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45100 - LOG\_ID\_EC\_REG\_FAIL\_LIMIT

**Message ID:** 45100

**Message Description:** LOG\_ID\_EC\_REG\_FAIL\_LIMIT

**Message Meaning:** FortiClient registration failed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45101 - LOG\_ID\_EC\_REG\_SUCCEED

**Message ID:** 45101

**Message Description:** LOG\_ID\_EC\_REG\_SUCCEED

**Message Meaning:** FortiClient registered

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45102 - LOG\_ID\_EC\_REG\_RENEWED

**Message ID:** 45102

**Message Description:** LOG\_ID\_EC\_REG\_RENEWED

**Message Meaning:** FortiClient registration renewed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16



Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45103 - LOG\_ID\_EC\_REG\_BLOCK

**Message ID:** 45103

**Message Description:** LOG\_ID\_EC\_REG\_BLOCK

**Message Meaning:** FortiClient registration blocked

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45104 - LOG\_ID\_EC\_REG\_UNBLOCK

**Message ID:** 45104

**Message Description:** LOG\_ID\_EC\_REG\_UNBLOCK

**Message Meaning:** FortiClient registration unblocked

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45105 - LOG\_ID\_EC\_REG\_DEREG

**Message ID:** 45105

**Message Description:** LOG\_ID\_EC\_REG\_DEREG

**Message Meaning:** FortiClient deregistered

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45106 - LOG\_ID\_EC\_REG\_LIC\_UPGRADED

**Message ID:** 45106

**Message Description:** LOG\_ID\_EC\_REG\_LIC\_UPGRADED

**Message Meaning:** FortiClient registration license upgraded

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45107 - LOG\_ID\_EC\_CONF\_DISTRIBUTED

**Message ID:** 45107

**Message Description:** LOG\_ID\_EC\_CONF\_DISTRIBUTED

**Message Meaning:** FortiClient configuration distributed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45108 - LOG\_ID\_EC\_FTCL\_UNREG

**Message ID:** 45108

**Message Description:** LOG\_ID\_EC\_FTCL\_UNREG

**Message Meaning:** FortiClient unregistered

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32

Log Field Name	Description	Data Type	Length
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45109 - LOG\_ID\_EC\_FTCL\_LOGOFF

**Message ID:** 45109

**Message Description:** LOG\_ID\_EC\_FTCL\_LOGOFF

**Message Meaning:** FortiClient logged off

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45110 - LOG\_ID\_EC\_FTCL\_ENABLE\_NOTSYNC

**Message ID:** 45110

**Message Description:** LOG\_ID\_EC\_FTCL\_ENABLE\_NOTSYNC

**Message Meaning:** FortiClient synchronization disabled

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45111 - LOG\_ID\_EC\_REG\_SYNC\_FAIL

**Message ID:** 45111

**Message Description:** LOG\_ID\_EC\_REG\_SYNC\_FAIL

**Message Meaning:** FortiClient synchronization failed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45112 - LOG\_ID\_EC\_REG\_FAIL\_KEY

**Message ID:** 45112

**Message Description:** LOG\_ID\_EC\_REG\_FAIL\_KEY

**Message Meaning:** FortiClient registration failed due to wrong registration key

**Type:** Event

**Category:** ENDPOINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45113 - LOG\_ID\_EC\_REG\_FAIL\_BLOCKED

**Message ID:** 45113

**Message Description:** LOG\_ID\_EC\_REG\_FAIL\_BLOCKED

**Message Meaning:** FortiClient registration failed due to blocked UID

**Type:** Event

**Category:** ENDPOINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32



Log Field Name	Description	Data Type	Length
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45114 - LOG\_ID\_EC\_REG\_QUARANTINE

**Message ID:** 45114

**Message Description:** LOG\_ID\_EC\_REG\_QUARANTINE

**Message Meaning:** FortiClient endpoint quarantined

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45115 - LOG\_ID\_EC\_REG\_UNQUARANTINE

**Message ID:** 45115

**Message Description:** LOG\_ID\_EC\_REG\_UNQUARANTINE

**Message Meaning:** FortiClient endpoint quarantine removed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45116 - LOG\_ID\_EC\_REG\_UNQUARANTINE\_ALL

**Message ID:** 45116

**Message Description:** LOG\_ID\_EC\_REG\_UNQUARANTINE\_ALL

**Message Meaning:** All FortiClient endpoint quarantines removed

**Type:** Event

**Category:** ENDPOINT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45117 - LOG\_ID\_EC\_REG\_FAIL\_VER

**Message ID:** 45117

**Message Description:** LOG\_ID\_EC\_REG\_FAIL\_VER

**Message Meaning:** FortiClient registration failed due to version too low

**Type:** Event

**Category:** ENDPOINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128

Log Field Name	Description	Data Type	Length
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45118 - LOG\_ID\_EC\_REG\_FAIL\_UNSUPPORTED

**Message ID:** 45118

**Message Description:** LOG\_ID\_EC\_REG\_FAIL\_UNSUPPORTED

**Message Meaning:** FortiClient registration failed due to unsupported route

**Type:** Event

**Category:** ENDPOINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 45151 - LOG\_ID\_EVENT\_DSSCC\_FAIL

**Message ID:** 45151

**Message Description:** LOG\_ID\_EVENT\_DSSCC\_FAIL

**Message Meaning:** PCI DSS compliance check failed

**Type:** Event

**Category:** COMPLIANCE-CHECK

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Module	string	32
msg	Log Message	string	
reason	Reason	string	256
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45152 - LOG\_ID\_EVENT\_DSSCC\_PASS

**Message ID:** 45152

**Message Description:** LOG\_ID\_EVENT\_DSSCC\_PASS

**Message Meaning:** PCI DSS compliance check passed

**Type:** Event

**Category:** COMPLIANCE-CHECK

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Module	string	32
msg	Log Message	string	
reason	Reason	string	256
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 45161 - LOG\_ID\_EVENT\_DSSCC\_EXEC

**Message ID:** 45161

**Message Description:** LOG\_ID\_EVENT\_DSSCC\_EXEC

**Message Meaning:** PCI DSS compliance check executed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 46000 - LOG\_ID\_VIP\_REAL\_SVR\_ENA

**Message ID:** 46000

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_ENA

**Message Meaning:** VIP real server enabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46001 - LOG\_ID\_VIP\_REAL\_SVR\_DISA

**Message ID:** 46001

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_DISA

**Message Meaning:** VIP real server disabled

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46002 - LOG\_ID\_VIP\_REAL\_SVR\_UP

**Message ID:** 46002

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_UP

**Message Meaning:** VIP real server up

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46003 - LOG\_ID\_VIP\_REAL\_SVR\_DOWN

**Message ID:** 46003

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_DOWN

**Message Meaning:** VIP real server down

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46004 - LOG\_ID\_VIP\_REAL\_SVR\_ENT\_HOLDDOWN

**Message ID:** 46004

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_ENT\_HOLDDOWN

**Message Meaning:** VIP real server entered hold-down

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46005 - LOG\_ID\_VIP\_REAL\_SVR\_FAIL\_HOLDDOWN

**Message ID:** 46005

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_FAIL\_HOLDDOWN

**Message Meaning:** VIP real server health check failed during hold-down

**Type:** Event

**Category:** SYSTEM

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46006 - LOG\_ID\_VIP\_REAL\_SVR\_FAIL

**Message ID:** 46006

**Message Description:** LOG\_ID\_VIP\_REAL\_SVR\_FAIL

**Message Meaning:** VIP real server health check failed

**Type:** Event

**Category:** SYSTEM

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
monitor-name	Health Monitor Type	string	35
monitor-type	Health Monitor Name	string	32
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

## 46400 - LOG\_ID\_EVENT\_EXT\_SYS

**Message ID:** 46400

**Message Description:** LOG\_ID\_EVENT\_EXT\_SYS

**Message Meaning:** FortiExtender system activity

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46401 - LOG\_ID\_EVENT\_EXT\_LOCAL

**Message ID:** 46401

**Message Description:** LOG\_ID\_EVENT\_EXT\_LOCAL

**Message Meaning:** FortiExtender AC activity

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46402 - LOG\_ID\_EVENT\_EXT\_REMOTE

**Message ID:** 46402

**Message Description:** LOG\_ID\_EVENT\_EXT\_REMOTE

**Message Meaning:** Remote FortiExtender activity

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46403 - LOG\_ID\_EVENT\_EXT\_LOCAL\_ERROR

**Message ID:** 46403

**Message Description:** LOG\_ID\_EVENT\_EXT\_LOCAL\_ERROR

**Message Meaning:** FortiExtender AC activity error

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46501 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_DETECTION

**Message ID:** 46501

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_DETECTION

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46502 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_GPSD

**Message ID:** 46502

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_GPSD

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM



**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46503 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_GPS\_LOC\_ACQUISITION

**Message ID:** 46503

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_GPS\_LOC\_ACQUISITION

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46504 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLD

**Message ID:** 46504

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLD

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46505 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLING\_PURGED

**Message ID:** 46505

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLING\_PURGED

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46506 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLING\_DAILY\_LOG

**Message ID:** 46506

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_BILLING\_DAILY\_LOG

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46507 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_FW\_UPGRADE

**Message ID:** 46507

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_FW\_UPGRADE

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46508 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_QDL\_DETECTION

**Message ID:** 46508

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_QDL\_DETECTION

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46509 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_REBOOT

**Message ID:** 46509

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_REBOOT

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46510 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_OP\_MODE

**Message ID:** 46510

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_OP\_MODE

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46511 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_POWER\_ON\_OFF

**Message ID:** 46511

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_POWER\_ON\_OFF

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46512 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_SIM\_STATE

**Message ID:** 46512

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_SIM\_STATE

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46513 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_LINK\_CONNECTION

**Message ID:** 46513

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_LINK\_CONNECTION

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46514 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_MANUAL\_HANOVER

**Message ID:** 46514

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_MANUAL\_HANOVER

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	



Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46515 - LOG\_ID\_INTERNAL\_LTE\_MODEM\_IP\_ADDR

**Message ID:** 46515

**Message Description:** LOG\_ID\_INTERNAL\_LTE\_MODEM\_IP\_ADDR

**Message Meaning:** Log description is not available

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46600 - LOG\_ID\_EVENT\_AUTOMATION\_TRIGGERED

**Message ID:** 46600

**Message Description:** LOG\_ID\_EVENT\_AUTOMATION\_TRIGGERED

**Message Meaning:** Automation stitch triggered

**Type:** Event

**Category:** SYSTEM

**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
stitch		string	36
subtype	Log Subtype	string	20
time	Time	string	8
trigger		string	36
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 46900 - LOG\_ID\_POE\_STATUS\_REPORT

**Message ID:** 46900

**Message Description:** LOG\_ID\_POE\_STATUS\_REPORT

**Message Meaning:** PoE device status reported

**Type:** Event

**Category:** SYSTEM

**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 47203 - LOG\_ID\_ENTER\_BYPASS

**Message ID:** 47203

**Message Description:** LOG\_ID\_ENTER\_BYPASS

**Message Meaning:** Bypass ports pair entered bypass mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency, Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 47204 - LOG\_ID\_EXIT\_BYPASS

**Message ID:** 47204

**Message Description:** LOG\_ID\_EXIT\_BYPASS

**Message Meaning:** Bypass ports pair exited bypass mode

**Type:** Event

**Category:** SYSTEM

**Severity:** Emergency, Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48000 - LOG\_ID\_WAD\_SSL\_RCV\_HS

**Message ID:** 48000

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_HS

**Message Meaning:** SSL handshake received

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48001 - LOG\_ID\_WAD\_SSL\_RCV\_WRG\_HS

**Message ID:** 48001

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_WRG\_HS

**Message Meaning:** SSL handshake message incorrect

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48002 - LOG\_ID\_WAD\_SSL\_SENT\_HS

**Message ID:** 48002

**Message Description:** LOG\_ID\_WAD\_SSL\_SENT\_HS

**Message Meaning:** SSL handshake sent

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48003 - LOG\_ID\_WAD\_SSL\_WRG\_HS\_LEN

**Message ID:** 48003

**Message Description:** LOG\_ID\_WAD\_SSL\_WRG\_HS\_LEN

**Message Meaning:** SSL handshake length invalid

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48004 - LOG\_ID\_WAD\_SSL\_RCV\_CCS

**Message ID:** 48004

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_CCS

**Message Meaning:** SSL ChangeCipherSpec received

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32



## 48005 - LOG\_ID\_WAD\_SSL\_RSA\_DH\_FAIL

**Message ID:** 48005

**Message Description:** LOG\_ID\_WAD\_SSL\_RSA\_DH\_FAIL

**Message Meaning:** RSA verification of Diffie-Hellman parameters failed

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48006 - LOG\_ID\_WAD\_SSL\_SENT\_CCS

**Message ID:** 48006

**Message Description:** LOG\_ID\_WAD\_SSL\_SENT\_CCS

**Message Meaning:** SSL ChangeCipherSpec sent

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48007 - LOG\_ID\_WAD\_SSL\_BAD\_HASH

**Message ID:** 48007

**Message Description:** LOG\_ID\_WAD\_SSL\_BAD\_HASH

**Message Meaning:** SSL Finished hash mismatch

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
ssllocal		string	76
sslremote		string	76
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48009 - LOG\_ID\_WAD\_SSL\_DECRY\_FAIL

**Message ID:** 48009

**Message Description:** LOG\_ID\_WAD\_SSL\_DECRY\_FAIL

**Message Meaning:** SSL decryption failed

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48011 - LOG\_ID\_WAD\_SSL\_LESS\_MINOR

**Message ID:** 48011

**Message Description:** LOG\_ID\_WAD\_SSL\_LESS\_MINOR

**Message Meaning:** SSL minor version less than configured minimum value

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48013 - LOG\_ID\_WAD\_SSL\_NOT\_SUPPORT\_CS

**Message ID:** 48013

**Message Description:** LOG\_ID\_WAD\_SSL\_NOT\_SUPPORT\_CS

**Message Meaning:** SSL Cipher Suites not supported

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48016 - LOG\_ID\_WAD\_SSL\_HS\_FIN

**Message ID:** 48016

**Message Description:** LOG\_ID\_WAD\_SSL\_HS\_FIN

**Message Meaning:** SSL handshake completed

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48017 - LOG\_ID\_WAD\_SSL\_HS\_TOO\_LONG

**Message ID:** 48017

**Message Description:** LOG\_ID\_WAD\_SSL\_HS\_TOO\_LONG

**Message Meaning:** SSL handshake too long

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48019 - LOG\_ID\_WAD\_SSL\_SENT\_ALERT

**Message ID:** 48019

**Message Description:** LOG\_ID\_WAD\_SSL\_SENT\_ALERT

**Message Meaning:** SSL alert sent

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5



Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48023 - LOG\_ID\_WAD\_SSL\_RCV\_ALERT

**Message ID:** 48023

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_ALERT

**Message Meaning:** SSL alert received

**Type:** Event

**Category:** WAD

**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48027 - LOG\_ID\_WAD\_SSL\_INVALID\_CONT\_TYPE

**Message ID:** 48027

**Message Description:** LOG\_ID\_WAD\_SSL\_INVALID\_CONT\_TYPE

**Message Meaning:** SSL Content Type invalid

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48029 - LOG\_ID\_WAD\_SSL\_BAD\_CCS\_LEN

**Message ID:** 48029

**Message Description:** LOG\_ID\_WAD\_SSL\_BAD\_CCS\_LEN

**Message Meaning:** SSL ChangeCipherSpec length invalid

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48031 - LOG\_ID\_WAD\_SSL\_BAD\_DH

**Message ID:** 48031

**Message Description:** LOG\_ID\_WAD\_SSL\_BAD\_DH

**Message Meaning:** SSL Diffie-Hellman value invalid

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48032 - LOG\_ID\_WAD\_SSL\_PUB\_KEY\_TOO\_BIG

**Message ID:** 48032

**Message Description:** LOG\_ID\_WAD\_SSL\_PUB\_KEY\_TOO\_BIG

**Message Meaning:** Certificate's public key too long

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48034 - LOG\_ID\_WAD\_SSL\_SERVER\_KEY\_HASH\_ALGORITHM\_MISMATCH

**Message ID:** 48034

**Message Description:** LOG\_ID\_WAD\_SSL\_SERVER\_KEY\_HASH\_ALGORITHM\_MISMATCH

**Message Meaning:** Server Key Exchange hash algorithm mismatch

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
received		uint8	
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48035 - LOG\_ID\_WAD\_SSL\_SERVER\_KEY\_SIGNATURE\_ALGORITHM\_MISMATCH

**Message ID:** 48035

**Message Description:** LOG\_ID\_WAD\_SSL\_SERVER\_KEY\_SIGNATURE\_ALGORITHM\_MISMATCH

**Message Meaning:** Server Key Exchange signature algorithm mismatch

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
expectedsignature		uint8	

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
receivedsignature		uint8	
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48038 - LOG\_ID\_WAD\_SSL\_RCV\_FATAL\_ALERT

**Message ID:** 48038

**Message Description:** LOG\_ID\_WAD\_SSL\_RCV\_FATAL\_ALERT

**Message Meaning:** SSL Fatal Alert received

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48039 - LOG\_ID\_WAD\_SSL\_SENT\_FATAL\_ALERT

**Message ID:** 48039

**Message Description:** LOG\_ID\_WAD\_SSL\_SENT\_FATAL\_ALERT

**Message Meaning:** SSL fatal alert sent

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11



Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48101 - LOG\_ID\_WAD\_AUTH\_FAIL\_PSK

**Message ID:** 48101

**Message Description:** LOG\_ID\_WAD\_AUTH\_FAIL\_PSK

**Message Meaning:** WAN Optimization peer PSK authentication failed

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
authgrp	Authorization Group	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
host	Host Name	string	256
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48102 - LOG\_ID\_WAD\_AUTH\_FAIL\_OTH

**Message ID:** 48102

**Message Description:** LOG\_ID\_WAD\_AUTH\_FAIL\_OTH

**Message Meaning:** WAN Optimization peer authentication failed

**Type:** Event

**Category:** WAD

**Severity:** Error

Log Field Name	Description	Data Type	Length
authgrp	Authorization Group	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
peer		string	36
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48300 - LOG\_ID\_WRG\_SVR\_FGT\_CONF

**Message ID:** 48300

**Message Description:** LOG\_ID\_WRG\_SVR\_FGT\_CONF

**Message Meaning:** Server side WAN Optimization FortiGate configured incorrectly

**Type:** Event

**Category:** WAD

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 48301 - LOG\_ID\_UNEXP\_APP\_TYPE

**Message ID:** 48301

**Message Description:** LOG\_ID\_UNEXP\_APP\_TYPE

**Message Meaning:** Unexpected application type for WAN Optimization

**Type:** Event

**Category:** WAD

**Severity:** Critical

Log Field Name	Description	Data Type	Length
app-type	Address Type	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 51000 - LOG\_ID\_NB\_TBL\_CHG

**Message ID:** 51000

**Message Description:** LOG\_ID\_NB\_TBL\_CHG

**Message Meaning:** Neighbor table changed

**Type:** Event

**Category:** ROUTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message	string	
service	Name of Service	string	64
srcip		ip	39
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 52000 - LOG\_ID\_EVENT\_SECURITY\_AUDIT\_FABRIC\_SUMMARY

**Message ID:** 52000

**Message Description:** LOG\_ID\_EVENT\_SECURITY\_AUDIT\_FABRIC\_SUMMARY

**Message Meaning:** Security Rating summary

**Type:** Event

**Category:** SECURITY-RATING

**Severity:** Notice

Log Field Name	Description	Data Type	Length
auditid		uint64	
auditscore		string	20
audittime		uint64	
criticalcount		uint32	
date		string	10
devid		string	16
eventtime		uint64	20
highcount		uint32	
level		string	11
logdesc		string	
logid		string	10
lowcount		uint32	
mediumcount		uint32	
passedcount		uint32	
subtype		string	20
time		string	8
type		string	16
vd		string	32

## 53000 - LOG\_ID\_SDNC\_CONNECTED

**Message ID:** 53000

**Message Description:** LOG\_ID\_SDNC\_CONNECTED

**Message Meaning:** Connected to SDN server

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 53001 - LOG\_ID\_SDNC\_DISCONNECTED

**Message ID:** 53001

**Message Description:** LOG\_ID\_SDNC\_DISCONNECTED

**Message Meaning:** Disconnected from SDN server

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 53002 - LOG\_ID\_SDNC\_SUBSCRIBE

**Message ID:** 53002

**Message Description:** LOG\_ID\_SDNC\_SUBSCRIBE

**Message Meaning:** Dynamic SDN address channel opened

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 53003 - LOG\_ID\_SDNC\_UNSUBSCRIBE

**Message ID:** 53003

**Message Description:** LOG\_ID\_SDNC\_UNSUBSCRIBE

**Message Meaning:** Dynamic SDN address channel closed

**Type:** Event

**Category:** SYSTEM

**Severity:** Information



Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 99951 - LOG\_ID\_NP6\_IPSEC\_ENGINE\_BUSY

**Message ID:** 99951

**Message Description:** LOG\_ID\_NP6\_IPSEC\_ENGINE\_BUSY

**Message Meaning:** NP6 IPsec engine is busy

**Type:** Event

**Category:** SYSTEM

**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 99952 - LOG\_ID\_NP6\_IPSEC\_ENGINE\_POSSIBLY\_LOCKUP

**Message ID:** 99952

**Message Description:** LOG\_ID\_NP6\_IPSEC\_ENGINE\_POSSIBLY\_LOCKUP

**Message Meaning:** NP6 IPsec engine is possibly locked up

**Type:** Event

**Category:** SYSTEM

**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

## 99953 - LOG\_ID\_NP6\_IPSEC\_ENGINE\_LOCKUP

**Message ID:** 99953

**Message Description:** LOG\_ID\_NP6\_IPSEC\_ENGINE\_LOCKUP

**Message Meaning:** NP6 IPsec engine is locked up

**Type:** Event

**Category:** SYSTEM

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

---

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

# GTP

## 41216 - LOGID\_GTP\_FORWARD

**Message ID:** 41216

**Message Description:** LOGID\_GTP\_FORWARD

**Message Meaning:** GTP forward

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7

Log Field Name	Description	Data Type	Length
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41217 - LOGID\_GTP\_DENY

**Message ID:** 41217

**Message Description:** LOGID\_GTP\_DENY

**Message Meaning:** GTP deny

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41218 - LOGID\_GTP\_RATE\_LIMIT

**Message ID:** 41218

**Message Description:** LOGID\_GTP\_RATE\_LIMIT

**Message Meaning:** GTP rate limit

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512

Log Field Name	Description	Data Type	Length
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41219 - LOGID\_GTP\_STATE\_INVALID

**Message ID:** 41219

**Message Description:** LOGID\_GTP\_STATE\_INVALID

**Message Meaning:** GTP state invalid

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3



Log Field Name	Description	Data Type	Length
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41220 - LOGID\_GTP\_TUNNEL\_LIMIT

**Message ID:** 41220

**Message Description:** LOGID\_GTP\_TUNNEL\_LIMIT

**Message Meaning:** Tunnel limit GTP message. These messages occur only when the maximum number of GTP tunnels is reached. No new tunnels are created when the maximum number is reached

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41221 - LOGID\_GTP\_TRAFFIC\_COUNT

**Message ID:** 41221

**Message Description:** LOGID\_GTP\_TRAFFIC\_COUNT

**Message Meaning:** Statistic summary information when the GTP tunnel is being torn down

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-bytes	Control Plane Data Bytes	uint64	20
c-ggsn	Control Plane GGSN IP Address	ip	39
c-ggsn-teid	Control Plane GGSN Tunnel Endpoint Identifier	uint32	10
c-pkts	Control Plane Packets	uint64	20
c-sgsn	Control Plane SGSN IP Address	ip	39
c-sgsn-teid	Control Plane SGSN Tunnel Endpoint Identifier	uint32	10
date	Date	string	10
duration	tunnel duration	uint32	10
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-bytes	User Plane Data Bytes	uint64	20
u-ggsn	user plane ggsn IP address	ip	39
u-ggsn-teid	user plane ggsn teid	uint32	10
u-pkts	User Plane Packets	uint64	20
u-sgsn	user plane sgsn IP address	ip	39
u-sgsn-teid	user plane sgsn tunnel endpoint identifier	uint32	10
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41222 - LOGID\_GTP\_USER\_DATA

**Message ID:** 41222

**Message Description:** LOGID\_GTP\_USER\_DATA

**Message Meaning:** GTP user data

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
profile	Profile Name	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
user_data	user traffic content inside gtp-u tunnel	string	256
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41223 - LOGID\_GTPV2\_FORWARD

**Message ID:** 41223

**Message Description:** LOGID\_GTPV2\_FORWARD

**Message Meaning:** GTPv2 forward message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41224 - LOGID\_GTPV2\_DENY

**Message ID:** 41224

**Message Description:** LOGID\_GTPV2\_DENY

**Message Meaning:** GTPv2 deny message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41225 - LOGID\_GTPV2\_RATE\_LIMIT

**Message ID:** 41225

**Message Description:** LOGID\_GTPV2\_RATE\_LIMIT

**Message Meaning:** GTPv2 rate limit message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20



Log Field Name	Description	Data Type	Length
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41226 - LOGID\_GTPV2\_STATE\_INVALID

**Message ID:** 41226

**Message Description:** LOGID\_GTPV2\_STATE\_INVALID

**Message Meaning:** GTPv2 state invalid message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3

Log Field Name	Description	Data Type	Length
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41227 - LOGID\_GTPV2\_TUNNEL\_LIMIT

**Message ID:** 41227

**Message Description:** LOGID\_GTPV2\_TUNNEL\_LIMIT

**Message Meaning:** Tunnel limit GTP (version 2) message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41228 - LOGID\_GTPV2\_TRAFFIC\_COUNT

**Message ID:** 41228

**Message Description:** LOGID\_GTPV2\_TRAFFIC\_COUNT

**Message Meaning:** Statistic summary information when the GTPv2 tunnel is being torn down

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-bytes	Control Plane Data Bytes	uint64	20
c-pkts	Control Plane Packets	uint64	20
cpdladdr	Control Plane Downlink IP Address	ip	39
cpdlisraddr	Control Plane ISR Downlink IP Address	ip	39
cpdlisrteid	control plane ISR downlink tunnel endpoint identifier	uint32	10
cpdlteid	control plane downlink tunnel endpoint identifier	uint32	10
cpuladdr	control plane uplink IP address	ip	39
cpulteid	control plane uplink teid	uint32	10
date	Date	string	10
duration	tunnel duration	uint32	10
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-bytes	User Plane Data Bytes	uint64	20
u-pkts	User Plane Packets	uint64	20
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41229 - LOGID\_GTPU\_FORWARD

**Message ID:** 41229

**Message Description:** LOGID\_GTPU\_FORWARD

**Message Meaning:** GTPU forward message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
dstport	Destination Port	uint16	5
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

## 41230 - LOGID\_GTPU\_DENY

**Message ID:** 41230

**Message Description:** LOGID\_GTPU\_DENY

**Message Meaning:** GTPU deny message

**Type:** GTP

**Category:** GTP-ALL

**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

# IPS

## 16384 - LOGID\_ATTCK\_SIGNATURE\_TCP\_UDP

**Message ID:** 16384

**Message Description:** LOGID\_ATTCK\_SIGNATURE\_TCP\_UDP

**Message Meaning:** Attack detected by UCP/TCP signature

**Type:** IPS

**Category:** SIGNATURE

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction		string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rawdataid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 16385 - LOGID\_ATTCK\_SIGNATURE\_ICMP

**Message ID:** 16385

**Message Description:** LOGID\_ATTCK\_SIGNATURE\_ICMP

**Message Meaning:** Attack detected by ICMP signature

**Type:** IPS

**Category:** SIGNATURE

**Severity:** Alert



Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction		string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
icmpcode	Destination Port of the ICMP message	string	6
icmpid	Source port of the ICMP message	string	8
icmptype	The type of ICMP message	string	6
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rawdataid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 16386 - LOGID\_ATTCK\_SIGNATURE\_OTHERS

**Message ID:** 16386

**Message Description:** LOGID\_ATTCK\_SIGNATURE\_OTHERS

**Message Meaning:** Attack detected by other signature

**Type:** IPS

**Category:** SIGNATURE

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rawdataid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 16399 - LOGID\_ATTACK\_MALICIOUS\_URL

**Message ID:** 16399

**Message Description:** LOGID\_ATTACK\_MALICIOUS\_URL

**Message Meaning:** Attack detected by a malicious URL

**Type:** IPS

**Category:** MALICIOUS-URL

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action		string	16
attack		string	256
attackcontext		string	2040
attackcontextid		string	10
attackid		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
eventtime		uint64	20
eventtype		string	32
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10

Log Field Name	Description	Data Type	Length
level		string	11
logid		string	10
msg		string	518
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
ref		string	
service		string	36
sessionid		uint32	10
severity		string	8
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

# SSH

## 61000 - LOG\_ID\_SSH\_COMMAND\_BLOCK

**Message ID:** 61000

**Message Description:** LOG\_ID\_SSH\_COMMAND\_BLOCK

**Message Meaning:** Depends on info in msg field

**Type:** SSH

**Category:** SSH-COMMAND

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	17
command		string	256
date		string	10
direction		string	
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcintf		string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61001 - LOG\_ID\_SSH\_COMMAND\_BLOCK\_ALERT

**Message ID:** 61001

**Message Description:** LOG\_ID\_SSH\_COMMAND\_BLOCK\_ALERT

**Message Meaning:** Depends on info in msg field

**Type:** SSH

**Category:** SSH-COMMAND

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action		string	17
command		string	256
date		string	10
direction		string	
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtype		string	32
fctuid		string	32
group		string	64

Log Field Name	Description	Data Type	Length
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61002 - LOG\_ID\_SSH\_COMMAND\_PASS

**Message ID:** 61002

**Message Description:** LOG\_ID\_SSH\_COMMAND\_PASS

**Message Meaning:** Depends on info in msg field

**Type:** SSH

**Category:** SSH-COMMAND

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
command		string	256



Log Field Name	Description	Data Type	Length
date		string	10
direction		string	
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61003 - LOG\_ID\_SSH\_COMMAND\_PASS\_ALERT

**Message ID:** 61003

**Message Description:** LOG\_ID\_SSH\_COMMAND\_PASS\_ALERT

**Message Meaning:** Depends on info in msg field

**Type:** SSH

**Category:** SSH-COMMAND

**Severity:** Alert

Log Field Name	Description	Data Type	Length
action		string	17
command		string	256
date		string	10
direction		string	
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61010 - LOG\_ID\_SSH\_CHANNEL\_BLOCK

**Message ID:** 61010

**Message Description:** LOG\_ID\_SSH\_CHANNEL\_BLOCK

**Message Meaning:** Depends on info in msg field

**Type:** SSH

**Category:** SSH-CHANNEL

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
date		string	10
direction		string	
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3

Log Field Name	Description	Data Type	Length
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

## 61011 - LOG\_ID\_SSH\_CHANNEL\_PASS

**Message ID:** 61011

**Message Description:** LOG\_ID\_SSH\_CHANNEL\_PASS

**Message Meaning:** Depends on info in msg field

**Type:** SSH

**Category:** SSH-CHANNEL

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
date		string	10
direction		string	
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtype		string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

# Traffic

## 2 - LOG\_ID\_TRAFFIC\_ALLOW

**Message ID:** 2

**Message Description:** LOG\_ID\_TRAFFIC\_ALLOW

**Message Meaning:** Allowed traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail		string	66
comment		string	1024
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66



Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwpvlanid		uint32	10

### 3 - LOG\_ID\_TRAFFIC\_DENY

**Message ID:** 3

**Message Description:** LOG\_ID\_TRAFFIC\_DENY

**Message Meaning:** Traffic violation

**Type:** Traffic

**Category:** FORWARD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32

Log Field Name	Description	Data Type	Length
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24

Log Field Name	Description	Data Type	Length
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwpvlanid		uint32	10

## 4 - LOG\_ID\_TRAFFIC\_OTHER\_START

**Message ID:** 4

**Message Description:** LOG\_ID\_TRAFFIC\_OTHER\_START

**Message Meaning:** Traffic other session start

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail		string	66
comment		string	1024
date	Date	string	10

Log Field Name	Description	Data Type	Length
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66

Log Field Name	Description	Data Type	Length
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39

Log Field Name	Description	Data Type	Length
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwpvlanid		uint32	10

## 5 - LOG\_ID\_TRAFFIC\_OTHER\_ICMP\_ALLOW

**Message ID:** 5

**Message Description:** LOG\_ID\_TRAFFIC\_OTHER\_ICMP\_ALLOW

**Message Meaning:** Traffic allowed ICMP

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16

Log Field Name	Description	Data Type	Length
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64



Log Field Name	Description	Data Type	Length
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16

Log Field Name	Description	Data Type	Length
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwpvlanid		uint32	10

## 6 - LOG\_ID\_TRAFFIC\_OTHER\_ICMP\_DENY

**Message ID:** 6

**Message Description:** LOG\_ID\_TRAFFIC\_OTHER\_ICMP\_DENY

**Message Meaning:** Traffic denied ICMP

**Type:** Traffic

**Category:** FORWARD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64

Log Field Name	Description	Data Type	Length
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwpvlanid		uint32	10

## 7 - LOG\_ID\_TRAFFIC\_OTHER\_INVALID

**Message ID:** 7

**Message Description:** LOG\_ID\_TRAFFIC\_OTHER\_INVALID

**Message Meaning:** Traffic other invalid

**Type:** Traffic

**Category:** FORWARD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16

Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
centralnatid	Central NAT ID	uint32	10
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrecvname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10

Log Field Name	Description	Data Type	Length
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3

## 8 - LOG\_ID\_TRAFFIC\_WANOPT

**Message ID:** 8

**Message Description:** LOG\_ID\_TRAFFIC\_WANOPT

**Message Meaning:** WAN optimization traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16



Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countssh		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
dstcountry	Country name for the destination IP	string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vrf		uint8	3
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 9 - LOG\_ID\_TRAFFIC\_WEBCACHE

**Message ID:** 9

**Message Description:** LOG\_ID\_TRAFFIC\_WEBCACHE

**Message Meaning:** Web cache traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
comment		string	1024
countwaf		uint32	10
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
dstcountry	Country name for the destination IP	string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcname	Source name	string	66

Log Field Name	Description	Data Type	Length
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vrf		uint8	3
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 10 - LOG\_ID\_TRAFFIC\_EXPLICIT\_PROXY

**Message ID:** 10

**Message Description:** LOG\_ID\_TRAFFIC\_EXPLICIT\_PROXY

**Message Meaning:** Explicit proxy traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16

Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
comment		string	1024
countssh		uint32	10
countwaf		uint32	10
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
dstcountry	Country name for the destination IP	string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66

Log Field Name	Description	Data Type	Length
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vrf		uint8	3
vwpvlanid		uint32	10

Log Field Name	Description	Data Type	Length
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

## 11 - LOG\_ID\_TRAFFIC\_FAIL\_CONN

**Message ID:** 11

**Message Description:** LOG\_ID\_TRAFFIC\_FAIL\_CONN

**Message Meaning:** Failed connection attempts

**Type:** Traffic

**Category:** FORWARD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
centralnatid	Central NAT ID	uint32	10
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24



Log Field Name	Description	Data Type	Length
poluuid	UUID of the Firewall Policy	string	37
sessionid	Session ID	uint32	10
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12 - LOG\_ID\_TRAFFIC\_MULTICAST

**Message ID:** 12

**Message Description:** LOG\_ID\_TRAFFIC\_MULTICAST

**Message Meaning:** Multicast traffic

**Type:** Traffic

**Category:** MULTICAST

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96

Log Field Name	Description	Data Type	Length
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66

Log Field Name	Description	Data Type	Length
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3

## 13 - LOG\_ID\_TRAFFIC\_END\_FORWARD

**Message ID:** 13

**Message Description:** LOG\_ID\_TRAFFIC\_END\_FORWARD

**Message Meaning:** Forward traffic

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
centralnatid	Central NAT ID	uint32	10
collectedemail		string	66
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
polycymode		string	8
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10

## 14 - LOG\_ID\_TRAFFIC\_END\_LOCAL

**Message ID:** 14

**Message Description:** LOG\_ID\_TRAFFIC\_END\_LOCAL

**Message Meaning:** Local traffic

**Type:** Traffic

**Category:** LOCAL

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64



Log Field Name	Description	Data Type	Length
apprisk	Application Risk Level	string	16
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17

Log Field Name	Description	Data Type	Length
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3

## 15 - LOG\_ID\_TRAFFIC\_START\_FORWARD

**Message ID:** 15

**Message Description:** LOG\_ID\_TRAFFIC\_START\_FORWARD

**Message Meaning:** Forward traffic session start

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16

Log Field Name	Description	Data Type	Length
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
centralnatid	Central NAT ID	uint32	10
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66

Log Field Name	Description	Data Type	Length
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwpvlanid		uint32	10

## 16 - LOG\_ID\_TRAFFIC\_START\_LOCAL

**Message ID:** 16

**Message Description:** LOG\_ID\_TRAFFIC\_START\_LOCAL

**Message Meaning:** Local traffic session start

**Type:** Traffic

**Category:** LOCAL

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
centralnatid	Central NAT ID	uint32	10
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66

Log Field Name	Description	Data Type	Length
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10



Log Field Name	Description	Data Type	Length
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3

## 17 - LOG\_ID\_TRAFFIC\_SNIFFER

**Message ID:** 17

**Message Description:** LOG\_ID\_TRAFFIC\_SNIFFER

**Message Meaning:** Sniffer traffic

**Type:** Traffic

**Category:** SNIFFER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appact		string	16
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
collectedemail		string	66
comment		string	1024
countapp		uint32	10
countav		uint32	10
countdlp		uint32	10
countemail		uint32	10
counttips		uint32	10
countweb		uint32	10
date		string	10
devcategory		string	32
devid		string	16
devtype		string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstmac		string	17
dstname		string	66
dstosname		string	66
dstosversion		string	66
dstport		uint16	5

Log Field Name	Description	Data Type	Length
dstserver		uint32	10
dstssid		string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid		string	37
duration		uint32	10
eventtime		uint64	20
fctuid		string	32
group		string	64
level		string	11
logid		string	10
masterdstmac		string	17
mastersrcmac		string	17
msg		string	64
osname		string	66
osversion		string	66
policyid		uint32	10
policyname		string	36
policytype		string	24
poluid		string	37
proto		uint8	3
rcvdbyte		uint64	20
rcvdpkt		uint32	10
sentbyte		uint64	20
sentpkt		uint32	10
service		string	63
sessionid		uint32	10
shaperdroprcvdbyte		uint32	10
shaperdropsentbyte		uint32	10
shaperperipdropbyte		uint32	10

Log Field Name	Description	Data Type	Length
shaperperipname		string	36
shaperrcvdname		string	36
shapersentname		string	36
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcmac		string	17
srcname		string	66
srcport		uint16	5
srcserver		uint32	10
srcssid		string	33
srcuid		string	37
subtype		string	20
time		string	8
trandisp		string	16
tranip		ip	39
tranport		uint16	5
transip		ip	39
transport		uint16	5
type		string	16
unauthuser		string	66
unauthuser		string	66
unauthusersource		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vpn		string	32
vpntype		string	14
vrf		uint8	3

## 19 - LOG\_ID\_TRAFFIC\_BROADCAST

**Message ID:** 19

**Message Description:** LOG\_ID\_TRAFFIC\_BROADCAST

**Message Meaning:** Broadcast traffic

**Type:** Traffic

**Category:** MULTICAST

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66

Log Field Name	Description	Data Type	Length
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32

Log Field Name	Description	Data Type	Length
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3

## 20 - LOG\_ID\_TRAFFIC\_STAT

**Message ID:** 20

**Message Description:** LOG\_ID\_TRAFFIC\_STAT

**Message Meaning:** Forward traffic statistics

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
centralnatid	Central NAT ID	uint32	10
collectedemail		string	66
comment		string	1024
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66



Log Field Name	Description	Data Type	Length
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
polycymode		string	8
policyname		string	36
policytype		string	24

Log Field Name	Description	Data Type	Length
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16

Log Field Name	Description	Data Type	Length
tranip	NAT destination IP	ip	39
transport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10

## 21 - LOG\_ID\_TRAFFIC\_SNIFFER\_STAT

**Message ID:** 21

**Message Description:** LOG\_ID\_TRAFFIC\_SNIFFER\_STAT

**Message Meaning:** Sniffer traffic statistics

**Type:** Traffic

**Category:** SNIFFER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96

Log Field Name	Description	Data Type	Length
appact		string	16
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
collectedemail		string	66
comment		string	1024
date		string	10
devcategory		string	32
devid		string	16
devtype		string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstmac		string	17
dstname		string	66
dstosname		string	66
dstosversion		string	66
dstport		uint16	5
dstserver		uint32	10
dstssid		string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid		string	37
duration		uint32	10
eventtime		uint64	20
fctuid		string	32

Log Field Name	Description	Data Type	Length
group		string	64
level		string	11
logid		string	10
masterdstmac		string	17
mastersrcmac		string	17
msg		string	64
osname		string	66
osversion		string	66
policyid		uint32	10
policyname		string	36
policytype		string	24
poluid		string	37
proto		uint8	3
rcvbyte		uint64	20
rcvdelta		uint64	20
rcvpkt		uint32	10
sentbyte		uint64	20
sentdelta		uint64	20
sentpkt		uint32	10
service		string	63
sessionid		uint32	10
shaperdroprcvbyte		uint32	10
shaperdropsentbyte		uint32	10
shaperperipdropbyte		uint32	10
shaperperipname		string	36
shaperrcvdname		string	36
shapersentname		string	36
srcintf		string	32
srcintfrole		string	10
srcip		ip	39

Log Field Name	Description	Data Type	Length
srcmac		string	17
srcname		string	66
srcport		uint16	5
srcserver		uint32	10
srcssid		string	33
srcuuid		string	37
subtype		string	20
time		string	8
trandisp		string	16
tranip		ip	39
tranport		uint16	5
transip		ip	39
transport		uint16	5
type		string	16
unauthuser		string	66
unauthuser		string	66
unauthusersource		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vpn		string	32
vpntype		string	14
vrf		uint8	3

## 22 - LOG\_ID\_TRAFFIC\_UTM\_CORRELATION

**Message ID:** 22

**Message Description:** LOG\_ID\_TRAFFIC\_UTM\_CORRELATION

**Message Meaning:** Forward traffic for UTM correlation

**Type:** Traffic

**Category:** FORWARD

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
centralnatid	Central NAT ID	uint32	10
collectedemail		string	66
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
date	Date	string	10
devcategory		string	32
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevcategory		string	32
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion		string	66
policyid	Firewall Policy ID	uint32	10
polycymode		string	8
policyname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10



Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlquality		string	320
vwlservice		string	64
vwplanid		uint32	10

# VoIP

## 44032 - LOGID\_EVENT\_VOIP\_SIP

**Message ID:** 44032

**Message Description:** LOGID\_EVENT\_VOIP\_SIP

**Message Meaning:** VoIP SIP

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
from		string	128
kind		string	10
level		string	11
logid		string	10
policy_id		uint32	10
profile		string	64
proto		uint8	3
session_id		uint32	10

Log Field Name	Description	Data Type	Length
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
to		string	512
type		string	16
vd		string	32
voip_proto		string	4

## 44033 - LOGID\_EVENT\_VOIP\_SIP\_BLOCK

**Message ID:** 44033

**Message Description:** LOGID\_EVENT\_VOIP\_SIP\_BLOCK

**Message Meaning:** VoIP SIP blocked

**Type:** VoIP

**Category:** VOIP

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
count		uint32	10
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
event_id		uint32	10
from		string	128
kind		string	10
level		string	11
logid		string	10
message_type		string	16
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
request_name		string	64
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
to		string	512
type		string	16
vd		string	32
voip_proto		string	4

## 44034 - LOGID\_EVENT\_VOIP\_SIP\_FUZZING

**Message ID:** 44034

**Message Description:** LOGID\_EVENT\_VOIP\_SIP\_FUZZING

**Message Meaning:** VoIP SIP fuzzing

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
column		uint32	10
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
line		string	128
logid		string	10
malform_data		uint32	10
malform_desc		string	47
message_type		string	16
policy_id		uint32	10
profile		string	64
proto		uint8	3
request_name		string	64
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
subtype		string	20
time		string	8

Log Field Name	Description	Data Type	Length
type		string	16
vd		string	32
voip_proto		string	4

## 44035 - LOGID\_EVENT\_VOIP\_SCCP\_REGISTER

**Message ID:** 44035

**Message Description:** LOGID\_EVENT\_VOIP\_SCCP\_REGISTER

**Message Meaning:** VoIP SCCP registered

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
session_id		uint32	10
srcip		ip	39

Log Field Name	Description	Data Type	Length
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

## 44036 - LOGID\_EVENT\_VOIP\_SCCP\_UNREGISTER

**Message ID:** 44036

**Message Description:** LOGID\_EVENT\_VOIP\_SCCP\_UNREGISTER

**Message Meaning:** VoIP SCCP unregistered

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64



Log Field Name	Description	Data Type	Length
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

## 44037 - LOGID\_EVENT\_VOIP\_SCCP\_CALL\_BLOCK

**Message ID:** 44037

**Message Description:** LOGID\_EVENT\_VOIP\_SCCP\_CALL\_BLOCK

**Message Meaning:** VoIP SCCP call blocked

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

## 44038 - LOGID\_EVENT\_VOIP\_SCCP\_CALL\_INFO

**Message ID:** 44038

**Message Description:** LOGID\_EVENT\_VOIP\_SCCP\_CALL\_INFO

**Message Meaning:** VoIP SCCP call information

**Type:** VoIP

**Category:** VOIP

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	15

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
locport		uint16	5
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
remip		ip	39
rempport		uint16	5
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

# WAF

## 30248 - LOGID\_WAF\_SIGNATURE\_BLOCK

**Message ID:** 30248

**Message Description:** LOGID\_WAF\_SIGNATURE\_BLOCK

**Message Meaning:** Web application firewall blocked application by signature

**Type:** WAF

**Category:** WAF-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64

Log Field Name	Description	Data Type	Length
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30249 - LOGID\_WAF\_SIGNATURE\_PASS

**Message ID:** 30249

**Message Description:** LOGID\_WAF\_SIGNATURE\_PASS

**Message Meaning:** Web application firewall passed application by signature

**Type:** WAF

**Category:** WAF-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30250 - LOGID\_WAF\_SIGNATURE\_ERASE

**Message ID:** 30250

**Message Description:** LOGID\_WAF\_SIGNATURE\_ERASE

**Message Meaning:** Web application firewall erased application by signature

**Type:** WAF

**Category:** WAF-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30251 - LOGID\_WAF\_CUSTOM\_SIGNATURE\_BLOCK

**Message ID:** 30251

**Message Description:** LOGID\_WAF\_CUSTOM\_SIGNATURE\_BLOCK

**Message Meaning:** Web application firewall blocked application by custom signature

**Type:** WAF

**Category:** WAF-CUSTOM-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10



Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30252 - LOGID\_WAF\_CUSTOM\_SIGNATURE\_PASS

**Message ID:** 30252

**Message Description:** LOGID\_WAF\_CUSTOM\_SIGNATURE\_PASS

**Message Meaning:** Web application firewall allowed application by custom signature

**Type:** WAF

**Category:** WAF-CUSTOM-SIGNATURE

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30253 - LOGID\_WAF\_METHOD\_BLOCK

**Message ID:** 30253

**Message Description:** LOGID\_WAF\_METHOD\_BLOCK

**Message Meaning:** Web application firewall blocked application by HTTP method

**Type:** WAF

**Category:** WAF-HTTP-METHOD

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Http Method	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30255 - LOGID\_WAF\_ADDRESS\_LIST\_BLOCK

**Message ID:** 30255

**Message Description:** LOGID\_WAF\_ADDRESS\_LIST\_BLOCK

**Message Meaning:** Web application firewall blocked application by address list

**Type:** WAF

**Category:** WAF-ADDRESS-LIST

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30257 - LOGID\_WAF\_CONSTRAINTS\_BLOCK

**Message ID:** 30257

**Message Description:** LOGID\_WAF\_CONSTRAINTS\_BLOCK

**Message Meaning:** Web application firewall blocked application by HTTP constraints

**Type:** WAF

**Category:** WAF-HTTP-CONSTRAINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
constraint	WAF http protocol restrictions	string	
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30258 - LOGID\_WAF\_CONSTRAINTS\_PASS

**Message ID:** 30258

**Message Description:** LOGID\_WAF\_CONSTRAINTS\_PASS

**Message Meaning:** Web application firewall allowed application by HTTP constraints

**Type:** WAF

**Category:** WAF-HTTP-CONSTRAINT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17

Log Field Name	Description	Data Type	Length
agent	Agent	string	64
constraint	WAF http protocol restrictions	string	
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32



## 30259 - LOGID\_WAF\_URL\_ACCESS\_PERMIT

**Message ID:** 30259

**Message Description:** LOGID\_WAF\_URL\_ACCESS\_PERMIT

**Message Meaning:** Web application firewall allowed application by URL access permit

**Type:** WAF

**Category:** WAF-URL-ACCESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30260 - LOGID\_WAF\_URL\_ACCESS\_BYPASS

**Message ID:** 30260

**Message Description:** LOGID\_WAF\_URL\_ACCESS\_BYPASS

**Message Meaning:** Web application firewall allowed application by URL access bypass

**Type:** WAF

**Category:** WAF-URL-ACCESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## 30261 - LOGID\_WAF\_URL\_ACCESS\_BLOCK

**Message ID:** 30261

**Message Description:** LOGID\_WAF\_URL\_ACCESS\_BLOCK

**Message Meaning:** Web application firewall blocked application by URL access

**Type:** WAF

**Category:** WAF-URL-ACCESS

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

---

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

## Web

### 12288 - LOG\_ID\_WEB\_CONTENT\_BANWORD

**Message ID:** 12288

**Message Description:** LOG\_ID\_WEB\_CONTENT\_BANWORD

**Message Meaning:** Web content banned word found

**Type:** Web

**Category:** CONTENT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12289 - LOG\_ID\_WEB\_CONTENT\_MMS\_BANWORD

**Message ID:** 12289

**Message Description:** LOG\_ID\_WEB\_CONTENT\_MMS\_BANWORD

**Message Meaning:** Web content MMS banned word found

**Type:** Web

**Category:** CONTENT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512



Log Field Name	Description	Data Type	Length
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12290 - LOG\_ID\_WEB\_CONTENT\_EXEMPTWORD

**Message ID:** 12290

**Message Description:** LOG\_ID\_WEB\_CONTENT\_EXEMPTWORD

**Message Meaning:** Web content exempt word found

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128

Log Field Name	Description	Data Type	Length
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12291 - LOG\_ID\_WEB\_CONTENT\_MMS\_EXEMPTWORD

**Message ID:** 12291

**Message Description:** LOG\_ID\_WEB\_CONTENT\_MMS\_EXEMPTWORD

**Message Meaning:** Web content MMS exempt word found

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12292 - LOG\_ID\_WEB\_CONTENT\_KEYWORD

**Message ID:** 12292

**Message Description:** LOG\_ID\_WEB\_CONTENT\_KEYWORD

**Message Meaning:** Message contained a key word in the profile list

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64

Log Field Name	Description	Data Type	Length
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12293 - LOG\_ID\_WEB\_CONTENT\_SEARCH

**Message ID:** 12293

**Message Description:** LOG\_ID\_WEB\_CONTENT\_SEARCH

**Message Meaning:** Search phrase detected

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512

Log Field Name	Description	Data Type	Length
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12305 - LOG\_ID\_WEB\_CONTENT\_MMS\_BANWORD\_NOTIF

**Message ID:** 12305

**Message Description:** LOG\_ID\_WEB\_CONTENT\_MMS\_BANWORD\_NOTIF

**Message Meaning:** Web content MMS banned word

**Type:** Web

**Category:** CONTENT

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128



Log Field Name	Description	Data Type	Length
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12544 - LOG\_ID\_URL\_FILTER\_BLOCK

**Message ID:** 12544

**Message Description:** LOG\_ID\_URL\_FILTER\_BLOCK

**Message Meaning:** URL address was blocked because it was found in the URL filter list

**Type:** Web

**Category:** URLFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12545 - LOG\_ID\_URL\_FILTER\_EXEMPT

**Message ID:** 12545

**Message Description:** LOG\_ID\_URL\_FILTER\_EXEMPT

**Message Meaning:** URL address was exempted because it was found in the URL filter list

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12546 - LOG\_ID\_URL\_FILTER\_ALLOW

**Message ID:** 12546

**Message Description:** LOG\_ID\_URL\_FILTER\_ALLOW

**Message Meaning:** URL address was allowed because it was found in the URL filter list

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12547 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTP\_BLK

**Message ID:** 12547

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTP\_BLK

**Message Meaning:** The request contained an invalid domain name

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3



## 12548 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTPS\_BLK

**Message ID:** 12548

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTPS\_BLK

**Message Meaning:** HTTP certificate request contained an invalid domain name

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12549 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTP\_PASS

**Message ID:** 12549

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTP\_PASS

**Message Meaning:** HTTP request contained an invalid name so the session has been filtered by IP only

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12550 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTPS\_PASS

**Message ID:** 12550

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_HTTPS\_PASS

**Message Meaning:** HTTPS request contained an invalid name so the session has been filtered by IP only

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12551 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_SNI\_BLK

**Message ID:** 12551

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_SNI\_BLK

**Message Meaning:** Insufficient resources

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64

Log Field Name	Description	Data Type	Length
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12552 - LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_SNI\_PASS

**Message ID:** 12552

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_HOSTNAME\_SNI\_PASS

**Message Meaning:** Getting the host name failed

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12553 - LOG\_ID\_URL\_FILTER\_INVALID\_CERT

**Message ID:** 12553

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_CERT

**Message Meaning:** Server certificate validation failed

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10



Log Field Name	Description	Data Type	Length
profile	Web Filter profile name	string	64
rcvbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12554 - LOG\_ID\_URL\_FILTER\_INVALID\_SESSION

**Message ID:** 12554

**Message Description:** LOG\_ID\_URL\_FILTER\_INVALID\_SESSION

**Message Meaning:** SSL session blocked because its identification number was unknown

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32
vrf		uint8	3

## 12555 - LOG\_ID\_URL\_FILTER\_SRV\_CERT\_ERR\_BLK

**Message ID:** 12555

**Message Description:** LOG\_ID\_URL\_FILTER\_SRV\_CERT\_ERR\_BLK

**Message Meaning:** SSL session blocked

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12556 - LOG\_ID\_URL\_FILTER\_SRV\_CERT\_ERR\_PASS

**Message ID:** 12556

**Message Description:** LOG\_ID\_URL\_FILTER\_SRV\_CERT\_ERR\_PASS

**Message Meaning:** SSL session ignored

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12557 - LOG\_ID\_URL\_FILTER\_FAMS\_NOT\_ACTIVE

**Message ID:** 12557

**Message Description:** LOG\_ID\_URL\_FILTER\_FAMS\_NOT\_ACTIVE

**Message Meaning:** The FortiGuard Analysis and Management Service is not active. You must enable this service

**Type:** Web

**Category:** URLFILTER

**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
vd	Virtual domain name	string	32

## 12558 - LOG\_ID\_URL\_FILTER\_RATING\_ERR

**Message ID:** 12558

**Message Description:** LOG\_ID\_URL\_FILTER\_RATING\_ERR

**Message Meaning:** Rating error occurred

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11

Log Field Name	Description	Data Type	Length
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
referralurl		string	512
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urltype	URL filter type	string	8
user	User name	string	256
vd	Virtual domain name	string	32

## 12559 - LOG\_ID\_URL\_FILTER\_PASS

**Message ID:** 12559

**Message Description:** LOG\_ID\_URL\_FILTER\_PASS

**Message Meaning:** URL passed because it was in the URL filter list

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5



Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urfilteridx	URL filter ID	uint32	10
urfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12560 - LOG\_ID\_URL\_WISP\_BLOCK

**Message ID:** 12560

**Message Description:** LOG\_ID\_URL\_WISP\_BLOCK

**Message Meaning:** URL blocked by Websense service

**Type:** Web

**Category:** URLFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12561 - LOG\_ID\_URL\_WISP\_REDIR

**Message ID:** 12561

**Message Description:** LOG\_ID\_URL\_WISP\_REDIR

**Message Meaning:** URL blocked with redirect message by Websense service

**Type:** Web

**Category:** URLFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12562 - LOG\_ID\_URL\_WISP\_ALLOW

**Message ID:** 12562

**Message Description:** LOG\_ID\_URL\_WISP\_ALLOW

**Message Meaning:** URL allowed by Websense service

**Type:** Web

**Category:** URLFILTER

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12688 - LOG\_ID\_WEB\_SSL\_EXEMPT

**Message ID:** 12688

**Message Description:** LOG\_ID\_WEB\_SSL\_EXEMPT

**Message Meaning:** URL address was exempted because it was found in the ssl-exempt

**Type:** Web

**Category:** SSL-EXEMPT

**Severity:** Information

Log Field Name	Description	Data Type	Length
action		string	11
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
forwardedfor		string	128
group		string	64
hostname		string	256
initiator		string	64
level		string	11

Log Field Name	Description	Data Type	Length
logid		string	10
msg		string	512
profile		string	64
proto		uint8	3
rcvdbyte		uint64	20
referralurl		string	512
reqtype		string	8
sentbyte		uint64	20
service		string	36
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
urlfilteridx		uint32	10
urlfilterlist		string	64
user		string	256
vd		string	32
vrf		uint8	3

## 12800 - LOG\_ID\_WEB\_FTGD\_ERR

**Message ID:** 12800

**Message Description:** LOG\_ID\_WEB\_FTGD\_ERR

**Message Meaning:** Rating error occurred (error)

**Type:** Web

**Category:** FTGD\_ERR

**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36



Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12801 - LOG\_ID\_WEB\_FTGD\_WARNING

**Message ID:** 12801

**Message Description:** LOG\_ID\_WEB\_FTGD\_WARNING

**Message Meaning:** Rating error occurred (warning)

**Type:** Web

**Category:** FTGD\_ERR

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39

Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 12802 - LOG\_ID\_WEB\_FTGD\_QUOTA

**Message ID:** 12802

**Message Description:** LOG\_ID\_WEB\_FTGD\_QUOTA

**Message Meaning:** Daily FortiGuard quota status

**Type:** Web

**Category:** FTGD\_QUOTA

**Severity:** Information

Log Field Name	Description	Data Type	Length
catdesc	Web category description	string	64
date	Date	string	10
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
level	Log Level	string	11
logid	Log ID	string	10
profile	Web Filter profile name	string	64
quotaexceeded	Quota has been exceeded	string	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

## 13056 - LOG\_ID\_WEB\_FTGD\_CAT\_BLK

**Message ID:** 13056

**Message Description:** LOG\_ID\_WEB\_FTGD\_CAT\_BLK

**Message Meaning:** URL belongs to an blocked category within the firewall policy

**Type:** Web

**Category:** FTGD\_BLK

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13057 - LOG\_ID\_WEB\_FTGD\_CAT\_WARN

**Message ID:** 13057

**Message Description:** LOG\_ID\_WEB\_FTGD\_CAT\_WARN

**Message Meaning:** URL belongs to a category with warnings enabled

**Type:** Web

**Category:** FTGD\_BLK

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64

Log Field Name	Description	Data Type	Length
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13312 - LOG\_ID\_WEB\_FTGD\_CAT\_ALLOW

**Message ID:** 13312

**Message Description:** LOG\_ID\_WEB\_FTGD\_CAT\_ALLOW

**Message Meaning:** URL belongs to an allowed category within the firewall policy

**Type:** Web

**Category:** FTGD\_ALLOW

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11

Log Field Name	Description	Data Type	Length
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10



Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13313 - LOG\_ID\_WEB\_FTGD\_RULE\_ALLOW

**Message ID:** 13313

**Message Description:** LOG\_ID\_WEB\_FTGD\_RULE\_ALLOW

**Message Meaning:** URL belongs to an override rule

**Type:** Web

**Category:** FTGD\_ALLOW

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
mode		string	32
msg	Log message	string	512
ovrdid		uint32	10
ovrdtbl		string	128
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
ruledata		string	512
ruletype		string	9
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13314 - LOG\_ID\_WEB\_FTGD\_OFF\_SITE\_ALLOW

**Message ID:** 13314

**Message Description:** LOG\_ID\_WEB\_FTGD\_OFF\_SITE\_ALLOW

**Message Meaning:** URL belongs to an override rule

**Type:** Web

**Category:** FTGD\_ALLOW

**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
mode		string	32
msg	Log message	string	512
ovrdid		uint32	10
ovrdtbl		string	128
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
ruledata		string	512
ruletype		string	9
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13315 - LOG\_ID\_WEB\_FTGD\_QUOTA\_COUNTING

**Message ID:** 13315

**Message Description:** LOG\_ID\_WEB\_FTGD\_QUOTA\_COUNTING

**Message Meaning:** FortiGuard web filter category quota counting log message

**Type:** Web

**Category:** FTGD\_QUOTA\_COUNTING

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13316 - LOG\_ID\_WEB\_FTGD\_QUOTA\_EXPIRED

**Message ID:** 13316

**Message Description:** LOG\_ID\_WEB\_FTGD\_QUOTA\_EXPIRED

**Message Meaning:** FortiGuard web filter category quota expired log message

**Type:** Web

**Category:** URLFILTER

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3



## 13317 - LOG\_ID\_WEB\_URL

**Message ID:** 13317

**Message Description:** LOG\_ID\_WEB\_URL

**Message Meaning:** URL has been visited

**Type:** Web

**Category:** URLFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13568 - LOG\_ID\_WEB\_SCRIPTFILTER\_ACTIVEX

**Message ID:** 13568

**Message Description:** LOG\_ID\_WEB\_SCRIPTFILTER\_ACTIVEX

**Message Meaning:** ActiveX script removed

**Type:** Web

**Category:** ACTIVEXFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13573 - LOG\_ID\_WEB\_SCRIPTFILTER\_COOKIE

**Message ID:** 13573

**Message Description:** LOG\_ID\_WEB\_SCRIPTFILTER\_COOKIE

**Message Meaning:** Cookie removed

**Type:** Web

**Category:** COOKIEFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13584 - LOG\_ID\_WEB\_SCRIPTFILTER\_APPLET

**Message ID:** 13584

**Message Description:** LOG\_ID\_WEB\_SCRIPTFILTER\_APPLET

**Message Meaning:** Java applet removed

**Type:** Web

**Category:** APPLETFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13600 - LOG\_ID\_WEB\_SCRIPTFILTER\_OTHER

**Message ID:** 13600

**Message Description:** LOG\_ID\_WEB\_SCRIPTFILTER\_OTHER

**Message Meaning:** Script entity removed

**Type:** Web

**Category:** SCRIPTFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10



Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13601 - LOG\_ID\_WEB\_WF\_COOKIE

**Message ID:** 13601

**Message Description:** LOG\_ID\_WEB\_WF\_COOKIE

**Message Meaning:** Cookie removed entirely

**Type:** Web

**Category:** COOKIEFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13602 - LOG\_ID\_WEB\_WF\_REFERER

**Message ID:** 13602

**Message Description:** LOG\_ID\_WEB\_WF\_REFERER

**Message Meaning:** Referrer removed from request

**Type:** Web

**Category:** COOKIEFILTER

**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

## 13603 - LOG\_ID\_WEB\_WF\_COMMAND\_BLOCK

**Message ID:** 13603

**Message Description:** LOG\_ID\_WEB\_WF\_COMMAND\_BLOCK

**Message Meaning:** Command blocked

**Type:** Web

**Category:** WEBFILTER\_COMMAND\_BLOCK

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
reqtype	Request type	string	8
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32
vrf		uint8	3

## 13616 - LOG\_ID\_CONTENT\_TYPE\_BLOCK

**Message ID:** 13616

**Message Description:** LOG\_ID\_CONTENT\_TYPE\_BLOCK

**Message Meaning:** Blocked by HTTP header content type

**Type:** Web

**Category:** CONTENT

**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
contenttype	Content Type from HTTP header	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

## 13632 - LOGID\_HTTP\_HDR\_CHG\_REQ

**Message ID:** 13632

**Message Description:** LOGID\_HTTP\_HDR\_CHG\_REQ

**Message Meaning:** Depends on info in msg field

**Type:** Web

**Category:** HTTP\_HEADER\_CHANGE

**Severity:** Information

Log Field Name	Description	Data Type	Length
agent		string	64
chgheaders		string	20480
date		string	10
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
transid		uint32	10
type		string	16
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

## 13633 - LOGID\_HTTP\_HDR\_CHG\_RESP

**Message ID:** 13633

**Message Description:** LOGID\_HTTP\_HDR\_CHG\_RESP



**Message Meaning:** Depends on info in msg field

**Type:** Web


**Category:** HTTP\_HEADER\_CHANGE

**Severity:** Information

Log Field Name	Description	Data Type	Length
agent		string	64
chgheaders		string	20480
date		string	10
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
transid		uint32	10
type		string	16
url		string	512
user		string	256
vd		string	32
vrf		uint8	3



**FORTINET®**



Copyright© 2023 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. In no event does Fortinet make any commitment related to future deliverables, features or development, and circumstances may change such that any forward-looking statements herein are not accurate. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.